



SIEMENS

www.siemens.com/polymobil

POLYMOBIL Plus

Simplicity and reliability in mobile X-ray imaging

Answers for life.

Technical data

POLYMOBIL Plus

X-ray generator and controls		
Mains voltage	110 V ± 10% 50/60 Hz 230 V ± 10% 50/60 Hz	
Power output	Standard: max. 125 kV 128 mA max. 250 mA 63 kV max. 16 kW – 99 kV – 161 mA – 100 ms (IEC 60601-2-7) min. 0.32 mAs	20 kW option: max. 125 kV 130 mA max. 300 mA 50 kV (to mAs < 10 mAs) max. 20 kW – 99 kV – 202 mA – 100 ms (IEC 60601-2-7) min. 0.32 mAs
Overcurrent release	An on-site 15 A/characteristic C overcurrent release (trip breaker) is recommended by DIN VDE 0100-710 for supply network voltages of 230 V/240 V. Country-specific requirements apply for the fuse values to be used for other supply network voltages.	
Impedance of the power supply	Max. 1 Ω at 110 V Max. 1 Ω at 230 V	
kVp range	40–125 kV in 23 or 45 steps	
mAs range (Tube current time product)	Line Voltage: 230 V 0.32–250 mAs in 30 or 59 steps: 0.50–200 mAs at 40–48 kV 0.40–250 mAs at 50 kV 0.40–200 mAs at 52–57 kV 0.32–200 mAs at 60–63 kV 0.32–160 mAs at 66–81 kV 0.32–125 mAs at 85–102 kV 0.32–100 mAs at 109–125 kV	Line Voltage: 110 V 0.32–160 mAs in 28 or 55 steps: 0.50–125 mAs at 40–48 kV 0.40–160 mAs at 50 kV 0.40–125 mAs at 52–57 kV 0.32–125 mAs at 60–63 kV 0.32–100 mAs at 66–81 kV 0.32–80 mAs at 85–102 kV 0.32–64 mAs at 109–125 kV
Shortest exposure time	≤ 4 ms (40–125 kV)	
Max. exposure time	6 s	
Exposure release	Exposure release button with 5 m (16.4 feet) of spiral cable	
Length of power cord	5.5 m	
Power line connection	Grounded safety power socket (L/N/Gnd)	
Tube housing		
X-ray tube	IAE X22 with a nominal focal spot value 0.8 (acc. to IEC 60336)	
Anode rotation	2,800 r.p.m., 50 Hz (anode angle 15°)	
Tube housing heat storage capacity	800,000 J = 1,100,000 HU	
Anode heat storage capacity	80,000 J = 107,000 HU	
Total inherent filtration	Min. 3.0 mm according to IEC 60522	
Collimator	Manually-adjustable multi-leaf collimator, rotatable ± 45°	
Tube housing assembly	Max. temperature 60°C, max. 2,800 mAs/h, nominal continuous rating 100 W until the covers reach 60°C	
Collimator light and light field intensity	Halogen lamp min. 180 lux at 1 m SID (without DAP equipment)	
Weight	Approx. 171 kg	
Dimensions		
footprint (l x w x h) (Tube in park position)	1,305 x 631 x 1,325 mm	
Tube positioning	Max. focal spot height 1,895 mm Min. focal spot height 420 mm Max. horizontal extension 1,100 mm	

POLYMOBIL Plus –
the versatile
allrounder

