



SHOWER

Model: CC1251

- ABS Plastic Bowl
- ABS Plastic Shower Head



The Cascaide™ Shower/Eyewash Unit

is exactly what is required to meet the need for quality manufacturing at a competitive price. This economical unit meets ANSI standards compliance, is packaged for quick and easy assembly and comes with the flanged floor mounting plate for freestanding installation. The highly visible UV resistant ABS plastic yellow showerhead along with the ABS Yello-Bowl® give it the necessary markings to be easily seen by a person in need. The eyewash heads are manufactured of solvent resistant yellow acetal and have integral hinged covers to shield them from dust and dirt when not in use, and to enable them to open automatically when water is flowing. The showerhead delivers a minimum of 20" (50.8cm) diameter pattern to the target area 60" (152.4cm) above standing level. The water flow, when properly installed, will provide a non-injurious stream of water for 15 minutes.

MODEL DESCRIPTION

MODEL	DESCRIPTION
CC1251	20 gpm Shr./EW
CC2251	30 gpm Shr./EW



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)



Encon Safety Products
Sam Houston Pkwy. N.
Houston, Texas 77041

PRODUCT FEATURES

- ANSI Z358.1 Certified
- Sch. 40 hot dipped galvanized steel pipe
- 20 gpm or 30 gpm @ 30/70 PSI shower head
- 2.4 gpm total at 30/70 PSI eyewash
- 1-1/4" NPT Supply
- 1-1/4" NPT Waste

CASCAIDE™ SHOWER/EYEWASH WITH STAINLESS STEEL COVERS



CASCAIDE™

The Cascaide™ Shower/Eyewash Unit introduces a quality product at a competitive price. This economical unit complies to the ANSI Z358.1 performance standard, is packaged for quick and easy assembly and comes with the floor flange mounting plate for freestanding installation. It is available with a Stainless Steel bowl and shower head, constructed of 304 stainless steel, to promote the safe, long life of your station and to provide you with more choices in safety equipment for your facility. The eyewash heads have integral hinged covers to shield them from dust and dirt when not in use, and to enable them to open automatically when water is flowing. The showerhead delivers a minimum of a 20" (50.8cm) diameter pattern to the target area 60" (152.4cm) above standing level. When properly installed, the shower will provide a non-injurious stream of water for 15 minutes.

SHOWER

Model: CC3261

- Stainless Steel Bowl
- Stainless Steel Shower Head



MODEL DESCRIPTION

CC1261	20 gpm Shr./EW with SS bowl
CC2261	30 gpm Shr./EW with SS bowl
CC3261	20 gpm Shr./EW with SS shower head & SS bowl
CC4261	30 gpm Shr./EW with SS shower head & SS bowl

PRODUCT FEATURES

- ANSI Z358.1 Certified
- Sch. 40 hot dipped galvanized steel pipe
- 20 gpm or 30 gpm @ 30/70 PSI shower head
- 2.4 gpm total at 30/70 PSI eyewash
- 1-1/4" NPT Supply
- 1-1/4" NPT Waste



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)



CASCAIDE™

Encon Safety Products
Sam Houston Pkwy. N.
Houston, Texas 77041