



Honeywell

Varies based on each installation due to environmental conditions.

Latin America
US/Canada

Authorized Countries:
UL/ORD-C634
ETL Listed to UL 634
FCC/IC

Approval Listings:
1.25" (32mm) L
0.45" (11.5mm) W x
2.44" (62mm) H x

Dimensions:
Tamper Protected: Yes
(Qty 1)

Power Requirements:
3V Lithium
Honeywell BL3-0004
(CR2450)
Duracell DL2450
Panasonic CR2450

Battery Life: Three years
(typical use)

Frequency: 2.4 GHz
Capable: Yes
Temperature Sensing

Magnetic Breaking Gap:
20ft (6 meters) plus*

Transmission Range:

Specifications
DOOR/WINDOW SENSOR

© 2016 Honeywell International Inc. All Rights Reserved. Country of Origin: Mexico.
www.honeywellsecurity.com | 1-800-323-4576
P.O. Box 9040
Melville, NY 11747

Designed in the USA

Simple Installation
Sends programming data right to the control panel when the battery tab is pulled.

No Touch Adjust
Devices can be adjusted remotely via AlarmNet 360™.

Simple Maintenance
User-replaceable batteries and system polling for device information saves time and maximizes efficiency.

CP-01 Approved

8 666 181 247 64 4

SIXMINICT

Part of a series of next-generation sensors featuring SiX™ Two-Way Wireless Technology, the Honeywell Sensor provides superior protection for doors and windows. The sleek, unassuming device blends with any décor and is an ideal choice when aesthetics are critical.

Includes
Sensor, Magnet, CR2450 Battery (1).

Mounting Hardware and Double-sided Tape.
For indoor use only.



Honeywell | SiX™ Two-Way Wireless Technology

DOOR/WINDOW SENSOR
Superior Perimeter Protection

Honeywell | SiX™ Two-Way Wireless Technology

DOOR/WINDOW SENSOR
Superior Perimeter Protection

Works with Lyric™

Dimensions: 2.44" (62mm) H x 0.45" (11.5mm) W x 1.25" (32mm) L

900-02769 11/16 Rev A

Honeywell | SiX™ Two-Way Wireless Technology

DOOR/WINDOW SENSOR
Superior Perimeter Protection

Extended Range

128-bit AES Encryption

4 -11/16" x 1-5/16" x 4-1/4" 900-02769 11/16 Rev.A Exterior
(4.687" x 1.313" x 4.250")