

ELATION® ACL 360i™			
DMX Channel Values / Functions Version 1 (20 DMX Channels)			
Specifications are subject to change without any prior written notice.			
MODE / CHANNEL			FUNCTION
BASIC	STAND	EXTEND	
1	1	1	PAN MOVEMENT [8 BIT]
			0-255 PAN Movement 630/540
		2	PAN FINE MOVEMENT [16 BIT]
			0-255 Fine Control of PAN Movement
2	2	3	TILT MOVEMENT [8 BIT]
			0-255 TILT Movement
		4	TILT MOVEMENT [16 BIT]
			0-255 Fine Control of TILT Movement
3	3	5	PAN CONTINUOUS MOVEMENT
			0-127 NO FUNCTION
			128-189 PAN Clockwise from FAST to SLOW
			190-193 NO Rotation
			194-255 PAN Counter-Clockwise from SLOW to FAST
4	4	6	TILT CONTINUOUS MOVEMENT
			0-127 NO FUNCTION
			128-189 TILT Clockwise from FAST to SLOW
			190-193 NO Rotation
			194-255 TILT Counter-Clockwise from SLOW to FAST
5	5	7	RED
			0-255 0 to 100%
6	6	8	GREEN
			0-255 0 to 100%
7	7	9	BLUE
			0-255 0 to 100%
8	8	10	WHITE
			0-255 0 to 100%

ELATION | **ACL 360i™** | dmx traits

ELATION© ACL 360i™			
DMX Channel Values / Functions Version 1 (20 DMX Channels)			
Specifications are subject to change without any prior written notice.			
MODE / CHANNEL			FUNCTION
BASIC	STAND	EXTEND	
9	9	11	COLOR PRESETS
			0 OFF
			1-4 COLOR PRESET 01
			5-8 COLOR PRESET 02
			9-12 COLOR PRESET 03
			13-16 COLOR PRESET 04
			17-20 COLOR PRESET 05
			21-24 COLOR PRESET 06
			25-28 COLOR PRESET 07
			29-32 COLOR PRESET 08
			33-36 COLOR PRESET 09
			37-40 COLOR PRESET 10
			41-44 COLOR PRESET 11
			45-48 COLOR PRESET 12
			49-52 COLOR PRESET 13
			53-56 COLOR PRESET 14
			57-60 COLOR PRESET 15
			61-64 COLOR PRESET 16
			65-68 COLOR PRESET 17
			69-72 COLOR PRESET 18
			73-76 COLOR PRESET 19
			77-80 COLOR PRESET 20
			81-84 COLOR PRESET 21
			85-88 COLOR PRESET 22
			89-92 COLOR PRESET 23
			93-96 COLOR PRESET 24
			97-100 COLOR PRESET 25
			101-104 COLOR PRESET 26
			105-108 COLOR PRESET 27
			109-112 COLOR PRESET 28
			113-116 COLOR PRESET 29
			117-120 COLOR PRESET 30
			121-124 COLOR PRESET 31
			125-128 COLOR PRESET 32

ELATION® ACL 360i™			
DMX Channel Values / Functions Version 1 (20 DMX Channels)			
Specifications are subject to change without any prior written notice.			
MODE / CHANNEL			FUNCTION
BASIC	STAND	EXTEND	
9	9	11	COLOR PRESETS [continued]
			129-132 COLOR PRESET 33
			133-136 COLOR PRESET 34
			137-140 COLOR PRESET 35
			141-144 COLOR PRESET 36
			145-148 COLOR PRESET 37
			149-152 COLOR PRESET 38
			153-156 COLOR PRESET 39
			157-160 COLOR PRESET 40
			161-164 COLOR PRESET 41
			165-168 COLOR PRESET 42
			169-172 COLOR PRESET 43
			173-176 COLOR PRESET 44
			177-180 COLOR PRESET 45
			181-184 COLOR PRESET 46
			185-188 COLOR PRESET 47
			189-192 COLOR PRESET 48
			193-196 COLOR PRESET 49
			197-200 COLOR PRESET 50
			201-204 COLOR PRESET 51
			205-208 COLOR PRESET 52
			209-212 COLOR PRESET 53
			213-216 COLOR PRESET 54
			217-220 COLOR PRESET 55
			221-224 COLOR PRESET 56
			225-228 COLOR PRESET 57
			229-232 COLOR PRESET 58
			233-236 COLOR PRESET 59
			237-240 COLOR PRESET 60
			241-244 COLOR PRESET 61
			245-248 COLOR PRESET 62
			249-252 COLOR PRESET 63
			253-255 COLOR PRESET 64
10	10	12	FLASH / STROBE
			0-31 LED OFF
			32-63 LED ON
			64-95 Strobe Effect SLOW to FAST
			96-127 LED ON
			128-159 Pulse Effect in Sequences
			160-191 Random Strobe Effect SLOW to FAST (Each Side x4)
			192-223 Random Strobe Effect SLOW to FAST (Individual LEDs)
			224-255 LED ON
11	11	13	DIMMER INTENSITY
			0-255 Intensity 0 to 100%
	12	14	DIMMER INTENSITY FINE
			0-255 Dimmer Intensity FINE Adjustment

ELATION® ACL 360i™			
DMX Channel Values / Functions Version 1 (20 DMX Channels)			
Specifications are subject to change without any prior written notice.			
MODE / CHANNEL			FUNCTION
BASIC	STAND	EXTEND	
12	13	15	COLOR MACROS
			0 NO FUNCTION
			1-14 LED OFF
			15-30 COLOR MACRO 01
			31-46 COLOR MACRO 02
			47-62 COLOR MACRO 03
			63-78 COLOR MACRO 04
			79-94 COLOR MACRO 05
			95-110 COLOR MACRO 06
			111-126 COLOR MACRO 07
			127-142 COLOR MACRO 08
			143-158 COLOR MACRO 09
			159-174 COLOR MACRO 10
			175-190 COLOR MACRO 11
			191-206 COLOR MACRO 12
			207-222 COLOR MACRO 13
			223-238 COLOR MACRO 14
			239-255 COLOR MACRO CROSSFADE
13	14	16	COLOR MACRO SPEED
			0-255 Auto Program Macro Speed SLOW to FAST
14	15	17	COLOR MACRO FADE
			0-100%
	16	18	DIMMING CURVE MODES
			0-20 STANDARD
			21-40 STAGE
			41-60 TV
			61-80 ARCHITECTURAL
			81-100 THEATRE
			101-255 Default to Unit Setting
15	17	19	PAN / TILT MOVEMENT SPEED
			0-225 MAX to MIN SPEED
			226-235 Blackout By Movement
			236-255 NO FUNCTION
16	18	20	LAMP ON/OFF, RESET, INTERNAL PROGRAMS
			0-79 Normal
			80-84 ALL Motor Reset
			85-99 NO FUNCTION
			100-119 Internal Program 1 (scene1~8)
			120-139 Internal Program 2 (scene9~16)
			140-159 Internal Program 3 (scene17~24)
			160-179 Internal Program 4 (scene25~32)
			180-199 Internal Program 5 (scene33~40)
			200-219 Internal Program 6 (scene41~48)
			220-239 Internal Program 7 (scene49~56)
			240-255 NO FUNCTION

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu