

**Model: WISE-3200**

**WIFI module**

**USER manual**

*Trusted ePlatform Services*

**ADVANTECH**

## **Federal Communication Commission Interference Statement**

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

#### Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

**This module is intended for OEM integrators only. Per FCC KDB 996369 D03 OEM Manual v01 guidance, the following conditions must be strictly followed when using this certified module:**

#### **KDB 996369 D03 OEM Manual v01 rule sections:**

##### 2.2 List of applicable FCC rules

This module has been tested for compliance to FCC Part 15C

##### 2.3 Summarize the specific operational use conditions

The module is tested for standalone mobile RF exposure use condition. Any other usage conditions such as co-location with other transmitter(s) or being used in a portable condition will need a separate reassessment through a class II permissive change application or new certification.

##### 2.4 Limited module procedures

Not applicable.

##### 2.5 Trace antenna designs

Not applicable.

##### 2.6 RF exposure considerations

This equipment complies with FCC mobile radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator & your body. If the module is installed in a portable host, a separate SAR evaluation is required to confirm compliance with relevant FCC portable RF exposure rules.

##### 2.7 Antennas

The following antennas have been certified for use with this module; antennas of the same type with equal or lower gain may also be used with this module. The antenna must be installed such that 20 cm can be maintained between the antenna and users.

The antenna information is listed as below.

Mode	Ant. Configure Mode	Ant.	Type	Manufacturer	P/N	Connector	Gain (dBi)
A	#1	1	Dipole	Gortec	AN2450-5010BRS	SMA Male Reverse	5.03
		2	PCB	Gortec	NB1377-A100BF	Mini Conntector	4.31
B	#2	1	PCB	Gortec	NB1377B130GX	Mini Conntector	4.79
		2			NB1377B130GX	Mini Conntector	5.04
*Only the antenna which has the maximum gain was chosen as a representative for the final test.							

## 2.8 Label and compliance information

The final end product must be labeled in a visible area with the following:  
 “Contains FCC ID: M82-WISE-3200”. The grantee's FCC ID can be used only when all FCC compliance requirements are met.

## 2.9 Information on test modes and additional testing requirements

This transmitter is tested in a standalone mobile RF exposure condition and any co-located or simultaneous transmission with other transmitter(s) or portable use will require a separate class II permissive change re-evaluation or new certification.

## 2.10 Additional testing, Part 15 Subpart B disclaimer

This transmitter module is tested as a subsystem and its certification does not cover the FCC Part 15 Subpart B (unintentional radiator) rule requirement applicable to the final host. The final host will still need to be reassessed for compliance to this portion of rule requirements if applicable.

As long as all conditions above are met, further transmitter test will not be required.

However, the OEM integrator is still responsible for testing their end- product for any additional compliance requirements required with this module installed.

**IMPORTANT NOTE:** In the event that these conditions can not be met (for example certain laptop configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID can not be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC authorization.

## **Manual Information To the End User**

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user’s manual of the end product which integrates this module.

The end user manual shall include all required regulatory information/warning as show in this manual.

**OEM/Host manufacturer responsibilities**

OEM/Host manufacturers are ultimately responsible for the compliance of the Host and Module. The final product must be reassessed against all the essential requirements of the FCC rule such as FCC Part 15 Subpart B before it can be placed on the US market. This includes reassessing the transmitter

module for compliance with the Radio and EMF essential requirements of the FCC rules. This module must not be incorporated into any other device or system without retesting for compliance as multi-radio and combined equipment.

Spec		
System	CPU	MIPS QCA 4531 650 MHz Processor
	RAM	DDR2 128MB
	SP I Flash	16MB Boot code & 128MB OpenWRT
Network	WAN	1 x 10/100Mbps for WAN
	LAN	1 x 10/100Mbps for LAN
Security		WEP 64 bit, WEP 128bit, WPA, WPA2, WPA+WPA2 (Mixed Mode) Password protected access
Communication	Wifi	IEEE 802.11b/g/n 2T2R
Expansion	Mini PCIe	1 x full size mini PCIe module
I/O	Antenna x1	WiFi
	LED x2	module Power on.
	Button x1	Reset button
	Serial port x1	RS232/422/485
	USB x1	USB 2.0
	RJ45 x2	WAN/LAN
Power	Power Supply Voltage	12V
	Power Type	DC-in
	Power Consumption	3 Watt
Environmental specifications	Operational Temperature	-20 ~ 70 °C
	Non-Operational Temp.	-40~ 85 °C
	Operating Humidity	5% ~ 95% Relative Humidity, non-condensing
	Dimensions (L x W x H)	143 x 101 x 30 mm
Weight		215 g
OS		Linux kernel 4.4.6, OpenWrt GCC 4.8.3 (for QCA MIPS SoCs)
	L2/L3 multilayer switch/router	<ul style="list-style-type: none"> <li>■ DHCP Client</li> <li>■ Access control list mask rules</li> <li>■ Hardware network address translation (NAT) engine.</li> </ul>
	WiFi	<ul style="list-style-type: none"> <li>■ Channel Number selection</li> <li>■ 5MHz - 40MHz channel bandwidth selection</li> <li>■ Support updating different SSID / Password</li> <li>■ Support Router/AP/Bridge/Client Mode</li> </ul>
	Uplink	WiFi 2.4G / WAN
	Downlink	WiFi 2.4G / LAN
	Operating Humidity	5% ~ 80% Relative Humidity, non-condensing
Certification		FCC/NCC

## Block Diagram

### Block Diagram

