

IN THE BOX

- Device
- Quick-Start Guide

GET STARTED

- Plug device into AC power outlet
- Download the APP from your iPhone or Android phone
- In the APP, choose “Add Device” option and follow the instruction to finish the setup.

FCC Radio Frequency Exposure: The output power of the radio technology used in the Products is below the radio frequency exposure limits set by the FCC. This device should be installed and operated with a minimum distance of 20cm between the radiator and your body.

FCC Compliance Information:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications that are not expressly approved by the manufacturer could void the user's authority to operate the equipment.

Product Specifications

Model: HD34BX

Ports: AC Power Port

Electrical Rating: 100-120VAC 15A Max

Operating temperature — 32°F to 95°F (0°C to 35°C).