



DCH3200

All-Digital, HDTV, M-Card™ Host Set-top

The Motorola DCH3200 all-digital HD Host set-top provides a full set of SDTV, HDTV, and data features and interfaces. The DCH3200 supports a wide range of current and future interactive applications running on Motorola's existing DCT legacy APIs.

Features

M-Card (Multi-stream CableCARD) Host support for conditional access

Compatible with Motorola DCT legacy APIs

Standard-definition (SD), enhanced-definition (ED), and high-definition (HD) MPEG-2 video support with output scaled to 480i, 480p, 720p, or 1080i

Single 54 to 864 MHz video tuner

Digital video (64 QAM/256 QAM)

Video scaling (Picture-in-Graphics)

Accelerated graphics

Motion-adaptive de-interlacing

Dolby™ Digital 5.1 and PCM audio

32 MB Flash (standard)

128 MB DRAM total (standard)

DOCSIS® 2.0 cable modem with support for DSG

RF out-of-band (OOB) data transmitter/receiver

On-screen diagnostics

Macrovision™, HDCP, 5C DTCP, and CGMS-A content protection schemes on the respective interfaces

Full-featured front panel display and controls

SPECIFICATION SHEET
DCH3200 Set-top Box

STANDARD INTERFACES

Front Panel	On/Standby and Message indicators, output video format indicator, 4-character 7-segment display, IR remote control sensor, USB 2.0 Host Type A port
Rear Panel	F-connector for cable input, M-Card slot, RF remodulated output (Ch 3/4), HDMI output, YPbPr component output, baseband composite video output, S-video output, L/R audio output, coaxial and optical S/PDIF digital audio outputs, USB 2.0 Host Type A port, 1394a interfaces (2), 10/100 Mbps Ethernet interface, mini-phone serial port

MANUFACTURING OPTIONAL FEATURES

M-Card pre-installed, 256 MB DRAM (upgrade from 128 MB)

SPECIFICATIONS

RF Input Frequency	54 to 864 MHz
Memory	16MB Flash; 128MB DRAM standard unified
Legacy Platform	Supported
Video	Up to 32-bit color, accelerated 2-D support, and scalable video-in-graphics
Processor	MIPS, RISC-based
Graphics Resolution	
SD Outputs	4:3 up to 720x480
HD Outputs	16:9 up to 1920x1080
Video Resolution	480i, 480p, 720p, and 1080i
Operating Temperature	15 °C to 42 °C (50 °F to 108 °F)
Operating Humidity	5 to 90% (non-condensing)
AC Voltage	105 to 125 VAC, 60 Hz
Accessory Outlet	Unswitched 4 A maximum, 500 W maximum, 105 to 125 VAC, 60 Hz
Power Dissipation	32 W (depending on features)
OOB Modulation	QPSK
Frequency	Agile receiver 70 to 130 MHz
Bandwidth	2.0 MHz maximum
Level	-15 to 15 dBmV
Digital Input Level	
64 QAM	-15 to 15 dBmV
256 QAM	-12 to 15 dBmV
Dimensions	17.2 in W x 12.70 in D x 2.76 in H (43.23 cm x 32.26 cm x 7.01 cm)
Weight	12.0 lb (5.4 kg)

Certain features may not be activated by your service provider, and/or their network settings may limit the feature's functionality. Additionally, certain features may require a subscription. Contact your service provider for details.

All features, functionality, and other product specifications are subject to change without notice or obligation.



Motorola, Inc. 101 Tournament Drive, Horsham, Pennsylvania 19044 U.S.A. www.motorola.com

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. Macrovision is a registered trademark of the Macrovision Corporation. Dolby is a trademark of Dolby Laboratories Licensing Corporation. HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. DOCSIS is a registered trademark of Cable Television Laboratories, Inc. M-Card is a trademark of Cable Television Laboratories, Inc. All other product or service names are the property of their respective owners. © Motorola, Inc. 2009. All rights reserved

365-095-10385-x1 5736 - 0209 - 0K