

OPERATING INSTRUCTIONS

1 SAFETY BATTERY PRECAUTIONS

- Non-rechargeable batteries are not to be recharged.
- Rechargeable batteries are only to be charged under adult supervision.
- Different types of batteries or new and used batteries are not to be mixed.
- Only batteries of the same or equivalent type as recommended are to be used.
- Batteries are to be inserted with the correct polarity.
- Exhausted batteries are not to be removed from the toy.
- The supply terminals are not to be short-circuited.
- Do not dispose the batteries in fire;batteries may leak or explode.
- Batteries should be replaced by adult.

2 STEP1:CHARGING THE BATTERY

Before you can experience all the fun and excitement of using your Amphibious Tank you must charge your Battery Pack. Follow these simple instructions for your initial charge-up and all recharges afterwards.




Fig-1

1. Plug the Charging Unit into a standard wall 220V outlet. (see Fig-1)
2. Allow the Battery Pack to charge for 4 hours.
3. Remove the Battery Pack from the Charging unit by pressing the battery release button and pulling it should fall warm.

▲ Note: Battery life varies depending on usage. An average charge should last approximately 20minutes. The 7.2V NiCd rechargeable battery should be charged by an adult.

▲ Important

After use, the Battery Pack may be hot Allow it to cool for at least 20 minutes before recharging.

If the Battery Pack shows signs of leakage or erosion, do not recharge;replace it immediately.

Do not disassemble the Battery Pack,if battery pack or charging unit becomes wet. Dry thoroughly before recharging.

Do not use any other rechargeable battery except for the standard 7.2V NiCd Battery Pack that was intended solely for use with the product.

The Battery Charger used with the toy is to be regularly examined for damage to the plug. Enclosure and other parts.

In the event of such damage, The toy must not be used with this battery until the damage has been repaired.

3 STEP2:INSTALLATION OF BATTERIES

Once you have charged your Battery Pack, you are now ready to install it your Amphibious Tank! Vehicle! You will also need to insert a standard 9-Volt battery into your Handset.

● Amphibious Tank

1. Remove the two rubber seal Attachments from the cockpit window.(see Fig.2)
2. Unscrew the three screws on top of the cockpit window (battery cover)with a Phillips screwdriver.(see Fig.3)
- 3.correctly connect the fully charged battery pack to the toy and insert the battery pack diagonally into the battery compartment according to the mark in the battery compartment (red wire up). (Fig. 4)
4. Replace the cockpit cover and rubber seal attachments. Failure to do so may result in damage to the vehicle.

● HANDSET:

1. Unscrew the battery cover on the rear of Handset controller and insert one 9-volt battery.(see Fig.5)
2. Replace the battery cover and screws.




Fig-2




Fig-3




Fig-4




Fig-5

● Set content

Check to make sure the tank functions correctly before installation of the accessories.

