

DESCRIPTION

The ORION® Mobile M endpoint is a two-way water endpoint for mobile applications.

In addition to providing the current and daily reading, the endpoint two-way functionality allows users to capture data profile information wirelessly, without having to directly access the endpoint, during the normal reading process.

The ORION Mobile M endpoint is a member of the time-tested ORION family of products from Badger Meter, designed for maximum flexibility. Since 2002, the ORION product family has been providing comprehensive Advanced Metering Analytics (AMA) for interval meter reading and data capture using both one-way and two-way communications.

FUNCTIONALITY

Operation: The endpoint continuously monitors the encoder circuit. At predetermined intervals, the endpoint broadcasts the totaled reading value along with other meter data to the mobile collection devices.

Activation: The endpoints offer a Smart Activation feature. All ORION endpoints are shipped in an inactive, non-transmitting state. After the endpoint is installed, it begins broadcasting data when the encoder senses the first usage of water. No field programming or tools are required to activate the endpoint.

Broadcast Mode: Once activated, the endpoints begin transmitting. After installation, using the endpoint two-way communication, an endpoint transmits its meter data every six seconds.

Data Profiling: The endpoints store up to 90 days of hourly historical interval meter data within nonvolatile memory.

Output Message: The endpoint broadcasts its unique serial number, current meter reading, daily reading and applicable status indicators for mobile reading collection.



APPLICATION

Configurations: Available in integral, remote or endpoint-only configurations, the endpoint can be deployed in indoor, outdoor and pit applications. The endpoint electronics and battery assembly are fully encapsulated in epoxy for environmental integrity.

Meter Compatibility: When attached to a Badger Meter encoder, the endpoint is compatible with all current Badger Meter Recordall® Disc, Turbo Series, Compound Series, Combo Series and Fire Service meters and assemblies, and with E-Series® Ultrasonic and M-Series® Electromagnetic flow meters.

Encoder Compatibility: The endpoint is suitable for use with all Badger Meter encoders as well as the following Badger Meter approved three-wire encoder registers that have a manufacture date of 2000 or newer, are programmed into the AMR/AMI three-wire output mode and have three-wires connected: Elster C700 Digital, InVISION and ScanCoder® encoders and evoQ4 meter (encoder output); Hersey® Translator; Master Meter® Octave® Ultrasonic meter encoder output; Metron-Farnier Hawkeye; Mueller Systems 420 Solid State Register (SSR) LCD; Neptune® ProRead, E-Coder® and ARB-V®; and Sensus® Electronic Register encoder (ECR) and ICE.

SPECIFICATIONS

Dimensions	5.125 in. (130 mm) (H) 1.75 in. (44 mm) diameter at top 2.625 in. (67 mm) (W) × 2.875 in. (73 mm) (D) at base
Broadcast Frequency MHz Band	FCC regulated 902...928 MHz frequency hopping modulation
Operating Temperature Range Storage and Meter Reading	-40...60° C (-40...140° F) NOTE: RF output may be reduced by extremely low temperatures. The water meter should not be subjected to temperatures below freezing.
Humidity	0...100% condensing
Battery	One (1) lithium thionyl chloride D cell (nonreplaceable)
Battery Life	20 years (calculated)

Construction: All ORION Mobile M endpoints are housed in an engineered polymer enclosure with an ORION RF board, battery and antenna. To assure long-term performance, the enclosure is fully potted to withstand harsh environments and to protect the electronics in flooded or submerged pit applications.

Wire Connections: ORION Mobile M endpoints are available with in-line connectors (Twist Tight or Nicor®) for easy installation and connection to compatible encoders/meters. The endpoints are also available with flying leads for field splice connections. Other wire connection configurations may be available upon request.

Range: Transmission reception depends on a number of factors: topographical features, a building's construction materials and obstacles such as buildings, trees, vegetation and fences. Temporary conditions, such as a vehicle parked near the endpoint or heavy rain or snow, could also affect reception. These factors need to be considered when installing and communicating with the endpoint using a handheld or mobile reading system. For a more in-depth discussion, see the white paper, *Understanding RF Propagation of AMR/AMI Systems*, available at www.badgermeter.com.

FEATURES

Communication Type	Two-Way
Application Type	Control/Monitor
Reading Interval Type	06:00 UTC/Now
Encoder Compatibility	Absolute/Incremental
Mobile Reading	✓
Premise Leak Detection	✓
Cut-Wire Indication	✓
Reverse Flow Indication (Absolute Encoder)	✓
No Usage Indication	✓
Encoder Error (Absolute Encoder)	✓
Low Battery Indication	✓
Remote Programming	✓
Remote Clock Synchronization	✓
Firmware Upgrades	✓

LICENSE REQUIREMENTS

This device complies with FCC and Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

- License Requirements:** ORION Mobile M endpoints comply with Part 15 of the FCC Rules. No license is required by the utility to operate an ORION meter reading system.
- Transportation:** The Federal Aviation Administration prohibits operating transmitters and receivers on all commercial aircraft. The ORION endpoint is considered an operating transmitter and cannot be shipped by air.
- Caution:** Changes or modifications to the equipment that are not expressly approved by Badger Meter could void the user's authority to operate the equipment.

SMART WATER IS BADGER METER

E-Series, M-Series, ORION and Recordall are registered trademarks of Badger Meter, Inc. Other trademarks appearing in this document are the property of their respective entities. Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists. © 2022 Badger Meter, Inc. All rights reserved.

www.badgermeter.com