## LBD8355/10 Bidirectional sound projector 6 W

www.boschsecurity.com







The LBD8355/10 is a sound projector for speech and music reproduction in indoor or outdoor applications such as shopping centers, factory grounds and sports fields.


#### System overview

Sound projectors are intended for applications where directing the sound beam is desirable. Similar in concept to a spotlight, a sound projector can be used to provide localized sound reproduction. Typical examples include restaurants, exhibitions, factory grounds and shopping centers. The enclosures are made from high-impact self-extinguishing ABS. The units are supplied with the sufficient 1m of length twocore cable for easy connection.

- Suitable for speech and music reproduction
- Simple power setting
- Option of mounting on ceiling or wall
- Robust self-extinguishing ABS enclosure









Acoustical performance opecifica per octave						
	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
SPL1.1	94.2	92.3	91.3	96.3	98.6	90.1
SPL Max	103. 2	101. 3	100.3	105.3	107.6	99.1
Q Factor	10.8	10.7	11.1	12.3	14.0	16.7
Efficien cy (in %)	1.7	1.1	0.9	2.7	4.6	0.6
H. Angle	180	180	180	180	95	95
V. Angle	180	180	180	170	90	80

Acoustical performance Specified per Octave





All dimensions in mm

Parts included				
Quantity	Component			
1	LBD8355/10 Bidirectional sound projector 6 W			

#### **Technical specifications**

#### Electrical

Maximum Power	8W	
Rated Power	6W	
Sound Pressure level at 6 W / 1 W ( 1 KHz at 1m)	100.3 dB / 91.3 dB (SPL)	
Effective frequency range (-10 dB)	150 Hz – 8kHz	
Opening Angle at 1 KHz / 4 KHz (-6 dB)	180°/95°	
Rated Voltage	100 V	
Rated impedance	1667 ohm	

#### Mechanical

Dimension (Diameter x Length)	154 x 200(in mm)	
Weight	2.1 kg	

#### Environmental

Operating temperature	-25 °C to +55 °C	
Storage temperature	-40 °C to +70 °C	

### **Ordering information**

LBD8355/10 Bidirectional sound projector 6 W Bidirectional sound projector 6 W Order number LBD8355/10

#### Represented by:

Europe, Middle East, Africa: Europe, Middle Last, Africa Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 emea.securitysystems@bosch.com emea.boschsecurity.com

10486848779 | en, V5, 06. Dec 2017

© Bosch Security Systems 2017 | Data subject to change without notice

**Germany:** Bosch Sicherheitssysteme GmbH Robert-Bosch-Ring 5 85630 Grasbrunn Germany www.boschsecurity.com

# North America: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 onlinehelp@us.bosch.com www.boschsecurity.us

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2699 apr.securitysystems@bosch.com www.boschsecurity.asia