

Canon

image**PROGRAF**

 image**PROGRAF**
iPF6350/6300



GRAPHIC ARTS
LARGE-FORMAT PRINTING



imagePROGRAF

SPECIFICATIONS



Print-Heads

PF-05 (2)

Technology

FINE (Full-photolithography Inkjet Nozzle Engineering)

Configuration

Two Print-Heads (Total 12 Colors)
6 Colors per Print-Head
Print-Head (L) Y/PC/C/PGY/GY/MBK
Print-Head (R) PM/M/BK/R/G/B

Number of Nozzles

2,560 per Color (30,720 Total)

Droplet Size

Uniform 4 Picoliter for all colors

Nozzle Pitch (Head Resolution)

1200 dpi

Print Head Swath

1.07 inch

Print Resolution (Max.)

2400 x 1200 dpi

Ink Type

LUCIA EX Ink (Pigment-based)

Ink Tank

PFI-105 (130ml): (BK, MBK, C, M, Y, PC, PM, GY, PGY, R, G, B)

Colors

Cyan, Photo Cyan, Magenta, Photo Magenta, Yellow, Black, Matte Black, Gray, Photo Gray, Red, Green, Blue

Ink Tank Shipped with Printer

12 Colors (90ml Starter Tank Each Color)

Ink Supply Method

Tubing System

Nozzle Recovery System

Non-firing Nozzle Detection and Compensation

Printer Controller

L-COA Controller

Printer Memory

384MB

Hard Disk Capacity

160GB (iPF6350 only)

Media Feed

Roll Feed

One Roll, Front Output

Top-Loading Manual Feed

One Sheet, Front Output

Front-Loading Manual Feed

One Sheet, Front Output

Media Width

8"-24" (Cut Sheet and Roll)

Minimum Media Length

Top-Loading Manual Feed

11.0" (279mm)

Front-Loading Manual Feed

13.8" (350mm)

Roll Feed

8" (203mm)

Maximum Print Length

Manual Feed (Top)

63" (1.6m)

Manual Feed (Front)

36" (914mm)

Roll Feed

59 Feet (18m)*

Borderless Printing Width (Roll Media Only)

10" (254mm), B4 (257mm), A3+ (329mm),
14" (356mm), 16" (407mm), A2 (420mm), A2+/17"
(432mm), B2 (515mm), A1 (594mm), 24" (610mm)

Media Cutter

Built-in Durable Rotary Blade

Printer Stand

Standard

Media Thickness

Top-Loading Manual Feed

0.07mm-0.8mm (2.8mil-31.4mil)

Front-Loading Manual Feed

0.5mm-1.5mm (19.6mil-59.0mil)

Roll Feed

0.07mm-0.8mm (2.8-31.4mil)

Media Core Sizes

2" or 3" Core (with Supplied Adapter)

Printable Margins

Manual Feed (Top/Front)

Leading and Left/Right Edges: 0.12" (3mm)

Trailing Edge, Front Feed: 0.90" (23mm)

Trailing Edge, Top Feed: 0.12" (3mm) Except Art Paper

Top Feed (Art Paper): 0.90" (23mm)

Roll Feed

All Sides: 0.12" (3mm) or 0" for Borderless

Maximum Media Roll Outer Diameter

5.9" (150mm)

Bundled Software

Printing Software

Canon Printer Driver, Print Plug-in for Photoshop®,**

Print Plug-in for Digital Photo Professional,***

Printer Driver Extra Kit**** (Free Layout,

imageRUNNER® Linking Function), Print Plug-in for

Microsoft® Office

Applications

PosterArtist Lite

Digital Photo Front-Access

Utilities

imagePROGRAF® Status Monitor (Windows®), Print

Monitor (Macintosh®), Media Configuration Tool,

Remote UI, Accounting Manager

Printer Language

GARO (Canon Proprietary)

Operating System*

Windows 2000 (32 bit), XP (32/64 bit), Server 2003
(32/64 bit), Server 2008 (32/64 bit), Windows Vista®
(32/64 bit), Windows 7 (32/64 bit) Macintosh OS X®
10.3.9-10.6 (32 bit), OS X 10.5-10.6 (64bit)

Interface

Standard

USB 2.0 High-Speed

10/100/1000Base-T/TX

Acoustic Noise

Operation

47dB or Less

Power Supply

AC 100-120V (50-60Hz)

Power Consumption

Maximum

100W or Less

Standby

6W or Less

Power Off

Less than 1W (compliant with executive order)

Certifications

UL, FCC Class B, ENERGY STAR®

Operational Environment

Temperature

59-86 F° (15-30 C°)

Relative Humidity

10-80% (No Condensation)

Dimensions with Stand (H x W x D)

39.1" x 46.4" x 34.3"

Weight

Approx. 146 lb. with Stand
(Excludes Ink Tank and Print-Heads)

Package Dimensions (H x W x D)/ Weight

25.4" x 52.0" x 36.0"/236 lb.

User-Replaceable Items

Print-Head (PF-05)

Maintenance Cartridge (MC-16)

Options

Roll Holder Set (RH-25)

PosterArtist

- * The maximum printable length varies depending on the application, OS, and RIP used. The maximum printable length from Canon Printer Driver is 50 feet.
- ** For Adobe® Photoshop 6, 7, CS, CS2, CS3, CS4 running on Windows 2000/XP/Windows Vista (32 bit)/Windows 7 or Macintosh OS X 10.2/10.3/10.4/10.5/10.6.
- *** For Digital Photo Professional version 2.1 or later running on Windows 2000/XP/Windows Vista (32 bit)/Windows 7 or Macintosh OS X 10.2/10.3/10.4/10.5/10.6.
- **** Not compatible with Windows 64-bit OS.
- For Canon Printer Driver. For printing from PostScript® applications such as Adobe Illustrator® or QuarkXPress®, please use a PostScript compatible RIP package. For a list of Canon recommended RIP packages, please consult with Canon Alliance and Industry Market program list of RIP vendors.

Canon
image*ANYWARE*

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Park
Melville, NY 11747

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGEPROGRAF, IMAGERUNNER, LUCIA, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Specifications and availability subject to change without notice. All output images and effects are simulated.
©2013 Canon U.S.A., Inc. All rights reserved.

