




8105
8095
8085

LIGHT PRODUCTION SOLUTIONS

Product Specifications



Main Unit

System Type

Digital Multifunction Imaging System

Functions

Standard: Copy, Print (UFR II), Scan, Send, Store
Optional: Print (PCL, Adobe® PS® 3™)

Operation Panel

10.4" SVGA Full-Color, TFT Upright Screen

Memory

Standard: 1.5GB RAM
Maximum: 2GB RAM

Hard Disk Drive

Standard: 80GB
Maximum: 250GB

Mirroring Hard Disk Drive

Optional (80GB, 250GB), Method: RAID1

Network Interface Connection

Standard: 10/100/1000Base-TX
Optional: Wireless LAN (IEEE 802.1x)

Other Interface

Standard: USB 2.0 (Host)x2, USB 2.0 (Device)
Optional: Device Port [USB 2.0 (Host)x2], Serial Interface, Copy Control Interface

Copy/Print Speed

Letter: **8105:** Up to 105 ppm
8095: Up to 95 ppm
8085: Up to 85 ppm
11" x 17": **8105:** Up to 53 ppm
8095: Up to 49 ppm
8085: Up to 43 ppm

Paper Sources (20 lb. Bond)

Standard: Dual 1,500-sheet Drawers
Dual 550-sheet Cassettes
100-sheet Stack Bypass
Optional: 3,500-sheet Paper Deck-C1 or
3,500-sheet POD Deck Lite-A1
Maximum: 7,700 Sheets
(with optional Paper Deck)

Output Paper Capacity (20 lb. Bond)

4,250 Sheets (with Staple Finisher or Booklet Finisher)

Output Paper Sizes

Drawers: Letter
Cassettes: 13" x 19", 12" x 18", 11" x 17",
Legal, Letter, Letter-R, Executive,
Statement-R, Custom Size
[5-1/2" x 7-1/8" to 13" x 19-1/4"
(140mm x 182mm to 330mm
x 488mm)]
Bypass: 13" x 19", 12" x 18", 11" x 17",
Legal, Letter, Letter-R, Executive,
Statement-R, Custom Size
[4" x 5-7/8" to 13" x 19-1/4"
(100mm x 148mm to 330mm
x 488mm)]

Acceptable Paper Weight

Drawers/
Cassettes: 14 lb. Bond to 80 lb. Cover
(52 to 220g/m²)
Bypass: 14 lb. Bond to 140 lb. Index
(52 to 256g/m²)

Duplexing

Paper Size: Standard Automatic Trayless Duplexing
(Up to 13" x 19")
Paper Weight: 14 lb. Bond to 80 lb. Cover
(52 to 220g/m²)

Special Media Support

Cassettes: Tab
Bypass: Transparency, Tracing, Labels

Warm-up Time

From Power On: 1 Minute or Less
From Sleep
Mode: 1 Minute or Less

From Energy Saver Mode:

Approximately 20 Seconds

Power Requirements

120-127V AC, 60Hz, 16A

Plug

NEMA 5-20P

Power Consumption

Maximum: 2.0kW or Less
Sleep Mode: 1W or Less
From Energy
Saver Mode: 171Wh or Less (-50% is selected)

Dimensions (H x W x D)

49-1/4" x 53-3/8" x 30-3/8"
(1252mm x 1481mm x 770mm)*

Installation Space (W x D)

93-3/4"*** x 30-3/8" (2382mm** x 770mm)
(when Booklet Finisher is attached, and Stack Bypass and
Auxiliary Tray are extended)

Weight

Approximately 534 lb. (242kg)**

Toner (Estimated Toner Yield)

70,000 Images @ 6% Coverage



8105
8095
8085

Main Unit (continued)

Image Reader Unit

Scan Resolution

Up to 600 x 600 dpi*

Acceptable Originals (Glass)

Sheet, Book, 3-Dimensional Objects (up to 4.4 lb.)

Maximum Original Size

Up to 11" x 17"

Document Feeder

Scan Method

Single-pass Duplexing Automatic Document Feeder

Acceptable Originals

Paper Size: 11" x 17", Legal, Letter, Letter-R, Statement, or Statement-R

Paper Weight: **BW Originals:** 13 lb. Bond to 80 lb. Cover (50 to 220g/m²)
Color Originals: 17 lb. Bond to 80 lb. Cover (64 to 220g/m²)

Scan Speed (BW/Color; Letter)

Simplex: 120/85 ipm (300 dpi)
120/51 ipm (600 dpi)[†]

Duplex: 200/100 ipm (300 dpi)
120/51 ipm (600 dpi)[†]

Paper Capacity (20 lb. Bond)

300 Sheets

Copy Specifications

First-Copy-Out Time (Letter)

2.7 Seconds or Less

Multiple Copies

1 to 9,999

Copy Exposure

Automatic or Manual (9 levels)

Magnification

From Platen Glass: 25% - 400% (1% increments)

From ADF: 25% - 200% (1% increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset R/E Ratios by Area, Finishing, Two-sided, Density/Exposure Adjustment, Original Type Selection, Interrupt Mode, Sample Set, Setting Confirmation/Cancel, Standard Keys, Reset, Guide Display, Job Duration Display, Reserved Copying

Special Copy Features

Two-page Separation, Booklet, Job Build, N on 1, Add Cover, Sheet Insertion, Different Size Originals, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Block, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Favorites Setting, Previous Settings, Secure Watermark (Optional)

Print Specifications

Processor

Canon Dual Custom Processor (Shared)

Memory

Standard: 1.5GB RAM

Maximum: 2GB RAM

Hard Disk Drive

Standard: 80GB

Maximum: 250GB

Engine Resolution

1200 x 1200 dpi

PDL Support

Standard: UFR II

Optional: PCL 5e, PCL 6, Adobe PostScript 3

Print Driver Supported OS

UFR II: Windows® (Windows 2000/XP/7/Server 2003/Server 2008/Windows Vista®), Citrix MetaFrame, Macintosh® (OS X 10.4.9 or later)

PCL 5e/6: Windows (Windows 2000/XP/7/Server 2003/Server 2008/Windows Vista), Citrix MetaFrame

Adobe PS 3: Windows (Windows 2000/XP/7/Server 2003/Server 2008/Windows Vista), Citrix MetaFrame, Macintosh (OS X 10.4.9 or later)

XPS: Windows Vista, Windows Server 2008, Windows 7

Direct Print Support

Standard: TIFF, JPEG, EPS^{††}

Optional: PDF, XPS^{††}

Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secure Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Save, Poster Printing

Scan Specifications

Network TWAIN Scan

Standard

Network Scan Utility

Color Network ScanGear

Universal Send Specifications

Sending Method

E-Mail, I-Fax, SMB, File Server (FTP, SMB, WebDAV), Mail Box

Color Mode

Auto Color Select (Color, Gray), Auto Color Select (Color, Black), Full Color, Grayscale, BW

Scan Resolution (dpi)^{††}

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Address Book Capacity

Max. 1,800 Destinations (Including 200 One-Touch Buttons)

Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP), WebDAV

E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

File Format

Standard: TIFF, JPEG, PDF, PDF (Compact), PDF (Apply Policy), PDF (Optimize for Web), PDF/A-1b, XPS, XPS (Compact)

Optional: PDF (Trace & Smooth), PDF/XPS (OCR), PDF (Encrypted), PDF/XPS (Digital Signature), PDF (Reader Extensions)

I-Fax Data Format

BW: TIFF (MH, MR, MMR)

Color: TIFF (Profile-C)

Universal Send Features

Two-sided Original, Different Size Originals, Original Type Selection, Book to Two Pages, Density/Exposure Adjustment, Sharpness, Document Name, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, Sender's Name (TTI), E-mail Priority

Fax Specifications

Maximum Number of Connection Lines

4□□□

Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Sending/Recording Size

Statement to 11" x 17"

Fax Features

Job Forwarding, Different-size Originals, Adjusting Overall Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Selecting the Telephone Line (when sending fax), Delayed Send, Preview, Finished Stamp, Job Done Notice, Original Type Selection, Two-sided Original, Book to Two Pages



8105
8095
8085

Main Unit (continued)

Store Specifications

Mail Box

| | |
|-----------------------|--|
| Number Supported: | 100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes |
| Maximum Pages Stored: | 8,000 |

Advanced Box

| | |
|--|--|
| Available Disk Space: | Approximately 10GB (Standard HDD), 113GB (250GB HDD) |
| Communication Protocol: | SMB ⁺⁺⁺ or WebDAV |
| Supported Client PC: | Windows (Windows 2000/XP/7/Windows Vista) |
| Max. Number of Concurrent Connections: | SMB: 32, WebDAV: 12 (Active Sessions) |
| Advanced Box Features: | Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support |

Memory Media

| | |
|-----------|--|
| Standard: | USB Memory |
| Optional: | SD, SDHC, CompactFlash, Memory Stick, Microdrive |

Security Features

Standard

Department ID Management, Single Sign-On H, Access Management System (Device and Function Level Log-in), Secure Print, Trusted Platform Module, User Access Control of Advanced Box, Mail Box Password Protection, IPV6, Restricting Features (Restricting the Send Function, Restricting New Addresses on Address Book), SSL Encrypted Communication, SNMPv1/v3, MAC/IP Address Filtering, SMTP Authentication, POP Authentication before SMTP, HDD Format, Adobe® LiveCycle® Rights Management ES Integration

Optional

Removable HDD, HDD Erase, HDD Encryption/Mirroring, Encrypted Secure Print, Encrypted PDF, Document Scan Lock, IPsec, Secure Watermark

Environmental Information

- ENERGY STAR® Qualified
- Ecomark
- RoHS Compliant
- WEEE Directive

Optional Accessories

Paper Supply Options

Paper Deck Unit-C1

| | |
|--------------------------|--|
| Paper Capacity: | 3,500 Sheets [20 lb. Bond (80g/m ²)] |
| Number of Drawers: | 1 |
| Acceptable Paper Weight: | 14 lb. Bond to 80 lb. Cover (52 to 220g/m ²) |
| Acceptable Paper Type: | Thin, Plain, Heavy, Color, Recycled, Pre-punched |
| Acceptable Paper Size: | Letter |
| Power Source: | From Main Unit |
| Power Consumption: | Approximately 44W (Maximum) |

| | |
|-------------------------|---|
| Dimensions (H x W x D): | 22-1/2" x 12-3/4" x 23" (570mm x 323mm x 583mm) |
| Weight: | Approximately 81.6 lb. (37kg) |

POD Deck Lite-A1

| | |
|--------------------------|--|
| Paper Capacity: | 3,500 Sheets [20 lb. Bond (80g/m ²)] |
| Number of Drawers: | 1 |
| Acceptable Paper Weight: | 14 lb. Bond to 140 lb. Index (52 to 256g/m ²) |
| Acceptable Paper Type: | Thin, Plain, Heavy, Color, Recycled, Pre-punched, Transparency, Labels, Bond, Letterhead |
| Acceptable Paper Size: | 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R |
| Power Requirement: | 120-127V AC, 60Hz, 5A |
| Power Consumption: | Approximately 288W (Maximum) |
| Plug: | NEMA 5-15P |
| Dimensions (H x W x D): | 22-1/2" x 23-5/8" x 24-1/2" (570mm x 601mm x 621mm) |
| Weight: | Approximately 110 lb. (50kg) |

Output Options

Booklet Finisher-F1 PRO

| | |
|----------------------------|---|
| Number of Trays: | 2 |
| Tray Output Capacity: | 5,000 Sheets (Letter, Statement-R, Executive) Tray A: 3,000 Sheets (Letter, Letter-R, Statement-R, Executive) 1,500 Sheets (11" x 17", Legal) Tray B: 2,000 Sheets (Letter, Letter-R, Executive) 1,000 Sheets (11" x 17", Legal) |
| Acceptable Paper Weight: | 14 lb. Bond to 140 lb. Index (52 to 256g/m ²) |
| Acceptable Paper Type: | Thin, Plain, Heavy, Color, Recycled, Pre-punched, Transparency, Tracing, Labels, Tab, Bond, Letterhead, Coated ^A |
| Acceptable Paper Size: | Stapling: Executive, Letter-R, Letter, Legal, 11" x 17" Sheet Stacking: Up to 13" x 19.2" Saddle Finisher: Letter-R, Legal, 11" x 17", 12" x 18", 12-5/8" x 17-11/16", 13" x 19", Custom Size [8-1/4" x 11" to 13" x 19-1/4" (210mm x 279mm to 330mm x 488mm)] |
| Staple Positions: | Corner/Double Stapling (All Sizes) |
| Maximum Stapling Capacity: | 100 Sheets [20 lb. Bond (80g/m ²)] (Letter, Executive) 50 Sheets [20 lb. Bond (80g/m ²)] (11" x 17", Legal, Letter-R) |

| | |
|---------------------------------|--|
| Maximum Saddle-stitch Capacity: | 25 Sheets [20 lb. Bond (80g/m ²)] |
| Paper Capacity of Staple Mode: | Tray A: 1,000 Sheets/100 Sets (11" x 17", Legal, Letter, Letter-R, Executive) Tray B: 2,000 Sheets/100 Sets (Letter, Letter-R, Executive) |
| Type of Staple: | Staple-N1 (5,000 x 3) Corner/Doubling Staple Staple-P1 (5,000 x 2) Saddle-stitch Staple |
| Power Requirement: | 120V AC/60Hz, 8A |

| | |
|-------------------------|---|
| Power Consumption: | Approximately 450W (Maximum) |
| Plug: | NEMA 5-15P |
| Dimensions (H x W x D): | 46-1/2" x 31-1/2" x 31-1/4" (1180mm x 800mm x 792mm) [□] |
| Weight: | Approximately 397 lb. (180kg) |

Puncher Unit-BB1 ^{□□}

| | |
|--------------------------|---|
| Acceptable Paper Weight: | 14 lb. Bond to 73 lb. Cover (52 to 200g/m ²) |
| Paper Sizes: | 2-Hole: Legal, Letter-R 3-Hole: 11" x 17", Letter, Executive |
| Punch Speed: | Up to 105 ppm (Depends on speed of Marking Engine) |
| Weight: | Approximately 6.7 lb. (3.0kg) |
| Power Source: | From Finisher |

Booklet Trimmer-D1 ^{□□}

| | |
|--------------------------|---|
| Margin Trimming: | Fore-Edge Trim |
| Trim Amount: | 0.08" to 0.78" (2mm to 20mm) |
| Trim Thickness: | 100 Sheets |
| Waste Tray Capacity: | 1,500 Sheets (with 0.78" Trim, 20 lb. Bond) |
| Acceptable Paper Weight: | 14 lb. Bond to 140 lb. Index (52g/m ² to 256g/m ²) |
| Output Tray Capacity: | 30 Booklets |
| Dimensions (H x W x D): | 41" x 62" x 30-3/8" (1040mm x 1575mm x 770mm) |
| Weight: | Approximately 335 lb. (152kg) |
| Power Source: | From Saddle Finisher |

Staple Finisher-D1

| | |
|--------------------------------|---|
| Number of Trays: | 3 |
| Total Output Capacity: | 4,250 Sheets (Letter, Statement-R, Executive) Tray A: 1,500 Sheets (Letter, Statement-R, Executive) 750 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R) Tray B: 250 Sheets (Letter, Statement-R, Executive) 125 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R) Tray C: 2,500 Sheets (Letter), 1,500 Sheets (Statement-R, Executive) 750 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R) |
| Acceptable Paper Weight: | 14 lb. Bond to 140 lb. Index (52 to 256g/m ²) |
| Acceptable Paper Type: | Thin, Plain, Heavy, Color, Recycled, Pre-punched, Transparency, Tracing, Labels, Tab, Bond, Letterhead, Coated ^A |
| Acceptable Paper Size: | 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size [4" x 5-7/8" to 13" x 19-1/4" (100mm x 148mm to 330mm x 488mm)] |
| Staple Positions: | Corner/Double Stapling: 11" x 17", Legal, Letter, Letter-R, Executive |
| Maximum Stapling Capacity: | 100 Sheets [20 lb. Bond (80g/m ²)] (Letter, Executive) 50 Sheets [20 lb. Bond (80g/m ²)] (11" x 17", Legal, Letter-R) |
| Paper Capacity of Staple Mode: | Tray A/C: 1,500 Sheets/100 Sets (Letter, Executive) 750 Sheets/50 Sets (11" x 17", Legal, Letter-R) |



8105
8095
8085

Optional Accessories (continued)

| | |
|---------------------------------------|---|
| Type of Staple: | Staple-G1 (5,000 x 3) for 100 Sheets Staple Staple-H1 (5,000 x 3) for 50 Sheets Staple |
| Power Requirement: | 100-240V, 50/60Hz, 2.8A |
| Power Consumption: | Approximately 185W (Maximum) |
| Plug: | NEMA 5-15P |
| Dimensions (H x W x D): | 41" x 25-3/4" (30-3/4"*) x 30-1/8" [1040mm x 654mm (782mm*) x 765mm] |
| Weight: | Approximately 134 lb. (61kg) |
| Booklet Finisher-D1 | |
| Number of Trays: | 3 |
| Total Output Capacity: | 4,250 Sheets (Letter, Statement-R, Executive) Tray A: 1,500 Sheets (Letter, Statement-R, Executive) 750 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R) Tray B: 250 Sheets (Letter, Statement-R, Executive) 125 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R) Tray C: 2,500 Sheets (Letter, Statement-R, Executive) 1,250 Sheets (Statement-R, Executive) 750 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R) |
| Acceptable Paper Weight: | 14 lb. Bond to 140 lb. Index (52 to 256g/m ²) |
| Acceptable Paper Type: | Thin, Plain, Heavy, Color, Recycled, Pre-punched, Transparency, Tracing, Labels, Tab, Bond, Letterhead, Coated ^Δ |
| Acceptable Paper Size: | 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size [4" x 5-7/8" to 13" x 19-1/4" (100mm x 148mm to 330mm x 488mm)] |
| Staple Positions: | Double Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Saddle-Stitch: 13" x 19", 12" x 18", 11" x 17", Legal, Letter-R, Custom Size [8-1/4" x 11" to 13" x 19-1/4" (210mm x 279mm to 330mm x 488mm)] |
| Maximum Stapling Capacity: | 100 Sheets [20 lb. Bond (80g/m ²)] (Letter, Executive) 50 Sheets [20 lb. Bond (80g/m ²)] (11" x 17", Legal, Letter-R) |
| Maximum Saddle-stitch Capacity: | 20 Sheets [20 lb. Bond (80g/m ²)] including one cover page up to 140 lb. Index (256g/m ²) |
| Paper Capacity of Staple Mode: | Tray A/C: 1,500 Sheets/100 Sets (Letter, Executive) 750 Sheets/50 Sets (11" x 17", Legal, Letter-R) |
| Paper Capacity of Saddle-stitch Mode: | 1 to 5 Sheets/25 Sets, 6 to 10 Sheets/15 Sets, 11 to 16 Sheets/10 Sets, 17 to 20 Sheets/5 Sets |
| Type of Staple: | Staple-G1 (5,000 x 3) for 100 Sheets Staple Staple-H1 (5,000 x 3) for 50 Sheets Staple Staple-P1 (5,000 x 2) for Saddle-Stitch Booklet |

| | |
|---|--|
| Power Requirement: | 100-240V, 50/60Hz, 2.8A |
| Power Consumption: | Approximately 224W (Maximum) |
| Plug: | NEMA 5-15P |
| Dimensions (H x W x D): | 41" x 30-1/4" (35-1/4"*) x 30-1/8" [1040mm x 767mm (896mm*) x 765mm] |
| Weight: | Approximately 238 lb. (108kg) |
| Puncher Unit-BF1** | |
| Acceptable Punch Paper Weight: | 14 lb. Bond to 140 lb. Index (52 to 256g/m ²) |
| Acceptable Punch Paper Type: | Thin, Plain, Heavy, Color, Recycled, Tab, Bond, Letterhead, Coated ^Δ |
| Acceptable Punch Paper Size: | 11" x 17", Legal, Letter, Letter-R |
| Punch Type: | 2 Holes: (Legal, Letter-R) 3 Holes: (11" x 17", Letter) |
| Distance Between Punch Holes: | 2 Holes: 2-3/4" (70mm) 3 Holes: 4-1/4" (108mm) |
| Punch Waste Tray Capacity: | Approximately 5,000 Sheets (20 lb. Bond) |
| Power Source: | From Finisher |
| Power Consumption: | Approximately 56W (Maximum) |
| Dimensions (H x W x D): | Inside the Finisher [15-1/2" x 3-3/4" x 15-1/2" (392mm x 95mm x 392mm)] |
| Weight: | Approximately 8.2 lb. (3.7kg) |
| Inner Booklet Trimmer-A1*** | |
| Trimming Method: | Face Trim |
| Trim Thickness: | 40 Sheets (2mm to 20mm Trimming Width) |
| Waste Tray Capacity: | 1,500 Sheets of Trimmed Strips [Width 0.78" (20mm), Letter, 20 lb. Bond (80g/m ²)] |
| Acceptable Paper Weight: | 16 lb. Bond to 140 lb. Index (60 to 256g/m ²) |
| Acceptable Paper Type: | Thin, Plain, Heavy, Recycled, Color, Coated ^Δ |
| Output Tray Capacity: | 30 Booklets |
| Power Source: | From Finisher |
| Power Consumption: | Approximately 51W (Maximum) (when in operation) |
| Dimensions (H x W x D): | Inside the Finisher [15-7/8" x 9-7/8" x 24-5/8" (403mm x 251mm x 625mm)] |
| Weight: | Approximately 70.5 lb. (32kg) |
| Professional Puncher-C1 (with Integration Unit*) | |
| Acceptable Punch Paper Weight: | Letter (3-hole, 5-hole, Velo Bind 11-hole, Plastic Comb 19-hole, Twin Loop 21-hole/32-hole, Color Coil 44-hole): 20 lb. Bond to 80 lb. Cover (75 to 216g/m ²) Letter (ProClick 32-hole): 20 lb. Bond to 65 lb. Cover (75 to 176g/m ²) |
| Acceptable Punch Paper Type: | Plain, Heavy, Color, Recycled, Tab, Coated ^Δ |

| | |
|------------------------------------|--|
| Acceptable Punch Paper Size: | Letter |
| Punch Pattern Die Sets (Optional): | Plastic Comb (19-hole) Twin Loop (21/32-hole) Color Coil (44-hole) Velo Bind (11-hole) Loose Leaf (3/5-hole) ProClick (32-hole) |
| Punch Waste Tray Capacity: | Approximately 25,000 Sheets or more of 20 lb. Bond (80g/m ²) with 4 holes punched |
| Power Requirement: | 120-127V/5.5A-60Hz (Maximum) |
| Power Consumption: | Professional Puncher-C1: Approximately 300W (Maximum) Integration Unit: Approximately 130W (Maximum) |
| Plug: | NEMA 5-15P |
| Dimensions (H x W x D): | Professional Puncher-C1: 41" x 12" x 31-1/4" (1040mm x 305mm x 792mm) Integration Unit: 41" x 9-7/8" x 31-1/4" (1040mm x 250mm x 792mm) |
| Weight: | Professional Puncher-C1: Approximately 176 lb. (80kg) Integration Unit: Approximately 88.2 lb. (40kg) |

| | |
|------------------------------------|--|
| Document Insertion Unit-K1* | |
| Number of Trays: | 2 |
| Acceptable Media: | Covers and Inserts |
| Tray Capacity: | Upper Tray: 200 Sheets [20 lb. Bond (80g/m ²)] Lower Tray: 200 Sheets [20 lb. Bond (80g/m ²)] |
| Acceptable Paper Weight: | 14 lb. Bond to 140 lb. Index (52 to 256g/m ²) |
| Acceptable Paper Type: | Thin, Plain, Heavy, Color, Recycled, Pre-punched, Tab, Bond, Letterhead, Coated ^Δ |
| Acceptable Paper Size: | 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Custom Size [7-1/8" x 7-1/8" to 13" x 19-1/4" (182mm x 182mm to 330mm x 488mm)] |
| Power Requirements: | 100-240V/1A, 50/60Hz |
| Plug: | NEMA 5-15P |
| Power Consumption: | 104W (Maximum) (with Staple/Booklet Finisher-D1) 115W (Maximum) (with Booklet Finisher-F1 PRO) |
| Dimensions (H x W x D): | 55-3/8" x 13-1/4" x 31-1/4" (1407mm x 336mm x 793mm) 55-3/8" x 29-3/8" x 31-1/4" (1407mm x 746mm x 793mm) (with Insertion Feeding Tray) |
| Weight: | Approximately 134 lb. (61kg) |



Optional Accessories (continued)

Paper Folding Unit-H1*

| | |
|--------------------------|--|
| Folding Method: | Roller Pressure Folding |
| Folding Type: | Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel fold |
| Acceptable Paper Weight: | 14 lb. Bond to 28 lb. Bond (52 to 105g/m ²) |
| Acceptable Paper Type: | Thin, Plain, Color, Recycled, Bond, Coated [^] |
| Acceptable Paper Size: | Accordion Z-Fold, C-Fold, Half-Fold: Letter-R Z-Fold: 11" x 17", Legal, Letter-R Double Parallel Fold: Legal, Letter-R |
| Power Requirements: | From Finisher |
| Power Consumption: | 140W (Maximum) |
| Dimensions (H x W x D): | 46-7/8" x 13-1/4" x 31-1/4" (1190mm x 336mm x 793mm) |
| Weight: | Approximately 157 lb. (71kg) |

Additional Print Controller Options

imagePASS-UI

| | |
|----------------------------|---|
| Type: | External |
| Processor: | Intel® Core™ Duo T2500 2.0GHz |
| System: | System 8 Release 2 |
| Memory: | 2GB (Standard/Maximum) |
| Hard Disk: | 80GB |
| Media Type: | DVD-RW Drive |
| Interface Connections: | 10/100/1000Base-T (RJ-45) |
| PDL Support: | Adobe PS 3/PCL 5e/PCL 6 |
| Print Resolution: | 1200 x 1200 dpi 2400 dpi Equivalent x 600 dpi |
| Print Driver Supported OS: | Adobe PS 3: Windows (Windows 2000/XP/7/Server 2003/Server 2008/Windows Vista), Macintosh® (OS X 10.3.9 or later) PCL 5e/6: Windows (2000/XP/7/Server 2003/Windows Vista) |
| Utility Software: | Remote Scan 5.3, Command Workstation® for Windows, Command Workstation for Mac, WebTools |
| Standard Features: | Hot Folders, Virtual Printers |
| EFI Options: | <ul style="list-style-type: none"> • SeeSequence Suite • SeeSequence Impose • SeeSequence Compose • Removable Hard Disk Drive • Integrated Interface and Stand (19" display, keyboard, mouse, and furniture stand) |

Other Optional Accessories

- Utility Tray-A1
- USB Keyboard
- Card Reader-C1***
- Copy Card Reader Attachment Kit-A1
- Braille Label Kit-F1
- ADF Access Handle-A1
- Copy Control Interface Kit-A1
- Convenience Stapler-B1
- PCL Printer Kit-AH1
- PS Printer Kit-AH1
- Direct Print Kit (for PDF/XPS)-H1
- Encrypted Secure Print-D1
- Barcode Printing Kit-D1****
- Web Access Software-H1*
- imageRUNNER ADVANCE Essentials
- Universal Send Advanced Feature Set-E1
- Universal Send Security Feature Set-D1
- Universal Send Digital User Signature Kit-C1
- Authorized Send**
- Secure Watermark-B1
- Wireless LAN Board-B1****
- USB Device Port-A1
- Multimedia Reader/Writer-A1^o
- Additional Memory Type B (512MB)^o
- Document Scan Lock Kit-A2
- Data Erase Kit-C1
- Super G3 Fax Board-AF1^o
- Super G3 2nd Line Fax Board-AF1^o
- Super G3 3rd/4th Line Fax Board-AE1^o
- Fax Board Attachment Kit-A1
- Remote Fax Kit-A1
- HDD Data Encryption and Mirroring Kit-C2
- Removable HDD Kit-AD1
- 2.5-inch/80GB HDD-C1
- 2.5-inch/250GB HDD-D1
- IP Sec Board-B2****
- Expansion Bus-F1
- Voice Guidance Kit-F1
- Remote Operator's Software Kit-B1
- eCopy Suite
- imageWARE Suite

* Height: To the top of the Upright Control Panel in the standard position. Width: To the right edge of the Upright Control Panel in the extended position.

*** Includes ADF and consumables.

[†] Standard color scan support is up to 300 dpi. Up to 600-dpi scanning requires Additional Memory Type B (512MB).

^{††} EPS and XPS cannot be printed directly from the Memory Media or Advanced Box.

^{†††} Browsing Advanced Box using SMB is not supported when imagePASS-UI is attached.

[□] Width is 41.75" (1090mm) when the extension tray is pulled out.

^{□□} Option for Booklet Finisher-F1 PRO.

^{□□□} Supports one line only when Booklet Finisher-F1 PRO is attached.

[^] Coated paper can only be loaded through the Document Insertion Unit-K1.

[▲] When the Auxiliary Tray is extended.

^{▲▲} Puncher Unit-BF1 installs internally within either Staple Finisher-D1 or Booklet Finisher-D1.

^{▲▲▲} Option for Booklet Finisher-D1.

[■] Requires Staple Finisher-D1 or Booklet Finisher-D1.

[■] Requires the Copy Card Reader Attachment Kit-A2.

[■] Requires PCL Printer Kit-AH1.

[◆] Requires PS Printer Kit-AH1 or Direct Print Kit (for PDF/XPS)-H1 when printing PDF files.

^{◆◆} Check with your Authorized Canon Dealer for availability.

^{◆◆◆} Requires Expansion Bus-F1.

[◇] Requires USB Device Port-A1.

^{◇◇} Required for 600-dpi color scanning.

^{◇◇◇} Requires Super G3 Fax Board-AF1.

^o Requires Fax Board Attachment Kit-A1 to install with Booklet Finisher-F1 PRO.

^{oo} Cannot be installed with Booklet Finisher-F1 PRO.

^{▲▲} Requires Super G3 Fax Board-AF1 and Super G3 2nd Line Fax Board-AF1.

NOTE: Some accessories require additional equipment or may be prerequisites for other options. Some accessories cannot be installed simultaneously. Check with your Canon Authorized Dealer for details.

Canon
*image*ANYWARE

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Park
Melville, NY 11747

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGERUNNER, IMAGEPASS, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Some items may not be available at this time; please check for availability. Specifications and availability subject to change without notice. ©2013 Canon U.S.A., Inc. All rights reserved.

1212RA-8000SS-PDF-IH

