

Canon



CORPORATE SOLUTIONS



imageRUNNER®
LBP3460


SPECIFICATIONS

MAIN UNIT

Type:	Desktop Laser Printer
Copying Method:	Electrophoto Method (RAPID Fusing System™)
Developing System:	Dry Dual Component Developing System
Memory:	Standard 64MB RAM Maximum 320MB RAM*
Network Interface	
Connections:	10/100Base-TX (RJ-45)
Other Interface:	USB 2.0 Hi-Speed/USB Full-Speed (USB 1.1 Equivalent)
User Interface:	LCD 16 Characters x 1 Line 8 LED Indicators 8 Operation Keys
First-Print Time:	8.0 Seconds
Warm-Up Time:	0 Seconds From Standby, 9 Seconds After Powering On
Print Speed:	35 ppm (Letter)
CPU:	R4000-333MHz**
Command Language:	UFR II/PCL5e/PCL6
Print Resolution	
UFR II/PCL5e/PCL6:	600 x 600 dpi 2400 dpi Equivalent x 600 dpi
Engine Resolution:	600 x 600 dpi
Printer Drivers	
UFR II:	Windows® (Windows 2000/XP/Server 2003, Citrix MetaFrame), Macintosh® (OS 10.2.8 or later)
PCL5c/PCL6:	Windows (Windows 98/Me/2000/XP/Server 2003, Citrix MetaFrame)
Halftone:	256 Gradations (Continuous-Tone)
Paper Sources	
Standard:	250-Sheet x One Paper Cassette (20 lb. Bond) 100-Sheet Multi-Purpose Tray
Optional:	500-Sheet x Up To One Paper Cassette
Maximum:	850 Sheets



Main Unit



Paper Feeder Unit PF-93

Paper Sizes	
Drawers:	Legal, Letter, Executive, Custom Sizes (Width: 5-7/8" to 8-1/2"; Length: 8-3/8" x 14")
Multi-Purpose Tray:	Legal, Letter, Executive, Statement, Index Card, Custom Sizes (Width: 3" to 8-1/2"; Length: 5" to 14") and Envelopes
Acceptable Paper Weight	
Cassettes:	17 lb. Bond to 35 lb. Bond
Multi-Purpose Tray:	17 lb. Bond to 65 lb. Cover
Maximum Paper Size:	Legal (216 x 355.6mm)
Output Capacity:	Approximately 250 Sheets (Face-Down) Approximately 50 Sheets (Face-Up)
Paper Output:	Face-Down/Face-Up
Duplexing:	Standard Automatic Trayless Duplexing (Legal, Letter)
Dimensions (H x W x D):	10-3/4" x 17-5/8" x 16-1/4" (Main Unit)
Installation Space (W x D):	17-5/8" x 24-1/2" (when Multi-Purpose Tray is extended)
Weight:	Approximately 35.5 lb. (16.1kg)***
Power Supply:	100 – 127V, 50/60Hz
Power Consumption	
Operating:	Approximately 580W (Average)
Standby:	Approximately 10W (Average)
Deep Sleep Mode:	Approximately 7W (Average)
Plug:	NEMA 5-15P

Toner (Estimated Yield):	Black (Cartridge 110): 6,000 Images [▲] Black (Cartridge 110 II): 12,000 Images [▲]
Optional Accessories	
Paper Feeder PF-36^{▲▲}	
Paper Sizes:	Legal, Letter, Executive, Custom Sizes (Width: 5-7/8" to 8-1/2"; Length: 8-3/8" x 14")
Paper Cassette Capacity:	500 Sheets (20 lb. Bond)
Dimensions (H x W x D):	6-5/8" x 17-5/8" x 18-7/8"
Weight:	Approximately 12.4 lb. (5.6kg)

Other Optional Accessories

- Expansion RAM ER-64
- Expansion RAM ER-128
- Expansion RAM ER-256

* One memory slot available for expanding memory.

** The upper limit of the frequency range.

*** Excluding the Toner Cartridge.

[▲] Toner cartridge yield in accordance with ISO/IEC 19752.

^{▲▲} Up to one additional paper cassette can be added.

Canon
image*ANYWARE*

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Park
Melville, NY 11747

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGERUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All other terms and product names may be trademarks or registered trademarks of their respective owners and are hereby acknowledged. Specifications and availability are subject to change without notice. ©2013 Canon U.S.A., Inc. All rights reserved.

