

Introduction to Sex Bolts & Mating Fasteners



What They Are....

Sex Bolts are mating fasteners—

a barrel with an internal thread, and a male screw.

They were originally designed to clamp material between the head of the barrel and the head of the screw, or to bridge the gap between 2 parts, like going through a hollow door.

Common Names For Mating Fasteners...

Sex Bolts—Architectural Bolts—Chicago Screws—Binding Posts—Post & Screw—Internal Thread Mating Fastener—Threaded Rivets

Uses For Sex Bolts...

- Acrylic fastening
- Air Hoods
- Aguariums
- Automotive aftermarket
- Awnings
- Bathroom Partitions
- Belts
- Bindery—Publishing
- Bleachers
- Boats
- Body Armor
- Bullet Proof Glass—joins the panels
- Buses
- Cabinetry
- Construction
- Display Fixtures
- Doors
- Exhibits

- Fence Systems
- Furniture
- Gates
- Glass Fastening
- Hand Rails
- Helmets
- Hinge Pins
- Hurricane Protection
- HVAC
- Kayaks
- Knives
- Lock Sets
- Lockers
- Museum Exhibits
- Orthopedic Braces
- Panic Bars
- Playground Equipment
- Plexiglass Fastening
- Plumbing

- Power Tool Manufacturing
- Railings for buildings
- Range Hoods
- RV Manufacturing
- Saddlebags on Motorcycles
- Seating
- Sheet Metal fastening
- Shutters
- Signs
- Spear Guns
- Stage Production and Lighting
- Stadiums
- Store Fixtures
- Taxidermy
- Trains
- Water Fountains
- Windshields
- & Many More

Variations....

Accurate has 15 years of experience in manufacturing these mating parts. We can make all sizes and head styles in house. We work in most materials available in bar form. Our specialized machinery and processes allow us to produce small quantity and production quantity runs.

See page 7 for help in ordering your custom part, and use one of our new SPECIAL SEX BOLT ORDER FORMS on pages ii-xv.







Pictorial Guide to Sex Bolts



Architectural Style

Smooth Head
Brass, Stainless, Aluminum, Steel
Pages 8–11



One-Way Tamperproof Style Stainless Steel

Pages 20-21



Binding Posts — Chicago Screws

Aluminum, Stainless Steel, Brass, Copper, Plastic Pages 26–35



Slotted Oval Head Style 82 Degree Countersunk Head



Hex Head Sex Bolts Stainless Steel Page 40



Combo Head StyleSlotted/Phillips Head
Steel Zinc & Stainless

Pages 12-15



Button Head Socket Drive Style
Stainless Steel
Page 22–23



Slotted Truss Head Style
Brass, Stainless Steel, Aluminum
Page 36–37



Grommet Nuts
Slotted Head — Plain Head — Open Head
Steel & Stainless Steel
Page 39



T Head Binding Posts
Aluminum
Page 41



Tamperproof Security Style
6 Lobe Drive with Security Pin
Stainless Steel
Pages 16–19



Flat Head Socket Drive Style
Stainless Steel
Page 24–25



Slotted Flat Head Style 82 Degree Countersunk Head Steel, Stainless Steel, Brass Page 38



Phillips Oversize Truss Head Style
Serrated under head
Stainless Steel & Steel

Page 40



Connector Nuts & Bolts
Steel, Brass, Aluminum
Page 41–42






Technical Guide to Sex Bolts

The most important criteria are:

- **1. BARREL DIAMETER** These bolts often are going through pre-drilled holes, and need to be able to fit. The barrel diameter should be slightly less than the hole diameter.
- "D"
 BARREL
 DIAMETER
- 2. BARREL LENGTH—This is the length measured from underneath the head to the end of the barrel.

 Normally the length of the barrel is shorter than the thickness of the material you are going through.
- #B"
 BARREL
 LENGTH
- **3. THREAD SIZE**—What size threads are in the barrel, and how much depth is required. The more thread depth, the more difficult these parts are to manufacture, and the more expensive.
- The "grip range", is the maximum thickness of the material that may be clamped between the male screw and the female sex bolt. Use a shorter male screw to avoid going too deep into the threads in the female barrel.



- **4. HEAD TYPE & DRIVE**—Most common is a "truss" style head. Other common drive styles are; none, slotted, socket and combo drive.
- **5. MATERIAL & FINISH**—We manufacture Sex Bolts in Steel, Aluminum, Brass, Copper and 18-8 and Type 316 Stainless Steel, available in several platings.



Architectural Series Sex Bolts—Pages 8–11

This is our most popular line of Sex Bolts, and are used mainly to set up door hardware (kickplates, panics bars, door closers, hinges) to doors.

Sex Bolts with a smooth head (and no drive) are knurled under the head, which prevents the female barrel from turning when the screw is tightened from the other side.

Bolts for the three most common door sizes are:

• 1-3/8" Thick Door
• 1-3/4" Thick Door
Use 1-3/16" length Sex Bolt
Use 1-9/16" length Sex Bolt

• 2-1/4" Thick Door Use 2-1/16" length Sex Bolt





Technical Guide to Sex Bolts

Combo Head Style Sex Bolts—Pages 12–15

The most economical solution for mating fasteners. Available from stock in 6-32 thru 5/16-18 sizes, in steel zinc and stainless steel materials. Female Barrels and Male screws and shoulder bolts are sold separately. Our male screws are manufactured to match the female barrels, and our male shoulder screws also match both the barrel and head dimensions. To properly identify the part we need the barrel diameter and length of the barrel from underneath the head.



Tamperproof Security Sex Bolts—Pages 16–19

Available from our stock in 10-24 and 1/4-20 sizes - 1/4" and 5/16" barrels. Our 6 Lobe with security pin drive allows for more secure and powerful driving without any cam out or head distortion. Female barrels are sold separately, and we also stock matching shoulder bolts and machine screws with matching dimensions.



One Way Partition Sex Bolts—Page 20-21

These are the standard sex bolts used for bathroom partitions.

Manufactured in Stainless Steel, and with standard one way tamperproof drives. Both the male and female sides have matching shoulders, and these are usually specified with a shoulder length for both male and female portions.



Socket Drive Barrel Bolts—Page 22–25

82 Degree Flat Head Barrel Bolts can be flush mounted for a finished appearance. Button Head have an industrial finished appearance. The socket drive in both styles allows for quick and efficient tightening with standard Hex Keys.



Binding Posts—Pages 26–35

These are the standard sex bolts developed originally for the printing industry, and used to bind catalogs together. Standard size is the 8-32 with .203" diameter barrel. We also stock the non-standard Stainless Steel, Brass and Copper items, for when increased strength or a different look is needed.



Slotted Truss Head Sex Bolts—Pages 36-37

Steel, Brass, Stainless Steel, and Aluminum are the materials we stock for these. Screw driver slot allows quick installation. Large heads have a finished appearance.







Technical Guide to Sex Bolts

Slotted Flat Head Sex Bolts—Page 38

82 Degree Slotted Flat Head Barrel Bolts can be flush mounted for a finished appearance. The screw driver slot allows for quick tightening. Stocked in Steel, Brass and Stainless materials.



Slotted Oval Head Sex Bolts—Page 38

82 Degree Slotted Oval Head Barrel Bolts are mounted in countersunk holes for a finished decorative appearance. The screw driver slot allows for quick tightening. Stocked in Steel, and Brass materials.



Grommet Nuts—Page 39

Originally designed for hinges (Full surface, Half surface, and Half mortise) they are also commonly used in the Display and Fixture industry. Slotted head is for quick and easy installation. The no slot (no drive) head is for tamperproof and secure applications, and the open head allows for infinite adjustment of the male mating screw.



Phillips Oversize Truss Head Sex Bolts—Pages 40

Oversize heads come with a Phillips drive. Serrations under the head aid in preventing turning and loosening from vibration. Stainless Steel and Steel with Chrome plating available.



Hex Head Sex Bolts—Pages 40

One of our strongest styles. Manufactured in 18-8 Stainless Steel for maximum corrosion resistance. Hex head allows for wrench tightening, and presents a substantial industrial look. Excellent strength characteristics.



T Head Binding Posts—Page 41

Specially designed for use in slotted materials. Insert the thin end and then rotate for placement. Used in display fixtures and other commercial applications.



Connector Nuts & Bolts—Page 41–42

The most commonly used nut in the furniture industry. Manufactured in steel, with the following finishes: plain, black, bronze, nickel, brass, and silver.










Ordering Special Sex Bolts

Accurate specializes in manufacturing small quantities of special sex bolts with a quick turn-around. We also make it as simple as possible for you to place an order or get a custom item quoted quickly—
To order or request a quote for a special order, fill out one of the special order forms on pages vi—xi, then cut it out and *Fax to 317-472-9010*. (Don't forget to make a copy of the blank form, for future use, before filling it out)


	Custom Bolt Type	Order Form
	Architectural Series Sex Bolt	Form SB-1
	Combo Head Sex Bolt	Form SB-2
- 0	Tamper Proof Sex Bolt	Form SB-2
04	Socket Drive Sex Bolt (Button Head)	Form SB-2
	Slotted Truss Head Sex Bolts	Form SB-2
	Phillips Truss Head Sex Bolts	Form SB-2
	Grommet Nuts	Form SB-2
*	Socket Drive Sex Bolt (Flat Head)	Form SB-3
	Slotted Flat Head Sex Bolts	Form SB-3
	Binding Post	Form SB-4
	Slotted Oval Head Sex Bolts	Form SB-5
(6	Hex Head Sex Bolts	Form SB-6

If, while filling in the order form, you have dimensions that are not critical, just write "standard" rather than a size. For example, if you need a sex bolt with a 1/2" Barrel Diameter, but the Head Diameter is not critical and does not need to be any special size, write "standard" for Head Diameter and we'll us the standard head size that would normally correspond to a 1/2" Barrel Diameter.















See chart on facing page for available sizes and order numbers



SPECIAL ORDERS
AVAILABLE—
Small Quantities
to Large Volume



Architectural Sex Bolts have smooth Truss Heads—no drive. The knurled barrel keeps the sex bolt from spinning while the flat head screw is tightened from the other side. These parts are secure as there is no way to turn the sex bolt without a drive in the head.

Architectural Sex Bolts are available in a variety of materials and finishes. Materials include Brass, Steel, Aluminum, 18-8 Stainless Steel, & Type 316 Stainless Steel. Available platings include Chrome, Brass, Dark Bronze, & Zinc.

Mating screw is Phillips flat head, steel, and plated to match the finish on the sex bolt. Stainless Sex Bolts have Stainless screws.


Priced by the set—(1) female sex bolt and (1) male Phillips flat head screw—or you can order only the female bolt.


Architectural Sex Bolts have many applications, but are most often used to attach door hardware (kickplates, panics bars, door closers, hinges) to doors. When used in a hollow door they provide strength, security, and easy assembly from the other side.




- Door and Lock Accessory mounts
- Hurricane Protection Shutters
- Elevator Protection Gates
- Architectural products Railings, Cabinetry, Shutters, Seats, and more.

HVAC ventilation installations are also good uses for Sex Bolts. They provide a strong, secure, easy to assemble, and good looking solution for many sheet metal anchoring applications.






























2-1/16

2-1/16

3

1/2

1-1/4

1-1/4

3/4

3/4

3/4

3/4

3/4

3/4

3/16

3/16

3/16

5/16-18

5/16-18

5/16-18

Brass

Dark Bronze

Chrome

5/16-18 x 1-1/2

5/16-18 x 1-1/2

5/16-18 x 1-1/2

5/16-18 x 1-1/2

Z5405

Z5410

Z5401

Z5402

Z5400-1A

Z5410-1E

Z5401-1E

Z5401-1A







See chart on facing page for available sizes and order numbers


When joining two pieces of material together, Sex Bolts provide a versatile and stable fastener. The domed side is used in security applications, as there is no way to turn the smooth head of the Sex Bolt. A hole drilled thru the 2 materials being fastened is a safe and convenient method of joining. Our large selection of head styles, sizes, and materials makes for a custom look at an in-stock price and delivery.

This example shows a bulletproof glass installation at a bank. The sex bolts present a beautiful and finished look with a strong mechanical joint. The all metal joint protects the glass.


Marine applications are a common use for our 18-8 and Type 316 Stainless Steel Sex Bolts. Docks and construction projects in both fresh and salt water areas use these. Many boat manufacturers use these for attaching accessories both above and below the water line. Sex Bolts are particularly useful in fiberglass marine applications, as they take much of the stress away from the fiberglass.











Small Quantities to Large Volume















Ar	chitect	ural S	eries S	ex Bo	lts	STEEL	MATERIA	AL	
D	В	С	Α	F	Е			Set	Female
Barrel	Barrel	Thread	Head	Head	Thread		Mating	Order	Bolt
Diameter	Length 1-3/16"	Depth 3/4"	Diameter 9/16"	Height 5/32"	Size 1/4-20	Plating None	Screw None	Number	Only Z5214
	1-7/8	3/4	9/16	5/32	1/4-20	Zinc	None	_	Z5201
3/8	1-9/16	1	9/16	5/32	1/4-20	Zinc	1/4-20 x 1"	Z5215	Z5215-1E
	1-9/16	1	9/16	5/32	1/4-20	Chrome	1/4-20 x 1-1/2	Z5216	Z5216-1E
Λ =	1-9/16	1 ural C	9/16 orioo C	5/32	1/4-20	Brass	1/4-20 x 1-1/2	Z5217	Z5217-1E
	chitect					10-0 3	TAINLESS		
D Barrel	B Barrel	C Thread	A Head	F Head	E Thread		Mating	Set Order	Female Bolt
Diameter	Length	Depth	Diameter	Height	Size	Plating	Screw	Number	Only
	1-3/16"	5/8"	1/2"	1/8"	8-32	None	8-32 x 7/8"	Z4876	Z4876-1
1/4	1-9/16 2	5/8 5/8	1/2 1/2	1/8 1/8	8-32 8-32	None None	8-32 x 7/8 8-32 x 7/8	Z4886 Z4889	Z4886-1 Z4889-1
	3	5/8	1/2	1/8	8-32	None	8-32 x 7/8	Z4890	Z4890-1
	1-3/16	3/4	1/2	1/8	10-32	None	10-32 x 1	Z5025	Z5025-1
	1-9/16	3/4	1/2	1/8	10-32	None	10-32 x 1	Z5125	Z5125-1
	2	3/4	1/2	1/8	10-32	None	10-32 x 1	Z5126	Z5126-1
5/16	3	3/4	1/2	1/8	10-32	None	10-32 x 1	Z5127	Z5127-1
	1-3/16	3/4	1/2	1/8	12-24	None	12-24 x 1	Z5128	Z5128-1
	1-9/16	3/4	1/2	1/8	12-24	None	12-24 x 1	Z5129	Z5129-1
	2-1/16	3/4	1/2	1/8	12-24	None	12-24 x 1	Z5130	Z5130-1
	3/4"	1/2"	9/16"	5/32"	1/4-20	None	1/4-20 x 1	Z5140	Z5220-1
	1 1-3/16	5/8 3/4	9/16 9/16	5/32 5/32	1/4-20 1/4-20	None None	1/4-20 x 7/8 1/4-20 x 1	Z5221 Z5142	Z5221-1 Z5222
3/8	1-9/16	3/4	9/16	5/32	1/4-20	None	1/4-20 x 1-1/2	Z5225	Z5225-1
0.0	2-1/16	3/4	9/16	5/32	1/4-20	None	1/4-20 x 1-1/2	Z5325	Z5325-1
	3 4	3/4 3/4	9/16 9/16	5/32 5/32	1/4-20 1/4-20	None None	1/4-20 x 1-1/2 1/4-20 x 1-1/2	Z5326 Z5327	Z5326-1 Z5327-1
		3/4	3/10	3/32	1/4-20	None	1/4-20 X 1-1/2	23321	23327-1
	1-9/16	3/4	3/4	3/16	5/16-18	None	5/16-18 x 1	Z5234	Z5234-1
1/2	1-3/4 2-1/16	3/4 3/4	3/4 3/4	3/16 3/16	3/8-16 5/16-18	None None	3/8-16 x 1 5/16-18 x 1-1/2	Z5235 Z5425	Z5235-1 Z5425-1
	3	3/4	3/4	3/16	5/16-18	None	5/16-18 x 1-1/2	Z5426	Z5426-1
Ar	chitect	ural S	eries S	ex Bo	lts	316 ST	FAINLESS	STEEL	
D	В	С	А	F	Е			Set	Female
Barrel					Thread				
Diameter	Barrel	Thread	Head	Head		Plating	Mating	Order	Bolt
Diameter	Barrel Length 1-3/16"	Thread Depth 5/8"	Diameter 1/2"	Head Height 1/8"	Size 8-32	Plating None	Screw 8-32 x 3/4"	Order Number Z5180	Bolt Only Z4877
	Length 1-3/16" 1-9/16	Depth 5/8" 5/8	Diameter 1/2" 1/2	Height 1/8" 1/8	Size 8-32 8-32	None None	Screw 8-32 x 3/4" 8-32 x 3/4	Number Z5180 Z5181	Only Z4877 Z4885
Diameter 1/4	Length 1-3/16" 1-9/16 2	Depth 5/8" 5/8 5/8	Diameter 1/2" 1/2 1/2	Height 1/8" 1/8 1/8	Size 8-32 8-32 8-32	None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4	Number Z5180 Z5181 Z5182	Only Z4877 Z4885 Z4893
	Length 1-3/16" 1-9/16 2 3	Depth 5/8" 5/8 5/8 5/8	Diameter 1/2" 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8	Size 8-32 8-32 8-32 8-32	None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4	Number Z5180 Z5181 Z5182 Z5183	Only Z4877 Z4885 Z4893 Z4894
1/4	Length 1-3/16" 1-9/16 2 3	Depth 5/8" 5/8 5/8 5/8 3/4	Diameter 1/2" 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8	Size 8-32 8-32 8-32 8-32 10-32	None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1	Number Z5180 Z5181 Z5182 Z5183 Z5190	Only Z4877 Z4885 Z4893 Z4894 Z5024
	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4	Diameter 1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8	Size 8-32 8-32 8-32 8-32 10-32 10-32	None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 10-32 x 1	Number Z5180 Z5181 Z5182 Z5183 Z5190 Z5191	Only Z4877 Z4885 Z4893 Z4894 Z5024 Z5124
1/4	Length 1-3/16" 1-9/16 2 3	Depth 5/8" 5/8 5/8 5/8 3/4	Diameter 1/2" 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8	Size 8-32 8-32 8-32 8-32 10-32	None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1	Number Z5180 Z5181 Z5182 Z5183 Z5190	Only Z4877 Z4885 Z4893 Z4894 Z5024
1/4	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4	Diameter 1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32	None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 10-32 x 1 10-32 x 1 10-32 x 1	Xumber Z5180 Z5181 Z5182 Z5183 Z5190 Z5191 Z5192 Z5193	Only
1/4	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4	Diameter 1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 10-32 x 1 10-32 x 1	Number Z5180 Z5181 Z5182 Z5183 Z5190 Z5191 Z5192	Only 24877 Z4885 Z4893 Z4894 Z5024 Z5124 Z5131 Z5132 Z5219
5/16	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3/4 1 1-3/16	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 11/4-20 1/4-20 1/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1	Number Z5180 Z5181 Z5182 Z5183 Z5190 Z5191 Z5192 Z5193 Z5194 Z5195 Z5196	Only
1/4	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3 1-3/16 1-9/16 1-9/16 1-9/16	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	Diameter 1/2" 1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 11/4-20 x 1/2 1/4-20 x 1/2 1/4-20 x 1-1/2 1/4-20 x 1-1/2	Number Z5180 Z5181 Z5182 Z5183 Z5190 Z5191 Z5192 Z5193 Z5194 Z5195 Z5196 Z5197	Only 24877 24885 24893 24894 25024 25124 25131 25132 25219 25223 25224 25197-1
5/16	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3/4 1 1-3/16	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 11/4-20 1/4-20 1/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1	Number Z5180 Z5181 Z5182 Z5183 Z5190 Z5191 Z5192 Z5193 Z5194 Z5195 Z5196	Only
1/4 5/16 3/8	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3/4 1 1-3/16 1-9/16 2-1/16 3	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	Diameter 1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32 5/32 5/32	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1	Number	Only
5/16	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3/4 1 1-3/16 1-9/16 2-1/16	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	Diameter 1/2" 1/2' 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32 3/16	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 11-32 x 1 11-4-20 x 1/2 1/4-20 x 1-1/2	Number Z5180 Z5181 Z5182 Z5183 Z5190 Z5191 Z5192 Z5193 Z5194 Z5195 Z5196 Z5199 Z5206	Only 24877 24885 24893 24894 Z5024 Z5124 Z5131 Z5132 Z5219 Z5223 Z5224 Z5197-1 Z5198-1 Z5206-1
1/4 5/16 3/8	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3/4 1 1-3/16 1-9/16 2-1/16 3	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32 5/32 5/32 3/16 3/16	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 11-20 x 1/2 1/4-20 x 1-1/2	Number	Only 24877 24885 24893 24894 Z5024 Z5124 Z5131 Z5132 Z5219 Z5223 Z5224 Z5197-1 Z5199-1 Z5206-1 Z5207-1
1/4 5/16 3/8	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3 1-3/16 1-9/16 2 3 2-1/16 3	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	Diameter 1/2" 1/2' 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32 3/16	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 11-32 x 1 11-4-20 x 1/2 1/4-20 x 1-1/2	Number Z5180 Z5181 Z5182 Z5183 Z5190 Z5191 Z5192 Z5193 Z5194 Z5195 Z5196 Z5199 Z5206	Only 24877 24885 24893 24894 Z5024 Z5124 Z5131 Z5132 Z5219 Z5223 Z5224 Z5197-1 Z5198-1 Z5206-1
1/4 5/16 3/8 1/2 5/8	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3/4 1 1-3/16 1-9/16 2-1/16 3	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	Diameter 1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32 5/32 3/16 3/16	Size 8-32 8-32 8-32 10-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 11-20 x 1/2 1/4-20 x 1-1/2	Number	Only 24877 24885 24893 24894 Z5024 Z5124 Z5131 Z5132 Z5219 Z5223 Z5224 Z5197-1 Z5198-1 Z5199-1 Z5206-1 Z5207-1
1/4 5/16 3/8 1/2 5/8	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3 1-3/16 1-9/16 2 3 2-1/16 3 3 2-1/16 3	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	Diameter 1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32 5/32 3/16 3/16	Size 8-32 8-32 8-32 10-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1	Number	Only 24877 24885 24893 24894 Z5024 Z5124 Z5131 Z5132 Z5219 Z5223 Z5224 Z5197-1 Z5198-1 Z5199-1 Z5206-1 Z5207-1
1/4 5/16 3/8 1/2 5/8 Ar	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3/4 1 1-3/16 1-9/16 2-1/16 3 2-1/16 3 Chitect	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32 5/32 5/32 5/32 1/4	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1	Number	Only
1/4 5/16 3/8 1/2 5/8 Ar	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3/4 1 1-3/16 1-9/16 2-1/16 3 3 chitect	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32 5/32 5/32 5/32 5/32	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20	None None None None None None None None	8-32 x 3/4" 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 11-32 x 1 11/4-20 x 1-1/2 11/4-21 x 1-1/2 11/4-21 x 1-1/2 11/4-21 x 1-1/2 11/4-21 x 1-1/2	Number	Only
1/4 5/16 3/8 1/2 5/8 Ar D Barrel Diameter	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3 3/4 1 1-3/16 1-9/16 2-1/16 3 2-1/16 3 Chitect B Barrel	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	Diameter 1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32 5/32 3/16 3/16 1/4 Ex Bo F Head	Size 8-32 8-32 8-32 8-32 10-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 11-32 x 1 11-420 x 1-1/2 1/4-20 x 1-1/2	Number Z5180 Z5181 Z5182 Z5183 Z5190 Z5191 Z5193 Z5194 Z5195 Z5196 Z5197 Z5198 Z5199 Z5206 Z5207 ERIAL	Only
1/4 5/16 3/8 1/2 5/8 Ar D Barrel	Length 1-3/16" 1-9/16 2 3 1-3/16 1-9/16 2 3 3/4 1 1-3/16 1-9/16 2-1/16 3 2-1/16 3 Chitect B Barrel Length	Depth 5/8" 5/8 5/8 5/8 5/8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	Diameter 1/2" 1/2" 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/4 1/2 1/4 1/2 1/4	Height 1/8" 1/8 1/8 1/8 1/8 1/8 1/8 1/8 1/8 5/32 5/32 5/32 5/32 5/32 3/16 3/16 1/4 Ex Bo F Head Height	Size 8-32 8-32 8-32 10-32 10-32 10-32 10-32 10-32 10-32 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20 11/4-20	None None None None None None None None	Screw 8-32 x 3/4" 8-32 x 3/4 8-32 x 3/4 8-32 x 3/4 10-32 x 1 1/4-20 x 1-1/2 5/16-18 x 1 5/16-18 x 1 1/2-13 x 1 NUM MAT	Number Z5180 Z5181 Z5182 Z5183 Z5190 Z5191 Z5193 Z5194 Z5195 Z5196 Z5197 Z5198 Z5199 Z5206 Z5207 ERIAL	Only





SEX BOLTS

*Mating Screws are Phillips Flat Head Machine Screws, 18-8 Stainless Steel





Mating Screws are Phillips Flat Head Machine Screws, Type 316 Stainless Steel








Combo Head Sex Bolts





The Accurate Combo Head System—"There is a difference"

Our engineers have developed a complete system and a set of standards for "off the shelf" Sex Bolts and Mating Parts. We stock a complete range of female barrels, which can be coupled with either our Shoulder Screws or machine screws.




Benefits:

- Truss Head, combination slotted/Phillips drive
- All components are matched. Heads on both male and female parts are identical.
- Shoulder Screws and Female Barrels allow different grip lengths to be achieved.
- Machine Screws present a finished set appearance.
- Heads manufactured in accordance with IFI Standards.



Store Fixtures use Sex Bolts everywhere. The finished appearance combined with secure joints and ease of installation make them very popular. Sex Bolts are especially useful and secure for metal tube applications, either round or square, as shown in these illustrations.



Combo Truss Head Barrel & Screw SETS—Steel Zinc









Tapped-Thru Slotted Head

Shorter lengths, where the tap comes thru the head, are slotted drive only.





Combo Head Sex Bolts

Combo Truss Head FEMALE BARRELS—Steel Zinc

Coml	bo Hea	ad Fem	ale Ba	rrels	STE	EL ZIN	С
Barrel	Barrel	Thread	Thread		Head	Head	Order
Diameter	Length	Size	Depth	Drive	Diameter	Height	Number
	3/8"	6-32	15/64"	Combo	5/16"	5/64"	Z4105
	1/2	6-32	3/8	Combo	5/16	5/64	Z4106
3/16	5/8	6-32	3/8	Combo	5/16	5/64	Z4107
3/10	3/4	6-32	3/8	Combo	5/16	5/64	Z4108
	7/8	6-32	3/8	Combo	5/16	5/64	Z4109
	1"	6-32	3/8	Combo	5/16	5/64	Z4110
	1/4	8-32	Thru	Slot	3/8	3/32	Z4435
	3/8	8-32	15/64"	Combo	3/8	3/32	Z4437
13/64	1/2	8-32	3/8	Combo	3/8	3/32	Z4438
10/04	5/8	8-32	3/8	Combo	3/8	3/32	Z4439
	3/4	8-32	3/8	Combo	3/8	3/32	Z4440
	1	8-32	3/8	Combo	3/8	3/32	Z4442
	1/4	10-24	Thru	Clat	7/16	1/8	Z4404
	5/16	10-24	Thru	Slot Slot	3/8	1/8	Z4404 Z4840
	3/8	10-32	5/16	Combo	3/6 7/16	1/8	Z4640 Z4406
	3/6 1/2	10-24	3/8	Combo	7/16 7/16	1/8	Z4408 Z4408
	5/8	10-24	3/8	Combo	7/16	1/8	Z4408 Z4410
1/4	3/4	10-24	3/8	Combo	7/16	1/8	Z4412
	1	10-24	3/8	Combo	7/16	1/8	Z4416
	1-1/4	10-24	3/8	Combo	7/16	1/8	Z4420
	1-1/2	10-24	3/8	Combo	7/16 7/16	1/8	Z4424
	2	10-24	3/8	Combo	7/16	1/8	Z4432
			0.0	5555			
	1/2	1/4-20	3/8	Combo	9/16	5/32	Z4443
	3/4	1/4-20	3/8	Combo	9/16	5/32	Z4444
5/16	1	1/4-20	3/8	Combo	9/16	5/32	Z4446
0.10	1-1/4	1/4-20	1/2	Combo	9/16	5/32	Z4448
	1-1/2	1/4-20	1/2	Combo	9/16	5/32	Z4450
	3/8	5/16-18	3/8	Combo	11/16	11/64	Z4145
3/8	1/2	5/16-18	3/8	Combo	11/16	11/64	Z4146
3/0	3/4	5/16-18	1/2	Combo	11/16	11/64	Z4148
	1	5/16-18	1/2	Combo	11/16	11/64	Z4150

Combo Truss Head Machine Screws—Steel Zinc

Manufactured to match our Combo Head Sex Bolts for a finished appearance. Heads are the same dimensions as our Combo Head Sex Bolts series.

Combo Head Mating S	STE	EL ZINC	
	Head	Head	Order
Size	Diameter	Height	Number
6-32 X 5/16 Steel Zinc	5/16"	5/64"	Z4074
8-32 X 5/16 Steel Zinc	3/8	1/8	Z4075
10-24 X 5/16 Steel Zinc	7/16	1/8	Z4085
1/4-20 X 5/16 Steel Zinc	9/16	5/32	Z4095
5/16-18 X 5/16 Steel Zinc	11/16	11/64	Z4096




Combo Head Shoulder Mating Screws—Steel Zinc

Combo Head Sho		STEE	ZINC				
Mates with	Shoulder	Shoulder	Thread	Thread	Overall	Drive	Order
Combo Head	Diameter	Length	Size	Length	Length		Number
13/64 Diameter	13/64"	1/4"	8-32	5/16"	9/16"	Combo	Z4000
1/4" Diameter	1/4	1/4	10-24	5/16	9/16	Combo	Z4025
5/16" Diameter	5/16	1/4	1/4-20	5/16	9/16	Combo	Z4050









Combo Head Sex Bolts






Benefits:

- Truss Head, combination slotted/Phillips drive
- All components are matched. Heads on both male and female parts are identical.
- Shoulder Screws and Female Barrels allow different grip lengths to be achieved.
- Machine Screws present a finished set appearance.
- Heads manufactured in accordance with IFI Standards.









Combo Truss Head Barrel & Screw SETS—18-8 Stainless Steel

	C	ombo-H	ead Barr	el & Scr	ew Sets—18/8	STAINLESS	STEEL	
Female	Female			Male	Female	Male	Quantity	18/8 ST/ST
Barrel	Barrel	Grip	Thread	Screw	Barrel	Screw	of Each	Set
Diameter	Length	Range	Size	Length	Order Number	Order Number	Part	Order Number
3/16	3/8"	3/8"	6-32	5/16"	Z4105SS	Z4074SS	1	Z4105SSPAK
13/64	3/8	3/8	8-32	5/16	Z4125SS	Z4075SS	1	Z4125SSPAK
13/64	3/4	3/4	8-32	5/16	Z4128SS	Z4075SS	1	Z4128SSPAK
	1/4	1/4	10-24	5/16	Z4404SS	Z4085SS	1	Z4404SSPAK
	3/8	3/8	10-24	5/16	Z4406SS	Z4085SS	1	Z4406SSPAK
1/4	1/2	1/2	10-24	5/16	Z4408SS	Z4085SS	1	Z4408SSPAK
1/4	3/4	3/4	10-24	5/16	Z4412SS	Z4085SS	1	Z4412SSPAK
	1	1	10-24	5/16	Z4416SS	Z4085SS	1	Z4416SSPAK
	1-1/2	1-1/2	10-24	5/16	Z4424SS	Z4085SS	1	Z4424SSPAK
5/16	3/8	3/8	1/4-20	5/16	Z4135SS	Z4095SS	1	Z4135SSPAK
5/16	1/2	1/2	1/4-20	5/16	Z4443SS	Z4095SS	1	Z4443SSPAK
3/8	1/2	1/2	5/16-18	5/16	74146SS	7409688	l 1	74146SSPAK





IMPORT







Combo Truss Head FEMALE BARRELS

Combo Head Sex Bolts

18-8 Stainless Steel





Com	bo Hea	ad Fem	ale Ba	arrels	STAI	NLES	SSTEE	L
Barrel	Barrel	Thread	Thread		Head	Head	18-8 St/St	Type 316 St/St
Diameter	Length	Size	Depth	Drive	Diameter	Height	Order #	Order #
	3/8"	6-32	19/64"	Combo	5/16"	5/64"	Z4105SS	Z4105-316SS
	1/2	6-32	3/8	Combo	5/16	5/64	Z4106SS	Z4106-316SS
2/46	5/8	6-32	3/8	Combo	5/16	5/64	Z4107SS	Z4107-316SS
3/16	3/4	6-32	3/8	Combo	5/16	5/64	Z4108SS	
	7/8	6-32	3/8	Combo	5/16	5/64	Z4109SS	
	1"	6-32	3/8	Combo	5/16	5/64	Z4110SS	
	1/4	8-32	Thru	Slot	3/8	3/32	Z4124SS	Z4124-316SS
	3/8	8-32	19/64	Combo	3/8	3/32	Z4125SS	Z4125-316SS
40/04	1/2	8-32	3/8	Combo	3/8	3/32	Z4126SS	Z4126-316SS
13/64	5/8	8-32	3/8	Combo	3/8	3/32	Z4127SS	Z4127-316SS
	3/4	8-32	3/8	Combo	3/8	3/32	Z4128SS	Z4128-316SS
	7/8	8-32	3/8	Combo	3/8	3/32	Z4129SS	
	1	8-32	3/8	Combo	3/8	3/32	Z4130SS	Z4130-316SS
	1/4	10-24	Thru	Slot	7/16	1/8	Z4404SS	Z4404-316SS
	3/8	10-24	5/16	Combo	7/16	1/8	Z4404SS Z4406SS	Z4404-316SS Z4406-316SS
	1/2	10-24	3/8	Combo	7/16	1/8	Z4408SS	Z4408-316SS
	5/8	10-24	3/8	Combo	7/16	1/8	Z4400SS Z4410SS	24400-31033
1/4	3/4	10-24	3/8	Combo	7/16	1/8	Z441033	Z4412-316SS
1/4	1	10-24	3/8	Combo	7/16	1/8	Z4416SS	Z4416-316SS
	1-1/4	10-24	3/8	Combo	7/16	1/8	Z4420SS	24410-01000
	1-1/2	10-24	3/8	Combo	7/16	1/8	Z4424SS	
	2	10-24	3/8	Combo	7/16	1/8	Z4432SS	
		10 2 1	0/0	CONTRO	77.10	170	2440200	
	3/8	1/4-20	19/64	Combo	9/16	5/32	Z4135SS	Z4135-316SS
	1/2	1/4-20	3/8	Combo	9/16	5/32	Z4443SS	Z4443-316SS
5/16	5/8	1/4-20	3/8	Combo	9/16	5/32	Z4137SS	
5/16	3/4	1/4-20	3/8	Combo	9/16	5/32	Z4444SS	Z4444-316SS
	7/8	1/4-20	3/8	Combo	9/16	5/32	Z4139SS	
	1	1/4-20	3/8	Combo	9/16	5/32	Z4446SS	Z4446-316SS
	3/8	5/16-18	3/8	Combo	11/16	11/64	Z4145SS	Z4145-316SS
	1/2	5/16-18	3/8	Combo	11/16	11/64	Z4146SS	Z4146-316SS
3/8	5/8	5/16-18	3/8	Combo	11/16	11/64	Z4147SS	
0/0	3/4	5/16-18	1/2	Combo	11/16	11/64	Z4148SS	Z4148-316SS
	7/8	5/16-18	1/2	Combo	11/16	11/64	Z4149SS	
	1	5/16-18	1/2	Combo	11/16	11/64	Z4150SS	Z4150-316SS
						HEAD HE	GHT	

New! Expanded Range! Vpe 316








Shorter lengths, where the tap comes thru the head, are slotted drive only.

Combo Truss Head Machine Screws

18-8 & Type 316 Stainless Steel





THREAD SIZE





Tamperproof Sex Bolts

6 Lobe with Pin Security Sex Bolts—The Complete System

A solution that replaces the traditional partition sex bolts, with superior drive characteristics, and a wider range of sizes. (See chart on facing page for available sizes and order numbers)




- All parts are matched for a finished appearance.
- Both female and male bolts feature the 6-Lobe with Pin Security Drive.
- 6-Lobe drive has many advantages—

No cam out during installation

No head distortion during driving,

No special tooling required for both installation and removal.

• Head dimensions for both male and female parts are matched, per IFI standards.







See chart on facing page for available sizes and order numbers



Truss Head 6 Lobe with Pin Security Screws


18-8 Stainless Steel

- Male screws available with or without shoulders.
- •6-Lobe drive has many advantages—

No cam out during installation

No head distortion during driving,

No special tooling required for both installation and removal.




SPECIAL ORDERS AVAILABLE— Small Quantities

to Large Volume



Truss Head 6 Lobe with Pin SHOULDER Security Screws

18-8 Stainless Steel







Tamperproof Sex Bolts





Female Truss Head Sex Bolts — 6 Lobe with Pin Security Drive

Female Sex Bolts and Male Tamperproof Truss Head Screws are sold separately

6 Lol	6 Lobe Tamperproof Security—Female Barrels—18-8 Stainless Steel								
Barrel Diameter	Barrel Length	Thread Size	Thread Depth	Head Diameter	Head Height	Drive Size	Order Number		
1/4"	3/8"	10-24	1/4"	7/16"	7/64"	T 20	Z4406T6S		
1/4	1/2	10-24	1/4	7/16	7/64	T 20	Z4408T6S		
1/4	5/8	10-24	1/4	7/16	7/64	T 20	Z4410T6S		
1/4	3/4	10-24	3/8	7/16	7/64	T 20	Z4412T6S		
1/4	1	10-24	3/8	7/16	7/64	T 20	Z4416T6S		
1/4	1-1/4	10-24	3/8	7/16	7/64	T 20	Z4420T6S		
1/4	1-1/2	10-24	3/8	7/16	7/64	T 20	Z4424T6S		
5/16	1/2	1/4-20	1/4	9/16	9/64	T 27	Z4443T6S		
5/16	3/4	1/4-20	3/8	9/16	9/64	T 27	Z4444T6S		
5/16	1	1/4-20	3/8	9/16	9/64	T 27	Z4446T6S		




6 Lobe with Pin Security Screws Truss Head—18-8 Stainless Steel									
	Head Head Order								
Size	Diameter	Height	Drive	Number					
10-24 X 1/4"	7/16"	7/64"	T 20	Z4580SS					
10-24 X 1/2	7/16	7/64	T 20	Z4582SS					
10-24 X 1	7/16	7/64	T 20	Z4588SS					
1/4-20 X 1/4	9/16	9/64	T 27	Z4591SS					
1/4-20 X 3/8	9/16	9/64	T 27	Z4590SS					
1/4-20 X 1/2	9/16	9/64	T 27	Z4592SS					



6 Lobe with Pin <mark>Shoulder</mark> Security Screws Truss Head—18-8 Stainless Steel									
	Shoulder	Shoulder	Thread	Head	Head		Order		
Size	Diameter	Length	Length	Diameter	Height	Drive	Number		
10-24 X 1/4"	1/4"	1/8"	1/4"	7/16"	1/8"	T20	Z4581SS		
10-24 X 1/4	1/4	1/4	1/4	7/16	1/4	T20	Z4583SS		
10-24 X 3/8	1/4	1/4	3/8	7/16	1/4	T20	Z4584SS		
10-24 X 5/8	1/4	1/4	5/8	7/16	1/4	T20	Z4585SS		
10-24 X 7/8	1/4	1/4	7/8	7/16	1/4	T20	Z4586SS		
1/4-20 X 1/4	5/16	1/4	1/4	9/16	1/4	T27	Z4593SS		
1/4-20 X 3/8	5/16	1/4	3/8	9/16	1/4	T27	Z4594SS		
1/4-20 X 5/8	5/16	1/4	5/8	9/16	1/4	T27	Z4595SS		
1/4-20 X 7/8	5/16	1/4	7/8	9/16	1/4	T27	Z4596SS		



Tamperproof Security Tools



6 Lobe with Pin Bit							
Hex Order							
Number	Size	Size					
BITT20	1/4"	T 20					
BITT27	1/4"	T 27					





Phone: 317-472-9000 • FAX: 317-472-9010 • *email: sales@ampg.com* • www.ampg.com


Tamperproof Sex Bolts

ALL-NEW EXTRA LARGE Tamperproof Sex Bolts

A solution for playground equipment, exercise equipment, detention centers, hospitals, or any other public spaces that need security hardware.


- Male screws available with or without shoulders.
- All parts are matched for a finished appearance.
- Both female and male bolts feature the 6-Lobe with Pin Security Drive.
- 6-Lobe drive has many advantages—
 No cam out during installation
 No head distortion during driving,
 No special tooling required for both installation and removal.
- Head dimensions for both male and female parts are matched, per IFI standards.






ALL-NEW EXTRA LARGE Security Screws —18-8 Stainless Steel

Female Sex Bolts and Male Tamperproof Truss Head Screws are sold separately




ALL-NEW EXTRA LARGE SHOULDER Security Screws —18-8 Stainless Steel





Tamperproof Security Tools for Extra Large Tamperproof Sex Bolts















ALL-NEW EXTRA LARGE Truss Head Sex Bolts — 6 Lobe with Pin Security Drive

Female Sex Bolts and Male Tamperproof Truss Head Screws are sold separately

EXTRA	LARGE 6	Lobe Tar	nperproo	f—Female	Barrels	18-	-8 ST/ST
Barrel	Barrel	Thread	Thread	Head	Head	Drive	Order
Diameter	Length	Size	Depth	Diameter	Height	Size	Number
	1/2"	3/8-16	5/16"	7/8"	1/4"	T40	Z4900T6S
	3/4	3/8-16	7/16	7/8	1/4	T40	Z4901T6S
1/2	1	3/8-16	5/8	7/8	1/4	T40	Z4902T6S
	1-1/2	3/8-16	5/8	7/8	1/4	T40	Z4903T6S
	2	3/8-16	5/8	7/8	1/4	T40	Z4904T6S
	1/2	1/2-13	5/16	1"	5/16"	T40	Z4906T6S
	3/4	1/2-13	7/16	1	5/16	T40	Z4907T6S
5/8	1	1/2-13	5/8	1	5/16	T40	Z4908T6S
	1-1/2	1/2-13	5/8	1	5/16	T40	Z4909T6S
	2	1/2-13	5/8	1	5/16	T40	Z4910T6S
	1/2	5/8-11	5/16	1-1/8"	3/8"	T45	Z4912T6S
	3/4	5/8-11	7/16	1-1/8	3/8	T45	Z4913T6S
3/4	1	5/8-11	3/4	1-1/8	3/8	T45	Z4914T6S
	1-1/2	5/8-11	3/4	1-1/8	3/8	T45	Z4915T6S
	2	5/8-11	3/4	1-1/8	3/8	T45	Z4916T6S
						•	
	1/2	3/4-10	5/16	1-1/4"	1/2"	T45	Z4918T6S
	3/4	3/4-10	7/16	1-1/4	1/2	T45	Z4919T6S
7/8	1	3/4-10	3/4	1-1/4	1/2	T45	Z4920T6S
	1-1/2	3/4-10	3/4	1-1/4	1/2	T45	Z4921T6S
	2	3/4-10	3/4	1-1/4	1/2	T45	Z4922T6S

	400
1	
1	
	1000 EE 10
	B0000000000000000000000000000000000000
	B1000 5
	CONTRACT OF

EXTRA LARG		TAINLESS TEEL		
	Head	Head		Order
Size	Diameter	Height	Drive	Number
3/8-16 x 3/4"	7/8"	1/4"	T40	Z4925SS
3/8-16 x 1-1/2	7/8	1/4	T40	Z4926SS
1/2-13 x 3/4	1	5/16	T40	Z4928SS
1/2-13 x 1-1/2	1	5/16	T40	Z4929SS
5/8-11 x 3/4	1-1/8	3/8	T45	Z4931SS
5/8-11 x 1-1/2	1-1/8	3/8	T45	Z4932SS
3/4-10 x 3/4	1-1/4	1/2	T45	Z4934SS
3/4-10 x 1-1/2	1-1/4	1/2	T45	Z4935SS



-4322100	

Truss		TAINLESS TEEL					
	Shoulder	Shoulder	Thread	Head	Head	•	Order
Size	Diameter	Length	Length	Diameter	Height	Drive	Number
3/8-16 x 3/4"	1/2"	1/4"	3/4"	7/8"	1/4"	T40	Z4938SS
3/8-16 x 1-1/2	1/2	1/4	1-1/2	7/8	1/4	T40	Z4940SS
1/2-13 x 3/4	5/8	1/4	3/4	1	5/16	T40	Z4945SS
1/2-13 x 1-1/2	5/8	1/4	1-1/2	1	5/16	T40	Z4947SS
5/8-11 x 3/4	3/4	1/4	3/4	1-1/8	3/8	T45	Z4950SS
5/8-11 x 1-1/2	3/4	1/4	1-1/2	1-1/8	3/8	T45	Z4952SS
0/4 40 0/4	7/0	4/4	0/4	4.4/4	4.0	T45	7405500
3/4-10 x 3/4	7/8	1/4	3/4	1-1/4	1/2	T45	Z4955SS
3/4-10 x 1-1/2	7/8	1/4	1-1/2	1-1/4	1/2	T45	Z4957SS







Tamperproof One-Way Sex Bolts

One Way Head Bathroom Partition Sex Bolts—The Complete System


Standard items for joining bathroom partitions and other secure installations. One Way Tamperproof Heads — 18-8 Stainless Steel, with 10-24 threads.

Partition Information:

For 1/2" thick partitions, order (1) Z4378 Male and (1) Z4379 Female For 1" thick partitions, order (1) Z4384 Male and (1) Z4381 Female For 1-1/4" thick partitions, order (1) Z4384 Male and (1) Z4382 Female

Female Barrel

Stainless Steel—Truss Head with One Way Slot 1/4" barrel diameter • 10-24 threads 7/16" head diameter • Serrations under head






See chart on facing page for available sizes and order numbers



Male Shoulder Screw


Stainless Steel—Truss Head with One Way Slot 1/4" shoulder diameter • 10-24 threads 7/16" head diameter • Serrations under head





Male and Female Set

Stainless Steel—Truss Head with One Way Slot







Tamperproof One-Way Sex Bolts





	ne Way Head F ss Head Fema	18-8 STAINL	ESS STEEL	
Barrel	Barrel	Thread	Head	Order
Length	Diameter	Size	Diameter	Number
1/4"	1/4"	10-24	7/16	Z4376
3/8	1/4	10-24	7/16	Z4379
1/2	1/4	10-24	7/16	Z4380
5/8	1/4	10-24	7/16	Z4377
3/4	1/4	10-24	7/16	Z4381
1	1/4	10-24	7/16	Z4382
One Way Head—No Serrations Under Head			STEE	L ZINC
1	5/16	12-24	31/64	Z4392



	ne Way Head P Iale Shoulder	18-8 STAINL	LESS STEEL	
Shoulder	Total Length	Thread	Thread	Order
Length	Under Head	Length	Size	Number
1/8	3/8	1/4	10-24	Z4378
1/8	1/2	3/8	10-24	Z4383
1/4	15/32	7/32	10-24	Z4375
1/4	19/32	11/32	10-24	Z4388
1/4	3/4	1/2	10-24	Z4384
1/4	15/16	11/16	10-24	Z4385
1/4	1-3/16	15/16	10-24	Z4386
1/4	1-5/16	1-1/16	10-24	Z4387





Or	ne Way Head F	Partition Sex B	18-8 S	TAINLESS :	STEEL	
	Female		Male	Male		
Grip	Barrel	Female Barrel	Screw	Screw Shoulder	Quantity of	Set
Range	Order Number	Length	Order Number	Length	Each Part	Order Number
1/2"	Z4379	3/8"	Z4378	1/8"	10	Z4379PAK
3/4	Z4380	1/2	Z4384	1/4	10	Z4380PAK
1	Z4381	3/4	Z4384	1/4	10	Z4381PAK
1-1/4	Z4382	1	Z4384	1/4	10	Z4382PAK





Button Head Socket Drive Barrel Bolts USASSMADE




Button Head Socket Drive Barrel Bolts — Female 18-8 Stainless Steel

A line of contemporary barrel bolts that have a button head with a hex drive. The smooth domed appearance of the head lends a sleek finished look to all products and installations.


Our standard size range is from 1/4" diameter x 3/8" length up to 7/8" diameter x 3" length. Manufactured in the USA from durable and corrosion-resistant Type 303 Stainless Steel, these parts are fully machined for a more precise part.

Used in industrial, construction, marine, and transportation, they rpovide excellent strength and versatility. Used in furniture and commercial applications, they present a beautiful modern look and finished appearance.





See chart on facing page for available sizes and order numbers






















Button Head Socket Drive















NOW

AVAILABLE



But	ton Head	18-8 Stair	nless Steel					
Shoulder	Overall	Shoulder	Thread	Thread	Head	Head	Hex Key	Order
Diameter	Length	Length	Size	Length	Diameter	Height	Size	Number
414	1/2"	1/4"	10-24	1/4"	7/16"	1/8"	5/32"	Z1768
1/4	1	1/2	10-24	1/2	7/16	1/8	5/32	Z1769
3/8	15/16	1/4	1/4-20	1/2	21/32	3/16	7/32	Z1624
0,0	11	1/2	1/4-20	1/2	21/32	3/16	7/32	Z1770
		4/0	0/0.40	4.0	7.0	4/4	F/40	74770
	1	1/2	3/8-16	1/2	7/8	1/4	5/16	Z1772
1/2	1-1/2	1	3/8-16	1/2	7/8	1/4	5/16	Z1774
	2	1-1/2	3/8-16	1/2	7/8	1/4	5/16	Z1776
	1	1/2	1/2-13	1/2	1"	5/16	3/8	Z1778
5/8	1-1/2	1	1/2-13	1/2	1"	5/16	3/8	Z1780
	2	1-1/2	1/2-13	1/2	1"	5/16	3/8	Z1782
	1	1/2	5/8-11	1/2	1-1/8	3/8	3/8	Z1784
3/4	1-1/2	1	5/8-11	1/2	1-1/8	3/8	3/8	Z1786
	2	1-1/2	5/8-11	1/2	1-1/8	3/8	3/8	Z1788
	1	1/0	E/0 11	1/0	1 1/0	2/0	2/0	74700
= 10	•	1/2	5/8-11	1/2	1-1/8	3/8	3/8	Z1790
7/8	1-1/2	1	5/8-11	1/2	1-1/8	3/8	3/8	Z1792
	2	1-1/2	5/8-11	1/2	1-1/8	3/8	3/8	Z1794











82° Flat Head Socket Drive Barrel Bolts USASSMADE




82 Degree Flat Head Socket Drive Barrel Bolts — Female **18-8 Stainless Steel**

Our 82° Flat Head Barrel Bolts are designed for use with countersunk holes, which allow the fasteners to sit flush with the surface, providing a clean and finished appearance. Made in the USA from Type 303 Stainless Steel which offers and excellent combination of strength and corrosion resistance.


Our standard size range is from 1/4" diameter x 3/8" length up to 7/8" diameter x 3" length. Specials are available in any size, call or email for a quote.
















SPECIAL ORDERS AVAILABLE— Small Quantities to Large Volume











82° Flat Head Socket Drive



New

Red







Flat Hea	d Socket	Drive—M	lale Mating	Screws	18-8 Stai	nless Steel
Thread	Overall	Thread	Head	Head	Hex Key	Order
Size	Length	Length	Diameter	Height	Size	Number
	3/8"	5/32"	33/64"	11/64"	5/32"	Z1730
10-24	5/8	25/64	33/64	11/64	5/32	Z1732
	1	49/64	33/64	11/64	5/32	Z1734
1/4-20	3/4	7/16	3/4	15/64	7/32	Z1736
	3/4	3/8	7/8	1/4	5/16	Z1738
3/8-16	1-1/4	7/8	7/8	1/4	5/16	Z1740
	1-3/4	1	7/8	1/4	5/16	Z1742
	3/4	3/8	1"	1/4	3/8	Z1744
1/2-13	1-1/4	7/8	1"	1/4	3/8	Z1746
	1-3/4	1	1"	1/4	3/8	Z1748
	3/4	3/8	1-1/8	1/4	3/8	Z1750
	1-1/4	7/8	1-1/8	1/4	3/8	Z1752
F/0 44	1-3/4	1	1-1/8	1/4	3/8	Z1754
5/8-11	3/4	3/8	1-1/4	1/4	1/2	Z1756
	1-1/4	7/8	1-1/4	1/4	1/2	Z1758
4	1-3/4	1	1-1/4	1/4	1/2	Z1760












RIVET HEAD



Aluminum Binding Posts & Screws

Accurate has the largest selection of Binding Posts available with either a Rivet Head or a Truss Head. They are also available in several materials—Aluminum, Stainless Steel, and Solid Brass. Aluminum available Black Anodized on special order.

In addition to the standard printing industry binding applications, binding posts provide a clean, flush, and secure fastener for many other applications, such as helmets, as shown below.



Female Barrels—Plain Aluminum

Truss H	ead Alum	inum Bin	ding Posts	—Fema	le—Tapped	I Thru Head
1/8"	13/64	13/32	.050070	8-32	Unlimited	Z4302X
3/16"	13/64	13/32	.050070	8-32	Unlimited	Z4303
1/4"	13/64	13/32	.050070	8-32	Unlimited	Z4304
3/8"	13/64	13/32	.050070	8-32	Unlimited	Z4306X
1/2"	13/64	13/32	.050070	8-32	Unlimited	Z4308T

Α	luminum l	Rivet Head Closed Top	Truss Head Closed Top				
Barrel	Barrel	Order	Order				
Length	Diameter	Head Diameter	Head Height	Threads	Thread Depth	Number	Number
1/4"	13/64	13/32	.040070	8-32	3/16	Z4304C	Nullibel
3/8"	13/64	13/32	.040070	8-32	1/4	Z4304C Z4306C	Z4306T
3/6 1/2"	13/64	13/32	.040070	8-32	3/8	Z4308C	Z4308X
5/8"	13/64	13/32	.040070	8-32	3/8	Z4300 Z4310	Z4310X
3/4"	13/64	13/32	.040070	8-32	3/8	Z4310 Z4312	Z4310X Z4312X
3/4 7/8"						24312	
7/8	13/64	13/32	.040070	8-32	3/8		Z4314X
1"	13/64	13/32	.040070	8-32	3/8	Z4316	Z4316X
1-1/4"	13/64	13/32	.040070	8-32	3/8	Z4320	Z4320X
1-1/2"	13/64	13/32	.040070	8-32	3/8	Z4324	Z4324X
1-3/4"	13/64	13/32	.040070	8-32	3/8	Z4328	Z4328X
2"	13/64	13/32	.040070	8-32	3/8	Z4332	Z4332X
2-1/4"	13/64	13/32	.040070	8-32	3/8	Z4336	Z4336X
2-1/2"	13/64	13/32	.040070	8-32	3/8	Z4344	Z4344X
2-3/4"	13/64	13/32	.040070	8-32	3/8	Z4346	Z4346X
3"	13/64	13/32	.040070	8-32	3/8	Z4348	Z4348X
3-1/4"	13/64	13/32	.040070	8-32	3/8		Z4350
3-1/2"	13/64	13/32	.040070	8-32	3/8		Z4358X
4"	13/64	13/32	.040070	8-32	3/8		Z4364X
4-1/2"	13/64	13/32	.040070	8-32	3/8		Z4366X
5"	13/64	13/32	.040070	8-32	3/8		Z4368X
6"	13/64	13/32	.040070	8-32	3/8		Z4396X





SPECIAL ORDERS
AVAILABLE—
Small Quantities
to Large Volume










Binding Post Screws— Plain Aluminum



Aluminum Binding Post Screws							
Screw	Head	Head	Order				
Size	Diameter	Height	Number				
8-32 X 3/16	13/32	.050070	Z4302				
8-32 X 1/4	13/32	.050070	Z4301				
8-32 X 5/16	13/32	.050070	Z4300516				
8-32 X 3/8	13/32	.050070	Z4300				



Binding Post Sets— Plain Aluminum

	Plain Aluminum Binding Post Sets								
	Female		Male	Male					
Grip	Barrel	Female Barrel	Screw	Screw	Quantity of	Set			
Range	Order Number	Length	Order Number	Length	Each Part	Order Number			
1/8"	Z4302X	1/8"	Z4302	3/16"	50	Z4302XPAK			
3/16	Z4303	3/16	Z4302	3/16	50	Z4303PAK			
1/4	Z4304C	1/4	Z4302	3/16	50	Z4304CPAK			
3/8	Z4306C	3/8	Z4301	1/4	50	Z4306CPAK			
1/2	Z4308	1/2	Z4301	1/4	50	Z4308PAK			
5/8	Z4310	5/8	Z4301	1/4	50	Z4310PAK			
3/4	Z4312	3/4	Z4301	1/4	50	Z4312PAK			
7/8	Z4314X	7/8	Z4301	1/4	50	Z4314XPAK			
1	Z4316	1	Z4301	1/4	50	Z4316PAK			
1-1/4	Z4320	1-1/4	Z4301	1/4	50	Z4320PAK			
1-1/2	Z4324	1-1/2	Z4301	1/4	50	Z4324PAK			
1-3/4	Z4328	1-3/4	Z4301	1/4	25	Z4328PAK			
2	Z4332	2	Z4301	1/4	50	Z4332PAK			
2-1/4	Z4336	2-1/4	Z4301	1/4	50	Z4336PAK			
2-1/2	Z4344	2-1/2	Z4301	1/4	50	Z4344PAK			
2-3/4	Z4346	2-3/4	Z4301	1/4	50	Z4346PAK			
3	Z4348	3	Z4301	1/4	50	Z4348PAK			
3-1/2	Z4358X	3-1/2	Z4301	1/4	50	Z4358XPAK			
4	Z4364X	4	Z4301	1/4	50	Z4364XPAK			
4-1/2	Z4366X	4-1/2	Z4301	1/4	50	Z4366XPAK			
5	Z4368X	5	Z4301	1/4	50	Z4368XPAK			
6	Z4396X	6	Z4301	1/4	50	Z4396XPAK			



Female Barrel has no slot — Male Screw has Slotted Truss Head Plain Aluminum — Male and Female Barrel Packaged Together

Binding Post Extensions— Plain Aluminum

	Binding Post Extensions—Aluminum									
Barrel	Barrel Barrel Thread Internal External Order									
Diameter	Length	Size	Tap Depth	Stud Lth	Plating	Number				
13/64	1/4	8-32	3/16	1/8	None	Z4370				
13/64	1/2	8-32	3/8	1/4	None	Z4371				
13/64	3/4	8-32	3/8	1/4	None	Z4372				
13/64	3/4	8-32	3/8	1/4	Black	Z4372-BK				
13/64	1	8-32	3/8	1/4	None	Z4373				



Dimensions match the standard Aluminum Binding Posts Threads: 8-32 Male, 8-32 Female











Aluminum Female Barrel: Barrel Dia. 13/64", 8-32 Threads, Head Dia. 13/32", Head Height .040/.070". **Permanent Drive Screw:** Steel with Nickel Plating. No Slot— These are tapped in, and cannot be unscrewed. Head Dia. .375-.410". Thread is spiral U Drive for permanent installation, .150" diameter.

	Aluminum Binding Post Barrel & Steel Permanent Drive Cap										
	Female	Male	Female	Male							
Grip	Barrel	Screw	Barrel	Screw	Quantity of	Set					
Range	Length	Length	Order Number	Order Number	Each Part	Order Number					
3/8"	3/8"	3/8"	Z4306X	Z4684	50	Z4306XCAP					
1/2	1/2	3/8	Z4308	Z4684	50	Z4308CAP					
5/8 3/4	5/8 3/4	3/8 3/8	Z4310 Z4312	Z4684 Z4684	50 50	Z4310CAP Z4312CAP					
7/8 1	7/8 1	3/8 3/8	Z4314X Z4316X	Z4684 Z4684	50 50 25	Z4314XCAP Z4316XCAP					
1-1/4 1-1/2	1-1/4 1-1/2	3/8 3/8	Z4320 Z4324	Z4684 Z4684	25 25	Z4320CAP Z4324CAP					
1-3/4 2	1-3/4 2	3/8 3/8	Z4328 Z4332	Z4684 Z4684	25 25	Z4328CAP Z4332CAP					

Truss Head Black Anodized Aluminum—Female Barrels

Truss	Truss Head Binding Post—Female—Black Anodized Aluminum Tapped Thru The Head										
Barrel	Barrel Barrel Head Head Thread Order										
Length	Diameter	Diameter	Height	Threads	Depth	Number					
1/8"	13/64	13/32	.050070	8-32	Unlimited	Z4302-BK					
3/16"	13/64	13/32	.050070	8-32	Unlimited	Z4303-BK					
1/4"	13/64	13/32	.050070	8-32	Unlimited	Z4304-BK					
3/8"	13/64	13/32	.050070	8-32	Unlimited	Z4306-BK					

Truss	Head Bin	ding Pos	t—Female-	-Black A	nodized	Aluminum					
	—Closed Top										
3/8"	13/64	13/32	.040070	8-32	1/4	Z4306C-BK					
1/2"	13/64	13/32	.040070	8-32	3/8	Z4308X-BK					
5/8"	13/64	13/32	.040070	8-32	3/8	Z4310X-BK					
3/4"	13/64	13/32	.040070	8-32	3/8	Z4312X-BK					
7/8"	13/64	13/32	.040070	8-32	3/8	Z4314X-BK					
1"	13/64	13/32	.040070	8-32	3/8	Z4316X-BK					
1-1/4"	13/64	13/32	.040070	8-32	3/8	Z4320X-BK					
1-1/2"	13/64	13/32	.040070	8-32	3/8	Z4324X-BK					
1-3/4"	13/64	13/32	.040070	8-32	3/8	Z4328X-BK					
2"	13/64	13/32	.040070	8-32	3/8	Z4332X-BK					
2-1/2"	13/64	13/32	.040070	8-32	3/8	Z4344X-BK					
2-3/4"	13/64	13/32	.040070	8-32	3/8	Z4346X-BK					
3"	13/64	13/32	.040070	8-32	3/8	Z4348X-BK					
4"	13/64	13/32	.040070	8-32	3/8	Z4364X-BK					
4-1/2"	13/64	13/32	.040070	8-32	3/8	Z4366X-BK					
5"	13/64	13/32	.040070	8-32	3/8	Z4368X-BK					
6"	13/64	13/32	.040070	8-32	3/8	Z4396X-BK					

















Truss Head Black Anodized Aluminum—Male Screws



Black Anodi	Black Anodized Aluminum Binding Post Screws								
Screw Size	Head Diameter	Head Height	Order Number						
8-32 X 3/16	13/32	.050070	Z4302S-BK						
8-32 X 1/4	13/32	.050070	Z4301-BK						
8-32 X 3/8	13/32	.050070	Z4300-BK						





Truss Head Black Anodized Aluminum—Sets

Female Barrel has no slot — Male Screw has Slotted Truss Head Male Screw and Female Barrel Packaged Together as Set

	Aluminum Binding Post Sets—Black Anodized Aluminum									
	Female	Female	Male	Female	Male					
Grip	Barrel	Thread	Screw	Barrel	Screw	Quantity of	Set			
Range	Length	Depth	Length	Order Number	Order Number	Each Part	Order Number			
1/8"	1/8"	OPEN	3/16"	Z4302-BK	Z4302S-BK	25	Z4374150			
3/16	3/16	OPEN	3/16	Z4303-BK	Z4302S-BK	25	Z4374151			
1/4	1/4	OPEN	3/8	Z4304-BK	Z4300-BK	25	Z4374100			
3/8	3/8	OPEN	3/8	Z4306-BK	Z4300-BK	25	Z4374102			
1/2	1/2	1/4"	3/8	Z4308X-BK	Z4300-BK	25	Z4374103			
5/8	5/8	3/8	3/8	Z4310X-BK	Z4300-BK	25	Z4374152			
3/4	3/4	3/8	3/8	Z4312X-BK	Z4300-BK	25	Z4374153			
7/8	7/8	3/8	3/8	Z4314X-BK	Z4300-BK	25	Z4374154			
1	1	3/8	3/8	Z4316X-BK	Z4300-BK	10	Z4374155			
1-1/4	1-1/4	3/8	3/8	Z4320X-BK	Z4300-BK	10	Z4374156			
1-1/2	1-1/2	3/8	3/8	Z4324X-BK	Z4300-BK	10	Z4374157			
1-3/4	1-3/4	3/8	3/8	Z4328X-BK	Z4300-BK	5	Z4374158			
2	2	3/8	3/8	Z4332X-BK	Z4300-BK	5	Z4374159			
2-1/2	2-1/2	3/8	3/8	Z4344X-BK	Z4300-BK	5	Z4374160			
3	3	3/8	3/8	Z4348X-BK	Z4300-BK	5	Z4374161			
4	4	3/8	3/8	Z4364X-BK	Z4300-BK	5	Z4374162			
5	5	3/8	3/8	Z4368X-BK	Z4300-BK	5	Z4374163			
6	6	3/8	3/8	Z4396X-BK	Z4300-BK	5	Z4374164			



18-8 Stainless Steel Binding Posts—Open Trus Head Female Barrels

18-8 St	18-8 Stainless Steel Binding Posts—Female—Open Truss Head							
Barrel	Barrel	Head	Head		Thread	Order		
Length	Diameter	Diameter	Height	Threads	Depth	Number		
1/8"	13/64"	13/32"	.050070"	8-32	Unlimited	Z4302X-SS		
3/16"	13/64	13/32	.050070	8-32	Unlimited	Z4303-SS		
1/4"	13/64	13/32	.050070	8-32	Unlimited	Z4304-SS		













18-8 St	ainless St	eel Bindir	g Posts—	Female—	Closed T	russ Head
Barrel	Barrel	Head	Head		Thread	Order
Length	Diameter	Diameter	Height	Threads	Depth	Number
1/4"	13/64	13/32	.040070	8-32	5/32	Z4304C-SS
3/8"	13/64	13/32	.040070	8-32	1/4	Z4306C-SS
1/2"	13/64	13/32	.040070	8-32	5/16	Z4308-SS
5/8"	13/64	13/32	.040070	8-32	3/8	Z4310-SS
3/4"	13/64	13/32	.040070	8-32	3/8	Z4312-SS
7/8"	13/64	13/32	.040070	8-32	3/8	Z4314X-SS
1"	13/64	13/32	.040070	8-32	3/8	Z4316-SS
1-1/4"	13/64	13/32	.040070	8-32	3/8	Z4320-SS
1-1/2"	13/64	13/32	.040070	8-32	3/8	Z4324-SS
1-3/4"	13/64	13/32	.040070	8-32	3/8	Z4328-SS
2"	13/64	13/32	.040070	8-32	3/8	Z4332X-SS
2-1/4"	13/64	13/32	.040070	8-32	3/8	Z4336X-SS
2-1/2"	13/64	13/32	.040070	8-32	3/8	Z4344X-SS
2-3/4"	13/64	13/32	.040070	8-32	3/8	Z4346X-SS
3"	13/64	13/32	.040070	8-32	3/8	Z4348X-SS
3-1/2"	13/64	13/32	.040070	8-32	3/8	Z4358X-SS
4"	13/64	13/32	.040070	8-32	3/8	Z4364X-SS
4-1/2"	13/64	13/32	.040070	8-32	3/8	Z4366X-SS
5"	13/64	13/32	.040070	8-32	3/8	Z4368X-SS
6"	13/64	13/32	.040070	8-32	3/8	Z4396X-SS

18-8 Stainless Steel Binding Posts Sets



SPECIAL ORDERS AVAILABLE— Small Quantities to Large Volume

MEMBER 2

	Binding Post Sets — 18/8 Stainless Steel									
			Male	Female	Male					
Grip	Female Barrel	Female Thread	Screw	Barrel	Screw	Quantity of	Set			
Range	Length	Depth	Length	Order Number	Order Number	Each Part	Order Number			
1/8"	1/8"	OPEN	3/16"	Z4302X-SS	Z4302-SS	25	Z4374050			
3/16	3/16	OPEN	3/16	Z4303-SS	Z4302-SS	25	Z4374051			
1/4	1/4	OPEN	1/4	Z4304-SS	Z4301-SS	25	Z4374052			
3/8	3/8	1/4"	3/8	Z4306C-SS	Z4300-SS	25	Z4374053			
3/8	3/8	1/4"	3/8	Z4306C-SS	Z4300-SS	10	Z4374053-10			
1/2	1/2	5/16"	3/8	Z4308-SS	Z4300-SS	10	Z4374054			
5/8	5/8	3/8	3/8	Z4310-SS	Z4300-SS	10	Z4374055			
3/4	3/4	3/8	3/8	Z4312-SS	Z4300-SS	10	Z4374056			
1	1	3/8	3/8	Z4316-SS	Z4300-SS	10	Z4374057			
1-1/4	1-1/4	3/8	3/8	Z4320-SS	Z4300-SS	10	Z4374058			
1-1/2	1-1/2	3/8	3/8	Z4324-SS	Z4300-SS	10	Z4374059			
1-3/4	1-3/4	3/8	3/8	Z4328-SS	Z4300-SS	10	Z4374060			
2	2	3/8	3/8	Z4332X-SS	Z4300-SS	5	Z4374105			
2-1/4	2-1/4	3/8	3/8	Z4336X-SS	Z4300-SS	5	Z4374106			
2-1/2	2-1/2	3/8	3/8	Z4344X-SS	Z4300-SS	5	Z4374107			
2-3/4	2-3/4	3/8	3/8	Z4346X-SS	Z4300-SS	5	Z4374108			
3	3	3/8	3/8	Z4348X-SS	Z4300-SS	5	Z4374109			
3-1/2	3-1/2	3/8	3/8	Z4358X-SS	Z4300-SS	5	Z4374110			
4	4	3/8	3/8	Z4364X-SS	Z4300-SS	5	Z4374111			
4-1/2	4-1/2	3/8	3/8	Z4366X-SS	Z4300-SS	5	Z4374112			
5	5	3/8	3/8	Z4368X-SS	Z4300-SS	5	Z4374113			
6	6	3/8	3/8	Z4396X-SS	Z4300-SS	5	Z4374114			

Female Barrel has no slot—Male Screw has Slotted Truss Head Stainless Steel—Male and Female Barrel Packaged Together











18-8 Stainless Steel Binding Screws

18-8 Stainless Steel Binding Screws								
Screw	Head	Head	Order					
Size	Diameter	Height	Number					
8-32 X 3/16	13/32	.050070	Z4302-SS					
8-32 X 1/4	13/32	.050070	Z4301-SS					
8-32 X 3/8	13/32	.050070	Z4300-SS					







Brass Binding Posts—Female—Open Truss Head

Bras	ss Bindin	g Posts-	-Female Ba	arrels—	Open Trus:	s Head
1/8"	13/64	13/32	.050070	8-32	Unlimited	Z4302X-BR
3/16"	13/64	13/32	.050070	8-32	Unlimited	Z4303-BR
1/4"	13/64	13/32	.050070	8-32	Unlimited	Z4304-BR
3/8"	13/64	13/32	.050070	8-32	Unlimited	Z4306X-BR




Brass Binding Posts—Female—Closed Truss Head

Brass Binding Posts—Female Barrels—Closed Truss Head							
Barrel	Barrel	Head	Head		Thread	Order	
Length	Diameter	Diameter	Height	Threads	Depth	Number	
1/4"	13/64	13/32	.040070	8-32	5/32	Z4304C-BR	
3/8"	13/64	13/32	.040070	8-32	1/4	Z4306-BR	
1/2"	13/64	13/32	.040070	8-32	5/16	Z4308-BR	
5/8"	13/64	13/32	.040070	8-32	3/8	Z4310-BR	
3/4"	13/64	13/32	.040070	8-32	3/8	Z4312-BR	
7/8"	13/64	13/32	.040070	8-32	3/8	Z4314X-BR	
1"	13/64	13/32	.040070	8-32	3/8	Z4316-BR	
1-1/4"	13/64	13/32	.040070	8-32	3/8	Z4320X-BR	
1-1/2"	13/64	13/32	.040070	8-32	3/8	Z4324X-BR	
1-3/4"	13/64	13/32	.040070	8-32	3/8	Z4328X-BR	
2"	13/64	13/32	.040070	8-32	3/8	Z4332X-BR	
2-1/4"	13/64	13/32	.040070	8-32	3/8	Z4336X-BR	
2-1/2"	13/64	13/32	.040070	8-32	3/8	Z4344X-BR	
2-3/4"	13/64	13/32	.040070	8-32	3/8	Z4346X-BR	
3"	13/64	13/32	.040070	8-32	3/8	Z4348X-BR	
3-1/2"	13/64	13/32	.040070	8-32	3/8	Z4358X-BR	
4"	13/64	13/32	.040070	8-32	3/8	Z4364X-BR	
4-1/2"	13/64	13/32	.040070	8-32	3/8	Z4366X-BR	
5"	13/64	13/32	.040070	8-32	3/8	Z4368X-BR	
6"	13/64	13/32	.040070	8-32	3/8	Z4396X-BR	














Brass Binding Screws


Brass Binding Screws							
Screw	Head	Head	Order				
Size	Diameter	Height	Number				
8-32 X 1/4	13/32	.050070	Z4301-BR				
8-32 X 5/16	13/32	.050070	Z4300-BR				






Brass Binding Post Sets

Female Barrel has no slot— Male Screw has Slotted Truss Head Plain Brass—Male and Female Barrel Packaged Together





	Brass Binding Post Sets									
	Female	Female	Male	Female	Male	Quantity	Set			
Grip	Barrel	Thread	Screw	Barrel	Screw	of Each	Order			
Range	Length	Depth	Length	Order Number	Order Number	Part	Number			
3/16"	3/16"	OPEN	1/4"	Z4303-BR	Z4301-BR	25	Z4374001			
1/4"	1/4"	OPEN	1/4"	Z4304-BR	Z4301-BR	25	Z4374002			
3/8"	3/8"	1/4"	5/16"	Z4306-BR	Z4300-BR	25	Z4374003			
1/2"	1/2"	3/8"	5/16"	Z4308-BR	Z4300-BR	25	Z4374004			
5/8"	5/8"	3/8"	5/16"	Z4310-BR	Z4300-BR	25	Z4374120			
3/4"	3/4"	3/8"	5/16"	Z4312-BR	Z4300-BR	25	Z4374005			
7/8"	7/8"	3/8"	5/16"	Z4314X-BR	Z4300-BR	10	Z4374121			
1"	1"	3/8"	5/16"	Z4316-BR	Z4300-BR	10	Z4374006			
1-1/4"	1-1/4"	3/8"	5/16"	Z4320X-BR	Z4300-BR	10	Z4374122			
1-1/2"	1-1/2"	3/8"	5/16"	Z4324X-BR	Z4300-BR	10	Z4374123			
1-3/4"	1-3/4"	3/8"	5/16"	Z4328X-BR	Z4300-BR	10	Z4374124			
2"	2"	3/8"	5/16"	Z4332X-BR	Z4300-BR	10	Z4374125			
2-1/4"	2-1/4"	3/8"	5/16"	Z4336X-BR	Z4300-BR	5	Z4374126			
2-1/2"	2-1/2"	3/8"	5/16"	Z4344X-BR	Z4300-BR	5	Z4374127			
2-3/4"	2-3/4"	3/8"	5/16"	Z4346X-BR	Z4300-BR	5 5	Z4374128			
3"	3"	2.0"	F/4C"	742407 DD	74200 DD	_	74074400			
	-	3/8"	5/16"	Z4348X-BR	Z4300-BR	5	Z4374129			
3-1/2" 4"	3-1/2" 4"	3/8"	5/16"	Z4358X-BR	Z4300-BR	5	Z4374130			
	· -	3/8"	5/16"	Z4364X-BR	Z4300-BR	5	Z4374131			
4-1/2"	4-1/2"	3/8"	5/16"	Z4366X-BR	Z4300-BR	5	Z4374132			
5"	5"	3/8"	5/16"	Z4368X-BR	Z4300-BR	5	Z4374133			
6"	6"	3/8"	5/16"	Z4396X-BR	Z4300-BR	5	Z4374134			



SPECIAL ORDERS AVAILABLE—

Small Quantities to Large Volume










Copper Binding Posts—Female—Closed Truss Head


	Copper Binding Posts — Closed Top Rivet Head								
Barrel Length	Barrel Diameter	Head Diameter	Head Height	Threads	Thread Depth	Order Number			
1/4"	13/64"	13/32"	.040070	8-32	5/32"	Z4304C-CU			
3/8"	13/64"	13/32"	.040070	8-32	1/4"	Z4306-CU			
1/2"	13/64"	13/32"	.040070	8-32	5/16"	Z4308-CU			
5/8"	13/64"	13/32"	.040070	8-32	3/8"	Z4310-CU			
3/4"	13/64"	13/32"	.040070	8-32	3/8"	Z4312-CU			
1"	13/64"	13/32"	.040070	8-32	3/8"	Z4316-CU			



Solid Copper Binding Screws—Slotted Head

Copper Binding Screws — Slotted Head						
Screw	Head	Head	Order			
Size	Diameter	Height	Number			
8-32 X 1/4	13/32"	.040070	Z4301-CU			
8-32 X 3/8	13/32"	.040070	Z4300-CU			





Copper Binding Post Sets

Female Barrel has no slot— Male Screw has Slotted Truss Head Plain Brass—Male and Female Barrel Packaged Together

	Copper Binding Post Sets — Closed Top Rivet Head								
Grip Range	Female Barrel Length	Female Thread Depth	Male Screw Length	Female Barrel Order Number	Male Screw Order Number	Quantity of Each Part	Set Order Number		
1/4"	1/4"	1/8"	3/8"	Z4304C-CU	Z4300-CU	10	Z4374140		
3/8"	3/8"	1/4"	3/8"	Z4306-CU	Z4300-CU	10	Z4374141		
1/2"	1/2"	3/8"	3/8"	Z4308-CU	Z4300-CU	10	Z4374142		
5/8"	5/8"	3/8"	3/8"	Z4310-CU	Z4300-CU	10	Z4374143		
3/4"	3/4"	3/8"	3/8"	Z4312-CU	Z4300-CU	10	Z4374144		
1"	1"	3/8"	3/8"	Z4316-CU	Z4300-CU	10	Z4374145		











Steel-Zinc Plated Binding Posts—Female Barrels



Steel-Zinc Plated Binding Posts—Female Barrels								
Barrel	Barrel	Head	Head	Th	Thread	Order		
Length	Diameter	Dia.	Height	Threads	Depth	Number		
1/8	13/64	13/32	.050070	8-32	Thru	Z4302X-STL		
3/16	13/64	13/32	.050070	8-32	Thru	Z4303-STL		
1/4	13/64	13/32	.050070	8-32	Thru	Z4304-STL		
3/8	13/64	13/32	.050070	8-32	1/4	Z4306C-STL		
1/2	13/64	13/32	.050070	8-32	3/8	Z4308-STL		
5/8	13/64	13/32	.050070	8-32	3/8	Z4310-STL		
3/4	13/64	13/32	.050070	8-32	3/8	Z4312-STL		
1	13/64	13/32	.050070	8-32	3/8	Z4316-STL		
1-1/4	13/64	13/32	.050070	8-32	3/8	Z4320-STL		
1-1/2	13/64	13/32	.050070	8-32	3/8	Z4324-STL		
1-3/4	13/64	13/32	.050070	8-32	3/8	Z4328-STL		
2	13/64	13/32	.050070	8-32	3/8	Z4332-STL		





Steel-Zinc Plated Binding Screws—Slotted Head



Steel Zinc Binding Screws							
Screw	Head	Head	Order				
Size	Diameter	Height	Number				
8-32 x 3/16	13/32	.050070	Z4302-STL				
8-32 X 3/8	13/32	.050070	Z4300-STL 4				

Steel-Zinc Plated Binding Post Sets



SPECIAL ORDERS
AVAILABLE—
Small Quantities
to Large Volume

	Steel–Zinc Binding Post Sets								
	Female	Female	Male	Female	Male				
Grip	Barrel	Thread	Screw	Barrel	Screw	Quantity of	Set		
Range	Length	Depth	Length	Order Number	Order Number	Each Part	Order Number		
1/8	1/8	Thru	3/16	Z4302X-STL	Z4302-STL	25	Z4302XPAK-STL		
3/16	3/16	Thru	3/16	Z4303-STL	Z4302-STL	25	Z4303PAK-STL		
1/4	1/4	Thru	3/16	Z4304-STL	Z4302-STL	25	Z4304PAK-STL		
3/8	3/8	1/4	3/16	Z4306C-STL	Z4302-STL	25	Z4306CPAK-STL		
1/2	1/2	3/8	3/8	Z4308-STL	Z4300-STL	25	Z4308PAK-STL		
5/8	5/8	3/8	3/8	Z4310-STL	Z4300-STL	25	Z4310PAK-STL		
3/4	3/4	3/8	3/8	Z4312-STL	Z4300-STL	25	Z4312PAK-STL		
1	1	3/8	3/8	Z4316-STL	Z4300-STL	10	Z4316PAK-STL		
1-1/4	1-1/4	3/8	3/8	Z4320-STL	Z4300-STL	10	Z4320PAK-STL		
1-1/2	1-1/2	3/8	3/8	Z4324-STL	Z4300-STL	10	Z4324PAK-STL		
1-3/4	1-3/4	3/8	3/8	Z4328-STL	Z4300-STL	10	Z4328PAK-STL		
2	2	3/8	3/8	Z4332-STL	Z4300-STL	10	Z4332PAK-STL		









Black Plastic Binding Post Barrels—Friction Fit

Plastic Binding Post Barrels: For use in 1/4" diameter holes. Barrel Diameter .215-.240. Slotted Truss Head, .100" Head Height. Friction Fit Internal Thread.

Black Plastic Binding Posts— Female Barrels—Friction Fit								
			Female					
Grip	Female Barrel	Head	Barrel					
Range	Length	Diameter	Order Number					
1/2"	1/2"	25/64"	Z4670					
5/8	5/8	25/64	Z4671					
3/4	3/4	25/64	Z4672					
1	1	25/64	Z4673					
1-1/4	1-1/4	25/64	Z4674					
1-1/2	1-1/2	25/64	Z4675					
1-3/4	1-3/4	25/64	Z4676					
2	2	25/64	Z4677					
2-1/4	2-1/4	27/64	Z4678					
2-1/2	2-1/2	27/64	Z4679					
3-1/4	3-1/4	27/64	Z4680					
4	4	27/64	Z4681					

Black Plastic Caps

Bla	Black Plastic Binding Post Caps Permanent or Removable						
Head	For use with Friction Fit	Order					
Height	Plastic Binding Post Barrels	Number					
	REMOVABLE: Slotted Binding Head						
7/64"		Z4683					
.075"	PERMANENT: Unslotted Flat Head	Z4682					



Female Plastic Binding Posts—Slotted Head

	F	Plastic Bindi	ng Posts-	-Female Barı	rels—Slo	tted Hea	d	
Barrel	Barrel	Head	Head		Thread			Order
Length	Diameter	Diameter	Height	Threads	Depth	Material	Color	Number
1/4"	.240"	3/8"	.100"	10-24	3/16"	Plastic	Black	Z4200
1/4	.240	3/8	.100	10-24	3/16	Plastic	White	Z4209
3/8	.240	3/8	.100	10-24	3/16	Plastic	Black	Z4201
3/8	.240	3/8	.100	10-24	3/16	Plastic	White	Z4210
1/2	.240	3/8	.100	10-24	3/16	Plastic	Black	Z4202
1/2	.240	3/8	.100	10-24	3/16	Plastic	White	Z4211
3/4	.240	3/8	.100	10-24	3/16	Plastic	Black	Z4203
3/4	.240	3/8	.100	10-24	3/16	Plastic	White	Z4212
7/8	.240	3/8	.100	10-24	3/16	Plastic	Black	Z4204
1	.240	3/8	.100	10-24	3/16	Plastic	Black	Z4205
1-1/4	.240	3/8	.100	10-24	3/16	Plastic	Black	Z4206
1-1/2	.240	3/8	.100	10-24	3/16	Plastic	Black	Z4207
2	.240	3/8	.100	10-24	3/16	Plastic	Black	Z4208



Plastic Binding Post Screws—Threaded—Slot Head

	Plastic Binding Post Male Screws—Slotted Head								
	Head	Head				Order			
Size	Diameter	Height	Threads	Material	Color	Number			
10-24 X 3/16	3/8"	.100"	10-24	Plastic	Black	Z4219			
10-24 X 3/16	3/8	100	10-24	Plastic	White	74218			



Black Plastic Binding Post Sets

	Black Plastic Binding Post Sets									
Grip Range	Female Barrel Length	Female Thread Depth	Female Barrel Order Nbr	Male Screw Order Nbr	Qty of Each Part	Order Number				
1/2	1/2	3/16	Z4202	Z4219	10	Z4202SET				
3/4	3/4	3/16	Z4203	Z4219	10	Z4203SET				
1	1	3/16	Z4205	Z4219	10	Z4205SET				
1-1/4	1-1/4	3/16	Z4206	Z4219	10	Z4206SET				
1-1/2	1-1/2	3/16	Z4207	Z4219	10	Z4207SET				
2	2	3/16	74208	74219	10	74208SFT				








Slotted Head Sex Bolts



Slotted Truss Head—Female Barrels

These Sex Bolts have slotted Truss Heads, no knurl under the head, no mating screw. Available in Steel, Steel–Zinc, Plain Brass, Brass Chrome, Stainless Steel, & Aluminum



Barrel Diameter Barrel Diameter Diamet	3/64 WIDE	3/64 WIDE TO END OF .05 FLAT ON HEAD ☐									
Steel	Slotted Truss Head Sex Bolts—Female Barrels										
	Barrel	Barrel	Thread	Thread		Head		Order			
13/64 3/8 8-32 1/4 7/16 9/64 Brass Black Ox Z4560-BX	Diameter	Length	Size	Depth	Diameter	Height	Plating	Number			
13/64 3/8 8-32 1/4 7/16 9/64 Black Ox Z4560-BX	Steel—Various Platings										
Steel-Zinc Plated Material 13/64 3/8 8-32 1/4 7/16 9/64 Zinc Z4560-ZN 1/4 1/4 8-32 .200 3/8 1/8 Zinc Z4505 1/4 1/2 8-32 1/4 3/8 1/8 Zinc Z4505 1/4 3/4 8-32 1/2 3/8 1/8 Zinc Z4510 1/4 1 8-32 1/2 3/8 1/8 Zinc Z4510 1/4 1 8-32 1/2 3/8 1/8 Zinc Z4520 Z4520 Z4516 Z4520 Z45	13/64	3/8	8-32		7/16	9/64	Brass	Z4560-BR			
13/64 3/8 8-32 1/4 7/16 9/64 Zinc Z4560-ZN 1/4	13/64	3/8	8-32	1/4	7/16	9/64	Black Ox	Z4560-BX			
1/4 1/4 8-32 .200 3/8 1/8 Zinc Z4500 1/4 1/2 8-32 1/4 3/8 1/8 Zinc Z4505 1/4 3/4 8-32 1/2 3/8 1/8 Zinc Z4510 1/4 1 8-32 1/2 3/8 1/8 Zinc Z4520 5/16 5/8 1/4-20 1/2 1/2 9/64 Zinc Z4520 5/16 3/4 10-32 1/2 7/16 9/64 Zinc Z4535 3/8 3/4 1/4-20 1/2 9/16 5/32 Zinc Z4541 3/8 1 1/4-20 1/2 9/16 5/32 Zinc Z4542 3/8 1 1/4-20 3/2 9/16 5/32 Zinc Z4542 3/8 1 1/4-20 3/2 9/16 5/32 Zinc Z4542 3/8 1 9/16 5/32 Zinc											
1/4	13/64	3/8	8-32	1/4	7/16	9/64	Zinc	Z4560-ZN			
1/4	1/4	1/4	0 22	200	2/0	1/0	Zino	74500			
1/4 3/4 8-32 1/2 3/8 1/8 Zinc Z4510 1/4 1 8-32 1/2 3/8 1/8 Zinc Z4520 5/16 5/8 1/4-20 1/2 1/2 9/64 Zinc Z4552 5/16 3/4 10-32 1/2 7/16 9/64 Zinc Z4535 3/8 3/4 1/4-20 1/2 9/16 5/32 Zinc Z4541 3/8 1 1/4-20 1/2 9/16 5/32 Zinc Z4542 3/8 1-9/16 1/4-20 3/4 9/16 3/16 Zinc Z4542 3/8 1/4 1/4 8-32	1										
1/4	1										
5/16 5/8 1/4-20 1/2 1/2 9/64 Zinc Z4552 5/16 3/4 10-32 1/2 7/16 9/64 Zinc Z4535 3/8 3/4 1/4-20 1/2 9/16 5/32 Zinc Z4541 3/8 1 1/4-20 3/4 9/16 5/32 Zinc Z4542 3/8 1-9/16 1/4-20 3/4 9/16 5/32 Zinc Z4542 3/8 1-9/16 1/4-20 3/4 9/16 5/32 Zinc Z4570 Brass Material 1/4 1/4 8-32 200 3/8 1/8 Plain Z4605 1/4 1/4 8-32 200 3/8 1/8 Plain Z4610 1/4 1/2 8-32 1/2 3/8 1/8 Chrome Z4610 1/4 1/3 3/4 8-32 1/2 3/8 1/8 Chrome Z4625											
5/16 3/4 10-32 1/2 7/16 9/64 Zinc Z4535 3/8 3/4 1/4-20 1/2 9/16 5/32 Zinc Z4541 3/8 1 1/4-20 1/2 9/16 5/32 Zinc Z4542 3/8 1 1/4-20 3/4 9/16 3/16 Zinc Z4542 3/8 1 1/4-20 3/4 9/16 3/16 Zinc Z4542 3/8 1 1/9/16 1/4-20 3/4 9/16 3/16 Zinc Z4570 Brass Material Brass Material Brass Material Brass Material Brass Material I/4 1/4 8-32 200 3/8 1/8 Chrome Z4600 24600 1/4 1/4 3/4 8-32 1/2 3/8 1/8 Chrome Z4625 1/4 1/4 1 8-32 1/2 3/8											
3/8	1										
3/8	5/16	3/4	10-32	1/2	7/16	9/64	Zinc	Z4535			
3/8	3/8	3/4	1/4-20	1/2	9/16	5/32	Zinc	74541			
3/8											
Brass Material	1										
1/4 1/4 8-32 .200 3/8 1/8 Plain Z4605 1/4 1/2 8-32 1/4 3/8 1/8 Chrome Z4610 1/4 1/2 8-32 1/4 3/8 1/8 Plain Z4615 1/4 3/4 8-32 1/2 3/8 1/8 Chrome Z4620 1/4 3/4 8-32 1/2 3/8 1/8 Chrome Z4625 1/4 1 8-32 1/2 3/8 1/8 Plain Z4630 1/4 1 8-32 1/2 3/8 1/8 Plain Z4630 1/4 1 8-32 1/2 3/8 1/8 Plain Z4635 5/16 1/2 10-32 1/4 7/16 9/64 Chrome Z4645 5/16 1/2 10-32 1/2 7/16 9/64 None Z4705 5/16 3/4 10-32 1/2 7/16											
1/4 1/4 8-32 .200 3/8 1/8 Plain Z4605 1/4 1/2 8-32 1/4 3/8 1/8 Chrome Z4610 1/4 1/2 8-32 1/4 3/8 1/8 Plain Z4615 1/4 3/4 8-32 1/2 3/8 1/8 Chrome Z4620 1/4 3/4 8-32 1/2 3/8 1/8 Chrome Z4625 1/4 1 8-32 1/2 3/8 1/8 Plain Z4630 1/4 1 8-32 1/2 3/8 1/8 Plain Z4630 1/4 1 8-32 1/2 3/8 1/8 Plain Z4635 5/16 1/2 10-32 1/4 7/16 9/64 Chrome Z4645 5/16 1/2 10-32 1/2 7/16 9/64 None Z4705 5/16 3/4 10-32 1/2 7/16	1/4	1/4	8-32	.200	3/8	1/8	Chrome	Z4600			
1/4 1/2 8-32 1/4 3/8 1/8 Plain Z4615 1/4 3/4 8-32 1/2 3/8 1/8 Chrome Z4620 1/4 3/4 8-32 1/2 3/8 1/8 Plain Z4625 1/4 1 8-32 1/2 3/8 1/8 Chrome Z4630 1/4 1 8-32 1/2 3/8 1/8 Chrome Z4630 1/4 1 8-32 1/2 3/8 1/8 Plain Z4635 5/16 1/2 10-32 1/4 7/16 9/64 Chrome Z4645 5/16 3/4 10-32 1/2 7/16 9/64 Chrome Z4655 Stainless Steel Material 1/4 1/4 8-32 1/2 7/16 9/64 None Z4700 1/4 1/4 8-32 1/2 3/8 1/8 None Z4705 1/4 1/	1			.200							
1/4 3/4 8-32 1/2 3/8 1/8 Chrome Z4620 1/4 3/4 8-32 1/2 3/8 1/8 Plain Z4625 1/4 1 8-32 1/2 3/8 1/8 Chrome Z4630 1/4 1 8-32 1/2 3/8 1/8 Plain Z4630 1/4 1 8-32 1/2 3/8 1/8 Plain Z4630 5/16 1/2 10-32 1/4 7/16 9/64 Chrome Z4645 5/16 1/2 10-32 1/2 7/16 9/64 None Z4650 5/16 3/4 10-32 1/2 7/16 9/64 None Z4655 Stainless Steel Material 1/4 1/4 8-32 200 3/8 1/8 None Z4700 1/4 1/2 8-32 1/2 3/8 1/8 None Z4710 1/4 1/2<	1/4						Chrome	Z4610			
1/4 3/4 8-32 1/2 3/8 1/8 Plain Chrome Z4625 1/4 1 8-32 1/2 3/8 1/8 Chrome Z4630 1/4 1 8-32 1/2 3/8 1/8 Plain Z4630 5/16 1/2 10-32 1/4 7/16 9/64 Chrome Z4640 5/16 1/2 10-32 1/4 7/16 9/64 None Z4645 5/16 3/4 10-32 1/2 7/16 9/64 Chrome Z4650 5/16 3/4 10-32 1/2 7/16 9/64 None Z4655 Stainless Steel Material 1/4 1/4 8-32 200 3/8 1/8 None Z4700 1/4 1/2 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4710 1/4	1										
1/4 1 8-32 1/2 3/8 1/8 Chrome Z4630 1/4 1 8-32 1/2 3/8 1/8 Plain Z4635 5/16 1/2 10-32 1/4 7/16 9/64 Chrome Z4640 5/16 1/2 10-32 1/4 7/16 9/64 None Z4650 5/16 3/4 10-32 1/2 7/16 9/64 Chrome Z4650 5/16 3/4 10-32 1/2 7/16 9/64 None Z4655 Stainless Steel Material 1/4 1/4 8-32 200 3/8 1/8 None Z4700 1/4 1/2 8-32 1/4 3/8 1/8 None Z4705 1/4 3/4 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4720 5/16 1	1										
1/4 1 8-32 1/2 3/8 1/8 Plain Z4635 5/16 1/2 10-32 1/4 7/16 9/64 Chrome Z4640 5/16 1/2 10-32 1/4 7/16 9/64 None Z4650 5/16 3/4 10-32 1/2 7/16 9/64 Chrome Z4650 5/16 3/4 10-32 1/2 7/16 9/64 None Z4655 Stainless Steel Material 1/4 1/4 8-32 200 3/8 1/8 None Z4700 1/4 1/2 8-32 1/4 3/8 1/8 None Z4705 1/4 3/4 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4720 5/16 1/2	1										
5/16 1/2 10-32 1/4 7/16 9/64 Chrome Z4640 5/16 1/2 10-32 1/4 7/16 9/64 None Z4645 5/16 3/4 10-32 1/2 7/16 9/64 Chrome Z4650 5/16 3/4 10-32 1/2 7/16 9/64 None Z4655 Stainless Steel Material 1/4 1/4 8-32 200 3/8 1/8 None Z4700 1/4 1/2 8-32 1/4 3/8 1/8 None Z4705 1/4 3/4 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4710 5/16 1/2 10-32 1/4 7/16 9/64 None Z4720 5/16 <t< td=""><td>1</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>	1										
5/16 1/2 10-32 1/4 7/16 9/64 None Z4645 5/16 3/4 10-32 1/2 7/16 9/64 Chrome Z4650 Stainless Steel Material 1/4 1/4 8-32 1/2 3/8 1/8 None Z4700 1/4 1/2 8-32 1/4 3/8 1/8 None Z4705 1/4 3/4 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4715 5/16 1/2 10-32 1/4 7/16 9/64 None Z4720 5/16 3/4 10-32 1/2 7/16 9/64 None Z4725 3/8 1/2 1/4-20 1/4 9/16 5/32 None Z4730 3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4732 3/	"		0-32	1/2	3/0	170	i iaiii	24000			
5/16 3/4 10-32 1/2 7/16 9/64 Chrome None Z4650 Stainless Steel Material 1/4 1/4 8-32 .200 3/8 1/8 None Z4705 1/4 1/2 8-32 1/4 3/8 1/8 None Z4705 1/4 3/4 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4715 5/16 1/2 10-32 1/4 7/16 9/64 None Z4720 5/16 3/4 10-32 1/2 7/16 9/64 None Z4725 3/8 1/2 1/4-20 1/4 9/16 5/32 None Z4730 3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 1 1/4-20 1/2 9/16 5/32 None Z4732 <t< th=""><th>5/16</th><th>1/2</th><th>10-32</th><th>1/4</th><th>7/16</th><th>9/64</th><th>Chrome</th><th>Z4640</th></t<>	5/16	1/2	10-32	1/4	7/16	9/64	Chrome	Z4640			
5/16 3/4 10-32 1/2 7/16 9/64 None Z4655 Stainless Steel Material 1/4 1/4 8-32 .200 3/8 1/8 None Z4700 1/4 1/2 8-32 1/4 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4715 5/16 1/2 10-32 1/4 7/16 9/64 None Z4720 5/16 3/4 10-32 1/2 7/16 9/64 None Z4725 3/8 1/2 1/4-20 1/4 9/16 5/32 None Z4730 3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 1 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32<	5/16	1/2	10-32		7/16	9/64	None	Z4645			
Stainless Steel Material	1										
1/4 1/4 8-32 .200 3/8 1/8 None Z4700 1/4 1/2 8-32 1/4 3/8 1/8 None Z4705 1/4 3/4 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4715 5/16 1/2 10-32 1/4 7/16 9/64 None Z4720 5/16 3/4 10-32 1/2 7/16 9/64 None Z4725 3/8 1/2 1/4-20 1/4 9/16 5/32 None Z4730 3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 3/4 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4	5/16	3/4						Z4655			
1/4 1/2 8-32 1/4 3/8 1/8 None Z4705 1/4 3/4 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4715 5/16 1/2 10-32 1/4 7/16 9/64 None Z4720 5/16 3/4 10-32 1/2 7/16 9/64 None Z4725 3/8 1/2 1/4-20 1/4 9/16 5/32 None Z4730 3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 3/4 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842											
1/4 3/4 8-32 1/2 3/8 1/8 None Z4710 1/4 1 8-32 1/2 3/8 1/8 None Z4715 5/16 1/2 10-32 1/4 7/16 9/64 None Z4720 5/16 3/4 10-32 1/2 7/16 9/64 None Z4725 3/8 1/2 1/4-20 1/4 9/16 5/32 None Z4730 3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 3/4 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842											
1/4 1 8-32 1/2 3/8 1/8 None Z4715 5/16 1/2 10-32 1/4 7/16 9/64 None Z4720 5/16 3/4 10-32 1/2 7/16 9/64 None Z4725 3/8 1/2 1/4-20 1/4 9/16 5/32 None Z4730 3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 3/4 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842	1										
5/16 1/2 10-32 1/4 7/16 9/64 None Z4720 5/16 3/4 10-32 1/2 7/16 9/64 None Z4725 3/8 1/2 1/4-20 1/4 9/16 5/32 None Z4730 3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 3/4 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842	1							_			
5/16 3/4 10-32 1/2 7/16 9/64 None Z4725 3/8 1/2 1/4-20 1/4 9/16 5/32 None Z4730 3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 3/4 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842	''-	'	0-02	1/2	5/0	1/0	INOILE	2-7/13			
5/16 3/4 10-32 1/2 7/16 9/64 None Z4725 3/8 1/2 1/4-20 1/4 9/16 5/32 None Z4730 3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 3/4 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842	5/16	1/2	10-32		7/16	9/64	None	Z4720			
3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 3/4 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842	5/16	3/4	10-32	1/2	7/16	9/64	None	Z4725			
3/8 19/32 1/4-20 1/2 9/16 5/32 None Z4731 3/8 3/4 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842	2/2	4.10	4/4.00	4/4	0/40	E/00	NI	74700			
3/8 3/4 1/4-20 1/2 9/16 5/32 None Z4732 3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842	1										
3/8 1 1/4-20 1/2 9/16 5/32 None Z4734 Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842											
Aluminum Material 3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842											
3/8 1/4 1/4-20 3/16 9/16 1/8 None Z4842		·									
	3/8	1/4	1/4-20				None	Z4842			
	3/8	7/8		9/16	9/16	1/8					









Small Quantities to Large Volume




Slotted Head Sex Bolts





Slotted Oval Head Sex Bolts—Female Barrels


Slotted Oval Head Sex Bolts are measured from over the head to the end of the barrel, and have a standard 82 degree countersunk head.



ER	
	1









Slotted Flat Head Sex Bolts—Female Barrels

Slotted Flat Head Sex Bolts are measured from over the head to the end of the barrel, and have a standard 82 degree countersunk head.









Thru

.715

.715




Steel Zinc, Steel Brass Plated, & Stainless Steel

3/4

.425

For hinge installations — available with slot for ease of installation, or without any slot for security installations. Used on Full Surface, Half Surface and Half Mortise Hinges, Prison Hinges and Heavy duty Institutional Hinges. Also used for installing door closers, panic bars, exit devices, kick plates, push plates, and all types of surface mounted door hardware.

5/16-18





Grommet Nuts									
Barrel Diameter	Barrel Length	Thread Size	Thread Depth	Head Diameter	Material	Slotted Order Number	No Slot Order Number	Open Head Fully Threaded Order Number	
5/16"	1/2"	10-32	1/4"	7/16"	Steel Zinc	Z4530	Z4521	Z4750	
5/16	1/2	12-24	1/4	7/16	Steel Zinc	Z4511	Z4522	Z4751	
3/8	1/2	1/4-20	1/4	9/16	Steel Zinc	Z4540	Z4523	Z4752	
1/2	1/2	3/8-16	1/4	3/4	Steel Zinc	Z4512	Z4524	Z4753	
5/16	1/2	10-32	1/4	7/16	Steel Brass Plated	Z4518	Z4525	Z4760	
5/16	1/2	12-24	1/4	7/16	Steel Brass Plated	Z4513	Z4526	Z4761	
3/8	1/2	1/4-20	1/4	9/16	Steel Brass Plated	Z4514	Z4527	Z4762	
1/2	1/2	3/8-16	1/4	3/4	Steel Brass Plated	Z4515	Z4528	Z4763	
5/16	1/2	10-32	1/4	7/16	Stainless Steel	Z4720	Z4529	Z4770	
5/16	1/2	12-24	1/4	7/16	Stainless Steel	Z4516	Z4531	Z4771	
3/8	1/2	1/4-20	1/4	9/16	Stainless Steel	Z4730	Z4532	Z4772	
1/2	1/2	3/8-16	1/4	3/4	Stainless Steel	Z4517	Z4533	Z4773	

Stainless


Stainless

Z5035

Z5040







Phillips, Hex Head, & T Head Sex Bolts










Phillips Truss Head Sex Bolts—Female Barrels


These Sex Bolts have Phillips Truss Heads, no knurl under the head, no mating screw. Available in Stainless Steel & Steel Chrome



	Phillips Truss Head Sex Bolts—Female Barrels									
Barrel Diameter	Barrel Length	Thread Size	Thread Depth	Head Diameter	Head Height	Material & Finish	Notes	Order Number		
3/16"	3/8"	6-32	1/4"	3/8"	3/32	Stainless	Serrations under head	Z4740		
7/32	3/8	8-32	1/4	7/16	3/32	Stainless	Serrations under head	Z4741		
1/4	1/2	10-24	3/8	9/16	9/64	Stainless	Serrations under head	Z4742		
1/4	1/2	10-24	3/8	13/32	1/8	Steel Chrome	Serrations under head	Z4850		
5/16	5/8	1/4-20	7/16	11/16	3/16	Stainless	Serrations under head	Z4743		
3/8	3/4	5/16-18	5/8	3/4	7/32	Stainless	Serrations under head	Z4744		
7/16	3/4	3/8-16	5/8	15/16	7/32	Stainless	Serrations under head	Z4745		

Hex Head Sex Bolts—Female Barrels

These Sex Bolts have Hex Heads, no knurl under the head, no mating screw. Available in Stainless Steel



Barrel Diameter Barrel Length Thread Size Thread Depth Across Height Height Order Number 5/16" 1/2" 10-24 5/16" 1/2" 3/16" Z4180-SS 5/16" 3/4 10-24 3/8 1/2 3/16 Z4181-SS 5/16" 1 10-24 3/8 1/2 3/16 Z4182-SS 3/8" 1/2 1/4-20 5/16" 5/8 13/64 Z4185-SS
5/16" 1/2" 10-24 5/16" 1/2" 3/16" Z4180-SS 5/16" 3/4 10-24 3/8 1/2 3/16 Z4181-SS 5/16" 1 10-24 3/8 1/2 3/16 Z4182-SS
5/16" 3/4 10-24 3/8 1/2 3/16 Z4181-SS 5/16" 1 10-24 3/8 1/2 3/16 Z4182-SS
5/16" 1 10-24 3/8 1/2 3/16 Z4182-SS
3/8" 1/2 1/4-20 5/16" 5/8 13/64 Z4185-SS
3/8" 3/4 1/4-20 3/8 5/8 13/64 Z4186-SS
3/8" 1 1/4-20 3/8 5/8 13/64 Z4187-SS
1/2" 1/2 3/8-16 5/16" 3/4 1/4 Z4190-SS
1/2" 3/4 3/8-16 3/8 3/4 1/4 Z4191-SS
1/2" 1 3/8-16 3/8 3/4 1/4 Z4192-SS




T Head Aluminum Sex Bolts/Binding Posts—Female Barrels

Special "T Slot" style head is used in commercial railing systems.



SPECIAL ORDERS AVAILABLE— Small Quantities to Large Volume








Connector Bolts & Nuts








Connector Nuts and Bolts are used for joining any two parts or pieces together, with a finished appearance. Most commonly used to join panels together, such as cabinets, book cases, and other furniture fixtures. The hex drive allows maximum leverage and force to be applied to the connection. These fasteners have a low profile and beveled edges on the exposed head, presenting a decorative and finished look.



Available in Plain Steel, or with the following finishes: Black Oxide, Bronze, Nickel, Brass, or Zinc

Connector Bolts (No Shoulder)								STEEL		
	L Length	L1 Thread	D Shank	Hex	Grip Ran	ige (MM)			Order	
Thread	Under Head	Length	Diameter	Drive	12MM Nut	17MM Nut	Material	Finish	Number *	
	20MM (.787")	17MM (.669")	5.4MM (.213")	4MM (.157")	21–25	21–30	Steel	Plain	Z4478-A	
	23MM (.906")	13MM (.512")	5.4MM (.213")	4MM (.157")	24–28	24-33	Steel	Plain	Z4479-A	
1/4-20	25MM (.984")	22MM (.866")	5.4MM (.213")	4MM (.157")	26-30	26-35	Steel	Plain	Z4480-A	
	30MM (1.181")	20MM (.787")	5.4MM (.213")	4MM (.157")	31–35	31–40	Steel	Plain	Z4481-A	
	35MM (1.378")	30MM (1.181")	5.4MM (.213")	4MM (.157")	36–40	36-45	Steel	Plain	Z4482-A	
									•	
	40MM (1.575")	30MM (1.181")	5.4MM (.213")	4MM (.157")	41–45	41–50	Steel	Plain	Z4483-A	
	45MM (1.772")	30MM (1.181")	5.4MM (.213")	4MM (.157")	46–50	46–55	Steel	Plain	Z4484-A	
1/4-20	50MM (1.969")	30MM (1.181")	5.4MM (.213")	4MM (.157")	51–55	51–60	Steel	Plain	Z4485-A	
	60MM (2.362")	40MM (1.575")	5.4MM (.213")	4MM (.157")	61–65	61–70	Steel	Plain	Z4486-A	
	70MM (2.756")	40MM (1.575")	5.4MM (.213")	4MM (.157")	71–75	71–80	Steel	Plain	Z4487-A	
		•			•					
	80MM (3.150")	40MM (1.575")	5.4MM (.213")	4MM (.157")	81–85	81–90	Steel	Plain	Z4488-A	
	90MM (3.543")	40MM (1.575")	5.4MM (.213")	4MM (.157")	91–95	91–100	Steel	Plain	Z4489-A	
1/4-20	100MM (3.937")	40MM (1.575")	5.4MM (.213")	4MM (.157")	101–105	101–110	Steel	Plain	Z4490-A	
	110MM (4.331")	40MM (1.575")	5.4MM (.213")	4MM (.157")	111–115	111–120	Steel	Plain	Z4491-A	
	120MM (4.724")	40MM (1.575")	5.4MM (.213")	4MM (.157")	121-125	121-130	Steel	Plain	Z4492-A	
	40MM (1.575")	30MM (1.181")	7MM (.276")	5MM (.197")	N/A	41–50	Steel	Plain	Z4493-A	
	50MM (1.969")	30MM (1.181")	7MM (.276")	5MM (.197")	N/A	51–60	Steel	Plain	Z4494-A	
5/16-18	60MM (2.362")	40MM (1.575")	7MM (.276")	5MM (.197")	N/A	61–70	Steel	Plain	Z4495-A	
J/ 10-10	70MM (2.756")	40MM (1.575")	7MM (.276")	5MM (.197")	N/A	71–80	Steel	Plain	Z4496-A	
	80MM (3.150")	40MM (1.575")	7MM (.276")	5MM (.197")	N/A	81–90	Steel	Plain	Z4497-A	
	100MM (3.937")	40MM (1.575")	7MM (.276")	5MM (.197")	N/A	101–110	Steel	Plain	Z4498-A	


Steel Connector Bolts (With Shoulder)



	Connector Bolts (With Shoulder)								STEEL		
Thread	L Length Under Head	L1 Thread Length	L2 Shoulder Length	Hex Drive	Grip Rar 12MM Nut	nge (MM) 17MM Nut	Material	Finish	Order Number *		
1/4-20	23MM (.906")	13MM (.512")	10MM (.394")	5MM (.197")	24–28	24–33	Steel	Plain	Z4467-A		
	30MM (1.181")	20MM (.787")	10MM (.394")	5MM (.197")	31–35	31–40	Steel	Plain	Z4468-A		
	35MM (1.378")	25MM (.984")	10MM (.394")	5MM (.197")	36–40	36–45	Steel	Plain	Z4469-A		
	40MM (1.575")	30MM (1.181")	10MM (.394")	5MM (.197")	41–45	41–50	Steel	Plain	Z4470-A		
	45MM (1.772")	35MM (1.378")	10MM (.394")	5MM (.197")	46–50	46–55	Steel	Plain	Z4471-A		
1/4-20	50MM (1.969")	40MM (1.575")	18MM (.709")	5MM (.197")	51–55	51–60	Steel	Plain	Z4472-A		
	60MM (2.362")	35MM (1.378")	18MM (.709")	5MM (.197")	61–65	61–70	Steel	Plain	Z4473-A		
	70MM (2.756")	35MM (1.378")	18MM (.709")	5MM (.197")	71–75	71–80	Steel	Plain	Z4474-A		
	80MM (3.150")	35MM (1.378")	18MM (.709")	5MM (.197")	81–85	81–90	Steel	Plain	Z4475-A		
	90MM (3.543")	35MM (1.378")	18MM (.709")	5MM (.197")	91–95	91–100	Steel	Plain	Z4476-A		
	100MM (3.937")	35MM (1.378")	18MM (.709")	5MM (.197")	101–105	101–110	Steel	Plain	Z4477-A		

Steel Connector Nuts

Available in Plain Steel, or with the following finishes: Black Oxide, Bronze, Nickel, Brass, or Zinc



	Co	STI	EEL			
	L	L1	D3			
	Barrel	Thread	Barrel			Order
Thread	Length	Depth	Diameter	Material	Finish	Number
1/4-20	12MM (.472")	8MM (.315")	9MM (.354")	Steel	Plain	Z4452-A
1/4-20	17MM (.669")	13MM (.512")	9MM (.354")	Steel	Plain	Z4456-A
5/16-18	17MM (.669")	13MM (.512")	11MM (.433")	Steel	Plain	Z4460-A



2005	ENHALL							
	PLAIN STEEL							
ODE FOR A FINISH OTHER THAN								
UMBER	S WITH THE FOLLOWING							
* REPL	ACE "A" IN THE ORDER							

CODE	FINISH
BX	BLACK OXIDE PLATED
BZ	BRONZE PLATED
NI	NICKEL PLATED
BR	BRASS PLATED
ZN	ZINC PLATED



* REPLACE "A" IN THE ORDER NUMBERS WITH THE FOLLOWING CODE FOR A FINISH OTHER THAN PLAIN STEEL

CODE	FINISH
BX	BLACK OXIDE PLATED
BZ	BRONZE PLATED
NI	NICKEL PLATED
BR	BRASS PLATED
ZN	ZINC PLATED



* REPLACE "A" IN THE ORDER NUMBERS WITH THE FOLLOWING CODE FOR A FINISH OTHER THAN PLAIN STEEL

CODE	FINIOR
BX	BLACK OXIDE PLATED
BZ	BRONZE PLATED
NI	NICKEL PLATED
BR	BRASS PLATED
ZN	ZINC PLATED



Accurate

Manufactured Phone: 317-472-9000 • FAX: 317-472-9010 • email: sales@ampg.com • www.ampg.com



Hex Head & Slotted Shoulder Bolts








Hex Head Shoulder Bolts

- available in 3/8" and 1/2" Shoulder Diameters and 12 Different Lengths
- available in Steel Zinc and 18-8 Stainless Steel

Also known as Lawn Mower Bolts for their use as the wheel axle for lawnmowers. These can be used for the same basic applications as our Stripper Bolts, but with a hex head for wrenching.



	Hex Head Shoulder Bolts—Steel & Stainless Steel									
Shoulder	Shoulder	Hex Head	Head	Thread	Thread	Overall	Order	Numbers		
Length	Diameter	Diameter	Height	Size	Length	Length	Steel	Stainless		
1-5/16"	.371–.375"	.621–.625"	.158–.188"	1/4-20 2A	3/4"	2-5/16"	Z0800	Z0800SS		
1-3/8	.371375	.621625	.158188	1/4-20 2A	3/4	2-3/8"	Z0801	Z0801SS		
1-7/16	.371375	.621625	.158188	1/4-20 2A	3/4	2-7/16"	Z0802	Z0802SS		
1-1/2	.371–.375	.621–.625	.158–.188	1/4-20 2A	3/4	2-1/2"	Z0803	Z0803SS		
1-9/16	.371–.375	.621–.625	.158–.188	1/4-20 2A	3/4	2-9/16"	Z0804	Z0804SS		
1-5/8	.371375	.621625	.158–.188	1/4-20 2A	3/4	2-5/8"	Z0805	Z0805SS		
1-3/4	.371–.375	.621–.625	.158–.188	1/4-20 2A	3/4	2-3/4"	Z0806	Z0806SS		
1-7/8	.371–.375	.621–.625	.158–.188	1/4-20 2A	3/4	2-7/8"	Z0807	Z0807SS		
2	.371–.375	.621–.625	.158–.188	1/4-20 2A	3/4	3"	Z0808	Z0808SS		
2-1/8	.371375	.621625	.158188	1/4-20 2A	3/4	3-1/8"	Z0809	Z0809SS		
2-1/4	.371375	.621625	.158188	1/4-20 2A	3/4	3-1/4"	Z0810	Z0810SS		
2-1/2	.371–.375	.621–.625	.158–.188	1/4-20 2A	3/4	3-1/2"	Z0811	Z0811SS		
1-5/16"	.496–.500"	.736–.750"	.220–.250"	3/8-16 2A	3/4"	2-5/16"	Z0710	Z0710SS		
1-3/8	.496–.500	.736–.750	.220–.250	3/8-16 2A	3/4	2-3/8"	Z0711	Z0711SS		
1-7/16	.496–.500	.736–.750	.220–.250	3/8-16 2A	3/4	2-7/16"	Z0712	Z0712SS		
1-1/2	.496–.500	.736–.750	.220–.250	3/8-16 2A	3/4	2-1/2"	Z0713	Z0713SS		
1-9/16	.496500	.736750	.220250	3/8-16 2A	3/4	2-9/16"	Z0714	Z0714SS		
1-5/8	.496500	.736–.750	.220250	3/8-16 2A	3/4	2-5/8"	Z0715	Z0715SS		
1-3/4	.496–.500	.736–.750	.220–.250	3/8-16 2A	3/4	2-3/4"	Z0716	Z0716SS		
1-7/8	.496–.500	.736–.750	.220–.250	3/8-16 2A	3/4	2-7/8"	Z0717	Z0717SS		
2	.496500	.736750	.220250	3/8-16 2A	3/4	3"	Z0718	Z0718SS		
2-1/8	.496500	.736–.750	.220250	3/8-16 2A	3/4	3-1/8"	Z0719	Z0719SS		
2-1/4	.496–.500	.736–.750	.220–.250	3/8-16 2A	3/4	3-1/4"	Z0721	Z0721SS		
2-1/2	.496–.500	.736–.750	.220250	3/8-16 2A	3/4	3-1/2"	Z0725	Z0725SS		



SPECIAL ORDERS AVAILABLE— Small Quantities

to Large Volume



Slotted Head Shoulder Bolts—18-8 Stainless Steel

Slotted Head Stripper Bolts—18-8 Stainless Steel									
Shoulder	Shoulder	Class 3A	Head	Head					
Diameter	Length	Threads	Dia.	Height	Order Number				
1/4"	3/8"	10-32	3/8	3/16	STR50010F06				
1/4"	1-1/2	10-32	3/8	3/16	STR50010F24				

^{*} Other sizes also available—Call us for more info





Precision Shoulder Screw





Brass Precision Shoulder Screws

These small size Shoulder Screws have a much tighter shoulder diameter tolerance of plus nothing to minus .001 inch, as opposed to standard Shoulder Screws that have a minus .004 to minus .002 diameter call out. The length of the shoulder is also held to plus .002 minus nothing, while the standard line carries a plus or minus .005" tolerance.

Precision Shoulder Screws—Hex Drive BRASS									
				;w5—i				Ь	
Shoulder	Shoulder	Shoulder Dia.	Shoulder Length		Thread	Thread	Hex Drive		Order
Diameter	Length	Tolerance	Tolerance	Threads	Length	Class	Size	Material	Number
	1/8	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	5/64	Brass	STR55018C02
	3/16	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	5/64	Brass	STR55018C03
1/8	1/4	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	5/64	Brass	STR55018C04
1/0	5/16	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	5/64	Brass	STR55018C05
	3/8	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	5/64	Brass	STR55018C06
	1/2	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	5/64	Brass	STR55018C08
	1/8	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	3/32	Brass	STR55031C02
	3/16	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	3/32	Brass	STR55031C03
	1/4	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	3/32	Brass	STR55031C04
	5/16	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	3/32	Brass	STR55031C05
3/16	3/8	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	3/32	Brass	STR55031C06
	1/2	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	3/32	Brass	STR55031C08
	5/8	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	3/32	Brass	STR55031C10
	3/4	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	3/32	Brass	STR55031C12
	1	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	3/32	Brass	STR55031C16
	1/8	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	1/8	Brass	STR55014F02
	3/16	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	1/8	Brass	STR55014F03
	1/4	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	1/8	Brass	STR55014F04
	5/16	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	1/8	Brass	STR55014F05
1/4	3/8	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	1/8	Brass	STR55014F06
	1/2	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	1/8	Brass	STR55014F08
	5/8	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	1/8	Brass	STR55014F10
	3/4	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	1/8	Brass	STR55014F12
	1	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	1/8	Brass	STR55014F16



These small size Shoulder Screws have a much tighter shoulder diameter tolerance of plus nothing to minus .001 inch, as opposed to standard Shoulder Screws that have a minus .004 to minus .002 diameter call out. The length of the shoulder is also held to plus .002 minus nothing, while the standard line carries a plus or minus .005" tolerance. Manufactured with a 6 lobe drive which anchors the screw to the wrench more firmly than the standard hex drive. This is helpful when assembling these small screws in tight places.


	Precision Shoulder Screws—Star Drive 303 St/St											
Shoulder	Shoulder	Shoulder Dia.	Shoulder Length		Thread	Thread	Star Drive		Order			
Diameter	Length	Tolerance	Tolerance	Threads	Length	Class	Size	Material	Number			
	1/8	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	T10	303 St/St	STR55218C02			
	3/16	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	T10	303 St/St	STR55218C03			
1/8	1/4	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	T10	303 St/St	STR55218C04			
1/0	5/16	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	T10	303 St/St	STR55218C05			
	3/8	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	T10	303 St/St	STR55218C06			
	1/2	+0 / -0.001"	+.002" / -0	4-40	5/32	2A	T10	303 St/St	STR55218C08			
	1/8	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	T25	303 St/St	STR55231C02			
	3/16	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	T25	303 St/St	STR55231C03			
	1/4	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	T25	303 St/St	STR55231C04			
	5/16	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	T25	303 St/St	STR55231C05			
3/16	3/8	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	T25	303 St/St	STR55231C06			
	1/2	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	T25	303 St/St	STR55231C08			
	5/8	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	T25	303 St/St	STR55231C10			
	3/4	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	T25	303 St/St	STR55231C12			
	1	+0 / -0.001"	+.002" / -0	8-32	3/16	2A	T25	303 St/St	STR55231C16			
	1/8	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	T30	303 St/St	STR55214F02			
	3/16	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	T30	303 St/St	STR55214F03			
	1/4	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	T30	303 St/St	STR55214F04			
	5/16	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	T30	303 St/St	STR55214F05			
1/4	3/8	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	T30	303 St/St	STR55214F06			
	1/2	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	T30	303 St/St	STR55214F08			
	5/8	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	T30	303 St/St	STR55214F10			
	3/4	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	T30	303 St/St	STR55214F12			
	1	+0 / -0.001"	+.002" / -0	10-32	1/4	2A	T30	303 St/St	STR55214F16			

Lengthening and Shortening Shim Washers are also available. See Page 72

















Socket Head Shoulder Bolts (Stripper Bolts)






Stainless Steel Stripper Bolts

The smooth shoulder functions as a bearing surface, pin, slide, or as a spacer. Used in many applications, they can be locaters, axles, pivot points, and retainers.

Our quality manufactured 18-8 and 316 Stainless Steel Shoulder Screws meet or exceed ASME B18.3 (2002). Both 18-8 and 316 are corrosion resistant, but Type 316 offers better resistance from the added molybdenum, and is preferred for salt water marine applications and exposures to industrial chemicals. Type 18-8 Stainless offers slightly more strength than Type 316.







SOCKET HEAD SHOULDER BOLTS (STRIPPER BOLTS)—STAINLESS STEEL											
SHOULDER DIAMETER	SHOULDER LENGTH	SHOULDER LENGTH TOLERANCE	THREAD SIZE	THREAD LENGTH	THREAD CLASS	HEAD DIA.	HEAD HEIGHT	DRIVE TYPE	HEX DRIVE SIZE	TYPE 303 ST/ST ORDER NUMBER	TYPE 316 ST/ST ORDER NUMBER
	1/8"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C02	STR60218C02
	5/32"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C02.5	STR60218C02.5
	3/16"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C03	STR60218C03
	7/32"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C03.5	STR60218C03.5
	1/4"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C04	STR60218C04
	9/32"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C04.5	STR60218C04.5
0.125	5/16"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C05	STR60218C05
0.120	11/32"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C05.5	STR60218C05.5
	3/8"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C06	STR60218C06
	13/32"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C06.5	STR60218C06.5
	7/16"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C07	STR60218C07
	15/32"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C07.5	STR60218C07.5
	1/2"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C08	STR60218C08
	5/8"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C10	STR60218C10
TOLERANCE:	3/4"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C12	STR60218C12
002 TO	1"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C16	STR60218C16
-0.004	1-1/4"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C20	STR60218C20
	1-1/2"	+/-0.005	4-40	5/32"	3A	.235250	.115125	HEX	5/64"	STR60118C24	STR60218C24
	1/8"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C02	STR60253C02
	5/32"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C02.5	STR60253C02.5
	3/16"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C03	STR60253C03
	7/32"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C03.5	STR60253C03.5
	1/4"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C04	STR60253C04
0.156	9/32"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C04.5	STR60253C04.5
	5/16"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C05	STR60253C05
	11/32"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C05.5	STR60253C05.5
	3/8"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C06	STR60253C06
	13/32"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C06.5	STR60253C06.5
	7/16"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C07	STR60253C07
	15/32"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C07.5	STR60253C07.5
TOLERANCE:	1/2"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C08	STR60253C08
002 TO	5/8"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C10	STR60253C10
-0.004	3/4"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C12	STR60253C12
	1"	+/-0.005	6-32	3/16"	3A	.266281	.115125	HEX	3/32"	STR60153C16	STR60253C16



Lengthening and Shortening Shim Washers are also available. See Page 72






Socket Head Shoulder Bolts (Stripper Bolts) USASMADE



Stainless Steel Stripper Bolts (cont'd)





											Steel
	SO	CKET HEA	D SHO	ULDER	BOLTS	(STRIP	PER BOL	_TS)—	STAINI	LESS STEEL	
SHOULDER	SHOULDER	SHOULDER	THREAD	THREAD	TUDEAD		LIEAD	DRIVE	HEX	TYPE 303 ST/ST	TYPE 316 ST/ST
DIAMETER	LENGTH	LENGTH	SIZE	LENGTH	THREAD	HEAD DIA.	HEAD HEIGHT	TYPE	DRIVE	ORDER NUMBER	ORDER NUMBER
		TOLERANCE							SIZE		
	1/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C02	STR60231C02
	5/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C02.5	STR60231C02.5
	3/16"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C03	STR60231C03
	7/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C03.5	STR60231C03.5
	1/4"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C04	STR60231C04
	9/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C04.5	STR60231C04.5
	5/16"	+/-0.005	8-32	3/16"	3A 3A	.296312	.146156	HEX	3/32" 3/32"	STR60131C05 STR60131C05.5	STR60231C05 STR60231C05.5
0.187	11/32" 3/8"	+/-0.005 +/-0.005	8-32 8-32	3/16" 3/16"	3A 3A	.296312 .296312	.146156 .146156	HEX HEX	3/32"	STR60131C05.5	STR60231C05.5
0.107	13/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C06	STR60231C06
	7/16"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C06.5	STR60231C06.5
	15/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C07.5	STR60231C07.5
	1/2"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C07.5	STR60231C07.5
	5/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C10	STR60231C10
	3/4"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C12	STR60231C12
	7/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C14	STR60231C14
	1"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C16	STR60231C16
	1-1/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C18	STR60231C18
	1-1/4"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C20	STR60231C20
	1-3/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C22	STR60231C22
TOLERANCE:	1-1/2"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C24	STR60231C24
002 TO	1-5/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C26	STR60231C26
-0.004	1-3/4"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C28	STR60231C28
	2"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60131C32	STR60231C32
										•	•
	1/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C02	STR60273C02
	5/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C02.5	STR60273C02.5
	3/16"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C03	STR60273C03
	7/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C03.5	STR60273C03.5
	1/4"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C04	STR60273C04
	9/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C04.5	STR60273C04.5
	5/16"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C05	STR60273C05
	11/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C05.5	STR60273C05.5
	3/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C06	STR60273C06
0.218	13/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C06.5	STR60273C06.5
0.210	7/16"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C07	STR60273C07
	15/32"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C07.5	STR60273C07.5
	1/2"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C08	STR60273C08
	5/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C10	STR60273C10
	3/4"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C12	STR60273C12
	7/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C14	STR60273C14
	1"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C16	STR60273C16
	1-1/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C18	STR60273C18
	1-1/4"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C20	STR60273C20
	1-3/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C22	STR60273C22
TOLERANCE:	1-1/2"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C24	STR60273C24
002 TO	1-5/8"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C26	STR60273C26
-0.004	1-3/4"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C28	STR60273C28
	2"	+/-0.005	8-32	3/16"	3A	.296312	.146156	HEX	3/32"	STR60173C32	STR60273C32

Lengthening and Shortening Shim Washers are also available. See Page 72








Socket Head Shoulder Bolts (Stripper Bolts)





Stainless Steel Stripper Bolts (cont'd)

18-8 & Type 316 Stainless Steel



SOCKET HEAD SHOULDER BOLTS (STRIPPER BOLTS)—STAINLESS STEEL											
SHOULDER SHOULDER THREAD THREA											
SHOULDER DIAMETER	SHOULDER LENGTH	LENGTH TOLERANCE	THREAD SIZE	THREAD LENGTH	THREAD CLASS	HEAD DIA.	HEAD HEIGHT	DRIVE TYPE	DRIVE SIZE	TYPE 303 ST/ST ORDER NUMBER	TYPE 316 ST/ST ORDER NUMBER
	1/8"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C02	STR60214C02
	5/32"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C02.5	STR60214C02.5
	3/16"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C03	STR60214C03
	7/32"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C03.5	STR60214C03.5
	1/4"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C04	STR60214C04
	9/32"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C04.5	STR60214C04.
	5/16"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C05	STR60214C05
	11/32"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C05.5	STR60214C05.
	3/8"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C06	STR60214C06
	13/32"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C06.5	STR60214C06.
	7/16"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C07	STR60214C07
	15/32"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C07.5	STR60214C07.
0.25	1/2"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C08	STR60214C08
0.25	5/8"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C10	STR60214C10
	3/4"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8" 1/8"	STR60114C12	STR60214C12
	1"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX		STR60114C16	STR60214C16
	1-1/8"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C18	STR60214C18
	1-1/4"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C20	STR60214C20
	1-3/8"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C22	STR60214C22
	1-1/2"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C24	STR60214C24
	1-5/8"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C26	STR60214C26
	1-3/4"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C28	STR60214C28
	2"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C32	STR60214C32
	2-1/4"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C36	STR60214C36
	2-1/2"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C40	STR60214C40
	2-3/4"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C44	STR60214C44
	3"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C48	STR60214C48
OLERANCE:	3-1/2"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C56	STR60214C56
002 TO	4"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C64	STR60214C64
-0.004	4-1/2"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C72	STR60214C72
	5"	+/-0.005	10-24	3/8"	3A	.357375	.177188	HEX	1/8"	STR60114C80	STR60214C80
	1/4"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C04	STR60251C04
	5/16"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C05	STR60251C05
	3/8"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C06	STR60251C06
	1/2"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C08	STR60251C08
	5/8"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C10	STR60251C10
	3/4"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C12	STR60251C12
	7/8"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C12	STR60251C12
	1"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C14	STR60251C14
	1-1/4"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C10	STR60251C10
0.312	1-1/4"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C20 STR60151C24	STR60251C20
	1-3/4"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C24 STR60151C28	STR60251C24
	2"										
	2-1/4"	+/-0.005 +/-0.005	1/4-20 1/4-20	7/16" 7/16"	3A 3A	.419438 .419438	.209219 .209219	HEX	5/32" 5/32"	STR60151C32	STR60251C32
								HEX		STR60151C36	STR60251C36
	2-1/2"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C40	STR60251C40
	2-3/4"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C44	STR60251C44
	3"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C48	STR60251C48
	3-1/2"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C56	STR60251C56
0.5541105	4"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C64	STR60251C64
OLERANCE:	4-1/2"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C72	STR60251C72
002 TO	5"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C80	STR60251C80
-0.004	5-1/2"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C88	STR60251C88
	6"	+/-0.005	1/4-20	7/16"	3A	.419438	.209219	HEX	5/32"	STR60151C96	STR60251C96



Lengthening and Shortening Shim Washers are also available. See Page 72










Stainless Steel Stripper Bolts (cont'd)





Ste											
	soc	CKET HEA	D SHO	ULDER	BOLTS	(STRIPF	PER BOL	_TS)—	STAINI	LESS STEEL	
SHOULDER DIAMETER	SHOULDER LENGTH	SHOULDER LENGTH TOLERANCE	THREAD SIZE	THREAD LENGTH	THREAD CLASS	HEAD DIA.	HEAD HEIGHT	DRIVE TYPE	HEX DRIVE SIZE	TYPE 303 ST/ST ORDER NUMBER	TYPE 316 ST/S ORDER NUMBI
	1/4"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C04	STR60238C04
	3/8"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C06	STR60238C0
	1/2"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C08	STR60238C0
	5/8"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C10	STR60238C1
	3/4"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C12	STR60238C1
	1"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C16	STR60238C1
	1-1/4"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C20	STR60238C2
	1-1/2"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C24	STR60238C
	1-3/4"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C28	STR60238C
	2"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C32	STR60238C
0.275	2-1/4"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C36	STR60238C
0.375	2-1/2"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C40	STR60238C
	2-3/4"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C44	STR60238C
	3"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C48	STR60238C
	3-1/4"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C52	STR60238C
	3-1/2"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C56	STR60238C
	3-3/4"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C60	STR60238C
	4"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C64	STR60238C
	4-1/2"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C72	STR60238C
	5"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C80	STR60238C
	5-1/2"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C88	STR60238C
	6"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C96	STR60238C
LERANCE:	6-1/2"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C104	STR60238C1
002 TO	7"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C112	STR60238C1
-0.004	7-1/2"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C120	STR60238C1
	8"	+/-0.005	5/16-18	1/2"	3A	.543562	.240250	HEX	3/16"	STR60138C128	STR60238C1
	3/8"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C06	STR60212C
	1/2"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C08	STR60212C
	5/8"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C10	STR60212C
	3/4"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C12	STR60212C
	1"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C16	STR60212C
	1-1/4"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C20	STR60212C
	1-1/2"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C24	STR60212C
	1-3/4"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C28	STR60212C
	2"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C32	STR60212C
	2-1/4"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C36	STR60212C
	2-1/2"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C40	STR60212C
0.5	2-3/4"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C44	STR60212C
	3"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C48	STR60212C
	3-1/4"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C52	STR60212C
	3-1/2"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C56	STR60212C
	3-3/4"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C60	STR60212C
	4"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C64	STR60212C
	4-1/4"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C68	STR60212C
	4-1/2"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C72	STR60212C
	4-3/4"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C76	STR60212C
	5"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C80	STR60212C
	5-1/2"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C88	STR60212C
	6"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C96	STR60212C
LERANCE:	6-1/2"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C104	STR60212C1
002 TO	7"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C104	STR60212C1
-0.004	7-1/2"	+/-0.005	3/8-16	5/8"	3A	.729750	.302312	HEX	1/4"	STR60112C112	STR60212C1
-0.004											

Lengthening and Shortening Shim Washers are also available. See Page 72










Socket Head Shoulder Bolts (Stripper Bolts)







SOCKET HEAD SHOULDER BOLTS (STRIPPER BOLTS)—STAINLESS STEEL SHOULDER SHOULDER SHOULDER THREAD THREAD THREAD HEAD DRIVE TYPE 303 ST/ST TYPE 316 ST/ST LENGTH HEAD DIA. DRIVE ORDER NUMBER DIAMETER LENGTH SIZE LENGTH CLASS **HEIGHT** TYPE ORDER NUMBER TOLERANCE SIZE 1/2' +/-0.005 1/2-13 3/4" ЗА .853-.875 .365-.375 HEX 5/16' STR60158C08 STR60258C08 5/8' +/-0.005 3/4" ЗА .853-.875 .365-.375 HEX 5/16' STR60158C10 STR60258C10 1/2-13 3/4" +/-0.005 1/2-13 3/4" ЗА .853-.875 .365-.375 HEX 5/16" STR60158C12 STR60258C12 STR60158C16 STR60258C16 1" +/-0.005 1/2-13 3/4" 3A .853-.875 .365-.375 HEX 5/16' 1-1/4" +/-0.005 1/2-13 3/4" ЗА .853-.875 .365-.375 HEX 5/16' STR60158C20 STR60258C20 1-1/2" +/-0.005 1/2-13 ЗА .853-.875 .365-.375 HEX 5/16' STR60158C24 STR60258C24 +/-0.005 .365-.375 HEX STR60158C28 STR60258C28 1-3/4" 1/2-13 3/4" 3A .853-.875 5/16' +/-0.005 1/2-13 3/4" 3A .853-.875 365-375 HFX 5/16' STR60158C32 STR60258C32 2-1/4" +/-0.005 1/2-13 3/4" .853-.875 .365-.375 HEX 5/16' STR60158C36 STR60258C36 2-1/2" +/-0.005 3/4" ЗА .853-.875 .365-.375 HEX 5/16' STR60158C40 STR60258C40 1/2-13 2-3/4" +/-0.005 1/2-13 3/4" 3A .853-.875 .365-.375 HEX 5/16' STR60158C44 STR60258C44 0.625 +/-0.005 1/2-13 3/4" .853-.875 .365-.375 HEX 5/16' STR60158C48 STR60258C48 +/-0.005 3-1/4" 1/2-13 3/4" ЗА .853-.875 .365-.375 HFX 5/16 STR60158C52 STR60258C52 3-1/2" +/-0.005 1/2-13 3/4" 3A 853-875 365-375 HFX 5/16' STR60158C56 STR60258C56 +/-0.005 .365-.375 STR60158C60 STR60258C60 3-3/4" 1/2-13 3/4" ЗА .853-.875 HEX 5/16" +/-0.005 1/2-13 3/4" ЗА .853-.875 .365-.375 HEX 5/16 STR60158C64 STR60258C64 4-1/4" +/-0.005 1/2-13 3/4" 3A 853-875 365-375 HFX 5/16' STR60158C68 STR60258C68 +/-0.005 .853-.875 .365-.375 STR60158C72 STR60258C72 4-1/2" 1/2-13 3/4" ЗА HEX 5/16' 4-3/4" +/-0.005 1/2-13 3/4" ЗА .853-.875 .365-.375 HEX 5/16' STR60158C76 STR60258C76 365-375 5" +/-0.005 1/2-13 3/4" 3A 853-875 HFX 5/16' STR60158C80 STR60258C80 5-1/2" +/-0.005 1/2-13 3/4" 3A .853-.875 .365-.375 HEX 5/16' STR60158C88 STR60258C88 +/-0.005 1/2-13 3/4" ЗА .853-.875 .365-.375 HEX 5/16' STR60158C96 STR60258C96 TOLERANCE 6-1/2" +/-0.005 3/4" 365-375 HFX 5/16' STR60158C104 1/2-13 3A 853-875 STR60258C104 -.002 TO 3/4" +/-0.005 1/2-13 ЗА .853-.875 .365-.375 HEX 5/16' STR60158C112 STR60258C112 -0 004 7-1/2" +/-0.005 1/2-13 3/4" ЗА .853-.875 .365-.375 HEX 5/16' STR60158C120 STR60258C120 +/-0.005 3/4" .365-.375 HEX 5/16' STR60158C128 STR60258C128 8" 1/2 - 133A .853-.875 1/2" +/-0.005 5/8-11 7/8" ЗА .977-1.00 .490-.500 HEX 3/8" STR60134C08 STR60234C08 5/8" +/-0.005 7/8" .977-1.00 .490-.500 HEX 3/8" STR60134C10 STR60234C10 5/8-11 ЗА 3/4" +/-0.005 5/8-11 7/8" ЗА 977-1 00 .490-.500 HEX 3/8" STR60134C12 STR60234C12 .490-.500 +/-0.005 5/8-11 7/8" ЗА .977-1.00 HEX 3/8" STR60134C16 STR60234C16 1-1/4" +/-0.005 5/8-11 7/8' .977-1.00 .490-.500 HEX 3/8" STR60134C20 STR60234C20 ЗА 1-1/2" +/-0.005 5/8-11 7/8" ЗА .977-1.00 .490-.500 HEX 3/8" STR60134C24 STR60234C24 1-3/4" +/-0.005 5/8-11 7/8" ЗА .977-1.00 .490-.500 HEX 3/8" STR60134C28 STR60234C28 +/-0.005 5/8-11 7/8' ЗА .977-1.00 .490-.500 HEX 3/8" STR60134C32 STR60234C32 2-1/4" HEX +/-0.005 5/8-11 7/8" 3A .977-1.00 .490-.500 3/8 STR60134C36 STR60234C36 2-1/2" +/-0.005 5/8-11 7/8" ЗА .977-1.00 .490-.500 HEX 3/8" STR60134C40 STR60234C40 2-3/4" +/-0.005 5/8-11 7/8' ЗА .977-1.00 .490-.500 HEX 3/8" STR60134C44 STR60234C44 0.75 +/-0.005 ЗА .490-.500 HEX 3/8" STR60134C48 STR60234C48 3" 5/8-11 7/8" .977-1.00 3-1/4" +/-0 005 5/8-11 7/8' 3A .977-1.00 490-500 HFX 3/8" STR60134C52 STR60234C52 3-1/2" +/-0.005 5/8-11 7/8' .977-1.00 .490-.500 HEX STR60134C56 STR60234C56 3-3/4" ЗА HEX 3/8' STR60134C60 STR60234C60 +/-0.005 5/8-11 7/8' .977-1.00 .490-.500 4" +/-0.005 5/8-11 7/8" 3A 977-1 00 .490-.500 HFX 3/8" STR60134C64 STR60234C64 4-1/4" .490-.500 STR60134C68 +/-0.005 5/8-11 7/8' .977-1.00 HEX 3/8" STR60234C68 4-1/2" +/-0.005 5/8-11 7/8' ЗА .977-1.00 .490-.500 HEX 3/8 STR60134C72 STR60234C72 4-3/4" +/-0.005 5/8-11 7/8' 3A 977-1 00 490-500 HFX 3/8" STR60134C76 STR60234C76 +/-0.005 .977-1.00 .490-.500 STR60134C80 STR60234C80 5" 5/8-11 7/8' ЗА HEX 3/8" 5-1/2" +/-0.005 5/8-11 7/8' ЗА .977-1.00 .490-.500 HEX 3/8 STR60134C88 STR60234C88 6" +/-0.005 5/8-11 7/8' 3A 977-1 00 490-500 HFX 3/8" STR60134C96 STR60234C96 TOLERANCE 6-1/2" +/-0.005 5/8-11 7/8" ЗА .977-1.00 .490-.500 HEX 3/8" STR60134C104 STR60234C104 -.002 TO +/-0.005 5/8-11 7/8" ЗА .977-1.00 .490-.500 HEX STR60134C112 STR60234C112 -0.004 7-1/2" STR60134C120 +/-0.005 5/8-11 7/8' 3A 977-1 00 490-500 HFX 3/8" STR60234C120



Lengthening and Shortening Shim Washers are also available. See Page 72

.977-1.00

.490-.500

Chart continued on next page

STR60234C128



STR60134C128

5/8-11








Stainless Steel Stripper Bolts (cont'd)








SOCKET HEAD SHOULDER BOLTS (STRIPPER BOLTS)—STAINLESS STEEL

SHOULDER DIAMETER	SHOULDER LENGTH	SHOULDER LENGTH TOLERANCE	THREAD SIZE	THREAD LENGTH	THREAD CLASS	HEAD DIA.	HEAD HEIGHT	DRIVE TYPE	HEX DRIVE SIZE	TYPE 303 ST/ST ORDER NUMBER	TYPE 316 ST/ST ORDER NUMBER
	1"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C16	STR60201C16
	1-1/4"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C20	STR60201C20
	1-1/2"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C24	STR60201C24
	1-3/4"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C28	STR60201C28
	2"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C32	STR60201C32
	2-1/4"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C36	STR60201C36
	2-1/2"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C40	STR60201C40
1.00"	2-3/4"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C44	STR60201C44
	3"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C48	STR60201C48
	3-1/2"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C56	STR60201C56
	4"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C64	STR60201C64
	4-1/2"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C72	STR60201C72
	5"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C80	STR60201C80
	5-1/2"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C88	STR60201C88
	6"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C96	STR60201C96
TOLERANCE:	6-1/2"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C104	STR60201C104
002 TO	7"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C112	STR60201C112
-0.004	7-1/2"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C120	STR60201C120
	8"	+/-0.005	3/4-10	1"	3A	1.287-1.312	.610625	HEX	1/2"	STR60101C128	STR60201C128

JUMBO Stainless Steel Stripper Bolts Only Available from Accurate!





JUMBO SOCKET HEAD SHOULDER BOLTS (STRIPPER BOLTS)—STAINLESS STEEL

						`			′		
SHOULDER DIAMETER	SHOULDER LENGTH	SHOULDER LENGTH TOLERANCE	THREAD SIZE	THREAD LENGTH	THREAD CLASS	HEAD DIA.	HEAD HEIGHT	DRIVE TYPE	HEX DRIVE SIZE	TYPE 303 ST/ST ORDER NUMBER	TYPE 316 ST/ST ORDER NUMBER
	1"	+/-0.005	7/8-9	1-1/8"	3A	1.723-1.750	.735750	HEX	5/8"	STR601012C16	STR602012C16
	1-1/4"	+/-0.005	7/8-9	1-1/8"	3A	1.723-1.750	.735750	HEX	5/8"	STR601012C20	STR602012C20
1.25"	1-1/2"	+/-0.005	7/8-9	1-1/8"	3A	1.723-1.750	.735750	HEX	5/8"	STR601012C24	STR602012C24
1.23	1-3/4"	+/-0.005	7/8-9	1-1/8"	3A	1.723-1.750	.735750	HEX	5/8"	STR601012C28	STR602012C28
	2"	+/-0.005	7/8-9	1-1/8"	3A	1.723-1.750	.735750	HEX	5/8"	STR601012C32	STR602012C32
	2-1/2"	+/-0.005	7/8-9	1-1/8"	3A	1.723-1.750	.735750	HEX	5/8"	STR601012C40	STR602012C40
TOLERANCE:	3"	+/-0.005	7/8-9	1-1/8"	3A	1.723-1.750	.735750	HEX	5/8"	STR601012C48	STR602012C48
002 TO	3-1/2"	+/-0.005	7/8-9	1-1/8"	3A	1.723-1.750	.735750	HEX	5/8"	STR601012C56	STR602012C56
-0.004	4"	+/-0.005	7/8-9	1-1/8"	3A	1.723-1.750	.735750	HEX	5/8"	STR601012C64	STR602012C64
	1"	+/-0.005	1-1/8-7	1-1/2"	3A	2.095-2.125	.980-1"	HEX	7/8"	STR601015C16	STR602015C16
1.5"	1-1/4"	+/-0.005	1-1/8-7	1-1/2"	3A	2.095-2.125	.980-1"	HEX	7/8"	STR601015C20	STR602015C20
1.5	1-1/2"	+/-0.005	1-1/8-7	1-1/2"	3A	2.095-2.125	.980-1"	HEX	7/8"	STR601015C24	STR602015C24
	1-3/4"	+/-0.005	1-1/8-7	1-1/2"	3A	2.095-2.125	.980-1"	HEX	7/8"	STR601015C28	STR602015C28
TOLERANCE:	2"	+/-0.005	1-1/8-7	1-1/2"	3A	2.095-2.125	.980-1"	HEX	7/8"	STR601015C32	STR602015C32
002 TO	2-1/2"	+/-0.005	1-1/8-7	1-1/2"	3A	2.095-2.125	.980-1"	HEX	7/8"	STR601015C40	STR602015C40
-0.004	3"	+/-0.005	1-1/8-7	1-1/2"	3A	2.095-2.125	.980-1"	HEX	7/8"	STR601015C48	STR602015C48

Lengthening and Shortening Shim Washers are also available. See Page 72



HESE BOLTS ARE ALL MADE IN








METRIC Socket Head Shoulder Bolts





Stainless Steel Stripper Bolts (METRIC)

Manufactured 100% in the USA to ISO 7379-1983 Specifications



	METRIC	SOCKET HE	AD SHO	DULDER	RBOLTS	S (STR	IPPER	BOLTS	S)—ST/	AINLESS STE	≣L.
SHOULDER DIAMETER	SHOULDER LENGTH	+.25MM/–0.00MM	THREAD SIZE	THREAD CLASS	THREAD LENGTH	HEAD DIA.	HEAD HEIGHT	DRIVE TYPE	HEX DRIVE SIZE	TYPE 303 ST/ST ORDER NUMBER	TYPE 316 ST/ST ORDER NUMBER
М3	4MM	+.25MM/-0.00MM	M2 X .4	5g6g		5MM	2MM	HEX	2MM	STR601M3X4	STR602M3X4
IVIO	5MM	+.25MM/-0.00MM	M2 X .4	5g6g		5MM	2MM	HEX	2MM	STR601M3X5	STR602M3X5
TOLERANCE:	6MM	+.25MM/-0.00MM	M2 X .4	5g6g		5MM	2MM	HEX	2MM	STR601M3X6	STR602M3X6
013MM TO	8MM	+.25MM/-0.00MM	M2 X .4	5g6g		5MM	2MM	HEX	2MM	STR601M3X8	STR602M3X8
-0.049MM	10MM	+.25MM/-0.00MM	M2 X .4	5g6g		5MM	2MM	HEX	2MM	STR601M3X10	STR602M3X10
N/ 4	4MM	+.25MM/-0.00MM	M3 X .5	5g6g		6MM	3MM	HEX	2MM	STR601M4X4	STR602M4X4
M4	5MM	+.25MM/-0.00MM	M3 X .5	5g6g		6MM	3MM	HEX	2MM	STR601M4X5	STR602M4X5
TOLERANCE:	6MM	+.25MM/-0.00MM	M3 X .5	5q6q		6MM	3MM	HEX	2MM	STR601M4X6	STR602M4X6
013MM TO	8MM	+.25MM/-0.00MM	M3 X .5	5g6g		6MM	3MM	HEX	2MM	STR601M4X8	STR602M4X8
-0.049MM	10MM	+.25MM/-0.00MM	M3 X .5	5g6g		6MM	3MM	HEX	2MM	STR601M4X10	STR602M4X10
845	10MM	+.25MM/–0.00MM	M4 X .7	5g6g		9MM	4MM	HEX	2.5MM	STR601M5X10	STR602M5X10
M5	12MM	+.25MM/–0.00MM	M4 X .7	5g6g		9MM	4MM	HEX	2.5MM	STR601M5X12	STR602M5X12
	16MM	+.25MM/–0.00MM	M4 X .7	5g6g		9MM	4MM	HEX	2.5MM	STR601M5X16	STR602M5X16
TOLERANCE:	20MM	+.25MM/-0.00MM	M4 X .7	5g6g		9MM	4MM	HEX	2.5MM	STR601M5X20	STR602M5X20
013MM TO	25MM	+.25MM/-0.00MM	M4 X .7	5g6g		9MM	4MM	HEX	2.5MM	STR601M5X25	STR602M5X25
-0.049MM	30MM	+.25MM/–0.00MM	M4 X .7	5g6g		9MM	4MM	HEX	2.5MM	STR601M5X30	STR602M5X30
	10MM	+.25MM/–0.00MM	M5 X .8	5g6g		10MM	4.5MM	HEX	3MM	STR601M6X10	STR602M6X10
	12MM	+.25MM/-0.00MM	M5 X .8	5g6g		10MM	4.5MM	HEX	3MM	STR601M6X12	STR602M6X12
М6	16MM	+.25MM/-0.00MM	M5 X .8	5g6g		10MM	4.5MM	HEX	3MM	STR601M6X16	STR602M6X16
	20MM	+.25MM/-0.00MM	M5 X .8	5g6g		10MM	4.5MM	HEX	3MM	STR601M6X20	STR602M6X20
	25MM	+.25MM/-0.00MM	M5 X .8	5g6g		10MM	4.5MM	HEX	3MM	STR601M6X25	STR602M6X25
TOLERANCE:	30MM	+.25MM/-0.00MM	M5 X .8	5g6g		10MM	4.5MM	HEX	3MM	STR601M6X30	STR602M6X30
013MM TO	40MM	+.25MM/-0.00MM	M5 X .8	5g6g		10MM	4.5MM	HEX	3MM	STR601M6X40	STR602M6X40
-0.049MM	50MM	+.25MM/-0.00MM	M5 X .8	5g6g		10MM	4.5MM	HEX	3MM	STR601M6X50	STR602M6X50
	12MM	+.25MM/-0.00MM	M6 X 1	5g6g		13MM	5.5MM	HEX	4MM	STR601M8X12	STR602M8X12
M8	16MM	+.25MM/-0.00MM	M6 X 1	5g6g		13MM	5.5MM	HEX	4MM	STR601M8X16	STR602M8X16
	20MM	+.25MM/-0.00MM	M6 X 1	5g6g		13MM	5.5MM	HEX	4MM	STR601M8X20	STR602M8X20
	25MM	+.25MM/-0.00MM	M6 X 1	5g6g		13MM	5.5MM	HEX	4MM	STR601M8X25	STR602M8X25
TOLERANCE:	30MM	+.25MM/-0.00MM	M6 X 1	5g6g		13MM	5.5MM	HEX	4MM	STR601M8X30	STR602M8X30
013MM TO	40MM	+.25MM/-0.00MM	M6 X 1	5g6g		13MM	5.5MM	HEX	4MM	STR601M8X40	STR602M8X40
-0.049MM	50MM	+.25MM/-0.00MM	M6 X 1	5g6g		13MM	5.5MM	HEX	4MM	STR601M8X50	STR602M8X50

Lengthening and Shortening Shim Washers are also available. See Page 72

Chart continued on next page

SPECIAL ORDERS
AVAILABLE—
Small Quantities
to Large Volume



THESE BOLTS ARE ALL MADE IN USA










METRIC Socket Head Shoulder Bolts

Stainless Steel Stripper Bolts (METRIC)

Manufactured 100% in the USA to ISO 7379-1983 Specifications



USAMADE



METRIC SOCKET HEAD SHOULDER BOLTS (STRIPPER BOLTS)—STAINLESS STEEL											
SHOULDER DIAMETER	SHOULDER LENGTH	SHOULDER LENGTH TOLERANCE	THREAD SIZE	THREAD CLASS	THREAD LENGTH	HEAD DIA.	HEAD HEIGHT	DRIVE TYPE	HEX DRIVE SIZE	TYPE 303 ST/ST ORDER NUMBER	TYPE 316 ST/ST ORDER NUMBER
	16MM	+.25MM/-0.00MM	M8 X 1	5g6g		16MM	7MM	HEX	5MM	STR601M10X16	STR602M10X16
	20MM	+.25MM/-0.00MM	M8 X 1	5g6g		16MM	7MM	HEX	5MM	STR601M10X20	STR602M10X20
M10	25MM	+.25MM/-0.00MM	M8 X 1	5g6g		16MM	7MM	HEX	5MM	STR601M10X25	STR602M10X25
	30MM	+.25MM/-0.00MM	M8 X 1	5g6g		16MM	7MM	HEX	5MM	STR601M10X30	STR602M10X30
	40MM	+.25MM/-0.00MM	M8 X 1	5g6g		16MM	7MM	HEX	5MM	STR601M10X40	STR602M10X40
TOLERANCE:	50MM	+.25MM/-0.00MM	M8 X 1	5g6g		16MM	7MM	HEX	5MM	STR601M10X50	STR602M10X50
013MM TO	60MM	+.25MM/-0.00MM	M8 X 1	5g6g		16MM	7MM	HEX	5MM	STR601M10X60	STR602M10X60
-0.049MM	70MM	+.25MM/-0.00MM	M8 X 1	5g6g		16MM	7MM	HEX	5MM	STR601M10X70	STR602M10X70
	16MM	+.25MM/-0.00MM	M10 X 1.5	5g6g		18MM	9MM	HEX	6MM	STR601M12X16	STR602M12X16
	20MM	+.25MM/-0.00MM	M10 X 1.5	5g6g		18MM	9MM	HEX	6MM	STR601M12X20	STR602M12X20
M12	25MM	+.25MM/-0.00MM	M10 X 1.5	5g6g		18MM	9MM	HEX	6MM	STR601M12X25	STR602M12X25
	30MM	+.25MM/-0.00MM	M10 X 1.5	5g6g		18MM	9MM	HEX	6MM	STR601M12X30	STR602M12X30
	40MM	+.25MM/-0.00MM	M10 X 1.5	5g6g		18MM	9MM	HEX	6MM	STR601M12X40	STR602M12X40
TOLERANCE:	50MM	+.25MM/-0.00MM	M10 X 1.5	5g6g		18MM	9MM	HEX	6MM	STR601M12X50	STR602M12X50
016MM TO	60MM	+.25MM/-0.00MM	M10 X 1.5	5g6g		18MM	9MM	HEX	6MM	STR601M12X60	STR602M12X60
-0.059MM	70MM	+.25MM/-0.00MM	M10 X 1.5	5g6g		18MM	9MM	HEX	6MM	STR601M12X70	STR602M12X70
	30MM	+.25MM/-0.00MM	M12 X 1.75	5g6g		24MM	11MM	HEX	MM8	STR601M16X30	STR602M16X30
M16	40MM	+.25MM/-0.00MM	M12 X 1.75	5g6g		24MM	11MM	HEX	8MM	STR601M16X40	STR602M16X40
14110	50MM	+.25MM/-0.00MM	M12 X 1.75	5g6g		24MM	11MM	HEX	8MM	STR601M16X50	STR602M16X50
	60MM	+.25MM/-0.00MM	M12 X 1.75	5g6g		24MM	11MM	HEX	8MM	STR601M16X60	STR602M16X60
TOLERANCE:	70MM	+.25MM/-0.00MM	M12 X 1.75	5g6g		24MM	11MM	HEX	8MM	STR601M16X70	STR602M16X70
016MM TO	80MM	+.25MM/-0.00MM	M12 X 1.75	5g6g		24MM	11MM	HEX	8MM	STR601M16X80	STR602M16X80
-0.059MM	90MM	+.25MM/-0.00MM	M12 X 1.75	5g6g		24MM	11MM	HEX	8MM	STR601M16X90	STR602M16X90
	40MM	+.25MM/-0.00MM	M16 X 2	5g6g		30MM	14MM	HEX	10MM	STR601M20X40	STR602M20X40
	50MM	+.25MM/-0.00MM	M16 X 2	5g6g		30MM	14MM	HEX	10MM	STR601M20X50	STR602M20X50
M20	60MM	+.25MM/-0.00MM	M16 X 2	5g6g		30MM	14MM	HEX	10MM	STR601M20X60	STR602M20X60
	70MM	+.25MM/-0.00MM	M16 X 2	5g6g		30MM	14MM	HEX	10MM	STR601M20X70	STR602M20X70
	80MM	+.25MM/-0.00MM	M16 X 2	5g6g		30MM	14MM	HEX	10MM	STR601M20X80	STR602M20X80
TOLERANCE:	90MM	+.25MM/-0.00MM	M16 X 2	5g6g		30MM	14MM	HEX	10MM	STR601M20X90	STR602M20X90
020MM TO	100MM	+.25MM/-0.00MM	M16 X 2	5g6g		30MM	14MM	HEX	10MM	STR601M20X100	STR602M20X100
-0.072MM	120MM	+.25MM/-0.00MM	M16 X 2	5g6g		30MM	14MM	HEX	10MM	STR601M20X120	STR602M20X120

Lengthening and Shortening Shim Washers are also available. See Page 72









Special Pan Head & Flat Head Machine Screws

Thread

Size

2-56

2-56

2-56

4-40

4-40

4-40

6-32

6-32

6-32

8-32

8-32

8-32

8-32

10-24

10-24

10-24

10-24

10-32

10-32

10-32

10-32

1/4-20

Length

1/4

3/8

1/2

1/4

3/8

1/2

1/4

3/8

1/2

1/2

5/8

3/8

1/2

5/8

3/4

3/8

1/2

5/8

3/4


1/2



Slotted Pan Head Machine Screws

4140 Allov Steel. Thru-Hardened to C40-C50 Black-Oxide Finish






Combo Phillips Pan Head Machine Screws with Pilot Points

18-8 Stainless Steel





Combo Phillips Pan Head Machine Screw w/Pilot Point

Macili	ile ociev	W W/I HOLT OITIL
Thread		18-8 St/St
Size	Length	Order Number
6-32	1/2"	SCR150P06C08
6-32	3/4	SCR150P06C12
6-32	1	SCR150P06C16
6-32	1-1/4	SCR150P06C20
8-32	1/2	SCR150P08C08
8-32	3/4	SCR150P08C12
8-32	1	SCR150P08C16
8-32	1-1/4	SCR150P08C20
10-32	1/2	SCR150P10F08
10-32	3/4	SCR150P10F12
10-32	1	SCR150P10F16
10-32	1-1/4	SCR150P10F20

Stainless Steel Slotted Pan Head Screws with Vent Hole

Slotted Pan Head Machine Screws

4140 Alloy Steel, Thru-Hardened, Black Oxide Finish

Head

Height

.045-.053

.045-.053

045- 053

058-068

058-068

.058-.068

.072-.082

.072-.082

.072-.082

.085-.096

.085-.096

.085-.096

.085-.096

.099-.110

.099-.110

.099-.110

.099-.110 .099-.110

.099-.110

.099-.110

099-110

.130-.144

Head

Diameter

.155-.167

.155-.167

155- 167

.205-.219

205-.219

.205-.219

.256-.270

.256-.270

.256-.270

.306-.322

.306-.322

.306-.322

.306-.322

.357-.373

.357-.373

.357-.373

.357-.373

.357-.373

.357-.373

.357-.373

357-373

.473-.492

Order

Number

SCR55002

SCR55004

SCR55006

SCR55012

SCR55014

SCR55016

SCR55022

SCR55024

SCR55026

SCR55032

SCR55034

SCR55036

SCR55038

SCR55050

SCR55052

SCR55054

SCR55056

SCR55058

SCR55070

SCR55072

SCR55074

SCR55080

SCREW LENGTH

18-8 Stainless Steel








Combo Phillips Flat Head Machine Screws with Pilot Points

18-8 Stainless Steel





SPECIAL ORDERS AVAILABLE— Small Quantities



50



Combo Phillips Flat Head Machine Screw w/Pilot Point										
	ile ociev	18-8 St/St								
Thread		10-0 31/31								
Size	Length	Order Number								
6-32	1/2"	SCR160P06C08								
6-32	3/4	SCR160P06C12								
6-32	1	SCR160P06C16								
6-32	1-1/4	SCR160P06C20								
8-32	1/2	SCR160P08C08								
8-32	3/4	SCR160P08C12								
8-32	1	SCR160P08C16								
8-32	1-1/4	SCR160P08C20								
10-32	1/2	SCR160P10F08								
10-32	3/4	SCR160P10F12								
10-32	1	SCR160P10F16								
10-32	1-1/4	SCR160P10F20								

Thread Size Screw Length Vent Hole Size Order Number 2-56 1/4" .028" SCR68002 2-56 5/16 .028 SCR68004 2-56 3/8 .028 SCR68006 2-56 3/8 .028 SCR68008 4-40 1/4" .035" SCR68012 4-40 3/8 .035 SCR68014 4-40 3/4 .035 SCR68016 4-40 3/4 .035 SCR68018 6-32 1/4" .038" SCR68024 6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68028 6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68028 8-32 1/2 .038 SCR68038 8-32 3/4 .042" SCR68040 8-32 3/4 .042" SCR68042 8-32 3/4 .042 SCR68044 10-3	Slotted Pan Head Screws w/Vent Hole											
Size Length Size Number 2-56 1/4" .028" SCR68002 2-56 5/16 .028 SCR68004 2-56 3/8 .028 SCR68006 2-56 1/2 .028 SCR68006 2-56 1/2 .028 SCR68006 2-56 1/2 .028 SCR68006 2-56 3/8 .035" SCR68012 4-40 1/4" .035" SCR68014 4-40 3/8 .035 SCR68016 4-40 3/4 .035 SCR68018 6-32 1/4" .038" SCR68024 6-32 3/8 .038 SCR68026 6-32 3/4 .038 SCR68028 6-32 3/4 .038 SCR68028 8-32 3/4 .042" SCR68030 8-32 3/8 .042 SCR68042 8-32 3/4 .042 SCR68042 8-32 3/4	Stainless Steel											
2-56 1/4" .028" SCR68002 2-56 5/16 .028 SCR68004 2-56 3/8 .028 SCR68006 2-56 1/2 .028 SCR68006 4-40 1/4" .035" SCR68012 4-40 3/8 .035 SCR68014 4-40 1/2 .035 SCR68016 4-40 3/4 .035 SCR68016 4-40 3/4 .035 SCR68016 4-32 1/4" .038" SCR68024 6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68030 8-32 1/2 .038 SCR68030 8-32 1/4" .042" SCR68040 8-32 3/4 .042" SCR68040 8-32 1/2 .042 SCR68040 8-32 1/2 .042 SCR68040 8-32 1/4" .042" SCR68040 8-32 1/4" .042" SCR68040 8-32 1/2 .042 SCR68040 8-32 1/2 .042 SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68066 10-32 1/12 .046 SCR68066	Thread	Screw	Vent Hole	Order								
2-56 5/16 .028 SCR68004 2-56 3/8 .028 SCR68006 2-56 1/2 .028 SCR68008 4-40 1/4" .035" SCR68012 4-40 3/8 .035 SCR68014 4-40 3/4 .035 SCR68016 4-40 3/4 .035 SCR68018 6-32 1/4" .038" SCR68024 6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68030 8-32 3/4 .042" SCR68030 8-32 3/8 .042 SCR68040 8-32 3/4 .042 SCR68044 10-32 3/4 .046" SCR68060 10-32 3/8 .046 SCR68064 10-32 3/4 .046 SCR68066 10-32 3/4 .046 SCR68066	Size	Length	Size	Number								
2-56 3/8 .028 SCR68006 2-56 1/2 .028 SCR68008 4-40 1/4" .035" SCR68012 4-40 3/8 .035 SCR68014 4-40 1/2 .035 SCR68016 4-40 3/4 .035 SCR68018 6-32 1/4" .038" SCR68024 6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68030 8-32 3/4 .042" SCR68038 8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68042 8-32 3/4 .042 SCR68042 8-32 3/4 .042 SCR68064 10-32 1/4" .046" SCR68066 10-32 1/4" .046" SCR68066 10-32 1/2 .046 SCR68064 10-32 3/4	2-56	1/4"	.028"									
2-56 1/2 .028 SCR68008 4-40 1/4" .035" SCR68012 4-40 3/8 .035 SCR68014 4-40 1/2 .035 SCR68016 4-40 3/4 .035 SCR68018 6-32 1/4" .038 SCR68028 6-32 3/4 .038 SCR68030 8-32 1/4" .042" SCR6804 8-32 3/8 .042 SCR6804 8-32 3/4 .042 SCR6804 10-32 1/4" .046" SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68060 10-32 3/8 .046 SCR68064 10-32 3/4 .046 SCR68064 10-32 3/4 .046 SCR68064												
4-40 1/4" 0.35" SCR68012 4-40 3/8 0.35 SCR68014 4-40 1/2 0.35 SCR68016 4-40 3/4 0.35 SCR68018 6-32 1/4" 0.38 SCR68024 6-32 3/8 0.38 SCR68026 6-32 1/2 0.38 SCR68030 8-32 1/4" 0.42" SCR68038 8-32 3/8 0.42 SCR68040 8-32 1/2 0.42 SCR68040 8-32 1/2 0.42 SCR68041 10-32 1/4" 0.46" SCR68061 10-32 1/4" 0.46" SCR68061 10-32 1/4" 0.46" SCR68062 10-32 1/2 0.46 SCR68062 10-32 1/2 0.46 SCR68064 10-32 3/4 0.46 SCR68066												
4-40 3/8 .035 SCR68014 4-40 1/2 .035 SCR68016 4-40 3/4 .035 SCR68018 6-32 1/4" .038" SCR68024 6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68030 8-32 1/4" .042" SCR68038 8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68040 10-32 1/4" .046" SCR68061 10-32 1/4" .046" SCR68061 10-32 1/4" .046" SCR68061 10-32 1/2 .046 SCR68064 10-32 3/8 .046 SCR68064 10-32 3/4 .046 SCR68066	2-56	1/2	.028	SCR68008								
4-40 3/8 .035 SCR68014 4-40 1/2 .035 SCR68016 4-40 3/4 .035 SCR68018 6-32 1/4" .038" SCR68024 6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68030 8-32 1/4" .042" SCR68038 8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68040 10-32 1/4" .046" SCR68061 10-32 1/4" .046" SCR68061 10-32 1/4" .046" SCR68061 10-32 1/2 .046 SCR68064 10-32 3/8 .046 SCR68064 10-32 3/4 .046 SCR68066												
4-40 1/2 .035 SCR68016 4-40 3/4 .035 SCR68018 6-32 1/4" .038 SCR68024 6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68030 8-32 1/4" .042" SCR68040 8-32 3/4 .042 SCR68040 8-32 1/2 .042 SCR68041 10-32 1/4" .046" SCR68060 10-32 1/4" .046" SCR68060 10-32 1/2 .046 SCR68064 10-32 3/4 .046 SCR68064 10-32 3/4 .046 SCR68066												
4-40 3/4 .035 SCR68018 6-32 1/4" .038" SCR68024 6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68030 8-32 1/4" .042" SCR68042 8-32 1/2 .042 SCR68042 8-32 1/2 .042 SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68064 10-32 3/4 .046 SCR68064 10-32 3/4 .046 SCR68066												
6-32 1/4" .038" SCR68024 6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68038 8-32 1/4" .042" SCR68038 8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68042 8-32 3/4 .042 SCR68042 10-32 1/4" .046" SCR68061 10-32 1/4" .046" SCR68062 10-32 3/8 .046 SCR68064 10-32 3/4 .046 SCR68064												
6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68030 8-32 1/4" .042" SCR68030 8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68042 8-32 3/4 .042 SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68064 10-32 3/4 .046 SCR68064	4-40	3/4	.035	SCR68018								
6-32 3/8 .038 SCR68026 6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68030 8-32 1/4" .042" SCR68030 8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68042 8-32 3/4 .042 SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68064 10-32 3/4 .046 SCR68064	0.00	4/48	000"	0000004								
6-32 1/2 .038 SCR68028 6-32 3/4 .038 SCR68030 8-32 1/4" .042" SCR68038 8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68042 8-32 3/4 .042 SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68062 10-32 3/4 .046 SCR68066 10-32 3/4 .046 SCR68066												
6-32 3/4 .038 SCR68030 8-32 1/4" .042" SCR68038 8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68042 8-32 3/4 .042 SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68062 10-32 1/2 .046 SCR68064 10-32 3/4 .046 SCR68066												
8-32 1/4" .042" SCR68038 8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68042 8-32 3/4 .042 SCR68042 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68062 10-32 1/2 .046 SCR68064 10-32 3/4 .046 SCR68066												
8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68042 8-32 3/4 .042 SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68062 10-32 1/2 .046 SCR68064 10-32 3/4 .046 SCR68066	6-32	3/4	.038	SCK68030								
8-32 3/8 .042 SCR68040 8-32 1/2 .042 SCR68042 8-32 3/4 .042 SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68062 10-32 1/2 .046 SCR68064 10-32 3/4 .046 SCR68066	8_32	1//"	042"	SCB68038								
8-32 1/2 .042 SCR68042 8-32 3/4 .042 SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68062 10-32 1/2 .046 SCR68064 10-32 3/4 .046 SCR68066												
8-32 3/4 .042 SCR68044 10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68062 10-32 1/2 .046 SCR68064 10-32 3/4 .046 SCR68066												
10-32 1/4" .046" SCR68060 10-32 3/8 .046 SCR68062 10-32 1/2 .046 SCR68064 10-32 3/4 .046 SCR68066												
10-32 3/8 .046 SCR68062 10-32 1/2 .046 SCR68064 10-32 3/4 .046 SCR68066	0 02	0/1	.0 12	001100044								
10-32 1/2 .046 SCR68064 10-32 3/4 .046 SCR68066	10-32	1/4"	.046"	SCR68060								
10-32 3/4 .046 SCR68066	10-32	3/8	.046	SCR68062								
	10-32	1/2	.046	SCR68064								
10-32 1 .046 SCR68068	10-32	3/4	.046	SCR68066								
	10-32	1	.046	SCR68068								



Sex Bolt Assortment Kits



18-8 Stainless Steel Sex Bolt Assortment Kit

Z4379PAK	Z4380PAK	Z4381PAK	Z4382PAK	Z4105SSPAK	Z4126SSPAK
Bathroom Partition Sex Bolts— assembled sets of male and female. 1/2" Grip Range, 1/4" Shoulder Dia.	Bathroom Partition Sex Bolts— assembled sets of male and female. 3/4" Grip Range, 1/4" Shoulder Dia.	Bathroom Partition Sex Bolts— assembled sets of male and female. 1" Grip Range, 1/4" Shoulder Dia.	Bathroom Partition Sex Bolts— assembled sets of male and female. 1-1/4" Grip Range, 1/4" Shoulder Dia.	Screw 18-8 P/Ns	13/64" Barrel Dia X 1/2" Lth 18-8 St/St with 8-32 Threads Combo Head Barrel Bolt with 8-32 X 5/16 Mating Male Screw 18-8 P/Ns Z4126SS + Z407SSS
Qty: 10 Sets	Qty: 10 Sets	Qty: 10 Sets	Qty: 10 Sets	Qty: 10 Sets	Qty: 10 Sets
Z4416SSPAK	Z4146SSPAK	75025	Z5125	Z5225	Z5325
Z441055PAK	Z414055PAK	Z5025	25125	25225	25325
1/4" Barrel Dia X 1" Lth 18-8 St/St with 10-24 Threads Combo Head Barrel Bolt with 10-24 X 5/16 Mating Male Screw 18-8 P/Ns Z4416SS + Z408SSS	3/8" Barrel Dia X 1/2" Lth 18-8 St/St with 5/16-18 Threads Combo Head Barrel Bolt with 5/16-18 X 5/16 Mating Male Screw 18-8 P/Ns Z4146SS + Z4096SS	5/16 Barrel X 1-3/16" Lth 18-8 St/St Architectural Sex Bolt & Mating Screw	5/16 Barrel X 1-9/16" Lth 18-8 St/St Architectural Sex Bolt & Mating Screw	3/8 Barrel X 1-9/16" Lth 18-8 St/St Architectural Sex Bolt & Mating Screw	3/8 Barrel X 2-1/16" Lth 18-8 St/St Architectural Sex Bolt & Mating Screw
Qty: 5 Sets	Qty: 5 Sets	Qty: 5 Sets	Qty: 5 Sets	Qty: 5 Sets	Qty: 5 Sets

Features:

- 12 of the most popular 18-8 Stainless Steel internal thread Sex Bolts
- 4 of the most popular Bathroom Partition Sets—18-8 S/S in 1/2", 3/4", 1", and 1-1/4" **Grip Ranges**
- All male and female Sets come assembled
- Assembled sets make it easy to figure out the right size
- Easy guide to re-order
- Use this Counter Display to show customers this hard to find product line!



18-8 Stainless Steel Combo Head Barrel Bolt Assortment Kit

Z4404SS	Z4406SS	Z4408SS	Z4412SS	Z4416SS	Z4424SS
1/4 Barrel Dia X 1/4" Lth (open head) with 10-24 Screw (Z4085SS)	1/4 Barrel Dia X 3/8" Lth with 10-24 Screw (Z4085SS)	1/4 Barrel Dia X 1/2" Lth with 10-24 Screw (Z4085SS)	1/4 Barrel Dia X 3/4" Lth with 10-24 Screw (Z4085SS)	1/4 Barrel Dia X 1" Lth with 10-24 Screw (Z4085SS)	1/4 Barrel Dia X 1-1/2" Lth with 10-24 Screw (Z4085SS)
Qty: 30 Sets	Qty: 30 Sets	Qty: 20 Sets	Qty: 20 Sets	Qty: 20 Sets	Qty: 10 Sets
Z4135SS	Z4443SS	Z4146SS	Z4126SS	Z4128SS	Z4125SS
5/16 Barrel Dia X 3/8" Lth with 1/4-20 Screw (Z4095SS)	5/16 Barrel Dia X 1/2" Lth with 1/4-20 Screw (Z4095SS)	3/8 Barrel Dia X 1/2" Lth with 5/16-18 Screw (Z4096SS)	13/64 Barrel Dia X 1/2" Lth with 8-32 Screw (Z4075SS)	13/64 Barrel Dia X 3/4" Lth with 8-32 Screw (Z4075SS)	13/64 Barrel Dia X 3/8" Lth with 8-32 Screw (Z4075SS)
Qty: 20 Sets	Qty: 10 Sets	Qty: 10 Sets	Qty: 30 Sets	Qty: 20 Sets	Qty: 30 Sets

Features:

- 12 of the most popular 18-8 St/St internal thread Combo Head Barrel Bolts
- · Easy guide to re-order
- Use this Counter Display to show customers this hard to find product line!
- MOST ITEMS ALSO **AVAILABLE IN TYPE 316** STAINLESS STEEL-FROM OUR STOCK



Steel Zinc Barrel Bolt Assortment Kit

Z4105	Z4108	Z4404	Z4406	Z4408	Z4412
3/16 Barrel Dia X 3/8" Lth with 6-32 Screw (Z4074)	3/16 Barrel Dia X 3/4" Lth with 6-32 Screw (Z4074)	1/4 Barrel Dia X 1/4" Lth (open head) with 10-24 Screw (Z4085)	1/4 Barrel Dia X 3/8" Lth with 10-24 Screw (Z4085)	1/4 Barrel Dia X 1/2" Lth with 10-24 Screw (Z4085)	1/4 Barrel Dia X 3/4" Lth with 10-24 Screw (Z4085)
Qty: 50 Sets	Qty: 30 Sets	Qty: 30 Sets	Qty: 30 Sets	Qty: 20 Sets	Qty: 20 Sets
Z4416	Z4435	Z4438	Z4440	Z4443	Z4446
1/4 Barrel Dia X	13/64 Barrel Dia	13/64 Barrel Dia	13/64 Barrel Dia	5/16 Barrel Dia X	5/16 Barrel Dia X
1" Lth with	X 1/4" Lth with	X 1/2" Lth with	X 3/4" Lth with	1/2" Lth with	1" Lth with
10-24 Screw	8-32 Screw	8-32 Screw	8-32 Screw	1/4-20 Screw	1/4-20 Screw
(Z4085)	(Z4075)	(Z4075)	(Z4075)	(Z4095)	(Z4095)
Qty: 20 Sets	Qty: 30 Sets	Qty: 30 Sets	Qty: 20 Sets	Qty: 20 Sets	Qty: 10 Sets

Features:

- 12 of the most popular Steel Zinc internal thread Combo Head Barrel Bolts
- · Easy guide to re-order
- Use this Counter Display to show customers this hard to find product line!









Sex Bolt Assortment Kits



Binding Post Assortment Kits—Aluminum, Brass, Stainless Steel

Features:

- 5 of the most popular internal thread female Binding Posts
- Matching screw fits in each barrel—total number of screws matches the number of barrels included
- Seeing the item makes it easy for your customer to figure out the right size
- Easy guide to re-order
- Use this Counter Display to show customers this hard to find product line!
- AVAILABLE FROM OUR STOCK IN ALUMINUM, BRASS, & 18-8 STAINLESS STEEL

Aluminum Assortment Kit	Order # Z4195
18-8 Stainless Steel Assortment Kit	Order # Z4196
Brass Assortment Kit	Order # Z4197

Z4300(SS/BR)	Z4308(SS/BR)	Z4312(SS/BR)	Z4320(SS/BR)	Z4332(XSS/XBR)	Z4348(XSS/XBR)
8-32 X 3/8	13/64 X 1/2	13/64 X 3/4	13/64 X 1-1/4	13/64 X 2"	13/64 X 3"
SLOTTED	BINDING POST	BINDING POST	BINDING POST	BINDING POST	BINDING POST
BINDING POST	8-32 INTERNAL	8-32 INTERNAL	8-32 INTERNAL	8-32 INTERNAL	8-32 INTERNAL
MACHINE SCREW	THREADS	THREADS	THREADS	THREADS	THREADS
TITICITITE SCILLIV	TTINE	TTINE	TTINE	I IIIICO DO	TTIRES
OL 400 D	01 40 5	O1 20 B	01 06 0	01 110	01 40 5
Qty: 120 Pcs	Qty: 40 Pcs	Qty: 30 Pcs	Qty: 26 Pcs	Qty: 14 Pcs	Qty: 10 Pcs



Binding Post Assortment Kits—Steel Zinc

Features:


- 5 of the most popular internal thread female Binding Posts
- Matching screw fits in each barrel—total number of screws matches the number of barrels included
- Seeing the item makes it easy for your customer to figure out the right size
- Easy guide to re-order
- Use this Counter Display to show customers this hard to find product line!

Z4300-STL	Z4308-STL	Z4312-STL	Z4316-STL	Z4324-STL	Z4332-STL
8-32 X 3/8	13/64 X 1/2	13/64 X 3/4	13/64 X 1"	13/64 X 1-1/2"	13/64 X 2"
SLOTTED	BINDING POST	BINDING POST	BINDING POST	BINDING POST	BINDING POST
BINDING POST	8-32 INTERNAL	8-32 INTERNAL	8-32 INTERNAL	8-32 INTERNAL	8-32 INTERNAL
MACHINE SCREW	THREADS	THREADS	THREADS	THREADS	THREADS
Qty: 120 Pcs	Qty: 40 Pcs	Qty: 30 Pcs	Qty: 26 Pcs	Qty: 14 Pcs	Qty: 10 Pcs

Solar Install Kit—18-8 Stainless Steel, 530 Pcs.

Features:

- Everything you need to install solar panels on a standard racking system, including:
 Flange Nuts, Fender Washers, Truss Head Sex Bolts, Tamperproof 6-Lobe with Pin Barrels, Combo-Head Barrels,
 T-Handle Bolts, Hanger Bolts, & Fully Threaded Studs
- Steel Box with Compartments





SPECIAL ORDERS
AVAILABLE—
Small Quantities

to Large Volume

52

