

CEILING FAN REMOTE CONTROLLER OPERATION AND INSTALLATION INSTRUCTIONS

(Please keep this instruction pamphlet.)

IMPORTANT POINTS TO REMEMBER:


1. Read and save these instructions.
2. Please note that all fixed wiring appliances should be installed by a qualified electrician.
3. The supply to the remote control receiver should be connected through a mains switch, i.e. existing wall switch.
4. Disconnect from power supply at wall switch before working on remote control receiver or ceiling fan.
5. Install receiver into the Switch cup of the ceiling fan to ensure proper protection
6. This unit is to be used for the control of ceiling fan and in an AC120V 60Hz power supply only.
7. Do not install in damp locations or immerse in water. (For indoor use only.)
8. Do not pull on or cut leads shorter.
9. Do not drop or bump the unit.
10. PLEASE NOTE: The battery will weaken with age and should be replaced before leaking takes place as this will damage the transmitter. Dispose of used battery properly, and keep the battery out of reach of children.
11. CAUTION: To reduce the risk of fire or injury, do not use this product in conjunction with any variable (rheostat) wall control.

INSTALLATION INSTRUCTIONS

CAUTION: INCORRECT WIRE CONNECTION WOULD DAMAGE THIS RECEIVER.

Note: If using a light kit, the light switch located on the light kit should be at "ON" position before operating the remote control.

1. Once the connection has been made, the receiver (model number MR77A) inserts into motor control case.



LEARNING PROCESS

1. This unit finished learning process inside manufactory, if replace transmitter or receiver, user need to redo learning process before using this unit.
2. Open battery cover (with battery, DC12V 1pcs, installed) and use a ball pen to set Code switch up or down. Then turn ceiling fan power on, press transmitter "FAN OFF" key over 5 seconds, down light will be flash twice, which indicate that learning process finished. Learning effect distance is same with remote range 8m. Please note that must press the "FAN OFF" key within 30 seconds after power on. If just replace batteries, no need to re-learn.
3. Please note that the transmitter can learn in multiple receiver, when doing learning process please make sure not learn in other receiver. Suggest to separate power switches of fans in 2 meter range.

LIGHT FUNCTION SELECT SWITCH

If installed energy light onto ceiling fan down light, please slide the "down light function select switch" to "ON" position. If installed tungsten light onto ceiling fan, please slide the "down light function select switch" to "DIM" position.

FUNCTIONS OF TRANSMITTER



- : ON/OFF- Press and release immediately to turn on or off the light.
DIMMER-Press and hold to dim or brighten light to the desired level and release.
(Tungsten only and down light function select switch" to "DIM" position.)



: Turn off the ceiling fan.

3 : Turn on the fan at high speed

2 : Turn on the fan at medium speed

1 : Turn on the fan at low speed



: Press and release immediately to set fan wind direction up or down.



TR171B

Installation of Transmitter Wall Mount Holder with two screws.

CAUTION:

To assure continued FCC compliance:

Any changes or modifications not expressly approved by the grantee of this device could void the user's authority to operate the equipment.

FCC ID : KUJCE10205

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.