



Cisco Systems, Inc  
170 West Tasman Drive  
San Jose, CA 95134

July 8, 2015

Subject: Changes to User Guide for LDKIW3702

Dear Examiner,

For the above FCC ID and this Class 2 Permissive Change (c2pc), we will be making the following changes to the Getting Started Guide. The revised version of the manual will be submitted to the FCC as soon as it is ready.

Page 12: Change the second warning to the following:

Warning: In order to comply with FCC and IC radio frequency (RF) exposure limits, antennas for this product should be located a minimum of 7.9 in. (20cm) or more from the body of all persons. For antennas with gain greater than 10dBi, the minimum separation distance must be at least 9 in. (23 cm).  
Statement 332

Page 44: Modify the “Declaration of Conformity for RF Exposure” statements by adding the following (for both US and Canada):

For antennas with gains greater than 10dBi, the minimum separation distance from the antenna to general bystanders is 9 inches (23 cm) to maintain compliance.

Page 44 and 45, you have two “Separation Distance” tables. Eliminate the first table and modify the second table to the following:

Separation Distance	
Antenna Gain	Minimum Separation Distance
<10 dBi	7.87 in. (20cm)
>10 dBi	9 in. (23cm)

If you have any questions regarding this application, please feel free to contact me.

Best Regards

Steve Granzella  
Compliance Engineering Manager  
Cisco Systems, Inc