

## General Specifications

### A. FRS/GMRS Frequency Allocation and Compatibility

**Important:** Please note that Cobra® GMRS models with 15 channels may designate different channel numbers for the same frequency. For example, a Cobra® 15 channel GMRS model would need to be tuned to channel 11 in order to communicate with a 22 channel GMRS tuned to channel 15. Please refer to the chart below for channel/frequency number compatibility.

**A = 22 Channel GMRS Channel No. Displayed**

**B = Channel No. For 15 Channel GMRS Models**

**C = Type of Radio Service**

**D = Frequency in MHz**

**E = Power in Watts ERP**

a = 3.0/2.0/0.5 (selectable)

b = 0.5

A	B	C	D	E
1	1	FRS/GMRS	462.5625	a
2	2	FRS/GMRS	462.5875	a
3	3	FRS/GMRS	462.6125	a
4	4	FRS/GMRS	462.6375	a
5	5	FRS/GMRS	462.6625	a
6	6	FRS/GMRS	462.6875	a
7	7	FRS/GMRS	462.7125	a
8		FRS	467.5625	b
9		FRS	467.5875	b
10		FRS	467.6125	b
11		FRS	467.6375	b
12		FRS	467.6625	b
13		FRS	467.6875	b
14		FRS	467.7125	b
15	11	GMRS	462.5500	a
16	8	GMRS	462.5750	a
17	12	GMRS	462.6000	a
18	9	GMRS	462.6250	a
19	13	GMRS	462.6500	a
20	10	GMRS	462.6750	a
21	14	GMRS	462.7000	a
22	15	GMRS	462.7250	a

### B. Receiver

	Unit	Nominal
1. Sensitivity		
For 12 DB SINAD	dBm	-121
For Call Signal Detection	dBm	-121
2. Max. Audio Output		
@10% THD	mW	200
3. Max. S/N Ratio		
@ 1mV RF Input	dB	50
4. Squelch		
a) Sensitivity	dBm	-121
b) Attack Time	mS	150
c) Closing Time	mS	200
5. Audio Frequency Response		
@ 300 HZ	dB	-3
@ 2500 HZ	dB	-10
6. Signal Displacement BW	+/-KHz	5
7. Adjacent Channel Rejection	dB	60
8. Intermodulation Rejection	dB	65
9. Spurious Response Rejection	dB	55

### C. Transmitter

	Unit	Nominal
1. Conducted Power		
GMRS	W	3
FRS Only	mW	500
2. Carrier Frequency Stability	±Hz	500
3. Modulation Limiting	KHz	2.5
4. Carrier Attack Time	mS	80
5. Audio Frequency Response		
@ 300 HZ	dB	-12
@ 2500 HZ	dB	+6
6. Audio Distortion	%	3
7. Hum Noise	dB	30
8. Transient Frequency Behavior		
a) TX On	mS	30
b) TX Off	mS	5

### D. Power Supply

	Unit	Nominal
1. Battery Life (5:5:90 RATIO)		
With Alkaline Batteries	HR	24
2. Battery Operating Range	V	4.2 - 6.0