

Nuova Distribution USA, LLC

6940 Salashan Parkway, Building A • Ferndale, WA 98248 www.nuovadistribution.com • (p) 360-366-2226 • (f) 360-366-4015

Appia Compact 220V 2 Group Spec Sheet

☐ Water Requirements

- 3/8" dedicated cold water line with shut-off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50 ppm. If water hardness exceeds 3gpg a water softener must be installed.
- Minimum incoming water flow rate of 35 GPH and maximum line pressure of 70 PSI / 5 BAR.

Water Softening Equipment

- 1. Water Softener Capacity: Single 4400 gpg
- 2. Water Softener Capacity: Double 8800 gpg
- 3. Water Softener Capacity: Triple 13200 gpg
- 4. Water Softener Capacity: Automatic Programmable
- 5. Water Softener Capacity: Manual 4400 gpg

Power Requirements

Volts: 220 (voltage range of 208-240)

Watts: 3000Amp draw: 14

Receptacle: Nema 6-20









NSF / ANSI Std.4

The average water consumption of this machine is 4 gallons per day, which represents 128 drinks at 4oz per drink.

☐ Water Softener/Maintenance Calculation

Cartridge Grain
Capacity

Water Hardness
(grains per gallon)

Gallon Capacity
of Cartridge

Gallons of Water
Used per Day

Days Until Cartridge
Needs to be Replaced

Shipping Dimensions & Weight


Height: 27 inchesDepth: 24 inchesWidth: 24 inchesWeight: 150 pounds

Counter Space Requirements

Height: 22 inchesDepth: 21 inchesWidth: 16 inchesWeight: 130 pounds

Drain Requirements

 Open gravity drain of minimum 1.25 inch I.D., within 4 feet of the machine.





l, the customer, understand that these requirements must be in when the installe	r arrives. Failure to have the site ready
will result in additional service and travel charges, and may cause further delays	in installation.

The result in a section and trainer shall got, and may section assays in metallicing		
Customer Name:	Signature:	
Company Name:		
Phone:	Fax:	Email: