



Advanced Switching Features

- + Dual Fiber XFP 10G Uplinking (Optional)
- + Dual Copper CX4 10G Uplinking (Optional)
- + Up to 48Gbps Total Stacking Bandwidth
- + Up to 8 Units Per Stack
- + Redundant Power Support (Optional)
- + Up to 32 Static IP Routes
- + 802.3ad (Link Aggregation)
- + 802.1v (Protocol-based VLANs)
- + Link Aggregation (64 groups/8 ports)
- + 802.1p Priority (8 WRR)
- + 802.1X Authentication
- + 4000 802.1q VLANs
- + IGMP Snooping
- + ACL L2/L3/L4
- + SNMPv1/v2/v3
- + TACACS+ & RADIUS
- + 802.1D/w/s Spanning Tree
- + SSH/SSL
- + Private/Guest VLANs

Unified Wired/Wireless

- + 256 Wireless VLANs
- + Up to 50 APs per Switch/Stack
- + Up to 600 Simultaneous WLAN Users per Switch/Stack
- + Supports 802.11a/b/g Standards
- + Seamless Wireless Roaming
- + Supports 10, 25, or 50 AP Licenses
- + Industry Standard Encryption: WEP, WPA™, WPA2™
- + Supports up to 16 SSIDs per AP
- + Centralized AP Management
- + GUI WLAN Monitoring & Logging
- + Automatic Channel Assignment
- + Dynamic WLAN Load Balancing
- + Rogue AP Detection & Containment

xStack® Managed 48-Port Gigabit Stackable L2+ Switch with 4 Combo SFP and 2 10-Gigabit Slots

Overview

The D-Link® xStack® 3200 Series switches provide effortless wireless technology convergence with traditional Layer 2 data access switching, emphasizing security, performance, and resiliency. Featuring the latest stacking technology, the DXS-3250 can stack up to eight units, providing up to 384 Gigabit ports. It can stack with other D-Link switches such as the DXS/DWS-3227 and DXS-3227P for extraordinary flexibility. The DXS-3250 provides 48 built-in copper Gigabit ports, including four combo SFP slots for easy, flexible connection to fiber-based Gigabit media. The DXS-3250 is also equipped with two module slots that support 10-Gigabit Ethernet for both copper CX4 and fiber XFP connections. When stacking through CX4 interfaces, a stacking bandwidth of 48Gbps can be achieved, for a total switching fabric capacity of up to 240Gbps. In addition, the DXS-3250 also supports IP static routing, 4000 VLANs, up to 64 trunk groups, and is wireless-ready, making it the most feature-rich, high-capacity switching solution in its class.

Unified Wireless and Wired

In a network made up of wired and wireless nodes, reliable coverage for both connection types is key. The DXS-3250 meets this demand and more. With a simple firmware upgrade, the DXS-3250 becomes an integrated wired and wireless switching solution capable of providing powerful wireless security, easy deployment, and centralized management. Centralized management is crucial for wireless technologies used in real-time inventory, data mining, and an array of personal electronics that demands mobility and seamless integration such as PDA and 3G/VoIP mobile phones. Additional software upgrades provide secure, seamless roaming between access points, ensuring uninterrupted data and voice communication throughout your wireless network.

DNA Stacking Architecture

The Distributed Network Architecture (DNA) technology embedded in the DXS-3250 is a D-Link exclusive. Switches built with DNA are easily stackable with little or no system downtime for expansion. The flexibility of DNA allows network administrators to use a number of topologies, such as ring or chain stacking, to connect anything up to 10GbE. Using DNA, the DXS-3250 provides system transparency with Port Mirroring, VLANs, and link aggregation across the stack. Unlike other stacking solutions, this allows VLANs to be added and removed without switch reconfiguration or VLAN trunks between devices. Port mirroring allows for the studying of all packets from a specific port anywhere in the stack, providing for superior troubleshooting and faster configuration with fewer errors.

DNA technology makes the DXS-3250 self-healing. This is how the switch can automatically detect new stack topologies and reconfigure the system for maximum performance. Failures within a stack are quickly discovered and traffic re-routed around failed devices. In the unlikely event of equipment failure, DNA provides for rapid reconfiguration, resulting in extremely fast failover times and little to no downtime.

Comprehensive Security

The DXS-3250 handles many security vulnerabilities previously delegated to standalone firewalls. It supports Access Control Lists (ACLs) based on MAC address, switch port, IP address, and/or TCP/UDP port numbers. The DXS-3250 also features 802.1X Authentication, Guest VLAN, and RADIUS and TACACS+ for strict access control over the network. Additionally, port-based security can help to protect network integrity. Port numbers can be pre-programmed for specific applications, allowing these applications to provide faster service and reduce load on the CPU.



xStack® Managed 48-Port Gigabit Stackable L2+ Switch with 4 Combo SFP and 2 10-Gigabit Slots

High Availability

The DXS-3250 supports “Shortest-Path” switching to improve resiliency, uptime, and network efficiency. It includes support for 802.3ad Link Aggregation and 802.1w Rapid Spanning Tree for increased network reliability and availability. It also supports an optional Redundant Power Supply (DPS-500).

Network Management

The DXS-3250 features a variety of network management options: Console CLI, Telnet, Web GUI, SNMPv1/v2/v3, and RMON. It also supports a variety of advanced traffic management options including: Layer 3 Static Routing, Bandwidth Control, Broadcast Storm Control, Private VLANs, and support for IGMP Snooping. Additionally, DNA stacking technology allows up to 16 DXS-3250 switches to be stacked together and managed as a single unit, regardless of the environment.

Advanced QoS

The DXS-3250 provides a robust and consistent set of QoS/CoS, supporting eight priority queues for 802.1p/ToS/DiffServ, with classification and marking based on MAC SA/DA, IP SA/DA, and/or TCP/UDP. It also provides extensive support for GARP/GVRP, 802.1q, and port-based VLANs for up to 4000 groups per device.

Wireless AP License

The xStack DXS-3250 provides secure, seamless roaming between access points to ensure clear, uninterrupted data and voice communication throughout your wireless network. The DXS-3250 supports an optional 10, 25, or 50 client AP license and is capable of supporting up to 50 APs per switch/stack with up to 600 WLAN clients.

Unified Wireless Switching¹

Centralized AP Management

The DXS-3250 can centrally manage all compatible access points. Your entire wireless network can be configured through a single interface. The DXS-3250 detects APs in real time, providing network utilization and performance data on all devices as it happens.

Wireless Security

The DXS-3250 provides enhanced wireless security to protect all of your data. Support for WEP, WPA™ and WPA2™ encryption guarantees network privacy. Rogue AP detection and containment ensure that only the APs you install are able to function on your network. AP detection classifies APs as “known” and “rogue”. The switch uses the APs to continuously scan radio channels to identify transmissions of unauthorized WLAN nodes and jam the rogue signals.

Seamless Wireless Roaming

Access Points connected to different broadcast domains tend to drop roaming users. As a result, the user’s wireless device (laptop, PDA, VoIP phone, etc.) needs to establish a new connection at the next AP. This can create a huge problem for “always connected” devices such as PDAs and VoIP phones.

D-Link has identified this problem and brings you a solution that provides seamless roaming between APs on different subnets. The solution is in the switch. The DXS-3250 handles all AP configuration and support so that users can roam seamlessly between all connected APs. It is like having one big AP! The user’s device retains its VLAN membership and IP address, guaranteeing uninterrupted communication.

Inter-switch Roaming

The DXS-3250 even supports wireless roaming between access points attached to different switches. Seamless Inter-switch roaming allows a station’s VLAN membership (IP subnet) and QoS parameters to be retained when roaming between APs connected to multiple switches throughout the network. Inter-switch roaming is extremely beneficial when creating a large WLAN environment such as a campus or multi-floor office. Inter-switch roaming allows the user complete freedom between switches located in different buildings or on different floors without disconnection or the need for re-authentication.



xStack® Managed 48-Port Gigabit Stackable L2+ Switch with 4 Combo SFP and 2 10-Gigabit Slots

Technical Specifications

Product Specifications

DXS-3250	xStack Managed 48-Port Gigabit Stackable L2+ Switch, 4 Combo SFP, 2 10-Gig Slots (Optional AP License required)
MAC Address Table	16K
Switch Fabric	240Gbps
VLANs	Supports Up to 4K VLAN Groups (Port-based, 802.1Q, GARP/GVRP, 802.1v Protocol-based Q-in-Q Tagging)
Priority Queues	8 Queues (802.1p/TOS/DiffServ) – Strict Priority or Weighted Round Robin Queue Scheduling
Classification QoS/ACLs	Based on: MAC, IP, TCP/UDP, Payload, Port, DSCP, 802.1p
Multicast Support	IGMP Snooping
End to End Flow Control	Flow Control Across Packet Processors
Link Aggregation Balancing	Based on MAC SA/DA, Based on IP SA/DA
MAC Table Search	Search MAC/IP to reveal source Unit/Port
Port Utilization	Measure Traffic, Total Port Capacity
Single Port Stacking	Chain/Ring Topology

Interface Options

RJ-45	10Base-T, 100Base-TX, & 1000Base-T
LC	With Optional Standard Small Form-Factor Pluggable (SFP) Gigabit Transceivers With Optional 10Gigabit XFP Transceivers
CX4	With Optional 10GBASE-CX4 Module
RPS	Redundant Power Supply Via DPS-500 (Optional)

Wireless Switching

AP License	Supports 10, 25, and 50 AP Licenses (Optional)
Max Allowed APs	50 APs per switch or 50 APs per stack
WLAN Encryption	WPA™, WPA2™, WEP (64 & 128 bit)
WLAN Security	802.1X Authentication
Rogue AP Detection	Port-based & Radio-based
Supported Roaming	Intra-switch, Inter-band, Inter-switch
802.11 Support	802.11a, 802.11b, 802.11g (based on supporting AP)
Max Users per AP	30 WLAN simultaneous users; 600 max per switch / stack
Wireless VLANs	256
SSIDs	16 concurrent SSIDs per AP
WLAN Management	HTTP, HTTPS, Telnet, SSH, SNMP
SYSLOG Events	Connection success / failure, Station roaming / AP connection, Error rates above threshold, Encryption errors
Logging Filters	Errors only, all events, per station, per AP
Additional Features	Automatic Channel Assignment, Dynamic Load Balancing



xStack® Managed 48-Port Gigabit Stackable L2+ Switch with 4 Combo SFP and 2 10-Gigabit Slots

Network Protocols and Standards

In Band & Out of Band	Telnet, CLI/Console, RMON, Web-based HTTP, SNMPv1/v2/v3, Syslog, Port Mirroring, TFTP Client, BootP Client, DHCP Client, BootP/DHCP Relay Agent, and DNS Client
IEEE	802.3 Ethernet, 802.3u Fast Ethernet, 802.3ab Gigabit Ethernet, 802.3z Gigabit Ethernet, 802.3ak 10GBASE-CX-4, 802.3ae 10GbE, 802.1D Spanning Tree, 802.1w Rapid Spanning Tree, 802.1p Priority Tags, 802.1q VLANs, 802.3ad Link Aggregation, 802.3x Flow Control, 802.1X Port-based Authentication, 802.1X MAC-based Authentication, 802.1s Multiple Spanning Tree, 802.1v protocol-based VLANs
IETF	RFC 1157 SNMP, RFC 1112/2236 IGMPv1/2, RFC 1757 RMON (4 Groups), RFC 1493 Bridge MIB, RFC 1213 MIB II, RFC 793 TCP, RFC 826 ARP, RFC 854 Telnet, Diffserv

Electrical & Emissions Summary

Emissions	CE Mark & FCC Class A
Power Supply	100-240VAC, 50/60 Hz Internal Universal
Power Consumption	90 Watts
Heat Dissipation	307 BTU/hr

Safety Agency Certifications and Environmental

Safety	CE/LVD, UL Listed (UL1950)/CUL
Temperature	Operating: 32° to 122°F (0° to 50°C) Storage: 4° to 158°F (-20° to 70°C)
Humidity	Operating: 0% ~ 90% RH, Non-condensing Storage: 0% ~ 95% RH, Non-condensing

Physical Specifications

Dimensions (W x D x H)	17.3in x 16.9in x 1.8in (439.9mm x 430mm x 44.9mm)
Height	1U
Weight	14.3 lbs (6.5 kg)

Warranty Information

Warranty	Lifetime ²
----------	-----------------------

Ordering Information

<u>Part Number</u>	<u>Description</u>
<u>Switch</u>	
DXS-3227	xStack Managed 24-Port Gigabit Stackable L2+ Switch, 4 Combo SFP, 1 Fixed XFP Slot, 2 10-Gigabit Slots
DXS-3227-TAA	xStack Managed 24-Port Gigabit Stackable L2+ Switch, 4 Combo SFP, 1 Fixed XFP Slot, 2 10-Gigabit Slots, (TAA Compliant)
DXS-3227P	xStack Managed 24-Port Gigabit Stackable L2+ PoE Switch, 4 Combo SFP, 1 Fixed XFP Slot, 2 10-Gigabit Slots
DXS-3250	xStack Managed 48-Port Gigabit Stackable L2+ Switch, 4 Combo SFP, 2 10-Gigabit Slots
DXS-3250-TAA	xStack Managed 48-Port Gigabit Stackable L2+ Switch, 4 Combo SFP, 2 10-Gigabit Slots, (TAA Compliant)
DWS-3227	xStack Managed 24-Port Gigabit Stackable L2+ Wireless Switch, 4 Combo SFP, 1 Fixed XFP Slot, 2 10-Gigabit Slots, 10-AP License



xStack® Managed 48-Port Gigabit Stackable L2+ Switch with 4 Combo SFP and 2 10-Gigabit Slots

Access Points

DWL-2230AP	xStack 3200 Series PoE Access Point, 802.11g
------------	--

Modules

DEM-411X	1-Port 10-Gigabit XFP Module for DXS-3227/DXS-3250
DEM-411T	1-Port 10-Gigabit CX4 Module for DXS-3227/DXS-3250
DEM-411S	Stacking Kit (2 DEM-411T Modules & 1 0.5m CX4 Cable) for DXS-3227/DXS-3250

Transceivers

DEM-310GT	1000BASE-LX SFP Module, up to 10Km
DEM-311GT	1000BASE-SX SFP Module, up to 550m
DEM-421XT	10GBASE-SR Multimode XFP, up to 300m
DEM-422XT	10GBASE-LR Singlemode XFP, up to 10Km

Redundant Power

DPS-500	Redundant Power Supply Unit, 140 Watt RPSU
DPS-800	2-Slot RPSU Open Chassis for DPS-200/DPS-500
DPS-900	8-Slot RPSU Open Chassis for DPS-200/DPS-500

AP License

DS-710	10 Access Point License, xStack Wireless Switching
DS-725	25 Access Point License, xStack Wireless Switching
DS-750	50 Access Point License, xStack Wireless Switching

¹ With purchase of AP license.

² Lifetime warranty available only in the USA and Canada if purchased on or after March 30, 2009. Visit www.dlink.com for warranty details.

All references to speed are for comparison purposes only. Product specification, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.