



IMI CORNELIUS INC ■ One Cornelius Place ■ Anoka, MN 55303-6234

Telephone (800) 238-3600

Facsimile (800) 535-4231

## OPERATORS MANUAL – ICE COOLED DISPENSERS

This instruction applies to all models of Drop-In and Free-Standing Ice Cooled dispensers.

### RECOMMENDED MAINTENANCE

Details of each task are listed immediately below the chart. Refer to the details by task number.

Maintenance Schedule				
Task	D	W	M	Q
1. Clean all exterior surfaces	O			
2. Clean dispensing valves, Post-Mix		O		
3. Clean dispensing valves, Pre-Mix		O		
4. Clean & sanitize ice bin			O	
5. Sanitize tank systems, post-mix and pre-mix				S
6. Sanitize syrup lines, B-I-B systems				S
7. Sanitize Bin Drain & Drip Tray Drain			O	
<b>Legend:</b>				
<u>D</u> aily	<u>W</u> eekly	<u>M</u> onthly	<u>Q</u> uarterly	
<u>O</u> perator	<u>S</u> erviceperson			

### DETAILS OF MAINTENANCE TASKS

#### 1. Clean All Exterior Surfaces

##### Cleaning The Tower

**IMPORTANT: DO NOT USE ABRASIVE CLEANERS**

- A. Remove the cup rest from the drip tray.
- B. Wash the drip tray with warm soapy water. Rinse the drip tray, allowing the rinse water to run down the drain hose.
- C. Wipe entire exterior of the tower with a damp cloth. Dry the tower with a clean cloth (see caution below).



**CAUTION:** To minimize the possibility of damaging the surface of the painted tower care must be taken when choosing a cloth. The cloth must be of clean cotton with a deep nap, or equivalent. If a damp cloth is instructed to use, it must be rinsed out in clean water, the damp or the dry cloth must be manually fluffed to a softened consistency before using to wipe or polish the painted tower.

- D. For the painted tower, (rather than a stainless steel tower) the painted surface may be cleaned using mild detergents or most house hold cleaners like “Fantastik or Mr. Clean”. After cleaning, wipe entire exterior of the tower with a damp cloth. **(Do not use strong soaps, abrasive cleaners or any cleaner that contains Alcohol)** Dry the tower with a clean cloth.
- E. The painted tower surface may be waxed after cleaning using “Simoniz” paste wax, Aero Wax or Glo-Coat. After applying wax, buff the surface with a clean dry cloth to a high luster finish.

## 2. Clean Dispensing Valves, Post-Mix

- A. Remove the valve cover(s) and wash in plain water.
- B. Remove the nozzle and the syrup diffuser and wash the parts in plain water.

**IMPORTANT:** When washing the dispensing valve, care must be taken not to get water on the electrical solenoid.

- C. Hold an appropriate container under the dispensing valve. Being very careful not to get water on the electrical solenoid, slowly pour plain water over the dispensing valve.
- D. Install the nozzle and syrup diffuser on the valve.
- E. Install the valve cover(s).

## 3. Clean Dispensing Valves, Pre-Mix

- A. Pour clean water over the valve to rinse away any sticky residue.
- B. Using a small round nylon bristle brush, clean the valve spout with plain water.
- C. Dry the valve with a clean dry cloth.

## 4. Clean and Sanitize Ice Bin, Drains and Drip Tray

**IMPORTANT:** Only trained and qualified persons should perform these cleaning and sanitizing procedures.

**Sanitizing Solution** - Household liquid bleach that contains 5.25% sodium hypochlorit concentration, (such as Hi-Lex or Chlorox).

Prepare the sanitizing solution by mixing 0.5-ounces of household bleach to one gallon of potable water. This mixture must not exceed 200 PPM of chorine, allowable by the FDA. Use this mixture for all sanitizing procedures.

- A. Remove all ice from the ice bin and melt any remaining ice with hot water.
- B. Remove ice bin drain strainer by lifting straight up.
- C. Prepare a mild detergent solution in 120° F potable water.  
DO NOT use water hotter than 120° F
- D. Using a nylon bristle brush (**Do Not use a wire brush**), clean the cold plate and the interior of the ice bin with the detergent solution.
- E. Pour the remainder of the detergent solution down the drip tray and bin drains. Observe that the solution flows freely. If not, determine the cause. It may be necessary to replace the drain tubing.

- F. Prepare two or more gallons of sanitizing solution. Pour half of the solution down the bin and drip tray drains. After the has completely drained, pour the remaining solution down the drains.
- G. Replace the drain strainer.
- H. Using a mechanical spray bottle, prepare sanitizing solution and spray the entire interior bin surfaces. Allow to air dry.

#### 5. Sanitize Tank Systems, Post-Mix and Pre-Mix

- A. Remove all ice from the ice bin and melt any remaining ice with hot water.
- B. Remove all the quick disconnects from all the tanks.
- C. Prepare a mild detergent soap solution in 100° F potable water in a suitable pail or bucket.
- D. Submerge all disconnects (gas and liquid) in the soap solution and then clean them using a nylon bristle brush (**Do Not use a wire brush**). Rinse with clean water.
- E. Prepare sanitizing solution and using a mechanical spray bottle, spray the disconnects. Allow to air dry.
- F. Using a clean, empty tank, prepare five gallons of sanitizing solution. Rinse the tank disconnects with approximately 9 oz. of the sanitizing solution. Close the tank.
- G. Connect a gas disconnect to the tank and then apply one of the product tubes to the tank of sanitizing solution. Operate the appropriate valve until the sanitizing solution is flowing from the valve.
- H. Repeat the step above, applying a different product tube each time until all tubes are filled with the sanitizing solution.
- I. For post-mix valves, remove the nozzle and syrup diffuser and clean them in a mild detergent soap solution. Rinse with clean water and reassemble the nozzle and syrup diffuser to the valve.
- J. For pre-mix valves, disconnect all product tubes from the tank of sanitizing solution and then open the valves to allow the pressure to be relieved. Remove the valves from the dispenser, disassemble and wash thoroughly in a mild detergent soap solution.
- K. Rinse the parts in clean water, reassemble the valve and reconnect it to the dispenser.
- L. Allow the sanitizing solution to remain in the tubes for the manufacturer's recommended exposure time.
- M. Discard the tank of sanitizing solution and connect the disconnects to a tank of potable water. Operate the valves until all sanitizer has been flushed from the system and only water is flowing.
- N. Connect the disconnects to the appropriate product tanks and operate each valve until all water is purged from the tubing.

#### 6. Sanitize Syrup Lines, B-I-B Systems

- A. Remove all ice from the ice bin and melt any remaining ice with hot water.
- B. Remove all the quick disconnects from all the B-I-B containers.
- C. Prepare a mild detergent soap solution in 100° F potable water in a suitable pail or bucket.
- D. Submerge all disconnects in the soap solution, then clean them using a nylon bristle brush (**Do Not use a wire brush**). Rinse with clean water.
- E. Using a plastic pail, prepare approximately five gallons of sanitizing solution.

- F. Rinse the B-I-B disconnects in the sanitizing solution.
- G. Sanitizing fittings must be attached to each B-I-B disconnect. If these fittings are not available, the fittings from empty B-I-B bags can be cut from the bags and used. These fittings open the disconnect so the sanitizing solution can be drawn through the disconnect.
- H. Place all the B-I-B disconnects into the pail of sanitizing solution. Operate all the valves until the sanitizing solution is flowing from the valve.
- I. Remove the nozzle and syrup diffuser from the valve and clean them in a mild detergent soap solution. Rinse with clean potable water and reassemble the nozzle and syrup diffuser to the valve.
- J. Allow the sanitizing solution to remain in the tubes for the manufacturer's recommended exposure time.
- K. Remove the sanitizing fittings from the B-I-B disconnects and place them in a container of potable water. Operate the valves until all the sanitizing solution has been purged from the tubing.
- L. Connect the disconnects to the appropriate B-I-B container. Operate the valves until all water has been flushed from the system and syrup is flowing freely.

## CO<sub>2</sub> SETTINGS

**IMPORTANT: The settings shown below are nominal settings and they may not satisfy your system. If your installer or serviceperson has indicated other pressure settings to you, please adhere to those settings. If your system is not performing to your satisfaction, call your serviceperson. DO NOT make adjustments without consulting with a qualified serviceperson.**

The CO<sub>2</sub> regulators should be set as indicated in the following chart:

<b>Post-Mix</b>	
<b>Regulator</b>	<b>Pressure Setting</b>
Primary (Carbonator)	90 – 120 PSI
Secondary, Sugared Syrup Tank	55 PSI
Secondary, Diet Syrup Tank	8 – 12 PSI
Secondary, B-I-B	60 PSI
<b>Pre-Mix</b>	
Basic Pressure	47 PSI
For each 10 ft. of horizontal tubing between tank and dispenser	Add 1 PSI
For each 2 ft. of elevation	Add 1 PSI
For each tank per flavor over 3 tanks	Add 1 PSI
Basic pressure shown is based on ambient temperature of 72°F. Use a Cornelius Pre-Mix slide rule for exact calculations.	

# DRINK DISPENSER VALVES

IMI CORNELIUS INC.  
MASON CITY IA.  
DRINK DISPENSERS

**VALVE TYPE**  
MANUFACTURER

<b><u>PORTION CONTROL</u></b>	<b><u>MAXIMUM OPERATING PRESSURE</u></b>
CORNELIUS	130 psi
LANCER	100psi
FLOWMATIC	100psi
McCANN	130psi
<b><u>PUSH BUTTON</u></b>	
CORNELIUS	130psi
LANCER	100psi
FLOWMATIC	100psi
McCANN	130psi
<b><u>LEVER TYPE</u></b>	
CORNELIUS	130psi
LANCER	100psi
FLOWMATIC	100psi
McCANN	130psi
<b><u>AUTOFILL LEVER</u></b>	
CORNELIUS	130psi
LANCER	100psi
FLOWMATIC	100psi
McCANN	130psi
<b><u>NON-ELECTRIC</u></b>	
CORNELIUS	130psi
LANCER	100psi
<b><u>PREMIX TYPE</u></b>	
CORNELIUS	130psi

# TROUBLESHOOTING

## TROUBLESHOOTING

Trouble	Probable Cause	Remedy
WATER-TO-SYRUP "RATIO" TOO LOW OR TOO HIGH	A. Dispensing valve syrup flow regulator not properly adjusted.	A. Adjust Water-to-Syrup "Ratio" of dispensed drink as instructed.
	B. CO <sub>2</sub> gas pressure to syrup tanks insufficient to push syrup out of tank or to pump from the B-I-B container.	B. Adjust syrup tanks secondary CO <sub>2</sub> regulator as instructed.
ADJUSTMENT OF DISPENSING VALVE SYRUP FLOW REGULATOR DOES NOT INCREASE TO DESIRED WATER-TO-SYRUP "RATIO"	A. Dispensing valve syrup flow regulator, syrup tank quick disconnect, or syrup line restricted.	A. Sanitize syrup system as instructed.
	B. Syrup tank quick disconnects not secure.	B. Secure quick disconnects.
	C. Syrup tanks secondary CO <sub>2</sub> regulator out of adjustment.	C. Adjust syrup tanks secondary CO <sub>2</sub> regulator as instructed.
	D. No syrup supply.	D. Replenish syrup supply.
	E. Improper syrup Baume.	E. Replace syrup supply.
	F. Dirty or inoperative piston or spring in dispensing valve syrup flow regulator.	F. Disassemble and clean dispensing valve syrup flow regulator.
	G. Tapered nylon washer inside tube swivel nut connector distorted from being overtightened.	G. Replace nylon washer and make sure it seats properly.
ADJUSTMENT OF DISPENSING VALVE SYRUP FLOW REGULATOR DOES NOT DECREASE TO DESIRED WATER-TO-SYRUP "RATIO"	A. Dirty or inoperative piston or spring in dispensing valve syrup flow regulator.	A. Disassemble and clean dispensing valve syrup flow regulator.

Trouble	Probable Cause	Remedy
DISPENSED PRODUCT CARBONATION TOO LOW	A. Carbonator primary CO <sub>2</sub> regulator out of adjustment for existing water conditions or temperature.	A. Adjust carbonator primary CO <sub>2</sub> regulator (Reference manual provided with carbonator).
	B. Air in carbonator tank.	B. Vent air out of carbonator tank through relief valve. Actuate dispensing valve carbonated water lever to make carbonator pump cycle on.
	C. Water, oil, or dirt, in CO <sub>2</sub> supply.	C. Remove contaminated CO <sub>2</sub> . Clean CO <sub>2</sub> system (lines, regulators, etc.) using a mild detergent. Install a clean CO <sub>2</sub> supply.
DISPENSED PRODUCT COMES OUT OF DISPENSING VALVE CLEAR BUT FOAMS IN CUP OR GLASS	A. Oil film or soap scum in cup or glass.	A. Use clean cup or glass.
	B. Ice used for finished drink is sub-cooled.	B. Do not use ice directly from freezer. Allow ice to become "wet" before using. (Refer to following <b>NOTE</b> ).
<b>NOTE: Crushed ice in the glass also causes dispensing problems. When finished drink hits sharp edges of ice, carbonation is released from dispensed drink.</b>		
	C. Carbonator CO <sub>2</sub> regulator pressure too high for existing water conditions or temperature.	C. Reduce carbonator CO <sub>2</sub> regulator pressure setting. (Reference manual provided with carbonator).
	D. Syrup over-carbonated with CO <sub>2</sub> as indicated by bubbles in inlet syrup lines leading to unit.	D. Remove syrup tanks quick disconnects. Relieve tank CO <sub>2</sub> pressure, shake tank vigorously, then relieve tank CO <sub>2</sub> pressure as many times as necessary to remove over-carbonation.

Trouble	Probable Cause	Remedy
DISPENSED PRODUCT PRODUCES FOAM AS IT LEAVES DISPENSING VALVE	A. Dispensing valve restricted or dirty.	A. Sanitize syrup system as instructed.
	B. Tapered nylon washer inside carbonated water line swivel nut connector distorted restricting carbonated water flow.	B. Replace nylon washer. Make sure it is properly seated.
	C. Dirty water supply.	C. Check water filter. Replace cartridge. (see <b>NOTE</b> )
	D. Warm Product - No ice in bin, bridged ice on cold plate or plugged drain.	D. Replenish ice, break ice up to eliminate bridging, unplug the drain.
<b>NOTE: If water supply is dirty, be sure to flush lines and carbonator completely. It may be necessary to remove lines to carbonator tank, invert tank, and flush tank and all inlet lines to remove any foreign particles or dirt.</b>		
NO PRODUCT DISPENSED FROM ALL DISPENSING VALVES	A. Transformer unplugged.	A. Plug in the transformer.
	B. No electrical power to transformer.	B. Check fuse or circuit breaker.
	C. Disconnected dispensing valves power cord.	C. Connect dispensing valves power cord.
	D. Disconnected or broken wiring to dispensing valves.	D. Connect or replace wiring.
	E. Inoperative transformer.	E. Replace transformer as instructed.
NO PRODUCT DISPENSED FROM ONE DISPENSING VALVE	A. Broken or disconnected wiring.	A. Repair or connect wiring.
	B. Inoperative dispensing valve solenoid coil.	B. Replace solenoid coil as instructed.
	C. Inoperative dispensing valve micro switch.	C. Replace micro switch as instructed.



Trouble	Probable Cause	Remedy
ONLY CARBONATED WATER DISPENSED	A. Quick disconnects not secure on syrup tanks.	A. Secure quick disconnects on syrup tanks.
	B. Out of syrup.	B. Replenish syrup supply as instructed.
	C. B-I-B connectors not properly connected.	C. Properly attach the connectors.
	D. Syrup secondary CO <sub>2</sub> regulator not properly adjusted.	D. Adjust syrup tanks secondary CO <sub>2</sub> regulator as instructed.
	E. Inoperable dispensing valve.	E. Repair dispensing valve.
	F. Dispensing valve syrup flow regulator not properly adjusted.	F. Adjust dispensing valve syrup flow regulator (Water-to-Syrup "Ratio") as instructed.
	G. Dispensing valve syrup flow regulator, syrup tank quick disconnect, or syrup lines restricted.	G. Sanitize syrup system as instructed.
ONLY SYRUP DISPENSED	A. Plain water inlet supply line shutoff valve closed.	A. Open plain water inlet supply line shutoff valve.
	B. Carbonator power cord unplugged from electrical outlet.	B. Plug carbonator power cord into electrical outlet.
	C. Carbonator primary CO <sub>2</sub> regulator not properly adjusted.	C. Adjust carbonator primary CO <sub>2</sub> regulator (Reference manual provided with carbonator).

# WARRANTY

IMI Cornelius Inc. warrants that all equipment and parts are free from defects in material and workmanship under normal use and service. For a copy of the warranty applicable to your Cornelius product, in your country, please write, Fax or telephone the IMI Cornelius office nearest you. Please provide the equipment model number and the date of purchase.

## IMI Cornelius Offices

AUSTRALIA ● P.O. 210, ● RIVERWOOD, ● NSW 2210, AUSTRALIA ● (61) 2 533 3122 ● FAX (61) 2 534 2166  
AUSTRIA ● AM LANGEN FELDE 32 ● A-1222 ● VIENNA, AUSTRIA ● (43) 1 233 520 ● FAX (43) 1-2335-2930  
BELGIUM ● BOSKAPPELLEI 122 ● B-2930 BRAASCHAAT, BELGIUM ● (32) 3 664 0552 ● FAX (32) 3 665 2307  
BRAZIL ● RUA ITAOCARA 97 ● TOMAS COELHO ● RIO DE JANEIRO, BRAZIL ● (55) 21 591 7150 ● FAX (55) 21 593 1829  
ENGLAND ● TYTHING ROAD ALCESTER ● WARWICKSHIRE, B49 6 EU, ENGLAND ● (44) 789 763 101 ● FAX (44) 789 763 644  
FRANCE ● 71 ROUTE DE ST. DENIS ● F-95170 DEUIL LA BARRE ● PARIS, FRANCE ● (33) 1 34 28 6200 ● FAX (33) 1 34 28 6201  
GERMANY ● CARL LEVERKUS STRASSE 15 ● D-4018 LANGENFELD, WEST GERMANY ● (49) 2173 7930 ● FAX (49) 2173 77 438  
GREECE ● 488 MESSOGION AVENUE ● AGIA PARASKEVI ● 153 42 ● ATHENS, GREECE ● (30) 1 600 1073 ● FAX (30) 1 601 2491  
HONG KONG ● 1104 TAIKOTSUI CENTRE ● 11-15 KOK CHEUNG ST ● TAIKOKTSUE, HONG KONG ● (852) 789 9882 ● FAX (852) 391 6222  
ITALY ● VIA PELLIZZARI 11 ● 1-20059 ● VIMARCATI, ITALY ● (39) 39 608 0817 ● FAX (39) 39 608 0814  
NEW ZEALAND ● 20 LANSFORD CRES. ● P.O. BOX 19-044 AVONDALE ● AUCKLAND 7, NEW ZEALAND ● (64) 9 8200 357 ● FAX (64) 9 8200 361  
SINGAPORE ● 16 TUAS STREET ● SINGAPORE 2263 ● (65) 862 5542 ● FAX (65) 862 5604  
SPAIN ● POLIGONO INDUSTRIAL ● RIERA DEL FONOLLAR ● E-08830 SANT BOI DE LLOBREGAT ● BARCELONA, SPAIN ● (34) 3 640 2839 ● FAX (34) 3 654 3379  
USA ● ONE CORNELIUS PLACE ● ANOKA, MINNESOTA ● (612) 421-6120 ● FAX (612) 422-3255