

CRAFTSMAN®

947626

To Remove Harmonic Balancer:

Before removing harmonic balancer, it may be necessary to first remove the radiator.

1. Remove the retaining bolt from the balancer.
2. Carefully choose the proper size bolts that fit the holes in the balancer. This kit includes:
 - Three black oxide-plated 3/8-24 x 2-in. fine pitch bolts
 - Three zinc-plated 5/16-18 x 2-in. coarse pitch bolts
 - Three yellow-plated M8-1.25 x 80mm metric bolts
 - Two black oxide-plated 3/8-16 4-in. coarse pitch bolts
3. Insert bolts through the slots in the puller, making sure that the washer head rests on the FLAT side of the casting.
4. Carefully thread the bolts into the balancer evenly.
5. Select the flat or pointed cap, as needed, and fit over the end of the large center forcing screw. Turn forcing screw slowly until balancer is removed.

To Remove Steering Wheel:

1. **DO NOT** use a hammer to remove the steering wheel. Damage to the wheel can result.
2. Select the bolts included that **EXACTLY** match the hole diameter and pitch with those on the steering wheel. If the bolts do not match, do not use this puller.
3. Check for alignment marks on the wheel and shaft. If there are no marks, make them on the wheel before removing it to help ease re-alignment during assembly.
4. Insert bolts through puller casting and screw into wheel. Make sure the washer head of the bolt is seated on the FLAT side of the casting.
5. Turn the large forcing screw slowly until the wheel is removed.



FULL UNLIMITED WARRANTY ON CRAFTSMAN HAND TOOLS

If this Craftsman Hand Tool ever fails to provide complete satisfaction, RETURN IT TO THE NEAREST SEARS STORE OR OTHER CRAFTSMAN OUTLET and it will be replaced, free of charge.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Sears, Roebuck and Co., Dept. 817WA, Hoffman Estates, IL 60179

NOTE: Always wear safety glasses or eye shields.

CONTENTS MADE IN USA
Sold by Sears, Roebuck and Co.
Hoffman Estates, IL 60179