TANK

COMMERCIAL ZERO-TURN RIDERS WITH SYNCHRO STEER TECHNOLOGY

TANK™ S 6031 TANK™ S 7237 TANK™ S 6032 D TANK™ S 7232 D TANK™ S 6031 LP TANK™ S 7237 LP

FEATURES

SELECT CUT SYSTEM™ DECK

CUTS UP TO 7 ACRES PER HOUR

FULLY HYDRAULIC POWER STEERING

HYDRAULIC POWER DECK LIFT

ADJUSTABLE STEERING COLUMN

......

REMOTE COOLING SYSTEM

PROVEN TANK®

31 AND 37 HP GAS, LIQUID PROPANE AND DIESEL OPTIONS WITH 60" AND 72" DECKS

3-YEAR LIMITED COMMERCIAL WARRANTY[†]

COMMERCIA



BUILD A BUSINESS THAT'S SECOND TO NONE WITH A RIDER THAT'S THE FIRST OF ITS KIND.

The TANK™S Series doesn't just get the job done. It gets it done faster, easier and better than you ever thought possible. Cub Cadet Commercial's unique Synchro Steer™ technology offers you four-wheel directional steering for added stability on hillsides and easier operation on the toughest terrain. And now you can choose between gas, diesel or liquid propane engines, so you get more of what you really want: control.

SEE HOW THESE FEATURES HELP YOU GET THE JOB DONE RIGHT AT CUBCADETCOMMERCIAL.COM.



EASIER TO OPERATE

Innovative features include a fully intuitive adjustable steering wheel with hydraulic power steering and forward and reverse foot pedals.



GREATER STABILITY AND MANEUVERABILITY

Synchro Steer™ technology offers four-wheel directional steering, unlike standard zero-turns. The TANK™ S Series also makes true zero-degree turns and tight maneuvers around any obstacle.



SELECT CUT SYSTEM™ DECK

The TANK™ S Series is equipped with an innovative sloped-nose front skirt, configurable inner baffle, offset and adjustable leading edges, ball wheels, and the SmartJet™ deck washing system.

WHAT THAT MEANS TO YOU

You spend less time learning controls and more time working in comfort, so you can remain productive all day long.

You get full control on hills and steep areas that often need a walk-behind. And, you can make tight turns around plants, shrubs and walkways — while avoiding turf damage.

You get clean cuts in any grass or terrain condition — and cleanup is quick and easy.

YOUR INDEPENDENT DEALER CAN ANSWER ALL YOUR QUESTIONS ABOUT THE MANY BENEFITS OF OWNING A CUB CADET.

LOCATE A DEALER AT CUBCADETCOMMERCIAL.COM

LOOKS LIKE INNOVATION RUNS IN THE FAMILY.

THE TANK S, TANK S DIESEL AND TANK S LIQUID PROPANE ZERO-TURN RIDERS.

GAS - SMOOTH AND DEPENDABLE.

The Kawasaki® 31 and 37 HP* V-Twin gas engines deliver both high performance and smooth operation with the convenience of gasoline power. Its superior cold-starting capabilities make it a dependable machine no matter what season or application you're tackling. Plus, the quieter operation also makes for a more comfortable — and more productive — workday.



DIESEL - DURABLE AND RELIABLE.

Powered by a 31.2 HP* Yanmar engine, the TANK S D runs cleanly, quietly and efficiently. The direct-injection engine produces steady and constant horsepower no matter the job. Plus, it has a higher torque reserve than the competitors' diesel engines, giving the operator more power so that they can get more done. Combine all that with superior reliability, durability and fuel economy and you've got a machine that can handle the rigorous commercial workload — day in and day out.

LIQUID PROPANE - CLEAN, SMART AND EFFICIENT.

If you are looking for a zero-turn rider that is good for the environment and also for your wallet, look no further than the TANK S LP. Liquid propane, in comparison to gas and diesel fuel, reduces smog-forming emissions by 60% and reduces toxic emissions by 80%. In fact, the TANK S LP meets all current emission requirements set by the EPA and CARB. Plus, liquid propane increases engine life and run times. But the best part — liquid propane is significently cheaper than gasoline or diesel fuel. So with the TANK S LP, you're not just helping the environment, you're helping yourself.



ATTACHMENTS

THAT BOOST PRODUCTIVITY ALL YEAR ROUND

Whether you're working through the heat of summer or the dead of winter, our attachments are made to boost your earning potential the whole year through. So you can maximize your profits while getting the best results possible.



COLLECTION SYSTEM WITH POWER ASSIST DUMP HOPPER Fits 60" deck only.



TRIPLE BAGGER Fits 60" deck only.



ULTRA-TRACTION TIRES



12-VOLT OUTLET



FUEL GAUGE



FULLY ENCLOSED CAB



SPREADER



MULCH KIT

Safety shield and toe guard must remain installed after mulch kit is added.



LIGHT KIT



SNOW BLADE

TANK COMMERCIAL ZERO-TURN RIDERS

IANI	COMMERCIAL	ZERO-TURN RIDER		
ENGINE	TANK [™] S 6031	TANK [™] S 7237		
Engine type	31 HP* Kawasaki® V-Twin OHV	37 HP* Kawasaki® V-Twin OHV		
Engine displacement/orientation	852cc/vertical	999cc/vertical		
Engine fuel	•	- Gas ──•		
Ignition	Capacitor discharge ignition (CDI) →			
Lubrication/filter	← Full pressure	e w/spin-on oil filter →		
Cooling system	•	–Air——•		
Air cleaner	Heavy-duty remote -	– replaceable dual element		
Alternator	•——12V - 15	amp. regulated ——•		
Fuel capacity	← Twin 7-gal. t	tanks w/fuel gauge →		
DRIVE SYSTEM				
Drive system	Dual Hydro-Gear™ PK-12 pumps & 310cc Parker wheel motors			
Ground speed	•——Fwd: 10 mph/Rev: 5 mph ——•			
Hydraulic fluid	Shell Rimula® — 15W40 and remote cooling system			
Hydro fluid capacity	•			
Hydraulic oil filter	- Standard, 25-micron cartridge type →			
Controls	Individual forward, reverse and park brake foot pedals			
Lock to lock turns (steering wheel)	2 turns/multi-position	n steering wheel and column		
Braking/parking brake	Expansion shoe/drum			
STEERING				
Power steering (front wheels)	Fully hydraulic power steer	ring w/Synchro Steer™ technology		
Front axle		, cast-iron axle		
CHASSIS				
Frame	Fully welded 2", heavy-	duty tubular steel (wide-track)		
TIRES				
Front tire size	•—16" x 6.5" −	8" (Turf Trac R/S) →		
Rear tire size	•—24" x 12" −	12" (Turf Master®) —◆		
DIMENSIONS				
Length x width x height	89" x 62" x 72"	89" x 74" x 72"		
Wheelbase	•	− 54" ──		
Front tread width	•	49.5"		
Rear tread width	•	- 58"•		
Weight (approx.)	1,470 lbs.	1,540 lbs.		
MOWING DECK				
Deck size/type	60" Select Cut System™	72" Select Cut System™		
Deck style/system	← 6-point susp	ension, full floating —•		
Deck blades	Three 21," high lift with	Three 25," med. lift with		
Deck biddes	extended cutting edge	extended cutting edge		
Deck construction		steel skirt, 3/8" rub guard, 1/4" adjustable ge reinforcements at spindle assemblies		
Deck wash	Patented SmartJet [™] high	-pressure deck washing system		
Deck lift	Dash-mount control l	ever w/hydraulic lift system		
Deck height adjustment	•—1" − 5" (in	.25" increments) ——•		
Blade spindle construction		I cast-aluminum housing pered roller bearings		
PTO engagement	-	T 3.5/250 ft. lb.——•		
Front anti-scalping wheels	4 standard, greasable	4 standard, greasable		
Rear anti-scalping rollers/striper	Full-width adjustable striper	Full-width adjustable striper/		
Deck PTO	← Electronic fir	ngertip engagement →		
ADDITIONAL SPECIFICATIONS				
ROPS		HA-1928 compliant) →		
Monitor/hour meter		ometer/maintenance minder		
Seat type/motion range front/rear		ension, lumbar and armrests back w/8.25" of travel		
Cup holder	Accommodates r	multiple-size containers		
Storage pouch	•———S	Standard ——•		
Bumper & rear hitch	Heavy-duty bump	er w/rear hitch standard		
WARRANTY [†]				

^{*}as rated by engine manufacturer

 $\label{lem:commercial} \mbox{Commercial products are intended for professional use}.$

 $^{^\}dagger \, \text{See}$ your local Cub Cadet Independent Commercial Dealer for warranty details.





NGINE	TANK™ S 6032 D	TANK™ S 7232 D	TANK™S 6031 LP	TANK™ S 7237 LP
	31.2 HP* Yanmar® Diesel	31.2 HP* Yanmar® Diesel	Kawasaki® V-Twin	Kawasaki® V-Twin
Engine type	3-cylinder OHV	3-cylinder OHV	(Liquid Propane Powered)	(Liquid Propane Powered)
Maximum torque	63.9 lbft. @ 1,200 RPM	63.9 lbft. @ 1,200 RPM	n/a	n/a
Engine displacement/orientation	1.33L/horizontal	1.33L/horizontal	852cc/vertical	999cc/vertical
Engine fuel	Diesel #2 (low sulfur) B-20	Diesel #2 (low sulfur) B-20	Liquid propane	Liquid propane
gnition	Direct injection w/glow plug	Direct injection w/glow plug	CDI	CDI
_ubrication/filter	Full-pressure trochoid pump w/spin-on oil filter	Full-pressure trochoid pump w/spin-on oil filter	Full-pressure pump w/spin-on oil filter	Full-pressure pump w/spin-on oil filter
Cooling system	Liquid w/high-output remote fan	Liquid w/high-output remote fan	Air	Air
Air cleaner	•	Heavy-duty remote — r	eplaceable dual element —————	•
Alternator	12V - 40 amp. regulated	12V – 40 amp. regulated	12V – 15 amp. regulated	12V – 15 amp. regulated
- uel capacity	Twin 7-gal. tanks w/fuel gauge	Twin 7-gal. tanks w/fuel gauge	Twin 33-lb. LPG vapor system tanks	Twin 33-lb. LPG vapor system tar
RIVE SYSTEM				
Orive system	•	—— Dual Hydro-Gear™ PK-12 pump	s & 310cc Parker wheel motors ——	•
Ground speed	• Fwd: 10 mph/Rev: 5 mph -			
Hydraulic fluid	Rimula® — 15W40 & remote cooling system			
lydro fluid capacity			v/filter —	
Hydraulic oil filter	•		artridge type —	•
Controls			e & park brake foot pedals —	
ock to lock turns (steering wheel)	•		teering wheel & column	
Braking/parking brake	•	· ·	shoe/drum	•
		Expansion	, wi wiii	
TEERING		Follows to the Control of the Control	/C	
Power steering (front wheels)	•		w/Synchro Steer™ technology ——	•
Front axle	•	Pivoting w/c	ast-iron axie	•
HASSIS				
rame	•	Fully-welded 2", heavy-dut	y tubular steel (wide-track) ————	•
IRES				
Front tire size	•	16" x 6.5" - 8"	(Turf Trac R/S) —	•
Rear tire size	•	24" x 12" - 12"	(Turf Master®) ————————————————————————————————————	•
IMENSIONS				
ength x width x height				
	90" x 62" x 72"	90" x 74" x 72"	90" x 62" x 72"	90" x 74" x 72"
	90" x 62" x 72"	90" x 74" x 72"	90" x 62" x 72" 4"	90" x 74" x 72"
Wheelbase	90" x 62" x 72"	5	4"	90" x 74" x 72"
Wheelbase Front tread width	90" x 62" x 72"		4"	90" x 74" x 72"
Wheelbase Front tread width Rear tread width	•		4"	•
Wheelbase Front tread width Rear tread width Weight (approx.)	90" x 62" x 72" 1,850 lbs.		4"	90" x 74" x 72"
Wheelbase Front tread width Rear tread width Weight (approx.) OWING DECK	1,850 lbs.		4"	1,545 lbs.
Vheelbase Front tread width Rear tread width Veight (approx.) OWING DECK Deck size/type	•	5 49 5 1,890 lbs. 72" Select Cut System	4"	•
Wheelbase Front tread width Rear tread width Weight (approx.) IOWING DECK Deck size/type Deck style/system	1,850 lbs. 60" Select Cut System™ Three 21" high lift with	5. 499 lbs. 72" Select Cut System™ 6-point suspens	4" 1.5" 8" 1,474 lbs. 60" Select Cut System** sion, full floating Three 21" high lift with	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with
Wheelbase Front tread width Rear tread width Weight (approx.) OWING DECK Deck size/type Deck style/system Deck blades	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	5	4" 1.5" 8" 1,474 lbs. 60" Select Cut System** sion, full floating Three 21" high lift with extended cutting edge	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Vheelbase Front tread width Rear tread width Veight (approx.) OWING DECK Deck size/type Deck style/system Deck blades	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	5	4" 1.5" 8" 1,474 lbs. 60" Select Cut System** sion, full floating Three 21" high lift with extended cutting edge	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Vheelbase Front tread width Rear tread width Veight (approx.) OWING DECK Deck size/type Deck style/system Deck blades Deck construction	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	5	4" 1.5" 8" 1,474 lbs. 60" Select Cut System™ sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustableinforcements at spindle assemblies	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Vheelbase Front tread width Rear tread width Weight (approx.) OWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	5. 49 1,890 lbs. 72" Select Cut System™ 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge steeleading edge and 7- and 10-gauge re—Patented SmartJet™ high-pre	4" 1.5" 8" 1,474 lbs. 60" Select Cut System™ sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustableinforcements at spindle assemblies	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Wheelbase Front tread width Rear tread width Weight (approx.) OWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	72" Select Cut System 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge ster leading edge and 7- and 10-gauge re Patented SmartJet* high-pre Dash-mount control leve	4" 1.5" 8" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable einforcements at spindle assemblies essure deck washing system	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Wheelbase Front tread width Rear tread width Weight (approx.) OWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	72" Select Cut System 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge ster leading edge and 7- and 10-gauge re Patented SmartJet* high-pre Dash-mount control leve	4" 4" 4" 8" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable einforcements at spindle assemblies essure deck washing system er w/hydraulic lift system "increments)	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Wheelbase Front tread width Rear tread width Weight (approx.) OWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	5. 499 1,890 lbs. 72" Select Cut System™ 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge stelleading edge and 7- and 10-gauge re Patented SmartJet™ high-pre Dash-mount control leve	4" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable inforcements at spindle assemblies essure deck washing system or w/hydraulic lift system "increments) ing w/greasable tapered roller bearing	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Wheelbase Front tread width Rear tread width Weight (approx.) OWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	72" Select Cut System" 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge steleading edge and 7- and 10-gauge releading edge and releading	4" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable inforcements at spindle assemblies essure deck washing system or w/hydraulic lift system "increments) ing w/greasable tapered roller bearing	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Wheelbase Front tread width Rear tread width Weight (approx.) IOWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction PTO engagement Front anti-scalping wheels Rear anti-scalping rollers/striper	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	72" Select Cut System" 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge steleading edge and 7- and 10-gauge releading edge and releading	4" 1,474 lbs. 60" Select Cut System" 60" Select Cut System" Sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable inforcements at spindle assemblies essure deck washing system er w/hydraulic lift system "increments) ing w/greasable tapered roller bearing 5/250 ft. lb.	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Wheelbase Front tread width Rear tread width Weight (approx.) IOWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction PTO engagement Front anti-scalping wheels Rear anti-scalping rollers/striper	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge D	72" Select Cut System 1,890 lbs. 72" Select Cut System 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge stere leading edge and 7- and 10-gauge re Patented SmartJet" high-pre Dash-mount control leve 1" - 5" (in .25) urable machined cast-aluminum hous Ogura GT 3. 4 standard Full-width adjustable striper/ 2 corner rollers	4" 1,474 lbs. 60" Select Cut System* sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable inforcements at spindle assemblies essure deck washing system by whydraulic lift system "increments) ing w/greasable tapered roller bearing 5/250 ft. lb. greasable	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Vheelbase Front tread width Rear tread width Veight (approx.) OWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction PTO engagement Front anti-scalping wheels Rear anti-scalping rollers/striper Deck PTO	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge D	72" Select Cut System 1,890 lbs. 72" Select Cut System 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge stere leading edge and 7- and 10-gauge re Patented SmartJet" high-pre Dash-mount control leve 1" - 5" (in .25) urable machined cast-aluminum hous Ogura GT 3. 4 standard Full-width adjustable striper/ 2 corner rollers	4" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable inforcements at spindle assemblies essure deck washing system er w/hydraulic lift system "increments) ing w/greasable tapered roller bearing 5/250 ft. lb. , greasable Full-width adjustable striper	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Wheelbase Front tread width Rear tread width Weight (approx.) OWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction PTO engagement Front anti-scalping wheels Rear anti-scalping rollers/striper Deck PTO DDITIONAL SPECIFICATIONS	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge D	72" Select Cut System" 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge ster leading edge and 7- and 10-gauge re Patented Smart Jet" high-pro Dash-mount control leve 1" - 5" (in .25) urable machined cast-aluminum hous Ogura GT 3. 4 standard Full-width adjustable striper/ 2 corner rollers Electronic finge	4" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable inforcements at spindle assemblies essure deck washing system er w/hydraulic lift system "increments) ing w/greasable tapered roller bearing 5/250 ft. lb. , greasable Full-width adjustable striper	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Wheelbase Front tread width Rear tread width Weight (approx.) IOWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction PTO engagement Front anti-scalping wheels Rear anti-scalping rollers/striper Deck PTO DDITIONAL SPECIFICATIONS ROPS	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge D	72" Select Cut System" 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge ster leading edge and 7- and 10-gauge re Patented Smart Jet" high-proposed for the system of t	4" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable einforcements at spindle assemblies essure deck washing system whydraulic lift system increments) ing w/greasable tapered roller bearing 5/250 ft. lb. , greasable Full-width adjustable striper	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Wheelbase Front tread width Rear tread width Weight (approx.) IOWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction PTO engagement Front anti-scalping wheels Rear anti-scalping rollers/striper Deck PTO DDITIONAL SPECIFICATIONS ROPS Monitor/hour meter	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	72" Select Cut System" 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge ster leading edge and 7- and 10-gauge re Patented Smart Jet" high-proposed for the system of t	4" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable einforcements at spindle assemblies essure deck washing system or w/hydraulic lift system "increments) ing w/greasable tapered roller bearing 5/250 ft. lb. , greasable Full-width adjustable striper rtip engagement SHA-1928 compliant) naintenance minder	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge
Wheelbase Front tread width Rear tread width Weight (approx.) IOWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction PTO engagement Front anti-scalping wheels Rear anti-scalping rollers/striper Deck PTO DDITIONAL SPECIFICATIONS ROPS Monitor/hour meter Seat type/motion range front/rear	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	72" Select Cut System" 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge ster leading edge and 7- and 10-gauge re Patented SmartJet" high-pr Dash-mount control leve 1" - 5" (in .25 urable machined cast-aluminum hous Ogura GT 3. 4 standard Full-width adjustable striper/ 2 corner rollers Electronic finge Standard foldable (O Hour/tachometer/n	4" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable einforcements at spindle assemblies essure deck washing system or w/hydraulic lift system "increments) ing w/greasable tapered roller bearing 5/250 ft. lb. , greasable Full-width adjustable striper rtip engagement SHA-1928 compliant) naintenance minder	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge le pgs Full-width adjustable striper 2 corner rollers
Wheelbase Front tread width Rear tread width Weight (approx.) OWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction PTO engagement Front anti-scalping wheels Rear anti-scalping rollers/striper Deck PTO DDITIONAL SPECIFICATIONS ROPS Monitor/hour meter Deat type/motion range front/rear Cup holder	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	72" Select Cut System" 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge ster leading edge and 7- and 10-gauge re Patented SmartJet" high-pr Dash-mount control leve 1" - 5" (in .25 urable machined cast-aluminum hous Ogura GT 3. 4 standard Full-width adjustable striper/ 2 corner rollers Electronic finge Standard foldable (O Hour/tachometer/n v adjustable suspension, lumbar & arn Accommodates mul	4" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable einforcements at spindle assemblies essure deck washing system whydraulic lift system increments) ing w/greasable tapered roller bearing s/250 ft. lb. , greasable Full-width adjustable striper rtip engagement SHA-1928 compliant) naintenance minder prests and reclining back w/8.25" of	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge le pgs Full-width adjustable striper 2 corner rollers
Wheelbase Front tread width Rear tread width Weight (approx.) IOWING DECK Deck size/type Deck style/system Deck blades Deck construction Deck wash Deck lift Deck height adjustment Blade spindle construction PTO engagement Front anti-scalping wheels	1,850 lbs. 60" Select Cut System™ Three 21" high lift with extended cutting edge	72" Select Cut System" 6-point suspens Three 25" med-lift with extended cutting edge 10-gauge fabricated with 7-gauge steleading edge and 7- and 10-gauge releading edge and 7- and control leve 1" - 5" (in .25 urable machined cast-aluminum hous Ogura GT 3. 4 standard Full-width adjustable striper/ 2 corner rollers Electronic finge Standard foldable (O Hour/tachometer/n dajustable suspension, lumbar & arn Accommodates mul	4" 1,474 lbs. 60" Select Cut System" sion, full floating Three 21" high lift with extended cutting edge el skirt, 3/8" rub guard, 1/4" adjustable elinforcements at spindle assemblies essure deck washing system whydraulic lift system increments) ing w/greasable tapered roller bearing s/250 ft. lb. , greasable Full-width adjustable striper rtip engagement SHA-1928 compliant) naintenance minder prests and reclining back w/8.25" of tiple-size containers	1,545 lbs. 72" Select Cut System™ Three 25" med-lift with extended cutting edge le pgs Full-width adjustable striper 2 corner rollers

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.