

CyberTAN

Product Specification

WM140

2.4GHz Draft 802.11n 1*1 miniCard Module

1. Specification

| Specifications | |
|-----------------------------|---|
| Product Name | 802.11 b/g/n Wireless LAN Module |
| Network Standards | Draft IEEE802.11n and 11 b/g -compliant |
| Data Rate | 802.11b: 11 / 5.5 / 2 / 1Mbps 802.11g: 54 / 48 / 36 / 24 / 18 / 12 / 9 / 6Mbps Draft 802.11n (20MHz, 800ns GI): 65, 58.5, 52, 39, 26, 19.5, 13, and 6.5Mbps Draft 802.11n (40MHz, 400ns GI): 135, 121.5, 108, 81, 54, 40.5, 27, and 13.5Mbps |
| Modulation | 802.11g/n---- OFDM 802.11b---- CCK (11Mbps, 5.5Mbps), QPSK (2Mbps), BPSK (1Mbps) |
| Technique | Direct Sequence Spread Spectrum(802.11b) |
| Network Architecture | Infrastructure and ad hoc |
| Operating Frequency | 2.4G 11b/g/n: 2.412 ~ 2.462 GHz: North America |
| Operating Channels | 11b: 1~11 for America 2.4GHz 11g/n: 1~11 for America |
| RF Output Power | 16dBm +/- 1.5dBm (2.4GHz, 11Mbps, CCK) 13.5Bm +/- 1.5dBm (2.4GHz, 54Mbps, OFDM) 13.5dBm +/- 1.5dBm (2.4GHz, 11n) |
| Antenna | Dipole antenna*1 |
| LED Indicators | N/A |
| Coverage Area | Indoor: 20M@54Mbps, 35M@24Mbps, 60M@6Mbps, 100M@11Mbps |

| | |
|------------------------------|--|
| Receive Sensitivity | -84 dBm @ 11M (CCK, 10% PER) -70 dBm @ 54M (2RX 11g OFDM, 10% PER) -70 dBm @ 54M (2RX 11a OFDM, 10% PER) -64 dBm @ 130Mbps (2.4GHz, 2RX 11n OFDM with 20MHz BW, 10% PER) -62 dBm @ 270Mbps (2.4GHz, 2RX 11n OFDM with 40MHz BW, 10% PER) |
| Power Consumption | TX Power consumption: < 700 mA RX Power consumption: < 460 mA |
| Operating Temperature | 0 to 60 °C |
| Humidity | 20% to 95% Non-condensing |
| Voltage | 3.3V |

2. Drivers Release Plan

| | Driver Release time | Utility Tools Release time |
|--------------|---------------------|----------------------------|
| Windows 2000 | | |
| Windows XP | | |
| Linux | | |
| VxWorks | | |

3. Compliant Approvals

3.1 Compliant Approvals

FCC Part 15 Class B, C, RSS-210

3.2 Compliant PTT approvals

Supported by customer request: USA & Canada

4. Warranty

One year limited warranty.

4.1 Warning statement

Federal Communication Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

IMPORTANT NOTE:

FCC Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

IEEE 802.11b or 802.11g operation of this product in the U.S.A. is firmware-limited to channels 1 through 11.

This device is intended only for OEM integrators under the following conditions:

- 1) The antenna must be installed such that 20 cm is maintained between the antenna and users, and
- 2) The transmitter module may not be co-located with any other transmitter or antenna,
- 3) For all products market in US, OEM has to limit the operation channels in CH1 to CH11 for 2.4G band by supplied firmware programming tool. OEM shall not supply any tool or info to the end-user regarding to Regulatory Domain change.

As long as 3 conditions above are met, further transmitter test will not be required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this module installed (for example, digital device emissions, PC peripheral requirements, etc.).

IMPORTANT NOTE: In the event that these conditions can not be met (for example certain laptop configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID can not be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC authorization.

End Product Labeling

This transmitter module is authorized only for use in device where the antenna may be installed such that 20 cm may be maintained between the antenna and users. The final end product must be labeled in a visible area with the following: "Contains FCC ID: N89-WM140".

Manual Information To the End User

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user's manual of the end product which integrates this module.

The end user manual shall include all required regulatory information/warning as show in this manual.

Industry Canada Statement

This device complies with RSS-210 of the Industry Canada Rules. Operation is subject to the following two conditions:

- 1) this device may not cause interference and
- 2) this device must accept any interference, including interference that may cause undesired operation of the device

This device has been designed to operate with an antenna having a maximum gain of 1.8dBi. Antenna having a higher gain is strictly prohibited per regulations of Industry Canada. The required antenna impedance is 50 ohms.

To reduce potential radio interference to other users, the antenna type and its gain should be so chosen that the EIRP is not more than required for successful communication.

IMPORTANT NOTE:

IC Radiation Exposure Statement:

This equipment complies with IC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

This device is intended only for OEM integrators

under the following conditions:

The transmitter module may not be co-located with any other transmitter or antenna.

As long as conduction above is met, further transmitter test will not be required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this module installed (for example, digital device emissions, PC peripheral requirements, etc.).

IMPORTANT NOTE: In the event that these conditions can not be met (for example certain laptop configurations or co-location with another transmitter), then the IC authorization is no longer considered valid and the IC ID can not be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate IC authorization.

End Product Labeling

The final end product must be labeled in a visible area with the following: "Contains TX IC : 5005A-WM140".

Manual Information That Must be Included

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove.

This RF module in the user's manual of the end product which integrates this module.

The user's manual for OEM Integrators must include the following information in a prominent location "IMPORTANT NOTE: To comply with FCC RF exposure compliance requirements. The antenna must not be co-located or operating in conjunction with any other antenna or transmitter".