What's Included

- 1. Radar Detector
- 2. Windshield mount
- 3. Power cord
- 4. Owner's Manual

Installation

- 1. Attach the radar detector to the bracket
- 2. Mount the radar detector firmly onto the windshield
- 3. Connect the power cord to the detector, and plug the adapter on the power cord into your vehicle's cigarette lighter receptacle

Controls & Settings

Volume Control: On/Off control, and to adjust the volume of the tone alerts

Mini USB port: Used for firmware updates when available

Key Buttons:

Dim	Mute	City
	IVIULO	OILV

SHORT PRESS on key button

Dim	Mute	City
Bright/Dim/Dark	Automute On/Off or Mute	Highway/City1/City2

Dim button: Short press on the Dim button changes the brightness setting.

Dim -> Dark-> Bright

Mute button pressed when at rest state: When the Mute button is pressed, it will turn on or off the auto-mute function

Mute button pressed when unit is *detecting***:** Pressing on the Mute button when the unit detects radar or laser will mute the alert

City button: Short press on the City button will change the detection mode.

Highway -> City1 -> City2

(Highway): All bands are detected

(City1): Alert will not sound until it reaches level 3 out of 6

(City2): No sound alert

LONG PRESS on key button

Dim	Mute	City	Dim+Mute+City
Voice	Ka	X-	Display Mode
On/Off	On/Off	On/Off	Change

Dim: Long press on the Dim button will turn the voice on/off

Mute: Long press on the Mute button will turn the Ka-Band on/off

City: Long press on the City button will turn the X band on/off

Dim+Mute+City: Pressing the Dim, Mute & City button simultaneously will change the display mode.

Normal display mode: Displays the band detected (X, K, and Ka) Frequency display mode: Displays frequency that is detected

WARNING

NOTE: THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY CHANGES OR MODIFICATIONS NOT EXPRESSLY APPROVED BY THE PARTY RESPONSIBLE FOR COMPLIANCE. SUCH MODIFICATIONS COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.