

We design and make what's
ON YOUR MIND!



YOKO TECHNOLOGY CORP.

No.199, Lide St., Zhonghe Dist., New Taipei City 23556, Taiwan R.O.C.
Tel : 886-2-8228-6161 Fax : 886-2-8228-6880
Service E-mail: yoko@yoko-tech.com
http : //www.yoko-tech.com

*Design and specifications are subject to change without notice.

▶ Wireless TDD Bridge ◀

LONG DISTANCE Transmission
Up to 50KM

RWK-WD2201, WD5201
Wireless P2P TDD Bridge

- Wireless TDMA technology
- Waterproof of IP67 standard
- 2.4GHz / 5.8GHz frequency band
- 23dBm / 25dBm output power
- Built-in 19dBi / 23dBi antenna
- Transmission distance of up to 50KM

RWK-WD2202, WD5202
Wireless P2MP TDD Bridge

- Wireless TDMA technology
- Waterproof of IP67 standard
- 2.4GHz / 5.8GHz frequency band
- 23dBm / 25dBm output power
- N Jack external connector
- Transmission distance of up to 50KM

RWK-WD2401, WD5401
Wireless TDD Repeater

- Wireless TDMA technology
- Waterproof of IP67 standard
- 2.4GHz / 5.8GHz frequency band
- 23dBm / 25dBm output power
- 19dBi+N Jack / 23dBi+N Jack
- Transmission distance of up to 50KM

RWK-WD2401
RWK-WD5401

▶ WiFi Outdoor Bridge ◀

SHORT DISTANCE Transmission
Up to 20KM

RWK-WA1801
WiFi Omni Antenna

- 2.4GHz frequency band
- 8dBi w/N Jack
- VSWR: 2.0 : 1 (Max.)
- Power handling: 10W
- Impedance: 50 ohms

RWK-WA8001
Extension Cable

- 3 meter low loss cable
- N Plug

RWK-WD1201
WiFi Outdoor AP / Bridge

- 802.11b/g standard
- Waterproof of IP67 standard
- 2.4GHz frequency band
- 24dBm output power
- 64/128bit WEP, WPA, WPA2
- Powered by 802.3af PoE

RWK-WA260, WA5601
Wireless P2MP Sector Antenna

- 2.4GHz / 5.8GHz frequency band
- 12dBi w/N Jack / 17dBi w/N Jack
- VSWR: 1.5 : 1 / 2.0 : 1
- Power handling: 10W / 5W
- Impedance: 50 ohms

RWK-WA2601
RWK-WA5601

RWK-WD1401
WiFi Outdoor Repeater

- 802.11b/g standard
- Waterproof of IP66 standard
- 2.4GHz frequency band
- 26dBm output power
- 64/128bit WEP, WPA, WPA2
- Powered by 802.3af PoE

The surveillance of fish farms to monitor water wheels in Yilan.

▶ Wireless Surveillance System with Solar Powered ◀

Application: Seaport, Forest, Highway, Weather, Reservoir, Pasture, Oil Field, Volcano - Fire Monitoring and Prevention

Control Center

The Power to Monitor:

- Wireless Video Transmission of up to 50KM
- No Local Source of Electrical Power Needed
- Deployment with Flexibility and Simplicity
- Rugged Enclosure Design for Harsh Environments

RWK-SS1201
Solar Panel

- Power: 140W
- Max power voltage Vmp (V): 18.29
- Max power current Imp(A): 7.65
- Open circuit voltage Voc(V): 21.96
- Short circuit current Isc(A): 8.17
- Solar cell efficiency: 16%
- Module efficiency: 14.39%

RWK-SS5901
Power Panel Box

- Weatherproof enclosure
- Easy to integrate with battery, controller
- High mobility with wheels

RWK-SS3001
Charge Controller

- Nominal output voltage: 12V, 60A
- Reverse polarity protection
- Short-circuit protection
- Over-current protection
- Lightning and transient surge protection
- High temperature protection
- Prevent reverse current from battery at night

RWK-SS2601
Battery

- Lead acid battery
- 12V, 150AH@10HR, deep cycle, maintenance free

YOKO YOKO TECHNOLOGY CORP.

We design and make what's
ON YOUR MIND!



2011 PRODUCT BROCHURE

▶ HD CCTV

RWK-H033, H233 *Full HD*
PTZ Camera

- 1080P Progressive Scan CMOS Sensor
- New Technology Low Lux Support
- 20X Sony Zoom Module / 18X Zoom Module
- High Stabilization Pan / Tilt Zoom Control
- Power Saving Support
- OSD Operation by IR Controller
- WDR / DNR / DSS Application Support

Coming Soon!

RWK-H221 *Full HD*
Box Camera

- 1080P Progressive Scan CMOS Sensor
- New Technology Low Lux Support
- C/CS Mount
- Mechanical IR Cut Filter (ICR)
- DC12V / AC24V Dual Power Design
- OSD Operation
- WDR / DNR / DSS Application Support

RWK-H222, H223 *Full HD*
Indoor / Outdoor IR Dome Camera

- 1080P Progressive Scan CMOS Sensor
- New Technology Low Lux Support
- 2.8-10.5mm Vari-Focal Lens with ICR
- 24 pcs IR LED (Up to 20M)
- 3AXIS Design (RHK-H223 Support Vanal Proof)
- OSD Operation
- WDR / DNR / DSS Application Support

RWK-H224 *Full HD*
IR Camera

- 1080P Progressive Scan CMOS Sensor
- New Technology Low Lux Support
- 3.7-12mm Vari-Focal Lens with ICR
- 48 pcs IR LED (Up to 40 / 20 / 10M)
- Concealed Cable Bracket and Weather Proof Design
- OSD Operation
- WDR / DNR / DSS Application Support

▶ CCTV

RWK-S401 *EffioE*
WDR Box Camera

- 1/3" Sony Super HAD II Double Density CCD Sensor
- 700 TVL
- 0.003 Low Lux Support
- C/CS Mount
- DC12V / AC24V Dual Power Design
- OSD Operation
- Mechanical IR Cut Filter (ICR)
- WDR / DNR / DSS Application Support

RWK-CA66, CA67 *EffioE*
Box Camera

- 1/3" Sony Exview HAD II CCD Sensor
- 700 TVL
- 0.01 Low Lux Support
- C/CS Mount
- DC12V / AC24V Dual Power Optional
- OSD Operation
- ATR / DNR / HLC Application Support

RWK-S431, S432 *EffioE*
AF Zoom Camera

- 1/3" Sony Super HAD II Double Density CCD Sensor
- 700 TVL
- Mechanical IR Cut Filter (ICR)
- 0.008 Low Lux Support
- 18X Mega Auto Focus Zoom Lens
- Support I.G. Pelco D/II Protocol
- OSD Operation
- WDR / DNR / DSS Application Support

RWK-S413, S414, S415 *EffioE*
WDR Speed Dome Camera

- 1/4" Sony Super HAD II Double Density CCD Sensor
- 600 TVL
- Mechanical IR Cut Filter (ICR)
- 0.008 Low Lux Support
- 36X Auto Focus Zoom Lens
- Auto Tracking and 3D Privacy Mask Support
- OSD Operation
- WDR / DNR / DSS Application Support

▶ CCTV

RWK-2G96, 2G97/2 *EffioE*
Indoor Dome Camera

- 1/3" Sony Exview HAD II CCD Sensor
- 700 TVL
- 0.01 Low Lux Support
- 2.8-10.5mm Vari-Focal Lens or 3.6mm Board Lens
- 3AXIS Mechanism for Lens Rotation
- 24 pcs IR LED and OSD Optional
- ATR / DNR / HLC Application Support

RWK-2H96, 2H97 *EffioE*
Outdoor Dome Camera

- 1/3" Sony Exview HAD II CCD Sensor
- 700 TVL
- 0.01 Low Lux Support
- 12mm Board Lens
- Weatherproofing IP66
- 3AXIS Concealed Cable Bracket
- High Power 32 pcs IR LED (Up to 50M)
- OSD Optional
- ATR / DNR / HLC Application Support

RWK-2F96, 2F97/7 *EffioE*
Cable Management IR Camera

- 1/3" Sony Exview HAD II CCD Sensor
- 700 TVL
- 0.01 Low Lux Support
- 12mm Board Lens
- Weatherproofing IP66
- 3AXIS Concealed Cable Bracket
- High Power 32 pcs IR LED (Up to 50M)
- OSD Optional
- ATR / DNR / HLC Application Support

RWK-2Q91, 2Q97/5
IR Camera

- 1/3" Color CCD Sensor
- 420 TVL
- 0.05 Low Lux Support
- 4.3 Board Lens
- Weatherproofing IP68
- 36 pcs IR LED (Up to 30M)
- OSD Operation
- Support AWB, AGC and AES

▶ DVR

RWK-9240
4CH H.264 Multiplex DVR

- 4CH D1 resolution recording @ 30FPS
- Dual streaming enhances the speed of network transmission
- VGA output high resolution up to 1280x1024
- 3G / GPRS mobile phone monitoring
- Watermark function
- Remote controller 1 to 4 (Optional)
- Multi-language OSD

RWK-9244, 9248, 9246
4CH / 8CH / 16CH H.264 Multiplex DVR

- 4CH/8CH/16CH Realtime recording (30FPS)
- Dual streaming enhances the speed of network transmission
- VGA output high resolution up to 1280x1024
- 3G / GPRS mobile phone monitoring
- Watermark function
- HDMI Output (Optional)
- Remote controller 1 to 4 (Optional)

3G/GPRS Mobile Surveillance

Through mobile phones or PDA, it is not impossible any more to monitor your office, your factories or your home anywhere, anytime in the world. This advanced wireless technology makes live monitoring truly LIVE!

Central Management System (CMS)

- Free software
- Connect up to 16 DVRs
- Multi-channel monitoring
- E-MAP
- Remote recording and backup
- Still image capture

▶ PSR

RWK-9116
Circuit Board of PSR

- H.264 Video Compression
- D1 resolution recording @ 30FPS
- VGA output high resolution up to 1280x1024
- Pre-Alarm / Post-Alarm function
- USB signal Output (pin connector)
- Alarm input/output
- IR Controller
- AVI file format

RWK-9114
Digital Video Capture Camera

- H.264 Video Compression
- D1 resolution recording @ 30FPS
- Pre-Alarm / Post-Alarm function
- USB signal Output (pin connector)
- Alarm input/output
- AVI file format

RWK-9123
Car Recorder

- 1/2.5" 5M CMOS Sensor
- FHD 1080P @ 30FPS
- H.264 Video Compression
- MOV file format
- HDMI output
- 2.5" TFT LCD
- Overwrite / File Protect Function

▶ GPS


TD300
Mini GPS Tracker

Assisted Global Positioning System

Securing, Monitoring & Tracking!

- Application**
- Industry (Staff management, Goods transportation, Vehicle)
 - Personal (Important person, Pets security, Outdoor activity)
 - Valuables (Expensive things, Equipment, Artistic work)

- Total Solution**
- GSM / SMS / GPRS communication.
 - Quad-band GSM (850 / 900 / 1800 / 1900MHz) and GPRS class10.
 - SOS button for immediate rescue/reaction & located exact location.
 - Low Battery alert & abnormal movement (anti-theft) alert.



- Feature**
- Total Solution including Web-base Tracking Software : www.anytra.com
 - GSM/SMS/GPRS communication.
 - Quad-band GSM (850/900/1800/1900MHz) and GPRS class10.
 - Support AGPS function.
 - SOS button for immediate rescue/action & located exact location.
 - Low Battery alert.
 - Abnormal movement (anti-theft) alert.
 - Accessories:
 - Rechargeable Li-Ion Battery and AC adaptor.
 - Rechargeable Li-Ion Battery and External Power Cable to Car Battery.