Owner's Manual & Safety Instructions

Save This Manual Keep this manual for the safety warnings and precautions, assembly, operating, inspection, maintenance and cleaning procedures. Write the product's serial number in the back of the manual near the assembly diagram (or month and year of purchase if product has no number). Keep this manual and the receipt in a safe and dry place for future reference.

REV 15e

20-60 x 60mm SPOTTING SCOPE with Tripod





ITEM 62774

Visit our website at: http://www.harborfreight.com Email our technical support at: productsupport@harborfreight.com

When unpacking, make sure that the product is intact and undamaged. If any parts are missing or broken, please call 1-888-866-5797 as soon as possible.

Copyright[©] 2015 by Harbor Freight Tools[®]. All rights reserved.

No portion of this manual or any artwork contained herein may be reproduced in any shape or form without the express written consent of Harbor Freight Tools.

Diagrams within this manual may not be drawn proportionally. Due to continuing improvements, actual product may differ slightly from the product described herein.

Tools required for assembly and service may not be included.

AWARNING

Read this material before using this product. Failure to do so can result in serious injury. SAVE THIS MANUAL.

Specifications

	Magnification	20x ~ 60x
	Scope View	2.2-1 Degree
j	Tripod Mount	1/4" - 20 Thread
	Overall Dimensions	3-1/8" D x 14-1/4" Folded

Eyepiece	Fixed, 45° Angle
Objective Lens Diameter	60mm
Ocular Lens Diameter	17mm
Field of View	38-17M/1000M

IMPORTANT SAFETY INFORMATION

General Safety Warnings

- RISK OF SERIOUS INJURY AND BLINDNESS. DO NOT LOOK DIRECTLY AT OR NEAR THE SUN WITH THE SPOTTING SCOPE.
- Do not subject the Spotting Scope lenses to direct sunlight. Light ray concentration may cause a fire and/or burns.
- 3. Do not use when tired or when under the influence of alcohol, drugs or medication.
- This product is not a toy. Do not allow children to play with or near this item.
- 5. Use as intended only.
- 6. Inspect before every use; do not use if parts are loose or damaged.

- Have product serviced by a qualified repair person using only identical replacement parts.
- WARNING: This product contains di (2-ethylhexyl) phthalate (DEHP), a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. (California Health & Safety Code § 25249.5, et seq.)
- 9. The warnings, precautions, and instructions discussed in this instruction manual cannot cover all possible conditions and situations that may occur. It must be understood by the operator that common sense and caution are factors which cannot be built into this product, but must be supplied by the operator.

Functions



Operation



Read the ENTIRE IMPORTANT SAFETY INFORMATION section at the beginning of this manual including all text under subheadings therein before set up or use of this product.

General Operating Instructions

Note: Do not place the Spotting Scope in water or use in the rain. The Scope is not waterproof.

- 1. Remove the protective Lens Cap.
- Look into the Eyepiece on the Spotting Scope and rotate the Focusing Knob in either direction to focus on the object being viewed. Rotate Knob until a clear image is obtained.
- To zoom in or out, rotate the Zoom Ring to the desired magnification setting. Use the Focusing Knob to refocus.

4. If strong sunshine is affecting visibility, extend the Sunshade by pulling it out.

WARNING! RISK OF SERIOUS INJURY AND BLINDNESS. DO NOT LOOK DIRECTLY AT OR NEAR THE SUN WITH THE SPOTTING SCOPE.

 If the Spotting Scope is moved from a cold environment into a warmer one, condensation may form on the lens. This is a normal reaction which will disappear in about one hour.

Mounting Spotting Scope on Tripod

- Pull out the Tripod legs and place the Tripod on a level, stable surface.
- Place the Mounting Bracket that is attached to the Spotting Scope onto the Tripod Head.
- Thread the Screw Knob on the Tripod Head into the Mounting Bracket attached to the Scope and firmly tighten to secure the Spotting Scope in place.

Maintenance and Servicing



Procedures not specifically explained in this manual must be performed only by a qualified technician.

AWARNING

TO PREVENT SERIOUS INJURY FROM TOOL FAILURE: Do not use damaged equipment. If abnormal noise or vibration occurs, have the problem corrected before further use.

Cleaning and Maintenance

- BEFORE EACH USE, inspect the general condition of the Spotting Scope. Check for:
 - · loose hardwar
 - · misalignment or binding of moving parts
 - · cracked or broken parts
 - any other condition that may affect its safe operation.

- AFTER USE, replace the Lens Cap and place the Spotting Scope in its case. Store indoors in a moisture-free environment out of children's reach.
- To clean the lenses, use a soft, lint-free cloth dampened with a small amount of lens cleaning solution. Do not pour the lens cleaning solution directly on the lens. Do not use excessive pressure to clean the lenses or scratching may occur.

Record Serial Number Here:

Note: If product has no serial number, record month and year of purchase instead.

Limited 90 Day Warranty

Harbor Freight Tools Co. makes every effort to assure that its products meet high quality and durability standards, and warrants to the original purchaser that this product is free from defects in materials and workmanship for the period of 90 days from the date of purchase. This warranty does not apply to damage due directly or indirectly, to misuse, abuse, negligence or accidents, repairs or alterations outside our facilities, criminal activity, improper installation, normal wear and tear, or to lack of maintenance. We shall in no event be liable for death, injuries to persons or property, or for incidental, contingent, special or consequential damages arising from the use of our product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation of exclusion may not apply to you. THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS.

To take advantage of this warranty, the product or part must be returned to us with transportation charges prepaid. Proof of purchase date and an explanation of the complaint must accompany the merchandise. If our inspection verifies the defect, we will either repair or replace the product at our election or we may elect to refund the purchase price if we cannot readily and quickly provide you with a replacement. We will return repaired products at our expense, but if we determine there is no defect, or that the defect resulted from causes not within the scope of our warranty, then you must bear the cost of returning the product.

This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

