


## AISC-360-10 Example 001

### COMPOSITE GIRDER DESIGN

#### EXAMPLE DESCRIPTION

A typical bay of a composite floor system is illustrated below. Select an appropriate ASTM A992 W-shaped beam and determine the required number of  $\frac{3}{4}$  in.-diameter steel headed stud anchors. The beam will not be shored during construction. To achieve a two-hour fire rating without the application of spray applied fire protection material to the composite deck,  $4\frac{1}{2}$  in. of normal weight ( $145\text{ lb/ft}^3$ ) concrete will be placed above the top of the deck. The concrete has a specified compressive strength,  $f'_c = 4\text{ ksi}$ .

#### GEOMETRY, PROPERTIES AND LOADING



#### Member Properties

W21x50  
 $E = 29000\text{ ksi}$   
 $F_y = 50\text{ ksi}$

#### Loading

$w = 800\text{ plf}$  (Dead Load)  
 $w = 250\text{ plf}$  (Construction)  
 $w = 100\text{ plf}$  (SDL)  
 $w = 1000\text{ plf}$  (Live Load)

#### Geometry

Span,  $L = 45\text{ ft}$

## TECHNICAL FEATURES OF ETABS TESTED

Composite beam design, including:

- Selection of steel section, camber and shear stud distribution
- Member bending capacities, at construction and in service
- Member deflections, at construction and in service

## RESULTS COMPARISON

Independent results are referenced from Example I.1 from the AISC Design Examples, Version 14.0.

Output Parameter	ETABS	Independent	Percent Difference
Pre-composite $M_u$ (k-ft)	344.2	344.2	0.00%
Pre-composite $\Phi_b M_n$ (k-ft)	412.5	412.5	0.00%
Pre-composite Deflection (in.)	2.6	2.6	0.00%
Required Strength $M_u$ (k-ft)	678.3	678.4	0.01%
Full Composite $\Phi_b M_n$ (k-ft)	937.1	937.1	0.00%
Partial Composite $\Phi_b M_n$ (k-ft)	763.2	763.2	0.00%
Shear Stud Capacity $Q_n$	17.2; 14.6	17.2; 14.6	0.00%
Shear Stud Distribution	46	46	0.00%
Live Load Deflection (in.)	1.34	1.26	6.0%
Required Strength $V_u$ (kip)	60.3	60.3	0.00%
$\Phi V_n$ (k)	237.1	237.1	0.00%

PROGRAM NAME: ETABS  
REVISION NO.: 3

## COMPUTER FILE: AISC-360-10 EXAMPLE 001.EDB

### CONCLUSION

The ETABS results show an acceptable comparison with the independent results. The live load deflection differs due to a difference in methodology. In the AISC example, the live load deflection is computed based on a lower bound value of the beam moment of inertia, whereas in ETABS, it is computed based on the approximate value of the beam moment of inertia derived from Equation (C-I3-6) from the *Commentary on the AISC Load and Resistance Factor Design Specification – Second Edition*.

## HAND CALCULATION

### Properties:

#### Materials:

ASTM A572 Grade 50 Steel

$$E = 29,000 \text{ ksi}, F_y = 50 \text{ ksi}, w_{\text{steel}} = 490 \text{ pcf}$$

4000 psi normal weight concrete

$$E_c = 3,644 \text{ ksi}, f'_c = 4 \text{ ksi}, w_{\text{concrete}} = 145 \text{ pcf}$$

#### Section:

W21x50

$$d = 20.8 \text{ in}, b_f = 6.53 \text{ in}, t_f = 0.535 \text{ in}, t_w = 0.38 \text{ in}, k = 1.04 \text{ in}$$

$$A_{\text{steel}} = 14.7 \text{ in}^2, S_{\text{steel}} = 94.6 \text{ in}^3, Z_{\text{steel}} = 110 \text{ in}^3, I_{\text{steel}} = 984 \text{ in}^4$$

#### Deck:

$$t_c = 4 \frac{1}{2} \text{ in.}, h_r = 3 \text{ in.}, s_r = 12 \text{ in.}, w_r = 6 \text{ in.}$$

#### Shear Connectors:

$$d = \frac{3}{4} \text{ in}, h = 4 \frac{1}{2} \text{ in}, F_u = 65 \text{ ksi}$$

### Design for Pre-Composite Condition:

#### Construction Required Flexural Strength:

$$w_D = (10 \cdot 75 + 50) \cdot 10^{-3} = 0.800 \text{ kip/ft}$$

$$w_L = 10 \cdot 25 \cdot 10^{-3} = 0.250 \text{ kip/ft}$$

$$w_u = 1.2 \cdot 0.800 + 1.6 \cdot 0.250 = 1.36 \text{ kip/ft}$$

$$M_u = \frac{w_u \cdot L^2}{8} = \frac{1.36 \cdot 45^2}{8} = 344.25 \text{ kip-ft}$$

#### Moment Capacity:

$$\Phi_b M_n = \Phi_b \cdot Z_s \cdot F_y = (0.9 \cdot 110 \cdot 50) / 12 = 412.5 \text{ kip-ft}$$

Pre-Composite Deflection:

$$\Delta_{nc} = \frac{5w_D L^4}{384EI} = \frac{5 \cdot \frac{0.800}{12} \cdot (45 \cdot 12)^4}{384 \cdot 29,000 \cdot 984} = 2.59 \text{ in.}$$

Camber =  $0.8 \cdot \Delta_{nc} = 0.8 \cdot 2.59 = 2.07$  in., which is rounded down to 2 in.

**Design for Composite Flexural Strength:**

Required Flexural Strength:

$$w_u = 1.2 \cdot 0.800 + 1.2 \cdot 0.100 + 1.6 \cdot 1 = 2.68 \text{ kip/ft}$$

$$M_u = \frac{w_u \cdot L^2}{8} = \frac{2.68 \cdot 45^2}{8} = 678.38 \text{ kip-ft}$$

Full Composite Action Available Flexural Strength:

Effective width of slab:

$$b_{\text{eff}} = \frac{10.0}{2} \cdot 2 \text{ sides} = 10.0 \text{ ft} \leq \frac{45.0 \text{ ft}}{8} = 11.25 \text{ ft}$$

Resistance of steel in tension:

$$C = P_y = A_s \cdot F_y = 14.7 \cdot 50 = 735 \text{ kips} \quad \text{controls}$$

Resistance of slab in compression:

$$A_c = b_{\text{eff}} \cdot t_c = (10 \cdot 12) \cdot 4.5 = 540 \text{ in}^2$$

$$C = 0.85 \cdot f'_c \cdot A_c = 0.85 \cdot 4 \cdot 540 = 1836 \text{ kips}$$

Depth of compression block within slab:

$$a = \frac{C}{0.85 \cdot b_{\text{eff}} \cdot f'_c} = \frac{735}{0.85 \cdot (10 \cdot 12) \cdot 4} = 1.80 \text{ in.}$$

Moment resistance of composite beam for full composite action:

$$d_1 = (t_c + h_r) - \frac{a}{2} = (4.5 + 3) - \frac{1.80}{2} = 6.60 \text{ in.}$$

$$\Phi M_n = \Phi \left( P_y \cdot d_1 + P_y \cdot \frac{d}{2} \right) = 0.9 \left( 735 \cdot 6.60 / 12 + 735 \cdot \frac{20.8 / 12}{2} \right) = 937.1 \text{ kip-ft}$$

## Partial Composite Action Available Flexural Strength:

Assume 50.9% composite action:

$$C = 0.509 \cdot P_y = 373.9 \text{ kips}$$

Depth of compression block within concrete slab:

$$a = \frac{C}{0.85 \cdot b_{\text{eff}} \cdot f'_c} = \frac{373.9}{0.85 \cdot (10 \cdot 12) \cdot 4} = 0.92 \text{ in.}$$

$$d_1 = \left( t_c + h_r \right) - \frac{a}{2} = (4.5 + 3) - \frac{0.92}{2} = 7.04 \text{ in.}$$

Compressive force in steel section:

$$\frac{P_y - C}{2} = \frac{735 - 373.9}{2} = 180.6 \text{ kips}$$

Steel section flange ultimate compressive force:

$$C_{\text{flange}} = b_f \cdot t_f \cdot F_y = 6.53 \cdot 0.535 \cdot 50 = 174.7 \text{ kips}$$

Steel section web (excluding fillet areas) ultimate compressive force:

$$C_{\text{web}} = (d - 2 \cdot k) \cdot t_w \cdot F_y = (20.8 - 2 \cdot 1.04) \cdot 0.38 \cdot 50 = 355.7 \text{ kips}$$

Steel section fillet ultimate compressive force:

$$C_{\text{fillet}} = \frac{P_y - (2 \cdot C_{\text{flange}} + C_{\text{web}})}{2} = \frac{735 - (2 \cdot 174.7 + 355.7)}{2} = 14.5 \text{ kips}$$

Assuming a rectangular fillet area, the distance from the bottom of the top flange to the neutral axis of the composite section is:

$$\begin{aligned} x &= (k - t_f) \cdot \left[ \frac{(P_y - C) / 2 - C_{\text{flange}}}{C_{\text{fillet}}} \right] \\ &= (1.04 - 0.535) \cdot \left[ \frac{180.6 - 174.7}{14.98} \right] = 0.20 \text{ in.} \end{aligned}$$

Distance from the centroid of the compressive force in the steel section to the top of the steel section:

$$d_2 = \frac{C_{flange} \bullet t_f / 2 + ((P_y - C) / 2 - C_{flange}) \bullet (t_f + x / 2)}{(P_y - C) / 2}$$

$$= \frac{174.7 \bullet 0.535 / 2 + (180.6 - 174.7) \bullet (0.535 + 0.2 / 2)}{180.6} = 0.279 \text{ in.}$$

Moment resistance of composite beam for partial composite action:

$$\Phi M_n = \Phi [C \bullet (d_1 + d_2) + P_y \bullet (d_3 - d_2)]$$

$$= 0.9 \left[ 373.9 \bullet (7.04 + 0.279) + 735 \bullet \left( \frac{20.8}{2} - 0.279 \right) \right] / 12 = 763.2 \text{ kip-ft}$$

### Shear Stud Strength:

From AISC Manual Table 3.21, assuming the shear studs are placed in the weak position, the strength of  $\frac{3}{4}$  in.-diameter shear studs in normal weight concrete with  $f'_c = 4$  ksi and deck oriented perpendicular to the beam is:

$$Q_n = 17.2 \text{ kips for one shear stud per deck flute}$$

$$Q_n = 14.6 \text{ kips for two shear studs per deck flute}$$

### Shear Stud Distribution:

There are at most 22 deck flutes along each half of the clear span of the beam. ETABS only counts the studs in the first 21 deck flutes as the 22<sup>nd</sup> flute is potentially too close to the point of zero moment for any stud located in it to be effective. With two shear studs in the first flute, 20 in the next in the next twenty flutes, and one shear stud in the 22<sup>nd</sup> flute, in each half of the beam, there is a total of 46 shear studs on the beam, and the total force provided by the shear studs in each half span is:

$$\Sigma Q_n = 2 \bullet 14.6 + 20 \bullet 17.2 = 373.9 \text{ kip}$$

## Live Load Deflection:

Modulus of elasticity ratio:

$$n = E/E_c = 29,000/3,644 = 8.0$$

Transformed elastic moment of inertia assuming full composite action:

Element	Transformed Area $A$ (in <sup>2</sup> )	Moment Arm from Centroid $y$ (in.)	$Ay$ (in. <sup>3</sup> )	$Ay^2$ (in. <sup>4</sup> )	$I_0$ (in. <sup>4</sup> )
Slab	67.9	15.65	1,062	16,620	115
W21x50	14.7	0	0	0	984
	82.6		1,062	16,620	1,099

$$I_x = I_0 + Ay^2 = 1,099 + 16,620 = 17,719 \text{ in.}^4$$

$$\bar{y} = \frac{1,062}{82.6} = 12.9 \text{ in.}$$

$$I_{tr} = I_x - A \cdot \bar{y}^2 = 17,719 - 82.6 \cdot 12.9^2 = 4,058 \text{ in.}^4$$

Effective moment inertia assuming partial composite action:

$$I_{equiv} = I_s + \sqrt{\Sigma Q_n / P_y} (I_{tr} - I_s) = 984 + \sqrt{0.51} (4,058 - 984) = 3,176 \text{ in.}^4$$

$$I_{eff} = 0.75 \cdot I_{equiv} = 0.75 \cdot 3,176 = 2,382 \text{ in.}^4$$

$$\Delta_{LL} = \frac{5w_L L^4}{384EI_{eff}} = \frac{5 \cdot (1/12) \cdot (30 \cdot 12)^4}{384 \cdot 29,000 \cdot 2,382} = 1.34 \text{ in.}$$

## **Design for Shear Strength:**

### Required Shear Strength:

$$w_u = 1.2 \cdot 0.800 + 1.2 \cdot 0.100 + 1.6 \cdot 1 = 2.68 \text{ kip/ft}$$

$$V_u = \frac{w_u \cdot L}{2} = \frac{2.68 \cdot 45}{2} = 60.3 \text{ kip-ft}$$



PROGRAM NAME: ETABS

REVISION NO.: 3

Available Shear Strength:

$$\Phi V_n = \Phi \cdot 0.6 \cdot d \cdot t_w \cdot F_y = 1.0 \cdot 0.6 \cdot 20.8 \cdot 0.38 \cdot 50 = 237.1 \text{ kips}$$