




**Rack PDU, Switched, 2U, 32A, 230V, (16)C13**  
**Part Number: AP7922**



## Output

Nominal Output Voltage	230V	
Maximum Total Current Draw per Phase	32A	
Output Connections	(16) IEC 320 C13	

## Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	IEC 309 32A 2P+E
Cord Length	3 meters
Maximum Input Current per phase	32A
Load Capacity	7360 VA

## Physical

Net Weight	4.50 KG
Maximum Height	89.00 mm
Maximum Width	445.00 mm
Maximum depth	114.00 mm
Shipping Weight	6.55 KG
Shipping Height	140.00 mm
Shipping Width	508.00 mm
Shipping Depth	368.00 mm
Color	Black

## Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

## Conformance

Regulatory Approvals	CCC,CE,EN 55022 Class A,EN 55024,EN 61000-3-2,EN 61000-3-3,GOST,IRAM,MIC,VDE
Standard Warranty	2 years repair or replace

All rights reserved. All APC trademarks are property of American Power Conversion. Other trademarks are property of their respective owners. Specifications are subject to change without notice.