

MOWERS

WALK BEHIND

J SERIES

JS28 | JS38 | JS48



JOHN DEERE



John Deere Walk-Behind Mowers

Meet the mowers that go easy on you...and your budget.

- JS48 has an electric start for added convenience and a spin-on oil filter for extended life
- The JS38 and JS48 offer a convenient single lever height-of-cut adjuster
- Rugged 22-inch steel decks include 3-in-1 blades
- The JS28, JS38 and JS48 all feature durable Briggs & Stratton engines with a "Fresh Start" cap that automatically drips fuel stabilizer to help prevent stale gas.
- MowMentum™ Drive System features a pivoting handle, allowing you to comfortably mow at precisely the right speed with less effort

Behind you all season long: your John Deere dealer

When you buy a John Deere, you're getting more than just a machine: you're getting the knowledge and expertise that only comes from a John Deere dealer. Ask about the variety of service plans available or visit www.readytomow.com to find out how you can get "Service Delivered" without ever leaving your home.

SPECIFICATIONS	JS28	JS38	JS48
Engine:			
Gross Torque Power**	7.25	7.25	8.75
Displacement	190cc	190cc	190cc
Valves	Side	Side	Overhead
Starting	Pull Cord	Pull Cord	Electric Start with Pull Cord backup
Choke / Primer	Fresh Start & Ready Start	Fresh Start & Ready Start	Fresh Start & Ready Start
Deck	22" 14 gauge steel	22" 14 gauge steel	22" 14 gauge steel
Blades	3-in-1 for use in all applications (mulching, side discharge and bagging)	3-in-1 for use in all applications (mulching, side discharge and bagging)	3-in-1 for use in all applications (mulching, side discharge and bagging)
Single lever height of cut	4-point	Yes	Yes
Height of Cut	9 settings from 1.2" to 4.2"	9 settings from 1.2" to 4.2"	9 settings from 1.2" to 4.2"
Discharge	Rear/Side	Rear/Side	Rear/Side
Drive System	MowMentum Drive System™	MowMentum Drive System™	MowMentum Drive System™
Transmission	Variable drive transmission; front wheel	Variable drive transmission; rear wheel	Variable drive transmission; rear wheel
Variable Speed	0-4 mph	0-4 mph	0-4 mph
Adjustable Handle	Standard 3 position	Standard 3 position	Standard 3 position
Front Wheels	Stationary 8 inch	Stationary 8 inch	Stationary 8 inch
Rear Wheels	Stationary 8 inch	Stationary 9 inch	Stationary 9 inch
Bag; Side Discharge and Mulch Ready	Standard	Standard	Standard
Bagger Capacity 2.5 bushel	Standard	Standard	Standard
Total Weight	95 lbs	95 lbs	100 lbs



MowMentum Drive™ allows the customer to choose the speed to follow the mower by pivoting the drive handle.



Single lever height adjuster makes it convenient to change the height of cut in nine settings from 1.2" to 4.2".

** Gross Torque Power: a direct way to measure the turning force an engine can produce.

All power levels are stated ft-lbs per SAE J1940 as rated by the engine manufacturer. The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's website for additional information.

This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification, design and price of products described in this literature without notice. John Deere's green and yellow color scheme, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company.

