

IP360 System Overview & Functions



P360

Full IP Entry System

LIST PRICED CATALOGUE

CONTENTS

INTRODUCTION

IP360 OVERVIEW IP360 SYSTEM FEATURES

CAME BPT PANELS & MONITORS

FUTURA IP MONITOR THANGRAM IP PANEL

IP360 SYSTEM & EXAMPLE SCHEMATICS

IP360: SYSTEM PARAMETERS SINGLE-FAMILY HOME CONFIGURATIO SERVERLESS CONFIGURATION MINI SERVER CONFIGURATION MAIN SERVER CONFIGUARATION CRESTRON INTEGRATION IP360 PRECONFIGURED KITS CAME CONNECT

COMPONENTS PRICELISTS

THANGRAM IP PANELS FUTURA IP MONITORS SYSTEM COMPONENTS ACCESSORIES

ADDITIONAL SYSTEMS MILESIGHT CCTV CCTV PRICELIST



8
 9

	10
ON	11
	12
	13
	14
	16
	18
	20

22
23
24
25

26
27

P360

THE 360 DEGREE IP

LIMITLESS

IP360 by BPT is an exceptionally advanced, highly flexible video entry system. It surpasses the limits of traditional video entry systems. It features extensive system setup features, for example, there is no limit on the distance between panels, intercoms and receivers.

OPEN SYSTEM

In a rapidly-changing world that constantly offers new technologies, IP360 fully meets the growing need for simplification and integration between different systems.

By using standard communication protocols, the system opens up to endless possibilities of application, enabling the use of BPT video entry systems within multi-division systems. This allows the various devices in the group to communicate with each other and with third-party systems using a common language.

MAXIMUM FLEXIBILITY

IP360: the video entry system that's right for all installation environments.

Advanced video entry system functions to match the most modern residential, business, industrial and service-sector scenarios. Individual homes or large residential complexes: IP360 provides the perfect solution.

BPT IP360 THANGRAM IP panels* INTERNET **IP360** Local area networks Crestron monitors

INTEGRATION WITH LAN NETWORK

All the IP360 system devices can be connected to existing LAN networks, adding the functionalities of the digital system without the need for any special wiring. The system uses Ethernet distribution as its main communication structure.

The ethernet network guarantees almost infinite expansion of the system.

CLOUD CONNECTED

CAME Connect allows you to remotely control your IP360 door entry system at the touch of a button using any device connected to the internet. Using a standard network connection, IP360 comminicates with a main central server allowing remote access through the CAME Connect web based platform and supporting app.

This allows users remote system access via any internet ready device allowing the freedom of control even when you are not on site. It also enables installers to monitor CAME Connected installations, intervening quickly and safely when necessary.



CAME NNECT

CLOUD CONNECTED TECHNOLOGY

*PoE or local power supply.

IP360 SYSTEM FEATURES

VIDEO ENTRY SYSTEM ON MOBILE DEVICES



VIDEO ENTRY SYSTEM ALWAYS AT YOUR FINGERTIPS

manage audio/video calls through the IP360 App Store and Android[™] Play.

The BPT XIP Mobile app enables you to The BPT XIP Mobile app gives you the ability to remotely and securely open & close doors, control lighting and entry system directly from multiple mobile view feeds from multiple sources, including CCTV or tablet devices. The app is free to download from the cameras. You'll get notifications for received, missed or rejected calls. Plus contact list management.

VIDEO ENTRY SYSTEMS ON PC



VIDEO ENTRY SYSTEM AT THE CLICK OF A MOUSE The BPT video entry system can be managed and enjoyed

from your home or office PC using the special "Soft Receiver" software, available on USB flash drive or CD. A full server is required.

THE APPLICATION TO INSTALL A REAL IP RECEIVER ON YOUR PC

WITH SIP DEVICES



IP360 can interfaced with third-party devices using the SIP protocol, such as, home automation terminals or VoIP telephone switchboards*, all without using any special interfaces.

In this way it will be possible to receive a video entry

system call and open a gate or a door from the touch panel without needing to have a video entry phone in the home. In addition, the system lets you use SIP telephone interfaces with analogue or GSM phones. This means you can always be reached on a landline or your mobile phone.

* For more details on supported models, please contact CAME BPT.



THE CCTV SYSTEM



IP360 enables users to view images from entry panels, both traditional and IP video cameras, internal receivers or from a connected porter's desk. Analogue cameras can be connected to the system's power supplies or directly to the gateways using the relevant selector switches.

For the Milesight CCTV range of IP360 compatible devices. See page 26.

INTEGRATION WITH CAME'S HOME AUTOMATION SYSTEM



home automation system. Integrating the two systems, meaning installation of additional devices can be avoided.

IP360 offers many functions integrating multiple systems. Video streams sent from IP video cameras can be displayed on installed FUTURA IP terminals.



Motion detection using integrated IP video cameras can be programmed to trigger video entry system actions such as controlling lights or activating video calls to smartphones and tablets.

IP360 easily integrates fully with CAME's All the video entry system functions will be managed directly from the home automation touch screens. IP360 and CAME's home automation together take video entry systems to new, even more advance levels.

FUTURA IP

The video receiver with user-friendly 7" display that's perfect in any room thanks to its simple and sophisticated design.


- SIP protocol.
- H.264 video codec, G.711 audio codec.
- Built-in webserver for setting up and managing via browser.
- Door status feedback.
- PoE or local power supply.



Available in black and white versions.

THANGRAM IP

BPT's first fully IP entry panel that can be directly connected within a LAN network. Combining innovative, sophisticated design and high performance, THANGRAM IP is the next generation of entry panel.



Unlimited intercom calls to other FUTURA IP internal receivers, smartphones or tablets*. Advanced, multilingual user interface.

Display of IP video cameras present in the system.

Perfect video quality in all environmental conditions. Colour video camera with VGA resolution (640x480), angle of view 82° vertically and 100° horizontally.

Compatible with all the existing accessories in the THANGRAM range.

The incredibly robust design, features an IP54 protection rating. This provides excellent protection against water and impact damage.

> Button plates are backlit. Blue illumination can be disabled or the brightness can be adjusted.

> > wall mounted

recessed

Dimensions

(WxHxD) 99x254x26 mm

(WxHxD) 127x201x2* mm

. . . .

....

....

.

......

.

ONSO

Dimensions

(WxHxD) 212x161x28 mm wall mounted (WxHxD) 212x161x10.5 mm recessed

ppt

- PoE and local power supply.
- Easy to setup via local HTML5 webpage interface.
- Standard SIP video and VoIP protocols.
- Recessed or wall-mounted installation.
- Updates firmware from the web.
- Thickness of 2 mm (recessed).
- Compatible with BPT XIP system.
- Integration with CAME's home automation system

SIP, H.264 video codec, G.711 audio codec. Built-in webserver.

High-tech Heart

LED illuminated pictograms for door status, active communication, call in progress and system busy notifications.

Stylish design.

- 12V electric lock output.
- 2 in/out contacts with functions which can be programmed via webpage interface.
- 1 local door opener contact.
- 1 relay output.

ppt

IP360: 360 SYSTEM PARAMETERS

T.		
-		
.1111		
-		
_		






	THANGRAM IP without server	With miniserver* (miniSER)	With full server (ETISER/XIP)
Max no of panels.	Unlimited	Unlimited	Unlimited
Max no of individual calls.	Unlimited	Unlimited	Unlimited
Max number of simultaneous calls.	4	10	20
Max number of devices ringing simultaneously.	4	10	18
Inbuilt iOS/Android connections via Cloud or Crestron integrations.	4	6 (Expandable to 10)	0 (Unlimited licenses can be added)
PoE.	Yes	No (requires VAS 101 PSU)	No (PSU supplied)
Concierge feature.	No	No	Yes



SINGLE-FAMILY HOME CONFIGURATION WITHOUT SERVER

In this configuration:


- Maximum of 4 simultaneous calls from entry panels.
- Maximum of 4 simultaneous calls to IP receivers within the home.
- Unlimited entry panels.
- iOS/Android integration.



WITH MINISERVER

In this configuration:

- Maximum of 10 simultaneous calls from entry panels.
- Maximum of 10 simultaneous calls to IP receivers within the home.
- Unlimited entry panels.
- iOS/Android integration.



• IP receivers.

- WiFi connectivity within the home.
- · Cloud connectivity via internet connection.

SERVERLESS CONFIGURATION FOR MULTI DWELLING UNITS


SIMPLY CONNECT IP360 DEVICES TO YOUR NETWORK

In this configuration:

P360 SYSTEM

- Maximum of 4 simultaneous calls from entry panels.
- Maximum of 4 simultaneous calls to IP receivers within a single apartment / office.
- Unlimited entry panels.

- Unlimited iOS/Android integrations.
- Unlimited IP receivers.
- WiFi connectivity within apartment / office.
- · Cloud connectivity via landlord's internet connection.



MINI SERVER CONFIGURATION FOR MULTI DWELLING UNITS USE THE MINISERVER TO INCREASE THE CALL CAPACITY


- In this configuration: • Unlimited IP receivers. • Maximum of 10 simultaneous calls from entry panels. • Maximum of 10 simultaneous calls to IP receivers • WiFi connectivity within apartment / office. within a single apartment / office. • Cloud connectivity via local apartment internet connection. • Unlimited entry panels. Example setup for apartment / office capable of handling up-to 10 simultaneous calls connecting through IP devices. through IP devices with 3G/4G connectivity. LAN LAN FUTURA IP FUTURA IP FUTURA IP monitor **EUTURA IP monitor** monitor monitor LAN LAN 99 **99 FUTURA IP FUTURA IP** FUTURA IP monitor FUTURA IP monitor monitor monitor LAN Smartphone(s) or tablet(s)* + FUTURA IP monitor FUTURA IP monitor LAN 0 Ŀ
 - FUTURA IP monitor

Sector and the sector of the

ETI/miniSER

server

----.....



*Via the free XIP mobile app. † Not available through CAME BPT. Representative illustration; please contact our sales team for technical schematics.


MAIN SERVER CONFIGURATION FOR MULTI DWELLING UNITS

FOR SYSTEMS REQUIRING STATE OF THE ART CONCIERGE FACILITIES

In this configuration:

- Maximum of **20** simultaneous calls from entry panels.
- Maximum of 18 simultaneous calls to IP receivers within a single apartment / office.
- Unlimited entry panels.
- Unlimited iOS/Android integrations.

- Unlimited IP receivers.
- WiFi connectivity within apartment / office.
- · Cloud connectivity via landlord's internet connection.
- Unlimited concierge PC based switchboards.




MAIN SERVER CONFIGURATION FOR MULTI DWELLING UNITS

INCLUDING MINI SERVER - LIMITLESS POSSIBILITIES

In this configuration:

- Maximum of 20 simultaneous calls from entry panels.
- Maximum of **10** simultaneous calls to IP receivers
- within a single apartment / office.
- Unlimited entry panels.
- Unlimited IP receivers.



- WiFi connectivity within apartment / office.
- Cloud connectivity via local apartment internet connection.
- Note: a dedicated rack mount server is available, for up to 65 simultaneous calls. Please contact our sales team for details.

*Via the free XIP mobile app. † Not available through CAME BPT. Representative illustration; please contact our sales team for technical schematics.





SEAMLESS INTEGRATION WITH IP360 FROM BPT



It is now possible for seamless IP integration between Crestron monitors and BPT systems.

Since 2010 there has been extensive development and close technical cooperation between Crestron (world leader in AV and home automation system controls) and BPT – UK (leader in the video door entry system market). This has lead to truly cutting edge lifestyle control.

Crestron and BPT R&D departments have worked together to create a system with full interoperability between the BPT IP360 video door entry system and Crestron home control. Without the requirement for any additional specialist units, the BPT and Crestron systems can work in complete harmony.

Entry control can be accessed seamlessly with Crestron touchscreen panels and remote devices. And release the full functionality of the IP360 system, such as the IP porter facilities, by using a shared network.

With this level of flexibility from two market leaders, the possibilities are limitless.

Many other leading brands of automation control are supported by IP360.

For more details, contact the BPT sales department on sales@bpt.co.uk or 01442 230 800.


- Single or multi network architecture as required.
- Standard LAN platform.
- · Central switchboard management system.
- Direct IP connection.
- Easy to install.






INTEGRATION DEMO SUITE IS NOW OPEN, CONTACT OUR HEMEL HEMPSTEAD BRANCH TO ARRANGE

SINGLE-FAMILY HOME SERVERLESS



SINGLE-FAMILY HOME

MINI SERVER ΙΔΝ ***** PoF THANGRAM IP switch(es) THVIP/1 video entry panel I AN 1001 2 VAS/101 ETI/miniSER power supply server





16



Crestron monitor





*Via the free XIP mobile app. † Not available through CAME BPT. Representative illustration; please contact our sales team for technical schematics.


IP360 PRECONFIGURED KITS

IP360 KITS


IP360 is completed with a range of standard kits to enable easy ordering. These kits are preconfigured so that all you have to do is follow our quickstart guide and add a series of simple credentials, using your mobile phone, to complete the setup.



EXAMPLE CONNECTIVITY KIT WITHOUT MONITOR



FUTURA IP monitor





THANGRAM IP 1 way IP360 video keypad kit to 3 i0: and 1 FUTURA IP white. Single call button, with acce includes black FUTURA IP.

18


	Code	Price
oid devices. Single call button.	IP360THV/1	£835.00
)S/Android devices. Single call	IP360THKV/1	£971.25
oid devices white FUTURA IP.	IP360THFW/1	£1395.00
)S/Android devices ess control keypad,	IP360THKFW/1	£1531.25
oid devices black FUTURA IP.	IP360THFB/1	£1395.00
S/Android devices ess control keypad,	IP360THKFB/1	£1531.25

CAME CNNECT

CLOUD CONNECTED TECHNOLOGY

BE PART OF THE FUTURE

CAME Connect enables both the Installer and the end-user to monitor and control the equipment through an easy to use cloud-based app.



DEVICES MAP

SUPPORT REQUESTS

All of your installation sites at your finger tips



For more information, visit www.CAMEconnect.net



COMPONENTS PRICELIST

THANGRAM VIDEO PANELS

Article	Description	Code	Price
	THANGRAM IP video entry panel (PoE) 1 button.	THVIP/1	£835.00
	THANGRAM IP video entry panel (PoE) 2 button.	THVIP/2	£837.50
	THANGRAM IP video entry panel (PoE) 3 button.	THVIP/3	£840.00
	THANGRAM IP video entry panel (PoE) 4 button.	THVIP/4	£840.00
	THANGRAM IP video entry panel (PoE) 6 button.	THVIP/6	£858.75
	THANGRAM IP video entry panel (PoE) 8 button.	THVIP/8	£865.00
	THANGRAM IP video entry panel (PoE) with keypad 1 button.	THKVIP/1	£971.25
	THANGRAM IP video entry panel (PoE) with keypad 2 button.	THKVIP/2	£977.50
	THANGRAM IP video entry panel (PoE) with keypad and digital display. For fully digital calling to multiple units.	THVDIGI	£1073.08

THANGRAM AUDIO PANELS

Article	Description	Code	Price
100 100 100	THANGRAM IP audio entry panel (PoE) 1 button.	THAIP/1	£530.00
	THANGRAM IP audio entry panel (PoE) 2 button.	THAIP/2	£532.50
	THANGRAM IP audio entry panel (PoE) 3 button.	THAIP/3	£535.00
100 100	THANGRAM IP audio entry panel (PoE) 4 button.	THAIP/4	£535.00
200 2003	THANGRAM IP audio entry panel (PoE) 6 button.	THAIP/6	£553.75
	THANGRAM IP audio entry panel (PoE) 8 button.	THAIP/8	£560.00
	THANGRAM IP audio entry panel (PoE) with keypad 1 button.	THKAIP/1	£666.25
	THANGRAM IP audio entry panel (PoE) with keypad 2 button.	THKAIP/2	£672.50
	THANGRAM IP audio entry panel (PoE) with keypad and digital display. For fully digital calling to multiple devices.	THADIGI	£768.08

FUTURA IP MONITORS

Article	Description	Code	Price
	FUTURA IP hands-free video receiver with colour 7" LCD display, equipped with user graphics interface. Power over Ethernet (PoE) power supply, built-in voicemail function, soft-touch buttons, white. Dimensions (LxHxD): 212 x 161 x 28 mm wall-mounted, 212 x 161 x 10.5 mm recessed	FUTURA IP WH	£533.75
	FUTURA IP hands-free video receiver with colour 7" LCD display, equipped with user graphics interface Power over Ethernet (PoE) power supply, built-in voicemail function, soft-touch buttons, black. Dimensions (LxHxD): 212 x 161 x 28 mm wall-mounted, 212 x 161 x 10.5 mm recessed.	FUTURA IP BK	£533.75

COMPONENTS PRICELIST

SYSTEM COMPONENTS

Article	Description	Code	Price
	Full system server. This allows the use of porter software and centralises the access control functions and porter services. It comes in a container measuring 150 x 150 x 51mm. IP40 protection rating. Power supply 230 V AC 600 mA.	ETI/SER XIP	£1975.00
	XIP system mini server. Low DIN 6-module dimensions. Requires power supply (12 - 24 V DC, 300 mA max).	ETI/miniSER	£815.00
	3-relay unit for auxiliary services (controlling lights, openings, ringtones etc.). Low DIN 4-module dimensions. IP30 protection rating. Power supply 11/18V DC 200 mA.	VLS/3	£155.00
	Digital call module for multi dwelling with RFID and built-in display. Keypad can be used for coded access.	DCOMBO	£253.08
	Access control keypad metal colour satin chrome for coded access. Dimensions (LxHxD): 60x60x14 mm.	DNA/ME	£146.25
	Additional power supply for mini server. Low DIN 4-module dimensions. IP30 protection rating. Powered from mains 230 V AC 50/60 Hz.	VAS/101	£77.50
	Additional power supply. Low DIN 8-module dimensions. IP30 protection rating. Powered from mains 230 V AC 50/60 Hz.	VAS/100.30	£90.00
	Single button. Dimensions (LxHxD): 20x60x14 mm.	DPS	£5.00
	Double height button. Dimensions (LxHxD): 40x60x14 mm.	DPH	8.75
2 3	Double button. Dimensions (LxHxD): 20x60x14 mm.	DPD	£11.25
-	Single plastic cap covered in metal colour satin chrome. Dimensions (LxHxD): 20x60x12 mm.	DTS/ME	£5.00
	Single plastic cap covered in metal colour satin chrome. Dimensions (LxHxD): 20x60x12 mm.	DTH/ME	£6.25
	Information module for generic messages. Do not use as a call button.	DMI	£5.43

ACCESSORIES FOR INSTALLATION

Article	Description	Code	Price
	Plastic recessed box. For use with DCI or DCI/ME. Dimensions (LxHxD): 140x294x54.5 mm.	DSI	£5.00
H	Plastic recessed frame covered in satin chrome, metal colour. Requires DSI. Dimensions (LxHxD): 127x280x30 (1.2) mm.	DCI/ME	£22.50
	Front plate in anodised aluminum. Opaque black colour. Dimensions (LxHxD): 99x254x18 mm.	DPF/NF	£23.75
	Front plate in anodised aluminum. Metal colour. Dimensions (LxHxD): 99x254x18 mm.	DPF/ME	£23.75

ACCESSORIES



Desk mount for FUTURA IP monitor.

Flush mount box for FUTURA IP monitor.

KT VXL	£92.50
FUTURA BB	£26.25

P360 SYS




Milesight offer comprehensive IP video surveillance solutions.

Milesight will integrate seamlessly with the IP360 system and a wide variety of CAME BPT products.



EXAMPLE CCTV LAYOUT WITH MINISERVER & CCTV



CCTV PRICELIST

MINI SERIES

Article	Description	Resolution	Lens	Video compression	VGA	Code	Price
<u></u>	IR mini dome camera.	2048*1536 @20fp	Fixed lens 3.6mm	H.264 H.265	\checkmark	MS-C4482-PB 4.0MP	£187.80
•	Vandal-proof mini dome camera.	2592*1520 @20fps	Fixed lens 3.6mm	H.264 H.265	~	MS-C4473-PB 4.0MP	£213.90
()	MS-A73 adapter plate. 15*122.5*10mm, 28g * ABS+PC * For side outlet.					£2.60	
<u>()</u>	MS-A71 wall mount. 140×215mm, 348g * Aluminum alloy * For wall or vertical structure.					£20.85	
-5	Mini bullet camera.	2592*1520	Fixed lens 4mm	H.264 H.265	\checkmark	MS-C4463-PB	£253.03

NVR SERIES

Article	Description	MP support	On-board memory	Local display		Code	Price
Article				HDMI	VGA	code	Flice
Ü	4K/H.265 Mini NVR. 1* 100M/1000M. 2*USB2.0 interfaces.	3840*2160 (4K/8MP)	1TB	~	N/A	MS-N1009-UT	£323.45
	WD 1TB 2.5inch HDD.	1TB capacity S Can be added				WD10JUCT	£247.80

ACCESSORIES

Article	Description	Details	Code	Price £26.08
00	Pole mount.	170*51.5*152.6mm, 720g. Installation environment: For strapping cameras on poles between 102-127mm (4.1-5 inches) in diameter. Applicable for all Milesight network cameras.	MS-A01	
2	Corner bracket (internal).	170*23.2*205.3mm, 543g. For mounting cameras on an internal corner. Applicable for all Milesight network cameras.	MS-A02	£26.08
Corner bracket (external).		170*152.6*76.3mm, 905g. For mounting cameras on an external corner. Applicable for all Milesight network cameras.	MS-A03	£26.08

NETWORK SWITCHES

Article	Description	Details	Code	Price	
Network switch. Network switch. Network switch. Network switch.		4-port PoE switch + 2 uplink ports. Power supply included.	XNS04P	£95.20	
		8-port PoE switch + 1 Uplink port. Power supply included.	XNS08P	£190.38	
		16-port PoE managed switch + 4 Uplink ports (2 ethernet and 2 optical). 100-240 VAC power supply.	XNS016PF	£872.65	



CAME BPT - South - Tel: 01442 230 800 - Fax: 01442 244 729 Liberta House, Maxted Road, Maylands Industrial Estate, Hemel Hempstead HP2 7DX

> CAME BPT - Midlands - Tel: 0115 921 0430 - Fax: 0115 921 0431 Unit 3, Orchard Park Industrial Estate, Town Street, Sandiacre, Nottingham NG10 5BP

> CAME BPT - North - Tel: 0161 406 9800 - Fax: 0161 406 4791 Unit 14, Latham Close, Bredbury Park Industrial Estate, Bredbury Stockport, SK6 2SD

CAME BPT - IRELAND - Tel: 01 429 5660 - Fax: 01 429 5956 Unit A1, Ballymount Corporate Park, Ballymount, Dublin 12, IRELAND



For account customers, please contact your local branch for trade terms.