Revision Date 05/26/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	Boardwalk Air Freshener Citrus	BWK904
Material number	:	1048768 / A07759	
Manufacturer or supplier's	deta	ails	
Company	:	Boardwalk / Essendant Co.	
Address	:	One Parkway North Deerfield, IL 60015	
Telephone	:	844-828-5617	
Emergency telephone nu	mb	ers	
For SDS Information		: 844-828-5617	
For a Medical Emergency	/	:	
For a Transportation		: Chemtel: 1(800)255-3924	

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Emergency

Appearance	Aerosol containing a liquefied gas
Colour	yellow
Odour	characteristic

GHS Classification

Flammable aerosols Gases under pressure Eye irritation Specific target organ toxicity - single exposure	 Category 1 Liquefied gas Category 2A Category 3 (Central nervous system)
GHS Label element	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use.

sion 1.0	ESHENER CITRUS 12N6.6 Revision Date 05/26/2015	BWK904 Print Date 03/21/2017
	 P261 Avoid breathing dust/ fume/ g P264 Wash skin thoroughly after ha P271 Use only outdoors or in a well P280 Wear eye protection/ face pro Response: P304 + P340 + P312 IF INHALED: and keep at rest in a position comfor POISON CENTER or doctor/ physic P305 + P351 + P338 IF IN EYES: F for several minutes. Remove contact easy to do. Continue rinsing. P337 + P313 If eye irritation persists attention. Storage: P405 Store locked up. P410 + P412 Protect from sunlight. temperatures exceeding 50 °C/ 122 P403 Store in a well-ventilated plact Disposal: P501 Dispose of contents/container regulation. 	as/ mist/ vapours/ spray. Indling. -ventilated area. tection. Remove victim to fresh ai ortable for breathing. Call cian if you feel unwell. Rinse cautiously with wate of lenses, if present and s: Get medical advice/ Do not expose to °F. e.
Potential Health Effects		
Carcinogenicity:		
IARC	No component of this product present a equal to 0.1% is identified as probable, human carcinogen by IARC.	
ACGIH	No component of this product present a equal to 0.1% is identified as a carcinog carcinogen by ACGIH.	
OSHA	No component of this product present a equal to 0.1% is identified as a carcinog	
NTP	carcinogen by OSHA. No component of this product present a equal to 0.1% is identified as a known o by NTP.	

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 50 - < 70
propane	74-98-6	>= 20 - < 30

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure.

Version 1.0	Revision Date 05/26/2015	Print Date 03/21/2017
	If unconscious place in recovery pos advice.	sition and seek medical
In case of skin contact	 Wash off immediately with plenty of minutes. If on clothes, remove clothes. Wash contaminated clothing before If skin irritation persists, call a physic 	re-use.
In case of eye contact	 Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a sp In case of contact, immediately flush for at least 15 minutes. 	
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to an If symptoms persist, call a physician DO NOT induce vomiting unless dire physician or poison control center.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Use personal protective equipment.
protective equipment and	Ensure adequate ventilation.
emergency procedures	Remove all sources of ignition.

Version 1.0	Revision Date 05/26/2015	Print Date 03/21/2017	
	Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.		
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains ir respective authorities. 		
Methods and materials for containment and cleaning up			

BWK904

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations. Do not breathe vapours or spray mist.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Keep in a dry, cool and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Keep away from oxidising agents, strongly acid or alkaline materials and amines.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1

Version 1.0

Revision Date 05/26/2015

BWK904 Print Date 03/21/2017

		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses
Skin and body protection	:	impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: yellow
Odour	: characteristic
Odour Threshold	: no data available
рН	: no data available

Version 1.0

Revision Date 05/26/2015

BWK904
Print Date 03/21/2017

Melting point/freezing point	:	no data available no data available
Boiling point Flash point	:	
Evaporation rate	:	no data available no data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit	:	no data available
Lower explosion limit	:	no data available
Vapour pressure	:	no data available
Relative vapour density	:	no data available
Density	:	no data available
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	not determined
Partition coefficient: n- octanol/water	:	no data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	no data available
Viscosity		
Viscosity, kinematic	:	no data available
Heat of combustion	:	36.44 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Acids Oxidizing agents Bases Amines
Hazardous decomposition products	: Carbon monoxide Carbon dioxide (CO2)

Version 1.0

Revision Date 05/26/2015

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components: acetone: Acute oral toxicity : LD50 rat: 5,800 mg/kg Acute inhalation toxicity : LC50 rat: 132 mg/l Exposure time: 3 h LC50 rat: 50.1 mg/l : LD50 guinea pig: > 7,426 mg/kg Acute dermal toxicity LD50 rabbit: > 7,426 mg/kg propane: Acute inhalation toxicity : LC50 mouse: 1,237 mg/l Exposure time: 2 h LC50 rat: 658 mg/l Exposure time: 4 h LC50 rat: 1,355 mg/l

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

acetone: propane:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available Persistence and degradability no data available **Bioaccumulative potential** Product: Partition coefficient: n-: Remarks: no data available octanol/water Mobility in soil no data available Other adverse effects no data available Product: Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances This product neither contains, nor was manufactured Remarks with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). : no data available Additional ecological information

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Version 1.0	Revision Date 05/26/2015	Print Date 03/21/2017
Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations. 	
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch	n on, the empty drum.

BWK904

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Fire Hazard Sudden Release of Pressure Hazard Acute Health Hazard
SARA 302	:	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

	DUINOUT
Revision Date 05/26/2015	Print Date 03/21/2017
: SARA 313: This material does not co components with known CAS numbe threshold (De Minimis) reporting leve Title III, Section 313.	rs that exceed the
This product does not contain any ch California to cause cancer, birth defe reproductive harm.	
is product are reported in the following inve	entories:
On TSCA Inventory	
This product contains one or several compone Canadian DSL nor NDSL.	ents that are not on the
Not in compliance with the inventory	
Not in compliance with the inventory	
	 SARA 313: This material does not co components with known CAS numbe threshold (De Minimis) reporting leve Title III, Section 313. This product does not contain any ch California to cause cancer, birth defe reproductive harm. is product are reported in the following inve On TSCA Inventory This product contains one or several compon- Canadian DSL nor NDSL. Not in compliance with the inventory Not in compliance with the inventory Not in compliance with the inventory

BWK904

3


4

2

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION



OSHA GHS Label Information:

Hazard pictograms	
Signal word	: Danger:
Hazard statements	: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	:
	Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/

Version 1.0

Revision Date 05/26/2015

fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection. **Response:** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. **Storage:** Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place.

BWK904

Print Date 03/21/2017

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.0
Revision Date:	05/26/2015
Print Date:	03/21/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.