


Precision Steel Car's Riveted 40 Ft. Boxcar



Precision Steel Car

Website:

www.precisionsteelcar.com

E-mail:

info@precisionsteelcar.com

Revised 4/5/12

Paul Vernon: (513) 571-5739

PSC Riveted 40 ft. Boxcar Kit: Parts List

<u>Body</u>	<u>Qty.</u>	<u>Material</u>	<u>Ladders</u>	<u>Qty.</u>	<u>Material</u>	<u>Roof</u>	<u>Qty.</u>	<u>Material</u>
Riveted Side 6ft Door	2	Steel	Ladder Upright S1	2	Alum	Roof Panel Bowtie	1	Steel
Top Door Track 6ft	2	Steel	Ladder Upright S2	2	Alum	Roof Bowtie	10	Steel
Bottom Door Track 6ft	2	Steel	Ladder Upright E1	2	Alum	Roof Hat Sections	11	Steel
Door Vertical Frame	2	Steel	Ladder Upright E2	2	Alum	Walkway Middle Bracket	6	Steel
Door Opening Brace	4	Steel	Ladder Bracket	10	Steel	Walkway Side Bracket	4	Steel
Dreadnaught End Backer	2	Steel	Ladder Bottom Mounts	4	Steel	Walkway End Bracket	2	Steel
Dreadnaught Top Stamping	2	Steel	Angled Stirrup Step	2	Steel	Punched Walkway 2.5"x10"	5	Alum
Dreadnaught Bottom Stamping	2	Steel	Grab Iron 2.25" D	28	Alum	Punched Walkway 2.5"x6.875"	2	Alum
Floor Sheet	1	Steel				Punched Walkway 3.5"x5.625"	2	Alum
Square Stirrup Step	2	Steel	<u>Frame</u>	<u>Qty.</u>	<u>Material</u>	Grab Iron 2.5" A	4	Alum
Uncoupling Plate	2	Steel	Main Frame	2	Steel			
Grab Iron Bracket	8	Steel	Major Cross Beam	2	Steel			
Grab Iron 2.25" A	2	Alum	Minor Cross Beam	5	Steel			
Grab Iron 2.5" D	4	Alum	Bolster Frame	4	Steel			
Grab Iron 2.75" C	2	Alum	Frame End	2	Steel			
Door Catch Left	2	Steel	Frame Bottom	1	Steel			
Door Catch Right	2	Steel	Cross Beam Bottom	2	Steel			
Brake Wheel Housing Kit	1	Pkg	Coupler Plate	2	Steel			
Modern Brake Wheel	1	Steel						
Brake Wheel Platform Kit	1	Pkg	<u>Door</u>	<u>Qty.</u>	<u>Material</u>			
Standoff 3/8" Long	4	Alum	6ft Youngstown Door Backer	2	Steel			
Bell Crank	1	Brass	6ft Youngstown Door Frame	2	Steel			
Bell Crank Mount	1	Steel	Door Catch Mount	4	Steel			
Boxcar Door Latch Kit	2	Pkg	Door Catch Handle	2	Steel			
Boxcar Door Stop Top	2	Brass	Youngstown Door Detail	4	Steel			
Boxcar Door Stop Bottom	2	Brass	Grab Iron 2" C	2	Steel			
Triple Valve Mount	1	Steel						
Brake Cylinder Mount	1	Steel						
Reservoir Mount	1	Steel						
Roof Brace	2	Steel						
							Total Parts	198

Recommended Assembly Techniques

- Follow Instruction Steps.
- We suggest buying Clecos, they are great temporary fastening devices used in riveting, get them at Aircraft Tool Supply Company. (www.aircraft-tool.com)
- Always test fit pieces without riveting or welding, to see how the kit goes together.
- Do not over squeeze/set rivets in the aluminum extrusion, it as soft as the aluminum rivets and will bow and twist.
- Refer to the PSC website for pictures of an assembled car.
- **Tack weld, when applying the final welds the longer pieces will shrink over the entire length.** Finish welding from one end to the other to avoid warping.
- It is easier to undo a tack weld than a bead.
- Plan your welds, most of the welds can be hidden.
- Skip weld every 4-6 inches, continuous welding will cause extreme warping and twisting.
- Add any extras, such as provisions for safety chains, as early as possible. It's easier to modify a piece before it is welded to the assembly.

Items to be Supplied by Buyer

Recommended Tools

- Welder
- Welding Clamps, C-clamps, Visegrip
- Rivet Gun/Rivet Squeezer
- Cordless Drill with #42 Drill bit
- Cleco Pliers/Clamps

Fasteners

- 3/32" Dia. Rivets Lengths:
 - ~1200, 3/16"
 - ~250, 1/4"
 - ~150, 5/16"
- 1/8" Dia. Rivets Lengths:
 - ~10, 3/16"
- 3-48 Hex Head Screws or per customer preference
- Epoxy for bonding metal (Loctite 330 Depend Adhesive recommended)

Couplers and Trucks are not included with this kit.

Mounting of the trucks is to be determined by the buyer. This includes making adapter plates for mounting the trucks. The buyer is responsible for creating any additional parts needed to mount trucks or couplers. When creating these parts the buyer must calculate and modify the adapters, trucks, or kit for side bearing heights and coupler heights. Couplers and Trucks should be mounted at Step 7

Precision Steel Car is not responsible for defects resulting from poor assembly or careless handling. Replacement parts may be available to purchase.


Step 1


****Before starting with the frame, make any necessary preparations for couplers and trucks.*

Begin by tacking the coupler plate into the frame sides. Lay the assembly upside down and continue by adding in the cross members and bolster frames.

Add the bottom sheet and cross member covers. Plug weld over the tabs.

Weld on frame ends






Step 2

Build the door by plug welding the frame to the door back plate. Weld in door slide stop mechanism. Rivet on the top door details. Finish the rivet line at the bottom of the door.


Apply the grab iron and door latch. Form an eyelet from 3/32 wire bent 180 degrees around a 1/8 rod.

Orient latch as shown.




Note: Insert Door Catch into Mounts before welding

Step 3



Step 4



Epoxy top edge of end stampings

Start by tacking the sides onto the end backer plates, do not rivet yet. Start with the bottom dreadnaught end stampings, clamp in place. The bottom of the end should match the bottom of the sides.

Drill from inside through stamping using holes in the sides as guides.


Next clamp the top end stamping in place, it will overlap the bottom by approximately $\frac{1}{2}$ ". Use a mallet to adjust bent tabs as needed.

Use epoxy to fasten top edge of upper dreadnaught end stamping.

Rivet ends.

Center raised panels between rivet lines


Line up end with sides



Corner Detail

Step 5

Assemble the ladders as shown. If using solid rivets with a squeezer *do not squeeze too hard*, the aluminum extrusion will distort. Do not use a pneumatic rivet tool (air hammer) to set rivets.



Side Ladder Assy.: 2/car

Ladder Upright S1


Ladder Upright S2

(2) Ladder Brackets

(7) 2 1/4" D Grab Irons

(2) Ladder Bottom Mounts

(1) Angled Stirrup



End Ladder Assy.: 2/car


Ladder Upright E1

Ladder Upright E2

(3) Ladder Brackets

(7) 2 1/4" D Grab Irons

Step 6



Brake wheel Assembly
(one end only)

End Ladder Assembly



Walkway
(one end only)


Detail the car ends as shown.

The Brake wheel assembly is mounted on four (4) 5/16" standoffs, the holes are located on the backer panel.


The walkway will mount on the raised ribs of the stamped ends. Line up the notch with the chain of the brake wheel assembly.

The walkway and brake wheel are mounted on one end only.


Drill through stamped ends to mount end ladder assemblies. The ladder brackets will line up with the raised ribs.



Step 7



Frame End Detail



*****Ensure provisions have been made for mounting trucks and couplers at this point!**


With the car upside down, weld the floor into the car body. Note orientation of the slots and holes for the stirrup steps. The floor will be level with the ends of the car. Use many small tack welds. Weld the frame in place once the floor is in place. The frame will fit into slots in the floor and end panels

Floor flush with sides/ends

Step 8



Door Stop




Uncoupling Plate

Door Catch
(Left and Right)




Side Ladder

Square Stirrup



Side Ladder
Uncoupling Plate



Door Catch
Placement

Insert side ladder assembly into slots in the floor sheet, weld and bolt ladder assembly in place.

Insert uncoupling plate into groove in the end of the floor sheet, weld in place.

Rivet the square stirrups.

Insert door assemblies into door tracks, bolt door stops in place.

Tack weld the door catches (left and right) to the lower door track. These should be placed to hold the door fully closed and fully open.

Step 9

Begin by welding the raised panels to the roof. Center over the holes and plug weld.

Epoxy the hat sections across the width of the roof. Center between the raised panels and the rivet holes with the $\frac{1}{2}$ " spacing.




Drill and rivet the hat sections and the end walkway supports. Also rivet the remaining holes around the perimeter of the roof.

Tack weld the remaining walkway supports. Note their spacing below.

Bolt the walkways in place with the 10" long sections in the middle with seams on supports.


The grab irons mount on corner of the 3 1/2" Wide end walkways.

This finishes the standard kit.



Hat Section Detail

Step 10




Bell Crank & Mount

Install the bell crank mount to the bottom of the car in-line with the chain from the brake wheel housing. Install the bell crank into the mount as shown thread chain onto it.

Weld the two roof braces on either side of the door to provide additional stiffness to the sides.

(Note: These parts are not necessary if the roof is permanently attached.)


Roof Braces



Step 11: Optional Details

(if purchased)

The Anglecock and Gladhand assembly mounts to the right side of the car frame end on both ends of the car. Locate the reservoir on the bottom of the car between the cross members. Weld the cylinder mount to the cross member. The brake cylinder and triple valve mounts weld to the floor of the carbody. Bolt the valve and cylinder to the mounts.




Glad Hand Assembly

Triple Valve
& Mount

Cylinder
& Mount

Reservoir
& Mount



For More Detail Parts or Other Car Kits, Visit:

www.precisionsteelcar.com

Or e-mail: info@precisionsteelcar.com