



PERFECTION  
SOLUTIONS

2008

**SIGNAMAX**<sup>™</sup>  
CONNECTIVITY SYSTEMS

**Signamax LLC**, a US based company, is uniquely focused on providing high-performance networks and complex distribution solutions for customers worldwide. We provide complete unified products for copper and fiber based network connections designed for increased performance, reliability and easy installation. Signamax components are also popular for their valued performance/price ratio.



**Signamax worldwide support**

Our knowledgeable sales, technical support and engineering staff is dedicated to understand the requirements of our customers. With company headquarters in Washington DC and contracted distributors in 14 European countries and production in US, Europe and Asia, Signamax Connectivity Systems is uniquely positioned to deliver complete network solutions to our customers worldwide. Moreover, with our new central warehouse and sales center for Europe in Czech Republic we can now provide better service and support to all European partners and customers.

**Product solutions**

With **Signamax Connectivity Systems** you can get the right solution for comprehensive complete infrastructure.




Signamax Network Connectivity Systems line represents one of the industry's best products for high performance Ethernet, Fast Ethernet and Gigabit Ethernet components including interface cards, switches and media converters supporting both copper and fiber optic based networks. Signamax Media Converters allow mixed media and speeds in networks for optimum performance. Signamax managed and unmanaged Switches range from 5 to 24 ports with support for 10/100Base to 1000Base speeds with both copper and fiber terminations. Signamax Wireless Products are perfectly suitable for mobile users and allow building of high-performance wireless networks and links. Signamax wireless networks are interactively compatible and allow high speeds of 11/22/54/108 Mbps.



Our premise cabling product line includes patch cords, panels and network components for Category 5 Enhanced, Category 6, Category 6A, Category 7 and fiber optic systems designed to exceed the latest ANSI/TIA/EIA, ISO/IEC and CENELEC specifications. We also supply distribution frames, data racks and cable management systems. All certified Signamax system installations are covered by 20 Years Registered System Warranty encompassing all system elements.

**Standards and Quality**

You will find that our products have better design, easier installation and bring unique level of performance and reliability to your network than most suppliers can offer. They are designed for the most demanding applications engineered to meet stringent standards and specifications. Each manufactured product has been tested to comply with the standards of organizations such as ANSI/TIA/EIA, ISO/IEC, CENELEC and IEEE. Signamax network and complex solutions are certified by independent laboratories and backed up by long-term performance warranties that keep peace in your mind.



**RoHS**

We, here at Signamax, care about the environment we live in. Therefore our products comply with the RoHS directive (2002/95/EC) valid from July 1st, 2006.

Visit the [www.signamax.eu](http://www.signamax.eu) web page to find your local Signamax representative.

# Table of Content

## Network Connectivity Systems

### A: Triple Play

IP Phones	A1–A2
VoIP ATA Gateway	A3
VoIP Gateway	A4
VoIP Gateway w. SIP Proxy Server	A5
VoIP Gateway w. H323 Gatekeeper	A5
Modular High Density VoIP Gateway	A6
IP PBX	A7
IP DSLAM	A8
ADSL 2/2+ Routers	A9–A10
IP Camera	A11–A12
IP Set Top Box	A13–A14

### B: Media Converters

Switching Fiber Converters	B1–B2
10/100 to 100BaseFX PoE Fiber Media Converters	B3–B4
Switching Managed Media Converters	B5–B6
10/100BaseT/TX Switching PCI Fiber Optic Media Converters	B7
VDSL Ethernet Extender	B8
10/100BaseT/TX Switching Mini Fiber Optic Media Converters	B9
Stand Alone Managed Switching Media Converters	B10
Hardened Media Converters with LFS	B11
Single Channel Hardened Media Converters	B12
Gigabit Media Converters	B13
10/100/1000 Switching Fiber Optic Media Converters	B14
SFP Fiber Converters	B15
Serial Data to Fiber/TP Media Converters	B16
Single Fiber WDM Converters	B17
Singlemode to Multi Mode Converters	B18
Basic Media Converters	B19
12-Port Rack Mount Media Converters	B20
16-Bay Media Converter Rack Mount Chassis	B21
18-Bay Rack Mount Managed Media Converter Chassis	B22
8-Bay Managed Media Converter Chassis	B23
WebSmart Media Converters	B24
16-Slot Chassis for Modular EPON Media Converter	B25–B26

### C: Ethernet Switches and Routers

5- & 8-Port 10/100 Desktop Switches	C1–C2
8-Port 10/100 Desktop PoE Switches	C3
8-Port Managed Desktop Switches	C4
Desktop WebSmart Fast Ethernet Switch	C5
Fast Ethernet 16-Port Desktop Switches	C6
10/100BaseT/TX Rack Mount Unmanaged Ethernet Switch	C7
16-Port WebSmart 10/100 Managed Ethernet Switches	C8
Gigabit PoE Management Switch Series	C9
Modularized 24+2G Access Switch	C10
Metro and Metro PoE Stackable Switches w. 2 Combo Ports	C11
Metro Stackable Switches with 4 Combo Ports	C12
Compact Fiber Access Switch	C13
5- & 8-Port 10/100/1000BaseT/TX Desktop Switches	C14
WebSmart Gigabit Ethernet Switches	C15
Gigabit Management Switch	C16
Advanced Gigabit L2 Managed Switches	C17
24-Port 10/100 + 4G Combo L3 Switches	C18
Hardened Ethernet Switches	C19
Hardened Managed Switches	C20
4-Port Broadband Access Router	C21
Signamax USB NAS	C22
SFP Fiber Modules	C23
10 Gbps Modules	C24

### D: Network Interface Cards

Gigabit Ethernet PCI Adapter Cards	D1
Fast Ethernet PCI Adapter Cards	D2

### E: KVM Switches

2-Port USB KVM Switch	E1
4-Port Slim Desktop Switch	E2
8- and 16-Port 19" Rackmount KVM Switches	E3–E4
KVM Hydra Cables	E5
VGA Splitter	E6

### F: Wireless LAN

Wireless Access Point 802.11b/g	F1
Wireless AP/Router 802.11b/g	F2
Wireless PCI Card 802.11b	F3
Wireless PCI Card 802.11b/g	F4
Wireless PCMCIA Card 802.11b/g	F5
Wireless USB Dongle 802.11b/g	F6
Wireless AP/Router 802.11a/b/g	F7
Wireless Access Point 802.11a/b/g	F8
Wireless Outdoor Access Point 802.11a/b/g	F9
Wireless PCI Card 802.11a/b/g	F10
Wireless PCMCIA Card 802.11a/b/g	F11
Wireless USB Dongle 802.11a/b/g	F12
Wireless Mini PCI Card 802.11a/b/g	F13
Wireless AP/Router 802.11b/g/n	F14
Wireless MIMO Client Adapters 802.11b/g/n	F15
Antennas for 2.45 GHz Band	F16
Accessories for WiFi Units	F16
Antennas for 5 GHz Band	F17–F18

## Premise Connectivity Systems

### G: Structured Cabling

Introduction to Structured Cabling	G1–G3
What is Structured Cabling?	G3
Structured Cabling Testing	G4–G6
10GBaseT and Structured Cabling	G7–G8

### H: Work Area Outlet Systems

Category 6 Wall Outlets	H1
Category 5E Wall Outlets	H2
Category 6A Keystone Jacks	H3
Category 6 Keystone Jacks	H4
Category 5E Keystone Jacks	H5
Keystone Jack Modular Outlets	H6
Keystone Multimedia Modules	H6

### I: Patch Panels

Unloaded Shielded Patch Panel for 10G	I1
Category 6 Shielded Patch Panels	I2
Category 6 Unshielded Patch Panels	I3
Category 5E Shielded Patch Panels	I4
Category 5E Unshielded Patch Panels	I5
ISDN Patch Panels	I6

### J: Patch Cords/Testers

S-FTP Category 6A Patch Cords	J1
S-FTP Category 6 Patch Cords	J1
S-FTP Category 5E Patch Cords	J2
UTP Category 6 Patch Cords	J2
UTP Category 5E Patch Cords	J3
T-Adapters and Testers	J4
Inline Couplers and Connection Boxes	J4

### K: Installation Cable

S-STP Category 7 Installation Cable	K1
Certificates 10GBaseT	K2
FTP Category 6 Installation Cable	K3
UTP Category 6 Installation Cable	K4
UTP Category 5E Installation Cable	K5
FTP Category 5E Installation Cable	K6

### L: Fiber Optic Systems

Fiber Optic Patch Cords	L1–L2
Fiber Optic Adapters	L3
Fiber Optic Patch Panels	L4
Wall Mount Fiber Optic Box	L4

### M: Data Racks

19" Data Racks	M1–M2
19" Server Racks	M3
19" Wall Mounted Racks	M4
19" Assembled Data Racks	M5–M6
19" Fan Units	M7
19" Shelves	M8–M9
Diode Lighting Unit	M10
Accessories	M11–M12

# Keeping Your World



In today's technology driven environment, the backbone of your organization is your network—keeping you connected to staff, customers, suppliers, and the world at large. To run a successful enterprise, you need a network that is reliable, fast, and ready to accommodate the inevitable growth and change you will experience. We are the company that can deliver you network solutions that are up to all those challenges, we are **Signamax Connectivity Systems**.

Our mission is to provide end-to-end network connectivity for all your needs. As your single source for your full range of both **Network & Premise Connectivity Systems**, Signamax delivers you wide range of high-performance and cost effective products for Ethernet, Fast Ethernet, Gigabit Ethernet and 10G Ethernet applications.

The Signamax media converters enable mixed media and also mixed speeds on a network for optimum performance. Our portfolio includes managed and unmanaged switches, that are offered in configurations from **5 to 48 ports** with support of **10/100Base to 1000Base** speeds with both copper and fiber terminations. Signamax wireless products allow building of high-performance wireless networks and links, which can complement or replace standard cabling infrastructure and allow high speeds up to **54 Mbps** in **2.4 GHz** as well as in **5 GHz** band.

Signamax brought to you some great new products and solutions for the upcoming year 2008. We are pleased to introduce our **new hardened Ethernet switches** and media converters that are designed to operate in the harsh environments at the edge of the network as well as new structured cabling components designed to comply with **new 10GBase standards**.

# Connected

The Signamax Premise Connectivity System enables you to build a network infrastructure that can accommodate all your network applications. This system is comprised of wiring solutions for your equipment room, distribution cabling and cross-connects to your work-areas with a wide-range of high-performance copper & fiber-optic components, all designed to work together as a system. Whenever you will need products from **category 5E**, **category 6**, or even **category 6A** and **category 7**, we are able to provide suitable solution upon your needs. From the smallest desktop installation projects to the largest enterprise fiber-optic installations, Signamax has the widest range of network solutions, which you will need to support your business.

You will find that our products are designed better, install with greater ease and bring an unparalleled level of performance and reliability to your network. Our systems are designed for the most demanding applications, engineered to meet stringent standards and specifications. Each product is manufactured to the highest quality standards and properly tested to ensure that it exceeds the application standards, such as **TIA/EIA**, **ISO/IEC** and **CENELEC**. The strength and integrity of our Network & Premise Connectivity Systems are backed by the skills and experience of our technical staff.

At Signamax, we are dedicated to help your business run more efficiently. With Signamax connectivity systems provided with long-term performance warranties you can have a peace of mind you want when selecting **Network & Premise Connectivity Systems** to support your network. If you would like to keep your world connected, choose the supplier that can make it happen, **Signamax Connectivity Systems**.




# NETWORK CONNECTIVITY SYSTEMS





## Triple Play



**IP Phones**

**VoIP ATA Gateway**

**VoIP Gateway**

**VoIP Gateway w. SIP Proxy Server**

**VoIP Gateway w. H.323 Gatekeeper**

**Modular High Density VoIP Gateway**

**IP PBX**

**IP DSLAM**

**ADSL 2/2+ Routers**

**IP Camera**

**IP SetTopBox**

# IP Phones

Signamax, delivers stable, low-cost and fully featured IP telephones to customers.

065-9013 Signamax VoIP SIP Phone conforms to SIP standard and support ADSL, Cable Modem, LAN and WAN, ideal for both enterprise and home users.

065-9011 is a full-featured IP-based telephone set for home telephony via Ethernet base communication. It supports SIP RFC3261 protocol.

Two 10/100BaseT embedded switch/hub RJ-45 ports allow connect to office LAN and PC on your table. It is easily interface with ADSL/Cable Modem that is provided by ITSP, ISP or Carrier company to provide VoIP services to residential and SOHO application.



Model 065-9013

## FUNCTIONS

- Message Waiting Indicator
- Do Not Disturb
- Configurable Ring Tones
- Adjustable Ring Volume
- Full Duplex Speakerphone
- Mute
- Shared Lines
- Multiple Lines
- Multiple Proxies
- Music on Hold
- Backup Setting
- GMT Setting
- Date and Time display (Manual / SNTP)
- Optional: Digital answering machine
- Status Indication: Talk & Idle & Hold & Unregistered
- 200 Names and Numbers Phonebook: 2 Numbers per Contact
- Calling Number with Phonebook Name Matching
- Call Log: Outgoing, Answered and Missed Calls (Each 20 Entries)
- Call Timer
- Speed Dial: 10 Numbers Max
- Redial
- Incoming Call with Number and Name Displaying
- Call Transfer: Attended & Blind
- Call Forwarding: Unconditional & No Answer & on Busy

## IP Phones

PART NO.	DESCRIPTION
065-9005	Signamax SIP WiFi Phone 802.11b
065-9011	Signamax VoIP SIP Phone
065-9013	Signamax VoIP SIP Phone Advanced
065-9014	Signamax VoIP SIP Phone with PoE

## SPECIFICATIONS

### 065-9005

#### PERFORMANCE CHARACTERISTICS

**Call Control Protocol:** SIP (RFC2543/RFC3261)  
**Codec:** G.711 / G.729a  
**Battery:** 3.6 V, 1,350 mAh Lithium  
**Battery Life:** 3.2 hr talk time, 24 – 26 hours standby  
**Wireless Access Protocol:** CSMA/CA  
**Frequency Range:** 2.4 – 2.497 GHz  
**Number of Channel:** Up to 14 channels  
**Data Rate:** 802.11b Direct Sequence Rate  
 Scaling at 1, 2, 5.5, and 11 Mbps  
**Range RF output:** 30 mW peak  
**Outdoor:** 1,000 +ft./300 +m  
**Indoor:** Up to 295 ft./75,5 m

#### PHYSICAL CHARACTERISTICS

**Display LCD:** 112 x 64 graphic mode, w/backlight  
**Notification:** Ringer/vibration  
**Port:** Ear-phone jack, mini-USB port

#### NETWORK CHARACTERISTICS

**Protocol:** TCP/IP; DHCP; IEEE 802.11b protocol  
**Security:** Wired Equivalent Privacy (WEP) 64 and 128 bit  
**Accessories:** AC adapter with mini-USB cable  
**Regulatory:** EMI/RFI: FCC Class B, CE



Model 065-9005

### 065-9011

#### APPLICABLE STANDARDS

**WAN interface:** One RJ-45 10/100BaseT  
**LAN interface:** One RJ-45 10/100BaseT  
**Power adapter:** 5V DC  
**LCD Display:** 13 characters, 2 lines  
**Keys:** Function 4, Memory 5, Menu control 4  
**Hand free Speaker phone:** with Echo cancellation  
**Network connect:** Fix IP, DHCP, PPPoE  
**Link Mode (SIP):** Proxi mode and Peer to peer mode  
**Link Mode (H323):** Peer to peer, Gatekeeper mode, DDNS mode  
**Protocol:** SIP (RFC3216)  
**Audio Codec support:** G.711U, G.711A, G.723.1, G.729, G.729A

#### QoS support:

WLAN (802.1p/q)  
**Telephony features:** Mute, forward, Hold, Redial, Transfer  
**Configure management:** LCD Front panel Web Browser, Telnet, Welltech's EMS  
**DTMF (SIP):** In-band, RFC 2833 out-band DTMF generation/detection

#### ENVIRONMENT

**Operating Temp:** 0° – 40°C  
**Storage Temp:** -10° – 60°C  
**Humidity:** 10-90% non-condensing, operating and non-operating/storage  
**Dimensions (WxHxD):** 200 x 79 x 210 mm  
**Weight:** 830 g

#### CERTIFICATIONS

FCC Part 15 Class B, CE Class B



Model 065-9011

### 065-9013

#### PROTOCOLS

SIP: RFC3261; DTMF: inband, RFC2833, SIP Info;  
 RTP: RFC1889; RTCP: RFC3605, RFC3611;  
 DNS: RFC1035; FTP: RFC959;  
 TFTP: RFC1350; HTTP: RFC1945, RFC2616;  
 SNMP: RFC1361, RFC2030; SNMP: RFC1157;  
 DHCP: RFC2131, RFC2132; PPPoE: RFC2516; NAT: RFC1631, RFC2663

#### VOICE QUALITY

VAD – Voice Activity Detection;  
 CNG – Comfort-Noise Generation;  
 AEC – Acoustic Echo Cancellation;  
 QoS – Quality of Service;  
 Jitter Buffer (optional or dependent on IP telephone system);  
 Codec Support – G.711, G.723.1, G.729, G.722.

#### SECURITY

Encrypted (AES/DES) Voice Communication  
 Password Protected for Configuration  
 MD5 for SIP Authentication

#### MAINTENANCE

Web Browser Administration via Built-in Web Server,  
 Auto-Upgradable via HTTP/FTP

#### ENVIRONMENT

**Operating Temperature:** 0° – 50°C  
**Storage Temperature:** -10° – 60°C  
**Relative Humidity:** 10-90% (Non-condensing)

#### BOX CONTENTS

Signamax VoIP Phone, Power adaptor,  
 User's Manual, Quick Installation Guide,  
 Optional accessories: RJ-45 Ethernet Cable, Headset, CD

### 065-9014

#### PROTOCOLS

SIP v1 (RFC 2543), SIP v2 (RFC 3261), SIP RPORT(RFC 3581),  
 IP/TCP/UDP/RTP/RTCP, ICMP/ARP/RARP/SNTP,  
 FTP/DNS/TFTP/DHCP, PPPoE client, HTTP/NAT/DHCP server

#### VOICE QUALITY

VAD(Voice Activity Detection), CNG(Comfort Noise Generator)  
 AEC(Acoustic Echo Cancellation) G.168  
 Packet Loss Compensation, Adaptive Jitter Buffer

#### CODEC

G.711 64kbit/s (ulaw/alaw), G.723.1 6.3k/5.3k bit/s  
 G.726 16k/24k/32k/40k bit/s (ADPCM)  
 G.729A 8k bit/s (CS-ACELP), G.729B (VAD/CNG)

#### APPLICABLE STANDARDS

**Network Interface:** RJ45\*2 10/100BaseT  
**NAT Traversal:** STUN  
**Display:** 16 characters\* 2 lines Backlit, grayscale  
**Keypad:** 40 Keys totally, 9 Soft keys,  
 10 Feature keys (Phone Book, Redial, DND, Hold, Transfer,  
 Conference, Forward, Voice Message, Intercom, Volume Adjustment)  
**Tone:** Ring Tone, Ring Back Tone, Dial Tone, Busy Tone, Programmable Tone

#### ADMINISTRATION

Web-Based Configuration  
 Telnet Configuration  
 Keypad Configuration  
 Auto Provisioning on boot

#### DTMF

In-band DTMF  
 RFC2833( Out-of-band DTMF)  
 SIP INFO

#### ENVIRONMENT

**Operating Temperature:** 0° – 50°C  
**Storage Temperature:** -10° – 60°C  
**Relative Humidity:** 10-90% (Non-condensing)

#### SECURITY

HTTP 1.1 basic/digest authentication for web setup  
 MD5 for SIP authentication (RFC 2069/RFC 2617)

#### QOS

IEEE 802.1Q VLAN, ToS Field

## VoIP ATA Gateway

When you use your high-speed Internet connection to make phone calls, you'll lower your monthly phone bills and add services and features not available with traditional phone service.

The Signamax ATA Gateways enables high-quality feature telephone service through your high speed Internet access (Cable or DSL Internet connection). Just plug Ethernet cable to WAN port of Signamax ATA Gateway and use the one/two standard telephone jacks to connect your existing phones, fax machines or PSTN line. Each phone jack operates independently, with separate phone service and phone numbers -- same like having two phone lines. With an appropriate Internet telephone service provider, you'll get clear telephone reception and reliable fax connections, even while using the Internet at the same time for normal data operations.

There is no necessary to set up any extra device that the embedded NAT function can allow user's PC to gallop on internet directly. Furthermore users can take advantage of many new and exciting IP telephony applications by connecting analog phone to this gateway. It is standard-based communication device that deliver true, next generation voice-over-IP (VoIP) application to residences and small-to medium enterprise in Internet communication environment.



Model 065-9056



Model 065-9055



Model 065-9061



Model 065-9062



Model 065-9066

### VoIP Gateway - ATA

PART NO.	DESCRIPTION
065-9055	Signamax VoIP Gateway, 1xWAN, 1xLAN, 1xFXS, 1xPSTN
065-9056	Signamax VoIP Gateway, 1xWAN, 1xLAN, 2xFXS
065-9061	Wireless Router+VoIP, 1xFXS, 1xPSTN
065-9062	Wireless Router+VoIP, 2xFXS
065-9066	Quad-Band GSM over VoIP Gateway

# VoIP Gateway

The 065-9200S/065-9400S Series VoIP Gateway is fully both H.323 and SIP standard compliant residential gateway that provides a total solution for integrating voice-data network and PSTN. By simple installation, this revolutionary compact voice over IP (VoIP) gateway could be configured as a 2/4 FXS/FXO VoIP Gateway which provides voice connectivity over the IP network and to the Public Switched Telephone Network (PSTN). Gateway is equipped with a four port Ethernet switch and built-in NAT router function that provides Internet access using only one IP address. Besides, it provides high voice quality and optimized packet voice streaming over managed and public (Internet) IP networks.



Model 065-9404s

The Signamax 065-9800 Series VoIP Gateway is fully H.323/SIP standard compliant residential gateway that provides a total solution for integrating voice-data network and PSTN. By simple installation, this revolutionary compact voice over IP (VoIP) gateway could be configured as 8 channels high density FXS/FXO VoIP Gateway which provides voice connectivity over the IP network and to the Public Switched Telephone Network (PSTN). The Gateway is equipped NAT router function that provides Internet access using only one IP address. Besides, it provides high voice quality and optimized packet voice streaming over managed and public (Internet) IP networks.

## SPECIFICATIONS

### RJ-45

LAN 1 – 4x for PC connection

### RJ-11 PHYSICAL INTERFACE

Up to 8x FXO/FXs voice ports

### POWER

Voltage: DC 12V  
Current: 1A

### LED

WAN: WAN link status indication  
LAN: LAN link status indication  
Status: VoIP status indication  
Power: Power status indication  
Phone: Analog phone status indication 5

### PROTOCOL

SIP RFC 3261, Outbound proxy, Support IP or domain name for primary and secondary proxy address and auto switching is enabled.

### CALL FUNCTION

Call Forwarding, Call Transfer, Un-connection LED alarm, Call Hold, Calling Number Delivery

### VOICE FEATURE

Voice codec, G.711 (A-law/ $\mu$ -law), G.723.1, G.729, G.711 FAX pass-through mode, RTP / RTCP, Echo Cancellation G.168, Silence Detection/Suppression, Comfort Noise Generation, DTMF Detection/Generation, Call Tone Generation

### NETWORK

Network connection, PPPoE (RFC 2516) a. Account / password can be saved, b. Auto reconnection after disconnection, DHCP client (for WAN port), Static IP, DHCP Server and NAT, Bridge for LAN interface, QoS, ToS, Diff Serv, Support SNTP

### SYSTEM MANAGEMENT

Support Web, Telnet for remote control, Username / Password for login to make configuration

### FIRMWARE UPDATE / UPGRADING

TFTP / FTP / Web remote update

### ENVIRONMENT

AC Power, 110 – 220V  $\pm$  10V, 60 Hz  $\pm$  3Hz, Environment, Temperature: 0° – 40°C, Humidity: 10-90% RH

### CERTIFICATION

FCC Part 15, CE Class B, LVD



Model 065-9201s

## VoIP Gateway

PART NO.	DESCRIPTION
065-9200s	VoIP Gateway 1xWAN, 4xLAN, 2xFxs
065-9201s	VoIP Gateway 1xWAN, 4xLAN, 1xFxs, 1xFxo
065-9200s	VoIP Gateway, 1xWAN, 4xLAN, 2xFXo
065-9400s	VoIP Gateway 1xWAN, 4xLAN, 4xFxs
065-9401s	VoIP Gateway 1xWAN, 4xLAN, 3xFxs, 1xFxo
065-9402s	VoIP Gateway 1xWAN, 4xLAN, 2xFxs, 2xFxo
065-9404s	VoIP Gateway 1xWAN, 4xLAN, 4xFxo
065-9800s	VoIP Gateway 1xWAN, 4xLAN, 8xFxs
065-9802s	VoIP Gateway 1xWAN, 4xLAN, 6xFxs, 2xFxo
065-9804s	VoIP Gateway 1xWAN, 4xLAN, 4xFxs, 4xFxo
065-9806s	VoIP Gateway 1xWAN, 4xLAN, 2xFxs, 6xFxo
065-9808s	VoIP Gateway 1xWAN, 4xLAN, 8xFxo

## VoIP Gateway

This Signamax 065-9400SVR and 065-9200SVR Series SIP Proxy Server is designed as an embedded-based platform. It performs internet telephony services, like registration status, call detail record and security registration policy. The Signamax 065-9400SVR provides a comprehensive, powerful platform for delivering IP telephony applications based on the Session Initiation Protocol (SIP). It also build in VoIP 2/4 voice channels Gateway which support SIP signal protocols.

This 065-9200SK/065-9400SK Gatekeeper is designed as an embedded-based platform. It performs internet telephony services, like registration, call detail record and security registration policy. Besides Gatekeeper function, 065-9200SK/065-9400SK also build in VoIP Gateway which both support H.323 and SIP signal protocols. A variety of H.323 entities including IP phone, gateway, soft phones as well as different vendor's Gatekeepers have been well tested with.



065-9201svr



065-9201sk

### VoIP Gateway w. SIP Proxy Server

PART NO.	DESCRIPTION
065-9200svr	VoIP Gateway w. SIP Proxy Server 1xWAN, 4xLAN, 2xFxs
065-9201svr	VoIP Gateway w. SIP Proxy Server 1xWAN, 4xLAN, 1xFxs, 1xFxo
065-9202svr	VoIP Gateway w. SIP Proxy Server 1xWAN, 4xLAN, 2xFXo
065-9400svr	VoIP Gateway w. SIP Proxy Server 1xWAN, 4xLAN, 4xFxs
065-9401svr	VoIP Gateway w. SIP Proxy Server 1xWAN, 4xLAN, 3xFxs, 1xFxo
065-9402svr	VoIP Gateway w. SIP Proxy Server 1xWAN, 4xLAN, 2xFxs, 2xFxo
065-9404svr	VoIP Gateway w. SIP Proxy Server 1xWAN, 4xLAN, 4xFxo

### VoIP Gateway w. H.323 Gatekeeper

PART NO.	DESCRIPTION
065-9200sk	VoIP Gateway w. H.323 Gatekeeper 1xWAN, 4xLAN, 2xFxs
065-9201sk	VoIP Gateway w. H.323 Gatekeeper 1xWAN, 4xLAN, 1xFxs, 1xFxo
065-9202sk	VoIP Gateway w. H.323 Gatekeeper 1xWAN, 4xLAN, 2xFXo
065-9400sk	VoIP Gateway w. H.323 Gatekeeper 1xWAN, 4xLAN, 4xFxs
065-9401sk	VoIP Gateway w. H.323 Gatekeeper 1xWAN, 4xLAN, 3xFxs, 1xFxo
065-9402sk	VoIP Gateway w. H.323 Gatekeeper 1xWAN, 4xLAN, 2xFxs, 2xFxo
065-9404sk	VoIP Gateway w. H.323 Gatekeeper 1xWAN, 4xLAN, 4xFxo

## SPECIFICATIONS

### All models svr/sk

#### TELEPHONY SPECIFICATION

Voice Codec: G.711, G.729 AB, G.723 (6.3 Kbps / 5.3 Kbps)  
 FAX support: T.30 / T.38  
 Echo Cancellation: G.165/G168  
 FXO Caller ID detection: DTMF and FSK  
 Adjustable AC Termination Impedance:  
 600 / 900 ohm and complex Impedance  
 Life-Line support (IP/ power failure over relay)  
 Polarity Reversal: Type I and Type II

#### IP SPECIFICATIONS

H.323 v2/v3/v4 and SIP (RFC 3261), RAS, SDP (RFC 2327),  
 Symmetric RTP, STUN (RFC3489), ENUM (RFC 2916).  
 LAN: NAT, Virtual Server, DHCP Server  
 WAN: PPPoE client, DHCP client, Fix IP Address, DDNS client  
 Network Address Translation: Providing build-in NAT router function  
 Smart QoS: Guarantee the voice bandwidth

#### CALL FEATURES

Voice channels status display; Direct Call Mode: peer to peer call;  
 Register Call Mode: register to H.323 Gatekeeper or  
 SIP Proxy Server  
 Adjustable volume: -9 – 9 db  
 Silence Compression, Auto Dial for speed, Dynamic Jitter Buffer

#### CONFIGURATION & MANAGEMENT

Web-based Graphical User Interface  
 Remote management over the IP Network  
 FTP firmware upgrade, Backup and Restore Configuration file

#### GENERAL SPECIFICATION

**AC power:** AC100 – 240V, DC12V / 1.5A, 50 – 60 Hz  
**Temperature:** 0° – 45°C (Operation)  
**Humidity:** up to 90% non-condensing  
**Emmission:** FCC Part 15 Class B, CE Mark  
**Telephone Safety:** FCC Part 68  
**Dimension:** 260 x 130 x 35 mm  
**Weight:** 900 g (Aluminum)

# Modular High Density VoIP Gateway

By Modular hardware design 065-9850/065-9854/065-9858 Series makes any combination of the telephone interface. The Signamax 065-9850/065-9854/065-9858 Series VoIP Gateway is fully SIP and /H.323 standard compliant high density gateway that provides a total solution for integrating voice-data network and PSTN. By modular installation, this revolutionary compact voice over IP (VoIP) gateway could be easily configured as 9850/9860/9870 channels high density FXS/FXO VoIP Gateway which provides voice connectivity over the IP network and to the Public Switched Telephone Network (PSTN).

## SPECIFICATIONS

### TELEPHONY SPECIFICATION

Voice Codec: G.711 (A-law / $\mu$ -law), G.729 AB, G.723 (6.3 Kbps / 5.3 Kbps), FAX support : T.30 / T.38  
 Echo Cancellation: G.165/G.168  
 FXO Caller ID detection: DTMF and FSK (Optional)  
 FXO Hang up detection / anti-seized:  
 Tone Learning Automatically / Manual Tone, Learning (Optional)  
 Answer supervision: Support Battery Reverse Detection and Voice Detection  
 FXO answer delay time: Support delay 0 - 8000 ms to answer.  
 Adjustable AC Termination Impedance: 600 / 900 OHM and complex Impedance, Failsafe Mechanism (FXS relay to FXO):  
 Power failed bypass support / Internet failed bypass / Registered failed bypass / Unconditional bypass 12 KHz and 16 KHz Metering (Customized)

### IP SPECIFICATIONS

H.323 v2/v3/v4 and SIP (RFC 3261), SDP (RFC 2327), Symmetric RTP, STUN (RFC3489), ENUM (RFC 2916), RTP Payload for DTMF Digits (RFC2833), Outbound Proxy Support.  
 LAN: Support Virtual Server, DHCP Server  
 WAN: Support PPPoE client, DHCP client, Fix IP Address, DDNS client  
 Network Address Translation: Providing build-in NAT router function  
 Smart QoS: Guarantee the voice bandwidth  
 IP TOS (IP Precedence) / DiffServ

### CALL FEATURES

Voice channels status display  
 Direct Dialing Mode: peer to peer call (support IP Address Call or Domain Name Call)  
 Register Call Mode: register to SIP Proxy Server or H.323 Gatekeeper  
 Adjustable volume: -9 – 9 db  
 Silence Compression / VAD  
 Auto Dial for speed, Dynamic Jitter Buffer, Hot-Line Support

### CONFIGURATION & MANAGEMENT

Web-based Graphical User Interface  
 RS232 for configuration, Remote management over the IP Network  
 FTP firmware upgrade, Backup and Restore Configuration file  
 Front LCD Panel for System Status and Management  
 Syslog client support

### GENERAL SPECIFICATION

Standard 50 pin RJ-21 Telco connectors  
 AC power: AC100 – 240V, DC12V/1.5A, 50/60 Hz  
 Temperature: 0° – 40°C (Operation)  
 Humidity: up to 90% non-condensing  
 Emission: FCC Part 15 Class B, CE Mark  
 Dimension: 440 x 250 x 45 mm  
 Weight: 3,500 g

## VOIP KEY FEATURES

- Modular design to accommodate various types of telephony interfaces
- Both support SIP and H.323 protocols: SIP Registration and Digest Authentication; H.323 Gatekeeper Registration
- Single Number / Account for multiple ports
- Caller ID Delivery and Detection: FXS support DTMF&FSK Caller ID generation; FXO supports DTMF&FSK Caller ID detection. (Optional)
- Smart VoIP call Dialing Book: VoIP call Book could provide any application VoIP call to any type destination (Domain name / IP address, PSTN or PBX) or hunting number setting
- AC termination Impedance: 600/900 OHM and complex impedance
- Answer Supervision for Polarity Reversal Detection and Voice detection
- NAT traversal: This feature allow gateway to operate behind any NAT/Firewall device. Need not to change any configuration of NAT/Firewall like setting virtual server
- Smart-QoS Guaranteed: This bandwidth management feature provide good voice quality when user place a VoIP call and access internet at the same time
- The gateway will automatically start to reserve bandwidth for voice traffic when VoIP call proceeds
- Call Hunting Facility: This function helps gateway to use the lines effectively. This facility automatically transfers your incoming call to a free line. Subscribers need not indicate numerous numbers of each port of gateway
- Voice channels status display: This function display each port status like as onhook, offhook, calling number callee's number, talk duration, codec
- Pulse Dial support: Support pulse dialing generation and detection. (Optional)
- Flash Detection and Generation Program: FXO support Flash Generation and FXS support Flash Detection
- FXO answer Mode: FXO provides Ringing Answer, Connection Answer and Non Answer for configuration

## Modular High Density VoIP Gateway

PART NO.	DESCRIPTION
065-9850	Signamax Modular VoIP Gateway Chassis 1xWAN, 1xLAN, 8xFXs, 1xRS-232, Standard 50pin telco Connector
065-9854	Signamax Modular VoIP Gateway Chassis 1xWAN, 1xLAN, 4xFXs 4xFXo, 1xRS-232, Standard 50pin telco Connector
065-9858	Signamax Modular VoIP Gateway Chassis 1xWAN, 1xLAN, 8xFXo, 1xRS-232, Standard 50pin telco Connector
<b>Modules</b>	
065-9860	Module 8x FXs Ports for Modular Chassis 065-985x
065-9861	Module 4x FXs / 4x FXo Ports for Modular Chassis 065-985x
065-9862	Module 8x FXo Ports for Modular Chassis 065-985x

# IP PBX

Full featured Internet Telephone IP PBX System for SOHO and Enterprises!

Signamax 065-9101 combines complete IP-PBX features with standards based SIP for telephony solution that can stand alone or integrate with existing phone systems. 065-9101 is an embedded system with built-in SIP Proxy Server and NAT router for SOHO user not only provide network function but also provide an IP PBX feature in office.

Signamax 065-912x / 065-914x Series Full Featured Internet Telephone IP PBX System for SMB! There is no requirement to replace current analog PBX infrastructure. As a result, VoIP will be viewed as attainable by more businesses, providing greater opportunities for resellers to offer VoIP as part of their portfolio. The 065-912x / 065-914x series emphasizes open architecture, scalability and higher Return on Investment. The 065-912x / 065-914x series offers a multitude of features including extensive PBX functionality, integrated voicemail, cost saving call routing functionality, IP routing, SIP call signaling and much more.

Signamax 065-9155 is designed and optimized for SMB enterprise daily communications with easy configuration and cost advantages. Designed as a highly reliable, stable, and open telephony solution. It provides the advanced features of telephony which are required for around 200 users on their telecommunication needs.

The 065-9155 is an embedded system with built-in SIP Proxy/Registrar Server and NAT traversal that make it perfect for SMB enterprise usage. The 065-9155 provides not only basic call functions like Call Forward, Call Transfer on traditional PBX System, but also many advanced functions including Meet-Me Conference, Call Parking, and Voice Mail System with E-mail Notification and Attachment etc. These advanced functions are impossible on traditional PBX. The 065-9155 provides IP-based communications, 3-layer IVR, Meet-Me Conference, Call Parking, Voice Mail System with E-mail Notification and Attachment, and Web GUI Management. The 065-9155 also provides 2 PCI slots that can insert FXO, FXS or ISDN BRI module cards, so enterprise can seamlessly integrate with existing traditional PBX. With the 065-9155, standard SIP phones can be easily integrated in your office.

065-9155 is established by a very stable embedded system platform. All the System Configurations, Voice Mail and Call Detail Record are stored in the flash disk. Administrators could backup the system configuration file to their own computer through web GUI. If the system is damaged, administrator only have to restore the configuration file to a new 065-9155. No more re-configuration is needed and minimizes the maintenance effort.

## VoIP IP PBX System

PART NO.	DESCRIPTION
065-9101	Signamax VoIP IP PBX, 1xWAN, 1xLAN
065-9120	Signamax VoIP IP PBX, 1xWAN, 4xLAN, 2xFXS
065-9122	Signamax VoIP IP PBX, 1xWAN, 4xLAN, 2 FXO
065-9140	Signamax VoIP IP PBX, 1xWAN, 4xLAN, 4xFXS
065-9144	Signamax VoIP IP PBX, 1xWAN, 4xLAN, 4 FXO
065-9155	Signamax Modular VoIP IP PBX, 1xWAN, 1xLAN, Rack Mount
<b>Modules</b>	
065-9160	Module 4xFXS Ports for 065-915x Chassis
065-9161	Module 4 FXO Ports for 065-915x Chassis
065-9162	Module 4x ISDN BRI Ports for 065-915x Chassis

# IP DSLAM

065-9074/8 Series IP DSLAM has 24/48 ports subscriber line interface with POTS splitter built-in achieved 1U height space saving design. 065-9074/8 Series came with unique bandwidth management, flow prioritization and data flow security control key feature. 065-9074/8 Series provided QoS (quality of service) capability to meet triple play (voice, data, video) requirement, support ADSL/ADSL2/ADSL2+/G.SHDSL interface, stackable up to 8 065-9074/8 can be cascaded. No matters in features, performance, and cost wise, 065-9074/78 Series is the best choice for NSP (network service provider).

## IP DSLAM

PART NO.	DESCRIPTION
065-9074	Signamax IP DSLAM ADSL/ADSL2+, 24 ports, 2x1000Base-TX Uplink
065-9078	Signamax IP DSLAM, ADSL/ADSL2+, 48 ports, 2x1000BaseTX Uplink
065-9081	Signamax IP DSLAM Uplink Module 1x100BaseTX + 2x1000Base TX
065-9082	Signamax IP DSLAM Uplink Module 1x100BaseTX + 1x1000BaseTX + 1x1000LX
065-9083	Signamax IP DSLAM Uplink Module 1x100BaseTX + 1x1000BaseTX + 1x1000LX
065-9094	Signamax IP DSLAM G.SHDSL.bis CPE unit, 4port switch, 4 wires
065-9098	Signamax IP DSLAM G.SHDSL.bis CPE unit, 4port switch, 8wires

## SPECIFICATIONS

### SYSTEM FEATURES

48/24 ports interface ADSL/2+ subscriber interface with built-in POTS Splitter  
 48/24 ports G.SHDSL/G.SHDSL.bis subscriber interface (optional)  
 One 100BaseT MGNT+ Two 1000BaseT or one Giga LX Uplink/Subtend  
 Interface optional, Stackable up to 8 units to be cascaded  
 Centronic 50 pin connector for line in and out  
 8 VCs per xDSL port, 128 MAC address per xDSL port  
 48\*128 MAC address, Packet size 64 byte to 1,522 byte  
 PPPoE Intermediate Agent, DHCP Relay Agent  
 Inter-Working: IPOA to IPOE Trunneling, PPPoA to PPPoE  
 inter-working, Multiple mechanisms of prioritizing traffic

### MULTICAST

- Up to 256 multicast addresses
- IGMP v1, v2, v3
- Multicast VLAN mapping: Independent VLAN multicast (IVM), Shared VLAN Multicast (SVM)
- Handle PPPoE Encapsulated IGMP packets

### BRIDGING

- Ethernet Bridging - Broadcast, Flooding/Dropping
- VLAN bridging: 512 VLAN support, Static VLAN, VLAN Stacking, VLAN Trunking

### ADSL/ADSL2/ADSL2+ INTERFACE

ADSL/ADSL2/ADSL2+: Downstream DMT data rate 32 Kb/s up to 25 Mbps;  
 Upstream DMT data rate 32 Kb/s up to 1 Mbps  
 Comply with ITU G.992.1 (G.DMT); G.DMT.bis; ITU G.992.2 (G.Lite);  
 ANSI T1.413 issue 2; ITU G.994.1 (G.handshake) for ADSL,  
 G.992.3 for ADSL2, and G.992.5 for ADSL2+  
 Extended power management capabilities to optimize power consumption  
 for each application, Distance up to 18 kft

### G.SHDSL/G.SHDSL.BIS INTERFACE

G.SHDSL: Symmetric transmission rate up to 2.3 Mbps (2-wire)  
 G.SHDSL.bis: Symmetric transmission rate up to 5.7 Mbps (2-wire)  
 Comply with G.991.2

### MANAGEMENT

Microsoft windows based GUI MSE  
 Local RS-232 CLI and Ethernet SNMP/TELNET management  
 Remote in-band SNMP/TELNET management  
 Firmware upgradeable via FTP or TFTP, Support SNMP v1, v2c

### PROTOCOLS SUPPORT

STP; IGMP snooping, GMRP, GVRP, LACP,  
 SNMP/UDP/IP/MAC/Ethernet

### OPERATING REQUIREMENTS

Operating Temperature: 0° – 50 °C  
 Storage Temperature: -30° – 70 °C  
 Operating Humidity: 5-90% RH non-condensing  
 Dimension (D x W x H): 400 x 440 x 44 mm  
 Weight: 6.8 kg  
 AC power model: 90 – 240V AC, 50 – 60 Hz  
 DC power model: -42 to -56 VDC  
 Power Consumption: 100 Watts

### UPLINK UPGRADEABLE MODULE INTERFACE

1\*1000BaseT-MGNT+2\*1000BaseT  
 1\*1000BaseT-MGNT+1\*1000BaseT+  
 1\*1000Fx (SX/LX/LH/ZX)

### QoS

Input Rate Limiting (IRL) on a per-AAL5 interface  
 Output Rate Limiting (ORL) on a per ATM-port  
 and Ethernet basis  
 Rate Limiting

### SECURITY

Throtting Control, Sticky Bridge Ports  
 MAC Adress Access Control List,  
 IP Adress Access Control List

## ADSL 2/2+ Routers

Signamax ADSL routers are designed to provide a simple and cost-effective ADSL Internet connection for a private Ethernet network. The ADSL (Asymmetric Digital Subscriber Line) connection is made using ordinary telephone line. Signamax provide latest ADSL 2+ standards for high speed Internet access (up to 24Mbps for Downstream). With a built-in 4-Port switch (065-9088/065-9089), up to four computers or devices can simultaneously be connected and share Internet access.

Signamax offers the advanced security enhancements (IP/MAC Filter, Application Filter and URL Filter) to protect your network from unwanted intruders breaking into your system by malicious agents from outside of your network. Signamax brings you advanced features as VLAN support, QoS, Port Mapping and many others. Routers also provide full IGMP as well and that is why they are the best choice for Triple Play applications specially IPTV distributed via ADSL 2+ line.

You can configure Signamax ADSL routers not only via common html (Web Management) access but also you can use external easy setup utility software on CD, too. Signamax Router compliance to supported ADSL standards: ANSI T1.413 Issue 2, ITU-T G.992.1 (G.dmt), ITU-T G.992.2 (G.lite), ITU-T G.992.3 (G.dmt.bis/ADSL2), and ITU-T G.992.5 (ADSL2+) specification. Both Annex A (ADSL over POTS) and Annex B (ADSL over ISDN) are supported.



Model 065-9089

### ADSL 2/2+ Routers

PART NO.	DESCRIPTION
065-9087	Signamax ADSL2/2+ Modem Router 1xLAN, AnnexB
065-9087A	Signamax ADSL2/2+ Modem Router 1xLAN, AnnexA
065-9088	Signamax ADSL2/2+ Modem Router 4xLAN, AnnexB
065-9088A	Signamax ADSL2/2+ Modem Router 4xLAN, AnnexA
065-9089	Signamax ADSL2/2+ WiFi Modem Router 4xLAN, 802.11b/g, AnnexB
065-9089A	Signamax ADSL2/2+ WiFi Modem Router 4xLAN, 802.11b/g, AnnexA
065-9085	ADSL Splitter, 3xRJ-11, AnnexB
065-9086	ADSL Splitter, 3xRJ-11, AnnexA

## SPECIFICATIONS

### ADSL COMPLIANCE

- Full-rate ANSI T1.413 Issue 2
- ITU G.992.1 (G.dmt) Annex A and B
- Splitterless ITU G.992.2 (G.lite) specification
- ITU G.992.5 (ADSL2plus)
- ITU G.994.1 (G.hs), ITU G.992.3 (G.dmt.bis / ADSL2)
- Supports splitterless ADSL implementation
- Supports Dying Gasp

### ATM SUBSYSTEM

- PPP over ATM (RFC 2364), Bridged IP over ATM (RFC 1483)
- PPP over Ethernet (RFC 2516), ATM Forum UNI 3.1/4.0 PVC
- Multiprotocol Encapsulation over AAL5 (RFC 2684)
- Supports up to 8 Virtual Channel Connections (VCCs)
- Supports UBR, CBR, and VBR service classes
- Support OAM F4/F5 look-back, AIS and RDI OAM cells

### FEATURES

- IP Alias, User Datagram Protocol (UDP)
- Transmission Control Protocol (TCP)
- Internet Control Message Protocol (ICMP)
- Internet Group Management Protocol (IGMP)
- PPP over PAP (RFC1334), PPP over CHAP (RFC1994)
- MIB II support (RFC1213), NAT (Network Address Translation)
- Transparent bridging as specified in IEEE 802.1D
- Dynamic Host Configuration Protocol (DHCP)
- Dynamic DNS support
- Routing Information Protocol (RIP) v1 and v2
- Supports Virtual LAN (VLAN)
- Supports Quality of Service (QoS)

### MANAGEMENT

- TFTP client and server
- FTP server and client, Universal Plug and Play (UPnP) support
- Web-based Graphical User Interface (GUI) enabling end-user device configuration via HTTP
- DHCP client and server
- Update of boot image or configuration data via TFTP/ FTP
- Syslog, Built-in Diagnostic Tools
- SNMP MIB support

### ETHERNET INTERFACE

- IEEE 802.3, 10/100 Mbps
- Ethernet interface supporting up to 64 LAN hosts

### VISUAL INDICATORS

- PWR – on when power on
- DSL LINK – on when ADSL is connected, flashing when attempting connection
- DSL ACT – on when transmitting/receiving data on the WAN
- LAN LINK – on when Physical Ethernet link is up

## IP Camera

Signamax 065-9001 Internet Camera and 065-9003 Internet Wireless Camera, a camera device that can be connected directly to an Ethernet or Fast Ethernet network also supported by the wireless transmission based on the IEEE 802.11g standard 065-9003. Compared to the conventional PC Camera, the Internet Camera features a built-in CPU and web-based solutions that can provide a cost-effective solution to transmit real-time high-quality video images and sounds for monitoring. This Internet Camera can be managed remotely, accessed and controlled from any PC/Notebook over the Intranet or Internet via a web browser. The simple installation procedures and webbased interface allow you to integrate it into your network easily. With comprehensive applications supported, this Signamax Internet Camera is your best solution for remote monitor, high quality, and high performance video images.



Model 065-9003

### FEATURES

- Simple to use just plug and view the image from the Internet Camera with a valid IP address
- Embedded Web UI configuration with Administrator ID/Password protection
- Secured User Management by ID and Password
- Allows remote access from web browser for live image viewing
- Supports TCP/IP networking, UPnP, SMTP e-mail, HTTP and other Internet related protocols
- Powerful application software for image capture and video recording:
  - Multiple Video Window Simultaneously,
  - Motion Detection with alert and E-mail sending,
  - Recording triggered by Motion Detection, Schedule, and Manual,
  - Single Frame Image Snap shot.
- Digital Zoom and Mirror function supported
- Support 10/BaseT/100BaseTX Ethernet with Auto-MDI/MDIX

### IP Camera

PART NO.	DESCRIPTION
065-9001	LAN IP Camera
065-9003	Wireless IP Camera

## SPECIFICATIONS

### IMAGE SENSOR

Sensor resolution: 640 x 480 pixel  
Sensor: Color CMOS Sensor  
Lens: f: 6.0 mm, F: 1.8

### IMAGE (VIDEO SETTING)

JPEG still image compression  
Image frame rate: QCIF@30fps, 25fps@CIF, 10fps@VGA  
Compression Rate selection: 5 levels, very low, low, middle, high, very high  
Frame rate setting: 1, 5, 7, 15, 20, auto (depends on the video format)  
Video resolution: 160 x 120, 320 x 240, 640 x 480  
Automatic Gain control Yes  
Automatic Exposure Yes  
Automatic White Balance Yes  
Digital Zoom Yes  
Upside down and Mirror Yes

### COMMUNICATION

LAN port: RJ-45, 10/100M auto-sensed, AUTO-MDIX  
Communication protocol: HTTP, FTP, TCP/IP, UDP, ARP, ICMP, BOOTP, DHCP, PPPoE, SMTP, DDNS, UPnP

### SYSTEM

CPU: RDC R2880  
RAM: 8 MByte  
Flash ROM: 2 MByte  
OS: RTOS

### SOFTWARE

Browser: Internet Explorer 5.0 or above, Netscape 6.0 or above  
Application Software: IPview application software  
OS supported: Microsoft Windows 98 SE, ME, NT 4.0, 2000, XP

### FEATURES

**System:** Server Name, Location, Admin ID and Password  
LED Control: Normal/OFF/Dummy

#### TCP/IP

Static IP Address: IP Address, Subnet Mask, Default Gateway  
Dynamic IP Address: DHCP, BOOTP, PPPoE (Service Name, User ID, User Password)  
Primary DNS Address, Secondary DNS Address

#### Users

Add User: 64 users account maximum, User Name, User Password, Delete User

#### Date/Time Setting

Date: Year/Month/Day (Default: 2001:10:01)  
Time: Hour/Minute/Second (Default: 08:30:00)  
NTP Protocol, NTP Server Address, Time Zone

#### Image

Compressing Rate: 5 levels, very low/low/medium/high/very high  
Frame Rate: 1/5/7/15/20/Auto  
Video Resolution: 160 x 120, 320 x 240/640 x 480  
Brightness Control Yes  
Contrast Control Yes  
Saturation Control Yes  
Light Frequency 50/60 Hz  
Digital Zoom Yes  
Upside down and Mirror Yes  
Anti-Flicker Yes

#### Upload configuration

FTP Server, Time Schedule, Manual Operation

#### Dynamic DNS

Service, User Name, Password, Domain Name

#### Others

Reset, Factory Reset to Default setting

#### Web Browser Supported

Internet Explorer 5.0 or above  
Netscape 6.0 or above

### POWER

Power: DC 5V, switching type power supply  
Power consumption: 3.5 Watt (700 mA x 5V)

### LED

Power LED: Blue color  
Activity LED: Orange color

### OPERATING ENVIRONMENT

Operating temperature: 5° – 40°C  
Storage temperature: 25° – 50°C  
Humidity: 5-95% non-condensing

### EMI

FCC / CE / VCCI class B



Model 065-9001



Model 065-9001 back



Model 065-9003 back

## IP Set Top Box

065-9021 is an IP STB fully compatible with ISMA standard. It is widely used in communities, hotels and broadband environment for receiving MPEG-4 liveprogram and VOD. Meanwhile, with the support of head-end system, 065-9021 can be used for video shopping, network games, support EPG and so on.



Model Model 065-9021



Model 065-9021

### FEATURES

- **Video Format:** MPEG-4 SP/ASP Video Decoding
- **Audio Formats:** MP3 and AAC
- **Picture Formats:** JPEG, BMP, PNG and GIF animated picture formats
- **Network Interfaces:** 1x10/100MBase-T RJ45
- **Browser:** Embedded browser, supports HTML network surfing
- **Supports IGMP Multicast,** which is capable of Receiving channelized of multicast programs
- **Transport Standard:** Open International Streaming Standard ISMA 1.0/1.1 and TS stream
- **Games:** JavaScript based network games
- **VOD:** Video/Audio programs on demand

### IP Set Top Box

PART NO.	DESCRIPTION
065-9021	Signamax IP Set Top Box MPEG-4
065-9022	Signamax IP Set Top Box MPEG2
065-9023	Signamax IP Set Top Box MPEG2&4

### FUNCTIONS

- **Media On demand:** Plays the video program in the playlist of EPG, supports play/stop/ pause/fast forwarding and backward/mute/volume up/volume down/Left and Right Audio channel/Stereo. It supports progress indication as well. It can also plays MP3 program in the play list of EPG supports play, stop, pause, mute, volume up, volume down and progress indication.
- **Multicast program:** Gets the channel information from the EPG and supports channel lineup. It does not support fast forwarding, fast backward, and pause. It supports mute, volume up, volume down, left and right Audio channels and stereo.
- **WEB Browsing:** Browses the Internet web pages of HTML 4.0 and Javascript 1.5 with the embedded browser.
- **Electronic Program Guide:** Enters the main EPG screen of the operator. Gets the information of the program and the playlist. Supports EPG dynamic upgrade, VOD, music on demand, picture viewing and network games.
- **Parameter configuration and display:** Supports PPPoE dialing through STB (modem bridge connection mode). Supports statically and dynamically obtain IP address. Configures the network parameter such as user name, password, DNS server, subnet mask, gateway and static IP address. Configures HTTP upgrade server, default PG server and default URL address. Modifies Password. Configures TV mode. Displays product information. Configures NTP server address. Configures Time Zone.

## SPECIFICATIONS

### Model 065-9021

#### MEDIA FORMATS

Video Formats: MPEG-4 ISO/IEC 14496-2 Advance simple profile without GMC and QPEL  
 Audio Formats: MP3 and AAC  
 Picture Formats: JPEF and GIF static pictures

#### STREAMING PROTOCOLS

Internet Streaming Media Alliance (ISMA) Implementation Specification version 1.0, including the following: Transport Protocols:  
 RTP: A Transport Protocol for Real-Time Applications, IETF RFC 1889;  
 RTP Profile for Audio and Video Conferences with Minimal Control, IETF RFC 1890; Transmission Control Protocol, IETF RFC793;  
 UDP: User Datagram Protocol IETF RFC768.  
 RTP Payload formats: RTP Payload Format for Transport of MPEG-4 Elementary Streams, IETF RFC 3640  
 Content distribution: MPEG-4 MP4 Format – ISO/IEC 14496-1:2000(E)  
 Media controls: Real Time Streaming Protocol (RTSP), IETF RFC 2326  
 Media Announce: SDP: Session Description Protocol, IETF RFC2327

### Model 065-9022

#### VIDEO DECODING

Decoding Standard: ISO/IEC 13818-2 MPEG-2 MP@ML  
 Video Format: PAL/NTSC/SECAM  
 Aspect Ratio: 4:3, 16:9  
 Output Definition: 720 x 480 or 720 x 576 SD

#### AUDIO DECODING

Decoding Standards: ISO/IEC 13818-3  
 Decoding Formats: MPEG-1, 2, 3  
 Sample Rates: 32, 44.1, 22.05, 24 and 48 KHz  
 Output Modes: Single and dual audio channels

#### PROTOCOLS SUPPORTED

IP protocol: IP v4  
 Network Protocols: HTTP 1.0/1.1, DHCP, IGMP v1/v2,  
 TCP/IP, DNS, PPPoE and NTP  
 Streaming Media Protocols: RTP/RTCP/RTSP/SDP

### Model 065-9023

#### MEDIA FORMATS

Video Formats: MPEG-4 ISO/IEC 14496-2 Advance simple profile without GMC and QPEL  
 Audio Formats: MP3 and AAC  
 Picture Formats: JPEF and GIF static pictures

#### VIDEO DECODING

Decoding Standards: ISO/IEC 13818-2 MPEG-2 MP@ML,  
 ISO/IEC 14496-10, MPEG-4 MP@L3  
 Video Format: PAL/NTSC, Aspect Ratio: 4:3, 16: 9  
 Output Definition: 720 x 480 or 720 x 576 SD

#### AUDIO DECODING

Decoding Standards: ISO/IEC 13818-3, ATSC A/52 and ISO/IEC 14496-3  
 Decoding Formats: MPEG Layer1/2/3, AC3, MPEG-2/4 AAC (ADTS)  
 Sample Rate: 32, 44.1, 22.05, 24 and 48 KHz

#### PROTOCOLS SUPPORTED

IP protocol: IP v4  
 Network Protocols: HTTP 1.0/1.1, DHCP, IGMP v1/v2, TCP/IP, DNS,  
 SNMP v2, PPPoE and NTP  
 Streaming Media Protocols: RTP/RTCP/RTSP/SDP

#### NETWORK PROTOCOLS

HTTP 1.0/1.1, DHCP, NTP1.1 and IGMPV1/V2.,  
 Supports IPv4

#### ACCESSORIES

IPSTB Box: 1  
 Audio/Video line: 1 suit  
 Net line: 1  
 Power Supply: 1  
 User Instruction: 1  
 Remote Control: 1  
 Batteries: 1 pair

#### TECHNICAL SPECIFICATIONS

Audio: MP3, AAC  
 Video: MPEG-4 ASP, SP, 4:3 and 16:9-aspect ratio  
 NTSC/PAL TV signal, 720 x 480 or 720 x 576 SD output  
 Sample Rate: 32, 44.1, 48, 88.2 and 96 KHz  
 Picture formats: GIF and JPEG  
 OSD: 256 colors, 16 level alpha blending

#### SYSTEM MAINTENANCE

Upgrade: Manual/Automatic application software upgrade  
 System Configuration: Manual/Automatic configuration

#### PICTURE FORMAT

Static pictures: JPEG, BMP, PNG  
 Animated picture: GIF

#### INTERFACES

Input Interface: RJ45  
 Output Interfaces: RCA, S-Video  
 Network Interface: 1x10/100M Base-T  
 IR Interface: NEC

#### OSD

Color: 32-bit true color  
 Alpha blending: 256 levels

#### THIRD PARTY SOFTWARE SUPPORTED

Browser: Ant or iPanel  
 Games: JavaScript games

#### PICTURE FORMAT

Static pictures: JPEG, BMP, PNG  
 Animated picture: GIF

#### INTERFACES

Input Interface: RJ45  
 Output Interfaces: RCA S-Video, SCART, and S/P DIF  
 Network Interface: 1x10/100M Base-T  
 IR Interface: NEC/RC5

#### OSD

Color: 32-bit true color  
 Alpha blending: 256 levels

#### THIRD PARTY SOFTWARE SUPPORTED

Browser: Ant or iPanel  
 Middleware: International leading middleware  
 Games: JavaScript games

#### SYSTEM MAINTENANCE

Upgrade: Manual/Automatic application software upgrade  
 System Configuration: Manual/Automatic configuration

# NETWORK CONNECTIVITY SYSTEMS





## Media Converters



B

### **Switching Fiber Converters**

**10/100 to 100BaseFX Power over Ethernet Fiber Media Converters**

### **Switching Managed Media Converters**

**10/100BaseT/TX Switching PCI Fiber Optic Media Converters**

### **VDSL Ethernet Extender**

**10/100BaseT/TX Switching Mini Fiber Optic Media Converters**

**Stand Alone Managed Switching Media Converters**

### **Hardened Media Converters with LFS**

**Single Channel Hardened Media Converters**

### **Gigabit Media Converters**

**10/100/1000 Switching Fiber Optic Media Converters**

### **SFP Fiber Converters**

**Serial Data to Fiber/TP Media Converters**

**Single Fiber WDM Converters**

**Singlemode to Multi Mode Converters**

**Basic Media Converter**

**12-Port Rack Mount Media Converters**

**16-Bay Media Converter Rack Mount Chassis**

**18-Bay Rack Mount Managed Media Converter Chassis**

**8-Bay Managed Media Converter Chassis**

### **WebSmart Media Converters**

**16-Slot Chassis for Modular EPON Media Converters**

## Switching Fiber Converters

Signamax Connectivity Systems' Switching Media Converters provide an intelligent solution for long distance connections between legacy 10BaseT networks and the newer 100Base Fast Ethernet or 1000Base Gigabit Ethernet networks. These converters are designed to handle a wide variety of fiber optic network applications and eliminate the 412 meter distance limitation when connecting hub-based sub-networks at 100BaseFX. They also extend the maximum Single Mode fiber distance, spanning over 75 km with the 065-1120XLD model.

Built-in 10/100 or 10/100/1000 switch enables the fiber cable connection to operate at 100 Mbps connected to either a 10BaseT or a 100BaseTX network, while remaining completely 100BaseFX or 1000BaseSX standard-compliant. Fiber connection can also operate in full duplex mode whether the RJ45 port is connected to a full duplex switch or a half duplex hub.

Each Media Converter provides a 10/100BaseT/TX auto-negotiating RJ45 twisted-pair connector port featuring store-and-forward switching architecture. Built-in switch does the network segmentation to provide the maximum fiber distance. Now with Auto-MDIX capability on the twisted-pair port for more convenient connection. Each Media Converter is also equipped with LFS (Link Fault Signaling) feature.



### Switching Fiber Converters

PART NO.	DESCRIPTION	FIBER TYPE
065-1100	10/100BaseT/TX to 100BaseFX Converter	ST Multi Mode
065-1110	10/100BaseT/TX to 100BaseFX Converter	SC Multi Mode
065-1170	10/100BaseT/TX to 100BaseFX Converter	VF45 Multi Mode
065-1172	10/100BaseT/TX to 100BaseFX Converter	MTRJ Multi Mode
065-1174	10/100BaseT/TX to 100BaseFX Converter	LC Multi Mode
065-1120A	10/100BaseT/TX to 100BaseFX Converter	SC Single Mode (15 km span)
065-1120ED	10/100BaseT/TX to 100BaseFX Converter	SC Single Mode (40 km span)
065-1120XLD	10/100BaseT/TX to 100BaseFX Converter	SC Single Mode (75 km span)
065-11DINMT	DIN rail mounting bracket for 065-11xx series media converters	

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT  
 IEEE 802.3u 100BaseTX  
 IEEE 802.3u 100BaseFX  
 IEEE 802.3ab 1000BaseT  
 IEEE 802.3z 1000BaseSX

### FIXED PORTS

#### Models 065-1100/1110/1170/1172/1174/1120/1120ED/1120XLD:

1 Auto-MDIX twisted-pair port meeting IEEE 802.3 10BaseT & IEEE 802.3u 100BaseTX standard specifications; Category 5 or better cable, 100 meters maximum distance for 100BaseTX, Category 3 or better cable, 100 meters maximum distance for 10BaseT

#### plus

1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 62.5/125 or 50/125 micron Multi Mode fiber optic cable, 2,000 meters maximum distance

#### or

1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 15 kilometers maximum distance (model 065-1120)

#### or

40 kilometers maximum distance (model 065-1120ED)

#### or

75 kilometers maximum distance (model 065-1120XLD)

### PERFORMANCE

**Latency:** < 4.2  $\mu$ s (LIFO)

**Throughput @ 100Base:** 148,809 pps

**Throughput @ 1000Base:** 1,488,100 pps (64-byte packets)

### LEDs

Per unit: Power status, RJ45 port speed

Per Port: LNK/ACT, FDX/COL

Six LEDs total

### PHYSICAL CHARACTERISTICS

#### Case dimensions (L x W x H):

110 x 81 x 23 mm (4.33 x 3.19 x 0.91")

Fiber connector interface varies with model.

**Weight:** 150 grams

### SAFETY

UL Listed



Model 065-1100



Model 065-1110



Model 065-1170



Model 065-1172



Model 065-1174

## 10/100 to 100BaseFX Power over Ethernet Fiber Media Converters

The Signamax 065-1050 series Media Converters are 10/100BaseT/TX to 100BaseFX Power over Ethernet (PoE) devices that serve as Power Sourcing Equipment (PSE), which allows the converter to provide power to IEEE 802.3af PoE standard-compliant Powered Devices (PDs) using the twisted pair connection. This AC-powered PoE Media Converter combines data received over a fiber optic link with -48 Volt DC power, which the PD can use instead of a separate power connector. The 065-1050 series converters are also equipped with PD signature-sensing, power monitoring, over-voltage protection, low voltage detection, and input fault protection features. The 065-1050 series' Link Fault Signaling (LFS) capability allows the media converter to monitor both the fiber and copper RX ports for signal loss. In case of a loss of RX signal on one media port, the converter will automatically disable the TX signal to the other media port, thus passing through the link fault. Far End Fault (FEF) capability enables the converter to stop sending link pulse to the link partner once a loss of the fiber RX signal is encountered; the link partner will then synchronously stop sending data, thereby preventing the loss of data that would occur when trying to transmit over a failed link.

The Signamax 065-1052 series Media Converters are PoE 10/100BaseT/TX to 100BaseFX Powered Devices supporting two types of media, 10/100BaseT/TX and 100BaseFX, for network connection. They are also equipped with Link Fault Signaling (LFS), to maintain link integrity and enable automatic failover when used with Spanning Tree-equipped switches.



Model 065-1050

### 10/100 to 100BaseFX Power over Ethernet Fiber Media Converters

PART NO.	DESCRIPTION
065-1050ST	10/100BaseT/TX to 100BaseFX PSE PoE Media Converter, Multi Mode/ST, 2 km
065-1050SC	10/100BaseT/TX to 100BaseFX PSE PoE Media Converter, Multi Mode/SC, 2 km
065-1050SM	10/100BaseT/TX to 100BaseFX PSE PoE Media Converter, Single Mode/SC, 15 km
065-1050SMED	10/100BaseT/TX to 100BaseFX PSE PoE Media Converter, Single Mode/SC, 40 km
065-1050SMXLD	10/100BaseT/TX to 100BaseFX PSE PoE Media Converter, Single Mode/SC, 75 km
065-1052ST	10/100BaseT/TX to 100BaseFX PD PoE Media Converter, Multi Mode/ST, 2 km
065-1052SC	10/100BaseT/TX to 100BaseFX PD PoE Media Converter, Multi Mode/SC, 2 km
065-1052SM	10/100BaseT/TX to 100BaseFX PD PoE Media Converter, Single Mode/SC, 15 km
065-1052SMED	10/100BaseT/TX to 100BaseFX PD PoE Media Converter, Single Mode/SC, 40 km
065-1052SMXLD	10/100BaseT/TX to 100BaseFX PD PoE Media Converter, Single Mode/SC, 75 km

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT  
 IEEE 802.3u 100BaseTX  
 IEEE 802.3u 100BaseFX  
 IEEE 802.3af Power over Ethernet (PoE)

### FIXED PORTS

#### models 065-1050ST, 065-1050SC, 065-1050SM, 065-1050SMED, 065-1050SMXLD:

1 Auto-MDIX twisted-pair port meeting IEEE 802.3 10BaseT & IEEE 802.3u 100BaseTX standard specifications; Category 5 or better cable, 100 meters maximum distance for 100BaseTX, Category 3 or better cable, 100 meters maximum distance for 10BaseT

#### plus

1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 62.5/125 or 50/125 micron Multi Mode fiber optic cable, 2,000 meters maximum distance (model 065-1050ST & 065-1050SC)

#### or

1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 15 kilometers maximum distance (model 065-1050SM)

#### or

1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 40 kilometers maximum distance (model 065-1050SMED)

#### or

1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 75 kilometers maximum distance (model 065-1050SMXLD)

#### models 065-1052ST, 065-1052SC, 065-1052SM, 065-1052SMED, 065-1052SMXLD:

1 Auto-MDIX twisted-pair port meeting IEEE 802.3 10BaseT & IEEE 802.3u 100BaseTX standard specifications; Category 5 or better cable, 100 meters maximum distance for 100BaseTX, Category 3 or better cable, 100 meters maximum distance for 10BaseT

#### plus

1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 62.5/125 or 52/125 micron Multi Mode fiber optic cable, 2,000 meters maximum distance (model 065-1052ST & 065-1052SC)

#### or

1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 15 kilometers maximum distance (model 065-1052SM)

#### or

1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 40 kilometers maximum distance (model 065-1052SMED)

#### or

1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 75 kilometers maximum distance (model 065-1052SMXLD)

### PERFORMANCE

**Latency:** < 4.2 μs (LIFO)

**Throughput @ 100Base:** 148,809 pps (64-byte packets)

### LEDs

models 065-1050ST, 065-1050SC, 065-1050SM, 065-1050SMED, 065-1050SMXLD:

Power, PoE, TP Link/Act, 100, FX Link/Act, FDX/COL, 4W, 7W, 15.4W, Power Bad

models 065-1052ST, 065-1052SC, 065-1052SM, 065-1052SMED, 065-1052SMXLD:

FX Link/Act, FX FDX/Col, TX Link/Act, TX 100, PSE Power Good, PSE Power Bad, Power

### PHYSICAL CHARACTERISTICS

**Case dimensions (L x W x H):**

models 065-1050ST, 065-1050SC, 065-1050SM, 065-1050SMED, 065-1050SMXLD:

185 x 112 x 30 mm (7.28 x 4.41 x 1.18")

models 065-1052ST, 065-1052SC, 065-1052SM, 065-1052SMED, 065-1052SMXLD:

94 x 70.3 x 26.2 mm (3.70 x 2.77 x 1.03") Fiber optic interface varies with model.

### SAFETY

FCC Part 15 Class A & CE Mark



Model 065-1052SC



Model 065-1052ST

## Switching Managed Media Converters

Signamax Connectivity Systems' 065-1400 series Managed Switching Media Converters are modular SNMP-managed media converter cards available with a variety of interfaces to provide copper-to-fiber conversion for mission-critical networks. They are used with the 065-1480 Managed Media Converter Rack Mount Chassis to enable network managers to remotely monitor the status of their entire network via RJ45 (in band) or RS-232 (out of band) connection to the 065-1481 series SNMP Management Module included with every Signamax 065-1480 chassis system. Up to eighteen managed media converters are supported in a single 2U-high chassis. Equipped with Link Fault Signaling (LFS) and Loopback Testing capabilities, they extend the enterprise LAN configuration range up to 60 km while simultaneously minimizing downtime expenses and extending the lifespan and reach of existing copper-based managed switches.

Signamax Connectivity Systems' 065-1400 series Singlemode to Multi Mode Managed Media Converters are an enhancement to the Signamax SNMP-managed media converter system. These card-based converters are available with a variety of interfaces to provide Single Mode-to-Multi Mode fiber conversion for mission-critical Fast Ethernet, Gigabit Ethernet, and Asynchronous Transfer Mode (ATM) networks. Gigabit Ethernet Single Mode-to-Single Mode repeater model is also available on request. They are used with the 065-1480 Managed Media Converter Rack Mount Chassis to enable network managers to remotely monitor the status of their entire network via RJ45 (in band) or RS-232 (out of band) connection to the 065-1481 series SNMP Management Module included with every Signamax 065-1480 chassis system. Up to eighteen managed media converters are supported in a single 2U-high chassis. They extend the enterprise LAN or carrier network range up to 60 km while simultaneously minimizing downtime expenses and extending the lifespan and reach of existing copper-based managed switches.



## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3u 100BaseFX  
IEEE 802.3 10BaseT  
IEEE 802.3u 100BaseTX

### FIXED PORTS

#### 100BaseFX models:

1 ST duplex fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 62.5/125 or 50/125 micron Multi Mode fiber optic cable, 2,000 meters maximum distance;  
1 SC duplex fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 62.5/125 or 50/125 micron Multi Mode fiber optic cable, 2,000 meters maximum distance;  
1 SC duplex fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 30 kilometers maximum distance or 60 kilometers maximum distance

### PERFORMANCE

**Delay:** less than 21 bit times

### PHYSICAL CHARACTERISTICS

#### Dimensions (L x W x H):

171.5 x 69 x 21.5 mm  
(6.75 x 2.72 x 0.85")

Fiber optic interface varies with model.

**Weight:** 115 grams

**Power:** External power supply;  
12 Volts DC;

0.8A (Supplied via 065-1480 chassis only)

**Power consumption:** 2.8 Watts maximum

**Operating temperature:** 0° – 50°C  
(32° – 122°F)

**Storage temperature:** -20° – 70°C  
(-4° – 158°F)

**Operating humidity:** 10-80%,  
non-condensing

**Storage humidity:** 5-90%, non-condensing

### EMISSIONS

FCC part 15 Class A, CE Mark



Model 065-1476A/B



Model 065-1476AED/BED

## Switching Managed Media Converters

PART NO.	DESCRIPTION
065-1400	10/100BaseT/TX to 100BaseFX Converter ST Multi Mode
065-1410	10/100BaseT/TX to 100BaseFX Converter SC Multi Mode
065-1420	10/100BaseT/TX to 100BaseFX Converter SC Single Mode (30 km span)
065-1420ED	10/100BaseT/TX to 100BaseFX Converter SC Single Mode (60 km span)
065-1476A	10/100BaseT/TX to 100BaseFX Converter WDM Single Mode (20 km span)
065-1476B	10/100BaseT/TX to 100BaseFX Converter WDM Single Mode (20 km span)

## 10/100BaseT/TX Switching PCI Fiber Optic Media Converters

Signamax Connectivity Systems' Switching PCI Fiber Optic Media Converters are an excellent solution for fiber-to-the-desktop installations where the workstation computers have pre-installed Network Interfaces. These media converters are inserted into one of the PC's available PCI slots, and a copper patch cable is used to connect the media converter to the existing network interface jack on the PC's motherboard or in an adjoining PCI slot. The fiber optic cable then connects to the fiber-based cabling plan for network connectivity. Avoids the need for fiber NIC driver maintenance in environments where PCs are used in both fiber- and copper-connected areas. These converters are designed to handle both legacy 10BaseT and 100BaseTX Fast Ethernet devices on their twisted pair port while maintaining 100BaseFX Fast Ethernet transmission on the fiber optic port. Plug-and-play simplicity makes connection easy.

Each Media Converter provides a 10/100BaseT/TX auto-negotiating RJ45 twisted-pair connector port with Auto-MDIX capability for convenient connection. Built-in 10/100 switch enables the fiber cable connection to operate at 100 Mbps connected to either a 10BaseT or a 100BaseTX network, while remaining completely 100BaseFX standard-compliant.



Model 065-1060SC



Model 065-1060ST

### 10/100BaseT/TX Switching PCI Fiber Optic Media Converters

PART NO.	DESCRIPTION
065-1060SC	PCI card-based 10/100BaseT/TX to 100BaseFX, Multi Mode/SC, 2 km
065-1060ST	PCI card-based 10/100BaseT/TX to 100BaseFX, Multi Mode/ST, 2 km
065-1060SM	PCI card-based 10/100BaseT/TX to 100BaseFX, Single Mode/SC, 20 km
065-1060SMED	PCI card-based 10/100BaseT/TX to 100BaseFX, Single Mode/SC, 40 km
065-1060SMXLD	PCI card-based 10/100BaseT/TX to 100BaseFX, Single Mode/SC, 75 km

### SPECIFICATIONS

#### APPLICABLE STANDARDS

IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX,  
IEEE 802.3u 100BaseFX, ANSI/IEEE 802.3 NWAY,  
Auto-negotiation, PCI Specification 2.0/2.1

#### PERFORMANCE

**Latency:** < 4.2  $\mu$ s (LIFO)  
**Throughput @ 100Base:** 148,809 pps (64-byte packets)

#### LEDs

Per Port: LNK/ACT TX, LNK/ACT FX, Two LEDs total

#### ARCHITECTURE

32-Bit PCI Bus Mastering

#### FIXED PORTS

1 Auto-MDIX twisted-pair port meeting IEEE 802.3 10BaseT & IEEE 802.3u 100BaseTX standard specifications; Category 5 or better cable, 100 meters maximum distance for 100BaseTX, Category 3 or better cable, 100 meters maximum distance for 10BaseT **plus** 1 fiber optic port with SC (model 065-1060SC) or ST (model 065-1060ST) meeting IEEE 802.3u 100BaseFX standard specification; 62.5/125 or 50/125 micron Multi Mode fiber optic cable, 2,000 meters maximum distance **or** 1 SC duplex fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 20 kilometers maximum distance (model 065-1060SM) **or** 40 kilometers maximum distance (model 065-1060SMED) **or** 75 kilometers maximum distance (model 065-1060SMXLD)

# VDSL Ethernet Extender

The Signamax VDSL Ethernet Extender is a point-to-point DSL solution that efficiently extends 10/100 Ethernet circuits to over 600 meters (1,960 feet) at 30 Mbps using existing straight pair copper wire. The 065-1138 will allow Ethernet Networking in existing facilities without pulling extra cable. This is the perfect solution to Ethernet on the factory floor where systems have been upgraded from slower serial communications to Ethernet networkig.

Installation is easy with a single switch setting, one end is set for local and the other remote. The 065-1138 is used in pairs to extend Ethernet connectivity over existing voice grade copper wire.

## KEY FEATURES

- High-Speed Full-Duplex 30Mbps communications link over existing copper cable, Symetric along the VDSL
- 8 Speeds with speed indicator LEDs on top of unit 30 Mbps @ up to 1,970 ft., ratchets down to 1 Mbps @ about 6,200 ft.
- Operates transparent to high layer protocols such as TCP/IP
- Auto-MDIX and Auto-sensing 10Base-T or 100Base-TX and Full or Half-Duplex on the Ethernet port
- Plug and Play design for simple installation, single switch config
- Eleven status LEDs for simple monitoring of the device and connection status

## VDSL Ethernet Extender

PART NO.	DESCRIPTION
065-1138	10/100BaseT/Tx Ethernet over VDSL Extender

## SPECIFICATIONS

### STANDARDS

IEEE802.3 10BASE-T  
 IEEE802.3u 100BASE-TX  
 Ethernet over VDSL

### PROTOCOL

Transparent to higher layer protocols

### CONFIGURATION

One DIP switch set: Local (CO) or Remote (CPE)  
 A link is established between a Local unit and a Remote unit (plug & play)

### ETHERNET INTERFACE

One RJ-45 connector Auto-MDIX and Auto-sensing 10/100Base-T/TX and Full/Half-duplex

### VDSL COPPER INTERFACEL

One RJ-11 connector VDSL port

### TRANSMISSION

Ethernet Data Rate: 10/100Mbps Full/Half-Duplex  
 VDSL line rate: 1/3/5/10/15/20/25/30 Mbps

### CABLE CONNECTION

RJ-45 (10BASE-T): UTP CAT. 3, 4, 5 (2-pair wire)  
 RJ-45 (100BASE-TX): UTP CAT. 5 (2-pair wire)  
 VDSL: Telephone line 24 AWG (0.5mm diameter, 1-pair wire) or larger

### CABLE LENGTH

Ethernet: Maximum 100 meters (328 ft.) (UTP LAN cable)  
 VDSL: Maximum 1,900 meters (6,230 ft., 0.5 mm diameter phone line)

### LEDS

Ethernet: Lnk/Act, Fdx  
 VDSL: Err, Lnk, Loc, Rmt

### POWER

**Power Input:** 12V DC @ 0.8A, external power supply adapter  
**Frequency:** 47Hz to 63Hz

### PHYSICAL CHARACTERISTICS

**Power Adapter:** Universal 100-240 VAC  
 50-60 Hz 12VDC 0.2A External Power Supply  
**Power Dissipation:** 2.4 W Max  
**Operating Temperature:** 0 to 60°C  
**Storage Temperature:** -20 to 70°C  
**Operating Humidity:** 10-90%, non-condensing  
**Dimensions:** 80.3 x 109.2 x 23.8 mm (W x D x H)  
**Weight:** 150 g

### EMISSIONS

FCC part 15 Class A, CE Mark

## 10/100BaseT/TX Switching Mini Fiber Optic Media Converters

Signamax Connectivity Systems' Switching Mini Fiber Optic Media Converters provide an intelligent solution for fiber optic connectivity where simplicity, low cost, and minimum footprint are the primary considerations. These converters are designed to handle both legacy 10BaseT and 100BaseTX Fast Ethernet devices on their twisted pair port while maintaining 100BaseFX Fast Ethernet transmission on the fiber optic port. Plug-and-play simplicity makes connection easy.

Each Media Converter provides a 10/100BaseT/TX auto-negotiating RJ45 twisted-pair connector port with Auto-MDIX capability for more convenient connection. Built-in 10/100 switch enables the fiber cable connection to operate at 100 Mbps connected to either a 10BaseT or a 100BaseTX network, while remaining completely 100BaseFX standard-compliant. Fiber connection can also operate in full duplex mode whether the RJ45 port is connected to a full duplex switch or a half duplex hub.



Model 065-1010



Model 065-1000

### 10/100BaseT/TX Switching Mini Fiber Optic Media Converters

PART NO.	DESCRIPTION
065-1000	10/100BaseT/TX to 100BaseFX, Multi Mode/ST, 2 km
065-1010	10/100BaseT/TX to 100BaseFX, Multi Mode/SC, 2 km
065-1020	10/100BaseT/TX to 100BaseFX, Single Mode/SC, 20 km
065-1020ED	10/100BaseT/TX to 100BaseFX, Single Mode/SC, 40 km
065-1020XLD	10/100BaseT/TX to 100BaseFX, Single Mode/SC, 75 km

### SPECIFICATIONS

#### APPLICABLE STANDARDS

IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3u 100BaseFX

#### FIXED PORTS

1 Auto-MDIX twisted-pair port meeting IEEE 802.3 10BaseT & IEEE 802.3u 100BaseTX standard specifications; Category 5 or better cable, 100 meters maximum distance for 100BaseTX, Category 3 or better cable, 100 meters maximum distance for 10BaseT plus 1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 62.5/125 or 50/125 micron Multi Mode fiber optic cable, 2,000 meters maximum distance (model 065-1010 & 065-1010) or 1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 20 kilometers maximum distance (model 065-1020) or 40 kilometers maximum distance (model 065-1020ED) or 75 kilometers maximum distance (model 065-1020XLD)

#### PERFORMANCE

Latency: <4.2 μs (LIFO)

Throughput @ 100Base: 148,809 pps (64-byte packets)

#### LEDs

Per Port: LNK/ACT TX, LNK/ACT FX  
Two LEDs total

#### PHYSICAL CHARACTERISTICS

Case dimensions (L x W x H):

80 x 54 x 22 mm (3.15 x 2.13 x 0.87")

Fiber optic interface varies with model.

Weight: 0.122 kg

#### SAFETY

UL Listed

# Stand Alone Managed Switching Media Converters

Signamax Connectivity Systems' 065-1600 series Stand Alone Managed Switching 10/100 Media Converters are individually-housed SNMP-managed media converters available with Single Mode and Multi Mode interfaces to provide copper-to-fiber conversion for mission-critical networks. They are typically used as circuit endpoint devices together with the Signamax Managed Media Converter Rack Mount Chassis System to enable network managers to remotely monitor the status of their entire fiber optic Fast Ethernet network all the way to the fiber optic circuit's last termination.

An individual SNMP management agent is included with each Signamax 065-1600 series stand alone managed converter. Equipped with Link Fault Signaling (LFS) and Loopback Testing capabilities, they extend the enterprise LAN configuration range up to 60 km while simultaneously minimizing downtime and technician dispatch expense.



Model 065-1696

Model 065-1610



## Stand Alone Managed Switching Media Converters

PART NO.	DESCRIPTION
065-1600	10/100BaseT/TX to 100BaseFX Converter ST Multi Mode
065-1610	10/100BaseT/TX to 100BaseFX Converter SC Multi Mode
065-1620	10/100BaseT/TX to 100BaseFX Converter SC Single Mode (30 km span)
065-1620ED	10/100BaseT/TX to 100BaseFX Converter SC Single Mode (60 km span)
065-1620XLD	10/100BaseT/TX to 100BaseFX Converter SC Single Mode (90 km span)
065-1676A	10/100BaseT/TX to 100BaseFX Converter WDM Single Mode (20 km span)
065-1676B	10/100BaseT/TX to 100BaseFX Converter WDM Single Mode (20 km span)
065-1676AED	10/100BaseT/TX to 100BaseFX Converter WDM Single Mode (40 km span)
065-1676BED	10/100BaseT/TX to 100BaseFX Converter WDM Single Mode (40 km span)
065-1696	10/100/1000BaseT/TX to 1000BaseSX Converter SC Multi Mode
065-1696LX	10/100/1000BaseT/TX to 1000BaseSX Converter SC Single Mode
065-1696LXWDMA	10/100/1000BaseT/TX to 1000BaseSX Converter WDM Single Mode
065-1696LXWDMB	10/100/1000BaseT/TX to 1000BaseSX Converter WDM Single Mode

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3u 100BaseFX

### FIXED PORTS

1 twisted-pair port meeting IEEE 802.3 10BaseT & IEEE 802.3u 100BaseTX standard specifications; Category 5 or better cable, 100 meters maximum distance for 100BaseTX, Category 3 or better cable, 100 meters maximum distance for 10BaseT **plus** 1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 62.5/125 or 50/125 micron Multi Mode fiber optic cable, 2,000 meters maximum distance **or** 1 SC duplex fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 20 kilometers maximum distance (model 065-1620) **or** 40 kilometers maximum distance (model 065-1620ED) **or** 60 kilometers maximum distance (model 065-1620XLD) **or** 1 WDM fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 20 kilometers maximum distance (models 065-1676A and 065-1676B) **or** 1 WDM fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 40 kilometers maximum distance (models 065-1676AED and 065-1676BED)

### PERFORMANCE

**Latency:** < 0.25  $\mu$ s (LIFO)

**Throughput:** 148,809 pps (64-byte packets)

### PHYSICAL CHARACTERISTICS

**Dimensions (L x W x H):** 267 x 126 x 44 mm

Fiber connector protrusion varies with model

**Weight:** 1.0 kg

**Power:** Internal power supply; 90 – 240 Volts AC

**Operating temperature:** 0° – 50°C

**Storage temperature:** -20° – 70°C

**Operating humidity:** 10-80%, non-condensing

**Storage humidity:** 5-90%, non-condensing

**EMI:** FCC part 15 Class A, CE Mark

## Hardened Media Converters with LFS

Signamax has responded to the demands of fiber optic deployment in rugged environments by introducing the 065-1800 series of hardened media converters. The 065-1800 series provides flexibility in connector types with the extended temperature and humidity ranges required for high-risk installations. Switching models are available for converting Fast Ethernet twisted pair copper cabling to both Multi Mode and Single Mode fiber optic cabling, including models supporting single-strand Single Mode fiber requirements using Wave Division Multiplexing (WDM) technology. In addition, Fast Ethernet Single Mode to Multi Mode converters round out the line, making Signamax the choice for your harsh environment Fast Ethernet fiber optic conversion needs. Also Gigabit models are available.



Model 065-1810TB



Model 065-1800

### Hardened Media Converters with LFS

PART NO.	DESCRIPTION
065-1800	10/100BaseT/TX to 100BaseFX MM/ST, 2 km Hardened Converter
065-1810	10/100BaseT/TX to 100BaseFX MM/SC, 2 km Hardened Converter
065-1820	10/100BaseT/TX to 100BaseFX SM/SC, 20 km Hardened Converter
065-1800TB	10/100BaseT/TX to 100BaseFX MM/ST, 2 km Hardened Converter, Terminal Block
065-1810TB	10/100BaseT/TX to 100BaseFX MM/SC, 2 km Hardened Converter, Terminal Block
065-1820TB	10/100BaseT/TX to 100BaseFX SM/SC, 20 km Hardened Converter, Terminal Block
065-1895	1000 to 1000SX MM/SC, Hardened Converter
065-1895TB	1000 to 1000SX MM/SC, Hardened Converter, Terminal Block
065-1897	1000 to 1000LX SM/SC, Hardened Converter
065-1897TB	1000 to 1000LX SM/SC, Hardened Converter, Terminal Block

#### PERFORMANCE

**Latency:** <4.2  $\mu$ s (LIFO)  
**Throughput:**  
 148,809 pps @ 100 Mbps;  
 14,880 pps @ 10Mbps  
 (64-byte packets)

#### LEDs

**Switching 10/100 to 100FX models:**  
 Per Unit – Power status, Speed (2 LEDs)  
 Per Port – LNK/ACT, FDX/COL (2 LEDs)  
 6 LEDs total

#### PHYSICAL CHARACTERISTICS

**Dimensions:** 130 x 110 x 30 mm  
**Weight:** 0.8 kg  
**Power:** External power supply; 12 Volts DC; 0.5 A  
**Operating temperature:** -34 – 74°C  
**Storage temperature:** -45 – 93°C  
**Operating and storage humidity:** 10-95%, non-condensing

### SPECIFICATIONS

#### APPLICABLE STANDARDS

IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3u 100BaseFX

#### FIXED PORTS

##### Switching 10/100 to 100FX models:

1 twisted-pair port meeting IEEE 802.3 10BaseT & IEEE 802.3u 100BaseTX standard specifications; Category 5 or better cable, 100 meters maximum distance for 100BaseTX, Category 3 or better cable, 100 meters maximum distance for 10BaseT plus 1 fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 62.5/125 or 50/125 micron Multi Mode fiber optic cable, 2,000 meters maximum distance or 1 SC duplex fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 20 kilometers maximum distance (Model 065-1820)

##### 1000BaseT to 1000BaseSx/Lx models:

1 twisted-pair port meeting IEEE 802.3ab 1000BaseT plus 1 fiber optic port meeting IEEE 802.3z 1000BaseSX standard specification; 62.5/125 or 50/125 micron Multi Mode fiber optic cable or 1 SC duplex fiber optic port meeting IEEE 802.3z 1000BaseLX standard specification; 9/125 micron Single Mode fiber optic cable, spanning: 20 kilometers maximum distance (Model 065-1897)

Models w. TB are equipped with Terminal Block

#### EMISSIONS

CC part 15 Class A, CE Mark

# Single Channel Hardened Media Converters

Signamax offers its Hardened Media Converter Series as a concrete and affordable answer in response to an increase in fiber optics cabling deployment. Signamax's 065-1830 Series is one of the most complete solutions in media conversion. 065-1830 Series are available in all varieties of fiber connectors and 065-1830, fiber multi-mode/single-mode to Single Mode fast Ethernet media converter, comes in a wide range of selections. There are options for SC, ST, VF-45, MT-RJ, and LC multi-mode to SC and ST single-mode. We also provide in single-mode to single-mode converter/bridge.

## KEY FEATURES

- Full wire-speed forwarding rate
- 0.8 A 12 VDC external universal PSU
- 0° to 45°C operating temperature range
- Aluminum case
- Supports Wall Mounting installation or expansion use with

## Single Channel Hardened Media Converters

PART NO.	DESCRIPTION
065-1832	100Base-FX Multi Mode (SC) to 100Base-FX Single Mode 15km (SC) Media Converter
065-1830	100Base-FX Multi Mode (ST) to 100Base-FX Single Mode 15km (SC) Media Converter
065-1832ED	100Base-FX Multi Mode (SC) to 100Base-FX Single Mode 40km (SC) Media Converter
065-1830ED	100Base-FX Multi Mode (ST) to 100Base-FX Single Mode 40km (SC) Media Converter
065-1876A	100Base-FX Multi Mode (SC) to 100Base-FX Single Mode (SC) WDM – TX: 1,310 nm/RX: 1,550 nm Media Converter
065-1876B	100Base-FX Multi Mode (SC) to 100Base-FX Single Mode (SC) WDM – TX: 1,550 nm/RX:1,310 nm Media Converter

## SPECIFICATIONS

### STANDARDS

IEEE802.3u 100Base-FX

### LED

Per Unit: Power Status (Power), Link

### POWER

#### Power Input:

Input Voltage: 12 V DC

Input Current: 0.23 A

Power Consumption: 2.76 W Max.

### ISO

Manufactured in an ISO9001 facility

### PHYSICAL CHARACTERISTICS

**Forward and Filtering Rate:** 148,810 pps for 100 Mbps

**Operating Temperature:** 0° to 45°C

**Storage Temperature:** -10° to 70°C

**Ambient Relative Humidity:** 10-90%, non-condensing

**Dimensions (W x D x H):** 80.3 x 109 x 24 mm

**Weight:** 150 g

**Casing:** Aluminumcase

### EMISSIONS

CE Mark Class A, FCC Part 15 Class A

## Gigabit Media Converters

Signamax Connectivity Systems' Gigabit Ethernet Media Converters make it simple to extend distances over Multi Mode or Single Mode fiber. They are designed to expand the scope of your Gigabit Ethernet network applications and are 100% compliant with Ethernet IEEE 802.3ab and 802.3z specifications. These converters maintain the same form factor as other Signamax media converters, allowing use in the model 065-1185 16-Bay Signamax Rack Mount Chassis. Twisted pair to fiber optic converters for both Multi Mode and Single Mode fiber, Multi Mode to Single Mode converters, and Single Mode to Single Mode extenders are available.



Model 065-1195

### SPECIFICATIONS

#### APPLICABLE STANDARDS

- IEEE 802.3ab 1000BaseT
- IEEE 802.3z 1000BaseLX
- IEEE 802.3z 1000BaseSX

#### FIXED PORTS

One twisted-pair port meeting IEEE 802.3ab standard specification; Category 5e or better cable, 100 meters maximum distance **and/or**

One fiber optic port meeting IEEE 802.3z standard; 62.5/125 micron Multi Mode fiber optic cable, 220 meters maximum distance or 50/125 micron Multi Mode fiber optic cable, 550 meters maximum distance (model 065-1194 & 065-1195)

**or**

1 fiber optic port meeting IEEE 802.3z 1000BaseLX standard specification; 9/125 micron Single Mode fiber optic cable, spanning 10 kilometers maximum distance (model 065-1194 & 065-1197)

**or**

20 kilometers maximum distance (models 065-1194ED, 065-1197ED & 065-1198XLD)

#### PERFORMANCE

1,488,000 packets per second at 1,000 Mbps

#### LEDs

**Power;** TX; RX; FDX/COL; LNK6; LNKC (or LNK1; LNK2, model 065-1198XLD)

#### PHYSICAL CHARACTERISTICS

##### Dimensions (L x W x H):

110 x 81 x 23 mm (4.33 x 3.19 x 0.91")

**Weight:** 150 grams

#### SAFETY

UL Listed

### Gigabit Media Converters

PART NO.	DESCRIPTION
065-1194	1000BaseSX to 1000BaseLX Gigabit Ethernet SC Multi Mode to SC Single Mode Media Converter, 10 km span
065-1194ED	1000BaseSX to 1000BaseLX Gigabit Ethernet SC Multi Mode to SC Single Mode Media Converter, 20 km span
065-1195	1000BaseT to 1000BaseSX Gigabit Ethernet Media Converter, SC Multi Mode
065-1197	1000BaseT to 1000BaseLX Gigabit Ethernet Media Converter, SC Single Mode, 10 km span
065-1197B	1000BaseT to 1000BaseLX Gigabit Ethernet Basic Media Converter, SC Single Mode, 10 km span
065-1197ED	1000BaseT to 1000BaseLX Gigabit Ethernet Media Converter, SC Single Mode, 20 km span
065-1198XLD	1000BaseLX to 1000BaseLX Gigabit Ethernet fibre optic repeater, SC Single Mode, 20 km span each port

# 10/100/1000 Switching Fiber Optic Media Converters

Signamax Connectivity Systems' 10/100/1000 Switching Media Converter provides an intelligent solution for long distance connections between legacy 10BaseT and 100BaseTX networks and the newer 1000Base Gigabit Ethernet networks. The built-in 10/100/1000 switch enables the fiber optic connection to operate at 1,000 Mbps connected to either a 10BaseT, 100BaseTX, or a 1000BaseT network, while remaining completely 1000BaseSX standard-compliant for the fiber optic connection. The fiber connection can also operate in full duplex mode whether the RJ45 port is connected to a full duplex switch or a half duplex hub.

Each model 065-1196 Media Converter provides a 10/100/1000BaseT/TX auto-negotiating RJ45 twisted-pair connector port featuring store-and-forward switching architecture. Built-in switch does the network segmentation to provide the maximum fiber distance. Auto-MDIX capability on the twisted-pair port allows convenient connection.



Model 065-1196

## 10/100/1000 Switching Fiber Optic Media Converters

PART NO.	DESCRIPTION
065-1196	10/100/1000BaseT/TX to 1000BaseSX, Multi Mode/SC
065-1196LX	10/100/1000BaseT/TX to 1000BaseLX, Single Mode/SC (10 km span)
065-1196LXED	10/100/1000BaseT/TX to 1000BaseLX, Single Mode/SC (20 km span)

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT  
 IEEE 802.3u 100BaseTX  
 IEEE 802.3ab 1000BaseT  
 IEEE 802.3z 1000BaseSX/LX

### FIXED PORTS

1 Auto-MDIX twisted-pair port meeting IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX & IEEE 802.3ab 1000BaseT standard specifications; Category 5e or better cable, 100 meters maximum distance for 1000BaseT, Category 5 or better cable, 100 meters maximum distance for 100BaseTX, Category 3 or better cable, 100 meters maximum distance for 10BaseT **plus**  
 1 fiber optic port meeting IEEE 802.3z 1000BaseSX standard specification; 62.5/125 micron Multi Mode fiber optic cable, 220 meters maximum distance, or 50/125 micron Multi Mode fiber optic cable, 550 meters maximum distance (model 065-1196) **or**  
 1 fiber optic port meeting IEEE 802.3z 1000BaseLX standard specification; 9 micron Single Mode fiber optic cable, 10 km maximum distance (model 065-1196LX) **or**  
 1 fiber optic port meeting IEEE 802.3z 1000BaseLX standard specification; 9 micron Single Mode fiber optic cable, 20 km maximum distance (model 065-1196LXED)

### PERFORMANCE

**Latency:** < 4.2  $\mu$ s (LIFO)  
**Throughput @ 100Base:** 148,809 pps (64-byte packets)  
**Throughput @ 1000Base:** 1,488,100 pps (64-byte packets)

### LEDs

Per unit: Power status, RJ45 port speed  
 Per Port: LNK/ACT, FDX/COL  
 Six LEDs total

### PHYSICAL CHARACTERISTICS

**Case dimensions (L x W x H):**  
 110 x 81 x 23 mm (4.33 x 3.19 x 0.91")  
 Fiber optic interface varies with model.  
**Weight:** 150 grams

### SAFETY

UL Listed

# SFP Fiber Converters

The Signamax 10/100/1000 to 1000SX/LX (SFP) Media Converter is specifically designed to offer fiber advantages for mission-critical networks like Telco/ISP backbones, cable operators, banking and enterprise networks.

It can reduce network downtime and increase Quality of Service levels. The converter is completely transparent when installed, so the network performs exactly the way it would do normally—only now, it can incorporate both copper and fiber mediums.

This flexibility in cabling allows network managers to put fiber cables anywhere within a network without changing the arrangement of the copper-based Gigabit segments. Their compact size allows the converters to be wall-mounted to save space. Several converters can be simultaneously installed by using the 065-1185 19" rack-mountable chassis.

The Signamax SFP converter takes advantage of intelligent connection technology to support Auto-negotiation, thereby eliminating the hassle of manually configuring or monitoring settings. This ensures plug-n-play operability.



## SFP Fiber Converters

PART NO.	DESCRIPTION
065-1192	10/100/1000BaseT/Tx to SFP Fiber Converter, 1x SFP Slot

## SPECIFICATIONS

### INTERFACE

- One 10/100/1000 Mbps Ethernet port
- Auto MDI/MDI-X support on RJ-45 port
- One SFP slot for Gigabit links
- Extends distances from 220m up to 120km under full-duplex mode
- Supports Link Fault Signaling on both fiber port and copper port

### MANAGEMENT

- Alarm LED illuminates to indicate link failure
- Status LEDs for easy monitoring of device's status

### STANDARDS

- IEEE 10/100Base-TX, IEEE 802.3ab 1000Base-T
- IEEE 802.3z 1000Base-SX/LX
- FCC Part 15 of Class A & CE approved
- Complies with IEEE 10/100Base-TX, IEEE 802.3ab 1000Base-T and IEEE 802.3z 1000Base-SX/LX

### CONNECTOR

- 1 x RJ-45, 1 x Fiber

### MECHANICAL & ENVIRONMENTAL

- External power supply, Chassis-compliant (internal power supply)
- FCC Class A & CE approved, RoHS-compliant

### MAX. DISTANCE

- UTP: 100 meters (Cat. 5/5e/6)
- Fiber: SFP; up to 120km (single-mode)

### UNIT LED

- PWR: Illuminated for normal operation

### POWER

- Power Input:** 12V DC @ 0.8A, external power supply adapter
- Frequency:** 47 Hz to 63 Hz

### PHYSICAL CHARACTERISTICS

- Operating Temperature:** 0° to 50°C
- Storage Temperature:** -20° to 70°C
- Operating Humidity:** 10-90%, non-condensing
- Storage Humidity:** 5-90%, non-condensing
- Dimensions (D x W x H):** 109.2 x 73.8 x 23.4 mm
- Weight:** 158 g

### EMISSIONS

- FCC Part 15 of Class A & CE approved

### DIP SWITCHES

- DIP 1 – LFS: Enable/disable Link-Fault Signaling (LFS)

# Serial Data to Fiber/TP Media Converters

Signamax Connectivity Systems' Serial Data Fiber Media Converters make it simple to extend distances over Multi Mode or Single Mode fiber. They are designed to expand the scope of your RS-232 or RS-422/485 serial data applications, and are 100% compliant with EIA RS-232 unbalanced and both RS-422 & RS-485 4-wire balanced line specifications. Converters for both Multi Mode and Single Mode fiber are available in RS-232/-422/-485 configurations.



Model 065-1163FSM

## KEY FEATURES

- Auto MDI/MDI-X
- External power supply
- FCC Class A & CE approved
- 3-in-1 RS-232/422/485 serial interfaces
- Chassis compliant (internal power supply)
- Auto-detecting 10/100 Mbps Ethernet interface
- Extended distances up to 1.2 km (24 AWG) using RS-422/485
- Supports serial port asynchronous data rates up to 115.2 Kbps
- Managed via CLI, Telnet, RS-232 Console, and Menu-driven interfaces
- Distributed and scalable solution with 256 virtual COM ports control from one device server
- Complies with EIA/TIA-232, EIA/TIA-574, IEEE 802.3 (10Base-T), IEEE 802.3u (100Base-TX)
- Supports 4 wires full duplex asynchronous serial data transmission (RS-422/485)
- Supports 2 wires half-duplex asynchronous serial data transmission (RS-485)
- The Nebility and Webility with Virtual COM (HP Open View and IBM/Tivoli NetView compatible)

## Serial Data Fiber Optic/TP Media Converters

PART NO.	DESCRIPTION
065-1163T	RS-232/422/485 to 100BaseT/Tx RJ45 Converter
065-1163FST	RS-232/422/485 fiber optic Media Converter, ST Multi Mode connector 2,000 meter span
065-1163FSC	RS-232/422/485 fiber optic Media Converter, SC Multi Mode connector 2,000 meter span
065-1163FSM	RS-232/422/485 fiber optic Media Converter, SC Single Mode connector, 20 km span

## SPECIFICATIONS

### APPLICABLE STANDARDS

EIA RS-232, EIA RS-422, EIA RS-485, FIXED PORTS  
One DB-9 serial data port meeting  
EIA RS-232, EIA RS-422 and EIA RS-485

### STANDARD SPECIFICATION.

Push-button switch on rear panel for DTE/DCE selection (all models)  
DIP switch panel on 065-116x series for DTE/DCE selection and timer for multipoint (RS-485) environments.  
Maximum distance: 1,000 meters **and**  
One fiber optic port supporting either 62.5/125 micron or 50/125 micron Multi Mode fiber optic cable, 2,000 meters maximum distance **or**  
one fiber optic port supporting either 9/125 micron or 10/125 micron Single Mode fiber optic cable, spanning 20 kilometers maximum distance

### PERFORMANCE

Supports 5 Mbps (maximum) data transfer rate  
Bit error rate (BER): < 10<sup>-9</sup>

### LED INDICATORS

Unit: Power  
Fiber Port: LNK; RCV

### PHYSICAL CHARACTERISTICS

Dimensions (L x W x H): 110 x 81 x 23 mm  
Weight: 150 grams

### SAFETY

UL Listed

## Single Fiber WDM Converters

Signamax Connectivity Systems' Switching Single Fiber Wave Division Multiplexing (WDM) Media Converters with Link Fault Signaling allow data typically carried over two strands of fiber optic cable to be carried over a single strand of fiber optic cable, utilizing two different wavelengths to carry signals in both directions simultaneously. This technology doubles the capacity of a company's fiber optic network, allowing a carrier or an enterprise business to minimize its operational costs by eliminating or delaying the deployment of additional fiber optic capacity. These converters are available in Single Mode only, and span distances of up to 20 kilometers with the 065-1176ALFS and 065-1176BLFS models.

Since WDM Switching Media Converters utilize two different wavelengths with one end of a circuit transmitting on the other end's receive frequency (and vice versa), they must be used in A/B pairs. A circuit utilizing these converters would therefore use a single strand of Single Mode fiber optic cable plus one each of the 065-1176ALFS and 065-1176BLFS depending upon the distance spanned. All Signamax WDM converters are equipped with Link Fault Signaling to provide the means for an SNMP-managed switch to recognize a failure on a fiber channel or twisted-pair connection, enabling the switch to automatically route to a backup path if the connected switch is equipped with Spanning Tree Algorithm. Each WDM Media Converter provides a 10/100BaseT/TX auto-negotiating RJ45 twisted-pair connector port, and features store-and-forward switching architecture. Auto-MDIX capability on the twisted-pair port is also provided for convenient connections.



Model 065-1176ALFS

### SPECIFICATIONS

#### APPLICABLE STANDARDS

IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX  
IEEE 802.3u 100BaseFX

#### FIXED PORTS

1 Auto-MDIX twisted-pair port meeting IEEE 802.3 10BaseT & IEEE 802.3u 100BaseTX standard specifications; Category 5 or better cable, 100 meters maximum distance for 100BaseTX, Category 3 or better cable, 100 meters maximum distance for 10BaseT **plus** 1 WDM fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning 20 kilometers maximum distance (models 065-1176ALFS and 065-1176BLFS) **or** 1 WDM fiber optic port meeting IEEE 802.3u 100BaseFX standard specification

#### PERFORMANCE

**Latency:** < 4.2  $\mu$ s (LIFO) Throughput @  
**100Base:** 148,809 pps (64-byte packets)

#### LEDs

Per unit: Power status, RJ45 port speed,  
Per Port: LNK/ACT, FDX/COL, Six LEDs total

#### PHYSICAL CHARACTERISTICS

**Case dimensions (L x W x H):** 110 x 81 x 23 mm  
Fiber optic interface varies with model

**Weight:** 150 grams

USB power connector on the rear panel optionally powers converter from computer's USB port.

#### SAFETY

UL Listed

### Single Fiber WDM Converters

PART NO.	DESCRIPTION	FIBER TYPE
065-1176ALFS	10/100BaseT/TX to 100BaseFX, SM/SC, 20 km, Tx=1,310 nm; Rx=1,550 nm	Simplex SC Single Mode
065-1176BLFS	10/100BaseT/TX to 100BaseFX, SM/SC, 20 km, Tx=1,550 nm; Rx=1,310 nm	Simplex SC Single Mode

# Singlemode to Multi Mode Converters

Signamax Connectivity Systems' Singlemode to Multi Mode Converters provide efficient solutions for interconnecting Multi Mode fiber LANs over longer distances by integrating Single Mode fiber optic cable into the LAN. They also enable Ethernet LAN and WAN connectivity, by providing a Multi Mode interface to Single Mode fiber carrier demarcation points. Models are available for Single Mode to Multi Mode conversion between Fast Ethernet devices, or for Asynchronous Transfer Mode (ATM) applications transported over a Synchronous Optical Network (SONET). Each Media Converter is enclosed in a compact, strong metal case and includes an external power supply for stand-alone applications. They can also be installed without modification in the Signamax 065-1185 Rack Mount Chassis system, featuring redundant power supplies for high reliability in multiple converter installations.

## SPECIFICATIONS

### APPLICABLE STANDARDS

- Ethernet IEEE 802.3u
- Asynchronous Transfer Mode (ATM) 155 Mbps Specifications (model 065-1190)
- Asynchronous Transfer Mode (ATM) 622 Mbps Specifications (model 065-1190HS)
- Synchronous Optical Network (SONET) Optical Carrier – 3 (OC-3) Specifications (model 065-1190)
- Synchronous Optical Network (SONET) Optical Carrier – 12 (OC-12) Specifications (model 065-1190HS)
- Synchronous Digital Hierarchy (SDH) STM-1 Specifications (model 065-1190)
- Synchronous Digital Hierarchy (SDH) STM-4 Specifications (model 065-1190HS)

### FIXED PORT SPECIFICATIONS

**models 065-1130, 065-1130ED, 065-1130XLD:**

ST connector; 2,000 meters max. distance  
100BaseFX Multi Mode fiber optic interface,

**models 065-1132, 065-1132ED, 065-1132XLD:**

SC connector; 2,000 meters max. distance  
100BaseFX Multi Mode fiber optic interface,

**models 065-1130, 065-1130ED, 065-1130XLD,**

**065-1132, 065-1132ED & 065-1132XLD:**

SC connector, 100BaseFX Single Mode fiber interface; Standard model: 15 kilometers max. distance

**ED model:** 40 kilometers max. distance

**XLD model:** 75 kilometers max. distance

**SONET OC-3 / ATM 155 Mbps**

**Multi Mode fiber optic interface,**

**model 065-1190:**

ST connector; 2,000 meters max. distance

**SONET OC-3 / ATM 155 Mbps**

**Single Mode fiber optic interface,**

**model 065-1190:**

SC connector; 20 kilometers max. distance

**SONET OC-12 / ATM 622 Mbps**

**Multi Mode fiber optic interface,**

**model 065-1190HS:**

ST connector; 2,000 meters max. distance

**SONET OC-12 / ATM 622 Mbps**

**Single Mode fiber optic interface,**

**model 065-1190HS:**

SC connector; 20 kilometers max. distance

### PERFORMANCE

**Delay:** less than 21 bit times

### PHYSICAL CHARACTERISTICS

**Case dimensions (L x W x H):**

110 x 81 x 23 mm

(4.33 x 3.19 x 0.91")

Fiber optic interface varies with model.

**Weight:** 150 grams

### SAFETY

UL Listed



Model 065-1130

## Singlemode to Multi Mode Converters

PART NO.	DESCRIPTION
065-1130	100BaseFX SC Single Mode (15 km span) to ST Multi Mode
065-1130ED	100BaseFX SC Single Mode (40 km span) to ST Multi Mode
065-1130XLD	100BaseFX SC Single Mode (75 km span) to ST Multi Mode
065-1132	100BaseFX SC Single Mode (15 km span) to SC Multi Mode
065-1132ED	100BaseFX SC Single Mode (40 km span) to SC Multi Mode
065-1132XLD	100BaseFX SC Single Mode (75 km span) to SC Multi Mode
065-1190	ATM 155 Mbps / SONET OC-3 SC Single Mode (20 km span) to SC Multi Mode

## Basic Media Converters

Signamax Fast Ethernet WDM Media Converters are designed to bridge a 100Base-TX signal to a 100Base-FX signal. It's used to extend the connection distance between two Fast Ethernet Twisted-pair devices via fiber cable transparently with no performance degradation.

WDM Switching Media Converters utilize two different light spectra with one end of a circuit transmitting on the other end's receive frequency (and vice versa), they must be used in A/B pairs. A circuit utilizing these converters would therefore use a single strand of Single Mode fiber optic cable plus one each of the 065-1176A and 065-1176B. It's supported Auto-negotiation & flow control function on Twisted-pair port.



Model 065-1186



Model 065-1176A



Model 065-1197B

### Basic Media Converter

PART NO.	DESCRIPTION
065-1197B	1000BaseT to 1000BaseLX, SM 10 km, SC
065-1176A	10/100BaseT/TX to 100BaseFX SC SM (20 km) Tx = 1,310, Rx = 1,550
065-1176B	10/100BaseT/TX to 100BaseFX SC SM (20 km) Rx = 1,310, Tx = 1,550
065-1186	16-Slot Basic Media Converter Chassis

### SPECIFICATIONS

#### APPLICABLE STANDARDS

IEEE 802.3 10BaseT  
IEEE 802.3u 100BaseTX  
IEEE 802.3u 100BaseFX

#### FIXED PORTS

1 Auto-MDIX twisted-pair port meeting IEEE 802.3 10BaseT & IEEE 802.3u 100BaseTX standard specifications; Category 5 or better cable, 100 meters maximum distance for 100BaseTX, Category 3 or better cable, 100 meters maximum distance for 10BaseT **plus** 1 WDM fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning 20 kilometers maximum distance (models 065-1176ALFS and 065-1176BLFS) **or** 1 WDM fiber optic port meeting IEEE 802.3u 100BaseFX standard specification; 9/125 micron Single Mode fiber optic cable, spanning 40 kilometers maximum distance (models 065-1176AEDLFS and 065-1176BEDLFS)

#### PERFORMANCE

**Latency:** < 4.2  $\mu$ s (LIFO) Throughput @  
**100Base:** 148,809 pps (64-byte packets)

#### LEDs

Per unit: Power status, RJ45 port speed,  
Per Port: LNK/ACT, FDX/COL  
Six LEDs total

#### PHYSICAL CHARACTERISTICS

**Case dimensions (L x W x H):** 110 x 81 x 23 mm  
Fiber optic interface varies with model

**Weight:** 150 grams

USB power connector on the rear panel optionally powers converter from computer's USB port

#### SAFETY

UL Listed

# 12-Port Rack Mount Media Converters

The Signamax 065-1200 12-Channel Rack Mount Media Converter is a perfect solution for large installations that utilize many of the same type of media converters. The 065-1200 contains 12 channels of media conversion in a standard rack mountable case only one rack unit high. This extremely high port density allows the maximum number of media converter channels per rack for enterprise-level businesses and carriers. Redundant fan-cooled power supplies ensure maximum system uptime.

The 065-1200 has a choice of configurations, utilizing the same technology and connector types as the standalone media converters in the 065-1100 series for 10/100BaseT/TX to 100BaseFX conversion. Standard or Link Fault Signaling (LFS) versions are available. In addition, the 065-1200 can be optionally equipped with twelve channels of Gigabit Ethernet 1000BaseT to 1000BaseSX media conversion, replacing twelve 065-1195 converters.



Model 065-1200ST00

## 12-Port Rack Mount Media Converter

PART NO.	DESCRIPTION
065-1200ST00	10/100BaseT/TX to 100BaseFX Converters ST Multi Mode
065-1200SC10	10/100BaseT/TX to 100BaseFX Converters SC Multi Mode
065-1200LC74	10/100BaseT/TX to 100BaseFX Converters LC Multi Mode
065-1200SC20	10/100BaseT/TX to 100BaseFX Converters SC Single Mode (15 km span)
065-1200SC20ED	10/100BaseT/TX to 100BaseFX Converters SC Single Mode (40 km span)
065-1200SC95	1000BaseT to 1000BaseSX Converters SC Multi Mode
065-1200SC97	1000BaseT to 1000BaseLX Converters SC Single Mode

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX  
 IEEE 802.3u 100BaseFX, IEEE 802.3ab 1000BaseT  
 IEEE 802.3z 1000BaseSX

### FIXED PORTS

Twelve channels of media conversion, each with a twisted pair port and a corresponding fibre optic port meeting either of the following specifications:

#### 065-11xx series and 065-11xxLFS series versions:

10/100BaseT/TX to 100BaseFX, Multi Mode fibre; choice of SC, ST, VF45 or MTRJ connectors; maximum distance: 2,000 meters  
 10/100BaseT/TX to 100BaseFX, Single Mode fibre, SC connectors; MTRJ connectors available on request. Maximum distance: up to 75 kilometers

### LEDs:

Per unit: Power status, Speed (2 LEDs)  
 Per port: LNK/ACT, FDX/COL (2 LEDs)

### 065-1195 version:

1000BaseT to 1000BaseSX, Multi Mode fibre, SC connectors; MTRJ connectors available on request. Maximum distance, 1000BaseSX port:  
 220 meters over 62.5 micron Multi Mode fibre or 550 meters over 50/125 micron Multi Mode fibre (full duplex only)

### LEDs:

Per unit: Power status, FDX/COL, TX, RX (4 LEDs)  
 Per port: LNK/F for fibre port, LNK/C for copper port (1 LED each)

### PHYSICAL CHARACTERISTICS

#### Dimensions (W x D x H):

440 x 205 x 45 mm (17.3 x 8.0 x 1.8")

#### Weight: 3.1 kg maximum

Standard 19" rack mounting (hardware included)

### SAFETY

UL 1950

# 16-Bay Media Converter Rack Mount Chassis

The Signamax 065-1185 16-Bay Media Converter Rack Mount Chassis provides higher rack mount media converter density for large installations that can accommodate rear access to the chassis for power supply maintenance. The 065-1185 provides 16 bays of space for all 065-11xx series Signamax media converters in a standard two rack unit high enclosure. High port density allows a variety of media converter solutions to be utilized in a minimum amount of rack space for enterprise-level businesses and carriers. Redundant, fan-cooled load-sharing power supplies can be hot-swapped to ensure maximum system uptime.

The 065-1185 has a choice of power supply configurations, supporting AC power for 110 volt or 220 volt power systems or -48 volt DC power for carrier operations.



Model 065-1185

## 16-Bay Media Converter Rack Mount Chassis

PART NO.	DESCRIPTION
065-1185	16-Bay Rack Mount Media Converter Chassis System, includes 2 Redundant AC Power Supplies & 4 Fan Cooling Assemblies
065-1185DC	16-Bay Rack Mount Media Converter Chassis System, includes 2 Redundant -48 V DC Power Supplies & 4 Fan Cooling Assemblies
FO-AC-1185	Spare Redundant AC Power Supply for 16-Bay Chassis
FO-DC-1185	Spare Redundant -48 V DC Power Supply For 16-Bay Chassis
FO-1185FAN	Spare Individual Fan Assembly For 16-Bay Chassis

## SPECIFICATIONS

### CAPACITY

Sixteen bays, for up to sixteen 065-11xx series media converters

### LEDs

Power 1/Power 2: Power supply on-line

### SAFETY

UL 1950 listed

Cooling Fans: UL/cUL/TUV Listed/Approved

### PHYSICAL CHARACTERISTICS

Dimensions (L x W x H): 440 x 276 x 90 mm, 2 standard rack units

Weight: Approximately 8.5 kg, fully loaded


### POWER SUPPLIES

Load-sharing and hot-swappable,

2 supplied as standard equipment AC and -48 Volt

DC units available

Power status LED on each power supply, as well as remote status LEDs on front panel



Model 065-1185

# 18-Bay Rack Mount Managed Media Converter Chassis System

The Signamax™ 065-1480 18-Bay Managed Media Converter Rack Mount Chassis provides full SNMP management capabilities for mission-critical installations. The 065-1480 provides 18 bays of space for all 065-14xx series Signamax managed media converters in a standard 2U high enclosure. It also includes the 065-1481 Management Module, which communicates with the Signamax 065-14xx series media converters on the chassis' backplane. It provides full status information on the individual media converter's ports and allows the advanced management capabilities of the 065-14xx series managed media converters to be switched on or off remotely and individually. Diagnostic testing from a centralized location avoids unnecessary technician dispatch. Alarm traps can be sent to up to five remote IP addresses simultaneously, allowing integration within a variety of Network Management Systems. In-band and out-of-band management are supported by local and remote Telnet console Command Line Interface (CLI), a web browser-based Graphical User Interface (GUI), and a menu-driven interface.

Two fully redundant, load-sharing power supplies are standard, to ensure continued availability of the media converters in the event of a power supply failure. Either power supply is hot-swappable and can be taken off-line and removed from the unit while the media converters are operating; the media converters themselves are also hot-swappable. The 065-1480 also ships standard with three fully redundant, load-sharing cooling fans to ensure reliable operation.

Model 065-1480



## 18-Bay Rack Mount Managed Media Converter Chassis System

PART NO.	DESCRIPTION
065-1480	18-Bay Rack Mount Managed Media Converter Chassis System; includes 065-1481 SNMP Management Module, 2 Redundant AC Power Supplies, & 3 Fan Cooling Assemblies
065-1480DC	18-Bay Rack Mount Media Converter Chassis System; includes 065-1481 SNMP Management Module, 2 Redundant -48 V DC Power Supplies, & 3 Fan Cooling Assemblies
065-1481	Spare SNMP Management Module
AC-1480	Spare Redundant AC Power Supply for 18-Bay Chassis
DC-1480	Spare Redundant -48 V DC Power Supply For 18-Bay Chassis
1480FAN	Spare Individual Fan Assembly For 18-Bay Chassis

## SPECIFICATIONS

### 065-1480 Chassis

#### CAPACITY

Eighteen bays for up to eighteen 065-14xx Media Converters

#### CONSTRUCTION

SECC zinc-coated steel

#### COOLING

One 42.5 cfm rear-mounted fan, plus one fan for each of the two redundant power supplies.

#### LEDs

Power (2x): Power supply on-line  
FAN (3x): Fan status

#### DIMENSIONS (W x D x H)

440 x 276 x 90 mm  
(17.3 x 10.9 x 3.5")  
2 standard rack units

#### WEIGHT

Approximately 13.5 kg, fully loaded

### POWER SUPPLIES—LOAD SHARING AND HOT-SWAPPABLE

(2 supplied as standard equipment)

#### Input:

model 065-1480: 90 – 240 Volts AC,  
47 – 63 Hz

model 065-1480DC: -48 Volts DC

#### Output:

Normal +12 Volts DC (Min. +11.88 Volts,  
max. +12.12 Volts, 7.0 Amps)

#### Total Regulation:

+/-1.0%, Rip. 120 mV, Load 1.0%, Line 0.5%

#### Overload Protection:

All outputs protected against short circuit conditions; automatic recovery

#### Excess Voltage Protection:

Output level exceeding 13.2 Volts causes shutdown; automatic recovery

#### Temperature:

Operating: 0° – 40°C

Storage: -25° – 70°C

EMI: FCC Part 15 Class A, CE Class A

Safety: UL 1950 Listed

### 065-1481 Management Module

#### PROTOCOLS SUPPORTED

TCP, UDP, ICMP, IP, ARP

#### SERVICE

HTTP, Telnet, SNMP, TFTP

#### PORTS

DB-9 Serial Data (x1),  
RJ45 10/100BaseT/TX (x1)

#### LEDs

Power, System, Alert, 10/100 speed, Link/ACT

#### MIB SUPPORTED

MIB II, RMON

#### PHYSICAL CHARACTERISTICS

Storage temp.: -40° – 80°C

Operating temp.: 0° – 50°C

Maximum altitude: 10,000 ft.

Dimensions (L x W x H):

171.5 x 69 x 21.5 mm

Weight: 115 grams

EMI: FCC Part 15 Class A, CE Class A

# 8-Bay Managed Media Converter Chassis

Through out-of-band management via Web Browser, the Managed Media Converter System can be monitored and configured. Each 065-1400M Managed Converter Chassis features eight slots for 065-1485 Chassis Manager Media Converter and 065-1400CO Media Converters (CO) in one Managed Converter Chassis. The Managed Converter Chassis System is allowed to have four 065-1485 Managed Converter Chassis on one Managed Converter Chassis System by using IN/OUT Port for stacking. One 065-1485 chassis manager will manage four stacked chassis plus local and remote media converters.

## 8-Bay Managed Media Converter Chassis

PART NO.	DESCRIPTION
065-1485	8-Bay Managed Media Converter Chassis
065-1400M	10/100BaseT/Tx to 100BaseFX Multi Mode (ST)
065-1410M	10/100BaseT/Tx to 100BaseFX Multi Mode (SC)
065-1420M	10/100BaseT/Tx to 100BaseFX Single Mode (SC) – 20 Km
065-1420MED	10/100BaseT/Tx to 100BaseFX Single Mode (SC) – 40 Km
065-1476MA	10/100BaseT/Tx to 100BaseFX Single Mode (SC) WDM – TX: 1,310 nm/RX: 1,550 nm – 20 Km
065-1476MB	10/100BaseT/Tx to 100BaseFX Single Mode (SC) WDM – TX: 1,550 nm/RX: 1,310 nm – 20 Km
065-1476MAED	10/100BaseT/Tx to 100BaseFX Single Mode (SC) WDM – TX: 1,310 nm/RX: 1,550 nm – 40 Km
065-1476MBED	10/100BaseT/Tx to 100BaseFX Single Mode (SC) WDM – TX: 1,550 nm/RX: 1,310 nm – 40 Km
065-1410CO	10/100BaseT/Tx to 100BaseFX Multi Mode (SC)
065-1400CO	10/100BaseT/Tx to 100BaseFX Multi Mode (ST)
065-1420CO	10/100BaseT/Tx to 100BaseFX Single Mode (SC) – 20 Km
065-1420COED	10/100BaseT/Tx to 100BaseFX Single Mode (SC) – 40 Km
065-1476COA	10/100BaseT/Tx to 100BaseFX Single Mode (SC) WDM – TX: 1,310 nm/RX: 1,550 nm – 20 Km
065-1476COB	10/100BaseT/Tx to 100BaseFX Single Mode (SC) WDM – TX: 1,550 nm/RX: 1,310 nm – 20 Km
065-1476COAED	10/100BaseT/Tx to 100BaseFX Single Mode (SC) WDM – TX: 1,310 nm/RX: 1,550 nm – 40 Km
065-1476COBED	10/100BaseT/Tx to 100BaseFX Single Mode (SC) WDM – TX: 1,550 nm/RX: 1,310 nm – 40 Km

## SPECIFICATIONS

### POWER

#### Input:

100-240V AC, 50-60 Hz Internal Universal PSU

12V DC, 1.67A

Power Consumption: 32W Max

### LEDs

Per Unit: Power Status (Power), Fan Status, Stack Port Status

### SAFETY

Manufactured in an ISO9001 facility

### PHYSICAL CHARACTERISTICS

Casing: Metal case

Operating Temperature: 0° to 45°C

Storage Temperature: -10° to 70°C

Ambient Relative Humidity: 10-90% (non-condensing)

Dimensions (W x D x H): 440 x 235 x 44 mm

Weight: 3 kg

Installation: RackMounting

### EMISSION COMPLIANCE

CEMark Class A, FCC Part 15 Class A

# WebSmart Media Converters

Signamax Connectivity Systems' 065-1300 series Standalone WebSmart Switching Media Converters are individually-housed WebSmart media converters available with Single Mode and Multi Mode interfaces to provide copper-to-fiber conversion for mission-critical networks. They are typically used as circuit endpoint devices together with the Signamax Managed Media Converter Rack Mount Chassis System to enable network managers to remotely monitor the status of their entire fiber optic Fast Ethernet and Gigabit Ethernet network all the way to the fiber optic circuit's last termination.



Model 065-1300

## WebSmart Media Converters

PART NO.	DESCRIPTION
065-1300	10/100BaseT/TX to 100BaseFX WebSmart Media Converter, ST Multi Mode
065-1310	10/100BaseT/TX to 100BaseFX WebSmart Media Converter, SC Multi Mode
065-1320	10/100BaseT/TX to 100BaseFX WebSmart Media Converter, SC Single Mode
065-1376A	10/100BaseT/TX to 100BaseFX WebSmart Media Converter, WDM Single Mode
065-1376B	10/100BaseT/TX to 100BaseFX WebSmart Media Converter, WDM Single Mode
065-1395	1000BaseT to 1000BaseSX WebSmart Media Converter, SC Multi Mode
065-1397	1000BaseT to 1000BaseLX WebSmart Media Converter, SC Single Mode

## SPECIFICATIONS

### STANDARDS

- IEEE 802.3 10BaseT, Priority Protocols
- IEEE 802.3u 100BaseTX/100BaseFX
- IEEE 802.1x, IEEE 802.1p Class of Service

### FEATURES

- Number of Ports:
  - 1 10/100BaseT with RJ-45 Connector
  - 1 100BaseFX with Fiber Connector (Multi/Single Mode, ST/SC, LC, MT-RJ Connector)

### DATA TRANSFER RATE

- Ethernet:
  - 10 Mbps/Half-Duplex, 20 Mbps/Full-Duplex
- Fast Ethernet: 100 Mbps/Half-Duplex, 200 Mbps/Full-Duplex

### LEDs

- Per Port:**
  - (TX): Link/Act, Speed, FDX/COL
  - (FX): Link/Act, FDX/COL
- Per Unit:** Power

### TRANSMISSION MEDIA

- 10BaseT Cat. 3, 4, 5 UTP/STP, up to 100 m
- 100BaseTX Cat. 5 UTP/STP, up to 100 m
- 100BaseFX:**
  - 50/125 or 62.5/125 micron Multi Mode ST/SC Type Fiber optic cable, up to 2 km
  - 9/125 or 10/125micron Single Mode Fiber optic cable

### PHYSICAL CHARACTERISTICS

- Power Requirement:** DC 5V/2A
- Power Consumption:** 10 Watts (Max)
- Temperature:**
  - Operating:** 0° – 45°C
  - Storage:** -20° – 90°C
- Dimensions (L x W x H):** 130 x 77 x 24 mm
- Weight:** 0,28 grams
- Humidity:** 10-90% RH (non-condensing)
- EMI:** FCC Class A, CE

## 16-Slot Chassis for Modular EPON Media Converters

The manageable box is a 19" Media Converter Chassis with cabinet height 3U. It is designed to accommodate 16 slots of various type of fiber media converter module at a central location for multiple segments cross connection and network management. Any combination of GEAPON Fiber conversion solutions can be installed in a wiring closet for cable connection. The network management supports Web UI via browser, CLI via local console, Telnet interface and SNMPv2c.

Supports IEEE 802.3ah OAM function for CO and CPE site "Remote Failure Indication", "Remote Loopback" and "Link Monitoring". Supports "Port Configuration" and "Bandwidth Configuration". Models equipped with DC 48V power unit are also available for Telecom applications.

### 16-Slot Chassis for Modular EPON Media Converters

PART NO.	DESCRIPTION
098-1580	16-Slot EPON Converter Chassis with Dual AC Input Redundant Power Supply
098-1580RDC	16-Slot EPON Converter Chassis with Dual DC Input Redundant Power Supply
098-1580RADC	16-Slot EPON Converter Chassis with AC+DC Input Redundant Power Supply
098-1580AC	16-Slot EPON Converter Chassis with Single AC Input Redundant Power Supply
098-1580DC	16-Slot EPON Converter Chassis with Single DC Input Redundant Power Supply
ONU-1510	10/100/1000Base-T to EPON ONU Managed Converter
OLT-1515	10/100/1000Base-T to EPON OLT Managed Converter Module

### SPECIFICATIONS

#### PARAMETER

Capacity: 16 Slots for modular Media converter  
 Management: SNMP and web-base via in-band LAN port or local serial CLI  
 Power supply: Hot-swap redundant, high reliability/safety  
 Redundant Power Requirement:  
 AC Power Input:  
 Voltage: 100/240V AC  
 Frequency: 50-60Hz  
 Dissipation: 200W maximum  
 Telecom DC Input:  
 Voltage: 48V DC  
 Dissipation: 200W maximum

#### SAFETY

Complies with FCC Part 15 Class A & CE Mark Approval

#### PHYSICAL CHARACTERISTICS

**Ambient Temperature:** 0 to 70°C  
**Humidity:** -40° to 85°C  
**Dimensions:** 125 x 90 x 8 mm  
**Weight:** 8.52 kg (without power)  
 9.54 kg (includes 1 x AC power)  
 10.56 kg (includes 2 x AC power)  
 9.57 kg (includes 1 x DC power)  
 10.62 kg (includes 2 x DC power)  
 10.59 kg (includes 1 x AC power + 1 DC power)

## KEY FEATURES

- Supports standard 19" 3U high rack-mount chassis with 16 slots for converter modules
- 19-inch rack mount
  - The concentrator unit will fit in both Electronic Industries Association (EIA) standard compliant racks.
- Supports 3 fans for chassis heat radiating
- Operating temp range 0° – 50°C
- Supports chassis temperature detection with F/C both degree
- Supports FAN rotation rate (RPM) detection
- Supports chassis ID (CID) for chassis location indication
- Built-in management CPU module:
  - Supports DB-9 RS232 interface for console
  - Supports two Ethernet ports in management network
- Management Board LED display: PowerA/B, UTP port: Act/Link, CPU Run
- Supports hot-swappable and upgradeable management CPU module
- Supports hot-swappable converter modules
- Supports hot-swappable and loading-shared redundant power units, each can be DC or AC. Independent power input for each power modules
- Supports Real-Time Clock (RTC)
- Power monitor (absent/present, ON/OFF, DC/AC), fans monitor and temperature monitor
- Power supply: Hot-swap redundant, high reliability/safety
- Supports CO/CPE conversion port configuration for port state, Speed/Duplex, Flow Control and Bandwidth setting
- Comply with RoHS Requirement
- Provides a Gigabit Ethernet PON (Passive Optical Network), converting 10/100/1000 Mbps Ethernet into optical signals with an optical coupler for point-to-multipoint networks. The EPON OLT converter module for the center unit can be selected to provide datacom service for distances of up to 20 km. The same subscriber unit EPON ONU converter is used for remote CPE site, whether 20 km type.
- One OLT handles up to 32 subscribers per fiber
  - Implements full duplex with single SM fiber links, along with an optical coupler for 32 branches, making it possible to handle up to 32 subscribers per single optical fiber
- One chassis supports up to 512 subscribers
  - The center unit (rear access type) uses high-density packing to fit up to 512 subscribers into a 3U case height (132 mm), saving your valuable rack space
- Independent channel configuration
  - Additional EPON converter module can be added as needed to economically handle subscriber growth. In addition, maintenance is possible in channel units, making it possible to respond to a fault on one channel without affecting the others.

# NETWORK CONNECTIVITY SYSTEMS





## Ethernet Switches



**5- & 8-Port 10/100 Desktop Switches**

**8-Port 10/100 Desktop PoE Switches**

**8-Port Managed Desktop Switches**

**Desktop Web Smart Fast Ethernet Switch**

**Fast Ethernet 16-Port Desktop Switches**

**10/100BaseT/TX Rack Mount Unmanaged Ethernet Switch**

**16-Port WebSmart 10/100 Managed Ethernet Switches**

**Gigabit POE Management Switch series**

**Modularized 24+2G Access Switch**

**Metro and Metro PoE Stackable Switches with 2 Combo ports**

**Metro Stackable Switches with 4 Combo ports**

**Compact Fiber Access Switch**

**5- and 8-Port 10/100/1000BaseT/TX Desktop Switches**

**WebSmart Gigabit Ethernet Switches**

**Gigabit Management Switch**

**Advanced Gigabit L2 Managed Switches**

**24-Port 10/100 + 4G Combo L3 Switch**

**Hardened Ethernet Switches**

**Hardened Managed Switches**

**4-Port Broadband Access Router**

**Signamax USB NAS**

**SFP Fiber Modules**

**10 Gbps Modules**

## 5- & 8-Port 10/100 Desktop Switches

Signamax Connectivity Systems' Desktop Switches makes it easy to increase user capacity and let 10 and 100 Mbps devices directly communicate with each other. Full duplex mode multiplies total network capacity by providing up to 200 Mbps bandwidth per port rather than sharing 100 Mbps bandwidth between hub users, and segments networks for improved performance by forwarding traffic only to the users to whom the message was sent. Auto-sensing speed feature automatically handles both 10 Mbps and 100 Mbps users.

State-of-the-art switches provide a straightforward upgrade from hub-based shared Ethernet using your existing investment in hardware, cabling and personnel training. By combining simple installation with dual-speed flexibility and scalable expansion, Signamax Ethernet switches virtually guarantee high network performance. Now is an even more compact size for easy placement.



Model 065-7025B



Model 065-7028B

### 5- & 8-Port 10/100 Desktop Switches

PART NO.	DESCRIPTION
065-7025B	5-Port 10/100BaseT/TX Desktop Ethernet Mini Switch, external power supply, plastic case
065-7028B	8-Port 10/100BaseT/TX Desktop Ethernet Mini Switch, external power supply, plastic case
065-7013	8-Port 10/100BaseT/TX Desktop Ethernet Switch, external power supply, metal case
065-7015Q	5-Port 10/100BaseT/TX WebSmart Media Streaming Fast Ethernet Switch

## FEATURES

- Non-blocking Performance Improves Access to Network Resources
- Five/eight Independent Bandwidths with 10-200 Mbps Capability
- All Ports Support Auto-negotiation and Auto-MDI/MDI-X to Facilitate Installation and Troubleshooting
- Full Wire Speed Store-and-Forward Technology Instantly Eliminates Bad Packets
- Automatic Source Address Learning and Aging
- Support 1K MAC Address
- Built-in High Efficiency SRAM for Packet Buffer
- Support IEEE 802.3x Flow-control for Full-duplex and Back-pressure Flow-Control for Half-duplex
- Delicate Plastic Palm Size with an External Power Adapter
- Easy-to-Understand LEDs Display Real-time Traffic Status to Monitor and Diagnose the Network
- Built-in High Efficiency SRAM for Packet Buffer
- Broadcast Storm Filter, Runt and CRC Filtering Eliminate Erroneous Packets to Optimize the Network Bandwidth
- Support Power Saving Mode by Cable Detection

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT  
IEEE 802.3u 100BaseTX  
IEEE 802.3x Flow Control  
ANSI/IEEE 802.3 NWay Auto-negotiation

### PORTS

Model 065-7025B: 5 – RJ-45 10/100BaseT/TX Auto-MDI ports  
(IEEE 802.3 10BaseT; 802.3u 100BaseTX)  
Models 065-7028/065-7028B:  
8 – RJ-45 10/100BaseT/TX ports  
(IEEE 802.3 10BaseT; 802.3u 100BaseTX)  
16 – RJ-45 10/100BaseT/TX ports  
(IEEE 802.3 10BaseT; 802.3u 100BaseTX)

### PERFORMANCE

Throughput: 148,809 pps (64-byte packets)  
Switch Fabric Speed: 065-7025: 1.0 Gbps, 065-7028: 1.6 Gbps

### PHYSICAL CHARACTERISTICS

Dimensions (L x W x H): 065-7025B/8B: 159 x 100 x 28 mm  
Weight: 065-7025AB/8B: 0,3kg

### LEDS

Power, Full/Half Duplex, 10/100 Collision, Link/Activity (all models)

### SAFETY

Power supply UL & cUL listed



Model 065-7025B



Model 065-7025B back



Model 065-7013



Model 065-7013 back

## 8-Port 10/100 Desktop PoE Switches

The Signamax 065-7013PD is 8-Port Ethernet Switch consists of 8 Ethernet ports, port No. 8 can be either Ethernet port or PD port for DC power input. Connect PD port with POE switch to enhance your networking environment, user will not compromise to the electrical system.



Model 065-7308PoE



Model 065-7013PD

### 8-Port 10/100 Desktop PoE Switches

PART NO.	DESCRIPTION
065-7013PD	8-Port 10/100BaseT/TX Desktop Ethernet Switch, 1xPoE PD Port
065-7308PoE	8-Port 10/100BaseT/TX Desktop Ethernet Switch, 4xPoE PSE Ports

### FEATURES

- 8-Port 10/100BASE T/TX Nway (Auto-negotiation) Switch with RJ-45 connectors
- Port No. 8 is to be either Ethernet port or PD port which can get power source from the PSE port
- 48V powered-able as link with PSE port
- Provides low-voltage DC power over existing Cat.5 cable to a device with an Ethernet port
- Complies with IEEE 802.3 10BASE-T; IEEE 802.3u 100BASE-TX; IEEE802.3af
- Fully Flow Control Supported: Half-duplex mode- Backpressure, Full-duplex mode- IEEE 802.3x
- Full/Half-duplex modes auto detecting and Auto-MDIX in all ports (twisted pair)
- High performance even under full-duplex 200Mbps bandwidth each port and Zero-Packet Loss
- Broadcast storm control, Store & Forward switching methods
- Non-blocking & Non-head-of-line blocking full wire speed forwarding
- Auto-learning of networking configurations
- Supports 2K MAC address filtering, aging and 1 Mbits buffer memory
- Packet Filter/Forward Rate: 100 Mbps/148,800 pps, 10 Mbps/14,880 pps
- Status LEDs: Power, 10/100M, Link/Activity, and FDx
- Network Transmission Media: 10BASE-T Cat. 3, 4, 5 UTP/STP, 100BASE-TX Cat. 5 UTP/STP
- Power supply: From PD port or AC power cord input (90-260V/AC, 50-60 Hz) UL Safety
- Operating Temperature: 0° – 60°C
- Store Temperature: -20° – 90°C
- Humidity: 10-90% RH (Non-condensing)
- Dimension (L x W x H): 130 x 80 x 25 mm
- Weight: 0.35 kg
- Safety & EMI Certificates: CE & FCC
- Smart plug & play

# 8-Port Managed Desktop Switches

The Signamax 065-7508/065-7708 switches are an full L2 management 8-Port Fast Ethernet switches, with high performance and competitive price. They are perfect way to extend your network structure.

## KEY FEATURES

- 11" Metal Case
- Rack-Mount to 19" Cabinet
- No Fan No Noise
- Internal Power Supply
- Web-based Configuration and Management



Model 065-7508



Model 065-7708

## 8-Port Managed Desktop Switches

PART NO.	DESCRIPTION
065-7508	8-Port 10/100BaseT/Tx Desktop Web Smart Fast Ethernet Switch
065-7708	8-Port 10/100BaseT/Tx Desktop L2 Managed Switch

## SPECIFICATIONS

### STANDARDS

IEEE 802.3 10Base-T  
IEEE 802.3u 100Base-TX

### MEDIA

UTP CAT3 or up for copper port

### CHIP

88E6095+88E6218

### ACCESS METHOD

CSMA/CD

**Transmission Method:** Store and Forward

**MAC Address:** 8K

**Built-in Buffer:** 1.5 Mbits

**Data Transfer Rate:**

10/100Mbps (Half-duplex),  
20/200Mbps (Full-duplex for copper port)

### LEDs

Power, Link/Activity

### ENVIRONMENTAL

#### TEMPERATURE HUMIDITY

**Dimension (LxWxH):**

280 x 173 x 44 mm

**Weight:** 4000 g

**Temperature:**

0° to 50°C (operating),

-20° to 70°C (storage)

**Humidity:**

5 to 90 % non-condensing (operating),

5 to 90% non-condensing (storage)

### CERTIFICATIONS

FCC Part 15 Class A, CE Mark

## FEATURES

- Compliant with the IEEE802.3 10Base-T Ethernet, IEEE802.3u 100Base-TX
- 8 port 10/100Mbps TX Auto-Negotiation
- Supports TP interface Auto MDIX function for auto TX/RX swap
- Support up to 8K MAC address
- Up to 1.5 M bits packet buffer
- Supports Store & Forward architecture and performs forwarding and filtering
- Supports to handle up to 1522 bytes packet
- Supports 8 groups Port-Based VLAN and 512 groups 802.1q tag VLAN
- Supports rate control (64 Kbps – 80 Mbps)
- Supports port mirror
- Supports IEEE802.1D Spanning Tree and IEEE802.1w RSTP protocol
- Supports MAC address filter and binding (up to 400 rules)
- Supports IGMP snooping
- Supports port trunking (up to 12 groups and 8 ports in each group)
- Supports SNMP V1/V2, RMON MIB (group 1, 2, 3, 9)
- Supports access switch through Web/Telnet/Console
- Supports firmware upgrade through Web/Console
- Build-in power

# Desktop WebSmart Fast Ethernet Switch

065-7542 is 24-Port Desktop WebSmart Fast Ethernet Switch that is designed for small or medium network environment to strengthen its network connection. This product is compact in size, making it ideal for Desktop users with limited space. It also gives you the option of installing it in a 19" cabinet by rack-mount kits or underneath a desk. 065-7542 provides Smart features that are ideal for simple QoS/CoS applications and basic monitoring tools to improve network efficiency. Its security and management features, such as bandwidth control, and VLAN (IEEE 802.1Q VLAN tagging and port-based VLAN) to secure your network. Through a Web-based interface, an administrator can set up VLANs to segregate traffic, QoS to prioritize mission-critical data and link aggregation to create fat traffic pipelines. All of these features offer extra protection on the network edge. Best of all, the password-protected configuration interface can be accessed remotely.



Model 065-7542

## FEATURES

- Auto-MDI/MDI-X**  
 Every port can automatically sense your type of cable, so there is no need for crossover cables whether you are connecting this switch to another switch or to a computer.
- Auto-Negotiation**  
 Every port can automatically sense if the connected network devices are running at 10Mbps or 100Mbps and Half/Full-Duplex mode, and adjust accordingly.
- Non-Blocking**  
 This switch receives and forwards traffic seamlessly with its non-blocking wire-speed. Every port simultaneously supports up to 200 Mbps of bandwidth in full-duplex mode. This feature provides full wire speed to the connected devices and allows you to run a smooth network.
- Store and Forward**  
 By this function, this switch can maximize network performance while minimizing the propagation of bad network packets.

## Desktop WebSmart Fast Ethernet Switch

PART NO.	DESCRIPTION
065-7542	24-Port 10/100BaseT/Tx Desktop WebSmart Fast Ethernet Switch

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT  
 IEEE 802.3u 100BaseTX  
 IEEE 802.3x Flow Control  
 IEEE 802.1Q VLAN Tagging  
 IEEE 802.1p Class of Service  
 Priority Protocols

### FEATURES

Number of Ports: 24  
 MAC Address: 4K  
 Buffer Memory: 1.5 Mbits  
 Transmission Method: Store and Forward

### SMART FEATURES

Management: Password-protected Access, Port Settings, Web-base Management, Graphic User Interface

### NETWORK CHARACTERISTICS

Filtering/Forwarding Rates:  
 100Mbps port – 148,800 pps  
 10Mbps port – 14,880 pps  
 Transmission Media:  
 10BaseT Cat. 3, 4, 5 UTP/STP  
 100BaseTX Cat. 5 UTP/STP

### LEDs

Per Port: Link/Act, 10/100M  
 Per Unit: Power

### PHYSICAL CHARACTERISTICS

**Power Requirement:** 90-260V/AC, 50-60 Hz  
**Power Consumption:** 12 Watts (Max)  
**Dimensions (L x W x H):** 266 × 160 × 44 mm  
**Weight:** 1.7 kg  
**Operating Temperature:** 0° to 55°C  
**Storage Temperature:** -20° to 90°C  
**Humidity:** 10-90% RH (non-condensing)  
**Certifications:** FCC Class A, CE

# Fast Ethernet 16-Port Desktop Switches

The Signamax 16-Port Ethernet Switches are designed to allow simultaneous transmission of multiple packets via an internal high-speed data channel. This means that it can partition a network more efficiently than bridges or routers in most environments. Signamax 16-Port Ethernet Switch is a highly reliable network Switch and is the ideal device for bridging Ethernet to Fast Ethernet workgroups or networks. Simple and cost-effective, the Signamax Switch supports IEEE 802.3 10Base-T Ethernet and IEEE 802.3u 100Base-TX Fast Ethernet. This Switch is therefore fast being recognized as one of the most important building blocks of current networking technology. The front panel of the Switch provides LEDs for easy recognition of the Switch operation status and for troubleshooting. These LEDs display the power status of the system and link status speed, collision and receives status for each port. With Signamax 16-Port Ethernet Switch designed specifically for connecting workgroup devices and desktops, companies no longer have to invest in expensive and inflexible switches engineered primarily for backbone implementations. Instead, companies can deploy scaleable, affordable Switch that increases the aggregate bandwidth of the network by boosting throughput to the workgroups that need it most.

Model 065-7031



## SPECIFICATIONS

### APPLICABLE STANDARDS

- IEEE 802.3 10BaseT
- IEEE 802.3u 100BaseTX
- IEEE 802.3x Flow Control
- ANSI/IEEE 802.3 NWay Auto-negotiation

### PORTS

- 16 – RJ-45 10/100BaseT/TX ports  
(IEEE 802.3 10BaseT; 802.3u 100BaseTX)

### PERFORMANCE

- Throughput: 148,809 pps (64-byte packets)
- Switch Fabric Speed: 065-7031: 3.2 Gbps

### PHYSICAL CHARACTERISTICS

- Dimensions (L x W x H): 065-7031: 165 x 105 x 28 mm
- Weight: 065-7031: 1.1 kg

### LED STATUS INDICATORS

- Power, Full/Half Duplex, 10/100 Collision,  
Link/Activity (all models)

### SAFETY

- Power supply UL & cUL listed



Model 065-7032A



Model 065-7032A

## Fast Ethernet 16-Port Desktop Switches

PART NO.	DESCRIPTION
K19-7031	Rackmount Kit for 065-7031 – 19" Rack
065-7031	16-Port 10/100BaseT/TX Desktop Ethernet Switch, internal power supply, metal case
065-7032A	16-Port 10/100BaseT/TX Desktop Ethernet Switch, external power supply



# 10/100BaseT/TX Rack Mount Unmanaged Ethernet Switch

Signamax Connectivity Systems' 10/100BaseT/TX Ethernet Switches feature 24 10/100 ports, with the 065-7341 model.

This model transparently pass packets of up to 1,522 bytes, allowing its use in networks utilizing IEEE 802.1p and IEEE 802.1Q tagged packets. In addition, these models support 8K MAC addresses, and provide a true non-blocking switching architecture with full wire speed forwarding. The Signamax 065-7341 Switches provide a lower-cost answer to today's computing needs and high bandwidth requirements.



Model 065-7341

## 10/100BaseT/TX Rack Mount Unmanaged Ethernet Switch

PART NO.	DESCRIPTION
065-7341	24-Port 10/100BaseT/TX Switch Rack Mount

### SPECIFICATIONS

#### APPLICABLE STANDARDS

- IEEE 802.3 10BaseT
- IEEE 802.3u 100BaseTX
- IEEE 802.3u 100BaseFX
- IEEE 802.3x Flow Control

#### LEDs

- Per Unit: Power
- Per Port: LNK/ACT; 100 Mbps speed indicator

#### PHYSICAL CHARACTERISTICS

- Dimensions (W x D x H): 440 x 140 x 44 mm
- Weight: 2.8 kg

#### MEMORY

- Packet Buffer Size: 2.5 Mb shared packet buffers

#### PORTS

- 24 – Fixed 10/100BaseT/TX ports, RJ45 connectors with Auto-MDIX (IEEE 802.3u Type 10BaseT & 100BaseTX)
- Maximum distance:
  - IEEE 802.3 10BaseT – 2-pair UTP Cat. 3, 4, 5 or better, up to 100 meters
  - IEEE 802.3u 100BaseTX – 2-pair UTP Cat. 5 or better, up to 100 meters

#### PERFORMANCE

- Throughput: 148,800 pps at 100 Mbps
- 14,880 pps at 10 Mbps (64-byte packets)
- MAC Address Table Size: 8K entries

#### ENVIRONMENT

- Operating:
  - Temperature: 0° – 40°C
  - Relative Humidity: 10-90%, non-condensing
  - Altitude: 3,048 meters
- Non-Operating/Storage: Temperature: -25° – 70°C
- Relative Humidity: 10-90%, non-condensing

#### EMISSIONS

- FCC part 15 Class A, CE Mark Class A

# 16-Port WebSmart 10/100 Managed Ethernet Switch

Signamax Connectivity Systems' WebSmart 10/100 Ethernet Switches feature 16 10/100 ports, an optional 100BaseFX Multi Mode or Single Mode fiber module for longer distance network connections, and easy web-based administration. Fiber optic Multi Mode or Single Mode expansion module options allow installation of fiber cabling anywhere within your existing copper-based network. These switches also include advanced support for port-based Virtual Local Area Networking (VLAN) and multi-port inter-switch trunking for use in larger-scale networks. WebSmart administrative and configuration capabilities provide network administrators with powerful, easy-to-use tools to reduce unnecessary broadcast traffic, flexibly segment networks, and enhance network security—either by a local cable connection or remotely from any convenient location using a standard web browser.



Model 065-7531A

## 16-Port WebSmart 10/100 Managed Ethernet Switches

PART NO.	DESCRIPTION
065-7531A	16-Port 10/100BaseT/TX WebSmart 10/100 Switch + 1x Fast Ethernet Fiber Slot
<b>Expansion Modules</b>	
065-75SC	100BaseFX Expansion Module For 10/100 Switch – SC Multi Mode
065-75ST	100BaseFX Expansion Module For 10/100 Switch – ST Multi Mode
065-75SM	100BaseFX Expansion Module For 10/100 Switch – SC Single Mode (15 km span)

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3u 100BaseFX,  
IEEE 802.3x Flow Control

### PORTS

- 16 – RJ45 10/100BaseT/TX Auto-MDIX ports  
(IEEE 802.3 Type 10BaseT; 802.3u Type 100BaseTX)
- 1 – open 100BaseFX interface slot, RJ45 10/100BaseT/TX local console port

### LEDs

Per Switch: Power  
Per Console Port: Link, Activity  
Per Port: Link/Activity, 100 Mbps Speed

### PERFORMANCE

**Latency:** < 6.0  $\mu$ s (FIFO)  
**Throughput:** 148,810 pps (64-byte packets)  
**Switch Fabric Speed:** 3.6 Gbps  
**Address Table Size:** 2K MAC addresses

### PHYSICAL CHARACTERISTICS

**Dimensions (W x D x H):** 440 x 207 x 44 mm  
**Weight:** Approximately 2.8 kg

### EMISSIONS

FCC Class A, CE Mark

### SAFETY

UL 1950, CSA, TUV/GS



Model 065-75SC



Model 065-75ST



# Gigabit POE Management Switch series

Signamax Gigabit switch 065-7820 POE supports 12x 10/100/1000 Mbps Auto-negotiation, Auto-MDIX Ethernet ports and Power over Ethernet to IEEE 802.3af compliant devices. It's fully compliant with the standards of IEEE 802.3/u/x/z/ab/af. It is equipped with 12 Giga TP ports and 2 of which are dual media ports that accommodate optional 10/100/1000Base-T or SFP modules. In addition, the switch implements the QoS (Quality of Service), Mac Filtering Policy, Port Mirror, VLAN and full L2 protocol. The overall network management is enhanced and the network efficiency is also improved to accommodate high bandwidth applications with security.

## Signamax Gigabit POE Management Switch series

PART NO.	DESCRIPTION
065-7820POE	12-Port 10/100/1000BaseT/Tx Gigabit Managed Switch with 2 Combo

## SPECIFICATIONS

### APPLICABLE STANDARDS

- IEEE 802.3af PoE Standard, IEEE 802.3 10Base-T Ethernet (twisted-pair copper)
- IEEE 802.3u 100Base-T Ethernet (twisted-pair copper)
- IEEE 802.3ab 1000Base-T Ethernet (twisted-pair copper)
- IEEE 802.3z 1000Base-X Ethernet
- IEEE 802.3x Flow Control capability ANSI/IEEE 802.3 Auto-negotiation
- IEEE 802.1p Priority Tag, IEEE 802.1q VLAN

### SUBSCRIBER INTERFACE

- 12 Gigabit Ethernet ports, Auto-negotiation, Auto-MDIX
- Back pressure flow control for half duplex
- Flow control for full duplex
- Port 11, 12 are TP/SFP Fiber auto sense
- Connector: 12 RJ45 and 2 SFP module

### PERFORMANCE

- Switching capacity:**
- 12 Gigabit Ethernet ports with non-blocking wire speed performance
- 8K MAC addresses, 208 KB on-chip frame buffer, Jumbo frame support

### QOS

- Supports Layer 4 TCP/UDP Port and ToS Classification
- Supports 802.1p QoS with two level Priority queue

### BANDWIDTH CONTROL

- Supports bandwidth rating per port ingress and egress rate limit 1,000 Mbps with 1 Mbps increments

### VLAN

- Port-base VLAN, IEEE802.1q tag-base VLAN, 4094 Max

### PORTS TRUNK

- Ports trunking with 6 trunking group, up to 6 ports for each group

### BROADCAST/MULTICAST STORM

- Broadcast Storm control

### PORT MIRRORING

- All port support port mirroring

### POE FEATURES

- Supports IEEE 802.3af compliant u Supports
- Power over Ethernet (PSE) on each Gigabit UTP port
- Full power support for per POE port, 135W Supported
- Auto detect powered device and consumption levels
- Supports per port power consumption monitoring
- Smart feature for PD on/off, PD detection, power level, PD status and power feeding priority
- Circuit protection to prevent power interference between ports
- Supports per port PoE State setting
- Supports per port power priority setting
- LED indicators for POE ready and POE activity

### HW SPECIFICATION:

- Power Requirement 220W or 155W , Total Power for PoE 200W or 135W
- Dimensions (H x W x D):** 44 x 442 x 211 mm

# Modularized 24+2G Access Switch

Emanating from our expertise in developing network communication solutions, the 065-7750 Modularized 24-Port Ethernet Managed Switch incorporates leading switching technology and high-port density within a slim 1-rack unit chassis. The 065-7750 represents an industry first as no other switch in the market today can match the unique 3 x 8-Port modular, 2 GBIC slots plus console port design. This innovation offers the ultimate in flexibility and freedom to “mix-and-match” in terms of cabling (fiber + copper) and speed (Ethernet to Gigabit). Furthermore, the available redundant power supply makes the 065-7750 ideal for mission critical installation as it ensures no disruption in service due to surges or drops in power.



Model 065-7751

## SPECIFICATION

### STANDARDS AND COMPLIANCE

IEEE 802.3: 10BASE-T specification  
 IEEE 802.3x: Flow control  
 IEEE 802.3z: 1000BASE-SX/LX specification  
 IEEE 802.1d: Spanning-Tree Protocol  
 IEEE 802.1p: 1 Priority Queues  
 IEEE 802.1q: VLAN Tagging, RFC 1350, TFTP  
 IEEE 802.1v: VLAN Classification  
 IEEE 802.3u: 100BASE-TX and 100BASE-FX specification

### PERFORMANCE

**Throughput:** 14,880 packets per second (pps) to 10 Mbps ports  
 148,800 pps to 100BASE-TX ports, 1,488,000 pps to 1000BASE-T ports  
**Address Table Size:** 14K MAC entries  
**Buffer Memory:** 3Mbit Packet Memory  
**Flash Memory:** 512K  
**VLANs:** Port-based or 802.1q- Up to 256 VLANs, with GVRP for dynamic VLAN registration  
**Link Aggregation:** 2-4 ports can be combined into a fat pipe, 7 trunks  
**Max. Distance:** UTP: 100 meters (Category 5e or better)  
**Fiber:** 2,000 meters (62.5/125 micron fiber cabling)  
 20,000 meters (9/125 micron fiber cabling), 60,000 meters (9/125 micron fiber cabling)  
**Management via:** SNMP, Web Management, Command Line Interface (CLI), Menu-driven (Signamax's proprietary), RS-232 console

### NETWORK MANAGEMENT

System Configuration: Console port, Telnet, Web browser, SNMP/RMON NMS  
 Management Agent: SNMP Support: MIB II, Bridge MIB, Ethernet MIB, RMON MIB, and Signamax's Private MIB  
 RMON Groups: 1, 2, 3, 9 (Statistics, History, Alarm and Event)  
 Link Aggregation: 2-4 ports can be combined into a fat pipe, 7 trunks

### CONNECTORS AND CABLING

**Ports:** 3 x Fast Ethernet slots (for 8 or 4-Port modules); 2 x GBIC  
**Module Types:** 8-Port 100 Mbps LC, fiber 8-Port; 100 Mbps MT-RJ, fiber 8-Port 10/100 Mbps RJ-45 8-Port; 100Mbps WDM fiber 4-Port 100 Mbps SC fiber 4-Port; 100Mbps ST fiber, 2-Port Gigabit (GBIC)  
**SNMP control:** Out-of-band control: RS-232, In-band control: RJ-45, Fiber

### SNMP STANDARDS

RFC 1213: MIB II, RFC 1493, Bridge MIB  
 RFC 1643: Ethernet MIB, RFC 1757, RMON MIB, Proprietary Signamax MIB

### LEDs

#### Modular Ports:

10/100 Mbps, Green, Illuminates when data transmission rate 100Mbps  
 LNK ACT, Green, Flashes or illuminates when transmitting or receiving data packets FDX, Amber, Illuminates when in full duplex mode

**Gigabit Ports:** LNK ACT, Green, Flashes or illuminates when link pulses from a compliant device

### POWER CHARACTERISTICS

**AC input voltage:** 90 to 240V AC (auto-ranging) 50 to 60 Hz  
**Output:** 3.3V DC, 20A & 5V, 1A (71W),  
 2 Power supplies (1 primary and 1 redundant)

### ENVIRONMENTAL CHARACTERISTICS

**Operating:** Temperature: 0° – 50°C  
 Humidity: 5-90% (non-condensing)  
**Storage:** Temperature: -28° – 70°C  
 Humidity: 5-90% (non-condensing)

### HARDWARE SPEC.

Height: 4.4 cm, Width: 44 cm, Depth: 28.5 cm  
 Weight: 4.3 kg fully loaded  
 Mounting: Standard 19" Rack-mount case

### ELECTROMAGNETIC COMPATIBILITY

Emissions: FCC Part 15 of Class A, CE approved



Model 065-7750



Model 065-7754



Model 065-7752

## Modularized 24+2G Access Switch

PART NO.	DESCRIPTION
065-7750	Modularized 24+2G Access Switch
065-7751	8-Port 10/100BaseT/TX Module
065-7752	8-Port 100BaseFX Multi Mode LC Module
065-7753	8-Port 100BaseFX Single Mode LC Module
065-7754	4-Port 100BaseFX Multi Mode ST/SC Module

# Metro and Metro PoE Stackable Switches with 2 Combo Ports

Signamax Connectivity Systems' new stackable Metro Ethernet Power over Ethernet (PoE) Access Switch provides the capability to remotely power wireless access points, VoIP telephones, Powered Device (PD) Media Converters, and other devices that meet the IEEE 802.1af PoE standard. These switches provide non-blocking performance for two 10/100/1000BaseT/TX Dual Media Gigabit Ethernet ports plus 24 10/100BaseT/TX PoE-equipped ports. The 065-7726SPOE switch shares the same SNMP management package as its 065-7726S counterpart. Both ring and star Gigabit backbone network architectures are supported with full automatic failover AND PoE extension to every workstation. Enhanced Layer 3 look-ahead routing features and IEEE 802.1p Quality of Service / 802.1Q Tagged VLAN / IP Type of Service support make the Signamax 065-7726SPOE switch the cost-effective choice for creating an infrastructure capable of supporting Voice over IP telephony and wireless access.



Model 065-7710

## Metro and Metro PoE Stackable Switches with 2 Combo ports

PART NO.	DESCRIPTION
065-7710	Desktop Switch, 10-Port 10/100BaseT + 2x SFP, Management
065-7726S	Rackmount Switch 24-Port 10/100BaseT, 2x SFP, Management, Stackable
065-7726SPOE	PoE, Rackmount Switch 24-Port 10/100BaseT, 2x SFP, Management, Stackable

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX  
 IEEE 802.3ab 1000BaseT  
 IEEE 802.3af Power over Ethernet (PoE)  
 IEEE 802.3z 1000BaseSX/LX  
 IEEE 802.1p Priority (Quality of Service [QoS])  
 IEEE 802.1D/802.1w/802.1s Spanning Tree & Rapid Spanning Tree Protocols  
 IEEE 802.1Q Tagged VLAN with "Q-in-Q" support  
 IEEE 802.3x Flow Control, IEEE 802.3ad Link Aggregation  
 IEEE 802.1x Access Control

### PERFORMANCE

**Latency:** < 4.5 µs (LIFO)  
**Throughput:** 1.48810 million pps (64-byte packets)  
**Switch Fabric Speed:** 48.0 Gbps  
 PoE – 135W Supported

### ADMINISTRATION CONSOLE

1 – RS-232C DB-9 local console serial port

### PORTS

24 – RJ45 10/100BaseT/TX PoE-equipped ports  
 2 – Dual Media Gigabit Ethernet ports (2- RJ45 10/100/1000BaseT/TX ports with corresponding Small Form-factor Pluggable [SFP] auto-detecting ports)

### Optional Interfaces:

**065-77MM:** 1000BaseSX SFP fiber optic module with LC Multi Mode fiber connectors  
**Maximum distance:** 220 meters with 62.5/125 micron fiber cabling or 550 meters with 50/125 micron fiber cabling  
**065-77SM:** 1000BaseLX SFP fiber optic module with LC Single Mode fiber connectors  
**Maximum distance:** 10 km with 9/125 micron fiber cabling

### SNMP MANAGEMENT

Console port access via RS-232 cable, Telnet remote access, SNMP agent, and Web browser  
 Kermit/TFTP software-upgrade capability

### LEDs

Per Switch: Power, CPU  
 Per Port: Link/Activity (separate for SFPs), 10/100/1000 speed for RJ45 ports

### PHYSICAL CHARACTERISTICS

**Dimensions (W x D x H):** 442 x 210 x 44 mm  
 Standard 19" rack mounting (hardware included)  
**Weight:** 3.4 kg

### SAFETY

FCC Part 15 Class A & CE Mark Approval

# Metro Stackable Switches with 4 Combo Ports

The Signamax 065-7708 switch is an full L2 management 8-Port Fast Ethernet switch, with high performance and competitive price. It's a perfect way to extend your network structure.

The Signamax 065-7728 switch is an full L2 management 24-Port Fast Ethernet switch plus 4 Gigabits port (support auto copper/fiber switching), with high performance and competitive price. It's a perfect way to extend your network structure.

The Signamax 065-7764 switch is an full L2 management 48-Port Fast Ethernet switch plus 4 Gigabits port (support auto copper/fiber switching), with high performance and competitive price. It's a perfect way to extend your network structure.



Model 065-7728



Model 065-7708

## Metro Stackable Switches with 4 Combo ports

PART NO.	DESCRIPTION
065-7708	8-Port 10/100BaseT/TX L2 Managed Switch
065-7728	24-Port 10/100BaseT/Tx + 4xCombo RJ45/SFP
065-7764	48-Port 10/100BaseT/Tx + 4xCombo RJ45/SFP

Model 065-7764



## SPECIFICATIONS

### STANDARDS

IEEE 802.3 10Base-T,  
IEEE 802.3u 100Base-TX

### CHIP

88E6095+88E6218

### ACCESS METHOD

CSMA/CD

### MEDIA

UTP CAT3 or up for copper port

### LEDs

Power, Link/Activity

**Transmission Method:** Store and Forward

**MAC Address:** 8K

**Built-in Buffer:** 1.5 Mbits

**Data Transfer Rate:**

10/100Mbps (Half-duplex),

20/200Mbps (Full-duplex for copper port)

### ENVIRONMENTAL

#### TEMPERATURE HUMIDITY

**Dimension (LxWxH):**

280 x 173 x 44mm

**Weight:** 4,000 g

**Temperature:**

0° – 50°C (operating),

-20° – 70°C (storage)

**Humidity:**

5-90% non-condensing (operating)

5-90% non-condensing (storage)

### CERTIFICATIONS

FCC Part 15 Class A, CE Mark

## FEATURES

- Build-in power
- Supports port mirror
- 8-Port 10/100 Mbps TX Auto-Negotiation
- Support up to 8K MAC address
- Up to 1.5M bits packet buffer
- Supports IGMP snooping
- Supports TP interface Auto MDIX function for auto TX/RX swap
- Supports Store & Forward architecture and performs forwarding and filtering
- Supports IEEE802.1D Spanning Tree and IEEE802.1w RSTP protocol
- Supports 8 groups Port-Based VLAN and 512 groups 802.1q tag VLAN
- Compliant with the IEEE802.3 10Base-T Ethernet, IEEE802.3u 100Base-TX
- Supports rate control (64 Kbps – 80 Mbps)
- Supports to handle up to 1,522 bytes packet
- Supports MAC address filter and binding (up to 400 rules)
- Supports port trunking (up to 12 groups and 8 ports in each group)
- Supports SNMP V1/V2, RMON MIB (group 1, 2, 3, 9)
- Supports access switch through Web/Telnet/Console
- Supports firmware upgrade through Web/Console

# Compact Fiber Access Switch

Signamax' Connectivity Systems' Compact Fiber Access Switches provide the right port interface you need for fiber-extended networks. The 065-7111 series of switches allows cost-effective fiber extension to small workgroups and Programmable Logic Controller (PLC) clusters. These switches support enterprise-level network extension to distant buildings in a campus environment, and can also extend process control networks over fiber to production or control machinery equipped with PLCs at Fast Ethernet speeds. These switches, to allow administrative and production networks to coexist on the same fiber link transparently pass tagged VLAN and Quality of Service (QoS) packets used to separate and prioritize sub-networks.



Model 065-7111SC

## Compact Fiber Access Switch

PART NO.	DESCRIPTION
065-7111SC	Multi Mode Compact Fiber Access Switch – SC

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX  
IEEE 802.3u 100BaseFX, IEEE 802.3x Flow Control

### PORTS

8 – Fixed 10/100BaseT/TX Auto-MDIX ports, RJ45 connectors; (IEEE 802.3u Type 10BaseT & 100BaseTX)  
1 – Fixed 100BaseFX port, SC Multi Mode – connectors (IEEE 802.3u Type 100BaseFX)  
Maximum distance: 2,000 meters with 62.5/125 micron or 50/125 micron Multi Mode fiber cabling

### LEDS

Per Switch: Power  
Per Port: Link/Activity

### PERFORMANCE

Throughput:  
148,810 pps at 100 Mbps,  
14,800 pps at 10 Mbps (64-byte packets)  
Switch Fabric  
Speed: 1.6 Gbps  
Address, Table Size: 2,048 entries

### PHYSICAL CHARACTERISTICS

Dimensions (W x D x D): 254 x 135 x 35 mm  
Weight: 1.6 kg

### EMISSIONS

FCC part 15 Class A, CE Mark Class A, VCCI Class A

### MOUNTING

Desktop or wall mounting

### SAFETY

UL 1950, RoHS compatible

# 5- and 8-Port 10/100/1000BaseT/TX Desktop Switches

Signamax Connectivity Systems' 10/100/1000BaseT/TX Desktop Switches make it easy to increase user capacity and provide Gigabit Ethernet to devices in a small workgroup. Auto-sensing speed, duplex mode, and Auto-MDIX features automatically handle 10 Mbps, 100 Mbps, and 1,000 Mbps users. State-of-the-art switches provide a straight-forward upgrade from standard or Fast Ethernet, using your existing investment in hardware, cabling and personnel training.

By combining simple installation with compact size, Signamax Gigabit Ethernet desktop switches virtually guarantee high network performance.



Model 065-7908A

## 5 and 8-Port 10/100/1000BaseT/TX Desktop Switches

PART NO.	DESCRIPTION
065-7905A	5-Port 10/100/1000BaseT/TX Desktop Ethernet Mini Switch
065-7908A	8-Port 10/100/1000BaseT/TX Desktop Ethernet Mini Switch
065-7912	8-Port 10/100/1000BaseT/Tx Desktop WebSmart Ethernet Switch

## SPECIFICATIONS

### APPLICABLE STANDARDS

IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX  
 IEEE 802.3ab 1000BaseT, IEEE 802.3x Flow Control  
 IEEE 802.3z 1000Base-X Ethernet  
 ANSI/IEEE 802.3 Auto-negotiation,  
 IEEE 802.1q VLAN

### STANDARD COMPLIANCE

8 Gigabit Ethernet ports, Auto-negotiation, Auto-MDIX  
 Backpressure flow control for half duplex  
 Flow control for full duplex  
 Port 7,8 are TP/SFP Fiber auto sense  
 Connector: 8 RJ-45 and 2 SFP module

### PERFORMANCE

#### Throughput:

1,488,000 pps forwarding rate for 1,000 Mbps  
 148,800 pps forwarding rate for 100 Mbps  
 14,880 pps forwarding rate for 10 Mbps (64-byte packets)

#### Switch Fabric Speed:

model 065-7905A: 10 Gbps  
 model 065-7908A: 16 Gbps  
 model 065-7912: 8 Gbps

#### Address Table Size:

model 065-7905A/065-7912: 8K entries  
 model 065-7908A: 4K entries

### PORTS

5 – RJ45 10/100/1000BaseT/TX Auto-MDI ports  
 (IEEE 802.3 Type 10BaseT; 802.3u Type 100BaseTX;  
 IEEE Type 1000BaseT)  
 8 – RJ45 10/100BaseT/TX Auto-MDI ports (IEEE 802.3 Type  
 10BaseT; 802.3u Type 100BaseTX; IEEE Type 1000BaseT)

### PHYSICAL CHARACTERISTICS

#### Dimensions (W x D x H):

model 065-7905A: 171 x 98 x 29 mm  
 model 065-7908A: 190 x 120 x 38 mm  
 model 065-7912: 132 x 217 x 44 mm

#### Weight:

model 065-7905A: 254 g  
 model 065-7908A: 395 g  
 Desktop or wall mounting, via slots in case.

#### Voltage: 100-240V

#### Frequency: 50-60 Hz

#### Consumption: 20 W

#### Ambient Temperature: 0° to 50°C

#### Storage humidity: 5-90%

### LEDs

Per Switch: Power, CPU ACT, SFP  
 Per Port: Link/Activity, 100 Mbps, 1,000 Mbps

### SAFETY

Comply with FCC Part 15 Class A & CE Mark Approval

## WebSmart Gigabit Ethernet Switches

Signamax Connectivity Systems' 16- and 24-Port WebSmart™ Gigabit Ethernet Switch features 16 or 24 10/100/1000BaseT/TX twisted-pair ports to extend Gigabit Ethernet to your servers and workstation users with high-bandwidth requirements. This switch also includes advanced support for port-based Virtual Local Area Networking (VLAN) and multi-port inter-switch trunking for use in larger-scale networks. WebSmart™ administrative and configuration capabilities provide network administrators with powerful, easy-to-use tools to reduce unnecessary broadcast traffic, flexibly segment networks, and enhance network security—either by a local cable connection or remotely from any convenient location using a standard web browser.



Model 065-7942

### WebSmart Gigabit Ethernet Switches

PART NO.	DESCRIPTION
065-7932	Gigabit Switch 16-Port 10/100/1000BaseT/TX, WebSmart, 4Combo Ports
065-7942	Gigabit Switch 24-Port 10/100/1000BaseT/TX, WebSmart, 4Combo Ports

### SPECIFICATIONS

#### STANDARDS COMPLIANCE

- IEEE 802.3 10Base-T Ethernet (twisted-pair copper)
- IEEE 802.3u 100Base-T Ethernet (twisted-pair copper)
- IEEE 802.3ab 1000Base-T Ethernet (twisted-pair copper)
- IEEE 802.3z 1000Base-X Ethernet,
- IEEE 802.3x Flow Control capability
- ANSI/IEEE 802.3 Auto-negotiation, IEEE 802.1q VLAN

#### SUBSCRIBER INTERFACE

- 16/24 Gigabit Ethernet ports, Auto-negotiation, Auto-MDIX
- Backpressure flow control for half duplex
- Flow control for full duplex
- Port 13, 14, 15 and 16 are TP/SFP Fiber auto sense Connector: 16/24 RJ45 and 4 SFP module

#### PORT TRUNK

- Port trunking with 8 trunking group, Up to 12 ports for each group

#### BROADCAST STORM

- Broadcast Storm suppression

#### PERFORMANCE

##### Switching capacity:

- 32 Gbps forwarding bandwidth for switch, nonblocking switch fabric

##### Wire Speed Performance:

- 8K MAC addresses, 272 KB on-chip frame buffer, Jumbo frame support

#### VLAN

- Port-base VLAN, IEEE802.1q tag-base VLAN, 4094 Max

#### QOS

- Supports Layer 4 TCP/UDP Port and ToS Classification
- Supports 802.1p QoS with two level priority queue

#### PORT MIRRORING

- All port support port mirroring

#### HW SPECIFICATION

- Power Consumption: 30W max.

- Dimensions (H x W x D): 44 x 442 x 209 mm

- Weight: 2.78 kg

# Gigabit Management Switch

The 065-7840/065-7850 is a L2 managed Gigabit switch that supports SNMP, Web UI and CLI management interface. It is equipped with 24/8 Giga TP ports and 2/16 Giga ports which accommodate optional SFP modules. In addition, the switch implements the QoS (Quality of Service), Mac Filtering Policy, Port Mirror, VLAN and full L2 protocol. It is suitable for workgroups or WAN edge application.



Model 065-7850



Model 065-7840

## Gigabit Management Switch

PART NO.	DESCRIPTION
065-7840	Gigabit Switch 24-Port 10/100/1000BaseT/TX + 2 SFP Slots, L2 Management
065-7850	Gigabit Switch 8-Port 10/100/1000BaseT/TX + 16 SFP Slots, L2 Management

## SPECIFICATIONS

### STANDARDS COMPLIANCE

- IEEE 802.3x Flow Control capability
- IEEE 802.1q VLAN, IEEE 802.1p

### PERFORMANCE

- Switching capacity:**
- 24 Gigabit Ethernet ports with non-blocking wise speed performance
- 8K MAC addresses
- 400 KB on-chip frame buffer
- Supports Jumbo frame support, up to 9K
- Broadcast/Multicast Storm Suppression
- Port Mirroring

### VLAN

- Port-base VLAN;
- IEEE802.1q tag-base VLAN, up to 256 active VLANs
- Q-in-Q is an efficient method for enabling Subscriber Aggregation

### QOS

- Supports Layer 4 TCP/UDP Port and ToS Classification
- Supports 802.1p QoS with two level priority queue
- Supports priority in a Q-in-Q tag

### BANDWIDTH CONTROL

- Supports bandwidth rating per port ingress and egress rate limit 1,000 Mbps with 1 Mbps increments

### PROTOCOL

- LACP, Port trunking with 8 trunking group
- Up to 12 ports for each group, GVRP/GARP
- 802.1q with GVRP/ GARP
- Multicastingppression.ort.el priority queue
- Supports IGMP snooping including active and passive mode
- STP/RSTP, 802.1d/1w/1s STP

### NETWORK SECURITY

- 802.1x access control
- Management Access Policy Control (ACL)
- Snmpv1, v2c Network Management

### HW SPECIFICATION:

- Power Consumption 30W max.
- Dimensions (H x W x D):** 44 x 442 x 209 mm

## Advanced Gigabit L2 Managed Switches

065-7841/065-7851, a 24-Port Gigabit L2 Managed Switches, is a standard switches that meet all IEEE 802.3/u/x/z Gigabit, Fast Ethernet specifications. The switches include 24-Port 10/100/1000 Mbps TP and 4-Port Gigabit TP/SFP Fiber management Ethernet switch. The switch can be managed through RS-232 serial port, or through Ethernet port using CLI or Web-based management unit, associated with SNMP agent. With the SNMP agent, the network administrator can logon the switch to monitor, configure and control each port's activity in a friendly way. The overall network management is enhanced and the network efficiency is also improved to accommodate high bandwidth applications. In addition, the switch features comprehensive and useful functions such as QoS (Quality of Service), Spanning Tree, VLAN, Port Trunking, Bandwidth Control, Port Security, SNMP/RMON, IGMP Snooping capability via the intelligent software. It is suitable for both metro-LAN and office applications.



Model 065-7841

### Advanced Gigabit L2 Management Switches

PART NO.	DESCRIPTION
065-7841	Gigabit Switch 24-Port 10/100/1000BaseT/TX + 4 Combo Slots, Management
065-7851	Gigabit Switch 8-Port 10/100/1000BaseT/TX + 16 SFP Slots, Management

### FEATURES

- 4 Dual Media for Flexible Fiber Connection
- 9KB Jumbo Frame Support
- SSH/SSL/TACACS+/RADIUS for security network management
- Port Mirroring Helps Supervisor Monitoring Network
- Q-in-Q VLAN for performance & security and 4094 Vlan entries
- 802.1x Access Control Improve Network Security
- 802.1D Compatible, 802.1w Rapid Spanning Tree and 802.1s Multiple Spanning Tree
- Unknown Unicast/Broadcast/Multicast Storm Control
- Multicast Vlan Management for IPTV
- IP-Mac-Port binding for LAN security
- Based on Application traffic for QoS and rate limitation management
- DHCP relay agent

### SPECIFICATIONS

#### STANDARDS COMPLIANCE

IEEE 802.3x Flow Control capability  
IEEE 802.1q VLAN, IEEE 802.1p

#### PERFORMANCE

##### Switching capacity:

24 Gigabit Ethernet ports with non-blocking wise speed performance  
8 K MAC addresses, Supports Jumbo frame support, up to 9K  
Unknown Unicast/Broadcast/Multicast Storm Suppression  
Port Mirroring

##### VLAN:

Port-base VLAN  
IEEE802.1q tag-base VLAN, up to 4k active VLANs  
Q-in-Q is an efficient method for enabling Subscriber Aggregation  
Multicast Vlan management

##### VSM (Virtual Stacking Management)

Support 16 devices stacking  
Multiple switches can be managed via one IP address, just like software stacking  
Low cost and easily to establish network environment, not extra hardware require  
Not center on the physical location of wiring closets

#### QOS

Supports Layer 4 TCP/UDP Port and ToS Classification  
Supports 802.1p QoS with two level priority queue  
Supports priority in a Q-in-Q tag

#### BANDWIDTH CONTROL

Supports bandwidth rating per port ingress and egress  
rate limit 1000 Mbps with 1 Mbps

#### PROTOCOL

**LACP:** Port trunking with 12 trunking group up to 16 ports for each group

**GVRP/GARP:** 802.1q with GVRP/ GARP

**Multicasting:** Supports IGMP snooping including active and passive mode

**STP/RSTP/MSTP:** 802.1d/1w/1s

#### NETWORK SECURITY

802.1x access control for port based and mac based authentication  
Management Access Policy Control, Access control List, IP-mac-port binding, DHCP relay agent

# 24-Port 10/100BaseT/TX + 4G Combo L3 Switch

The Signamax L3 Switch is a high performance managed SNMP Layer 3 switch that provides users with 24 x 10/100 Mbps Ethernet and 4 Gigabit Combo ports. The Web/SNMP management provides remote control capability that gives flexible network management and monitoring options. Whether managed through “n-band” SNMP management station, internet web browser, or through “out-of-band” RS-232 console port, the 065-7428 facilitates network operational control and diagnosis.

For increased bandwidth application, 065-7428 can accommodate up to 32 trunk groups with LACP link aggregation. Moreover, these trunk ports are with fair-over function to provide redundant back up if one or more of ports are malfunctioning. It also supports both 802.1Q VLAN and GVRP VLAN Registration thereby simplifying network traffic segmentation, broadcast domain extension and other associated benefits of constructing VLANs. The abundance of features translates into increased efficiency and performance in network administration.



Model 065-7428

## SPECIFICATIONS

### STANDARDS

IEEE 802.3 10Base-T,  
 IEEE 802.3u 100Base-TX,  
 IEEE802.3ab 1000Base-T,  
 IEEE802.3z 1000Base-X

### MEDIA

UTP CAT3 or up for copper port,  
 Single-mode or Multi-mode fiber  
 (with SFP connect) for fiber port

### CHIP

BCM5650+BCM5248+  
 BCM5464S+IXP420

### ACCESS METHOD

CSMA/CD

**MAC Address:** 16K

**Built-in Buffer:** 256 Mbits

**Data Transfer Rate:**

10/100Mbps (Half-duplex),  
 20/200/2000 Mbps  
 (Full-duplex for copper port),  
 2000 Mbps only for fiber port

### LEDs

Power, Link/Activity

### ENVIRONMENTAL

#### TEMPERATURE HUMIDITY

**Dimension (LxWxH):**

438 x 250 x 44 mm

**Weight:** 5,000 g

**Temperature:**

0° to 50°C (operating),

-20° to 70°C (storage)

**Humidity:**

5 to 90% non-condensing (operating),

5 to 90% non-condensing (storage)

### CERTIFICATIONS

FCC Part 15 Class A, CE Mark

## FEATURES

- Compliant with the IEEE802.3 10Base-T Ethernet, IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X specifications
- 24 port 10/100 Mbps TX Auto-Negotiation and 4 port 10/100/1000 Mbps TX and 4 1000 Mbps SFP port (shared with 10/100/1000M port)
- Supports TP interface Auto MDIX function for auto TX/RX swap
- Support up to 16K MAC address, 16K IPv4 routing table
- Up to 256M bits packet buffer
- Supports Store & Forward architecture and performs forwarding and filtering
- Supports Jumbo frame up to 9 KB
- Support RIP1/RIP2 routing
- Support OSPF routing
- VLAN 802.1q tag VLAN (up to 4K group)
- Support rate control (64 Kbps – 100 Mbps for Fast Ethernet port and 64 Kbps – 1,000 Mbps for Gigabits port )
- Support port mirror
- Support IEEE802.1D Spanning Tree and IEEE802.1w RSTP protocol
- Support Layer2-Layer7 packet classification and filtering at line rate
- Supports SNMP V1/V2, RMON MIB (group 1, 2, 3, 9)
- Supports access switch through Web/Telnet/Console
- Supports firmware upgrade through Web/Console
- Build-in power

### 24-Port 10/100BaseT/TX + 4G Combo L3 Switch

PART NO.	DESCRIPTION
065-7428	L3 Managed 24-Port + 4G Combo Switch
065-7429	Advanced L3 Managed 24-Port 10/100BaseT/TX + 4G Combo Switch

## Hardened Ethernet Switches

The Signamax Hardened series compact Fast Ethernet Switches are equipped with 5-Port 10/100Base-TX or 4-Port 10/100Base-TX plus 1-Port 100Base-FX. By using standard auto-negotiation and the inclusion of auto-MDIX, Signamax provides a cost-effective way of integrating legacy 10 Mbps networks with 100 Mbps Fast Ethernet networks. The TX ports auto-negotiate for 10/100 Mbps speed and auto-detect Full or Half-duplex mode. The fiber port accommodates SC and ST with a fiber connection between two nodes that can reach up to 120 Km (74.4 miles). The Signamax hardened switch series can be DIN-Rail mounted and is equipped with Terminal Block power input to match the applications that require an Ethernet Switch.



Model 065-7405



Model 065-7408



Model 065-74081

### Hardened Ethernet Switches

PART NO.	DESCRIPTION
065-7405	Hardened Unmanaged Switch with 5-Port 10/100BaseT/TX
065-74051	Hardened Unmanaged Switch with 4-Port 10/100BaseT/TX + 1-Port 100BaseFX SC, MM
065-74052	Hardened Unmanaged Switch with 4-Port 10/100BaseT/TX + 1-Port 100BaseFX SC, SM
065-7401	Hardened Unmanaged Switch with 1-Port 10/100BaseT/TX + 1-Port 100BaseFX SC, MM
065-7402	Hardened Unmanaged Switch with 1-Port 10/100BaseT/TX + 1-Port 100BaseFX SC, SM
065-7408	Hardened Unmanaged Switch with 8-Port 10/100BaseT/TX
065-74081	Hardened Unmanaged Switch with 8-Port 10/100BaseT/TX + 1-Port 100BaseFX SC, MM
065-74082	Hardened Unmanaged Switch with 6-Port 10/100BaseT/TX + 2-Port 100BaseFX SC, MM
065-74084	Hardened Unmanaged Switch with 4-Port 10/100BaseT/TX + 4-Port 100BaseFX SC, MM

### SPECIFICATIONS

#### STANDARD

IEEE802.3 10Base-T, IEEE802.3u 100Base-TX/100Base-FX  
IEEE802.3x

#### PERFORMANCE

##### Forward and Filtering Rate:

14,880 pps for 10 Mbps  
148,810 pps for 100 Mbps

**Packet Buffer Memory:** 384 Kbits

##### Processing Type:

Store-and-Forward  
Half-duplex back-pressure and IEEE802.3x full-duplex flow control

**Address Table Size:** 2,048 MAC addresses

**Latency:** Less than 5.1 µs

#### LEDs

Per Unit: Power Status (Power 1, Power 2)

Per Port: 10/100TX, 100FX: Link/Activity (Green), Speed (Yellow)

#### PHYSICAL CHARACTERISTICS

##### Power Input:

**Input Voltage:** 12 to 48V DC (Terminal Block)

**Input Current:** 0.1A Max. (Terminal Block)

**Power Consumption:** 2.4W Max.

**Reverse Polarity Protection:** Present

**Mechanical Casing:** Plastic case

**Dimensions (W x D H):** 25 x 70 x 110 mm

**Weight:** 0.2 Kg

**Installation:** DIN-Rail Mounting

**Environment Operating Temperature:** -10° – 60 °C

**Storage Temperature:** -25° – 85°C

**Ambient Relative Humidity:** 10-95% (non-condensing)

#### REGULATORY APPROVALS EMISSION COMPLIANCE:

FCC Part 15, Class A, CE

#### SAFETY

UL 60950

# Hardened Managed Switches

The 065-741xx series, managed, Ethernet switches are designed to operate in the harsh environments at the edge of the network. Whether on the factory floor or the street corner, the 065-741xx will provide flawless communications when you need it most. The 065-741xx is a managed switch with the flexibility of eight 10/100 Ethernet ports that may be configured in various combinations of copper and fiber optic interfaces.

To increase its flexibility a 9th port may be added that is a Gigabit Ethernet interface, configured with copper or fiber optics. Flexibility is a main feature of the 065-741xx series product and it will fit any application that requires a tough, environmentally hardened Ethernet switch.

## FEATURES

- 4 Dual Media for Flexible Fiber Connection
- 9KB Jumbo Frame Support
- SSH/SSL/TACACS+/RADIUS for security network management
- Q-in-Q VLAN for performance & security and 4094 Vlan entries
- DHCP relay agent
- Multicast Vlan Management for IPTV
- IP-Mac-Port binding for LAN security
- 802.1x Access Control Improve Network Security
- 802.1D Compatible, 802.1w Rapid Spanning Tree and 802.1s Multiple Spanning Tree
- Unknown Unicast/Broadcast/Multicast Storm Control
- Port Mirroring Helps Supervisor Monitoring Network
- Based on Application traffic for QoS and rate limitation management



Model 065-7418

## Hardened Managed Switches

PART NO.	DESCRIPTION
065-7418	Hardened Managed Switch with 8-Port 10/100BaseT/TX
065-74181	Hardened Managed Switch with 8-Port 10/100BaseT/TX + 1-Port 100BaseFX
065-74182	Hardened Managed Switch with 6-Port 10/100BaseT/TX + 2-Port 100BaseFX
065-74184	Hardened Managed Switch with 4-Port 10/100BaseT/TX + 4-Port 100BaseFX
065-74185	Hardened Managed Switch with 8-Port 10/100BaseT/TX + 1-Port 10/100/1000BaseTX
065-74186	Hardened Managed Switch with 8-Port 10/100BaseT/TX + 1-Port 1000BaseSX
065-74187	Hardened Managed Switch with 8-Port 10/100BaseT/TX + 1-Port 1000BaseLX – 10 Km
065-74187ED	Hardened Managed Switch with 8-Port 10/100BaseT/TX + 1-Port 1000BaseLX – 20 Km

## SPECIFICATIONS

### STANDARD

IEEE802.3 10Base-T, IEEE802.3u 100Base-TX/100Base-FX,  
IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-SX/1000Base-LX,  
IEEE802.3x, IEEE802.1Q, IEEE802.1p, IEEE802.1w

### PERFORMANCE

**Protocols:** IGMP, GVRP, SNMP V1/V2, RMON, TFTP

#### Forward and Filtering Rate:

14,880 pps for 10 Mbps  
148,810 pps for 100 Mbps  
1,488,100 pps for 1,000 Mbps

**Packet Buffer Memory:** 256 Kbits

**Processing Type:** Store-and-Forward

Half-duplex back-pressure and IEEE802.3x full-duplex flow control

**Address Table Size:** 4KMAC addresses

**Latency:** Less than 9.6  $\mu$ s

### LEDs

Per Unit: Power Status (Power 1, Power 2)

Per Port: 10/100TX, 100FX: Link/Activity (Green), Speed (Yellow)

10/100/1000TX, 1000SX/LX: Link (Green), Activity (Yellow)

### PHYSICAL CHARACTERISTICS

#### Power Input:

Input Voltage: 12V DC (Power Jack); 10 to 30V DC (Terminal Block)  
Input Current: 2A Max

**Power Consumption:** 12V DC@1.48A, 24V DC@0.77A, 18.48W Max.

**Reverse Polarity Protection:** Present

**Mechanical Casing:** Aluminumcase

**Dimensions (W x D x H):** 50 x 125 x 135 mm

**Weight:** 0.8 Kg

**Installation:** DIN-Rail, Panel, Rack Mounting

**Environment Operating Temperature:** -34° – 74 °C

**Storage Temperature:** -40° – 85°C

**Ambient Relative Humidity:** 10-95% (non-condensing)

### REGULATORY APPROVALS EMISSION COMPLIANCE:

FCC Part 15, Class A

### SAFETY

UL 60950, EN 60950, IEC 60950, IEC 61000-6-2

## 4-Port Broadband Access Router

The Signamax 065-1507 Broadband Access Router is an intelligent solution for sharing Cable Modem or DSL services between home computers, small office computers, or branch office installation. The built-in 4-Port switch facilitates file sharing at either 10 Mbps or 100 Mbps, automatically determining the fastest possible connection speed and duplex mod. It also provides print server capabilities as well, to allow printer sharing between users without requiring a particular computer to be left on at all times. The 065-1507 Broadband Router incorporates a hardware-based firewall, securing your PCs from unwanted outside users breaking into your files and possibly using your PCs for illegal purposes.



Model 065-1507



Model 065-1507

### 4-Port Broadband Access Router

PART NO.	DESCRIPTION
065-1507	4-Port Broadband Access Router w. USB printer port

### FEATURES

- Allows multiple PCs to share one Internet connection
- Built-in firewall to protect your computers
- Integrated 4-Port 10/100BaseT/TX auto-sensing Fast Ethernet LAN switch
- WAN Port
- Built-in print server
- Web browser-based configuration and management
- DHCP Server
- Dynamic DNS
- Virtual Server
- Port Filter

### SPECIFICATIONS

#### PORTS:

- 4x RJ45 10/100BaseT/TX Local Area Network (LAN) ports
- 1x RJ45 10/100BaseT/TX Wide Area Network (WAN) port
- 1x DB-25 female parallel printer port
- 1x Serial Port

#### SUPPORTED PLATFORMS:

- Win95/98/NT/2000XP; Unix LPR
- Web-based configuration and management
- Power, 10/100, System Status, LAN Link/Activity, WAN Link/Activity
- External AC Power Supply
- Desktop and wall mounting
- Power supply UL & cUL listed
- FCC Part 15 Class B, CE Mark B, VCCI-B

# Signamax USB NAS

Signamax 065-1520 USB NAS can quickly and easily connect USB 2.0 hard drives. Add Gigabytes of storage to your existing LAN. You can connect up to 4 additional hard drives to provide over 1 Terabyte of shared storage for your networked computers, Windows, Mac and Unix. A great tool to use for sharing music and photo files or backup of network PC's and/or file servers.



Model 065-1520



## Signamax USB NAS

PART NO.	DESCRIPTION
065-1520	Signamax USB NAS

## SPECIFICATIONS

### HARDWARE

- Supported Standards: USB 1.1/2.0, IEEE 802.3, IEEE 802.3u
- Ports: 1-Port RJ45 10/100 Ethernet  
4-Ports USB 2.0
- Buttons: Power, Configuration Reset
- Cabling Type: Category 5 Ethernet
- LED's: Power, Ethernet Link USB1, USB2, USB3, USB4
- Dimensions: 85 x 155 x 25 mm
- Unit Weight: 350 g
- Power Input: External, 5V DC, 2A
- Certifications: FCC, CE
- Operating Temp: 5° – 40°C
- Storage Temp: -10° – 60°C

### SOFTWARE

- Linux Operating System
- User-friendly Web Based Interface
- Finder App to discover any number of 065-1520 devices
- Merges with existing Windows Workgroups
- DHCP client or fixed IP address
- File Sharing: FTP, SMB
- Printer Sharing
- Support for Windows
- Access Control List
- File System: FAT12/16/32, NTFS (read only)
- Support Multi Partition of Mass Storage
- Plug-in & Play hard drives—no need to power off to remove\*

\* Drives should be de-activated through the Web Based Interface to ensure no data loss.

## SFP Fiber Modules

The 065-77SM is a high performance and cost-effective module for serial optical data communication applications specified for single-mode of 1.25 Gbps. It operates with + 3.3V power supply. The module is intended for single-mode fiber, operates at a nominal wavelength of 1,310 nm and complies with Multi-source Agreement (MSA) Small Form Factor Pluggable (SFP).

Each module consists of a transmitter optical subassembly, a receiver optical subassembly and an electrical subassembly. All of them are housed in a metal package and the combination produces a reliable component.

This module is a duplex LC connector transceiver designed for use in Gigabit Ethernet applications and to provide IEEE-802.3z compliant link for 1.25 Gbps intermediate reach applications.

The 065-77SM transceivers use a intermediate wavelength (1,310 nm) FP laser diode to enable data transmissions of up to 10km on a single mode optical fiber.




Model 065-77SM



Model 065-77FESM



Model 065-77AMM



Model 065-77RJ

### SFP Fiber Modules

PART NO.	DESCRIPTION
065-77MM	SFP Fiber Module, Connector LC Multi Mode
065-77SM	SFP Fiber Module, Connector LC Single Mode
065-77AMM	SFP Fiber Module, Connector LC Multi Mode, Signamax Compatible
065-77ASM	SFP Fiber Module, Connector LC Single Mode, Signamax Compatible
065-77MAN	SFP Transceiver, RoHS Compliant 1.25 Gbps Managed, 1,310 nm, FP Laser
065-77RJ	SFP Transceiver, RoHS Compliant 1.25 Gbps 1000Base-T, RJ-45 Connector
065-77FEMM	SFP Transceiver, RoHS Compliant 100 Mbps Multi Mode, 1,310 nm, LED
065-77FESM	SFP Transceiver, RoHS Compliant 100 Mbps Single Mode, 1,310 nm, FP Laser
065-77WDMA	SFP Fiber Module Connector LC Single Mode WDM, Rx = 1,550, Tx = 1,310
065-77WDMB	SFP Fiber Module Connector LC Single Mode WDM, Tx = 1,550, Rx = 1,310
065-77CWDM1470	SFP Fiber Module LC Singlemode CWDM, 1.25 Gbps, 3.3V, 1,470 nm, 10 km
065-77CWDM1490	SFP Fiber Module LC Singlemode CWDM, 1.25 Gbps, 3.3V, 1,490 nm, 10 km
065-77CWDM1510	SFP Fiber Module LC Singlemode CWDM, 1.25 Gbps, 3.3V, 1,510 nm, 10 km
065-77CWDM1530	SFP Fiber Module LC Singlemode CWDM, 1.25 Gbps, 3.3V, 1,530 nm, 10 km
065-77CWDM1550	SFP Fiber Module LC Singlemode CWDM, 1.25 Gbps, 3.3V, 1,550 nm, 10 km
065-77CWDM1570	SFP Fiber Module LC Singlemode CWDM, 1.25 Gbps, 3.3V, 1,570 nm, 10 km
065-77CWDM1590	SFP Fiber Module LC Singlemode CWDM, 1.25 Gbps, 3.3V, 1,590 nm, 10 km
065-77CWDM1610	SFP Fiber Module LC Singlemode CWDM, 1.25 Gbps, 3.3V, 1,610 nm, 10 km

# 10 Gbps Modules

10 Gbps XENPAK transceiver module 065-10GMM is a hot pluggable module in the Z-direction that is usable in typical router line card applications, Storage, IP network and LAN and compliant to XENPAK MSA. The maximum transmission length of 065-10GMM is defined from 26m to 300m, depending on Multi Mode fiber types.

The 065-10GMM is a fully integrated 10.3 Gbit/s optical transceiver module that consists of a 850 nm wavelength VCSEL optical transmitter and receiver, XAUI interface, Mux and Demux with clock and data recovery (CDR).

Mechanical dimensions, connectors and footprint of 065-10GMM conform to XENPAK MSA. The module size is 4.76 x 1.42 x 0.46" with 70-pin electrical connector. The maximum power consumption is 4.0 W and power supply voltages are +3.3 V and +1.8 V.

## 10 Gbps Modules

PART NO.	DESCRIPTION
065-10GMM	10 Gbps module, 850 nm SC, 300 m
065-10GSM	10 Gbps module, 1,310 nm SC, 10 km
065-10GSMED	10 Gbps module, 1,550 nm SC, 40 km
065-10GBSMXLD	10 Gbps module, 1,550 nm SC, 80 km

## SPECIFICATIONS

### 065-10GMM

- 10 Gbps (10.3125 Gbit/s) Transceiver
- Compliant to IEEE 802.3ae 10GBASE-SR Application
- XAUI Electrical Interface: 4 Lanes @ 3.125 Gbit/s
- Hot Z-Pluggable
- SC-Duplex Optical Receptacle
- MDIO, DOM Support
- 850 nm wavelength VCSEL for Optical light source
- PIN Photo-detector
- Up to 300 m reach over 50/125 µm MMF with Minimum modal bandwidth @ 850 nm of 2,000 MHz
- Operating Case Temperature: -5° to 70°C
- Compliant to XENPAK MSA
- Mechanical Footprint (L x W x H): 4.76 x 1.42 x 0.46"

### 065-10GSM

- XAUI Electrical Interface: 4 Lanes @ 3.125 Gbit/s
- Hot Z-Pluggable
- SC-Duplex Optical Receptacle
- MDIO, DOM Support
- Uncooled 1.3 m DFB-LD
- PIN Photo-detector
- Operating Case Temperature: 0° to 70°C
- Compliant to IEEE 802.3ae 10GBASE-LR Application
- Compliant to XENPAK MSA
- Mechanical Footprint (L x W x H): 4.76 x 1.42 x 0.46"


### 065-10GBSMXLD

- 80 km Transmission Distance
- [TRE7062ENabcSW] 100 GHz DWDM application
- Cooled 1550-nm EA-DFB Transmitter and APD Receiver
- XAUI Electrical Interface: 4 Lanes @ 3.125 Gbit/s
- Comply with XENPAK MSA for ER application with expansion to 80 km
- Hot Pluggable
- SC-Duplex Optical Receptacle
- MDIO, DOM Support
- Operating Case Temperature: 0° to 70°C
- Mechanical Footprint (L x W x H): 4.76 x 1.42 x 0.46"

### 065-10GSMED

- XAUI Electrical Interface: 4 Lanes @ 3.125 Gbit/s
- Hot Z-Pluggable
- SC-Duplex Optical Receptacle
- MDIO, DOM Support
- 1.55 m laser
- PIN Photo-detector
- Operating Case Temperature: 0° to 70°C
- Compliant to IEEE 802.3ae 10GBASE-ER
- Compliant to XENPAK MSA

# NETWORK CONNECTIVITY SYSTEMS





# Network Interface Cards



**Gigabit Ethernet PCI Adapter Cards**

**Fast Ethernet PCI Adapter Cards**


# Gigabit Ethernet PCI Adapter Card

Signamax Connectivity Systems' Gigabit network adapter cards are used wherever it is necessary to provide Gigabit Ethernet capability directly into a server or workstation. These cards utilize the new high-speed 64/32-bit PCI Bus Mastering architecture and support IEEE 802.1p Quality of Service (QoS) and 802.1Q VLAN Tagging standards for complete network optimization.

The model 098-1122 twisted-pair LAN card supports the IEEE 802.3ab 1000BaseT specification in a Category 5E or better cabling system, using a standard RJ-45 jack. This card also supports 10BaseT and 100BaseTX transmission, allowing its use in networks evolving to Gigabit Ethernet.



Model 098-2000SX



Model 098-1122

## Gigabit Ethernet PCI Adapter Card

PART NO.	DESCRIPTION
098-1122	10/100/1000BaseT/TX PCI Network Adapter Card
098-2000SX	1000BaseSX – SC Multi Mode

## FEATURES

- Support Auto-negotiation function
- Auto-setups IRQ and I/O address
- Supports Virtual LAN (VLAN) and long frame (1,536 Bytes)
- Supports 802.1D and 802.1Q priority queuing
- IPv.4 checksum task off-loading
- Supports MDIX at 10; 100; 1,000 Mb/s
- Supports Jumbo packets (9K)
- Supports 64/32 bit, 66/33 MHz PCI Bus Master for high performance
- Full duplex design to double the performance to 20/200/2,000 Mbps
- One STP connector for 1,000 Mbps, 100 Mbps or 10 Mbps network speed
- Net System: NDIS 4,5 driver for Microsoft Windows 95/98, Win2000, Me, Netware driver for Server V.4/5, UNIX, Linux
- Compliant with PC 97 and PC 98 Hardware Design Guides, PC 99 Hardware Design Guide draft. ACPI v1.0, PCI Power Management Specification v1, OnNow Device Class Power Management Reference Specification—Network Device Class v1.0a
- Wake on LAN (WOL) support compliant with PC98, PC99, and OnNow, including directed packets, Magic Packet TM, ARP packets, pattern mach packets, and Phy status change

## SPECIFICATIONS

### STANDARD COMPLIANCE

IEEE 802.3 10BASE-T  
IEEE 802.3u 100BASE-TX  
IEEE 802.3ab 1000BASE-T

### ARCHITECTURE

PCI 2.1/2.2 (6/33 MHz)  
32 bit & 64 bit

### CONNECTOR: RJ-45

### TRANSMISSION RATE

10/100/1,000 Mbps

### TOPOLOGY: Star

### PROTOCOL: CSMA/CD

### NETWORK TRANSMISSION

#### MEDIA

10BASE-T Cat. 3, 4, 5 UTP/STP  
100BASE-TX Cat. 3, 4, 5  
UTP/STP  
1000ASE-TX Cat. 5, 6 UTP/STP

#### LED

100 Mb LINK/ACT, 1 Gb  
LINK/ACT

### PHYSICAL CHARACTERISTICS

#### Power Consumption:

7 Watts (Max)

Weight: 0.095 kg

Operating Temperature:

0° – 55°C

Store Temperature: -20° – 70°C

Dimension: 122.2 x 42.9 mm

Humidity:

10-90% (Non-condensing)


### SAFETY & EMI CERTIFICATES

CE & FCC-B


# Fast Ethernet PCI Adapter Cards

098-1111, the most cost-effective solution for end users, is equipped with Auto-negotiation function. Auto-negotiation function has become the basic requirement of network adapters. It automatically supports data transmission speeds ranging from 10 Mbps to 200 Mbps. This function smoothly and automatically switches drivers between 10 Mbps and 100 Mbps, Full- or Half-duplex, LAN connections.

Furthermore, an optional Boot ROM socket is provided to allow administrators to boot diskless computers from remote servers. This function is most frequently used for schools, libraries or other public buildings. 098-1111 runs in 32-bit PCI bus master mode. It is compliant with industrial standards and its drivers support all major operating systems.



Model 098-1111



Model 098-1100FSCR



Model 098-1100FSCR

## SPECIFICATIONS

### STANDARDS

IEEE 802.3u: 100BASE-TX  
IEEE 802.3: 10BASE-T

### BUS TYPE

PCI specification revision 2.1, 2.2

### NETWORK INTERFACE

One shielded RJ45 phone-type jack

### NETWORK MODES SUPPORTED

10BASE-T: CAT 3, 4, and 5 TP  
100BASE-TX: CAT 5 TP cable  
Full-duplex available in both modes

### LEDs

LINK (Green), TX/RX (Green)

### BOOT ROM (OPTIONAL)

64K Bytes with optional on-board  
Boot ROM socket

### DIMENSIONS

120 x 42 mm / 4.72 x 1.65 inches)

### ENVIRONMENT

Operating Temperature: 0° – 55°C  
Storage Temperature: -20° – 70°C  
Humidity: 10-90% Non-condensing

### SOFTWARE SUPPORT

Windows 95/98/ME/ NT/2000/XP  
Netware 3.x, 4.x, 5.x. Client 32,  
NDIS 2.0 Drivers, Packet Driver, Linux,  
SCO UNIX, Free BSD, DOS ODI

## FEATURES

- Sturdy Single Chip Design Enhances Reliability and Ensures Robust Running Usability
- Auto-negotiation Automatically Switches between 10/100 Mbps and Full-/Half-duplex Modes
- Equipped with one optional Boot ROM Socket to Boot Diskless Computers Remotely
- Fully Comply with IEEE 802.3u and IEEE 802.3 Standards
- Support IEEE 802.3x Flow-control for Full-duplex
- Shielded RJ45 Connector Provides Unified 100BASE-TX and 10BASE-T Network Media Interface
- Comply with PCI specification 2.1, 2.2
- Support ACPI, and PCI-Bus Power Management
- Compliant to PC99 and PC2001 Standards

## Fast Ethernet PCI Adapter Cards


PART NO.	DESCRIPTION
098-1100FSCR	100BaseFX PCI Network Adapter Card – SC Multi Mode
098-1111	10/100 Mbps Fast Ethernet PCI adapter, RJ-45 STP
098-1100FSMR	100BaseFX PCI Network Adapter Card – SC Single Mode

# NETWORK CONNECTIVITY SYSTEMS





## KVM Switches



**2-Port USB KVM Switch**

**4-Port Slim Desktop Switch**

**8- and 16-Port Rackmount  
KVM Switches**

**KVM Hydra Cables**

**VGA Splitter**

## 2-Port USB KVM Switch

The 098-8026 Slim Palmtop USB KVM Switch is a 2-Port compact KVM Switch with Audio and Mic switching function. Its USB support on the console side allows you to use USB keyboard and mouse. It comes with 2 sets of detachable USB KVM combo cables & 2 sets of Audio/Mic cables for SOHO and office desktop multimedia application. And it allows you to access, control, boot and reboot two USB-enabled multimedia computers with only one USB keyboard, mouse, monitor and optional speaker set and microphone, using the Switching Software Client installed on your PCs.

USB interface compatibility for multi-platform support

The USB interface technology offers multi-platform support for PC, Macintosh G3/G4 and iMAC. The KVM Switching Software client supports Windows/Mac platforms.



Model 098-8026



Model 098-8026

### SPECIFICATIONS

#### CABLES

- 2 x detachable USB KVM Combo Cable
- 2 x Audio/Mic Cables (USB Mini B-3.5 mm jack)

#### PC PORT CONNECTORS

- 2 x USB Type A
- 2 x audio/mic connector [USB Mini B]

#### CONSOLE PORT CONNECTORS

- 2 x USB Type A (Keyboard & Mouse)
- 1 x HDB 15-pin female
- 1 x 3.5 mm audio jack
- 1 x 3.5 mm mic jack

#### PC selection:

- Push button
- Hotkeys
- Switching Software (for Windows/Mac)

#### PC port LED: 2

VGA Resolution: 2,048 x 1,536

Power Type: USB interface power

Dimension (L x W x H): 96 x 61 x 24 mm

Size: Slim Palmtop

Housing: Plastic

#### SAFETY / EMISSION

FCC, CE

### SPECIAL FEATURES

- 2-Port Slim Palmtop KVM Switch with Audio&Mic and 2 x detachable USB KVM & 2 x Audio/Mic Cables
- USB console support for USB keyboard and mouse
- Audio and Microphone switching for uninterrupted multimedia experience across multi-platforms
- USB 1.1 Specification compliant
- Independent/simultaneous switching of both PC and audio/mic channel
- Multi-platform support for PCs and Macintosh G3/G4 MAC, iMAC
- Hot-plugging PCs for maintenance without powering down the KVM Switch or PCs
- Switching Software client for easy software switching on Windows and Mac platform
- User definable hotkeys
- Additional universal port switching hotkey—ScrollLock + ScrollLock—for non-Windows OS on PC platform
- Channel selection by push button, keyboard hotkeys and Switching Software Client (for Windows/Mac)
- LED indicators for easy status monitoring
- High VGA resolution 2,048 x 1,536
- USB interface power

### 2-Port USB KVM Switch

PART NO.	DESCRIPTION
098-8026	Slim Palmtop USB KVM Switch w/ Audio & Mic

# 4-Port Slim Desktop Switch

4-Port Slim Desktop PS/2 KVM Switch with Audio&Mic for SOHO and office multimedia applications. The 098-8040 Slim Desktop PS/2 KVM Switch provides Audio and Microphone switching function for SOHO and office desktop multimedia application. And it allows you to access, control, boot and reboot four PS/2-enabled multimedia computers using only one keyboard, video, mouse and optional speaker set and microphone.

Audio and Microphone Switching offers uninterrupted multimedia experience

The audio and microphone switching function of 098-8040 allows you to leverage the multimedia systems on each of your four computers. You can monitor the audio/mic input/output of each computer without plugging on and off the audio/mic cables. And it takes only one set of speaker and microphone instead of one set for each computer. Furthermore, it offers you user-programmable simultaneous/independent PC and audio/mic switching function for flexible multimedia and KVM Switching operation.

Zero Cabling Hassles for KVM users

This KVM Switch saves you cabling troubles with its 4 x 1.2 M detachable KVM and 4 x audio/mic cables. In fact, you have zero cabling troubles since you don't have to worry about finding suitable cables to fit—They comes within the box package!



Model 098-8040



Model 098-8040



Model 098-8040

## SPECIFICATIONS

**PC Connections:** 4

**Console Connections:** 1

### PC PORT CONNECTORS

- 4 x HDB 15-pin female (integrated with PS/2 interface)
- 4 x 3.5 mm audio in/out jack
- 4 x 3.5 mm mic in/out jack

### CONSOLE PORT CONNECTORS

- 1 x PS/2 Keyboard 6-pin Mini Din female
- 1 x PS/2 Mouse 6 pin Mini Din female
- 1 x HDB 15-pin female
- 1 x 3.5 mm audio in/out jack
- 1 x 3.5 mm mic in/out jack

### PC/Audio/Mic selection:

Push buttons/Hotkeys

**PC port LED:** 4 (Green)

**Keyboard/Mouse conversion:** PS/2

**VGA Resolution:** 2,048 x 1,536

**Power Type:** PS/2 interface power

**Dimension (L x W x H):**

164 x 72 x 26 mm

**Size:** Slim Palmtop

**Housing:** Plastic

**SAFETY / EMISSION**

FCC, CE

## SPECIAL FEATURES

- 4-Port Slim Desktop PS/2 KVM switch with audio&mic
- Audio and microphone switching for uninterrupted multimedia experience across multi-platforms
- Simultaneous/independent PC and Audio/Mic Switching (User-programmable)
- Hot-plugging PCs for maintenance without powering down the KVM Switch or PCs
- Channel selection by keyboard hotkeys and face-panel push buttons
- Autoscans delay time programmable
- Separate LED indicators for PC port and audio channel status monitoring
- High VGA resolution 2,048 x 1,536
- PS/2 interface power

## 4-Port Slim Desktop Switch

PART NO.	DESCRIPTION
098-8040	4-Port Slim Desktop PS/2 KVM Switch w/ Audio & Mic

## 8- and 16-Port Rackmount KVM Switches

The 098-8280/098-82160 are 8- and 16-Port cascadable 19" Rackmount KVM Switches with OSD. They are designed to provide robust and reliable KVM switching performance under harsh and critical environment either in corporate office or on industrial floor.

OSD Menu offers more intuitive and convenient control. The full-feature OSD gives an intuitive menu-driven operation most users will find dispensable for a truly convenient experience.

Port-capacity scalable up to two hundred more computers via daisy-chaining multiple KVM Switch units. Multiple units 098-8280/098-82160 could also be daisy-chained up to 16 levels and provide a total port capacity of up to two hundred more of PCs (depending on the unit combinations).

Centralized Rackmount Management.

The rackmount design offers a neat placement of the KVM Switches units on the rack for centralized management and also for security enhancement that could be provided by a locked server room.



Model 098-82160

### FEATURES

- 8- and 16-Port Cascadable 19" Rackmount KVM switch with OSD
- Cascadable up to 16 levels using daisy-chain cable
- Port capacity scalable up to 248/256 PCs with multiple units in daisy-chained configuration
- PS/2 style keyboard and mouse control
- Support Microsoft IntelliMouse®, IntelliMouse Explorer®, Logitech NetMouse® and other compatibles
- Channel selection and operation using front-panel push buttons, keyboard hotkeys and OSD Menu
- Support for DOS, Windows 95/98/SE/ME/2000/XP, Linux, etc.
- Dual numerical LED displays and LED indicators for easy port status monitoring
- Buzzer sound for port switching confirmation
- Autoscan mode for quick browsing of all connected computers
- Autoscan delay time programmable from 5 – 99" through OSD menu option
- Search PC by name
- Password protection
- High VGA resolution 2,048 x 1,536
- Video Bandwidth 250 MHz
- 19" rack mount design with metal enclosure for best shielding and protection

### 8- and 16-Port Rackmount KVM Switches

PART NO.	DESCRIPTION
098-8280	8-Port 19" Rackmount KVM Switch w/ Front-panel Buttons, Keyboard Hotkeys and OSD Control
098-82160	16-Port 19" Rackmount KVM Switch w/ Front-panel Buttons, Keyboard Hotkeys and OSD Control

## SPECIFICATIONS

### Model 098-8280

**PC Ports:** 8

**Console Port:** 1

**Daisy-chain port:** 1

**Daisy-chain level:** Up to 16 levels

**Max. PC Connection:** 248 PCs ( 1 x 098-8280 + 15 x 098-82160)

#### PC PORT CONNECTORS

8 x PS/2 Keyboard 6-pin Mini Din female

8 x PS/2 Mouse 6 pin Mini Din female

8 x VGA HDB 15-pin Female

#### CONSOLE PORT CONNECTORS

1 x PS/2 Keyboard 6-pin Mini Din female

1 x PS/2 Mouse 6 pin Mini Din female

1 x VGA HDB 15 pin female

**OSD:** Yes

**PC selection:** Push buttons / Hotkeys / OSD

**PC port LEDs:** 16

**Scan delay time:** 5 – 99 sec. programmable through OSD menu option

**VGA Resolution:** 2,048 x 1,536

**Video Bandwidth:** 250 MHz

**Humidity:** 0-90% RH, non-condensing

**Size:** Standard 19" rack mount

**Housing:** Metal enclosure

**Dimension (L x W x H):** 410 x 165 x 44.5 mm

**Power:** DC 9V 1A (required)

**Weight:** 2,200 g

#### SAFETY / EMISSION

FCC, CE

### Model 098-82160

**PC Ports:** 16

**Console Port:** 1

**Daisy-chain port:** 1

**Daisy-chain level:** Up to 16 levels

**Max. PC Connection:** 256 PCs (16 x 098-82160)

#### PC PORT CONNECTORS

16 x PS/2 Keyboard 6-pin Mini Din female

16 x PS/2 Mouse 6 pin Mini Din female

16 x VGA HDB 15-pin Female

#### CONSOLE PORT CONNECTORS

1 x PS/2 Keyboard 6-pin Mini Din female

1 x PS/2 Mouse 6 pin Mini Din female

1 x VGA HDB 15 pin female

**OSD:** Yes

**PC selection:** Push buttons / Hotkeys / OSD

**PC port LEDs:** 32

**Scan delay time:** 5 – 99 sec. programmable through OSD menu option

**VGA Resolution:** 2,048 x 1,536

**Video Bandwidth:** 250 MHz

**Humidity:** 0-90% RH, non-condensing

**Size:** Standard 19" rack mount

**Housing:** Metal enclosure

**Dimension (L x W x H):** 410 x 165 x 44.5 mm

**Power:** DC 9V 1A (required)

**Weight:** 3,500 g

#### SAFETY / EMISSION

FCC, CE



Model 098-82160 rear panel



Model 098-8280




Model 098-8280 rear panel

## KVM Hydra Cables

Tangle-proof, single-cable design combines monitor, keyboard and mouse cables into a single, flexible bundle.

Available in two types and in a variety of lengths for connection between CommandView KVM switches and your computers, and also as an extension between your monitor, keyboard, and mouse to the CommandView KVM switch.




Model 098-A018



098-A100



Model 098-A050



Model 098-A050

### KVM Hydra cables

PART NO.	DESCRIPTION
098-A015	KVM cable for 1.5 m, 2x PS/2 M/M + video M/F + 2x stereo
098-A018	KVM cable for 1.8 m, 2x PS/2 M/M + video M/F + 2x stereo
098-A030	KVM cable for 3.0 m, 2x PS/2 M/M + video M/F + 2x stereo
098-A050	KVM cable for 5.0 m, 2x PS/2 M/M + video M/F + 2x stereo
098-A100	KVM cable for 10.0 m, 2x PS/2 M/M + video M/F + 2x stereo

# VGA Splitter

Signamax Video Splitter is a VGA/SVGA/QXGA splitting device which boosts video signal from one PC to 2/4/8 monitors. Its built-in 300 Mhz Video Amplifier not only extends the transmission distance up to 210 ft (65 m) but also gains multiple high quality screens. It is very suitable for multiple display applications, such as Stock market monitor array, Educational demos, Airport & Railway station bulletin display.

## VGA Splitter

PART NO.	DESCRIPTION
098-8220	Signamax VGA splitter 2PC
098-8240	Signamax VGA splitter 4PC

## FEATURES


- Splitting one PC's screen into 2/4/8 monitors for simultaneously display.
- Bypass DDC2/DDC2AB PnP from PC-VGA port to MONITOR1 port.
- Support maximum resolution up to 2,048 x 1,536 @ 75 Hz
- Maximum transmission distance is up to 210 ft. (65 m), including cascades.
- A built-in voltage detector will shut down video synchronous signal to protect from low power supply.
- A brightness control to select high brightness screen for long distance cabling.
- No DC clamping offset on R/G/B signals works on all type monitors (CRT/LCD).

# NETWORK CONNECTIVITY SYSTEMS





## Wireless LAN



**Wireless Access Point 802.11b/g**

**Wireless AP/Router 802.11b/g**

**Wireless PCI Card 802.11b**

**Wireless PCI Card 802.11b/g**

**Wireless PCMCIA Card 802.11b/g**

**Wireless USB Dongle 802.11b/g**

**Wireless AP/Router 802.11a/b/g**

**Wireless Access Point 802.11a/b/g**

**Wireless Outdoor Access Point  
802.11a/b/g**

**Wireless PCI Card 802.11a/b/g**

**Wireless PCMCIA Card 802.11a/b/g**

**Wireless USB Dongle 802.11a/b/g**

**Wireless Mini PCI Card 802.11a/b/g**

**Wireless AP/Router 802.11b/g/n**

**Wireless MIMO Client Adapters  
802.11b/g/n**

**Antennas for 2.45 GHz Band**

**Accessories for WiFi units**

**Antennas for 5 GHz Band**

## Wireless Access Point 802.11b/g

Signamax 802.11g Access Points are the ideal solution for any network administrator who needs to expand the capacity of the wireless network. This is especially applicable to wireless networks in high traffic areas such as airports, coffee shops, shopping centers, sporting venues, and university campus deployments. At transfer rates of up to 54 Mbps. In addition to bridging 802.11b/g wireless networks, For more secure communication, the 065-1784A supports the encryption settings up to 152-bit WEP, and advanced security of WPA, WPA2 and AES. With its web-based configuration the Access Point is easy to install, alter or activate advanced setting, or update with the latest firmware.



Model 65-1784A



Model 65-1784A

### FEATURES

- Fully Comply with IEEE 802.11b and 802.11g Standard High-Speed Data Rate
- High-speed Wireless Connection Up to 54 Mbps Data Rate
- Support 64/128/152 bit WEP and WPA/WPA2 Encryption for Advanced Transfer Security
- Easy Installation, Management, and Configuration Reset
- Act as Repeater and AP at the Same Time via WDS
- Support IP Sharing to Allow More than One Device ON-Line Simultaneously
- Built-in Firewall Provides Additional Security

### Wireless Access Point 802.11b/g

PART NO.	DESCRIPTION
065-1784A	Wireless Access Point 802.11b/g

### SPECIFICATIONS

#### STANDARDS

IEEE 802.11b, IEEE 802.11g, IEEE 802.3, IEEE 802.3u, IEEE 802.3x  
Modulation Types  
802.11b: DQPSK, DBPSK and CCK  
802.11g: BPSK, QPSK, 16QAM, 64QAM, OFDM  
Operating Frequency: 2.400 – 2.497 GHz ISM band  
Operating Channels: 11 for N. America, 14 Japan, 13 Europe (ETSI),  
2 Spain, 4 France

#### DATA RATE

802.11g: 54, 48, 36, 24, 18, 12, 9 and 6 Mbps  
802.11b: 11, 5.5, 2, and 1 Mbps  
Media Access Protocol: CSMA/CA with ACK  
Receiver Sensitivity:  
802.11b: Typical -83 dBm for 11 Mbps @ 8% PER (Packet Error Rate)  
Typical -89 dBm for 2 Mbps @ 8% PER (Packet Error Rate)  
802.11g: Typical Sensitivity at Which Frame (1,000-byte PDUs)  
Error Rate = 10%  
-87 dBm at 6 Mbps; -86 dBm at 9 Mbps; -85 dBm at 12 Mbps;  
-83 dBm at 18 Mbps; -80 dBm at 24 Mbps;  
-76 dBm at 36 Mbps; -71 dBm at 48 Mbps; -66 dBm at 54 Mbps  
Transmitter Output Power  
802.11b: Typical 18 dBm at 11, 5.5, 2 and 1 Mbps  
802.11g: Typical RF Output Power at each Data Rate  
+14 – 15 dBm at 54 Mbps; +14 – 16 dBm at 48 Mbps;  
+16 – 18 dBm at 36, 24, 18, 12, 9, and 6 Mbps

#### ANTENNA

Dipole antennas with 2 dBi gain for 2.4 GHz

#### INTERFACE

Power Jack, Factory Reset Button,  
10/100M Base-T (UTP), Wireless Dipole Antenna  
Operating Voltage: 5V DC +/- 10%  
Power Consumption: max. 6W (TBD)  
Dimensions (L x W x H): 139.5 x 114.5 x 29.5 mm

#### LEDs

Power LED, 10/100M LED, Wireless LED

#### FEATURES

Transmit Power Control  
Control TX power level from full, 50%, 25%, 12.5%, and min.  
Radio control: Radio on/off supported  
Auto Channel selection: Scan channel and find a clear channel  
DFS/TPC: Dynamic Frequency Selection and Transmit Power Control  
Security: 64/128/152 bit WEP and WPA/WPA2 Encryption  
Authentication Type: Open System Authentication, Shared Key  
Authentication or both enabled

# Wireless AP/Router 802.11b/g

Signamax Wireless AP Router 065-1788, IEEE802.11b/g standard compliant, is a high quality and reliable Internet routing and security device, enables multiple users to share the Broadband Internet connection with or without wires through a Cable or DSL modem. Simply install the router, connect to Cable/DSL modem, and surf Internet without extra efforts. Acting as a 10/100 Mbps 4-Port Ethernet switch as well, the router, with all ports supporting MDI/MDIX, allows you to use CAT5 cable to uplink to other routers/switches.

The Wireless 11b/g AP Router is featured with advanced security technology, supporting WEP, WPA-PSK, WPA (Wi-Fi Protected Access) TKIP/AES, WPA2 and RADIUS. With the router, your network is armed with the highest levels of protection. The Router provides a total solution for the Small and Medium-sized Business (SMB) and the Small Office/Home Office (SOHO) markets, giving you an instant network today, and the flexibility to handle tomorrow's expansion and speed.



Model 065-1788

## Wireless AP/Router 802.11b/g

PART NO.	DESCRIPTION
065-1788	Wireless AP/Router 802.11b/g

## SPECIFICATIONS

### DATA RATE

11 Mbps (11b mode), 54 Mbps (11g mode)

### STANDARDS

IEEE 802.11b / 802.11g (Wireless),

IEEE 802.3 / 802.3u (Wired)

**Operating Radius:** Indoor: 100 m, Outdoor: 300 m

**Bridging:** IEEE 802.1x, Software bridge between wireless and wired LAN

**Routing:** Static Routing

RIP version 1 (RFC 1058) and version 2 (RFC 1723)

NAT (Network Address Translation)

NAPT (Network Address and Port Translation)

DHCP (Dynamic Host Configuration Protocol) Server/Client

### SECURITY & MANAGEMENT (FEATURE)

64/128 bits WEP Encryption and SSID

WPA/ WPA2, Clone MAC

SNMP (simple Network Management Protocol) v1, v2

Supports DDNS

Supports RADIUS Client

Configuration of NAT/NAPT

Supports Virtual Server and Virtual DMZ

Provides MAC filter, Client filter, and URL/IP filter

WAN, LAN, DMZ and AP statistics

Restore to Factory Default

System Log

UPnP, ALG and Help

WDS (only / AP)

AP (Bridge / Getway mode)

Software Upgrade through Web

Firewall

### ENVIRONMENTAL

**Interface:** LAN x 4, WAN x 1

**LED Indicators:** POWER, LINK (WLAN), ACT (WLAN), LAN x 4, WAN

**Wireless Frequency:** 2.400 – 2.4835 GHz

**Receiver Sensitivity:**

IEEE 802.11: -84 dBm (Typical),

IEEE 802.11g: -60 dBm (Typical)

**Transmit Output Power:** 11b: 19±1 dBm, 11g: 15±1 dBm

**Power:** AC 9V, 1A

**Dimension (L x W x H):** 160 x 95 x 30 mm

**Weight:** 200g

**Temperature:** 0° – 45°C (Operating), -20° – 70°C (Storing)

**Humidity:** 5-95% Non-Condensing

**Supported OS:** Windows 98SE, ME, 2000, XP, NT4.0, Mac and Linux

**Regulations:** FCC Part 15 class B, CE



Model 065-1788

## FEATURES & BENEFITS

- Maximum transfer rate up to 85 Mbps from WAN to LAN, 100 Mbps LAN to LAN and 11/54 Mbps through wireless channel enables High-speed access to ISP or corporate network
- Friendly GUI Configuration and Management software
- Supports IEEE 802.3 full duplex flow control
- Built-in DHCP server automatically assigns IP address to all workstations on your LAN
- 802.11b/802.11g provides WEP Encryption and SSID functions for security purpose
- Supports MAC filter, Client filter, URL and IP filter blocking and Hacker pattern detection
- Supports ALGs (Microsoft NetMeeting, MSN Messenger, Windows Media Player, DirectX 8.0, PPTP pass through, IPSec pass through, FTP, ICMP, SMTP, POP3, DNS, Telnet, HTTP, HTTPS, H.323, SIP, Real Audio, CuSeeMe, AOL and Games)

## Wireless PCI Card 802.11b

Signamax 065-1796 let you connect your desktop computer to a wireless network, and is suitable for small offices, home offices and places where cable can not be installed. PCI card complies with 802.11b in 2,4 GHz frequency band. Users connected will enjoy faster downloads and truly instant email communication at transfer rates of up to 11 Mbps.

For more secure communication, the 065-1796 support the encryption settings up to 64/128-bit WEP and MAC address filter. 065-1796 is compliant with PCI 2.2 standard and supports most of operating systems—Windows 98/2000/XP.



Model 065-1796

### FEATURES & BENEFITS

- Complies with IEEE 802.11b
- Compliant with PCI 2.2 Standard
- High security—WEP, MAC address filter
- Supports Windows 95/2000/XP
- Support AP, Client and Bridge mode
- Easy to install and configure

### Wireless PCI Card 802.11b

PART NO.	DESCRIPTION
065-1796	Signamax PCI card 802.11b, 11 Mbps, ext. antenna, SMA male rev.

### SPECIFICATIONS

**Standard:** IEEE802.11b compliant  
**Bus Type:** 32-bit PCI 2.2  
**Protocols:** TCP/IP  
**Modulation Technology:** DSSS  
**Data Encryption:** 64/128bit WEP encryption; TKIP (Temporal Key Integrity Protocol)  
**Frequency Band:**  
 2.412 – 2.462 GHz (US), 2.412-2.484 GHz (Japan)  
 2.412 – 2.472 GHz (Europe), 2.45-2.462 GHz (Spain)  
 2.457 – 2.472 GHz (France)  
**Channels:** 11 (US, Canada), 13 (Europe), 14 (Japan), 2 (Spain), 4 (France)  
**Data Rates & Modulation:**  
 11 Mbps: CCK, 5.5 Mbps: CCK, 2 Mbps: DQPSK, 1 Mbps: DBSK  
**Media Access Protocol:**  
 CSMA/CA (Carrier sense multiple access with collision avoidance)  
**Receive Sensitivity:**  
 11 Mbps @ -84 dBm, 5.5 Mbps @ -86 dBm, 2 Mbps @ -91 dBm,  
 1 Mbps @ -93 dBm  
**LED Indicators:** Power, Link  
**Supported OS:** Windows ME, 2000, XP, Unix-Linux

### ENVIRONMENTAL

**Transmit Output Power:** Up to 17 dBm  
**Operational Voltage:** 3.3/5V  
**Power Consumption:** Tx <350 mA / Rx <200 mA  
**Temperature:**  
 Operating: -0° to 55°C  
 Storage: -5° to 70°C  
**Humidity:**  
 Operating: 0-90% Non-Condensing  
 Storage: 0-95% Non-Condensing  
**Certifications:** FCC, CE, SAR  
**Warranty:** 2 years

### SYSTEM REQUIREMENTS

Computer with CPU PII 366MHz or better  
 128MB RAM or better  
 CD-ROM Drive  
 1 PCI slot

# Wireless PCI Card 802.11b/g

Signamax 065-1798 let you connect your desktop computer to a wireless network, and is suitable for small offices, home offices and places where cable can not be installed. PCI card complies with 802.11b/g in 2,4 GHz frequency band. Users connected will enjoy faster downloads and truly instant email communication at transfer rates of up to 54 Mbps.

It provides superior performance and interoperability within mixed mode network. For more secure communication, the 065-1798 support the encryption settings up to 128-bit WEP, WPA, WPA2 (TKIP/AES). 065-1798 is compliant with PCI 2.2 standard and supports most of operating systems—Windows 98/2000/XP/Vista, MAC OS and Linux too.



## FEATURES & BENEFITS

- Complies with IEEE 802.11b/g
- Compliant with PCI 2.2 Standard
- High security—WEP, WPA, WPA 2, 802.1x
- Supports Windows, MAC OS and Linux
- Lower power consumption
- Easy to install and configure

## Wireless PCI Card 802.11b/g

PART NO.	DESCRIPTION
065-1798	Signamax PCI card 802.11b/g, 54 Mbps, ext. antenna, SMA male rev.

## SPECIFICATIONS

**Standard:** IEEE 802.11b, IEEE 802.11g

**Bus Type:** 32-bit PCI bus

**Protocols:** TCP/IP

**Modulation Technology:**

IEEE 802.11b: DSSS

IEEE 802.11g: OFDM

**Modulation Method:**

IEEE 802.11b: DBPSK / DQPSK / CCK

IEEE 802.11g: BPSK, QPSK, 16QAM, 64QAM

**Data Rate:** IEEE 802.11b: 1, 2, 5.5, 11 Mbps

IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

**Operation Mode:** Ad hoc, Infrastructure, Soft AP

**Transmitter Power:** 17 (±2) dBm @11b, 14 (±2) dBm @ 11g

**Receive Sensitivity:**

Operating at 11 Mbps: < -80 dBm @ 8% FER,

54 Mbps: < -68 dBm @ 8% FER

**Operating Range:** Up to 300m, depending on surrounding environment

**Antenna:** External Antenna (2 dBi)

**Power Consumption:**

Transmit: around 616 mA @ 11b, 432 mA @ 11g

Receive: around 377 mA

**Security:** 64-bit, 128-bit WEP/ WPA / WPA2 (TKIP/AES)

**LED:** Red/Green LED indicator

**Operating System:** Windows XP/2K/CE/Vista,

MAC OS, Linux

### ENVIRONMENTAL

**Transmit Output Power:** Up to 17dBm

**Operational Voltage:** 3.3/5V

**Power Consumption:** Tx < 350 mA/Rx < 200 mA

**Operating temperature:** 0° – 55°C

**Storage temperature:** -5° – 70°C

**Humidity:** 0-90% Non-Condensing

**Certifications:** FCC, CE

**Warranty:** 2 years

### SYSTEM REQUIREMENTS

Computer with CPU PII 366 MHz or better

128 MB RAM or better

CD-ROM Drive

1 PCI slot

# Wireless PCMCIA Card 802.11b/g

Signamax 065-1791 let you connect your laptop computer to a wireless network, and is suitable for small offices, home offices and places where cable can not be installed. PCMCIA card complies with 802.11b/g in 2,4 GHz frequency band. Users connected will enjoy faster downloads and truly instant email communication at transfer rates of up to 54 Mbps.

It provides superior performance and interoperability within mixed mode network. For more secure communication, the 065-1791 support the encryption settings up to 128-bit WEP, WPA, WPA2 (TKIP/AES). 065-1791 is compliant with 32-bit Card Bus Type II standard and supports most of operating systems—Windows 98/2000/XP/Vista.



Model 065-1791

## FEATURES

- Complies with IEEE 802.11b/g
- Compliant with 32-bit Card Bus Type II
- High security—WEP, WPA, WPA 2, 802.1x
- Plug and Play
- Lower power consumption
- Easy to install and configure

## Wireless PCI Card 802.11b/g

PART NO.	DESCRIPTION
065-1791	Signamax PCMCIA card 802.11b/g, 54 Mbps

## SPECIFICATIONS

### STANDARDS:

IEEE 802.11b (up to 11 Mbps), IEEE 802.11g (up to 54 Mbps)

**Card Type:** 32-bit Cardbus Type II

### Modulation Technology:

IEEE 802.11g: BPSK, QPSK, 16 QAM, 64 QAM, OFDM

IEEE 802.11b: DQPSK, DBPSK, DSSS, CCK

### Frequency Band:

2,400-2,483.5 MHz ISM band (IEEE 802.11b/g)

**Antenna Type:** Integrated Printed-PCB antennas with dual diversity function

### Channels:

Thirteen channels for European countries (IEEE 802.11b)

Thirteen channels for European countries (IEEE 802.11g)

### Data Rates & Modulation:

1, 2, 5.5, 11 Mbps (IEEE 802.11b)

6, 9, 12, 18, 24, 36, 48, 54 Mbps (IEEE 802.11g)

**Data Security:** 64, 128-bit WEP, WPA, WPA2, 802.1x

**LED Indicators:** Power, Activity

**Supported OS:** Windows XP/2000/ME/98SE/Vista

### ENVIRONMENTAL

**Operational Voltage:** 5V -10%

### Network Architecture:

Ad-Hoc Mode (Peer-to-Peer without Access Point)

Infrastructure Mode (Communications to wired networks via Access Points with Roaming)

### Temperature:

Operating: 0° – 55°C

Storing: -20° – 75°C

### Humidity:

10-90%, non-condensing (operating)

5-95%, non-condensing (non-operating)

**Certification:** FCC, CE

**Warranty:** 2 years

# Wireless USB Dongle 802.11b/g

Signamax 065-1791A let you connect your laptop computer to a wireless network, and is suitable for small offices, home offices and places where cable can not be installed. USB Dongle complies with 802.11b/g in 2,4 GHz frequency band. Users connected will enjoy faster downloads and truly instant email communication at transfer rates of up to 54 Mbps.

It provides superior performance and interoperability within mixed mode network. For more secure communication, the 065-1791A support the encryption settings up to 128-bit WEP, WPA, WPA2 (TKIP/AES). 065-1791A is compliant with USB 2.0 standard and supports most of operating systems—Windows 98/2000/XP/Vista.

## FEATURES

- Complies with IEEE 802.11b/g
- Compliant with USB 2.0
- High security—WEP, WPA, WPA 2, 802.1x
- Plug and Play
- Lower power consumption
- Easy to install and configure

## Wireless USB Dongle 802.11b/g

PART NO.	DESCRIPTION
065-1791A	Signamax USB Dongle Adapter 802.11b/g, 54 Mbps

## SPECIFICATIONS

### STANDARDS:

IEEE 802.11b (up to 11 Mbps)  
IEEE 802.11g (up to 54 Mbps)

**Card Type:** USB 2.0

### Modulation Technology:

IEEE 802.11g: BPSK, QPSK, 16 QAM, 64 QAM, OFDM  
IEEE 802.11b: DQPSK, DBPSK, DSSS, CCK

### Frequency Band:

2,400-2,483.5 MHz ISM band (IEEE 802.11b/g)

**Antenna Type:** Integrated Printed-PCB antennas with dual diversity function

### Channels:

Thirteen channels for European countries (IEEE 802.11b)  
Thirteen channels for European countries (IEEE 802.11g)

### Date Rates & Modulation:

1, 2, 5.5, 11 Mbps (IEEE 802.11b)  
6, 9, 12, 18, 24, 36, 48, 54 Mbps (IEEE 802.11g)

**Data Security:** 64, 128-bit WEP, WPA, WPA2, 802.1x

**LED Indicators:** Power, Activity

**Supported OS:** Windows XP/2000/ME/98SE/Vista

### ENVIRONMENTAL

**Operational Voltage:** 5V -10%

### Network Architecture:

Ad-Hoc Mode (Peer-to-Peer without Access Point)  
Infrastructure Mode (Communications to wired networks via Access Points with Roaming)

### Temperature:

Operating: 0° – 55°C

Storing: -20° – 75°C

### Humidity:

10-90%, non-condensing (operating)

5-95%, non-condensing (non-operating)

**Certification:** FCC, CE

**Warranty:** 2 years

# Wireless AP/Router 802.11a/b/g

065-1756 Wireless 802.11a/b/g AP/Router is a complete all-in-one networking solution for homes and small/medium enterprises. With its built-in 4x 10/100 Mbps auto-sensing Ethernet switch ports, users can link multiple computers to Internet without any hassle. The built-in wireless function can let you connect wirelessly with your desktop or notebook computers from up to 300 meters away, and simultaneously in wireless A and G. The Wireless Router provides multiple levels of security: 64-bit/128-bit key WEP, WPA data encryption for high-level security. Moreover, the use of IEEE 802.1X offers an effective framework for authenticating and controlling user traffic to a protected network, as well as dynamically varying encryption keys. Proprietary wireless range extension technology expands wireless range at lower bit rate. 065-1756 is a special design for local network users to resist hackers from attacking your private network and share networking resource. Not only with the NAT as natural firewall, the build-in powerful advanced firewall proceeds SPI (Stateful Packet Inspection), stops LAN users accessing inappropriate web site, as well as setting the Internet accessing time schedule. Content filtering shields children from any inappropriateness allowing you to set levels for nudity, sex, violence, and language.



Model 065-1756

## FEATURES

- Provides High performance universal wireless network connectivity
- Ideal for multi-media data transmission with high speed wireless performance
- Enhanced security management to protect user network
- Supports VPN pass through, including IPsec and PPTP
- Supports routing ability
- Easy and fast installation and setup

## Wireless AP/Router 802.11 a/b/g

PART NO.	DESCRIPTION
065-1756	Signamax Wireless AP/Router 802.11a/b/g

## SPECIFICATIONS

### INTERFACE

**Host Interface:** WAN: 1x10/100Base-Tx (auto MDI/MDIX sensing)  
LAN: 4x10/100Base-T Ethernet switch port (auto sensing)  
**LED indicator:** LED x9: Power, DMZ, 11a, 11g, LAN1-LAN4, Internet  
**Antenna:** 802.11a: 4dBi (Peak Gain), 802.11g: 2 dBi (Peak Gain)

### RADIO CHARACTERISTICS

**Frequency Band:** 802.11a:  
US: UNI-Band 5.15 – 5.35 GHz,  
EU: UNI-Band 5.15 – 5.35 GHz  
UNI-Band 5.47 – 5.725 GHz, 802.11b/g: ISM band 2.4 – 2.4835 GHz  
**Modulation:** 802.11a/g: OFDM, 802.11b: CCK, DQPSK, DBPSK  
**Receive Sensitivity:** 802.11a/g: 6 Mbps – 10-5 BER @ -91 dBm,  
9 Mbps – 10-5 BER @ -90 dBm, 12 Mbps – 10-5 BER @ -89 dBm,  
18 Mbps – 10-5 BER @ -88 dBm, 24 Mbps – 10-5 BER @ -85 dBm,  
36 Mbps – 10-5 BER @ -82 dBm, 48 Mbps – 10-5 BER @ -75 dBm,  
54 Mbps – 10-5 BER @ -72 dBm, 108 Mbps – 10-5 BER @ -69 dBm  
**Transmit Power:** 802.11a: Max. 16 dBm @ 16QAM R3/4,  
802.11g: Typ: 16 dBm @ Normal Temp Range,  
802.11b: Typ: 18 dBm @ Normal Temp Range

### Data Rate:

802.11b: 11 Mbps, 5.5 Mbps, 2 Mbps, 1 Mbps, (Auto fallback);  
802.11a/g: Auto fallback

### Operating Range<sup>1</sup>:

802.11a: Up to 50 m (Indoor)  
802.11g: Up to 100 m (Indoor)

**Power Supply:** Input: AC 85 – 230V, 0.35A Output: DC 5V, 2.5A

### REQUIREMENT

**Operating Systems:** Win98SE/ME/2000/XP

### ENVIRONMENTAL

**Dimension (L x W x H):** 198 x 160 x 33 mm  
**Weight:** 700 g  
**Temperature:** 0° – 40°C (Operating), -20° – 70°C (Storing)  
**Humidity:** Operating 10-85% Non-Condensing,  
Storage 5-90% Non-Condensing

### SOFTWARE FEATURES

**Standard:** 802.3, 802.11a, 802.11b, 802.11g  
**Protocol Support:** TCP/IP, NetBEUI, IPX/SPX  
**Basics:** DHCP client/server, NAT, PPPoE Client, DNS Proxy/Relay, Dynamic DNS  
**Security:** 64/128-bit WEP encryption, WPA/802.1x (Authentication) MAC address filtering, IP Filtering, Content Filtering, DoS prevention, Time-of-Day ACL  
**Advanced:** DMZ Hosting, UPnP, VPN pass-through (IPSec/PPTP/L2TP), NTP  
**Management:** Embedded Web configuration, Web, firmware upgrade, configuration backup and restore are supported, DHCP, Static IP, PPPoE, and PPTP login support

**CERTIFICATION:** FCC class B, CE Mark

**WARRANTY:** 2 years

### PACKAGE CONTENT

Wireless 802.11a/b/g Broadband AP/Router  
CD-ROM with User Guide, Quick Installation Guide, DC Power Adapter, RJ45 Cat. 5, UTP cable

<sup>1</sup> The transmission speed varies in the surrounding environment

# Wireless Access Point 802.11a/b/g

Signamax 065-1755 Wireless 11a/b/g Dual-Band Access Point can be accessed in all three 802.11 wireless networks. 065-1755 contains two separate wireless connectivity radio transceivers, which support all three popular wireless networking specifications. One of the two transceivers uses 2.4 GHz frequency band and supports both wireless 802.11b and 802.11g, which offers up to 11 Mbps and 108 Mbps data rate respectively. The other transceiver uses 5 GHz frequency band and supports wireless 802.11a, also up to 108 Mbps. Since two radio waves operate in different frequency bands, they can work simultaneously and cover your wireless zone with high-speed performance. In terms of security, 065-1755 offers up to 128-bit WEP Encryption, WPA and also includes MAC address filtering, which allows you to assign Internet Access to those you permit. The configuration and installation is made to be simple and fast following the web browser-based setup wizard.

## FEATURES & BENEFITS

- Provide High performance universal wireless network connectivity
- Ideal for multi-media data transmission with high speed wireless performance
- Easy and fast installation and setup
- WDS: AP, Bridge, Repeater, and AP Client
- Atheros XRTM eXtended Range technology



Model 065-1755

## Wireless Access Point 802.11a/b/g

PART NO.	DESCRIPTION
065-1755	Signamax Wireless 5 GHz Access Point/Client/Repeater 802.11a/b/g

## SPECIFICATIONS

### INTERFACE

**Ethernet LAN:** One 10/100Base-T Ethernet switch port (auto sensing)  
**LED indicator:** LED x4: Power, LAN, 11a link/Act, 11g link/Act  
**Antenna:** 802.11a: 4 dBi (Peak Gain), 802.11b/g: 2 dBi (Peak Gain)  
**Reset Button:** Reset to default setting (hold the reset button after 6 sec)

### RADIO CHARACTERISTICS

**Standard:** IEEE 802.11a 802.11b and 802.11g for WLAN; 802.3 for wired LAN  
**Frequency Band:** 802.11a: US: UNI-Band 5.15 – 5.35 GHz  
 EU: UNI-Band 5.15 – 5.35 GHz; UNI-Band 5.47 – 5.725 GHz  
 802.11b/g: ISM band 2.4 – 2.4835 GHz  
**Modulation:** 802.11b: 11 Mbps & 5.5 Mbps CCK; 2 Mbps: DQPSK; 1 Mbps: BPSK  
 802.11g and 802.11a: OFDM  
**Media Access Protocol:** CSMA/CA with ACK  
**Transmit Power:** 802.11a: Max 16dBm@16QAM R3/4  
 802.11g: Typ. 16 dBm @ Normal Temp Range  
 802.11b: Typ. 18 dBm @ Normal Temp Range  
**Receive Sensitivity:** 802.11a: 6 Mbps 10-5 BER @ -91 dBm; 54 Mbps 10-5BER @ -72 dBm; 108 Mbps 10-5BER @ -69 dBm  
 802.11g: 11 Mbps 10-5 BER @ -85 dBm; 54 Mbps 10-5 BER @ -72 dBm; 108 Mbps 10-5BER @ -69dBm  
**Data Rate:** 802.11b: 11, 5.5, 2, 1 Mbps, auto fallback  
 802.11g & 802.11a: 108, 54, 48, 36, 24, 18, 12, 9, 6 Mbps  
**Operating Range:** 802.11b: up to 300 m (Outdoor), 35 – 60 m (Indoor)  
 802.11g: up to 50 m (Outdoor), 20 m (Indoor)  
 802.11a: up to 300 m (Open space), 100 m (Indoor)

\* The performance various depend on environment.

### ENVIRONMENTAL

**Dimension (L x W x H):** 195 x 160 x 27 mm  
**Weight:** 700 g  
**Temperature:** 0° – 40°C (Operating), -20° – 70°C (Storing)  
**Humidity:** 95% Non-Condensing

### SOFTWARE FEATURES

**Protocol Support:** TCP/IP, IPX, NetBEUI  
**Security:** Up to 64bit/128-bit WEP & WPA, MAC address filtering, IP Filtering, Content Filtering, DoS prevention, Time-of-Day ACL  
**Operating mode:** AP, AP Client, Repeater, P2P & P2MP Bridge  
**Management:** Built-in HTTP Server for setup and remote management via any browser

### POWER SUPPLY

**Input:** AC 85 – 230V, 0.35A  
**Output:** DC 5V, 2.5A

### CERTIFICATION

FCC class B, CE Mark

### WARRANTY

2 years

### PACKAGE CONTENT

One Wireless AP, One CD-ROM with User Guide  
 One DC Power Adapter, One Quick Installation Guide  
 One RJ45 Cat.5 UTP cable

# Wireless Outdoor Access Point 802.11a/b/g

Signamax 065-1761 Wireless 11a+g Dual-Band Outdoor Access Point w. Integrated 20dBi Outdoor Flat Antenna can be accessed in all three 802.11 wireless networks. 065-1761 contains two separate wireless connectivity radio transceivers, which support all three popular wireless networking specifications. One of the two transceivers uses 2.4 GHz frequency band and supports both wireless 802.11b and 802.11g, which offers up to 11 Mbps and 108 Mbps data rate respectively. The other transceiver uses 5 GHz frequency band and supports wireless 802.11a, also up to 108 Mbps. Since two radio waves operate in different frequency bands, they can work simultaneously and cover your wireless zone with high-speed performance. In terms of security, 065-1761 offers up to 128-bit WEP/WPA Encryption and also includes MAC address filtering, which allows you to assign Internet Access to those you permit. The configuration and installation is made to be simple and fast following the web browser-based setup wizard.



Model 065-1761



Model 065-1761

## FEATURES & BENEFITS

- Protocol Support TCP/IP, IPX, NetBEUI
- Security Up to 64bit/128-bit WEP & WPA, MAC address filtering
- MAC address filtering, IP Filtering, Content Filtering
- DoS prevention, Time-of-Day ACL
- Operating mode AP, AP Client, Repeater, P2P & P2MP Bridge
- Management Built-in HTTP Server for setup and remote management via any browser

## SPECIFICATIONS

### RADIO CHARACTERISTICS

Standard IEEE 802.11a 802.11b and 802.11g for WLAN; 802.3 for wired LAN  
 Frequency Band 802.11a: US: UNI-Band 5.15–5.35 GHz, EU: UNI-Band 5.15–5.35 GHz, UNI-Band 5.47–5.725 GHz  
 802.11b/g: ISM band 2.4–2.4835 GHz  
 Modulation 802.11b: 11 Mbps & 5.5 Mbps CCK; 2 Mbps: DQPSK; 1 Mbps: BPSK  
 802.11g and 802.11a: OFDM  
 Media Access Protocol CSMA/CA with ACK  
 Transmit Power 802.11a: Max 16dBm@16QAM R3/4  
 802.11g: Typ. 16 dBm @ Normal Temp Range  
 802.11b: Typ. 18 dBm @ Normal Temp Range  
 Receive Sensitivity 802.11a: 6 Mbps 10 – 5 BER @ -91dBm; 54 Mbps 10–5BER @ -72 dBm; 108 Mbps 10–5BER @ -69dBm  
 802.11g: 11 Mbps 10–5 BER @ -85dBm; 54 Mbps 10–5 BER @ -72 dBm; 108 Mbps 10–5BER @ -69dBm  
 Data Rate 802.11b: 11, 5.5, 2, 1 Mbps, auto fallback  
 802.11g & 802.11a: 108, 54, 48, 36, 24, 18, 12, 9, 6 Mbps

### INTERFACE

Ethernet LAN One 10/100Base-T Ethernet switch port (auto sensing)  
 Integrated Outdoor 20 dBi Flat Antenna 5.150 – 5.875 GHz  
 Interface for 2,4 GHz Antenna (SMA)  
 Reset Button Reset to default setting (hold the reset button after 6 sec), 802.3af PoE support

### ENVIRONMENTAL

**Dimension:** 190 x 216 x 50 mm  
**Weight:** 1,800 g  
**Temperature:** -20° – 60°C (Operating), -20° – 70°C (Storing)  
**Humidity:** 95% Non-Condensing

### POWER SUPPLY

**Input Input:** AC 85 – 230V, 0.35A  
**Output Output:** DC 5V, 2.5A

**CERTIFICATION:** FCC class B, CE Mark

**WARRANTY:** 2 years

### PACKAGE CONTENT

One Wireless Outdoor AP, One CD-ROM with User Guide  
 One DC Power Adapter, One Quick Installation Guide  
 One RJ45 Cat.5 UTP cable

Wireless Outdoor Access Point 802.11a/b/g

PART NO.	DESCRIPTION
065-1761	Wireless 11a+g Dual-Band Outdoor Access Point w. Integrated 20dBi Outdoor Flat Antenna

# Wireless PCI Card 802.11a/b/g

Signamax 065-1750 Wireless 11a/b/g PCI Adapter offers high-speed wireless connection with a data rate up to 108 Mbps. 065-1750 supports seamless roaming from cell to cell in all types of wireless networks. You can place your desktop computers anywhere at home or in the office building without any wire limitation. The 065-1750 supports advanced security features including 64/128-bit Wired Equivalent Privacy (WEP) & WPA encryption for more secured user network environment.

The 3dBi high gain Antenna makes 065-1750 more sensitive to the wireless surrounding. Wider and longer receiving range increases your Internet access mobility and still provides the speed you need for large file download, digital video and audio transmissions.



Model 065-1750



Model 065-1750

## SPECIFICATIONS

### INTERFACE

**Host Interface:** PCI rev2.3 Interface  
**LED indicator:** Activity, Network Link  
**Antenna:** Dual Band a: 3dBi antenna / b: 1dBi

### RADIO CHARACTERISTICS

**Standard:** IEEE 802.3, 802.3u, 802.11a, 802.11b, 802.11g  
**Frequency Band:** 802.11a:  
 US: UNI-Band 5.15 – 5.35 GHz  
 EU: UNI-Band 5.15 – 5.35 GHz, UNI-Band 5.47 – 5.725 GHz  
 802.11b/g: ISM band 2.4 – 2.4835 GHz  
**Modulation:** 802.11a/g: OFDM,  
 802.11b: CCK, DQPSK, DBPSK  
**Receive Sensitivity:**  
 802.11a: -70 dBm @ 54 Mbps 10% PER  
 802.11g: -72 dBm @ 54 Mbps 10% PER  
 802.11b: -88 dBm @ 11 Mbps 10% PER  
**Transmit Power:** 802.11a: 11 – 18 dBm;  
 802.11g: 15 – 19 dBm  
 802.11b: 18 ±1 dBm  
**Data Rate:**  
 802.11a: 54, 48, 36, 24, 18, 12, 9, 6 Mbps per channel,  
 auto fallback;  
 802.11b: 11, 5.5, 2, 1 Mbps per channel, auto fallback;  
 802.11g: 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 Mbps  
 per channel, auto fallback  
**Operating Range:**  
 802.11a: Up to 50 m (Indoor)  
 802.11g: Up to 100 m (Indoor)

### ENVIRONMENTAL

**Dimension (L x W x H):** 147 x 120 x 20 mm  
**Weight:** 104 g  
**Security:** 802.11a: 64/128-Bit WEP, WPA  
 802.11b/g: 64/128-Bit WEP, WPA  
**Temperature:**  
 0° – 60°C (Operating), -20° – 80°C (Storing)  
**Humidity:**  
 Operating 10-85% Non-Condensing  
 Storage 5-90% Non-Condensing  
**Operating Voltage:** 3.3V ±5%

### REQUIREMENT

**Operating Systems:** Win98SE/ME/2000/XP/Vista

### CERTIFICATION

FCC, CE

### WARRANTY

2 years

### PACKAGE CONTENT

Dual-Band Wireless 802.11a/b/g PCI Adapter  
 Setup CD-ROM with User Guide, Quick Installation Guide

## FEATURES

- One adapter connects either 2.4 GHz (802.11b or 802.11g) or 5 GHz (802.11a) networks.
- Advanced security features with up to 128-bit WEP encryption and WPA
- Easy to setup

## BENEFITS

- Dual-Band wireless adapter connects your desktop PC to 802.11a, 802.11b, 802.11g wireless networks
- Protects your wireless communications with up to 128-bit encryption
- Incredible data rates up to 108 Mbps

## Wireless PCI Card 802.11a/b/g

PART NO.	DESCRIPTION
065-1750	Signamax Wireless 5 GHz PCI Card 802.11a/b/g

# Wireless PCMCIA Card 802.11a/b/g

The 065-1751 Wireless 11a/b/g CardBus Adapter offers high-speed wireless connection with a data rate up to 108 Mbps. It can provide the speed you need for large file download, digital video and audio transmissions. 065-1751 supports seamless roaming from cell to cell in all types of wireless networks. You can place your notebook anywhere at home or in the office building without any wire limitation. The 065-1751 supports advanced security features including 64/128-bit Wired Equivalent Privacy (WEP) & WPA encryption for more secured user network environment.



Model 065-1751

## Wireless PCMCIA Card 802.11a/b/g

PART NO.	DESCRIPTION
065-1751	Signamax Wireless 5 GHz PCMCIA Card 802.11a/b/g

## BENEFITS

- Dual-Band wireless adapter connects your desktop PC to 802.11a, 802.11b, 802.11g wireless networks
- Protects your wireless communications with up to 128-bit encryption
- Incredible data rates up to 108 Mbps

## FEATURES

- One adapter connects either 2.4 GHz (802.11b or 802.11g) or 5 GHz (802.11a) networks
- Advanced security features with up to 128-bit WEP encryption and WPA
- Easy to setup

## SPECIFICATIONS

### INTERFACE

**Host Interface:** CardBus Interface  
**LED indicator:** Power, Network Link  
**Antenna:** Integrated Dual Band diversity antenna

### RADIO CHARACTERISTICS

**Standard:** IEEE 802.3, 802.3u, 802.11a, 802.11b, 802.11g  
**Frequency Band:** 802.11a: US: UNI-Band 5.15 – 5.35 GHz  
 EU: UNI-Band 5.15 – 5.35 GHz, UNI-Band 5.47 – 5.725 GHz  
 802.11b/g: ISM band 2.4 – 2.4835 GHz  
**Modulation:** 802.11a/g: OFDM  
 802.11b: CCK, DQPSK, DBPSK  
**Receive Sensitivity:** 802.11a: -70dBm @54 Mbps 10% PER  
 802.11g: -72 dBm @ 54 Mbps 10% PER  
 802.11b: -88 dBm @ 11 Mbps 10% PER  
**Transmit Power:** 802.11a: 11 – 18 dBm; 802.11g: 15 – 19dBm  
 802.11b: 18 ±1dBm  
**Data Rate:** 802.11a<sup>1</sup>: 54, 48, 36, 24, 18, 12, 9, 6 Mbps per channel, auto fallback; 802.11b: 11, 5.5, 2, 1 Mbps per channel, auto fallback  
 802.11g<sup>2</sup>: 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 Mbps per channel, auto fallback  
**Operating Range<sup>2</sup>:** 802.11a: Up to 50 m (Indoor)  
 802.11g: Up to 100 m (Outdoor)

### ENVIRONMENTAL

**Dimension (L x W x H):** 120 x 54 x 8 mm  
**Weight:** 42 g  
**Security:** 802.11a: 64/128-Bit WEP, WPA  
 802.11b/g: 64/128-Bit WEP, WPA  
**Temperature:** 0° – 60°C (Operating), -20° – 80°C (Storing)  
**Humidity:**  
 Operating 10-85% Non-Condensing  
 Storage 5-90% Non-Condensing  
**Operating Voltage:** 3.3V ±5%

### REQUIREMENT

**Operating Systems:** Win98SE/ME/2000/XP/Vista

### CERTIFICATION

FCC, CE

### WARRANTY

2 years

### PACKAGE CONTENT

Dual-Band Wireless 802.11a/b/g CardBus Adapter  
 Setup CD-ROM with User Guide, Quick Installation Guide

<sup>1</sup> Support enhanced proprietary Super Mode up to 108 Mbps

<sup>2</sup> The transmission speed varies in the surrounding environment

# Wireless USB Dongle 802.11a/b/g

The 065-1752 Wireless 11a/b/g USB Dongle offers high-speed wireless connection with a data rate up to 54 Mbps. It can provides the speed you need for large file download, digital video and audio transmissions. 065-1752 supports seamless roaming from cell to cell in all types of wireless networks. You can place your desktop computers anywhere at home or in the office building without any wire limitation. The 065-1752 supports advanced security features including 64/128-bit Wired Equivalent Privacy (WEP) & WPA encryption for more secured user network environment.



## FEATURES

- One adapter connects either 2.4 GHz (802.11b or 802.11g) or 5 GHz (802.11a) networks
- Advanced security features with up to 128-bit WEP encryption and WPA
- Easy to setup

## BENEFITS

- Dual-Band wireless adapter connects your desktop PC to 802.11a, 802.11b, 802.11g wireless networks
- Protects your wireless communications with up to 128-bit encryption
- Incredible data rates up to 54 Mbps

## Wireless USB Dongle 802.11a/b/g

PART NO.	DESCRIPTION
065-1752	Signamax Wireless USB Dongle Adapter 802.11a/b/g

## SPECIFICATIONS

### INTERFACE

- Host Interface:** USB2.0
- LED indicator:** Power
- Antenna:** Integrated Dual Band diversity antenna

### RADIO CHARACTERISTICS

- Standard:** IEEE 802.3, 802.3u, 802.11a, 802.11b, 802.11g
- Frequency Band:** 802.11a: US: UNI-Band 5.15 – 5.35 GHz  
EU: UNI-Band 5.15 – 5.35 GHz. UNI-Band 5.47 – 5.725 GHz
- 802.11b/g: ISM band 2.4 – 2.4835 GHz
- Modulation:** 802.11a/g: OFDM
- 802.11b: CCK, DQPSK, DBPSK
- Receive Sensitivity:** 802.11a: -70dBm @54 Mbps 10% PER
- 802.11g: -72 dBm @ 54 Mbps 10% PER
- 802.11b: -88 dBm @ 11 Mbps 10% PER
- Transmit Power:** 802.11a: 11 – 18dBm; 802.11g: 15 – 19dBm
- 802.11b: 18 ±1dBm
- Data Rate:** 802.11a: 54, 48, 36, 24, 18, 12, 9, 6 Mbps per channel, auto fallback; 802.11b: 11, 5.5, 2, 1 Mbps per channel, auto fallback
- 802.11g: 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 Mbps per channel, auto fallback
- Operating Range:** 802.11a: Up to 50 m (Indoor)
- 802.11g: Up to 100 m (Indoor)

### ENVIRONMENTAL

- Dimension:** 80 x 25 x 10 mm (L x W x H)
- Weight:** 20 g
- Security:** 802.11a: 64/128-Bit WEP, WPA
- 802.11b/g: 64/128-Bit WEP, WPA
- Temperature:** 0° – 50°C (Operating), -20° – 80°C (Storing)
- Humidity:** Operating 10-85% Non-Condensing
- Storage 5-90% Non-Condensing
- Operating Voltage:** 5V ±5%

### REQUIREMENT

- Operating Systems:** Win2000/XP/Vista, Linux

### CERTIFICATION

- FCC, CE

### WARRANTY

- 2 years

### PACKAGE CONTENT

- Dual-Band Wireless 802.11a/b/g USB Dongle
- Setup CD-ROM with User Guide, Quick Installation Guide

<sup>1</sup> The transmission speed varies in the surrounding environment

# Wireless Mini PCI Card 802.11a/b/g

The 065-1753 Wireless mini PCI card compatible with 802.11a/b/g offers high-speed wireless connection with a data rate up to 108 Mbps. It can provide the speed you need for large file download, digital video and audio transmissions. 065-1753 supports seamless roaming from cell to cell in all types of wireless networks. You can insert this card anywhere to different router boards supporting Atheros chipsets.

The 065-1753 supports advanced security features including 64/128-bit Wired Equivalent Privacy (WEP) & WPA encryption for more secured user network environment.



Model 065-1761

## Wireless Mini PCI Card 802.11a/b/g

PART NO.	DESCRIPTION
065-1753	Wireless Mini PCI Card 802.11a/g/b

### CHIPSET

Atheros AR5006XS(AR5414A)

### INTERFACE

Mini PCI Interface Type IIIA

### ENVIRONMENTAL

Dimension: 60 x 45 x 4 mm

Weight: 20 g

Security:

802.11a: 64/128-Bit WEP, WPA

802.11b/g: 64/128-Bit WEP, WPA

Temperature: 0° – 55°C (Operating), -20° – 80°C (Storing)

Humidity: Operating 10-85% Non-Condensing

Storage 5-90% Non-Condensing

Operating Voltage: 3.3V ±5%

### REQUIREMENT

System Requirements

Desktop PC containing:

- 32-bit PCI slot

- 64 MB memory or greater

- 300 MHz processor or greater

Microsoft Windows 98 Second Edition/Millennium Edition/2000/Windows XP

Operating Range:

Open Space: Up to 260 m, Indoor: 100 m

The transmission speed varies in the surrounding environment

Network Protocol: TCP/IP, IPX, NDIS4 and NDIS5, NDIS 5.1

Management Utility: Monitor Internet Access Status via UI

Supplied Driver: Windows 98SE/ME/2000/XP, Linux

### WARRANTY

2 years

### NETWORK STANDARD

IEEE 802.11a, 802.11b, 802.11g

### STANDARDS

IEEE 802.3, IEEE 802.3u, IEEE 802.11a, IEEE 802.11b,

IEEE 802.11g draft standard, Wi-Fi compliant

## SPECIFICATIONS

### RADIO CHARACTERISTICS

#### Frequency Band:

802.11a: 5.15 – 5.85 GHz (subject to local regulations)

802.11b: ISM band 2.400 – 2.484 GHz (subject to local regulations)

802.11g: ISM band 2.400 – 2.484 GHz (subject to local regulations)

#### Number of Channel

802.11a: subject to local regulations

802.11b: USA and Canada – 11, Most European

countries – 13, Japan – 14, France – 14

802.11g: USA and Canada – 13, Most European countries – 13, Japan – 14

#### Spreading

802.11a: Orthogonal Frequency Division Multiplexing (OFDM)

802.11b: Direct Sequence Spread Spectrum (DSSS)

802.11g: Orthogonal Frequency Division Multiplexing (OFDM)

#### Modulation

802.11a/g: 64 QAM, 16 QAM, QPSK, BPSK

802.11b: CCK, DQPSK, DBPSK

#### Data Rate

802.11a: 54, 48, 36, 24, 18, 12, 9, 6 Mbps per channel, auto fallback for extended range

802.11b: 11, 5.5, 2, 1 Mbps per channel, auto fallback for extended range

802.11g: 108, 54, 48, 36, 24, 18, 12, 9, 6 Mbps

per channel, auto fallback for extended range

**Antenna:** Single antenna with 1dBi antenna gain

at 2.4 GHz band and 2dBi antenna gain at 5 GHz band (External antenna)

#### Transmitted power

802.11a: 17dBm

802.11g: 18dBm

802.11b: 19dBm

tolerance: +/-1.5dBm

#### Receive Sensitivity

802.11a/g

Nominal Temp Range:

- 6 Mbps 10-5 BER @ -90 dBm, typical

- 9 Mbps 10-5 BER @ -89 dBm, typical

- 12 Mbps 10-5 BER @ -88 dBm, typical

- 18 Mbps 10-5 BER @ -86 dBm, typical

- 24 Mbps 10-5 BER @ -82 dBm, typical

- 36 Mbps 10-5 BER @ -78 dBm, typical

- 48 Mbps 10-5 BER @ -72 dBm, typical

- 54 Mbps 10-5 BER @ -68 dBm, typical

802.11b

Typ. -88 dBm @ 11 Mbps, +/-2dBm

Typ. -91 dBm @ 5.5 Mbps

Typ. -92 dBm @ 2 Mbps

Typ. -93 dBm @ 1 Mbps

#### Power consumption (peak)

802.11a

Continue TX: 510 mA @ 3.3V

Continue RX: 250 mA @ 3.3V

802.11b

Continue TX: 380 mA @ 3.3V

Continue RX: 220 mA @ 3.3V

802.11g

Continue TX: 400 mA @ 3.3V

Continue RX: 280 mA @ 3.3V

# Wireless AP/Router 802.11b/g/n

Signamax 065-1710 complies with 802.11n draft 2.0 wireless standard in 2,4 GHz frequency band. Utilizing the advanced MIMO technology, it can support the data transmission rate of up to 300 Mbps and the coverage distance is far than IEEE 802.11b/g products. Stable wireless connection and high bandwidth enable you to enjoy the network applications without any interruption.

Users connected will enjoy faster downloads and truly triple play communication at transfer rates of up to 300 Mbps. It provides superior performance and interoperability within mixed mode network. For more secure communication, the 065-1710 support the encryption settings up to 128-bit WEP, WPA, WPA2 (TKIP/AES). 065-1710 contains 1 x WAN Port + 4 x LAN Port Switch + IEEE 802.11b/g/n AP/Router.

## Wireless AP/Router 802.11b/g/n

PART NO.	DESCRIPTION
065-1710	Signamax Wireless LAN Broadband AP/Router 802.11b/g/n

## SPECIFICATIONS

### Data Transfer Rates:

11 Mbps (11b mode), 54 Mbps (11g mode),  
300 Mbps (802.11n draft 2.0)

**Standard:** IEEE 802.11b / 802.11g, 802.11n (Wireless),  
IEEE 802.3 / 802.3u (Wired)

**Operating Radius:** Indoor: 100 m, Outdoor: 300 m

**Routing:** Static Routing  
RIP version 1 (RFC 1058) and version 2 (RFC 1723)  
NAT (Network Address Translation)  
NAPT (Network Address and Port Translation)  
DHCP (Dynamic Host Configuration Protocol) Server/Client

### SECURITY & MANAGEMENT (FEATURE)

NAT/NAPT IP Sharing  
Anti-DoS Firewall  
Virtual Server/DMZ  
Complies with 2.4GHz Draft 802.11n and backward compatible  
with IEEE 802.11b/g standards  
Supports 64/128-bit WEP Encryption and WPA-PSK, WPA2-PSK

#### Security

High speed data rate – up to 300 Mbps  
Supports WMM function to meet the multi-media data bandwidth requirement  
Supports advanced MIMO technology, enhancing the throughput and coverage  
range significantly  
Supports Special Applications (Port Triggers)  
Supports DDNS (DynDNS, TZO)  
VPN Pass Through (IPSec/PPTP)  
Obtain WAN IP by PPPoE/Static IP/PPTP/DHCP  
DHCP Server  
Web User Interface (Remote Configuration)  
System Status  
Security Log  
Firmware Upgrade

### ENVIRONMENTAL

**Interface:** 1xWAN RJ-45, 4xLAN RJ-45  
**LED Indicators:** POWER, LINK (WLAN), ACT (WLAN), LAN x 4, WAN  
**Wireless Frequency:** 2.400 – 2.4835 GHz  
**Receiver Sensitivity:** IEEE 802.11b: -84 dBm (Typical),  
IEEE 802.11g/n: -60 dBm (Typical)  
**Transmit Output Power:** 11b: 19±1 dBm, 11g/n: 15±1 dBm  
**Power:** 12V DC  
**Temperature:** 0° – 40°C (Operating), -20° – 70°C (Storing)  
**Humidity:** 5-95% Non-Condensing  
**Supported OS:** Windows 98SE/ME/2000/XP, NT4.0, Mac and Linux  
**Regulations:** FCC Part 15 class B, CE  
**Warranty:** 2 years

# Wireless MIMO Client Adapters 802.11b/g/n

Signamax 065-1711/12/13 complies with 802.11n draft 2.0 wireless standard in 2,4 GHz frequency band. Utilizing the advanced MIMO technology, it can support the data transmission rate of up to 300 Mbps and the coverage distance is far than IEEE 802.11b/g products. Stable wireless connection and high bandwidth enable you to enjoy the network applications without any interruption.

Users connected will enjoy faster downloads and truly triple play communication at transfer rates of up to 300 Mbps. It provides superior performance and interoperability within mixed mode network. For more secure communication, the 065-1711/12/13 support the encryption settings up to 128-bit WEP, WPA, WPA2 (TKIP/AES). 065-1711/12/13 is compliant with 32-bit Card Bus Type II / 32-bit PCI / USB 2.0 standard and supports most of operating systems—Windows 98/2000/XP/Vista.

## FEATURES

- Complies with 802.11n draft, 802.11g and 802.11b standards
- Farther coverage, less dead spaces and higher throughput with MIMO technology
- Supports QoS-WMM, WMM-PS
- Supports 64/128-bit WEP, WPA (TKIP with IEEE 802.1x), WPA2 (AES with IEEE 802.1x) functions for high level of security
- Supports the most popular operating system: Windows 2000/XP/XP64/Vista
- Supports 32-bit Cardbus interface / 32-bit PCI / USB 2.0
- Supports WPS (WiFi Protected Setup)

## SPECIFICATIONS

### Standards:

IEEE 802.11b (up to 11 Mbps)  
IEEE 802.11g (up to 54 Mbps)  
IEEE 802.11n (up to 300 Mbps)

**Card Type:** 32-bit Cardbus Type II / 32-bit PCI / USB 2.0

### Frequency Band:

2,400-2,483.5 MHz ISM band (IEEE 802.11b/g/n)

**Antenna Type:** 3 x Internal antenna

### Data Rates & Modulation:

11b: 1/2/5.5/11 Mbps  
11g: 6/9/12/24/36/48/54 Mbps  
11n (20 MHz): MCS0-15, 32 with Half Guard Interval Support (up to 144 Mbps)  
11n (40 MHz): MCS0-15, 32 with Half Guard Interval Support (up to 300 Mbps)

**Data Security:** 64, 128-bit WEP, WPA, WPA2, 802.1x

**LED Indicators:** Power, Activity

**Supported OS:** Windows XP/2000/ME/98SE/Vista

## ENVIRONMENTAL

**Operational Voltage:** 5V -10%

### Temperature:

Operating: 0° – 55°C  
Storing: -20° – 75°C

### Humidity:

10-90%, non-condensing (operating)  
5-95%, non-condensing (non-operating)

**Certifications:** FCC, CE

**Warranty:** 2 years


## Wireless MIMO Client Adapters 802.11b/g/n

PART NO.	DESCRIPTION
065-1711	Signamax PCMCIA card 802.11b/g/n, 300 Mbps
065-1712	Signamax PCI card 802.11b/g/n, 300 Mbps
065-1713	Signamax USB Adapter 802.11b/g/n, 300 Mbps

## Antennas for 2.45 GHz Band



Model 065-2411



Model 065-2408


Model 065-2412

### Signamax Antennas for 2.45 GHz Band

PART NO.	DESCRIPTION	CONNECTOR
065-2408	OMNI-8.5 Omnidirectional antenna, Gain 8,5 dBi, to be used in ISM band – 2.4 GHz, vertical HPBW, V25°	N female
065-2411	UNI-11 Unidirectional antenna, Gain 11,5 dBi, to be used in ISM band – 2.4 GHz, HPBW – H80°, V30°	SMA female
065-2412	OMNI-12 Omnidirectional antenna, Gain 12 dBi, to be used in ISM band – 2.4 GHz, HPBW – V20°	N female

## Accessories for WiFi Units

The 065-18xx Signamax series coaxial cable reductions are best to be used for connecting WiFi Access Point, Bridges, Clients and/or WiFi Routers to external antennas.



Model 065-1811



Model 065-1834

### Signamax cables for connecting WiFi units to external antennas

PART NO.	DESCRIPTION	LENGTH
065-1811	Reduction from SMA female rev. (regular WiFi connector) to N male. Cable used: RG-58	0.25 m
065-1812	Reduction from SMA female rev. (regular WiFi connector) to N male. Cable used: RG-58	0.5 m
065-1813	Reduction from SMA female rev. (regular WiFi connector) to N male. Cable used: RG-58	0.75 m
065-1821	Reduction from SMA female rev. (regular WiFi connector) to N female. Cable used: RG-58	0.25 m
065-1822	Reduction from SMA female rev. (regular WiFi connector) to N female. Cable used: RG-58	0.5 m
065-1823	Reduction from SMA female rev. (regular WiFi connector) to N female. Cable used: RG-58	0.75 m
065-1832	Reduction from SMA female rev. (regular WiFi connector) to SMA male. Cable used: CNT-195	0.5 m
065-1834	Reduction from SMA female rev. (regular WiFi connector) to SMA male. Cable used: CNT-195	1 m
065-1836	Reduction from SMA female rev. (regular WiFi connector) to SMA male. Cable used: CNT-195	3 m
065-1838	Reduction from SMA female rev. (regular WiFi connector) to SMA male. Cable used: CNT-195	5 m

## Antennas for 5 GHz

The Signamax Antennas are designed by Signamax for the 5 GHz communication system. After structure optimized and being tuned carefully, it has excellent performance such as very good VSWR, high gain and big F/B Ratio etc. The strong structure and small dimension make it easy to install. Each antenna is tested by HP network analyzer strictly before delivery.



Model 065-5020



Model 065-5020

### Antennas for 5 GHz communication system

PART NO.	DESCRIPTION
<b>Antennas for 5.150 – 5.875 GHz Band</b>	
065-5020	UNI-directional antenna, Gain 20 dBi, Band 5.150 – 5.875 GHz, Vert./Hor. pol., connector N Female
<b>Antennas for 5.725 – 5.875 GHz Band</b>	
065-5808	OMNI-directional antenna, Gain 8 dBi, Band 5.725 – 5.875 GHz, Vert. pol., connector N Female
065-5812	OMNI-directional antenna, Gain 12 dBi, Band 5.725 – 5.875 GHz, Vert. pol., connector N Female
065-5818	UNI-directional antenna, Gain 18 dBi, Band 5.725 – 5.875 GHz, Vert./Hor. pol., connector N Female
065-5824	UNI-directional antenna, Gain 24 dBi, Band 5.725 – 5.875 GHz, Vert./Hor. pol., connector N Female
065-5829	UNI-directional antenna, Gain 29 dBi, Band 5.725 – 5.875 GHz, Vert./Hor. pol., connector N Female
065-5832	UNI-directional antenna, Gain 32 dBi, Band 5.725 – 5.875 GHz, Vert./Hor. pol., connector N Female
<b>Antennas for 5.400 – 5.725 GHz Band</b>	
065-5423	UNI-directional antenna, Gain 23,5 dBi, Band 5.400 – 5.725 GHz, Vert./Hor. pol., connector N Female
065-5428	UNI-directional antenna, Gain 28,5 dBi, Band 5.400 – 5.725 GHz, Vert./Hor. pol., connector N Female
065-5431	UNI-directional antenna, Gain 31,5 dBi, Band 5.400 – 5.725 GHz, Vert./Hor. pol., connector N Female

## SPECIFICATIONS

### 065-5020

Frequency Range: 5,150 – 5,875 MHz  
Gain: 20 dBi  
Vertical Beamwidth: 16°  
Horizontal Beamwidth: 16°  
VSWR:  $\leq 1.5$   
Nominal Impedance: 50  $\Omega$   
Polarization: Vertical / Horizontal  
Max Power: 100W  
Dimension: 190 x 216 x 50 mm  
Weight: 1.1 kg  
Connector: N female  
Rated Wind Velocity: 60 m/s

### 065-5808

Frequency Range: 5,725 – 5,875 MHz  
Gain: 8 dBi  
Vertical Beamwidth: 16°  
Horizontal Beamwidth: 360°  
VSWR:  $\leq 1.5$   
Nominal Impedance: 50  $\Omega$   
Polarization: Vertical  
Max Power: 100W  
Dimension:  $\geq 20$  x 350 mm  
Weight: 200 g  
Connector: N female  
Rated Wind Velocity: 60 m/s

### 065-5812

Frequency Range: 5,725 – 5,875 MHz  
Gain: 12 dBi  
Vertical Beamwidth: 7°  
Horizontal Beamwidth: 360°  
VSWR:  $\leq 1.5$   
Nominal Impedance: 50  $\Omega$   
Polarization: Vertical  
Max Power: 100W  
Dimension:  $\geq 20$  x 540 mm  
Weight: 500 g  
Connector: N female  
Rated Wind Velocity: 60 m/s

### 065-5818

Frequency Range : 5,150 – 5,350/  
5,725 – 5,875 MHz  
Gain: 18 dBi  
Horizontal Beamwidth: 40 $\pm$ 5°  
Vertical Beamwidth: 40 $\pm$ 5°  
F/B Ratio: 15 dB  
VSWR:  $\leq 1.5$   
Nominal Impedance: 50  $\Omega$   
Polarization: Vertical  
Max Power: 100W  
Connector: N female  
Dimension: 190 x 216 x 50 mm

### 065-5824

Frequency range: 5,725 – 5,875 MHz  
Gain: 24 dBi  
VSWR:  $\leq 1.5$   
Nominal Impedance: 50  $\Omega$   
Polarization: Vertical or Horizontal  
Max Power: 100W  
Connector: N Female  
Horizontal Beamwidth: 9°  
F/B ratio:  $\geq 30$  dB  
Diameter: 0.4 m  
Weight: 3 kg

### 065-5829

Frequency range: 5,725 – 5,875 MHz  
Gain: 29 dBi  
VSWR:  $\leq 1.5$   
Nominal Impedance: 50  $\Omega$   
Polarization: Vertical or Horizontal  
Max Power: 100W  
Connector: N Female  
Horizontal Beamwidth: 6°  
F/B ratio:  $\geq 35$  dB  
Diameter: 0.6 m  
Weight: 5 kg

### 065-5832

Frequency range: 5,725 – 5,850 MHz  
Gain: 32.5 dBi  
VSWR:  $\leq 1.5$   
Nominal Impedance: 50  $\Omega$   
Polarization: Vertical or Horizontal  
Max Power: 100W  
Connector: N Female  
Horizontal Beamwidth: 4°  
F/B ratio:  $\geq 38$  dB  
Diameter: 0.9 m  
Weight: 10 kg

### 065-5423, 065-5429, 065-5431

Freq. Range: 5,400 – 5,725 MHz  
Gain: 23.5, 28.5, 31.5 dBi  
Hor. Beamwidth: 9, 6, 4°  
Vert. Beamwidth: 9, 6, 4°  
F/B Ratio:  $\geq 30$ ,  $\geq 35$ ,  $\geq 38$  dB  
VSWR:  $\leq 1.65$   
Input Impedance: 50  $\Omega$   
Polarization: Vertical or Horizontal  
Max. Power: 100W  
Connector: N Female  
Diameter: 0.4, 0.6, 0.9  
Weight: 3, 5, 10 kg



Model 065-5423



Model 065-5431




Model 065-5832




Model 065-5808

# NETWORK CONNECTIVITY SYSTEMS





# Structured Cabling



**Introduction to Structured Cabling**

**What is Structured Cabling?**

**Structured Cabling Testing**

**10GBaseT and Structured Cabling**

# Introduction to Structured Cabling

## History

Until the beginning of the 1980's, the majority of computer networks worked in the host/terminal mode. Applications as well as data were stored centrally on a host computer and user stations, so-called terminals, handled them in this centralized way. Considering the text character of this type of communication, it was not necessary to build special high capacity transmission paths in terminal networks.

The prevalence of terminal networks ended in 1981 when IBM launched their first personal computer onto the market. This new type of work station, which, contrary to terminals, was equipped with a local memory and their own outputs for connecting peripherals, meant a different—decentralized—mode of operation for users. This greater independence, however, brought two important issues,

1. Difficult administration of workstations (i.e. problem solving and software installation).
2. Mutual user cooperation.

It was therefore necessary to find a way that would enable to connect the new PC's into a network, through which it would be possible to share files, applications, and costly peripherals in the same manner as it had been previously on terminal networks.

In the beginning, several solutions arose from different producers. The differences in applied technologies and the diversity in the components of these new systems, however, led to their mutual incompatibility. The solution was to design a universal system, which would set recommended standards determining the electrical and physical characteristics of cables as well as connecting hardware. At the beginning of the 1990's, therefore, the American National Standards Institute (ANSI) asked Telecommunications Industry Association (TIA) and Electronic Industries Alliance (EIA) to propose a uniform standard for cabling systems. One of the most suitable ways for the new cabling system design was to use the already existing solution introduced by the American telecommunication company AT&T. These networks used AT&T's telephone distribution systems that were installed in most administrative buildings. They had a star topology and used a twisted pair cable as the main transmission medium. The outcome of the Standards Commission work was the first specification for structured cabling, which was published in July 1991 and was referred to as ANSI/TIA/EIA 568. Together with technical bulletins TSB-36 and TSB-40 issued a little later, the standard defined the basic transmission requirements for Category 3, 4, and 5.

In 1995, the first update of the above mentioned standard and also the first version of an international ISO/IEC 11801 standard were issued. A year later, in 1996, the organization CENELEC published the first European standard for structured cabling, with the designation EN 50173. As a result of a new high-speed protocols development (e.g. Gigabit Ethernet), these standards were updated in 2000 and 2002. The updates defined new parameters, which must be met by structured cabling components in order to comply with the new protocol requirements. The standards were supplemented with further measured or numerated parameters, such as PSNEXT, PSACR, PSELFEXT, Delay Skew, and so on. In these specification updates new Category 5 (today known as Category 5E, please see below for more information), and later Category 6 as well as Category 7, were introduced.

# Introduction to Structured Cabling

## Currently existing categories

**Category 3**—this is the first and thus oldest category in structured cabling. In the beginning, Category 3 components were used for both voice and data transmissions. The bandwidth was defined up to 16 MHz with data rates of 10 Mbps. Today, Category 3 is predominantly used only for telephone distribution systems (e.g. connection from ISDN patch panels to telephone PBX board, telephone equipment cords etc).

**Category 5E**—at present, Category 5E (or Enhanced Category 5) is still the most frequently used category in structured cabling. The first standard for Category 5E was published in 2000 and was referred to as ANSI/TIA/EIA 568B.1 (for the American standards), CENELEC EN 50173-1:2000 (for the European standards), and ISO/IEC 11801:2000 (for the international standards). In CENELEC as well as ISO/IEC specifications it is still referred to as Category 5 (i.e. not Category 5E). The “Category 5E” is officially used only in ANSI/TIA/EIA standards; it was originally introduced by the manufactures themselves in order to distinguish between the already existing Category 5 components and the “new” improved Category 5 products (i.e. today known as Category 5E). As mentioned above, Category 5E structured cabling components are suitable for the Gigabit Ethernet protocol (i.e. 1000BaseT), which should fit the requirements of most company networks with regular data traffic. However, the 1 Gbps transmission rate is the limit for all Category 5e components and no further improvement will be possible.

**Category 6**—the final specification of Category 6 was published in 2002. The document update is known as ANSI/TIA/EIA 568B.2-1 (for the American standards), EN 50173-1:2002 (for the European standards), and ISO/IEC 11801:2002 (for the international standards). Category 6 is specified up to 200 MHz (standard bandwidth) and 250 MHz (testing bandwidth). The double available bandwidth in comparison with Category 5E requires higher component quality. On the other hand, if these quality requirements are met, Category 6 components offer improved performance and transmission reliability.

**Category 6A**—a new category that is currently being defined by the organizations that set the standard recommendations for structured cabling. The “new” Category 6 will be referred to as “Augmented Category 6” or “Category 6A”. It is developed specifically for the new 10GBaseT Ethernet protocol in mind. Category 6A will offer 500 MHz bandwidth and thus will be suitable for the most data-intensive applications used on metallic computer networks. You can learn more about the 10GBaseT protocol as well as Category 6A further on in this catalogue (please see the “10GBaseT and Structured Cabling” section).

**Category 7**—this category was first mentioned in 1997, however, its specification was not finished before 2002. Now Category 7 is specified in CENELEC EN 50173-1:2002 and ISO/IEC 11801:2002 standards; in the TIA/EIA standards Category 7 is not mentioned. The bandwidth that is defined for the current Category 7 is 600 MHz (standard bandwidth) and 750 MHz (testing bandwidth). With reference to the Category 6a and its 500 MHz frequency, it will be necessary to re-define the current Category 7. It is estimated that a “new” Category 7 will be introduced and it will be referred to as “Augmented Category 7” or “Category 7A” with the bandwidth of up to 1,000 MHz.

The table below shows supported protocols, bandwidth, maximum transmission rates, and recommended use for all categories.

	Cat 3	Cat 4	Cat 5	Cat 5E	Cat 6	Cat 6A	Cat 7	Cat 7A
<b>Supported Protocols</b>	Analog. Voice, ISDN, 10BaseT	IBM Token Ring	100BaseT and lower	1000BaseT and lower	1000BaseTX and lower	10GBaseT and lower	10GBaseT and lower	10GBaseT and lower
<b>Bandwidth</b>	16 MHz	20 MHz	100 MHz	100 MHz	200 MHz/ 250 MHz	500 MHz	600 MHz/ 750 MHz	1,000 MHz
<b>Maximum Transmission Rate</b>	10 Mbps	16 Mbps	100 Mbps (Fast Ethernet)	1,000 Mbps (Gigabit Ethernet)	1,000 Mbps (Gigabit Ethernet)	10 Gbps	10 Gbps	10 Gbps
<b>Usability</b>	Predominantly telephone distribution systems	No longer installed	No longer installed	Regular data and voice traffic	Higher data traffic (multimedia, streaming)	High data traffic, backbone distribution systems, SAN	High data traffic, backbone distribution systems, SAN	High data traffic, backbone distribution systems, SAN

# Introduction to Structured Cabling


In the ISO/IEC 11801 generic cabling standard document, further copper cabling distinctions referred to as "Classes" were introduced. Classes are used for classifying the permanent link or channel performance rather than for rating the individual structured cabling components. The brief description of all classes as specified in the ISO/IEC standard is the following:

- Class A** – analogue voice telephony with the bandwidth of up to 10 KHz.
- Class B** – frequencies up to 1 MHz for voice and slow data links (i.e. IBM 3270 terminals etc.)
- Class C** – this class corresponds to a permanent link or channel performance using Category 3 components. Similarly to Category 3, it covers the bandwidth of up to 16 MHz. Its primary application today is to classify telephone distribution systems.
- Class D** – ratified in 1995 but updated in 2000 and 2002. Today Class D covers the bandwidth of up to 100 MHz.
- Class E** – this class was finished in 2002. Class E corresponds to the permanent link or channel performance using Category 6 components with the bandwidth of up to 200 MHz as standard and 250 MHz as the bandwidth to which Class E/Category 6 is actually tested.
- Class E<sub>A</sub>** – a new class that is currently being defined. Class E<sub>A</sub> will be specified up to 500 MHz and corresponds to permanent link or channel performance of Category 6A cabling. In particular, Class E<sub>A</sub> is aimed to be used with 10GBaseT protocol.
- Class F** – this class covers the standard bandwidth of up to 600 MHz and the testing bandwidth of up to 750 MHz. Class F corresponds to the permanent link or channel performance of Category 7 components.

## What is Structured Cabling?

Structured cabling is a universal system

- that supports digital as well as analog signal transmissions,
- in which the telecommunication outlets are installed even in locations where they are not needed at the moment of installation,
- that use data cables with four twisted pairs and fiber cables,
- in which long technical and also moral service life is expected,
- whose correct functionality is as important for a company as the functioning of the electrical distribution system or any other system in company's infrastructure.



# Structured Cabling Testing



Testing has a major significance for the correct functionality of structured cabling. Testing devices are able to measure installed components and determine whether all requirements defined in the international standards necessary for reliable operation have been met. For Category 5e and Category 6 the following main parameters are measured:

## Wire Map

This parameter checks the correct termination of cable wires in telecommunication outlets and patch panels, including the shielding in STP cabling. At the same time, it checks the signal throughput on the whole cable length—i.e. it is able to show any open-circuit or short circuit faults. The Wire Map parameter is very important but in itself it cannot ensure the correct functionality of an installed computer network.

### What to do if the Wire Map parameter fails?

First, it is necessary to check whether the individual wires have been installed correctly in the termination block. If so (i.e. the wire map corresponds to the standardized T568A or T568B schemes) and the Wire Map parameter still fails, there could be several causes for this: an incorrectly terminated wire in the termination block, a wire interruption inside the cable, or a short-circuit.

Advanced testing devices are able to determine the location of the fault with a relatively high accuracy and by doing so make fixing the problem easier.


T568A and T568B wire map schemes:

### T568A

1. white-green
2. green
3. white-orange
4. blue
5. white-blue
6. orange
7. white-brown
8. brown

### T568B

1. white-orange
2. orange
3. white-green
4. blue
5. white-blue
6. green
7. white-brown
8. brown



## NEXT (Near End Cross Talk)

NEXT is the value that expresses how much signal can get from one pair to another pair within one cable.

The measurement of cross-talk at the near end takes place at the same end of the cable as the location of the signal source. For this parameter, all combinations of pairs are measured within one cable—i.e. 12-36, 12-45, 12-78, 36-45, 36-78, 45-78. This measuring is done for both ends.



### What to do if the NEXT parameter fails?

First, it is essential to find out at which end of the cable NEXT is showing the error (this function is supported by all advanced testing devices). Then it is necessary to check the maximum permitted unlaidd of wires in one pair on the termination block—that should not be more than 13 mm. Typically for category 6, the 13 mm does not necessarily ensure that the NEXT parameter will pass so it is essential to keep the pair unlaidd as short as possible. It is also important that the original twisting of each pair is preserved during installation and that there is no air core between the twisted wires in a pair. A frequent source of cross-talk problems can also be the use of cable couplings. Hence if a cable is not long enough, it is better to replace it with a cable of a corresponding length rather than use couplings.

## Attenuation

Attenuation shows the difference between the strength of the initial signal and the strength of the signal after it gets to the other end of the wire. It is caused mainly by the wire resistance and is usually larger for higher frequencies. Attenuation also increases as the diameter of the cable decreases—this means that a cable with a size of AWG 24 has a slightly higher attenuation than an AWG 23 cable.



### What to do if the attenuation parameter fails?

The length of the horizontal cable must be checked—i.e. whether the electrical length of the link (the actual length of the twisted pairs inside the cable) corresponds to the maximum permitted permanent link of 90 m. A frequent cause of higher attenuation is also an incorrectly terminated wire in patch panels, outlets, or keystones.


## Structured Cabling Testing

### ACR (Attenuation to Crosstalk Ratio)

ACR is a theoretical parameter (i.e. it is not measured but is deduced from two previously measured values) which shows the margin between the NEXT and attenuation values:  $ACR [dB] = NEXT [dB] - A [dB]$ . If the level of attenuation meets or approaches the level of near end cross-talk, the transmitted signal will be lost. The interval between NEXT and attenuation must be at least 10 dB.

*What to do if the ACR parameter fails?*

As the ACR parameter is dependent on the NEXT as well as attenuation values, an improvement of these two parameters will influence the resulting ACR values.



### FEXT (Far End Cross Talk)

FEXT expresses the cross-talk of the signal from one pair to another pair within one cable measured at the far end. This is the same parameter as NEXT, only with FEXT, the measurement is done at a different cable end. Again, all combinations of pairs are measured within one cable—i.e. 12-36, 12-45, 12-78, 36-45, 36-78, and 45-78. FEXT serves an important basis for the following ELFEXT parameter.



### ELFEXT (Equal Level Far End Cross Talk)

ELFEXT corresponds much better to the actual situation during data transfer than FEXT. It is because the cross-talk inside the cable decreases as the attenuation increases. Just as with ACR, ELFEXT is a theoretical parameter (i.e. it is not measured but is calculated from other previously measured values):  $ELFEXT [dB] = FEXT [dB] - A [dB]$ . Thus ELFEXT is the cross-talk at the far end decreased by the attenuation.

### PSNEXT (Power Sum NEXT)

PSNEXT is a theoretical value calculated from the previously measured NEXT. The PSNEXT parameter is primarily important for protocols that use all four pairs for signal transfer (e.g. Gigabit Ethernet). The output sum of cross-talk at the near end shows how much signal gets from three pairs to the remaining fourth pair. The source of the signal and measurement of cross-talk takes place at the same end of the cable.



*What to do if the PSNEXT parameter fails?*

Just as with other parameters, PSNEXT is also influenced by the measured values of NEXT. Thus, an improvement in the near end cross-talk value will affect the resulting value of PSNEXT.

### PSELFEXT (Power Sum ELFEXT)

PSELFEXT is calculated from the ELFEXT value. Just like PSNEXT, this parameter is important for protocols that use all four pairs for signal transfer. PSELFEXT expresses how much signal in the same cable gets from three pairs to the remaining fourth pair. The source of the signal and measurement of cross-talk takes place at opposite ends of the cable.


### Propagation Delay

This value expresses a delay of the signal travelling from one end of the cable to the other. The typical delay of the signal in a category 5e cable is around 5 ns per 1 m; the permitted limit is 5.7 ns per 1 m, which is 570 ns per 100 m. Propagation Delay also serves as a basis for testing the Delay Skew value.

### Delay Skew

Delay Skew shows the difference in signal delay between the fastest and the slowest pair. The Delay Skew parameter is affected by (1.) different length of the pairs; (2.) difference in material (resistance, impedance etc.); (3.) the effect of surrounding interference. If the difference is too great, there can be an incorrect interpretation of data by the active device (usually a switch, network card, etc.). Just as for PSNEXT and PSELFEXT, the Delay Skew parameter is critical for protocols that use all four pairs, such as Gigabit Ethernet.

### DELAY SKEW



# Structured Cabling Testing

## Length


There is a direct proportionality between the length and attenuation (i.e. the longer the length of cable, the higher the attenuation). Testing devices use so-called TDR (Time Domain Reflectometry) for measuring lengths. This means that a pulse is sent down the cable, then it is reflected back onto the remote unit, and subsequently the time during which the pulse travels the whole track is recorded. Based on the NVP (i.e. Nominal Velocity of Propagation, which expresses the signal speed in the cable as compared to the speed of light in a vacuum), the length of the measured segment is calculated. This concerns the length of the twisted pairs inside the cable (so-called electrical length), not “untangled” cable (so-called physical length). At 85 m, the variation between electrical and physical length can be up to 5 m depending on the twisting of each pair.

## Return Loss


Return Loss shows the reflection of the signal because of varying impedance at different cable parts. Due to these impedance imbalances, part of the energy can return to the transmitter, which can cause the signal interference.

When testing structured cabling, two basic topologies are used:

**Permanent link**—the connection from the patch panel to the work area telecommunication outlet (i.e. horizontal cabling); this is the most permanent fixture on the structured cabling and cannot easily be taken apart. The maximum permitted length is 90 m.



**Channel**—the connection from the active device (e.g. switch) in the data rack to the network card in the computer, patch cords included. The recommended maximum length of an equipment cord in the data rack is 5 m; the maximum recommended length for work area cord is 20 m. The length of the channel (i.e. the horizontal cabling plus equipment cord as well as work area cord) should not exceed 100 m.



# 10GBaseT and Structured Cabling

Gigabit Ethernet was, until recently, considered to be the limit that would be very difficult to overcome on metallic structured cabling. Now it is obvious that 1 Gbps will not be the maximum transmission rate that can be achieved on copper twisted pair cables. The new 10GBaseT Ethernet standard that was published in June 2006 by the IEEE 802.3an group proves this. In the first stage, this new protocol with transmission speeds of up to 10 Gbps will be primarily employed in backbone distribution systems, SAN's (Storage Area Networks), and data centers.

## 1. Running 10GBaseT on currently existing cabling

The document ANSI/TIA/EIA TSB 155 deals with operating 10GBaseT over currently existing Category 5E and 6 cabling. The test results performed in connection with this bulletin showed that it will not be possible to run 10 Gbps data transfers on Category 5E networks and that on current unshielded Category 6 cabling the 10GBaseT protocol will be able to operate for a distance of up to 55 m. This length limitation should be improved on shielded Category 6 systems but it is highly recommended to use Category 6A components for all new 10G installations as the this new category was primarily designed to provide full compatibility with no length or other limitations for the 10GBaseT. The factor that plays an important role in the above mentioned length restriction is the so-called Alien Crosstalk. It is influenced by the amount of crosstalk signal from external sources, such as other cables in a cable bundle, electronic devices operated nearby, telephones, etc.

## 2. New requirements for future cabling systems for 10GBaseT

As it was already mentioned, a new category with bandwidth of up to 500 MHz (i.e. double of what is available for the current Category 6) was defined to ensure full compatibility of cabling systems with the 10GBaseT protocol, both including the Permanent Link and Channel topologies as well as unshielded and screened cabling. This new category is referred to as "Augmented Category 6" or "Category 6A" and will be published in the upcoming structured cabling specification updates (e.g. ANSI/TIA/EIA 568B.2-10). These updates are currently available in drafts and will be published for the wide public very soon.

Similarly to Category 6A, a "new" Category 7 will be defined. It will be referred to as "Augmented Category 7" or "Category 7A" with bandwidth of up to 1,000 MHz (as compared to 600 MHz of the current Category 7).

Signamax Category 7 shielded cable parameters (at temperature of 20°C).  
The cable supports 10GBaseT. See page K1 for more.


f (MHz)	Attenuation (dB/100 m)	NEXT (dB)	PS-NEXT (dB)	ACR (dB/100 m)	PS-ACR (dB/100 m)	ELFEXT (dB/100 m)	PS-ELFEXT (dB/100 m)	Return loss (dB)
1	1.8	100	97	98	95	105	105	–
4	3.4	100	97	97	94	105	102	27
10	5.4	100	97	95	92	97	94	30
16	6.8	100	97	93	90	93	90	30
20	7.7	100	97	92	89	91	88	30
31.2	9.6	100	97	90	87	87	84	30
62.5	13.7	100	97	86	83	81	78	30
100	17.4	100	97	83	80	77	74	30
125	19.5	95	92	75	72	75	72	26
155.5	21.9	94	91	72	69	73	70	26
175	23.3	93	90	70	67	72	69	25
200	25.0	92	89	67	64	71	68	25
250	28.1	90	87	62	59	69	66	24
300	30.9	89	86	58	55	67	64	24
450	38.3	87	84	48	45	64	61	23
600	44.8	85	82	40	37	61	58	22
750	52.0	83	80	31	28	59	56	21
900	59.4	82	79	23	20	58	55	20

Signamax Category 6A shielded cable parameters (at temperature of 20°C).  
The cable supports 10GBaseT.

f (MHz)	Attenuation (dB/100 m)	NEXT (dB)	PS-NEXT (dB)	ACR (dB/100 m)	PS-ACR (dB/100 m)	ELFEXT (dB/100 m)	PS-ELFEXT (dB/100 m)	Return loss (dB)
1	1.8	100	97	98	95	105	105	–
4	3.4	100	97	97	94	105	102	27
10	5.4	100	97	95	92	97	94	30
16	6.8	100	97	93	90	93	90	30
20	7.7	100	97	92	89	91	88	30
31.2	9.6	100	97	90	87	87	84	30
62.5	13.7	100	97	86	83	81	78	30
100	17.4	100	97	83	80	77	74	30
125	19.5	95	92	75	72	75	72	26
155.5	21.9	94	91	72	69	73	70	26
175	23.3	93	90	70	67	72	69	25
200	25.0	92	89	67	64	71	68	25
250	28.1	90	87	62	59	69	66	24
300	30.9	89	86	58	55	67	64	24
400	38.3	87	84	48	45	64	61	23
500	44.8	85	82	40	37	61	58	22

# NETWORK CONNECTIVITY SYSTEMS





# Work Area Outlet Systems



**Category 6 Wall Outlets**

**Category 5E Wall Outlets**

**Category 6A Keystone Jacks**

**Category 6 Keystone Jacks**

**Category 5E Keystone Jacks**

**Keystone Jack Modular Outlets**

**Keystone Multimedia Modules**


## Category 6 Wall Outlets

Signamax Category 6 outlets are designed for an easy installation. This is ensured by strain relief providing cable positioning and screening contact between the shielded cable and metallic outlet housing. The outlet has a slim design and excellent EMC performance.

The modular construction of the outlet allows flush mounting or wall mounting installation using universal back box. The Signamax Category 6 outlets exceed all electrical parameters specified in the TIA/EIA 568-B.2-1, ISO/IEC 11801:2002, and EN 50173-1 standards. Both T568A and T568B wiring configurations are supported on the LSA+/Krone IDC termination block.



W45/6-2ESH/R



W45/6-2ESH/R back view uncovered



W45/6-2E/R



W45/6-2E/R back view

### Category 6 Wall Outlets


PART NO.	DESCRIPTION
W45/6-2ESH/R	Shielded Wall Outlet Cat 6, 80 x 80 mm, White
W45/6-2ESH	Shielded Wall Outlet Cat 6, 80 x 80 mm, Ivory
W45/6-2E/R	Unshielded Wall Outlet Cat 6, 80 x 80 mm, White
W45/6-2E	Unshielded Wall Outlet Cat 6, 80 x 80 mm, Ivory
W45-AP80-32/R	Wall Mounted Back Box 80 x 80 x 32 mm, White
W45-AP80-32	Wall Mounted Back Box 80 x 80 x 32 mm, Ivory



W45-AP80-32/R

# Category 5E Wall Outlets

For Signamax Category 5 Enhanced outlet its high transmission parameters is the key attribute. Two angled RJ45 ports are covered by plastic frame that fits trunking systems using 80 x 80 mm modules. Outlet has an excellent EMC performance and is developed for all demanding markets. Modular construction of the outlet allows flush mount or wall mount installation using universal back box. Space for port numbering stickers or direct marking above each port allows an easy administration and is user friendly.



W45/5-2ESH




W45/5-2ESH



W45/5-2E

## Category 5E Wall Outlets

PART NO.	DESCRIPTION
W45/5-2ESH/R	Shielded Wall Outlet Cat 5E, 80 x 80 mm, White
W45/5-2ESH	Shielded Wall Outlet Cat 5E, 80 x 80 mm, Ivory
W45/5-2E/R	Unshielded Wall Outlet Cat 5E, 80 x 80 mm, White
W45/5-2E	Unshielded Wall Outlet Cat 5E 80 x 80 mm, Ivory
W45-AP80-32/R	Wall Mounted Back Box 80 x 80 x 32 mm, White
W45-AP80-32	Wall Mounted Back Box 80 x 80 x 32 mm, Ivory



W45/5-2E back view




W45-AP80-32

## Category 6A Keystone Jacks

Signamax 10G shielded Category 6A keystone jacks have been designed to meet the need for high-bandwidth applications, such as 10GBaseT. These components have very slim profile and thus can fit in all highest density applications. They are engineered to exceed the 10G/Category 6A permanent link as well as channel level requirements and are fully tested up to 500 MHz.

The compliancy of the Signamax 10G keystones with 10G/Category 6A standards have been confirmed by both permanent link and channel certificates issued by an independent testing laboratory GHMT. The Signamax 10G keystone jacks support T568A and T568B wiring for maximum flexibility using an easy to read color-code wiring label and can be terminated by standard 110 or Krone termination tools. New contact design provide enhanced plug to jack connection integrity and protects against damage caused by insertion of 4 or 6 position plugs and are rated for 1,000 plug insertions.



KJS458-10G



KJS458-10G



KJS458-10G

### Category 6A Shielded Keystone Jacks

PART NO.	DESCRIPTION
KJS458-10G	10G Shielded Keystone Jack, Universal Wiring, T568A/B


<b>Protocols:</b>	10GBaseT
<b>Life Cycle:</b>	1,000 plug insertions
<b>Contact Material:</b>	50µ gold and 100µ nickel
<b>IDC Block:</b>	dual 110/Krone 8p8c
<b>IDC Block Life Cycle:</b>	200 terminations
<b>Wire:</b>	AWG 26-22
<b>Other material:</b>	FR according to UL94V-2
<b>Storage Temperature:</b>	-40° – 80°C
<b>Operation Temperature:</b>	-40° – 80°C
<b>Max. Humidity Operation:</b>	93%



# Category 6 Keystone Jacks

Signamax Connectivity Systems Category 6 Keystone Jacks have been designed to meet the need for high-bandwidth applications. Category 6 connectors are slim in profile for the highest density applications, and are engineered to exceed all TIA/EIA-568-B.2-1 Category 6 permanent link and channel level requirements. Category 6 jacks are fully tested to 250 MHz. Category 6 jacks support both T568A and T568B wiring for maximum flexibility using an easy to read color-code wiring label and can be terminated using standard 110 or Krone termination tools. New contact design provide enhanced plug to jack connection integrity and protects against damage caused by insertion of 4 or 6 position plugs and are rated for 1,000 plug insertions providing for the highest level of system reliability. These jacks feature the ability to mount either color-coded icon tabs for service identification or dust covers to protect unused jacks form dust and other contaminants. Jacks are available in various colors and are supplied with three color-matched icon tabs and dust covers for voice or data identification.


KJS458-C6



KJ458-C6-RD



KJ458-C6-WH



KJ458-C6-YE



KJ458-C6-BK



KJ458-C6-BK

## Category 6 Unshielded Keystone Jacks

PART NO.	DESCRIPTION
KJ458-C6-WH	Category 6 Unshielded Keystone Jack, Universal Wiring T568A/B, White
KJ458-C6-BK	Category 6 Unshielded Keystone Jack, Universal Wiring T568A/B, Black
KJ458-C6-BU	Category 6 Unshielded Keystone Jack, Universal Wiring T568A/B, Blue
KJ458-C6-GN	Category 6 Unshielded Keystone Jack, Universal Wiring T568A/B, Green
KJ458-C6-RD	Category 6 Unshielded Keystone Jack, Universal Wiring T568A/B, Red
KJ458-C6-YE	Category 6 Unshielded Keystone Jack, Universal Wiring T568A/B, Yellow

## Category 6 Shielded Keystone Jack

PART NO.	DESCRIPTION
KJS458-C6	Category 6 Shielded Keystone Jack, Universal Wiring, T568A/B

## Category 5E Keystone Jacks

Category 5E Keystone Jacks exceed permanent link and channel level requirements as defined in TIA/EIA-568-B.2 and are fully tested to 155 MHz. Provide a sound platform for supporting all today's network operating systems including Gigabit Ethernet.

Category 5E jacks can be terminated with industry standard 110 or Krone termination tools and feature color-coding for both T568A and T568B wiring. Jacks feature the ability to mount either color-coded icon tabs for service identification or dust covers to protect unused jacks from dust and other contaminants. Jacks are available in various colors and are supplied with three color-matched icon tabs and dust covers for voice or data identification.




KJ458-C5E-BK



KJ458-C5E-WH



KJ458-C5E-YE



KJ458-C5E-GN

### Category 5E Unshielded Keystone Jacks

PART NO.	DESCRIPTION
KJ458-C5E-WH	Category 5E Unshielded Keystone Jack, Universal Wiring T568A/B, White
KJ458-C5E-BK	Category 5E Unshielded Keystone Jack, Universal Wiring T568A/B, Black
KJ458-C5E-BU	Category 5E Unshielded Keystone Jack, Universal Wiring T568A/B, Blue
KJ458-C5E-GN	Category 5E Unshielded Keystone Jack, Universal Wiring T568A/B, Green
KJ458-C5E-RD	Category 5E Unshielded Keystone Jack, Universal Wiring T568A/B, Red
KJ458-C5E-YE	Category 5E Unshielded Keystone Jack, Universal Wiring T568A/B, Yellow

### Category 5E Feed-Thru Coupler

PART NO.	DESCRIPTION
KRJ45/5S	Category 5E Panel Mount Feed-Thru Coupler, Black
KRJ45/5S-SH	Category 5E Shielded Panel Mount Feed-Thru Coupler, Black



KRJ45/5S

### Category 5E Shielded Keystone Jack

PART NO.	DESCRIPTION
KJS458-C5E	Category 5E Shielded Keystone Jack, Universal Wiring, T568A/B




KJS458-C5E

# Keystone Jack Modular Outlets

Modular outlets from Signamax are dedicated to be user-friendly solution for customers who need high modularity in reasonable quality. Contains wide range of outlets and frames, each usable for all keystone jacks, modular jacks and faceplates from our portfolio.

KJGM



KJGM – back




KJGM-WH

## Keystone Jack Modular Outlets

PART NO.	DESCRIPTION
KJGM	Modular Outlet for 2 x 45 Keystone, 80 x 80 mm, Ivory
KJGM-WH	Modular Outlet for 2 x 45 Keystone, 80 x 80 mm, White

# Keystone Multimedia Modules

Signamax Premise Connectivity System offers a wide range of keystone connector modules designed to create a customized multimedia solution in any single or double gang faceplate or surface mount box. Applications include wide variety of small form factor fiber optic couplers.



CMK-ST




CMK-BL

## Keystone Multimedia Modules

PART NO.	DESCRIPTION
CMK-BL	Blank Keystone Module
CMK-ST	ST MM Fiber Connector Module
CMK-SC	SC MM Fiber Connector Module

# NETWORK CONNECTIVITY SYSTEMS





## Patch Panels



**Unloaded Shielded Patch Panel for 10G**

**Category 6 Shielded Patch Panels**

**Category 6 Unshielded Patch Panels**


**Category 5E Shielded Patch Panels**

**Category 5E Unshielded Patch Panels**

**ISDN Patch Panels**

# Unloaded Shielded Patch Panel for 10G

Signamax shielded unloaded patch panel is designed to be used with the Signamax 10G shielded Category 6A keystone jacks (i.e. KJS458-10G) and therefore is an important part of the Signamax 10G high-performance solution. The panel can be loaded with 24 keystones and is equipped with a cable management bar to secure the cables and ensure proper and stable connection. The colour of the Signamax shielded unloaded patch panel is black and its height is 1U.



EPP-0-24SH



EPP-0-24SH

## Category 6A Shielded Patch Panels

PART NO	DESCRIPTION	RACK SPACE
EPP-0-24SH	24-Port Unloaded Shielded Patch Panel for 10G keystones	1U

**Number of Ports:** 24 port  
**Color:** Black  
**Units:** 1U  
**Height:** 44 mm  
**Width:** 484 mm  
**Depth:** 114 mm  
**Storage Temperature:** -40° – 70°C  
**Operation Temperature:** -30° – 60°C  
**Max. Humidity Operation:** 93%




# Category 6 Shielded Patch Panels

Signamax shielded Category 6 patch panel is designed to be used with other Category 6 components as part of complete high-performance solution. The panel meets all electrical parameters specified in the TIA/EIA 568-B.2-1, ISO/IEC 11801:2002 and EN 50173-1 standards. It supports both T568A and T568B wiring configurations using an easy to read color-coded wiring label. Each port of the Signamax Category 6 panel is sequentially numbered for easy administration. The panel is equipped with finger-screw strain reliefs to secure the cables and to ensure proper connection between the shield of the cable and the panel. The Signamax shielded Category 6 patch panel is equipped with LSA+/Krone IDC termination block.



EPP-8KS6-24SH



EPP-8KS6-24SH

## Category 6 Shielded Patch Panels

PART NO	DESCRIPTION	RACK SPACE
EPP-8KS6-24SH	24-Port Category 6 Shielded Patch Panel	1U


Each panel is supplied with a set of installation screws, earthing set and plastic ties for cable fixing. Cable organizer, base frames, blind panels and other accessories are available on special request.  
Panel is supplied in grey colour (RAL 7035).

# Category 6 Unshielded Patch Panels

Signamax Category 6 unshielded patch panels are designed to exceed TIA/EIA-568-B.2-1, ISO/IEC 11801:2002 and EN 50173-1 performance specifications providing usable bandwidth beyond 250 MHz. These high-density panels are available in 12- through 48-Port versions and feature enhanced front and rear labeling for easy circuit identification. Signamax Category 6 unshielded panels support both T568A and T568B wiring configurations using an easy to read color-coded wiring label. These panels are constructed for maximum durability and feature a fully enclosed, 8-Port modular design, which provides flexibility and protection of printed circuitry during termination. A newly designed RJ45 contact configuration provides enhanced plug to jack connection integrity for superior reliability. Rear termination is made quick and easy using a 4-pair inline 110 type connector compatible with industry standard 110 termination tool. The panels include an integrated cable management feature for routing and strain relief requirements.



24458MD-C6C



48458MD-C6C

Tested up to 350 MHz

## Category 6 Unshielded Patch Panels

PART NO	DESCRIPTION	RACK SPACE
12458MD-C6C	12-Port Category 6 Patch Panel, Universal Wiring T568A/B	1U
24458MD-C6C	24-Port Category 6 Patch Panel, Universal Wiring T568A/B	1U
48458MD-C6C	48-Port Category 6 Patch Panel, Universal Wiring T568A/B	2U


Standard jack colour is black. Other colour jacks are available.



12458MD-C6C

# Category 5E Shielded Patch Panels

Signamax Category 5E shielded patch panel is designed to exceed TIA/EIA-568-B.2, ISO/IEC 11801:2002 and EN 50173-1 performance specifications providing usable bandwidth beyond 155 MHz. This panel is available in 24-Port version and features enhanced front and rear labeling for easy circuit identification. The panel supports both T568A and T568B wiring configurations using an easy to read color-coded wiring label. It is constructed for maximum durability and features a fully enclosed, 8-Port modular design, which provides flexibility and protection of printed circuitry during termination. The Signamax shielded Category 5E panel includes an integrated cable management feature for cable routing and strain relief requirements.



EPP-8KS5-24-SH



EPP-8KS5-24-SH

## Category 5E Shielded Patch Panels

PART NO	DESCRIPTION	RACK SPACE
EPP-8KS5-24SH	24-Port Category 5E Shielded Patch Panel	1U

*Each panel has Back Krone IDC block and is supplied with the grounding set and plastic ties for cable attachment. Panel is supplied in grey colour (RAL 7035).*

# Category 5E Unshielded Patch Panels

Signamax Category 5E unshielded patch panels have been engineered for high-performance, high-density, and ease of installation. These panels exceed both component and channel performance as specified in TIA/EIA-568-B.2, ISO 11801:2002 and EN 50173-1, and include new features for port labeling, colour-coding and cable management. These Signamax Category 5E panels are designed for maximum strength, which allows for termination with a standard multi-pair 110 impact tool to reduce installation time. The panels feature a fully enclosed design for protection of printed circuitry during termination. The Signamax Category 5E unshielded panels include an integrated cable management feature for routing and strain relief requirements.



48458MD-C5E



24458MD-C5E

## Category 5E Unshielded Patch Panels

PART NO	DESCRIPTION	RACK SPACE
12458MD-C5E	12-Port Category 5E Patch Panel, Universal Wiring T568A/B	1U
24458MD-C5E	24-Port Category 5E Patch Panel, Universal Wiring T568A/B	1U
48458MD-C5E	48-Port Category 5E Patch Panel, Universal Wiring T568A/B	2U

Standard jack colour is black. Other colour jacks are available.




24458MD-C5E




12458MD-C5E

# ISDN Patch Panels

Signamax ISDN Category 3 patch panel is a high-density telecommunication panel with 25 and 50 standard RJ45 jacks. The panel meets all latest standards and electrical parameters and is designed for termination of two pair cable in Krone termination blocks. Printed circuit board together with high quality components ensures the Category 3 performance. Integrated back cable management for separate cables provides organized and secure installation. All ports are numbered. The panel is available in 1U height.



ISDN25



ISDN50

## Category 3 Shielded Patch Panels

PART NO	DESCRIPTION	RACK SPACE
ISDN25	25-Port Category 3 ISDN Patch Panel	1U
ISDN50	50-Port Category 3 ISDN Patch Panel	1U

### SPECIFICATIONS

#### 25-Port Category 3 ISDN patch panel

Front connector  
RJ45, 8P8C, connected pins 3-6  
Plated by 30 micro inches of gold over nickel  
Jacks grouped into blocks by 5 pieces, single layer  
Terminal block  
4 position Krone block, 4P4C, all connected


#### DIMENSIONS (H x W x D)

43.8 mm x 464.7 mm x 130.5 mm

### SPECIFICATIONS

#### 50-Port Category 3 ISDN patch panel

Front connector  
RJ45, 8P8C, connected pins 3-6  
Plated by 30 micro inches of gold over nickel  
Jacks grouped into blocks by 5 pieces, double layer  
Terminal block  
8 position Krone block, 8P8C, all connected





ISDN50



ISDN25

# NETWORK CONNECTIVITY SYSTEMS





## Patch Cords/Testers

**S-FTP Category 6A Patch Cords**

**S-FTP Category 6 Patch Cords**

**S-FTP Category 5E Patch Cords**

**UTP Category 6 Patch Cords**

**UTP Category 5E Patch Cords**

**T-Adapters and Testers**

**Inline Couplers and Connection Boxes**

## S-FTP Category 6A Patch Cords

Signamax shielded 10G Category 6A patch cables with high quality RJ45 connectors are assembled by using AWG 26 individually shielded pairs PiMF patch cable. The high quality plugs are plated by gold over nickel on polished bronze for up to 2,500 plug cycles. The Category 6A halogen-free patch cables are available in 1m, 2m, 3m, 5m and 10m lengths. Protection provided by rubber boots prevents pair-to-pair disturbance inside the body of the connector and increases performance of the patch cable.



C6A-315GY

### S-FTP Category 6A Patch Cords

LENGTH	GREY
0.5 m	C6A-315GY-0.5 MB
1 m	C6A-315GY-1 MB
2 m	C6A-315GY-2 MB
3 m	C6A-315GY-3 MB
5 m	C6A-315GY-5 MB
7 m	C6A-315GY-7 MB
10 m	C6A-315GY-10 MB



## S-FTP Category 6 Patch Cords

Signamax shielded Category 6 patch cables with high quality Category 6 connector are assembled using 26 AWG individually shielded pairs patch cable. The high quality Category 6 plugs are plated by gold over nickel on polished bronze for up to 2,500 plug cycles. Protection provided by rubber boots prevents pair-to-pair disturbance inside the body of the connector and increases performance of the patch cable.



C6-315GY

### S-FTP Category 6 Patch Cords

LENGTH	GREY	GREEN	BLUE	RED	YELLOW
0.5 m	C6-315GY-0.5 MB	C6-315GR-0.5 MB	C6-315BU-0.5MB	C6-315RD-0.5 MB	C6-315YE-0.5 MB
1 m	C6-315GY-1 MB	C6-315GR-1 MB	C6-315BU-1MB	C6-315RD-1 MB	C6-315YE-1 MB
2 m	C6-315GY-2 MB	C6-315GR-2 MB	C6-315BU-2MB	C6-315RD-2 MB	C6-315YE-2 MB
3 m	C6-315GY-3 MB	C6-315GR-3 MB	C6-315BU-3MB	C6-315RD-3 MB	C6-315YE-3 MB
5 m	C6-315GY-5 MB	C6-315GR-5 MB	C6-315BU-5MB	C6-315RD-5 MB	C6-315YE-5 MB
7 m	C6-315GY-7 MB	C6-315GR-7 MB	C6-315BU-7MB	C6-315RD-7 MB	C6-315YE-7 MB
10 m	C6-315GY-10 MB	C6-315GR-10 MB	C6-315BU-10MB	C6-315RD-10 MB	C6-315YE-10 MB

*Other lengths, colours or halogen free cables on request.*

# S-FTP Category 5E Patch Cords

Signamax shielded Category 5 Enhanced patch cables are assembled using high quality 26 AWG double shielded patch cable. Protection provided by molded boots prevents pair-to-pair disturbance inside the body of the connector and increases performance of the patch cable.

C5E-315GY



## S-FTP Category 5E Patch Cords

LENGTH	GREY	GREEN	BLUE	RED	YELLOW
0.5 m	C5E-315GY-0.5 MB	C5E-315GR-0.5 MB	C5E-315BU-0.5 MB	C5E-315RD-0.5 MB	C5E-315YE-0.5 MB
1 m	C5E-315GY-1 MB	C5E-315GR-1 MB	C5E-315BU-1 MB	C5E-315RD-1 MB	C5E-315YE-1 MB
2 m	C5E-315GY-2 MB	C5E-315GR-2 MB	C5E-315BU-2 MB	C5E-315RD-2 MB	C5E-315YE-2 MB
3 m	C5E-315GY-3 MB	C5E-315GR-3 MB	C5E-315BU-3 MB	C5E-315RD-3 MB	C5E-315YE-3 MB
5 m	C5E-315GY-5 MB	C5E-315GR-5 MB	C5E-315BU-5 MB	C5E-315RD-5 MB	C5E-315YE-5 MB
7 m	C5E-315GY-7 MB	C5E-315GR-7 MB	C5E-315BU-7 MB	C5E-315RD-7 MB	C5E-315YE-7 MB
10 m	C5E-315GY-10 MB	C5E-315GR-10 MB	C5E-315BU-10 MB	C5E-315RD-10 MB	C5E-315YE-10 MB
15 m	C5E-315GY-15 MB	C5E-315GR-15 MB	C5E-315BU-15 MB	C5E-315RD-15 MB	C5E-315YE-15 MB
20 m	C5E-315GY-20 MB	C5E-315GR-20 MB	C5E-315BU-20 MB	C5E-315RD-20 MB	C5E-315YE-20 MB

*Other lengths, colours or halogen free cables on request.*

# UTP Category 6 Patch Cords

Signamax continues to set the standard for high-quality, high-performance patch cords. These Category 6 cables are manufactured to the strictest performance requirements as specified in TIA/EIA-568-B.2-1, ISO 11801:2002 and EN 50173-1 using the highest-level connector design and cable construction. Signamax category 6 patch cords incorporate slim-profile snag-free boots, which protect the plug latch, and a flexible, but durable cable strain relief. All patch cords use a special new connector design that assures maximum pair twist for unparalleled transmission performance and signal integrity. All cords are 100% tested.

C6-114GY




## UTP Category 6 Patch Cords

LENGTH	GREY	GREEN	BLUE	RED	YELLOW
0.5 m	C6-114GY-0.5 MB	C6-114GR-0.5 MB	C6-114BU-0.5 MB	C6-114RD-0.5 MB	C6-114YE-0.5 MB
1 m	C6-114GY-1 MB	C6-114GR-1 MB	C6-114BU-1 MB	C6-114RD-1 MB	C6-114YE-1 MB
2 m	C6-114GY-2 MB	C6-114GR-2 MB	C6-114BU-2 MB	C6-114RD-2 MB	C6-114YE-2 MB
3 m	C6-114GY-3 MB	C6-114GR-3 MB	C6-114BU-3 MB	C6-114RD-3 MB	C6-114YE-3 MB
5 m	C6-114GY-5 MB	C6-114GR-5 MB	C6-114BU-5 MB	C6-114RD-5 MB	C6-114YE-5 MB
7 m	C6-114GY-7 MB	C6-114GR-7 MB	C6-114BU-7 MB	C6-114RD-7 MB	C6-114YE-7 MB
10 m	C6-114GY-10 MB	C6-114GR-10 MB	C6-114BU-10 MB	C6-114RD-10 MB	C6-114YE-10 MB

*Other lengths, colours or halogen free cables on request.*

## UTP Category 5E Patch Cords

Signamax unshielded Category 5 Enhanced patch cables with high quality connector are assembled using high quality 26 AWG patch cable. High quality plugs are plated by gold over nickel on polished bronze for up to 2,500 plug cycles. Protection provided by molded boots prevents pair-to-pair disturbance inside the body of the connector and increases performance of the patch cable.



C5E-114YE



C5E-114GY



C5E-114RD

### UTP Category 5E Patch Cords

LENGTH	GREY	GREEN	BLUE	RED	YELLOW
0.5 m	C5E-114GY-0.5 MB	C5E-114GR-0.5 MB	C5E-114BU-0.5 MB	C5E-114RD-0.5 MB	C5E-114YE-0.5 MB
1 m	C5E-114GY-1 MB	C5E-114GR-1 MB	C5E-114BU-1 MB	C5E-114RD-1 MB	C5E-114YE-1 MB
2 m	C5E-114GY-2 MB	C5E-114GR-2 MB	C5E-114BU-2 MB	C5E-114RD-2 MB	C5E-114YE-2 MB
3 m	C5E-114GY-3 MB	C5E-114GR-3 MB	C5E-114BU-3 MB	C5E-114RD-3 MB	C5E-114YE-3 MB
5 m	C5E-114GY-5 MB	C5E-114GR-5 MB	C5E-114BU-5 MB	C5E-114RD-5 MB	C5E-114YE-5 MB
7 m	C5E-114GY-7 MB	C5E-114GR-7 MB	C5E-114BU-7 MB	C5E-114RD-7 MB	C5E-114YE-7 MB
10 m	C5E-114GY-10 MB	C5E-114GR-10 MB	C5E-114BU-10 MB	C5E-114RD-10 MB	C5E-114YE-10 MB
15 m	C5E-114GY-15 MB	C5E-114GR-15 MB	C5E-114BU-15 MB	C5E-114RD-15 MB	C5E-114YE-15 MB
20 m	C5E-114GY-20 MB	C5E-114GR-20 MB	C5E-114BU-20 MB	C5E-114RD-20 MB	C5E-114YE-20 MB

*Other lengths, colours or halogen free cables on request.*

# T-Adapters and Testers

When installing a cabling system, checking for open or short circuits is always a requirement. Signamax remote cable testers answer the need for testing T568A, T568B, 10BaseT, 10Base2, 10Base5 and Token Ring systems, for UTP and STP cabling.

## Remote Cable Tester with USB Port

PART NO	DESCRIPTION
E097X	Remote Cable Tester with USB Port



E079X

## T-Adapters

PART NO	DESCRIPTION
TA-V1	T-Adapter for splitting 4-pair Outlet to one 10Base-T and one Telephone Outlet
TA-V2	T-Adapter for splitting 4-pair Outlet to two 10Base-T Outlets
TA-V3	T-Adapter for splitting 4-pair Outlet to two Telephone Outlets

*T-Adapters must be used in pairs.*



TA-V1

# Inline Couplers and Connection Boxes

Inline couplers and connection boxes allow a simple operation with installation cables, which can be easily extended. Broken cables can be coupled with no need to install new complete cable segment. Connection boxes can be used for all standard 4- to 8-wire installation cables of 26-22 AWG up to 10 mm outer diameter.



KRJ45-VEB5



KRJ45-VEB6

## Inline Couplers and Connection Boxes

PART NO	DESCRIPTION
KRJ45-S	Inline Coupler E-TA 8/8 unshielded RJ45 UTP
KRJ45-VEBB	Inline Coupler E-TA 8/8 shielded RJ45 STP
KRJ45-VEB6	Connection Box LSA+ up to 600 MHz, Cat6, unshielded
KRJS45-VEB6	Connection Box LSA+ up to 600 MHz, Cat6, shielded
KRJ45-VEB5	Connection Box LSA+, Cat5e, unshielded
KRJS45-VEB5	Connection Box LSA+, Cat5e, shielded






KRJS45-VEB6

# NETWORK CONNECTIVITY SYSTEMS





## Installation Cable



**S-STP Category 7 Installation Cable**

**Certificates 10GBaseT**

**FTP Category 6 Installation Cable**


**UTP Category 6 Installation Cable**

**UTP Category 5E Installation Cable**

**FTP Category 5E Installation Cable**

## S-STP Category 7 Installation Cable

Signamax Category 7 shielded installation cable complies with the most stringent parameters with significant headroom for installation safety. Selected design goes hand-in-hand with the best quality which, with strictly controlled production, guarantees the highest performance. The shielded Category 7 installation cable is produced in S-STP configuration (PimF—Pair in metal foil) and is tested up to 900 MHz. Its excellent performance ensures full compatibility with all new high-speed data protocols, such as 10GBaseT. Foamed PE insulated conductors in the cable have the pairs shielded by aluminum foil (each pair separately) and copper braid (all four pairs). Sheath material is supported by fire retardant halogen free compound. Signamax Category 7 shielded installation cable complies with the latest standards as specified in EN 50173-1 and ISO/IEC 11801:2002.



BC7-4DS-HF

### Construction, Mechanical and Electrical Properties

Bending radius	
Minimum bending radius, installation	8 x D
Minimum bend radius, installed	4 x D

Tensile strength	
Maximum tensile load, installation	100 N
Maximum tension load, installed	No stretch

Temperature limits	
Installation	0° to +50°C
Operation	-20° to +60°C

Fire classification	
LSOH	IEC 60332-1

Heat release	
LSOH	500 MJ/km

Insulation resistance	> 5,000 MΩ/km
Resistance unbalance, maximum	2%
NVP	79%
Delay skew	20 ns/100 m
Diameter of copper conductor	AWG 23
Outer diameter	7.0 mm
Weight	65 kg/km



Transfer impedance, nominal IEC96-1	
1 MHz	1.1 MΩ/m
10 MHz	1.0 MΩ/m

### Transmission characteristics acc. to CAT 7 (at 20°C)

Frequency (MHz)	Attenuation, nom. (dB/100 m)	NEXT (dB)	ACR (dB)
1.00	1.9	118	116
10.00	5.8	105	99
16.00	7.1	100	93
20.00	8.0	99	91
31.25	10.0	98	88
62.50	14.7	94	79
100.00	18.5	90	71
300.00	29.0	83	54
600.00	48.7	77	28
750.00	54.0	75	21
900.00	57.0	74	17

### S-STP Category 7 Installation Cable

PART NO.	DESCRIPTION
BC7-4DS-HF	Category 7 S-STP Installation Cable, 500 m reels, LSOH

# Certificates 10GBaseT



## Certificate

<b>Description:</b>	Modular Jack	<b>Signamax</b> 10G Shielded Keystone Jack, Universal Wiring, T568A/B Part-No.: KJS458-10G
Data Cable 90m		<b>Signamax</b> Category 7 S-STP Installation Cable, LSOH Part-No.: BC7-4DS-HF

**Applied standards:** TIA/EIA-568-B.2-10 (Draft 7.0)  
Transmission performance specifications for 4-pair 100 Ω augmented category 6 cabling (Category 6A)

**Results:** Up to a bandwidth of **500MHz** the sample, a **2-Connector permanent Link**, meet the limits of the specified standards and regulations.

The test results which were determined in the course of the measurement refer to the submitted specimen. Any future technical modifications of the data cables or connectors are subject to the responsibility of the manufacturer.

This Certificate refers to the comprehensive test report, **no. P1750a 07-E, from August 06<sup>th</sup> 2007** and shall only be applicable in conjunction with the test report.

Bexbach, August 06<sup>th</sup> 2007

  
 Dirk Wilhelm, engineer  
 (Chairman of the Managing Board)



GHMT AG  
 In der Kolling 13  
 D-66450 Bexbach  
 Phone: +49 (0) 68 26 / 92 28 - 0  
 Fax: +49 (0) 68 26 / 92 28 - 99  
 E-Mail: info@ghmt.de  
 http://www.ghmt.de

---

GHMT Aktiengesellschaft

Signamax Permanent Link Certificate



## Certificate

<b>Description:</b>	Modular Jack	<b>Signamax</b> 10G Shielded Keystone Jack, Universal Wiring, T568A/B Part-No.: KJS458-10G
Patch Cord 2x5m		<b>Signamax</b> 10G Category 6A S-STP patch cable, grey, 5m Part-No.: CGA-315GY-SMB
Data Cable 90m		<b>Signamax</b> Category 7 S-STP Installation Cable, LSOH Part-No.: BC7-4DS-HF

**Applied standards:** TIA/EIA-568-B.2-10 (Draft 7.0)  
Transmission performance specifications for 4-pair 100 Ω augmented category 6 cabling (Category 6A)


ISO/IEC 11801 Amendment 1 JTC 1/SC N1055  
Information technology – Generic cabling for customer premises

**Results:** Up to a bandwidth of **500MHz** the sample, a **2-Connector Channel**, meet the limits of the specified standards and regulations.

The test results which were determined in the course of the measurement refer to the submitted specimen. Any future technical modifications of the data cables or connectors are subject to the responsibility of the manufacturer.

This Certificate refers to the comprehensive test report, **no. P1754a 07-E, from August 09<sup>th</sup> 2007** and shall only be applicable in conjunction with the test report.

Bexbach, August 09<sup>th</sup> 2007

  
 Dirk Wilhelm, engineer  
 (Chairman of the Managing Board)



GHMT AG  
 In der Kolling 13  
 D-66450 Bexbach  
 Phone: +49 (0) 68 26 / 92 28 - 0  
 Fax: +49 (0) 68 26 / 92 28 - 99  
 E-Mail: info@ghmt.de  
 http://www.ghmt.de


---

GHMT Aktiengesellschaft

Signamax Channel Certificate

## FTP Category 6 Installation Cable

Signamax Category 6 shielded installation cable BC6-4S is a high-performance data cable that is designed to meet the demands of today's most advanced voice and data networks. Category 6 cables support 1000Base-T/TX protocols for data rates up to 1 Gb/s and exceed the requirements of ANSI/TIA/EIA-568-B.2-1, ISO 11801:2002 and EN 50173-1:2002 standards. The Signamax Category 6 cable conductor is AWG 23 bare copper wire with high density polyethylene insulation. The non-metallic cross separator inside the cable ensures the best crosstalk elimination between individual pairs. The jacket of the BC6-4S horizontal cable is produced with PVC compound and its color is grey, the halogen-free version is also available.



### Mechanical Properties

Bending radius	≥ 20 mm without load ≥ 40 mm with load
Temperature range, during operation	-20° up to +60°C
during installation	0° up to +50°C

### Construction

Conductor	bare copper wire Ø 0.56 mm (AWG23)
Insulation	Polyethylene, Ø 1.0 mm
Twisting	2 cores to the pair

### Electrical Properties (at 20°C ± 5°C)

DC loop resistance	≤ 176 Ω/km
Resistance unbalance	≤ 2%
Insulation resistance (500 V)	≥ 5,000 MΩ *km
Capacitance at 800 Hz	nom. 48 nF/km
Capacitance unbalance (pair to ground)	≤ 1,500 pF/km
Characteristic impedance (1-100 MHz)	(100 ± 15) Ω
Characteristic impedance (1-100 MHz) (1-100 MHz)	(100 ± 15) Ω (100 ± 22) Ω
Nominal velocity of propagation	approx. 67%
Propagation delay	≤ 535 ns/100 m
Delay skew	≤ 20 ns/100 m
Test voltage (DC, 1 min)	
Core/Core and Core/Screen	1,000 V

### Transmission characteristics acc. to Category 6 (at 20°C)

f (MHz)	Attenuation (dB/100 m)		NEXT (dB)		ACR (dB/100 m)		Return loss (dB)
	max.	nom.	min.	nom.	min.	nom.	min.
1	2	2	74	90	71.8	88	23
4	3.8	3.8	65	89	61.2	85.2	23
10	6	6	59	89	53	82.8	23
16	7.6	7.6	56	86	48.4	78.1	23
20	8.5	8.5	55	84	46.5	75.8	23
31.2	10.7	10.7	52	81	41.3	70.7	23
62.5	15.5	15.1	47	77	31.5	61.8	23
100	19.9	19.1	44	74	24.1	54.7	23
125	22.5	21.3	43	72	20.5	51	21
155.5	25.4	23.8	42	71	16.6	47.1	21
175	27.1	25.3	41	70	13.9	44.9	21
200	29.2	27	40	69	10.8	42.3	21
250	33	32.6	38	68	5	35.2	19

### Technical Data


Product code	Outer diameter mm	Fire load MJ/km	kWh/m	Weight kg/km	Copper content kg/km	Tensile force N
BC6-4S	6.2	329	0.091	42	18	80

### FTP Category 6 Installation Cable

PART NO.	DESCRIPTION
BC6-4S	Category 6 FTP Installation Cable, 500 m reels, PVC
BC6-4S-HF	Category 6 FTP Installation Cable, 500 m reels, LSOH

# UTP Category 6 Installation Cable

Signamax Category 6 unshielded installation cable is designed to provide the highest level of transmission performance to meet the needs of today's most advanced voice and data networks. Category 6 cables support 10Base-T through 1000Base-T/TX protocols for data rates up to 1 Gb/s and exceed the requirements of TIA/EIA-568-B.2-1, ISO 11801:2002 and EN 50173-1 standards. The Signamax Category 6 cable conductor is AWG 23 bare copper wire with high density polyethylene insulation. The non-metallic cross separator inside the cable ensures the best crosstalk elimination between individual pairs.



## Mechanical Properties

Bending radius	≥ 20 mm without load ≥ 40 mm with load
Temperature range, during operation	-20° up to +60°C
during installation	0° up to +50°C

## Electrical Properties (at 20°C ± 5°C)

DC loop resistance	≤ 176 Ω/km
Resistance unbalance	≤ 2%
Insulation resistance (500 V)	≥ 5,000 MΩ *km
Capacitance at 800 Hz	nom. 48 nF/km
Capacitance unbalance (pair to ground)	≤ 1,500 pF/km
Characteristic impedance (1-100 MHz)	(100 ± 15) Ω
Characteristic impedance (1-100 MHz) (1-100 MHz)	(100 ± 15) Ω (100 ± 22) Ω
Nominal velocity of propagation	approx. 67%
Propagation delay	≤ 535 ns/100 m
Delay skew	≤ 20 ns/100 m
Test voltage (DC, 1 min)	
Core/Core and Core/Screen	1,000 V

## Construction

Conductor	bare copper wire Ø 0.56 mm (AWG23)
Insulation	Polyethylene, Ø 1.0 mm
Twisting	2 cores to the pair
Sheath	non metallic cross separator (spline) PVC

## Transmission characteristics acc. to CAT 6 (at 20°C)

f (MHz)	Attenuation (dB/100 m)		NEXT (dB)		ACR (dB/100 m)		Return loss (dB)
	max.	nom.	min.	nom.	min.	nom.	min.
1	2	2	74	90	71.8	88	23
4	3.8	3.8	65	89	61.2	85.2	23
10	6	6	59	89	53	82.8	23
16	7.6	7.6	56	86	48.4	78.1	23
20	8.5	8.5	55	84	46.5	75.8	23
31.2	10.7	10.7	52	81	41.3	70.7	23
62.5	15.5	15.1	47	77	31.5	61.8	23
100	19.9	19.1	44	74	24.1	54.7	23
125	22.5	21.3	43	72	20.5	51	21
155.5	25.4	23.8	42	71	16.6	47.1	21
175	27.1	25.3	41	70	13.9	44.9	21
200	29.2	27	40	69	10.8	42.3	21
250	33	32.6	38	68	5	35.2	19

## Technical Data

Product code	Outer diameter	Fire load		Weight	Copper content	Tensile force
	mm	MJ/km	kWh/m			
BC6-4	6.2	329	0.091	39	18	80


## UTP Category 6 Installation Cable

PART NO.	DESCRIPTION
BC6-4	Category 6 UTP Installation Cable, 500 m reels, PVC

Halogen free cable available on request.

## UTP Category 5E Installation Cable

The Category 5E unshielded installation cable is mostly used cable for data transmission where no electromagnetic disturbance is a problem. Supplied as part of complete Signamax Category 5E solution, the cable represents one of the key elements for safety and economical data transfer. Sophisticated cable design ensures very low electromagnetic emiteny and low crosstalk. All parameters exceed requirements specified by TIA/EIA 568-B.2-1, ISO/IEC 11801:2002, and EN 50173-1 standards. The Signamax Category 5E cables are suitable for the high-speed 1000BaseT Ethernet protocol. Sheath material is supported by fire retardant PVC and halogen free compound.



### Construction

Conductor	bare copper wire Ø 0.51 mm (AWG 24)
Insulation	Polyethylene, Ø 0.95 mm
Twisting	2 cores to the pair
Sheath	PVC alt. FRNC

### Mechanical Properties

Bending radius	≥ 20 mm without load ≥ 40 mm with load
Temperature range, during operation	-20° up to +60°C
during installation	0° up to +50°C

### Electrical Properties (at 20°C ± 5°C)

DC loop resistance	≤ 192 Ω/km
Resistance unbalance	≤ 2%
Insulation resistance (500 V)	≥ 2,000 MΩ *km
Capacitance at 800 Hz	nom. 48 nF/km
Capacitance unbalance (pair to ground)	≤ 1,500 pF/km
Characteristic impedance (1-100 MHz)	(100 ± 15) Ω
Nominal velocity of propagation	approx. 67%
Propagation delay	≤ 535 ns/100 m
Delay skew	≤ 20 ns/100 m
Test voltage (DC, 1 min)	
Core/Core and Core/Screen	1,000 V

### Transmission characteristics acc. to Category 5e (at 20°C)

f (MHz)	Attenuation (dB/100 m)		NEXT (dB)		ACR (dB/100 m)		Return loss (dB)
	max.	nom.	min.	nom.	min.	nom.	min.
1	2	1.9	65	71	63.3	69.1	23
4	3.9	3.7	56	62	52.4	58.3	23
10	6.3	6.0	50	56	44.0	50.0	23
16	8.0	7.6	47	53	39.3	45.3	23
20	9.0	8.5	46	51	36.8	43.0	23
31.2	11.4	10.7	43	49	31.5	37.9	23
62.5	16.5	15.7	38	44	21.9	28.4	23
100	21.3	19.8	35	41	14.0	21.2	23

### Technical Data

Product code	Outer diameter mm	Fire load		Weight kg/km	Copper content kg/km	Tensile force N
		MJ/km	kWh/m			
BC5E-4	5.9	336	0.093	35	17.5	80


### UTP Category 5E Installation Cable

PART NO.	DESCRIPTION
BC5E-4	Category 5E UTP Installation Cable, 305 m boxes, PVC

Halogen free cable available on request.

# FTP Category 5E Installation Cable

The Category 5E shielded installation cable is mostly used cable for data transmission where electromagnetic disturbance is a problem. Supplied as part of complete Signamax Category 5E solution, the cable represents one of the key elements for safety and economical data transfer. Sophisticated cable design ensures very low electromagnetic emityency and low crosstalk. All parameters exceed requirements specified by TIA/EIA 568-B.2-1, ISO/IEC 11801:2002, and EN 50173-1 standards. The Signamax Category 5E cables are suitable for the high-speed 1000BaseT Ethernet protocol.



## Construction

Conductor	bare copper wire Ø 0.51 mm (AWG 24)
Insulation	Polyethylene, Ø 0.95 mm
Twisting	2 cores to the pair
Sheath	PVC alt. FRNC

## Mechanical Properties

Bending radius	≥ 20 mm without load ≥ 40 mm with load
Temperature range, during operation	-20° up to +60°C
during installation	0° up to +50°C

## Electrical Properties (at 20°C ± 5°C)

DC loop resistance	≤ 192 Ω /km
Resistance unbalance	≤ 2%
Insulation resistance (500 V)	≥ 2,000 MΩ *km
Capacitance at 800 Hz	nom. 48 nF/km
Capacitance unbalance (pair to ground)	≤ 1,500 pF/km
Characteristic impedance (1-100 MHz)	(100 ± 15) Ω
Nominal velocity of propagation	approx. 67%
Propagation delay	≤ 535 ns/100 m
Delay skew	≤ 20 ns/100 m
Test voltage (DC, 1 min)	
Core/Core and Core/Screen	1,000 V

## Transmission characteristics acc. to CAT 5E (at 20°C)

f (MHz)	Attenuation (dB/100 m)		NEXT (dB)		ACR (dB/100 m)		Return loss (dB)
	max.	nom.	min.	nom.	min.	nom.	min.
1	2	1.9	65	71	63.3	69.1	23
4	3.9	3.7	56	62	52.4	58.3	23
10	6.3	6.0	50	56	44.0	50.0	23
16	8.0	7.6	47	53	39.3	45.3	23
20	9.0	8.5	46	51	36.8	43.0	23
31.2	11.4	10.7	43	49	31.5	37.9	23
62.5	16.5	15.7	38	44	21.9	28.4	23
100	21.3	19.8	35	41	14.0	21.2	23

## Technical Data


Product code	Outer diameter mm	Fire load		Weight kg/km	Copper content kg/km	Tensile force N
		MJ/km	kWh/m			
BC5E-4S	5.9	336	0.093	35	17.5	80

## FTP Category 5E Installation Cable

PART NO.	DESCRIPTION
BC5E-4S	Category 5E FTP Installation Cable, 305 m boxes, PVC


Halogen free cable available on request.

**NETWORK CONNECTIVITY SYSTEMS**





# Fiber Optic Systems



**Fiber Optic Patch Cords**

**Fiber Optic Adapters**

**Fiber Optic Patch Panels**

**Wall Mount Fiber Optic Box**

# Fiber Optic Patch Cords

Fiber optic patch cords are suited for equipment jumper cable, cross connects, and work area connections. All patch cords are manufactured using OFNR riser grade cable and are 100% factory tested to ensure performance to TIA/EIA-568-B-2, ISO 11801:2002 and EN 50173-1 standards. ST/ST, SC/SC and hybrid ST/SC Patch Cords are available in both multimode (62.5/125  $\mu\text{m}$  and 50/125  $\mu\text{m}$ ) and singlemode cable-types, in duplex and simplex versions.



## ST Fiber Optic Patch Cords

PART NO.	DESCRIPTION
FC-2/2-LM	ST to ST Duplex Multi Mode Patch Cord, 62.5/125
FC50-2/2-LM	ST to ST Duplex Multi Mode Patch Cord, 50/125
FC9-2/2-LM	ST to ST Duplex Single Mode Patch Cord, 9/125

For length substitute L in P/N.

1=1 meter      2=2 meters      3=3 meters      5=5 meters  
Other lengths and Simplex are available.




ST/ST Duplex

## SC Fiber Optic Patch Cords

PART NO.	DESCRIPTION
FC-4/4-LM	SC to SC Duplex Multi Mode Patch Cord, 62.5/125
FC50-4/4-LM	SC to SC Duplex Multi Mode Patch Cord, 50/125
FC9-4/4-LM	SC to SC Duplex Single Mode Patch Cord, 9/125

For length substitute L in P/N.

1=1 meter      2=2 meters      3=3 meters      5=5 meters  
Other lengths and Simplex are available.




SC/SC Duplex

## SC/ST Fiber Optic Patch Cords

PART NO.	DESCRIPTION
FC-4/2-LM	SC to ST Duplex Multi Mode Patch Cord, 62.5/125
FC50-4/2-LM	SC to ST Duplex Multi Mode Patch Cord, 50/125
FC9-4/2-LM	SC to ST Duplex Single Mode Patch Cord, 9/125

For length substitute L in P/N.


1=1 meter      2=2 meters      3=3 meters      5=5 meters  
Other lengths and Simplex are available.  
Other connectors on request.



ST/SC Duplex

# Fiber Optic Patch Cords

Signamax MTRJ and LC fiber optic patch cords suited for equipment jumper cable, cross connects, and work area connections. All patch cords are manufactured using OFNR riser grade cable and are 100% factory tested to ensure performance to TIA/EIA-568-B-3, ISO 11801:2002 and EN 50173-1 standards. MTRJ/MTRJ, LC/LC and hybrid MTRJ and LC to ST and SC multimode (62.5/125  $\mu\text{m}$  and 50/125  $\mu\text{m}$ ) patch cords are available.



LC/LC Duplex



LC/ST (SC) Duplex



MTRJ Duplex



ST/MTRJ Duplex



SC/MTRJ Duplex

## LC Fiber Optic Patch Cords

PART NO.	DESCRIPTION
FC-9/9-LM	LC to LC Duplex Multi Mode Patch Cord, 62.5/125
FC-9/2-LM	LC to ST Duplex Multi Mode Patch Cord, 62.5/125
FC-9/4-LM	LC to SC Duplex Multi Mode Patch Cord, 62.5/125
FC50-9/9-LM	LC to LC Duplex Multi Mode Patch Cord, 50/125
FC50-9/2-LM	LC to ST Duplex Multi Mode Patch Cord, 50/125
FC50-9/4-LM	LC to SC Duplex Multi Mode Patch Cord, 50/125

For length substitute L in P/N.

1=1 meter      2=2 meters      3=3 meters      5=5 meters

Other lengths are available.

## MTRJ Fiber Optic Patch Cords

PART NO.	DESCRIPTION
FC-8/8-LM	MTRJ to MTRJ Duplex Multi Mode Patch Cord, 62.5/125
FC-8/2-LM	MTRJ to ST Duplex Multi Mode Patch Cord, 62.5/125
FC-8/4-LM	MTRJ to SC Duplex Multi Mode Patch Cord, 62.5/125
FC50-8/8-LM	MTRJ to MTRJ Duplex Multi Mode Patch Cord, 50/125
FC50-8/2-LM	MTRJ to ST Duplex Multi Mode Patch Cord, 50/125
FC50-8/4-LM	MTRJ to SC Duplex Multi Mode Patch Cord, 50/125

For length substitute L in P/N.

1=1 meter      2=2 meters      3=3 meters      5=5 meters

Other lengths are available.

# Fiber Optic Adapters

SIGNAMAX Premise Connectivity System Fiber optic connectors are offered in wide range of types. All standard shapes are offered in both multimode and singlemode construction.

Signamax offers a wide variety of fiber optic adapters including ST, SC, LC and MTRJ. Our ST and SC adapters are available with a phosphor bronze sleeve for universal applications (MM/SM). All SC, LC and MTRJ adapters are provided with retaining clips for easy, snap-in mounting.




FA-ST

## ST Fiber Connectors and Adapters

PART NO.	DESCRIPTION
FC-ST-MM	ST MM Connector, Zirconia sleeve, crimping, 3.0 mm
FC-ST-SM	ST SM Connector, Zirconia sleeve, crimping, 3.0 mm
FA-ST02	ST MM/SM Adapter w/Phosphor Bronze Sleeve

Singlemode Adapter available on request.




FA-SC

## SC Fiber Connectors and Adapters

PART NO.	DESCRIPTION
FC-SC-MM	SC MM Connector, Phosphor bronze sleeve, crimping, 3.0 mm, Simplex
FC-SC-SM	SC SM Connector, Zirconia sleeve, crimping, 3.0 mm, Simplex
FA-SCD02-B	SC Duplex MM Adapter, Phosphor Bronze Sleeve, Beige
FA-SCD03-BU	SC Duplex SM Adapter, Zirconia Ceramic Sleeve, Blue

SM and Simplex Adapters available on request.



FA-LC

## LC Fiber Connectors and Adapters

PART NO.	DESCRIPTION
FC-LC-MM	LC MM Connector, Phosphor bronze sleeve, crimping, 3.0 mm, Simplex
FC-LC-SM	LC MM Connector, Zirconia sleeve, crimping, 3.0mm, Simplex
FA-LCD02-B	LC Duplex MM Adapter w/Phosphor Bronze Sleeve
FA-LCD03-B	LC Duplex SM Adapter, Zirconia Sleeve

SM available on request.



FA-MTRJ


## MTRJ Fiber Connectors and Adapters

PART NO.	DESCRIPTION
FC-MTM-MM	MTRJ MM Connector, Phosphor bronze sleeve, crimping, 3.0 mm, Male
FC-MTF-MM	MTRJ MM Connector, Phosphor bronze sleeve, crimping, 3.0 mm, Female
FC-MTM-SM	MTRJ MM Connector, Zirconia sleeve, crimping, 3.0 mm, Male
FC-MTF-SM	MTRJ MM Connector, Zirconia sleeve, crimping, 3.0 mm, Female
FA-MTRJ-B	MTRJ MM/SM Adapter

## Fiber Optic Pigtails

PART NO.	DESCRIPTION
FC50-PI-ST-2m	Pigtail 2m ST 50/125 $\mu$ m
FC50-PI-SC-2m	Pigtail 2m SC 50/125 $\mu$ m
FC50-PI-LC-2m	Pigtail 2m LC 50/125 $\mu$ m
FC-PI-ST-2m	Pigtail 2m ST 62.5/125 $\mu$ m
FC-PI-SC-2m	Pigtail 2m SC 62.5/125 $\mu$ m
FC-PI-LC-2m	Pigtail 2m LC 62.5/125 $\mu$ m

Other lengths and accessories (splice tray, fusion protector) available on request.



Pigtail SC

# Fiber Optic Patch Panels

Signamax 19" Rack mountable fiber optic patch panel is designed for direct fiber optic cables termination. Standard size is 1U. The patch panel is modular and contains two parts—body and faceplate for several adapter types and count. Panel has fully metal massive construction for usage in critical environments and can be easily pulled out with no need to be dismantled from the rack. Rear section accommodates cable entry and cable holder that protects cables against damage.




FP-1U

## Fiber Optic Patch Panels

PART NO.	DESCRIPTION
FP-1U	Fiber optic patch panel without face plate 1U
FP-12ST-1U	1U face plate for fiber optic patch panel for 12 ST adapters
FP-16ST-1U	1U face plate for fiber optic patch panel for 16 ST adapters
FP-24ST-1U	1U face plate for fiber optic patch panel for 24 ST adapters
FP-12SCD-1U	1U face plate for fiber optic patch panel for 12 duplex SC adapters
FP-16SCD-1U	1U face plate for fiber optic patch panel for 16 duplex SC adapters
FP-24SCD-1U	1U face plate for fiber optic patch panel for 24 duplex SC adapters
BPE-SC-3-01	Blank plate SC duplex

Colour grey RAL 7035



Face plates

# Wall Mount Fiber Optic Box

Signamax Wall Mount Fiber Optic Box is used for the direct termination of fibers. The rear section accommodates cable entry and protects against taking out the cables. Box includes two separate sections for fusion splice trays and for routing optical patch cords to the equipment. Box is fitted with two locks with different keys. The Signamax four-rack space fiber optic enclosure contains all of the features of the two-rack space model, but with additional capacity to manage fiber counts up to 144. Cable entry/exit feature utilizes a flexible grommet seal, which is cut at time of installation to accommodate the desired cable diameters for entry and exit points. These grommets provide a dust & debris barrier during and after installation.




RA2-FO-A05

## Wall Mount Fiber Optic Box


PART NO.	DESCRIPTION
RA2-FO-A05	Wall mounted fiber optic box without accessories
RA-FO-24ST	Panel for RA2-FO-A05 and for 24 ST adapters
RA-FO-24SC	Panel for RA2-FO-A05 and for 24 SC adapters
RA-FO-12ST	Panel for RA2-FO-A05 and for 12 ST adapters
RA-FO-12SC	Panel for RA2-FO-A05 and for 12 SC adapters

Colour grey RAL 7035




Panels

# NETWORK CONNECTIVITY SYSTEMS





## Data Racks



**N M**

**19" Data Racks**

**19" Server Racks**

**19" Wall Mounted Racks**

**19" Mounted Rack Signamax**

**19" Assembled Data Racks**

**19" Fan Units**

**19" Shelves**

**Diode Lighting Unit**


**Accessories**

# 19" Data Racks

Attractive design and high quality are hallmarks of these data racks. Their basic framework is welded metal plate, multiple-bent for the strength and rigidity necessary for heavier equipment. All profile moldings are flexible and adjustable. Vent slots in the upper or lower cabinetry allow airflow for efficient cooling. The door is made of safety glass, and can be mounted for either left or right-hand opening on either the front or rear of the data rack. The side-walls and door are assembled and provided with ground straps. These data racks can also be interconnected into sets, for larger switch or server rooms.



1. Skeleton
2. Glass door (right-or left-hand) (three-point bar locking)
3. Flush door (upon request only) (right-or left-hand) (three-point bar locking)
4. Side cover
5. Rear cover (right-or left-hand) (three-point bar locking)
6. Cable opening
7. Ceiling cover
8. Cross bar
9. 19" Frame
10. Filter (both in the bottom and the ceiling)
11. Adjustable feet
12. Travel wheels (upon request only)
13. Roof cover



#### Fan units

Can be mounted in the lower and/or the upper part of the enclosure without effecting available rack space. Dust filter included.

#### Wheels

Four wheels, two of which are adjustable. (available on request)

#### Supply includes

4 adjustable feet, Brush insert (foam insert), Door lock including set of 2 keys.

#### Colour and material

1.4 mm sheet steel, shaded 4 mm safety glass. Grey colour (RAL 7035), black colour (RAL 9005).

#### Adjustable feet

All feet can be adjusted up to 20 mm to compensate for uneven floors and assure high stability.

#### Door lock

Adjustable 3-point lock on the front door.

#### Front and side access

The door and sidewalls can be easily removed.

#### Cable entry

Via the slot in the lower back side and through the top of the rack, either through brushes or gasket foam. Entry from the top of the rack is available on special request.

#### Profile moldings

Four profile moldings are easily adjustable.

19" Data Racks

PART NO.	DESCRIPTION
REC-6156B	19" Rack Signamax, height 15U, width and depth 600 mm
REC-6186B	19" Rack Signamax, height 18U, width and depth 600 mm
REC-6246B	19" Rack Signamax, height 24U, width and depth 600 mm
REC-6286B	19" Rack Signamax, height 28U, width and depth 600 mm
REC-6326B	19" Rack Signamax, height 32U, width and depth 600 mm
REC-6386B	19" Rack Signamax, height 38U, width and depth 600 mm
REC-6426B	19" Rack Signamax, height 42U, width and depth 600 mm
REC-6456B	19" Rack Signamax, height 45U, width and depth 600 mm

PART NO.	DESCRIPTION
REC-6288B	19" Rack Signamax, height 28U, width 600 mm, depth 800 mm
REC-6328B	19" Rack Signamax, height 32U, width 600 mm, depth 800 mm
REC-6388B	19" Rack Signamax, height 38U, width 600 mm, depth 800 mm
REC-6428B	19" Rack Signamax, height 42U, width 600 mm, depth 800 mm
REC-6458B	19" Rack Signamax, height 45U, width 600 mm, depth 800 mm

PART NO.	DESCRIPTION
REC-8288B	19" Rack Signamax, height 28U, width and depth 800 mm
REC-8328B	19" Rack Signamax, height 32U, width and depth 800 mm
REC-8388B	19" Rack Signamax, height 38U, width and depth 800 mm
REC-8428B	19" Rack Signamax, height 42U, width and depth 800 mm
REC-8458B	19" Rack Signamax, height 45U, width and depth 800 mm

PART NO.	DESCRIPTION
REC-6421B	19" Rack Signamax, height 42U, width 600 mm and depth 1,000
REC-8421B	19" Rack Signamax, height 42U, width 800 mm and depth 1,000

PART NO.	DESCRIPTION
REC-8286B	19" Rack Signamax, height 28U, width 800 mm, depth 600 mm
REC-8326B	19" Rack Signamax, height 32U, width 800 mm, depth 600 mm
REC-8386B	19" Rack Signamax, height 38U, width 800 mm, depth 600 mm
REC-8426B	19" Rack Signamax, height 42U, width 800 mm, depth 600 mm
REC-8456B	19" Rack Signamax, height 45U, width 800 mm, depth 600 mm



Side wall hinge



Bottom part



Metal handle



Door hold

## 19" Server Racks

Signamax 19" Server Racks are especially suitable for server installation, but all other 19" components and accessories can be installed as well. Back of the rack is perforated and allows higher air flow. All other attributes are identical with regular Signamax 19" Data Racks (see page M1).



### 19" Server Racks

PART NO.	DESCRIPTION
RECS-6421B	19" Server Rack Signamax, height 42U, width 600 mm, depth 1,000 mm, bottom end top cable entry
RECS-8421B	19" Server Rack Signamax, height 42U, width 800 mm, depth 1,000 mm, bottom end top cable entry

# 19" Wall Mounted Racks

Vent slots in the upper and lower part of the Signamax Wall Mounted Data Rack allow sufficient airflow inside. Can be mounted upside-down, enabling the door to be opened from the left or right. Wall section can be directly hinged on the wall or by means of a fixed frame. Front door is made of safety glass. The rack is lockable. Center section lock system can be unlocked separately.



## 19" Wall Mounted Racks – not divided

PART NO.	DESCRIPTION
RECW-044B	Signamax 19" Wall Mounted Rack, height 4U, depth 400 mm
RECW-064B	Signamax 19" Wall Mounted Rack, height 6U, depth 400 mm
RECW-094B	Signamax 19" Wall Mounted Rack, height 9U, depth 400 mm
RECW-124B	Signamax 19" Wall Mounted Rack, height 12U, depth 400 mm
RECW-154B	Signamax 19" Wall Mounted Rack, height 15U, depth 400 mm
RECW-184B	Signamax 19" Wall Mounted Rack, height 18U, depth 400 mm
RECW-214B	Signamax 19" Wall Mounted Rack, height 21U, depth 400 mm

## 19" Wall mounted racks – divided

PART NO.	DESCRIPTION
RECW-065B	Signamax 19" Wall Mounted Rack, height 6U, depth 500 mm
RECW-095B	Signamax 19" Wall Mounted Rack, height 9U, depth 500 mm
RECW-125B	Signamax 19" Wall Mounted Rack, height 12U, depth 500 mm
RECW-155B	Signamax 19" Wall Mounted Rack, height 15U, depth 500 mm
RECW-185B	Signamax 19" Wall Mounted Rack, height 18U, depth 500 mm
RECW-215B	Signamax 19" Wall Mounted Rack, height 21U, depth 500 mm

*Cable entry: From the top, bottom or the back of the data rack.*

*Ground strap: Four ground straps are mounted.*

*Colour and Material:*


*RAL 7035, 1.4 mm sheet steel, shaded 4 mm safety glass. Black colour (RAL 9005) available on request.*

# 19" Assembled Data Rack

The Signamax Assembled Rack is suitable for installation of structured cabling components—e.g. patch panels, active equipment and telecommunication cabling components. The design of the rack is accommodated to fit most computing and data centers.

## Rack Description

This 19" Assembled Data Rack consists of assembled skeleton. The front side door is mounted using three hinges and secured by 1-point lock. The safety glass used in the door assembly provides high safety. The removable back and side covers are locked and can be opened with a key that is provided with the rack. The cable entry is located under the back cover. The side and back covers are swappable. In the bottom and ceiling, slots for optional fan installation are provided. These racks can be attached together to form groups. The surface is treated with pulverized color for internal environment (for external environment on request only) according to RAL color scale. Standard color is grey (RAL 7035) and black (RAL 9005).



### Standard package contains:

- |                             |                                    |
|-----------------------------|------------------------------------|
| 1. Bottom                   | 7. Guide                           |
| 2. Ceiling                  | 8. Glass Door(right- or left-hand) |
| 3. Ceiling and Bottom Cover | 9. Side Cover                      |
| 4. Bars                     | 10. Rear Cover                     |
| 5. Cross Bar                | 11. Cable Entry                    |
| 6. 19" Frame                | 12. Adjustable Feet                |

### Non-standard components (on request only)

- Full Door
- Perforated Door
- Perforated Side Cover
- Perforated Back Cover
- Travel Wheels

Table of standard Rack dimensions

PART NO.	DESCRIPTION
RECA-6156B	19" Assembled Signamax Rack, height 15U, depth and width 600 mm
RECA-6186B	19" Assembled Signamax Rack, height 18U, depth and width 600 mm
RECA-6246B	19" Assembled Signamax Rack, height 24U, depth and width 600 mm
RECA-6286B	19" Assembled Signamax Rack, height 28U, depth and width 600 mm
RECA-6326B	19" Assembled Signamax Rack, height 32U, depth and width 600 mm
RECA-6386B	19" Assembled Signamax Rack, height 38U, depth and width 600 mm
RECA-6426B	19" Assembled Signamax Rack, height 42U, depth and width 600 mm
RECA-6456B	19" Assembled Signamax Rack, height 45U, depth and width 600 mm
RECA-6288B	19" Assembled Signamax Rack, height 28U, depth 800 mm, width 600 mm
RECA-6328B	19" Assembled Signamax Rack, height 32U, depth 800 mm, width 600 mm
RECA-6388B	19" Assembled Signamax Rack, height 38U, depth 800 mm, width 600 mm
RECA-6428B	19" Assembled Signamax Rack, height 42U, depth 800 mm, width 600 mm
RECA-6458B	19" Assembled Signamax Rack, height 45U, depth 800 mm, width 600 mm
RECA-8288B	19" Assembled Signamax Rack, height 28U, depth and width 800 mm
RECA-8328B	19" Assembled Signamax Rack, height 32U, depth and width 800 mm
RECA-8388B	19" Assembled Signamax Rack, height 38U, depth and width 800 mm
RECA-8428B	19" Assembled Signamax Rack, height 42U, depth and width 800 mm
RECA-8458B	19" Assembled Signamax Rack, height 45U, depth and width 800 mm
RECA-8286B	19" Assembled Signamax Rack, height 28U, depth 600 mm, width 800 mm
RECA-8326B	19" Assembled Signamax Rack, height 32U, depth 600 mm, width 800 mm
RECA-8386B	19" Assembled Signamax Rack, height 38U, depth 600 mm, width 800 mm
RECA-8426B	19" Assembled Signamax Rack, height 42U, depth 600 mm, width 800 mm
RECA-8456B	19" Assembled Signamax Rack, height 45U, depth 600 mm, width 800 mm
RECA-6421B	19" Assembled Signamax Rack, height 42U, depth 1,000, width 600 mm
RECA-8421B	19" Assembled Signamax Rack, height 42U, depth 1,000, width 800 mm



Skeleton detail – inside assembly



1-point door lock



Skeleton detail – outside assembly


## 19" Fan Units

Signamax 19" Fan Units are constructed to fit into all Signamax 19" Data Racks, to provide forced airflow inside. Fits in lower as well as in the upper part of the rack. Standard and recommended installation is in the lower part of the rack to ensure a proper "chimney-effect", which supplies the rack with fresh air. Fan units allow airflow of up to 160 m<sup>3</sup>/hour. All fan units are equipped with a thermostat to regulate the airflow for temperatures in the range of 0° to 60°C. Fan units can be deactivated by using the main switch.



REC-RMFT150B

REC-RMFT2B



REC-RMFT3B



REC-RMFT3B-IN



REC-RMFT30B

### 19" Fan Units with Thermostat

PART NO.	DESCRIPTION
REC-RMFT2B-IN	19" Fan unit 2x fan with inbuild thermostat
REC-RMFT3B-IN	19" Fan unit 3x fan with inbuild thermostat
REC-RMFT30B	Side wall Fan unit 3x fan
REC-RMFT70B	Lower/Upper Fan unit 2x fan
REC-RMFT150B	Lower/Upper Fan unit 4x fan

Colour grey (RAL 7035). Black (RAL 9005) available on request.

# 19" Shelves

Signamax shelves for keyboard, documentation and LCD monitor are designed for the installation into the 19" data rack profiles. Shelves with lockable drawers for safe stowage of service documentation and shelves with an integrated computer keyboard and monitor occupy the space of 1U. This gives you more room in the data rack.



Documentation shelf opened



## Keyboard and documentation shelves

PART NO.	DESCRIPTION
REC-SV-DOC	1U documentation shelf with lock
REC-SV-KB	Keyboard shelf 1U
REC-SV-KBM	Shelf for keyboard and LCD monitor, 1U

Colour grey (RAL 7035). Black (RAL 9005) available on request.



Keyboard shelf opened




Keyboard shelf closed


## 19" Shelves

Signamax 19" shelves are convenient for equipment not designed for 19" installations. Our product range includes shelves for fixed and drawer-style installations. Drawer-style system enables easier access to the equipment being used. Ventilated bottom assures cooling airflow to the equipment. Shelf supports and mounting brackets are included.

Fixed shelves are available in depths from 150 mm to 550 mm.  
Sliding shelves are available in depths from 250 mm to 450 mm.



REC-SV15B




REC-SV35B

### 19" Shelves

PART NO.	DESCRIPTION
REC-SV15B	Shelf, 150 mm depth, 1U
REC-SV25B	Shelf, 250 mm depth, 1U
REC-SV35B	Shelf, 350 mm depth, 1U
REC-SV45B	Shelf, 450 mm depth, 1U
REC-SV55B	Shelf, 550 mm depth, 1U
REC-SV65B	Shelf, 650 mm depth, 1U
REC-TSV25B	Drawer-style Shelf, 250 mm depth, 1U
REC-TSV35B	Drawer-style Shelf, 350 mm depth, 1U
REC-TSV45B	Drawer-style Shelf, 450 mm depth, 1U

Colour grey (RAL 7035). Black (RAL 9005) available on request.



REC-TSV45B

# 19" Diode Lighting Unit

The 19" diode lighting unit is constructed as a compact fixture designed for installation into 19" distribution board frames for illumination of equipment installed within distribution board. The ON/OFF pushbutton and the LED-signaling that indicates On/Off state are located on the face of the unit. The rear side is equipped with a socket for power feed. The underside of the unit is fitted with the line of LED—i.e. the light is directed downwards. The unit is movable in its holders forward or backward in order to set the optimal illumination direction.



## Diode Lighting Unit

PART NO.	DESCRIPTION
REC-LU-LED-BK	Diode Lighting Unit 1U black, RAL 9005
REC-LU-LED	Diode Lighting Unit 1U grey, RAL 7035

### MAIN CHARACTERISTICS

- High illuminating power
- Low electric power consumption
- Long lifespan
- Very low heat radiation

### TECHNICAL DATA

**Dimensions (W x H x D):** 483 x 44 x 125 mm  
**Mass:** 3 kg without connecting cable  
**Voltage system:** 1NPE, 230 V, 50/60 Hz, TN-S  
**Current:** 0.06A maximum  
**Power supply:** 15W maximum

## Accessories

These base frames are suitable for all Signamax data racks and are used for fixing the rack to the floor to assure stability. Cable inlets placed on each side of the base are covered by a filter grid. Filter grid can be removed to insert cables inside. Adjustable feet for 19" Data racks are to compensate for uneven floors and to assure high stability.



REC-RB-66BF



REC-CB

### Blanking panels

PART NO.	DESCRIPTION
EPP-BL1	Blank panel 1U, RAL 7035
EPP-BL2	Blank panel 2U, RAL 7035
EPP-BL3	Blank panel 3U, RAL 7035
EPP-BL4	Blank panel 4U, RAL 7035
EPP-BL6	Blank panel 6U, RAL 7035



REC-LU

### Base frames

PART NO.	DESCRIPTION
REC-RB-66BF	Rack Base Frame, 600 x 600 x 100 mm, 4 filters, RAL 7035
REC-RB-68BF	Rack Base Frame, 600 x 800 x 100 mm, 4 filters, RAL 7035
REC-RB-88BF	Rack Base Frame, 800 x 800 x 100 mm, 4 filters, RAL 7035
REC-RB-66-20	Rack Base Frame, 600 x 600 x 200 mm, 4 filters, RAL 7035
REC-RB-88-20	Rack Base Frame, 800 x 800 x 200 mm, 4 filters, RAL 7035



REC-MLU

### Accessories


PART NO.	DESCRIPTION
REC-FPPF-4	Mounting Kit M5 4pcs set
REC-FPPF-20	Mounting Kit M5 20pcs set
REC-FPPF-50	Mounting Kit M5 50pcs set
REC-LU	19" Light unit, 1U, 3 halogen lights, black colour
REC-MLU	Lighting unit fluorescent, mounting by magnet, RAL 7035
REC-CB	Signamax Racks Wheels, set of 4 pieces
REC-CCK	Racks connecting kit (incl. screws and nuts)
REC-LOCK	Half cylinder for the plastic lock




REC-CCK

# Accessories

Ring brackets are used for organizing cables inside of the enclosure. Cables are organized by vertical or horizontal organizer brackets. Two mounting sets allow multiple placement possibilities within the data rack. Metal brackets have a polished surface texture. 19" cable organizer with 5 plastic rings and side protection is designed for easy and fast management of patch cords and other cables.




EPCM2-4/8



EPCM4-4/8

## Cable Management Ring Brackets

PART NO.	DESCRIPTION	A	B
EPCM1-4/4	Cable management bracket 40 x 40 mm	40	40
EPCM1-4/8	Cable management bracket 40 x 80 mm	80	40
EPCM1-8/8	Cable management bracket 80 x 80 mm	80	80
EPCM2-4/4	Cable management bracket 40 x 40 mm	40	40
EPCM2-4/8	Cable management bracket 40 x 80 mm	80	40
EPCM2-8/8	Cable management bracket 80 x 80 mm	80	80
EPCM3-4/4	Cable management bracket 40 x 40 mm	40	40
EPCM3-4/8	Cable management bracket 40 x 80 mm	80	40
EPCM3-8/8	Cable management bracket 80 x 80 mm	80	80



REC-VP1

## Cable Organizer

PART NO.	DESCRIPTION
EC-VP1	Cable organizer 1U, with plastic rings, grey
REC-MCO-S60	Multi cable organizer, side mounting, 600 mm, RAL 7035
REC-MCO-S80	Multi cable organizer, side mounting, 800 mm, RAL 7035
REC-MCO-S100	Multi cable organizer, side mounting, 1,000 mm, RAL 7035
REC-MCO-F60	Multi cable organizer, front mounting, 600 mm, RAL 7035
REC-MCO-F80	Multi cable organizer, front mounting, 800 mm, RAL 7035
REC-MCO-F100	Multi cable organizer, front mounting, 1,000 mm, RAL 7035



REC-MCO-S60

**NOTES**





# References

ABB elektro Zilina (Slovakia)  
 Adelphia Cable (USA)  
 Air Jamaica (USA)  
 Augusta National Golf Club (USA)  
 AVEX Oravska Lesna (Slovakia)  
 Axton (Slovakia)  
 Bayern Chemie (Germany)  
 Bechtel Corporation (USA)  
 CASINO Austria (Austria)  
 Catholic University (Slovakia)  
 CCR-Princeton (USA)  
 CEZ (Czech republic)  
 Comcast Cable (USA)  
 Constantin University (Slovakia)  
 Depository Trust (USA)  
 eBanka (Czech republic)  
 Federal Bureau of Investigation (USA)  
 Federal Reserve Bank (USA)  
 Florida Department of Transportation (USA)

Fort Lauderdale International Airport (USA)  
 GTS (Czech republic)  
 Hilton-Wien (Austria)  
 Hospice of Marion County (USA)  
 Illinois National Bank (USA)  
 John F. Kennedy International Airport (USA)  
 Kia Motors Zilina (Slovakia)  
 Lidl (Germany)  
 Liquec Nitra (Slovakia)  
 Lockheed Martin Corporation (USA)  
 Miami Children's Hospital (USA)  
 Muckleshoot Indian Casino (USA)  
 Nestle (USA)  
 PepsiCola (USA)  
 Philadelphia International Airport (USA)  
 PPS Detva (Slovakia)  
 Prague International Airport (Czech republic)  
 Public schools (Germany)

Raven (Slovakia)  
 Remi (Germany)  
 Salt Lake City International Airport (USA)  
 SBC Telecom (USA)  
 Slovak Embassy Rome (Italy)  
 Social Insurance Company Poprad (Slovakia)  
 SPP Kosice (Slovakia)  
 Sprint (USA)  
 Stadtverwaltung DGF (Germany)  
 The May Company (USA)  
 Time Warner Cable (USA)  
 T-mobil Austria (Austria)  
 Twin City Foods (USA)  
 U.S. Navy (USA)  
 UNIQUA Insurance Company (Austria)  
 United Parcel Service (USA)  
 University of Denver (USA)  
 University of North Carolina (USA)  
 Verizon (USA)  
 Yakima Legends Casino (USA)

# Certificates



YOUR DISTRIBUTOR