

### MODELS

Compaq P1210 CRT Monitor  
210290-xxx

Note: AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability.

### SPECIFICATIONS

Type	Color auto- scanning with Digital Control			
Picture Tube (diagonal)	22 in/56 cm Diamondtron NF CRT			
Viewable (diagonal)	20 in/51 cm			
Pitch	0.24 mm Aperture Grill Pitch			
Graphic Preset Modes	1920 x 1440	1792 x 1344	1600 x 1200	1280 x 1024
	80 Hz/60 Hz, 75 Hz	85 Hz/60 Hz, 75 Hz	95 Hz/75 Hz, 85 Hz	110 Hz/60 Hz, 75 Hz, 85 Hz
	1024 x 768	800 x 600	640 x 480	
	145 Hz/75 Hz, 85 Hz	160 Hz/75 Hz, 85 Hz	160 Hz/60 Hz, 85 Hz	
Note: All modes are non-interlaced unless specified otherwise. V Frequency shown Maximum/Presets.				
Text Mode	720 x 400			
	70 Hz			
Mac Compatible Modes	1152 x 870			
	75 Hz			
Note: Adapter required.				
User-Programmable Modes	18 (9 Preset Modes and 9 Pre-loads)			
Anti-Glare/Anti-Reflection/Anti-Static	Yes/Yes/Yes			
Plug and Play	Yes			
Plug and Play Protocol	DDC1/2B			
Dual Video Inputs	Yes			
Approvals/Certifications	MPR-II (Low Emissions)	Yes		
	TCO-99	Yes		
	Energy Star Compliant	Yes		
	UL Listing	Yes		
	ISO9241-3 VOT Guidelines Approval	Yes		
	FCC Approval	Yes		
	CE Mark (including PFC)	Yes		
GS Mark	Yes			
Analog Controls	No			
	Brightness, Contrast	Yes		
On-Screen Controls	Yes			

# COMPAQ

### SPECIFICATIONS *(continued)*

Language Selection	English	Yes
	Spanish	Yes
	French	Yes
	German	Yes
	Dutch	No
	Italian	Yes
	Japanese	Yes
User Controls	Sizing and Positioning	Yes
	Pincushion	Yes
	Pincushion Balance	Yes
	Trapezoid	Yes
	Tilt (rotation)	Yes
	Color temperature	Yes
	Degauss	Yes
	Parallelogram	Yes
	Individual color control	Yes
	Zoom	Yes
	Moiré Cancellation	Yes
	Convergence	Yes
	Factory Reset	Yes
Corner Purity Adjustment	Yes	
AssetControl	Yes	
	<i>Note: When used with Compaq Intelligent Manageability CPUs and appropriate network software.</i>	
Pixel Clock Frequency (maximum)	340 MHz (2048 x 1536, 75 Hz, 120 kHz)	
Input Impedance	75 ohms	
Horizontal Frequency	30 to 121 kHz	
Vertical Frequency	50 to 160 Hz	
Power Supply	90 to 260 VAC	
Maximum Power Rating	155 W	
USB Capabilities	Built-in; 1 upstream, 3 downstream	
Synchronized Input	Separate H, V synchronized	
Signal Cable	Detachable 15-in D-sub to 15-pin D-sub cable. Two D-sub connectors on monitor	
Maximum Phosphorus Size	16 x 12 in/406.1 x 304.6 mm (20 in/507.6 mm diagonal)	
Dimensions (HxWxD)	19.7 x 19.7 x 19 in/500 x 500 x 482 mm	
Weight	66 lbs/30 kg	
Temperature	Operating	50° to 95° F/10° to 35° C
	Non-operating	-4° to 140° F/-20° to 60° C

---

### SPECIFICATIONS *(continued)*

Humidity	Operating	20% to 80%
	Non-operating	10% to 95%
Warranty	Three-year parts, three-year on-site labor, or next business day direct replacement	
	<a href="#">Note: Certain restrictions apply. Consult the Compaq Customer Service Support Center for details.</a>	

---

---

### COMPATIBILITY

---

#### Graphics Controllers

3Dlabs Oxygen GVX1  
3Dlabs OXYGEN VX1-16 (PCI)  
3Dlabs OXYGEN VX1-32 (AGP)  
ATI Mobility P  
ATI RAGE PRO TURBO 2X  
Compaq Powerstorm 300 (PCI)  
Compaq Powerstorm 350 (PCI)  
Diamond Viper V730  
Diamond Viper V770 Ultra  
ELSA GLoria II  
ELSA GLoria Synergy (PCI)  
ELSA Synergy II  
Intense3D Wildcat™ 4110  
Matrox Millennium II  
Matrox Millennium G100 (AGP)  
Matrox Millennium G200 (PCI)  
Matrox Millennium G400  
Matrox Millennium G450 (AGP and PCI)  
NVIDIA GeForce 2 GTS  
NVIDIA GeForce 256  
NVIDIA TNT2 M64  
NVIDIA TNT2 Pro  
NVIDIA Vanta  
RAGE ATI lic  
S3 VIRGE/MX (AGP)  
Velocity 4000

---

#### Chipsets

Intel 810e  
Intel 815  
Intel 815e

---