




QUOTATION

Everest Emergency Vehicles, Inc.
 Bob Haselman
 1133 Rankin Street Suite D-1
 St. Paul, MN 55116
 651-236-8944
 651-690-1871
 bob.haselman@everestev.com



Quote No: REV 7-3-1813
 Job/Order No: 6401
 07/30/2013 11:00:59

PART NO	S	DESCRIPTION	QTY
		== Road Rescue Boilerplate - 2013.003 01/02/13 ==	1
00-01-0999		Information - Scope, Purpose and Classification	1
		WARRANTY	1
00-02-8100		Warranty - Documentation	1
00-02-8200		Warranty - Module Structural	1
00-02-8300		Warranty - Electrical, Standard System	1
00-02-8400		Warranty - Paint	1
00-02-8500		Warranty - Conversion	1
		== Ford, F-Series, 189" WB - 168" Bodies - 2013.003 01/02/13 ==	1
		01- CHASSIS REQUIREMENTS	1
01-01-2401	S < >	2011 Ford F450 XLT 4X4, 108" C/A, 189"W/B, 16,500 GVWR (SO.CHASS.6401)	1
		Motorcraft alternator- 200 amp and 157 amp, 4.10 limited slip wide track rear axle, 4-wheel ABS, Lever activated 4X4, block heater, cruise control, power windows, power door locks, driver/passenger air bag, 40/20/40 bench seat, AM/FM with cd player, daytime running lights, adjustable brake and accelerator pedals, manual telescoping heated/power mirrors, OEM rubber floor, spare tire, Requires fuel fill for DEF tank located on the street side of the module just forward of the rear wheels and the installation of a hose/line Heat/AC system with expansion Valve. Install a CAN Vehicle Controller Module (CVC501-A) will also be added to the chassis to allow the rear Heat/AC to operate independent from the front. This is due to the 2012 F-450 chassis configuration (Q-195) ***Includes the Kelderman Air Suspension W/Electric Valve Control Package, Air Dryer, Heated Spitter Valve and Rear Sway-Bar***** Ref Truck Number 6355 for SR.	
		(ULTAMEDIC)	
		CHASSIS OPTIONS	1
01-03-1001		Alternator - Standard OEM	1
01-07-0120		Front Suspension - Ford F-Series (4x4)	1
01-07-1000		Sway Bar, Front - OEM	1
01-07-6410	< >	Rear Suspension - Kelderman, Ford F-Series With air dryer, std with Kelderman air suspension	1
01-07-9025	<	Air Dump W/Enable SW moved to rear doors, For Air Suspension Dump feature to be activated by the left rear entry door. With the enable switch in the "on" position. Switch to be mounted on the curbside rear entry door on the lock box. When enable switch is de-activated the air dump will not work. Ignition switch hot, std.	1
		Safety Triggers: (1) Dump switch to be 'on' position (2) Vehicle Must be in Park (3) Emergency Brake must be set (4) Module is to be in the 'On' position (5) Open Street side rear entry door	

PART NO	S	DESCRIPTION	QTY
01-17-5100	<	Block Heater Switch - Wired to Shoreline The chassis shall include a 110VAC powered engine block heater. The block heater shall be wired to the module shoreline system and will include an OEM disconnect located in the engine compartment. In the driver seat area, there shall be an On/Off switch with pilot light for the engine block heater, powered from shore. Switch shall be mounted behind the drivers seat on floor close to side wall and will have a "Block Heater Switch" plaque.	1
CAB EXTERIOR OPTIONS			1
01-20-0100		Mirrors - OEM Standard	1
CAB INTERIOR OPTIONS			1
01-21-3500		Cab Insulation - Thinsulate in Cab Ceiling (STANDARD)	1
01-21-5000	<	Rear View Mirror - Upgrade, Auto Dimming, Compass,Temp & Homelink The vehicle shall be equipped with a Night Vision Safety mirror that includes auto dimming, integrated compass, outside temperature gauge and three button programmable garage door opener. The mirror will mount on the OEM windshield in place of the OEM rear view mirror.	1
TIRES / WHEELS			1
01-23-4100	>	Spare Tire Bracket - Delete	1
01-24-2003		SS Wheel Simulators - Phoenix Brand w/ Lug Nut covers, F-Series	1
== Type 1 - UM 168" Module, F-Series - 2013.003 01/02/13 ==			1
02-01-7000	S < >	Ultramedic - 174"L x 96"W Type 1, crawl/-Though Module 13-3 REF truck # 6355 Ultramedic I - 174"L x 96"W Type I Crawl-Through Module. Aisle width to be 46". The interior headroom shall be 72" NOTE: 6 inches added to the length of Box SEE Part Number 02-02-1001 for pricing See Part # 03-19-2300 to change the Walk through to a crawl through. See Part # 04-04-1600: Battery tray and box will be coated with scorpion liner same color as exterior compartments.	1
02-01-9500		Interior Headroom - 72"	1
02-01-9622	>	Standard Aisle Width = 46"	1
02-02-1000		Materials, Type I & Type III	1
02-02-1001	X <	6" box extension, from 168" to 174" SO.BODY.6401 Ref SR#2013059 Module length is extended 6" to 174".	1
03 - MODULE EXTERIOR			1
03-02-0200	<	Module Undercoating (STANDARD) The entire underbody (excluding drive shaft, wheels, fuel tank and 12 inches either side of exhaust system) shall be sprayed with undercoating for rust prevention, corrosion protection and added sound deadening.	1
EXTERIOR MODULE CONSTRUCTION			1
03-03-1400	>	Module Roof Radius, 3 Inch High (STANDARD)	1
03-03-1500	>	Extreme Bonding Tape (STANDARD)	1
03-03-1600	>	Sub-floor Gusset Supports (STANDARD)	1
03-03-1700	>	One Piece Side Body Panels (STANDARD)	1
03-03-1800	>	Reinforce Rear Header (STANDARD)	1
03-03-1900	>	Single Sheet Module Roof Sheet (STANDARD)	1
03-03-2010	< >	Drop Curbside Forward Body Skirt - 5", Add Double Step, Light Duty Chassis Drop Curbside Forward Body Skirt, Add Double Step ahead of the Curbside Wheelwell - Drop curbside forward body skirt a total of 5 Inches lower than the rearward skirt and incorporate a Double Step in the Side Entry Step well. Increase the depth of stepwell inboard as far as sub structure permits. Side surfaces to be Diamond Plate. Step surface	1

PART NO	S	DESCRIPTION	QTY
		to be a combination of NFPA Diamond Plate and removable 9" Grip Strut insert. The second step to be fabricated of NFPA Diamond Plate and installed so that the step surface is midway between the stepwell floor surface and the module floor (Ulramedic, Promedic only)	
03-03-2110	< >	Drop Streetside Forward Body Skirt - 5", Light Duty Chassis The manufacturer shall drop the lower body skirt along the street side of the module ahead of the rear wheel well at the bottom of the module by approximately 5".	1
03-03-8005		Fuel Fill - Standard Pocket -Square	1
03-03-8400		DEF Fill - Standard Pocket	1
		MODULE ENTRANCE	1
03-05-0100	>	Module Access - Standard	1
03-06-0100	<	Entry Doors - Hidden Hinge, Seal on Door ,W/Fail Safe Latching,STD This includes the Fail Safe Latching mechanisms on all three entrance doors.	1
03-06-0700		Door Restraints - Rear, Polished Cast Aluminum, Pin & Slot Style	1
03-06-0800	<	Door Restraints - Side, Heavy Duty Gas Spring Hold Opens Curbside Door Restraint - Heavy Duty gas spring hold opens. - Attached by 1/4" x 20 SS Machine Screws with 1/4" x 20 Nut Inserts into Corner Gusset in Door Side entrance door to open to 90+ degrees. (STANDARD)	1
03-06-1011		Door Handles - TriMark Chrome	1
03-06-1200		Rotary Latches - (STANDARD)	1
03-06-1300		Nader Pins - (STANDARD)	1
03-06-1481	<	Interior Door Handles, Relocate to Top of Door The interior side and rear entrance door paddle handles and lock boxes shall be located at the top of each of the doors.	1
03-06-1500		Door Panel, Inner - Stainless Steel (STANDARD)	1
03-06-2200		Magnetic Entry Door Switches (STANDARD)	1
03-06-4010	>	Lock Boxes, White Diamond Grade (STANDARD)	1
03-06-4200		Coil Cords for Electrical Circuits (STANDARD)	1
03-06-4400		Door Panel Mounting Screws (STANDARD)	1
03-06-5059	<	Door Flashers - (3) Whelen 500 Red LED w/ Int Flasher (3) Whelen Series 500 Red LED lights with an internal flasher installed on patient entrance doors. (2) Outboard corners of rear door interior panels and (1) outboard corner of curbside door interior panel. Each light to flash when the respective door is opened.	1
03-06-6065	<	Power Door Locks - Module Entry Doors Install power door locks in side and rear entrance doors. Includes (2) lock/unlock switches, one at side door and one at rear door. Also includes (1) hidden switch in rear license frame for unlock function only. System will be tied to OEM chassis power locks so that both systems operate as one. Does not include wireless remote.	1
		SIDE DOOR STEP	1
03-08-3030		Stepwell Light - LED, Whelen 2", Clear	1
		WINDOWS	1
03-09-0030		Module Window Requirements	1
03-09-1120		Window - Side Entry Door, 18X18, Slider - Bronze Glass	1
03-09-1220		Window - Rear Entry Doors, 18X24, Fixed - Bronze Glass	1
03-09-2020	<	Window - Squad Bench 14X33.5, Fixed - Bronze Glass Reflective bronze window that is approximately 14"Hx33.5"L will be installed on the curbside wall above the squad bench.	1
03-09-2910	<	Dry Erase Boards, Over Squad Bench. Slides to each side. "Dry Erase" (2) Piece Sliding Window Covers - Over curbside squad bench window in sliding glass track. Each side recessed behind the corresponding side's backrest cushion when in the open position. Writing board to be	1

PART NO	S	DESCRIPTION	QTY
		polished white laminate on aluminum.	
		MODULE TO CHASSIS MOUNTING SYSTEM	1
03-10-5000		Module to chassis mounting system-Light Duty I (10)	1
03-11-6000		Connecting Bellows, Type I	1
		REAR BUMPER AND REAR STEP CONSTRUCTION	1
03-12-1800		Rear Bumper - Recessed 9" Pocket, Flip-up	1
03-12-3020	< >	Bumper Pods, CPI Cast Aluminum w/RR Logo. (UM & PM) Cast Products Bumper Pods, High Polish Finish. Mounted on the outboard rear step bumper frame members. The CPI cast aluminum pod shall include a RR Logo embossed in the cast pattern on the step tread.	1
03-12-4000	<	Warning Light, Interior for Rear Flip-up Bumper LED Warning Light to Indicate Rear Flip-up Bumper is Up. Install flashing LED warning light over rear doors in overhead cushion that is activated by proximity switch. Includes "BUMPER UP" plaque by light.	1
03-12-4210	<	Whelen OS Mini In Bumper Pocket Install (2) Whelen OS Mini (white LED) marker lights to illuminate the rear bumper step. Lights shall be located on the inside opposing faces of the bumper pocket. Lights shall turn ON when the curbside rear entry door is open.	1
03-12-5600	<	Tow Eyes - Rear Chrome with 6" x 6" x 6" Deep Box Mounted to Steel Reinforcement Plate bolted to the OEM Chassis Frame Rails. Tow Eyes to be Recessed In Rear Kick Panel in cast aluminum box's that are 6" x 6" x 6" deep. (Ultramedic, Promedic Only)	1
		INSULATION	1
03-13-2220	< >	Whisper Quiet - Sound Dampening/Thermal Insulation Package (UM & PM) Whisper Quiet - Sound Dampening/Thermal Insulation Package. (ULTRAMEDIC AND PROMEDIC)	1
		Reflective Barrier/Barymat/Spray Foam Thermal Insulation Package: A. Reflective Barrier - Low-E Foil Wrapped Insulation System - The module walls shall be insulated with high density 1" block foam. Wall areas that are too irregular for 1" block foam insulation, or where the block foam will interfere with wall outlets and wire chases, are to be insulated with 3M brand acoustical Thinsulate insulation. Then the entire interior of the module shall be wrapped with 1/4" Low-E foil wrapped radiant barrier foam style insulation. B. This radiant barrier material will cover the following: - Full ceiling and wrapping over the corner radius and down the sidewall - Full side, front and rear walls from the top of the wall to the lowest possible point along the side, front and rear walls - Seams to be taped with silver / foil ducting tape to secure seams. C. Barymat sound deadening insulation over wheel wells and interior side of exterior compartment walls. (Installed under 3M brand acoustical Thinsulate insulation). D. Spray foam underbody insulation prior to undercoat application, full subfloor coverage where applicable. Includes curbside step well area.	
		ELECTROLYSIS PREVENTION	1
03-14-4000	<	Electrolysis Prevention, Fluid Film (STANDARD) Fluid Film is used at Every Point Where the Mounting Process has the Propensity to Break Paint (STANDARD)	1
		COMBINATION RUB RAIL AND FENDER RING	1
03-15-6020	>	Crash Rail, Diamond Plate Formed ILOS Rubber	1
03-15-7040	< >	Fender Rings - Polished Alum, Dropped Skirts Both Sides - Type 1 & 3 Mounted with long leg forward on drop skirt both sides of module ILOS rubber.	1
		SPLASH GUARDS AND RUNNING BOARDS	1

PART NO	S	DESCRIPTION	QTY
03-16-1800	<	Mud Flaps - Rear, Black w/ RR Logo (Standard) Heavy Duty Rubber Mud Flaps w/ RR Logo - Heavy Duty Rubber Mud Flaps to be bolted to the wheel liner behind the rear duals with with 1/4" x 20 Stainless Steel bolts, washer and nylon locknut for ease of maintenance and repair (STANDARD)	1
03-16-3100		Running Board Inserts - 7" Grip Strut , Type I	1
03-17-1000	<	Drip Rails Polished Aluminum Drip Rails - Above All Doors, Entry and Compartment (Standard)	1
CAB TO MODULE ACCESS			1
03-19-2100	<	Cab to Module Fluid Dam, (STANDARD) Cab to Module Fluid Dam - A formed fluid dam, 4" tall to be installed below the cab to module walk through door to prevent fluids from contaminating the cab. The floor and fluid dam to be fully sealed. (STANDARD)	1
03-19-2300		Cab to Module, Crawl Through Door, ILOS	1
03-19-5500	>	Crawl Through Door - Type I & MD	1
LICENSE PLATE HOLDER			1
03-20-0550	<	Rear License Holder Location - Center Recessed in Bumper Pocket Diamond plate and sealed around all the edges with Sikaflex	1
EXTERIOR COMPARTMENT CONSTRUCTION			1
04-01-0100		Exterior Compartment Construction, Light Duty	1
04-01-3000	<	Door Sill Protection, Stainless Steel. (STANDARD) Door Sill Protection - Install Stainless Steel sill protector on lower edge of all door frames to prevent paint damage. (STANDARD)	1
EXTERIOR COMPARTMENT DOORS			1
04-02-0100		Compartment Door - Hidden Hinge, Seal on Door (UM)	1
04-02-0710	<	Compartment Handles, Exterior - TriMark Chrome (UM) TriMark Two-Point Cast w/Polished Chrome Paddle Handle and Housing, Locking and Non-Locking, with floating cam - Mounted in CNC Cut Opening in Each Compartment Door Skin w/OEM Clamp Assembly. (STANDARD ULTRAMEDIC)	1
04-02-0740		Compartment Handle, TriMark Chrome, Street side, locking	1
04-02-0745		Compartment Handle, TriMark Chrome, Street side, non-locking	1
04-02-0750		Compartment Handle, TriMark Chrome, Curbside, locking	1
04-02-0800	<	Compartment Door Locks - TriMark Compartment Door Handle Manual Locks. - All doors shall incorporate double cut, non-directional tumbler assemblies that are keyed alike (STANDARD)	1
04-02-1000		Compartment Door Nader Pin - (STANDARD)	1
04-02-1200		Compartment Door Lubrication - Door Handles and Latches (STANDARD)	1
04-02-1300		Compartment Door Reflectors - (STANDARD)	1
04-02-1500		Magnetic Compartment Door Switches - (STANDARD)	1
04-02-2010		Compartment Door Panel, Inner - Diamond Plate (STANDARD)	1
04-02-2300		Compartment Door, Gas Struts - (STANDARD)	1
04-02-2500		Compartment Door Panel Mounting Screws - (STANDARD)	1
04-03-0100		Compartment Switches - Door Jambs, Standard	1
04-03-0410		Compartment Light Locations - Ultramedic	1
04-03-1600	<	Door Open Indicators, (STANDARD Smart Display) Door Open Indicators, LCD/VGA - Magnetic Proximity Switches located at the top of the door between the jamb and the door frame will activate a door open indicator on the driver's control panel. The VGA screen will include a digital layout with door open indicators for each door, cab and module and activate the corresponding Interior compartment light. (STANDARD)	1
04-03-2400	S <	Compartment Lights - LED, Flexible Strip, KineQuip Kinequip flexible LED lighting ILOS compartment lighting. (# 1, 2, 4, 6, and 8 Compts) Install (2) Strips in each exterior compartment installed on inside of door flanges facing in. (1) strip on each side of door. (2) Full height strips in the #1 compartment. (Also wired to O2 light switch in rear switch panel)	1

PART NO	S	DESCRIPTION	QTY
		(2) Full height strips in the #2 compartment	
		(2) Full height strips in the #3 compartment	
		(2) Full height strips in the #4 compartment.	
		(2) Full height strips in the #6 compartment.	
		(2) Full height strips in the 6.5 compartment.	
		(2) Full height strips in the #8 compartment.	
		This option deletes all standard compartment lighting.	
04-03-2405	X <	Kinequip Strip Lights across top of compts SO.LTS.6401 Ref SR# 2013059 REF truck # 6355 Kinequip lights will be located on both sides of compts , then this code will take lights across top of every exterior compt. including #3,#6.5 and #8.	1
		EXTERIOR COMPARTMENT INTERIOR	1
04-04-1000	<	Exterior Compartment - Interior Finish, Scorpion Rubberized Exterior Compartment Interior Scorpion Rubberized Liner Color Choice. Scorpion rubberized polyurethane coating applied to the surfaces of ALL exterior compartment walls and dividers.	1
04-04-1001		Color = Dark Gray	1
04-04-1600	< >	Compartment #8.5 and Battery Tray Coated with Scorpion 8.5 Compartment and Battery Tray Shall be Coated with Scorpion Liner	1
04-04-2300	<	Exterior Compartment - Floor Matting "MateFlex" Black matflex to be installed in all exterior comp floors and shelves.	1
04-04-2400	<	Sweep-Out Edging - "MateFlex" Includes all std compartment floors with matflex. (Black)	1
04-05-0001	<	Exterior Compartment Shelving and Unistrut - Standard All exterior shelving Unistrut shall be welded to the walls prior to any compartment wall finish. Where specified, exterior adjustable shelves shall be box pan formed of a minimum .125 inch Aluminum Diamond Plate and corners shall be welded. Shelves shall be infinitely adjustable, and securely mounted to heavy gauge aluminum Unistrut track. (Standard)	1
04-05-6000	>	Compartment Shelving - Scorpion	9
04-05-6001	<	(1) Scorpion Shelf	9
		On all exterior compt shelves, including Right Stack Shelves. (1) in Compt. 1 (1) in compt. 2 (3) in compt. 4 (2) in compt. 6 (2) in compt. 8	
		Note: Dark Gray same as exterior compartments.	
		EXTERIOR - COMPARTMENT #1	1
04-06-0010	<	Electrical Storage - Compartment #1 #1 Compartment Electrical Storage - Recessed into the bulkhead side of compartment #1 shall be an enclosed area for the installation of miscellaneous electrical components. The aluminum cover for this area to be installed with 'J' molding The 'J' molding to be full length of panel on bottom and inboard side. Outboard side of panel to be secured with mechanical fasteners. (STANDARD)	1

PART NO	S	DESCRIPTION	QTY
04-06-0020	<	Compartment #1 - Full Height, Standard Configuration (UM) The forward most compartment on the street side of the module. It shall be externally vented with stamped louvers, to prevent compression of the air inside the compartment to allow you to shut the door. Note: See Part 04-03-2400 and 04-03-2405 for lighting modifications.	1
04-06-1600	< >	Shelf, Removable - (1) Full Width, Compartment #1 Install (1) full width removable shelf mounted in compartment #1. ILOS Note: This shelf to be scorpion lined same color as comp.	1
04-06-1700	>	Delete Divider, Fixed - Compartment #1	1
EXTERIOR - COMPARTMENT #2			1
04-07-0600	<	Compartment #2 - Standard Configuration, (UM) #2 Compartment to be directly behind the #1 compartment and below the interior action area shelf on the street side of the module. Includes (1) adjustable shelf on Unistrut track. Note: Drawer in face of Lower Left cabinet is recessed into the #2 comp. Also the inside access cabinet is recessed into #2 compartment. Note: See Part # 04-03-2400 and 04-03-2405 for lighting modifications. (STANDARD Ultramedic)	1
EXTERIOR - COMPARTMENT #3			1
04-08-3300	<	Compartment #3 - 8.5"H x 22"W w/Hinged Door #3 Compartment with Hinged Door - Hinged #3 compartment access door over streetside wheel well. Door is approximately 8.5"H x 22"W. Includes in/out access through the CPR seat and "NO" slide out tray. Note: See Part # 04-03-2400 and 04-03-2405 for lighting modifications. (Ultramedic, Promedic Only).	1
EXTERIOR - COMPARTMENT #4			1
04-09-3200	S < >	Compartment #4 - Full Height Full Height #4 Compartment streetside rear of module with Interior Upper left #4 Cabinet - #4 Compartment to be full height to bottom of upper left #4 cabinet. Compartment includes (1) adjustable shelf. Note: See option 04-03-2400 and 04-03-2405 for lighting modifications.	1
04-09-3700		Double Doors #4 Compartment	1
04-09-4505	<	Shelf Adjustable , Compartment #4, Standard Note: This shelf is to be scorpion lined same color as comp.	1
04-09-4520	S < >	Shelf Adjustable - Additional, Compartment #4 (2) additional shelves for #4 compartment. Location: Both in comp. 4. Note: Both of these shelves are to be scorpion lined same color as comp. Total of (3) shelves in this comp. No additional lights due to the usage of Kinequip lighting	2
EXTERIOR - COMPARTMENT #6			1
04-11-0600	<	Compartment #6 - Standard Configuration (UM) Exterior compartment #6 shall be located at the curbside rear of the module. The compartment shall have a single door. This compartment shall be configured primarily for the vertical storage of backboards and other miscellaneous equipment. The manufacturer shall install a louvered vent in the upper left wall of the #6 compartment to enable the door to close without added compression. This compartment shall be per the size and configuration shown in the attached prints. Compartment door to open past 90 degrees. Note: See option 04-03-2400 and 04-03-2405 for lighting modifications.	1

PART NO	S	DESCRIPTION	QTY
04-11-4510	<	Shelf Adjustable - Compartment #6 Mounted to the right of the divider. Located 41" up from floor to allow room for stairchair underneath. Note: Shelf will be scorpion lined same color as comp.	1
04-11-4520	< >	Shelf Adjustable - (1) Additional, Compartment #6 Must pick quantity if more than one is needed. Location: Mounted forward of the divider. Note: shelf will be scorpion lined same color as the comp.	1
04-11-4560	< >	Divider, Fixed - Compartment #6 (UM) Divider to be installed so there will be 10" clear opening to the right when comp. door is open.	1
04-11-4631	< >	Equipment Strap - (1), Quick Release, Plastic Buckle (1) equipment restraint strap with quick release buckle Must pick quantity if more than one is needed. Location: Mounted from wall one to divider for back boards.	1
EXTERIOR - COMPARTMENT #6.5			1
04-12-3400	< >	Compartment #6.5 - Base Configuration (UM & PM) This comp. will have a strap for the door to keep it from opening too far. Note: See option 04-03-2400 and 04-03-2405 for lighting modifications.	1
EXTERIOR - COMPARTMENT #8			1
04-14-1400	<	Compartment #8 - Full Height, "A" Style Configuration Exterior compartment #8 shall be the forward most compartment on the curbside of the module allowing interior / exterior access to the interior ALS cabinet. To be full height to the bottom of the locking drug cabinet. Also to include two adj shelves painted with scorpion liner the same color as the other exterior comps. Note: See option 4.3.24 and 4.3.500 for lighting modifications.	1
EXTERIOR - COMPARTMENT #8.5			1
04-15-0400	<	Compartment #8.5 - Drawer Style Battery Box Configuration Battery access door mounted slide out battery tray. Battery Tray to be Scorpion lined same color as other exterior comps. This does not include the slides. See Option 4.4.16 to spray scorpion on battery tray.	1
INTERIOR TRIM AND FEATURES			1
	<	New Interior Trim - All cabinet and wall panel aluminum trim to be Gray anodized. (No Black trim to be used). All protective corner trim will be Opaque and will include a matching domed end cap. (STANDARD)	1
INTERIOR ADJUSTABLE SHELVES			1
INTERIOR TRIM			1
05-05-1000		Interior Trim - Standard	1
HEADLINER			1
05-06-1100	<	Ceiling Medical Device Rail (STANDARD) A near surface mounted Medical Device rail system shall be installed over the primary cot. Each side of the track will have a solid surface accent stripe to match the action wall counter. The track system to be surface mounted and run the entire length of the module with the sole intent of providing easy access to allow the medical personnel to quickly access equipment for administering aid to the patient.	1

PART NO	S	DESCRIPTION	QTY
		See separate options for additional IV hangers, oxygen outlet and AM/FM speakers.	
		The medical device rail allows for provisions for standard: (1) IV Hanger (3) Patient Lights focused at head, torso and legs (2) antenna accesses under cot lights.	
		See separate options for additional IV hangers, oxygen outlets and AM/FM speakers.	
05-06-1200		Headliner - Vinyl Ceiling, No Seams (STANDARD)	1
05-06-1802	<	White LED Strip Lights, Ceiling Medical Device Rail. (UM & PM) Note: These should run full length due to the stop and turn lights being removed.	1
05-06-2600		DELETE - Red/Amber LED Turn/Brake Strip Lights (UM & PM)	1
FLOORING			
05-07-1000	<	Alluminum Floor/Wall Cove Moulding. (STANDARD) Seams at perpendicular floor and cabinet intersections will be finished with an aluminum cove moulding trim. The seams where cabinets meet floor will be sealed with a caulking sealant / adhesive before installing the aluminum cove moulding.	1
05-07-1400	<	Stainless Steel Rear Threshold, 45 Degree Chamfered (STANDARD) The rear door threshold shall be 14 gauge stainless steel with 45 degree chamfered edge. The threshold will be permanently installed with Sikaflex 252 sealant/adhesive. The Sikaflex material will both secure the threshold and provide a full perimeter seal to prevent fluid borne contamination. The threshold shall include 3M "Safety Walk" anti-skid tape to prevent slipping. There will be no holes drilled in the stainless and no screw type attachments required.	1
05-07-3000		Lonplate II Flooring Choice	1
05-07-3007		Color - 411 Putty	1
05-07-6100		Curbside Stainless Steel Threshold	1
HEAD BUMPERS			
BACKRESTS			
05-10-1301	S <	Rear Entry Door Grab Bars - "C" Bars, 16" Anti-Microbial SO.RBARS.6401 REF SR# 2013059 "C" Bars - 16" Anti-Microbial. 1.25" Diameter stainless steel "C" Bars mounted to each rear door. Approximately 16" wide by 24" high. Clear Anti-Microbial finish. Note: This is a new style "C" shaped bar to wrap around the window.	1
05-10-1401	S <	Side Entry Door Grab Bars - "C" Bar - 16" Anti-Microbial SO.SBAR.6401 REF SR#2013059 "C" Bar - 16" Anti-Microbial. 1.25" Diameter stainless steel "C" Bars mounted to side entry door. Approximately 16" wide by 24" high. Clear Anti-Microbial finish. Note: This is a new style "C" shaped bar to wrap around the window. Vertical portion of bar will partially block window view.	1
05-10-1903		Ceiling Grab Rail - Center 108" Anti-Microbial	1
05-10-2101	<	Ceiling Grab Rail - Streetside 72" Anti-Microbial 1.25" Diameter stainless steel grab rail mounted to ceiling. Streetside of center. Clear Anti-Microbial finish. Includes increasing the top flange of the U2 and U4 cabinets.	1
PLASMA HANGER			
05-11-4000		IV Hangers - CPI #IV2008 (STANDARD)	1
05-11-4002	<	Quantity (2) Installed in the standard locations above the Torso area the primary cot and squad bench.	1
INTERIOR STREETSIDE #1 - LEFT STACK and BULKHEAD			
05-12-1600	<	Left Stack - Storage Area #1 - 45 Deg Angled A two section vertical cabinet shall be provided behind the attendant seat on the streetside forward corner on a 45 degree bevel that includes the access doors to the cabinet. The lower cabinet door shall be aluminum with multi spec coating per previous options and the	1

PART NO	S	DESCRIPTION	QTY
		upper cabinet shall be a Lexan door with full perimeter extruded aluminum frame. This includes one adj shelf in the upper section. Note: Both Doors will have locking latches.	
05-12-1820	<	Shelf Adjustable, Additional - Left Stack Note: This is located in the Lower Left Stack	1
05-12-1850	<	Upper Bulkhead Cabinet, 17"D with Sliding Acrylic Doors For access to the electrical components, the upper bulkhead cabinet shall have a sliding doors and restocking feature installed in addition to the electrical power distribution cabinet. This includes one adj shelf. Cabinet back and shelf to be mounted with velcro for easy access to the electrical components. The cabinet will be approximately 17" D.	1
INTERIOR STREETSIDE #2 - ACTION AREA			
05-13-0700	<	Medical Device Rail - Action Area Wall An action wall Medical Device rail system shall be installed on the streetside wall. Each side of the track will have a solid surface accent stripe to match the action wall counter. The track system to be surface mounted and run the entire length of the action wall from the #1 compartment to the CPR seat. The medical device rail allows for provisions for the standard (2) Oxygen Outlets, Oxygen Solenoid Valve, Suction Regulator, 12V Outlet and 110V Outlet.	1 1
05-13-1100	X <	Angled Upper Left #2 Cabinet, Full Length Switch Panel Configuration Custom upper Left #2 cabinet w/Switch Panel Cabinet. The upper left #2.5 cabinet has been deleted and replaced with a padded beveled panel, The upper left #2 cabinet to be approximately 43" wide. Includes (1) adjustable shelf. The lower 6" area of upper left #2 to be a separate enclosed cabinet area that is full length with the entire length of the face of the cabinet tilted slightly down for ease of accessibility to the attendant.	1
05-13-2000	<	Stainless Steel Wall Panel- Entire Street Side Wall The street side wall shall be finished with full height, one piece stainless steel installed from the front of the forward action area to the rear of the rear action shelf aft of the CPR seat. The stainless steel is to be one single piece with no exposed fasteners.	1
05-13-2200	< >	Countertop - Forward Action Area and Rear Monitor Area. There shall be a sealed, solid surface counter top on the forward action area and the monitor/work shelf aft of the streetside CPR seat. The color and pattern design of the solid surface counter top material shall be as follows:	1
05-13-2215		Avonite Autumn Wheat, K3-7725	1
05-13-2500	<	Polish Avonite Counter Avonite countertop shall be polished to a high gloss finish.	1
05-13-2640	S <	Drawer - Slide-Out Laptop with Hinged Locking Lid Below Action Counter SO.SLIDE.6401 REF SR#2013059 There shall be a slide out laptop/paperwork drawer below action wall counter. The drawer shall incorporate a lift-up Lexan lid and a locking latch on the drawer face. Non Locking Slides w/Gas Assist strut. Strut shall be mounted on the bottom of the drawer to keep the drawer in the open position. Drawer shall be approximately 4 in. D x 13 in. W x 18" D. Note: Placement of drawer, attendant seat and cot is critical to allow for proper leg room. Note: THIS WILL RAISE THE HEIGHT OF THE A/A COUNTERTOP AND THE TELEMETRY AREA COUNTERTOP BY 4" TO ALLOW FOR ADDITIONAL LEG ROOM AND FOR DRAWER TO CLEAR THE COT. THIS WILL CREATE A 2" NOTCH IN THE	1

PART NO	S	DESCRIPTION	QTY
		NUMBER 2 COMPARTMENT.	
05-13-2645	X <	Slide out Drawer Below Action wall counter SO.DRWR.6401 REF SR# 2013059 REF truck # 6355 The interior of the drawer shall be approximately 12-1/2" H X 7" W X 18" D. Drawer shall have non-locking slides and a locking latch in the face of the drawer. Drawer to have (2) adj, plexi dividers that will run full depth of drawer.	1
05-13-2647	X <	Lower Left #2 cabinet, W Retaining Lip SO.CAB.6401 REF SR#2013059 This is recessed into the # 2 exterior compartment, with NO DOOR, and a retaining lip on the bottom. Approx 1" lip.	1
		INTERIOR STREETSIDE #3 - CPR SEAT	1
05-14-0500	<	Streetside - CPR Seat, Standard Configuration - The CPR seat shall include a flip up seat equipped with a gas strut hold open device and positive latch for securing the lid when closed. The CPR seat shall include a 2" foam seat and backrest, the upper and lower sections will be padded on both sides for added protection.	1
05-14-0900	<	CPR Seat Lid Hold-Down CPR Seat Lid Hold-down - Install a Black Tri Mark recessed paddle latch, (1) under CPR seat lid.	1
05-14-1000	S < >	Cabinet - Upper Left U3, 12"H x 41"W, Non-KKK Compliant There shall be a upper left U3 cabinet with sliding doors, restocking feature and no shelf. Cabinet shall be approximately 12" high, 10-3/4" deep, and shall span the full width between the upper left U2 and U4 cabinets. NOTE : The distance between the top of the CPR seat cushion to the bottom of the cabinet cushion will not be in compliance with KKK-A-1822F requirements for head clearance.	1
05-14-2450		Seat Belts, CPR Seat - Standard 2-Point	1
		INTERIOR STREETSIDE #4 - REAR AREA	1
05-15-1000	S <	Angled Upper Left #4 Cabinet Decrease the standard width of the cabinet 17" and add an angled section at the CPR seat. Upper left U4 cabinet with sliding Acrylic doors, restocking feature and (1) adjustable shelf. Cabinet shall be in the upper left street side rear of the module and will provide interior access only. Note: The exhaust fan has been moved to behind the U2 cabinet to allow cabinet U4 to be as wide as possible	1
05-15-4505	X <	Dawer,Slide out below rear countertop SO.SDRWR.6401 REF SR#2013059 REF truck # 6355 The interior of the drawer will be approximately 12-1/2"H X 8-3/4"W X 18"D Drawer shall have a non-locking slides and a locking latch on the face.	1
05-15-4700	S < >	Countertop - 18" Aft of CPR Seat Counter aft of CPR seat to be 18" wide. Requires notching the #4 compartment. The door frame notch close out at the rear of the counter to be 18" wide.	1
05-15-4900		Interior Access - Sliding Acrylic Doors, to Exterior Compartment #4	1
		INTERIOR CURBSIDE - SQUAD BENCH AREA	1
05-16-0100		Curbside Squad Bench - Seating Capacity (3), Two Piece Hinged Lid	1
05-16-0200		Seat Belts, Squad Bench - Standard 2-Point	1
05-16-0300		Restraint Belts, Squad Bench - Standard	1
05-16-0500	<	Medical Device Rail - Squad Bench A Medical Device Rail system shall be installed on the curb side wall. Each side of the track will have a solid surface accent stripe to match the action wall counter. The track system to be surface mounted. The medical device rail allows for previsions for the standard Oxygen Outlet and Ceiling Light Timer.	1

PART NO	S	DESCRIPTION	QTY
05-16-0600		Latches, Lids - Squad Bench Tri Mark , Standard	1
05-16-1323	<	Storage, Resessed (2) O2 Brackets - Open, Head of Squad Bench There shall be a recessed cabinet for (2) F.W. #521 portable oxygen bottle brackets at the forward end of squad bench. The cabinet shall be located to the left of the side entry door stepwell and below the squad bench lid. The cabinet shall be open access with no doors. See Part# 05-17-0320 for A Bar special And Part # 14-02-6120 for the 521 brkts.	1
05-16-1400	<	Interior, Squad Bench - Scorpion Liner The interior walls and floor of the squad bench base shall be coated with Scorpion spray on rubberized liner material. Same color as exterior comps. (DARK GRAY)	1
05-16-8200	<	Cabinet - Upper Squad Bench, 12"H Non-KKK Compliant There shall be a cabinet located above the squad bench. The cabinet will be approximately 8-1/2"H x 12"D and will the same length as the squad bench. The cabinet shall be divided into two (2) separate sections by a fixed center divider. Each section will have sliding Acrylic doors and restocking feature. The distance between the top of the squad bench cushion to the bottom of the cabinet cushion will not be in compliance with KKK-A-1822F requirements for head clearance. NOTE: Increase top flange by approx. 1" to allow for clearance of the c/s restocking doors and the c/s grab rail.	1
INTERIOR CURBSIDE - BIOHAZARD			
05-17-0320	< >	Squad Bench "A" Bar 18" - Anti-Microbial, Waste Only for F.W. 521 Installation stainless steel Anti-Microbial "A" style Grab Bar/Arm Rest mounted at the head of the squad bench. This bar shall have the ability to be pivoted or removed to allow for placing a long board patient on the squad bench. Mounted integral to the 'A' bar shall be an 8 quart waste container. The container shall be positioned in the upper section of the "A" Bar.	1
05-17-2000	>	Glove Butler(s)	1
05-17-2120	<	Glove Butler (4) Total - Over Curbside Entry, Surface Mounted There shall be (4) Glove Butler II glove boxes installed above the side module entrance door with drop down door and locking. Door to be bottom hinged to tip out for restocking. Access holes to be cut in door for glove removal.	1
INTERIOR CURBSIDE - RIGHT STACK STORAGE #8			
05-18-0600	<	Right Stack - Upper Heater-A/C Unit, Standard Configuration (UM & PM) heat A/C unit located at the top of the right stack/ALS cabinet. Conditioned air shall be distributed through six vents evenly spaced down the full length of the ceiling. There shall be a floor to ceiling plenum with intake vents of sufficient size to allow recirculation of the conditioned air.	1
05-18-0800		Right Stack - Hidden Air Intake (STANDARD)	1
05-18-1000	<	Right Stack - "A" Style Standard (UM & PM) Upper section to be locking drug cabinet with a single aluminum drop down door. Lower section to have framed 3/8" Lexan doors with locking latches and (2) adjustable shelves with access from interior or exterior. Note: Shelves will be scorpion lined same color as exterior comps. See Part # 04-03-2400 and 04-03-2405 for lighting modifications.	1
05-18-5110		U8 - Drug Cabinet, Single Aluminum Drop-Down Door, Interior	1
05-18-5310		L8 - ALS Cabinet, Dual Lexan Doors, (2) Adj Shelves, Interior / Exterior	1
05-18-5311	X <	Right stack shelves, .125 alum SO.2SHF.6401 REF SR#2013059 REF truck Number 6355 Right stack shelfe (2) will be made from .125 aluminum. Note: These will be scorpion lined per previous ref. code.	1

PART NO	S	DESCRIPTION	QTY
05-18-9110	<	Sweep-Out Floor Lower Right Stack ALS The floor of the Right Stack ALS cabinet shall be constructed of 14 Ga. Stainless steel and be sweep out style to the interior and exterior. Floor will be made of 14 gage SS.	1
ATTENDANT SEAT			1
05-19-5800	<	Attendant Seat - EVS Vac Form, 3-Point Belt, Swivel Base To ensure proper and safe use of the child seat feature, the swivel base must lock in forward facing or rearward facing positions only. NOTE: CHANGE THE DIMENSION FROM THE FRONT COT MOUNTING PLATE TO THE FRONT OF THE SEATBASE TO 22" FROM THE STANDARD 18". THE COT MOUNT WILL BE MOVED TOWARDS THE FRONT BY 6" TO MAKE UP FOR THE 6" BOX EXTENSION.	1
05-19-5805		Color - Taupe	1
INTERIOR COLORS			1
05-20-2000	<	Multi-Spec Interior Surfaces - Standard LOWER BAND - The patient compartment interior surfaces will be spray painted with a "Multi-Spec" base-coat/clear coat system anywhere a Thermo plastic laminate surface is normally installed. This includes interior wall panels, ALS cabinet, left stack, lower left cabinet and #1 and #6 exterior compartment surfaces. The manufacturer must use the same metal prep and finish processes as used on the exterior of the module to finish the interior surfaces to the following finish:	1
05-20-2012		Color - Buckskin #99-6003	1
05-20-5300	<	Upper Band Vinyl Color - Cabinets and Stitched Cushions Upper Band Vinyl Color Choice for cabinets and stitched cushions.	1
05-20-5310		Color - Heidi Soft Sandlewood HDI-6332	1
05-20-5500		Lower Band Vinyl Color - Vacuum Formed Cushions	1
05-20-5509		Color - Taupe	1
05-20-9000		Acrylic Glass Color Choice (STANDARD)	1
05-20-9003		Color - Smoke (Bronze)	1
MISC. INTERIOR OPTIONS			1
05-21-4000		Interior Cabinet Lights, Kinequip LED Strip	1
05-21-4040	<	Upper Left Cabinets - 2, 2.5 ,3, 4, 7 and 7.5 Note: The 2.5 has been deleted for the angled cabinet. Please use this set of lights for the left stack.	1
05-21-4041	X <	Whelen,2" Led lights, Surface mnt, under upper cabinets SO-LEDLTS-6401 REF. SR#2013059 Whelen #T0CACCCR with #TFLANGEC (3) Lights on the street side will be mounted at the 2" dead space under cabinets #2 and #4. (2) under # 2 cabinet evenly spaced (1) under #4 cabinet centered over telemetry countertop. These will be operated with a switch on the streetside switch panel. (2) Lights will be mounted (1) each under #7 and #7.5 cabinets. These will be mounted on the cushion and switched with there own switch in the C/S switch panel.	1
05-21-5100		Squad Bench & Lower Left, 11 Inch Stainless Kickpanels	1
05-21-7000	<	Interior Access, #6 Compartment, w/ Hinged Lexan Door The patient compartment shall include a inside/outside access to the #6 compartment. The access opening will be fully framed and will include an aluminum framed, single hinged, 3/8" Lexan door, secured with (2) locking latches. The access will be installed at the forward portion of the #6 compartment, and facing the aisle. The door will extend from the highest possible/practical point of the compartment down to the level of the shelf in comp. 6. the shelf is mounted 41" above the floor to leave room for stair chair and will be approx 11-1/2" wide. Exterior shelf retaining lip to be aligned with door opening	1

PART NO	S	DESCRIPTION	QTY
05-21-8900	<	Cabinet Latch - Southco Lever Latch, Chrome Locking	11
		All LATCHES ARE LOCKING IN THIS UNIT.	
06-01-0100		General Wiring - General Harness Standard	1
		COMMUNICATION	1
06-06-1011	S < >	Camera - Interior (1) Additional Mounted high in the forward bulkhead area and connected to the voyager LCD monitor pedestal in the cab headliner. Camera mounted rearward to record patient and crew activity.	1
		Note: Camera will have the microphone enabled for driver to hear from the module. Both cameras will be connected to the same monitor in cab headliner.	
06-06-1200	<	Camera System - Exterior Back-Up, Over Rear Doors for PC System Camera mounted exterior over the rear doors and connected to the Voyager LCD monitor pedestal mounted in the cab headliner. Wire to turn camera on when vehicle is placed in reverse. Note: Camera to have the Microphone enabled.	1
06-06-1600		Two Way Radio Routing Path Cab to Module. (STANDARD)	1
06-06-1700		Two Way Radio Prewire, 12VDC Power and Ground (STANDARD)	1
06-06-3004	< >	Antenna UHF/VHF - (4) Bases and Cables Install (4) NMO Antenna bases with pre-attached 35' cables. Road Rescue will not make or break any radio connections. Antenna Locations: Module ceiling Cable Termination Locations: (3) Front Console (1) lower left stack.	1
06-06-6100	<	Radio Power - (2) 8 Gauge 12VDC Power/Ground The Black ground wire to be connected to a main ground point, the Red power wire to be left unconnected near a direct to battery connection point inside the power distribution cabinet. Both wires to route to the lower section of the Left Stack/Radio Cabinet and be of sufficient length to allow routing to the Cab Console as an alternate radio installation location. Wires to be labeled at both ends	1
		RADIO AND CLOCKS	1
06-07-6000	<	Clock - Digital DDS 12/24 Hour 2.5" LED, Over Rear Doors Included with this vehicle, there shall be Digital 12/24 hour clock with 2.5" display recessed in the cushion over the right stack. Clock is approximately 6" x 18" and displays hours, minutes and seconds in 12 hour or military time and adjusts automatically for daylight savings time. Operates on Internal memory battery.	1
06-07-7400	<	Speakers - Mounted in Ceiling w/Volume Control in Action Wall (2) speakers wired to the OEM AM/FM/CD stereo. The speakers shall be recessed in the ceiling. There will be a volume control located in the action area.	1
		07 - ELECTRICAL 12 VOLT DC	1
07-01-0010	<	Crcrt Pwr Accs.,Ign/Shrline,1-20 amp 12VDC to 2 locs,W/O,PD9130 chrgr (1) 10 amp lead shall be coiled up behind the A./A panel for future use. (1) 10 amp lead shall be coiled up behind the drivers seat in the cab, for future use. Note: This code will be used when and additional battery charger has already been installed, the PD9130 will not be used with this option.	1
07-02-1000		Voltmeter - Standard	1
07-02-1100		Alarm,Low Voltage,With Buzzer and Indicator,in cab console	1
07-03-1000		Ammeter - for PC System	1
		BATTERY SYSTEM	1
07-05-0400	<	Batteries - Type I Configuration, (2) OEM (1) Additional The two OEM batteries under the hood. One additional battery shall be supplied by the	1

PART NO	S	DESCRIPTION	QTY
		manufacturer and located in the exterior compartment located below the right front ALS cabinet.	
07-07-0400	<	Module Disconnect - PC System The module disconnect shall utilize a dedicated switch located on the main drivers control panel to disconnect module power loads. This shall be a safety feature only and should not be used at any other time. This switch shall disconnect the entire module electrical system with the exception of the 12V DC outlets, DOT lighting circuitry including backup alarm, the door open warning display, and the chassis circuitry.	1
07-08-0100		Battery Ground	1
07-08-0203		(3) Straps	1
07-09-6000		Battery Charger - Prewire only, 12V. (STANDARD)	1
07-10-1000	<	Power Outlets 12V, (2) Power Point Style, On with Ignition (STANDARD) (1) outlet shall be mounted on the action wall and (1) outlet shall be mounted above the top shelf in the lower section of the right front stack ALS cabinet. Outlets on this circuit shall be wired "On with Ignition" and protected by a medical isolator.	1
07-10-5301	<	(1) Additional 12V Outlet, Direct to Battery In cab behind drivers seat next to console.	1
		FRONT CONSOLE	1
08-01-3101	<	Driver's Switch Panel/Radio Console - PC System, Custom Floor mounted aluminum console for switch panel, Siren, and (4) more components. Siren mounted in top portion. Remainder of face plate left blank for radio installer. Console to be larger than std. Ref. 6355 Console	1
08-01-4200	<	Cup Holder, (2) Position Aluminum in the Cab (2) position aluminum cup holder in the cab at the aft end of the driver's console. The holders shall be made of .125 aluminum wrapped with a high quality, commercial vinyl to match front console with a plastic laminated top designed to accommodate (2) removable plastic cups. Laminate shall match the front console faceplate.	1
08-02-0500		Driver's Control Panel - Carling Rocker Switches	1
08-02-4000	< >	Rear Heat A/C 'Enable' Switch, Front Console There shall be a rear heat A/C 'enable' switch on the front console	1
08-02-5600		Alarm, "Emergency Brake Not Set"	1
08-02-8000	<	Warning Lights - Cab Ceiling "Open Door", "Emergency Brake" There shall be (2) flashing LED lights in cab ceiling forward of OEM dome light with chrome accent rings. (1) Amber to flash when the emergency brake is applied and (1) Red to flash when compartment or module entrance door is open. Included shall be a Black plaque with White lettering that says 'OPEN DOOR' and one that say's 'EMERGENCY BRAKE APPLIED'. Mount forward of the OEM cab dome light, centered and parallel to the doors, close to each other.	1
		ATTENDANT CONTROL PANEL	1
08-03-0500	<	Attendant's Control Panel - Carling Rocker Switches All switches are same design as the Driver's control panel. Attendant's control panel includes red/amber/green patient status switches to actuate patient status indicators in driver's control panel and momentary switch to actuate audible alarm in driver's control panel. See below for all standard switch positions.	1

PART NO	S	DESCRIPTION	QTY
		Control panel meters and switch legends have electroluminescent backlighting. The switch function legend is screen printed from the back for durability, white on black to prevent bleed out and flush mounted in panel surface.	
		The standard rear switch panel shall include, at a minimum, three spare switches along with standard switching functions as follows:	
		1. Dome Lights - Three-way 'On/Off' with driver's control panel.	
		2. Cot Lights - 'Hi-Off-Lo'	
		3. Bench Lights - 'Hi-Off-Lo'	
		4. Oxygen Compartment Light 'On/Off'	
		5. Electric O2 'On/Off'	
		6. Suction 'On/Off'	
		7. Blank	
		8. Silent Signal (Green) 'On/Off'	
		9. Silent Signal (Amber) 'On/Off'	
		10. Silent Signal (Red) 'On/Off'	
		11. Signal Buzzer 'Momentary On'	
		12. Blank	
		13. Exhaust Fan 'On/Off'	
		14. Inverter 'On/Off'	
08-03-2300	<	Additional Rear Control Panel Curbside, PC System mount a secondary rear control panel on the curbside of the module on an access panel above the head of the squad bench. It shall include a cabinet angled towards the rear. The secondary control panel will work in conjunction with the primary rear control panel and the front control panel. Layout- Dome lights, cot lights, bench lights, suction, exhaust fan and O2 switch.	1
08-04-3902		Power Distribution - PC Board Electrical System (UM & PM)	1
		EMERGENCY SYSTEMS - Ford F-Series	1
		WARNING AUDIBLE - SIREN, SPEAKERS, AIR HORNS	1
09-03-1010	<	Siren Electronic - Whelen 295SLSA1 Whelen #295SLSA1 "Self Diagnostic", non-remote siren, with NC microphone. The siren shall be ignition powered and will provide hands free control feature that allows switching between three siren modes and siren off from the horn ring. Siren mode choices are user programmable from 17 different Scan-Lock siren tones. Includes remote Siren/Horn switch on drivers control panel.	1
09-03-2020	<	Speakers - (2) CPI "Though-The-Bumper" for F-Series Cast Products #SAD/P3806 speakers recessed in bumper.	1
09-03-4030	<	Siren Electronic, Additional - Whelen 'Howler' Whelen 'Howler' low frequency siren speaker system installed behind the OEM bumper. A momentary 'Aux Siren' switch and a 'Siren Brake' switch shall be installed.	1
09-05-0200		Backup Alarm (STANDARD)	1
09-06-0200		Emergency Sequencer/Load Manager (STANDARD)	1
		WARNING VISUAL LIGHT PACKAGE - LED (Whelen Super-Series)	1
		WARNING VISUAL - FRONT UPPER (ZONE A)	1
09-50-1307		Visual Warning Front Upper - (7) Seven Light Straight Line Configuration	1
		AUXILLARY EMERGENCY LIGHTS	1
		POWER SUPPLIES - SEQUENCERS	1
09-80-2300	< >	EEV,Wrng Lt Flshr - InPower 4875P2 Flshr,Terminal Strips EEV - InPower 4875P2 Flasher with alternating flash pattern.. Install a InPower 4875P2 Programmable Electronic Flasher ILOS in the dead space area. Flasher to be set to triple flash.	1

PART NO	S	DESCRIPTION	QTY
		Includes routing 4 conductor cable to ALL light heads ILOS. ALL WIRES TO BE LABELED LIGHTHEAD SPECIFIC AND ROUTED TO THE DEAD SPACE. Install (4) terminal strips in the dead space area labeled Phase 1, Phase 1P, Phase 2, and Phase 2P. Install (1) grounding stud near the 4875P2 flasher. Connect all of the scan lock wires to grounding stud. All lights are to alternate and the model #900's are to alternate flash over/under. All forward facing White lights are to be 'On' in Primary mode only. Program flash pattern on light heads as follows: Model #500 Grill lights = Steady #25 Model #700 lights = Steady #14 Model #900 lights = Steady/Steady Install a relay near the flasher for an auto PARK cutout circuit. Label this relay 'Park Cut Out'. NOTE: If the front fender intersection lights are ordered with split colors then the light head will be wired with constant power and set lighthouse to Comet flash alternating #3 flash pattern and if there are white LED's they will be 'On' in Primary mode only.	
09-95-1201	<	Whelen 900 LED, w/Chrome Flange - RED w/ Clear Lens (Internal Flasher) IATS Rear Body - Upper Curbside Window	1
09-95-1201	<	Whelen 900 LED, w/Chrome Flange - RED w/ Clear Lens (Internal Flasher) IATS Rear Body - Upper Streetside Window	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) IATS Rear Body - Lower Curbside Window Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal FI	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) IATS Front Body - Upper Curbside Outer Blue on top Red on the bottom	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) IATS Front Body - Upper Curbside Inner Red on top Blue on bottom	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) IATS Front Body - Upper Streetside Inner Red on top Blue on bottom	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) IATS Front Body - Upper Streetside Outer Blue on top Red on the bottom	1

PART NO	S	DESCRIPTION	QTY
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Streetside Body - Upper Forward Blue above Red below	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Streetside Body - Upper Rear Red above Blue below	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Curbside Body - Upper Forward Blue above Red below	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Curbside Body - Upper Rear Red above Blue below	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Rear Body - Upper Streetside Corner Blue above Red below	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Rear Body - Upper Curbside Corner Blue above Red below	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Front Body - Upper Curbside Corner Red on top Blue on bottom	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Front Body - Upper Center Blue on top Red on the bottom	1
09-95-1206	<	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Front Body - Upper Streetside Corner Red on top Blue on bottom	1

PART NO	S	DESCRIPTION	QTY
09-95-1206	X <	Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal Flasher) IATS Rear Body - Lower Streetside Window Whelen 900 LED, w/Chrome Flange - RED/BLUE Split, Clear Lens (Internal FI	1
09-95-2203	<	Whelen 700 LED - AMBER w/ Clear Lens (Internal Flasher) ILOS Rear Body - Upper Center	1
09-95-2209	<	Whelen 700 LED - RED/BLUE Split, Clear Lens (Internal Flasher) IATS Rear Intersectors-RH Side Red to front Blue to the rear	1
09-95-2209	<	Whelen 700 LED - RED/BLUE Split, Clear Lens (Internal Flasher) IATS Rear Intersectors LH Side Red to front Blue to rear	1
09-95-2209	<	Whelen 700 LED - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Intersectors - LH Side Blue to the front Red to the rear	1
09-95-2209	<	Whelen 700 LED - RED/BLUE Split, Clear Lens (Internal Flasher) ILOS Intersectors - RH Side Blue to the front Red to the rear	1
09-95-4206	S <	Whelen 500 LIN6 Super LED - RED/BLUE Split ILOS Grille - LH Standard Position (FORD) Red to outside Blue to inside	1
09-95-4206	S <	Whelen 500 LIN6 Super LED - RED/BLUE Split ILOS Grille - LH Standard Position (FORD) Red to outside Blue to inside	1
09-95-4208	X <	Whelen, Dominator lightbar,B,R,W.W.R.B SO.LBAR.6401 REF SR#2013059 REF truck Number 6355 Whelen #D6BRWWRB TIR3 Mounted on the lower bar of the front grille on special brkts. Lights to be TRI3's configured as follows: B/R/W/W/R/B set to comet flash 75. This bar will have a separate switch in drivers console labeled "AUX GRILL LTS"	1
09-95-9230		Housings, Cast, 500 Series, Grille, Ford, F-series, Pair	1

PART NO	S	DESCRIPTION	QTY
09-95-9235		Housings, Cast, 15 degree angled, 7x3, Intersection, F-series, Pair	1
		EXTERIOR AUTOMOTIVE LIGHTING	1
10-01-1030	<	Tail Lights, Brake/Turn - Whelen 600-Series LED (Max-Population) These lights shall have chrome trim rings and be mounted vertically above the rear diamond plate area. Note: See drawings for locations.	1
10-01-1220	<	Back-up Lights - Whelen 600-Series LED Rear (Max-Intensity) The rear of the module shall be equipped with Whelen 600 Series LED back-up lights. (maximum intensity) Note: Relocated to the rear tread bright area.	1
10-01-2010	<	Marker/Clearance Lights, Front - Whelen OS Mini LED, Amber The front of the module shall have (5) amber clearance lights. The clearance lights shall be Whelen OS Mini with chrome flanges. Note: This includes deleting the front light bar.	1
10-01-2110	<	Marker/Clearance Lights, Side and Rear - Whelen OS Mini LED, Red/Amber The side body marker lights and rear clearance lights shall be Whelen OS Mini LED type. There shall be (2) Amber mounted at the forward end of each side module roof extrusion, (2) Red mounted at the rearward end of each side module roof extrusion and (5) Red mounted in the rear module roof extrusion. In addition there shall be (2) Red marker lights on each side in the midline of the body at the rear. (1) On each side shall function as a marker light and (1) will function as a turn signal.	1
10-01-5020	<	Outboard Rear Flashers, Wired to OEM Brake Lights (STANDARD) The Red LED's thru the rear window flashers shall be wired to the OEM brake lights. These lights shall NOT function as brake lights when Emergency Flashers are on.	1
10-01-7100	<	Front Turn - Whelen 600-Series LED, Amber Arrow, w/ Flange On box front upper outer corners just under outer corner lights.	1
10-01-9510	<	Turn Signal / Brake - Interior, LED in Cushion Over Rear Doors (2) Turn Signals, (2) Brake LED Indicators in Cushion Over Rear Doors. - Install (2) Amber LED turn signal indicators and (2) Red LED brake light indicator on the cushion over the rear doors to inform personnel in patient compartment when the vehicle is turning and braking. These lights will have chrome bezels. Does not require any plaques.	1
		FLOOD AND LOAD SYSTEMS	1
10-02-1010	<	Scene Lighting - (4) Whelen 900 Series Super LED There shall be a total of four Whelen 900 Super LED, 24 diode, gradient 8-32 degree scene lights with chrome trim ring mounted two streetside and two curbside.	1
10-02-2030	<	Rear Load Lights - (2) Whelen 700 Series Super LED, 12 Diode 8-32° Scene (2) Whelen Model 700 Super LED, 12 diode, gradient 8-32 degree load lights over the rear module entry doors.	1
10-02-3010	<	Lighting Operation - Side Scene, Rear Load and Back-Up Lights, Standard The electrical system shall be wired so that the rear module load lights and the lower back-up lights will operate when the rear doors are open, the switch on the front panel is activated, or when the vehicle is placed in reverse. With the module power switch "off", both the lower back-up lights and the upper load lights will operate when the vehicle is	1

PART NO	S	DESCRIPTION	QTY
		placed in reverse. The curbside scene lights will operate when the curbside door is opened.	
10-02-4314	<	Scene, Additional - (1) Whelen Dual Panel Pioneer Flasher / Flood Light, Recessed There shall be a Whelen Pioneer Flasher/Flood light recessed into the front body wall. A separate switch shall be mounted in the front console that will change the light from the flash mode to the flood scene mode. The light shall be wired to activate in the flash warning mode with the warning lights and the flood mode on with ignition constant. (1) Whelen pioneer PFA2 Dual panel LED scene light installed in recess mount on the front wall of the module, just below cool bar in center. The pioneer Dual panel light to flash as a white center warning light. Also add separate switch on the front console to change light to a solid flood while in the warning mode. Also allow the pioneer to act as a front flood light with out the emergency master on. Locate switch with the Scene lights and mark as front flood.	1
10-02-7010	<	Fog / Driving Lights - Prewire Wires ran to the lower area behind grill. Switch located in front console.	1
		Cab Enty - Lighting	1
10-02-8020		Cab Entry, 4" Whelen LED Courtesy Lighting	1
		INTERIOR LIGHTING - CEILING	1
11-01-1400	<	Dome Lights - Kinequipe 8" Round LED The interior lighting system shall consist of (11) Kinequipe 8" Round LED Dome Lights fixtures in the following configuration: (3) Cot lights In the medical device rail over the primary cot (2) Bench lights over the squad bench (3) Dome lights Streetside (1) Dome light Curbside over head of squad bench (1) Dome light Curbside rear (1) Dome Light over the walkway The four outside corner lights and the (1) light over the CPR seat area and the (1) over the walkway shall be designated module dome lights and be activated when the side or rear module entrance doors are opened or by a three-way circuit allowing these lights to be turned on and off from cab or module. The lights over the primary cot and squad bench shall have switches in the module that will allow independent high/low/off control. The lights shall produce at least 35 foot candles of light over ninety percent of the cot surface area in the high setting.	1
11-01-9000	<	Timer - Restocking (STANDARD) A momentary switch to be wired direct to battery through a 15 minute timer to operate the Module Dome Lights while the vehicle is Off. This feature will enable personnel to clean and restock the vehicle, but eliminates the risk of leaving the lights on and draining the batteries. The momentary switch to be located on the curbside wall near the side entrance door.	1
		SPOTLIGHTS / HANDHELD LIGHTS	1
11-02-1000		Handheld Spotlight - Sho-Me 200,000 CP (STANDARD)	1
11-02-9100	<	Wiring for a Rechargeable Flashlight 12V Wiring for two flash lights. Direct to Batteries.	1
		ATTENDANT LIGHT	1
11-03-1500	<	Attendant Light - Kinequip LED Strip Under UL2-2.5 Cabinets, Action Wall Kinequip LED strip lighting under the upper left #2 Cabinet. Install Kinequip LED Strip Lighting on the bottom surface of the cabinets and close to the action wall. The LED strip shall be mounted in an anodized aluminum channel and run the full length of the Upper Left #2 cabinet. Includes an On/Off switch on the rear switch panel. ILOS Attendant Light.	1

PART NO	S	DESCRIPTION	QTY
12-01-5400	<	Shore Inlet - Kussmaul Super Auto-Eject, 20Amp White cover	1
12-01-8000	<	(1) Shore Indicator, "ON" Green Indicator Light Green LED waterproof indicator light installed above the shore power inlet. This light is to be wired after the GFI breaker to indicate shore power is 'ON' and breaker has not tripped.	1
12-02-0200	<	Receptacles, Interior - 110V-15A (1) Action Wall, (1) Right Stack here shall be two 110VAC 2-wire plus ground illuminated 15 amp duplex outlets, one located on the action area wall, and one in the right front stack ALS cabinet. The outlet in the ALS cabinet shall be located on the inboard wall of the lower section, above the top shelf. All 110VAC outlets shall be hospital grade.	1
12-02-2049		Receptacles, Interior - (1) Additional 110V-15A, Aft CPR Seat Counter	1
12-02-2050		Receptacles, Interior - (1) Additional 110V-15A, Action Area Wall	1
12-02-2100	< >	Receptacles, Interior - (1) Additional 110V-15A, Custom Location (each) Mounted on floor of cab behind driver seat next to console.	1
POWER SUPPLY - 110VAC			1
12-03-1110	<	Inverter Charger - Vanner 1050W, Indicator on Console The vehicle shall be equipped with a Vanner 'UL' listed 1050 watt inverter/55 amp battery charger #20-1050CUL with internal transfer relay. This system includes a battery charger indicator mounted on driver side of the radio console.	1
ENVIROMENTAL CLIMATE CONTROL SYSTEM			1
13-01-1200	<	HVAC - Central Air Flow Discharge (UM & PM) he design of the Heat/AC environmental system is to provide optimal air flow and distribution of conditioned air evenly to all areas of the module interior. Conditioned air shall not be discharged from one vent area but shall be distributed through multiple vents evenly spaced in a line down the length of the module ceiling. The plenum that supplies the vents shall be built into the module roof structure and shall not be visible. In order to support the efficient and effective performance of the system and to prevent the build-up of condensation inside, the interior of the plenum will be completely insulated with a reflective barrier insulation material.	1
13-01-2000		Climate Control - Standard (UM & PM)	1
13-02-0100		Exhaust Fan - Standard 100 CFM	1
13-02-0210		Exhaust Fan, Relocate - Behind #2.5 Cabinet	1
13-02-5602	>	HVAC Aux Front Wall COOLBAR - Hoseline, Ford F-series PC ELEC	1
13-02-9000		Heater Valves, (2) Manual Shut-off Valves	1
13-03-1000		Return Air System	1
13-03-2000		Return Air Central Plenum	1
13-03-3000		Heat /AC Cabinet	1
COT MOUNTING PROVISIONS			1
14-01-1010		Cot Mounting - Hardware	1
14-01-1110		Post & Wheel Cups - None (STANDARD)	1
14-01-1210		Safety Hook - Ship Loose	1
14-01-1230	<	Safety Hook - Stryker with bolts. With bolts shipped loose.	1
14-01-1500	<	Cot Mount - Stryker 6370 Single Center Position Note: Move cot forward a total of 6" for the additional box length Make sure to mount the attendant seat 22" from the front mounting plate.	1
OXYGEN AND AIR SYSTEMS			1
14-02-0050		Oxygen System - PC System	1
14-02-1000		O2 Cylinder Wrench - (STANDARD)	1
14-02-2000		O2 Cylinder Bracket - Zico #QR-MV (STANDARD)	1

PART NO	S	DESCRIPTION	QTY
14-02-3000		O2 Control - Electric with Manual Bypass on Action Wall. (STANDARD)	1
14-02-3160		Oxygen Regulator, with 24" braided hose extension (PC System)	1
14-02-4000	<	O2 Outlets - Ohio Style, (2) Action Wall, (1) Squad Bench (STANDARD) Note: Only one outlet in the A/A, one was moved to the ceiling per following ref. code.	1
14-02-4100		O2 Outlet - Relocate (1) Action Wall Outlet to Ceiling	1
14-02-4730	< >	O2 Gauge - 3000 psi, Compartment Wall, #1 Gauge installed on wall of #1 compartment. Mount as high as possible to allow removal of oxygen tank.	1
14-02-6120	< >	O2 Cylinder Holder - (2) FW-521 Universal Locate at the head of the squad bench, below in boxed out stepwell.	1
VACUUM SYSTEM			1
14-03-1010		Suction System - SSCOR On-Board (STANDARD)	1
14-03-3010	<	Ohio Vacuum Outlet, Quick Disconnect An Ohio style vacuum outlet shall be installed adjacent to the SSCOR suction canister. The outlet shall be provided with an Ohio style quick release barbed adapter for 5/16" suction hose.	1
MISC MEDICAL			1
14-04-1000		Fire Extinguisher - 5# (ABC) w/ Mounting Bracket. (STANDARD)	1
14-04-2020	<	IV Warmer - Minco 12VDC IV Warmer w/Switch There shall be a Minco 10A/12V heat pad/IV warmer with pad cover for interior cabinet. Includes 12V On/Off switch at action wall and thermostat preset to maintain 100 degrees F. Wired direct to batteries. Mounted in the lower section of the U2 cabinet. Includes "Heat Pad" plaque on exterior of cabinet where pad is located.	1
PAINT AND FINISH			1
15-00-0100		Road Rescue Paint Process - Standard	1
15-01-2000		Module Paint - Single Color, OEM White	1
15-01-5000		Cab Paint - Single Color, OEM White	1
GRAPHICS AND LETTERING			1
15-03-0500	X <	Two color Thunderbolt with a two inch QRS SO.GRAPH.6401 REF SR# 2013059 Scotchlite design as follows: Two color thunderbolt: LOWER 2" STRIPE TO BE White 5000 UPPER 8" STRIPE TO BE Blue 680-75 2" QRS TO BE Blue 680-75 All stripes to wrap around the back of the module.	1
15-03-3900		RR Badge Logos (STANDARD)	1
15-03-4000	<	RR Logos and Model Name (STANDARD) As a standard part of the manufacturer's production process, logos shall be applied to the following locations: Ultramedic with light colored body (3) White scotchlite RR logos: (1) on each entry door lock box (2) Black scotchlite RR Logos:(1) on each cab fender just below "A" pillar. (2) Black Scotchcal "Ultramedic" Logo" (1) each on the #4 and #6 comp. doors. (1) Road Rescue BAdge: Install just above rear diamond plate wrap on drivers side. Standard	1
15-03-4001		Ultramedic - Black Logos	1
15-03-6201	X <	Star Of Life, 32" Blue,Installed on Roof SO.STAR.6401 REF SR#2013059 Ref truck # 6355	1
15-04-1000		Nomenclature Plaques. DIESEL. (STANDARD)	1
16 - REFERENCES AND STANDARDS			1

