

LAB CONTROLS

\$0.00 0 items

Home About Support Quote Request News

Shop

Home Centrifuges Eppendorf 5804 Benchtop Centrifuge with F-34-6-38 Rotor

SALE!



Eppendorf 5804 Benchtop Centrifuge with F-34-6-38 Rotor



IN STOCK



90-DAY WARRANTY



LOW PRICE GUARANTEE

Item Number: 5804 F-34-6-38 Rotor Manufacturer:

Eppendorf Product Category: Centrifuges Brand Name:

Eppendorf Description: Eppendorf 5804 Benchtop

Centrifuge with F-34-6-38 Rotor *Have a quote from somewhere else? [Click Here](#)*

1 in stock

SKU: d2452a9a2bd5

Category: [Centrifuges](#)

Description

[Additional information](#)

Description

Item Number: 5804 F-34-6-38 Rotor

Manufacturer: Eppendorf

Product Category: Centrifuges

Brand Name: Eppendorf

Overview of Eppendorf 5804 Benchtop Centrifuge with F-34-6-38 Rotor

Eppendorf 5804 Benchtop Centrifuge with F-34-6-38 Rotor is available from Laboratory Controls LLC. This product comes with a 90 day warranty.

The bench-top centrifuges from Eppendorf are long established and enjoy a popularity that grows with every passing year. Thus, it was natural for Eppendorf to take the new technological possibilities into account and subject the popular Centrifuges 5804 (refrigerated: 5804 R) and 5810 (refrigerated: 5810 R) to a live-cell treatment. The result is a device with the same chassis, but with a considerably improved control panel and an inner life incorporating state of the art technology.

The comprehensive, modular accessory program covers separation in PCR tube strips and 1.5/2 ml test tubes as well as high-volume centrifugation of Falcon® tubes, flasks and filter plate systems ? and therefore practically all refrigerated and non-refrigerated applications up to 400 ml volume per tube.

F-34-6-38 rotor:

- 6 boreholes for different tubes (max. tube size: 85 ml)
- Max. rotational speed: 11,000 rpm (max. rcf: 15,550 x g)
- When used in Centrifuge 5810 R: max. rotational speed 12,000 rpm (max. rcf: 18,500 x g)
- Conical tubes such as 15 ml and 50 ml Falcon® tubes can be centrifuged with adapters in the fixed-angle rotor¹⁾
- Rotor, caps, adapters are autoclavable (20 min, 121°C)

Specifications

Max. RCF	20,913 x g
Max. RCF with fixed-angle rotor	20,913 x g
Max. RCF with swing-bucket rotor	4,500 x g

Max. RCF with plate rotor	2,250 × g
Speed	200 – 14,000 rpm (10 rpm steps)
Max. capacity	4 × 250 mL/
2 × 5 MTP	4 × 250 mL/
2 × 5 MTP	
Rotors available	12
Acceleration/braking ramps	10/10
Number of programs	35 user-defined programs
Timer	1 min to 99 min, with continuous run function, short-spin
Noise level	< 62 dB(A)
Power supply	230 V, 50 – 60 Hz
Max. power consumption	900 W
Dimensions (W × D × H)	47 × 55 × 34 cm

Height (with open lid)	74 cm
Weight w/o accessories	55 kg
Cooling	non-refrigerated
Temperature control range	–

Resources

Eppendorf 5804 Benchtop Centrifuge with F-34-6-38 Rotor Manual

Warranty Information

Laboratory Controls offers a best in the business full 90 day warranty on all refurbished items. This warranty covers your part against any material and or craftsmanship issues within one full year from purchase. Laboratory Controls will repair or replace your part at no charge. Please contact us for further information if you are in need of a repair.

Related products



Eppendorf 5415C Centrifuge

SALE!



Eppendorf 5424 Centrifuge

SALE!



Eppendorf 5415D Centrifuge

SALE!

Contact Us

Customer Phone
Number
(984) 444-9060

Site Info

Order Tracking
Policies
Site Map
Careers

Phone Hours

Monday - Thursday
8am - 8:00pm (EST)
Friday 8am - 6pm
(EST)

Social Media

Laboratory Controls
Facebook
PageLaboratory
Controls Twitter

U.S. Customer
Email:
sales@laboratorycon
trols.com
laboratorycontrolssal
es@gmail.com

[Privacy Policy](#)
[Terms & Conditions](#)

Saturday - Sunday
8am - 5:30pm (EST)



Mail:
6805 Dwight
Rowland Rd - Unit
611
Willow Springs, NC
27592

© 2017

Storefront designed by [WooCommerce](#).