# NEW HOLLAND G-SERIES ZERO-TURN-RADIUS MOWERS





# YARD WORK, MINUS THE WORK

# BREEZE THROUGH LAWN CARE WITH NEW HOLLAND ZERO-TURN-RADIUS MOWERS.

Who said perfection takes time? Powerful New Holland G-Series zero-turnradius mowers speed you through routine lawn maintenance faster than you ever thought possible.

These mowers literally turn on a dime, allowing you to squeeze around saplings and change direction in one graceful spin. This maneuverability not only makes you feel like a pro—it saves time with each pass, so you can finish work sooner and get back to life.

#### A CUT ABOVE THE REST

With four models ranging from 19 to 25 horsepower and mower widths from 42 to 52 inches, you'll find a New Holland zero-turn-radius mower that suits your exact needs. All models have a 7-mph speed that lets you zip through mowing jobs large and small. Other features include:

- Fore-aft adjustable seats, optional foot assist HOC kit (standard on the G4050) and arm rests (standard on the G4030 and G4050) for maximum comfort.
- Two control levers for easy operation —no thinking required!
- Hydrostatic transmission for a smooth, quiet ride
- Top-discharge design system for finecut grass with no clumping
- A deck washout port for fast deck cleaning
- Optional bagging and mulching kits to provide ultimate versatility




#### **BUILT TO LAST**

found free time.

No matter what model you choose, each New Holland mower includes a heavy-duty steel frame, tubular steel axle and cast-iron rear bumper. Nuts and bolts are used in place of self-tapping screws for added durability.

Want more? New Holland backs up each
G-series mower with a three-year limited warranty,
so you're guaranteed years of power-packed
performance. After all, you have
more important things to
worry about—like how
you'll spend all that new









## MOWING YOUR LAWN NEVER FELT SO GOOD

# POWER MEETS COMFORT IN THE NEW HOLLAND G-SERIES.

Go ahead—get comfortable. It's easy to do in the New Holland zero-turn-radius mower. The contoured, high-back seat with optional armrests (standard on the G4030 and G4050) makes this machine feel tailor-made to fit your shape. Everything adjusts to reach the right height in seconds— no tools needed.

With the smooth ride and quiet performance of the hydrostatic transmission, you'll feel like you're cruising in a luxury car. Go on: savor a sip of icy lemonade. Play your favorite tunes. Discover you do like yard work, after all.

#### INTUITIVE CONTROLS PUT YOU AT THE HELM

Operation comes naturally with the zero-turn-radius mower. Its two control levers take the place of the steering wheel, gas pedal, forward/reverse control and brake. They are ergonomically designed with hydraulic damping action to ensure smooth steering.

Each lever adjusts up and down to give you the perfect fit. Nearby, an angled side panel of controls sits within easy reach. Another one-handed adjustment lever lets you select one of seven cut heights and raise the mower deck for transport. The optional foot assist height of cut kit (standard on the G4050) makes changing the height a snap.

There's no thinking required—just the easy operation of a push mower combined with the power and efficiency of a tractor.

#### PRESERVES THE PEACE

You've worked hard to create your outdoor paradise. Why spoil the effect with a hot, noisy machine? The zero-turn-radius mower is right at home in mother nature. Its Kohler Courage engine has an internal balance system to minimize vibration, with an optional engine cover (standard on the G4050) to insulate noise and heat. Underneath it all, smooth front tires (ribbed on the G4010) and anti-scalp wheels gently massage the turf. With the quiet



transmission and nothing in front to impede your view, you might say you have the best seat in the house.

#### A QUALITY CUT, EVERY TIME

No matter what mower width you choose, each G-series mower is a full four inches deep. This creates a vacuum, allowing blades to cut and re-cut clippings into fine particles. The result: smooth, even dispersal without the clumps.

Deck washout ports provide quick cleaning underneath to maintain efficient airflow for optimum performance. Need to sharpen the blade, or get a deeper clean? No problem: the entire deck can be removed in under two minutes.



## VERSATILE PERFORMANCE

#### THE G-SERIES GIVES YOU THE FLEXIBILITY TO GET THE JOB DONE.

The zero-turn-radius mower does much more than cut grass. With these optional attachments, nothing stands between you and the yard you've always wanted.

- Double bagging system with an eightcubic-foot capacity. A high-lift mower blade set is available for the G4050.
- Mulching kit that includes aerodynamic blades, kickers and accelerators to cut clippings repeatedly for extra-fine mulch.
- Smooth tires to reduce tracking damage and allow for smooth turning around obstacles (standard on the G4020, G4030 and G4050; optional on the G4010) Twenty-inch tires on the G4050 deliver better traction and a smooth ride on uneven terrain.
- Adjustable armrests that make your ride extra-comfortable by reducing arm fatigue during long stretches (standard on the G4030 and G4050; optional on the G4010 and G4020).

- Rubber floor mat to reduce vibration and dampen noise during operation (not available on the G4050).
- Rear engine guard that protects the back of the engine above the bumper (standard on the G4020, G4030 and G4050; optional on the G4010).
- Engine cover that shields the driver from heat and noise while shielding the engine from dust, clippings and other debris.
- Foot assist height of cut kit (optional on the G4010 and G4020).
- Hitch kit that allows you to pull lightduty attachments.
- Front light kit (optional on the G4050 only) to make mowing possible in low light.
- Sunshade kit (optional on the G4050 only) to protect your skin and eyes from the hot summer sun.



Rear engine guard



Rubber floor mat





Adjustable armrests



Double bagging system

MODELS	G4010	G4020	G4030	G4050
NGINE				
lorsepower, hp (kW)	19 (14.2)	21 (15.7)	23 (17.2)	25 (18.6)
1ake	Kohler Courage SV590	Kohler Courage SV610	Kohler Courage SV720	Kohler Courage PRO
lo. of cylinders	1	1	2	2
io. of cylinders	1	1		
Cooling system				
uel capacity, gal. (L)		3 (11.4)		4 (15.1)
ull pressure lubrication		Stan	dard	
tarter key w/safety interlock	Standard			
ir cleaner				
PRIVE SYSTEM				
ype	Dual hydrostatic: trans	axle with integral nump and mo	tor: one at each wheel	Twin hydro-gear 7T2800
,pe	Duai riyarostatic. trans	axie with integral pump and mo	tor, one at each wheel	hydrostatic transaxle
		- 0 /		with charge pumps
Nax speed, reverse, mph (kph)				5 (8.0)
nplement clutch		Elec	tric	
RAKES				
ervice brake				
arking brake Lock	Automatic	engagement with steering lever	s in neutral	Manual LH lever
LECTRICAL				
oltage				
PERATOR STATION AND CONT	ROLS			
teering		Dual padded lever hydrostat	ic with hydraulic dampenina	
eat (adjustable fore and aft)	15" mid back	18" high back	18" high back	18" high back
rmrests	Optional	Optional	Standard	Standard
	Орцопа	Ориона		
up noider	Standard			
	Standard			
ront casters	Double yoke			
VHEELS AND TIRES				
ront Casters	10 x 4 ribbed	10 x 4 smooth	10 x 4 smooth	10 x 4 smooth
lear	18 x 7.5-8, 2-ply	18 x 9.5-8, 2-ply	18 x 9.5-8, 2-ply	20 x 10, 4-ply
DIMENSIONS, in. (cm)				
ength, overall				
with grass catcher		90.0 (228.6)		NA
less grass catcher				
3	•••••	/5.1 (	105.7 /	••••••
Vidth, overall	50.0 (40.4 7)	(0.0.(4.(0.0)	(0.0.(4.(0.0)	(50 (4 (5 4)
with deck deflector down	53.8 (136.7)	63.0 (160.0)	63.0 (160.0)	65.0 (165.1)
with deck deflector up	46.0 (116.8)	53.5 (135.9)	53.5 (135.9)	53.0 (134.6)
with grass catcher	52.8 (134.1)	56.8 (144.3)	56.8 (144.3)	NA
leight, overall, to top of seat	37.2 (94.5)	40.2 (102.1)	40.2 (102.1)	42.2 (107.2)
Vheelbase				
urning radius, inside rear wheei Iet weight, estimated, lb. (kg)	Zero turn			649 (294.4)
	, , , , ,			. ,,
<b>10WER DECKS</b> (optional mulching kits available)				
	C+ I I	NIA	NIA	NIA
2 in. (107 cm) side discharge	Standard	NA .	NA .	NA
0 in. (127 cm) side discharge	NA	Standard	Standard	NA
2 in. (132 cm) side discharge	NA	NA	NA	Standard
pindles	2	3	3	3
nti-scalp gauge wheels				
TTACHMENTS & ACCESSORIES				
-bag grass catcher (8 cu. ft./.23 m	3)	Onti	onal	
Pear engine guard	Ontional	Standard	Standard	Standard
ear erigirie gudru	Ориона	Standard	Standard	Standard
		Opti		
	0 1	Optional	Standard	Standard
ear engine guard ngine top coveroot assist height of cut kit	Optional	-		C: 1 1
oot assist height of cut kit mooth-tread front tires	Optional	Standard	Standard	Standard
oot assist height of cut kit mooth-tread front tires	Optional	Standard		
oot assist height of cut kit mooth-tread front tires	Optional	Standard		
oot assist height of cut kit	Optional	Standard NAOpti	onal	Optional

# VALUE, SERVICE AND SOLUTIONS

When you place your confidence in New Holland agricultural equipment, you also get the finest support. Your local New Holland dealer stands behind you at every step with the equipment, parts, service, and financial services you and your operation need.

Become part of the family. You'll find the perfect combination of equipment at your New Holland dealer, including a full line of tractors, hay and forage equipment, harvesting, crop production and material handling equipment. We're one big productive family. Ask your New Holland dealer about becoming part of the family and receive special FAMILY VALUE\$ discounts.

## FAMILY**VALUE\$**

Quality parts and service. Turn to your New Holland dealer after the sale for expert, factory-trained service and genuine New Holland-branded parts to keep you working productively season after season.

Financing solutions. Your New Holland dealer can tell you about smart ways to turn your financial challenges into opportunities with a portfolio of innovative financial services available through CNH Capital, including customized financing, leasing, insurance, and the purchasing convenience of a Commercial Revolving Account.



For reliable equipment, parts and service – or just honest advice on farming and finance – turn to New Holland and your trusted New Holland dealer.



#### YOUR NEW HOLLAND DEALER



We are proud to support the FFA.

#### Visit our Web site at www.newholland.com/na

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas

© 2008 CNH America LLC. All rights reserved. New Holland and CNH Capital are registered trademarks of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

