Environmental & Combustion Controls

> Wireless FocusPRO® Thermostats

TH5320R1002

Wireless FocusPRO® Non-Programmable Thermostat. RedLINK™ Enabled. Up to 3H/2C Heat Pump or Up to 2H/2C Conventional. Gas, Oil, Electric, Heat Pump, Forced Warm Air, Hot Water, Steam or Gravity. Battery Power Only.

Locate Distributors   Product Specifications   Literature and Documents

Overview

Easily add a zone to a TrueZONE™ system without running new wires. Choose from programmable or non-programmable.

Features

- Powered by RedLINK™ reliability
- No interference with other wireless devices in the home
- Works with compatible RedLINK™ enabled devices
- Same great features of the FocusPRO® thermostat now wireless
- Installs in minutes
- Can display outdoor temperature and humidity
- 1 year battery life
- 2 month low battery warning
- Dual Fuel enabled - requires THM5320R1000 Equipment Interface Module and C7089R1013 Wireless Outdoor Sensor (sold separately).

Product Specifications   → Back To Top

Description	Easily add a zone to a TrueZONE™ system without running new wires. Choose from programmable or non-programmable.
Application	Gas, oil, electric, heat pump, forced warm air, hot water, steam or gravity
Mounting	Horizontal
Changeover	Auto/Manual Selectable
Color	Premier White®
Stages	Up to 3 Heat / 2 Cool Heat Pump or Up to 2 Heat / 2 Cool Conventional
Power Method	Battery

Replacement Parts

- 50007072-001 - Replacement Battery Holder for FocusPRO TH5220, TH5320, TH6110, TH6220, and TH6320 Thermostat

Product Accessories

- 50002883-001 - FocusPRO 5000/6000 and PRO 3000/4000 Cover Plate Assembly
- 50007298-001 - 12 pack of medium coverplates (5 in. x 6 7/8 in.)
- REM5000R1001 - Use the Portable Comfort Control anywhere in the home to experience a new level of comfort and convenience. RedLINK™ Enabled. Works in both zoned and non-zoned applications.
- C7089R1013 - Senses outdoor temperature and humidity to display on RedLINK™ enabled thermostats and accessories.
- C7735A1000 - Mount on return duct for backup control of non-zoned RedLINK™ enabled wireless systems. Works with the EIM to maintain safe indoor temperatures if power is lost at the wireless thermostat.

Switch Positions (Fan)	AUTO-ON
Switch Positions (System)	HEAT-OFF-COOL-AUTO-EM.HEAT
Dimensions (in.)	3 9/16 in. High X 5 13/16 in. Wide X 1 1/2 in. Deep
Dimensions (mm)	91 mm High X 147 mm Wide X 38 mm Deep
Setting Temperature Range (F)	Heat: 40 F to 90 F; Cool: 50 F to 99 F
Setting Temperature Range (C)	Heat: 4.5 C to 32 C; Cool: 10 C to 37 C
Differential Temperature (F)	± 1 F
Differential Temperature (C)	±0.5 C
Sensor Element	Thermistor
Operating Temperature Range (F)	32 F to 120 F
Operating Temperature Range (C)	0 C to 48.9 C
Operating Humidity Range (% RH)	5 to 90% RH, non-condensing
Comments	Thermostat is also available in kits for zoned and non-zoned systems
Parts Needed for Operation (not included) - TrueZONE™ System	HZ432 or HZ322 TrueZONE™ panel; THM4000R1000 Wireless Adapter
Parts Needed for Operation (not included) - Non-Zoned System	THM5320R1000 Equipment Interface Module