

	Compression	A Complete Line for Copper and Aluminum Conductors <ul style="list-style-type: none">• Lugs• Taps• Splices• Custom Products	A 1 - 87
	ILSCONS	<ul style="list-style-type: none">• Color Coded• Manufactured from high strength copper alloy• Electro-tin plated• Vinyl insulation• Packaged in convenient small quantities• UL Listed and CSA Certified for 600 volts, 90° C	A1 88 - 106
	Split Bolts	For Copper and Aluminum Conductors <ul style="list-style-type: none">• Split Bolts• Two Bolt Clamps• Labor Saving Alternative Products	B 107 - 125
	Mechanical	A Complete Line for Copper and Aluminum Conductors <ul style="list-style-type: none">• Lugs• Taps• Splices• Custom Products	C 126 - 218
	Insulated Mechanical	<ul style="list-style-type: none">• Multi-tap and splicer reducer connectors• Broad wire range reduces inventory requirements• Insulating covers eliminate need to tape	D 219 - 230
	Insulation Piercing	Labor Saving Products <ul style="list-style-type: none">• Taps• Splices	E 231 - 232
	Power Distribution Blocks	<ul style="list-style-type: none">• Modular Types• One, Two and 3 Poles• Custom Products	F 233 - 253
	Grounding	<ul style="list-style-type: none">• Overhead• Underground• Copper and Aluminum	G 254 - 286

	<h2>Flex Braid</h2>	<ul style="list-style-type: none"> • Manufactured from pure copper braid • Electro-tin plated • Seamless pure copper ferrules • Inside ferrule ends are rounded • Swedged terminal to copper braid by cold forming • Extra flexible braided connector • Rated for 600 volts 	<div style="background-color: #0056b3; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">G1</div> <p>287 - 291</p>
	<h2>Underground</h2>	<ul style="list-style-type: none"> • Fully Insulated Watertight Products • Direct Burial Products 	<div style="background-color: #0056b3; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">H</div> <p>292 - 314</p>
	<h2>Heat Shrink, Silicone Tape</h2>	<ul style="list-style-type: none"> • Heavy Wall Tubing • Heavy Wall End Caps • Medium Wall Tubing • Thin Wall Tubing • Wrap 'N Seal 	<div style="background-color: #0056b3; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">I</div> <p>315 - 322</p>
	<h2>Tools</h2>	<ul style="list-style-type: none"> • Compression Tools and Dies • Mechanical Tools • Strippers • Cable Cutters 	<div style="background-color: #0056b3; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">J</div> <p>323 - 353</p>
	<h2>Specialty</h2>	<ul style="list-style-type: none"> • Oxide Inhibitor • Duct Seal • Neutral Bars 	<div style="background-color: #0056b3; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">K</div> <p>354 - 368</p>
	<h2>Merchandising</h2>		<div style="background-color: #0056b3; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">L</div> <p>369</p>
	<h2>Canada</h2>	<ul style="list-style-type: none"> • Refer to Canadian Catalog Supplement Published Separate • Contact ILSCO of Canada 	<div style="background-color: #0056b3; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">M</div> <p>370</p>
	<h2>Technical Information</h2>		<div style="background-color: #0056b3; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">N</div> <p>371 - 385</p>

Pictorial Index




















Compression

<p>CSWS</p>  <p>2 - 4</p>	<p>CSWD</p>  <p>5 - 10</p>	<p>CLWS</p>  <p>11 - 13</p>	<p>CLNS</p>  <p>14 - 16</p>	<p>CLWD</p>  <p>17 - 22</p>	<p>CLND</p>  <p>23 - 28</p>
<p>CLNF</p>  <p>29 - 30</p>	<p>CLNU</p>  <p>31</p>	<p>CSWN</p>  <p>32</p>	<p>CLWN</p>  <p>33</p>	<p>CCL</p>  <p>34 - 39</p>	<p>CRAM</p>  <p>40 - 41</p>
<p>SOLDER LUGS</p>  <p>42</p>	<p>CT</p>  <p>43</p>	<p>CTL</p>  <p>44</p>	<p>CCS</p>  <p>45</p>	<p>GGA</p>  <p>46</p>	<p>GGC</p>  <p>47</p>
<p>ULT</p>  <p>48</p>	<p>ELT</p>  <p>49</p>	<p>ALNN</p>  <p>50</p>	<p>ACL, ACN</p>  <p>51 - 54</p>	<p>2ACL, 2ACN</p>  <p>55 - 56</p>	<p>ASL</p>  <p>57</p>
<p>CPM, CPML</p>  <p>58 - 60</p>	<p>ACM</p>  <p>61 - 63</p>	<p>ACO</p>  <p>64 - 65</p>	<p>ACO-90</p>  <p>66</p>	<p>IACL</p>  <p>67</p>	<p>2IACL</p>  <p>68</p>
<p>AS</p>  <p>69 - 71</p>	<p>UCS</p>  <p>72</p>	<p>PICS</p>  <p>73</p>	<p>P840</p>  <p>74</p>	<p>AH</p>  <p>75</p>	<p>HT</p>  <p>76</p>
<p>RLT</p>  <p>77</p>	<p>COMPRESSION DIE INDEX</p> <p>78 - 87</p>				

ILSCONS

COOL SEAL  89	CRIMP 'N SEAL Rings  90	CRIMP 'N SEAL Forks, Splices, Disconnects, Bullets  91 - 92	ILSCON KITS  93	ILSCONS Non-Insulated Rings  94 - 97	ILSCONS Vinyl Rings  98 - 99
ILSCONS High Temperature Rings  100	ILSCONS Non-Insulated Forks  101	ILSCONS Vinyl Forks  102	ILSCONS Non-Insulated Splices  103	ILSCONS Vinyl Splices  104	ILSCONS Disconnects and Flag Terminals  105
ILSCON TOOLS  106					

Split Bolts

IK  108	IK3  109	SK  110	IKB  111	IKS  112	AK  113
DBA, DBA-S  114	IPC  115	GTA  116	SPAR  117	GTT  118	GTC  119
GT2  120	GT4T  121	GTA/GTT KIT  122 MGTT 123	PTA  124	PCT  125	

<p>TA</p>  <p>128</p>	<p>AU</p>  <p>129</p>	<p>T3A</p>  <p>130</p>	<p>T4A4</p>  <p>131</p>	<p>PB</p>  <p>132</p>	<p>TLK</p>  <p>133</p>	
<p>USGL</p>  <p>134</p>	<p>SPA</p>  <p>135</p>	<p>CA</p>  <p>136</p>	<p>GTA</p>  <p>137</p>	<p>GTT</p>  <p>138</p>	<p>GTC</p>  <p>139</p>	<p>GT2</p>  <p>140</p>
<p>GT4T</p>  <p>141</p>	<p>MGTT</p>  <p>142</p>	<p>PTA</p>  <p>143</p>	<p>PDH</p>  <p>144 - 145</p>	<p>PDE</p>  <p>146</p>	<p>PDL</p>  <p>147</p>	
<p>PDS</p>  <p>148 - 149</p>	<p>PDM</p>  <p>150 - 151</p>	<p>LDAU, LDBU</p>  <p>152</p>	<p>PDBU</p>  <p>153 - 155</p>	<p>LDA, LDB</p>  <p>156</p>	<p>PDA, PDC</p>  <p>157</p>	
<p>PDB</p>  <p>158 - 163</p>	<p>IPC</p>  <p>164</p>	<p>AK</p>  <p>165</p>	<p>DBA/DBA-S</p>  <p>166</p>	<p>AGC</p>  <p>167</p>	<p>SGC</p>  <p>167</p>	
<p>SGB</p>  <p>168</p>	<p>GBL</p>  <p>169</p>	<p>GBT</p>  <p>170</p>	<p>PED-Z</p>  <p>171</p>	<p>PED-X</p>  <p>172</p>	<p>PSA-Z</p>  <p>172</p>	
<p>PEC</p>  <p>172</p>	<p>PED-CP</p>  <p>173</p>	<p>PET</p>  <p>174</p>	<p>PTT</p>  <p>175</p>	<p>NB</p>  <p>176</p>	<p>USPA-SS</p>  <p>177</p>	
<p>DBK</p>  <p>178</p>	<p>ASK</p>  <p>178</p>	<p>SS, SSK, SSKC</p>  <p>179</p>	<p>PG</p>  <p>180</p>	<p>GRM</p>  <p>181</p>	<p>GRF</p>  <p>181</p>	

Pictorial Index


Mechanical (continued)

<p>SLU/SAU</p>  <p>182</p>	<p>SLS/SAS</p>  <p>182</p>	<p>E</p>  <p>183</p>	<p>H</p>  <p>183</p>	<p>SLUH</p>  <p>184</p>	<p>LO</p>  <p>185</p>
<p>VT/LO-S</p>  <p>186</p>	<p>XT</p>  <p>187</p>	<p>LY</p>  <p>187</p>	<p>CP</p>  <p>188</p>	<p>CO</p>  <p>189 - 190</p>	<p>COPP</p>  <p>191</p>
<p>TC</p>  <p>192</p>	<p>SX</p>  <p>193</p>	<p>2SC</p>  <p>194</p>	<p>N</p>  <p>195</p>	<p>MU</p>  <p>196</p>	<p>LU</p>  <p>196</p>
<p>CL</p>  <p>197 - 198</p>	<p>HL</p>  <p>199</p>	<p>CL</p>  <p>200</p>	<p>CL</p>  <p>200</p>	<p>H2L</p>  <p>201</p>	<p>H3L</p>  <p>202</p>
<p>CGRC</p>  <p>203</p>	<p>BGRC</p>  <p>204</p>	<p>SRC</p>  <p>205</p>	<p>GRC</p>  <p>206</p>	<p>DCGC</p>  <p>207</p>	<p>BGC</p>  <p>208 - 209</p>
<p>BGDB</p>  <p>210</p>	<p>D167</p>  <p>211</p>	<p>CAN</p>  <p>212</p>	<p>N-174</p>  <p>212</p>	<p>IK</p>  <p>213</p>	<p>IK3</p>  <p>214</p>
<p>SK</p>  <p>215</p>	<p>IKB</p>  <p>216</p>	<p>IKS</p>  <p>217</p>	<p>TORQUE INDEX</p> <p>218</p>		

Insulated Mechanical

PBT, PBTO  220	PBTD  221 - 222	PBTS  223 - 224	PBTM  225	PBTF  226 - 228	PCT  229
SPAR  230					







Insulation Piercing



Power Distribution Blocks

























PDH  234 - 235	PDE  236	PDL  237	PDS  238 - 239	PDM  240 - 241
LDAU, LDBU  242	PDBU  243 - 245	LDA, LDB  246	PDA, PDC  247	PDB  248 - 253

Grounding





GGA  256	GGC  257	ULT  258	ELT  259	CGRC  260	BGRC  261
--	--	--	--	---	---

Pictorial Index

Grounding

SRC  262	GRC  263	RLT  264	DCGC  265	BGC  266 - 267	BGDB  268
BGCS  269	SPS  270 - 271	SPD  272 - 273	TTGC  274	GUB  275	GPL3  276
GS/GSR  277	D167  278	CAN, N-174  279	AGC  280	SGC  280	SGB  281
GBL  282	CGBL  283	GBT  284	GRM  285	GRF  285	NB  286

Flex Braid

T  288	T  289	T  290	T  291
---	---	--	---








Underground

DBK  293	ASK  293	USPA-SS  294	SS, SSK, SSKC  295	PED-SS  296	GGA  297
GGC  298	ELT  299	SLU-DB, XT-DB  300	CGRC  301	BGRC  301	SRC  302


















Underground (continued)

GRC  303	RLT  304	BGC  305	BGDB  306	SPS  307 - 308	SPD  309 - 310
TTGC  311	GUB  312	GPL3  313	CGBL  314		

Heat Shrink









SILICONE TAPE  316	HEAVY WALL  317	HEAVY WALL End Caps  318	MEDIUM WALL  319	THIN WALL  320	THIN WALL Bulk Reels  321
HEAT GUN  322					

Tools












IDTB-6-LIO  324	ILCB-12-LIO  325	ILC-10-N  326	MT-25  327	94285  328	ND-58  329
ND-60  330	ILC-12-N  331	ILC-12H-N  332	IDT-6  333	IDT-6H  334	ILC-15H  335
5ACR  336	FP-1  337	HH-10N  338	COMPRESSION INDEX 339 - 345	COMPRESSION DIES & ADAPTORS  346 - 348	TOOL ACCESSORIES & ADAPTORS  349

Pictorial Index

Tools (continued)

94130  350	94145  350	WS-1  350	CTR  351	TS  352	TW  352
WR  352	94502  353				

Specialty Products

C  355	M  356	M  357	D167  358	CAN  359	N-174  359
NB  360	DE-OX  361	DUCT SEAL  362	NBW  363	Cable Ties  364 - 368	

Merchandising



ILSCO Alpha Numeric Index

Catalog No.	Page No.	Catalog No.	Page No.
ACN	51-54	FP-1	337
ACL	51-54	GBL	169, 282
2ACL	55-56	GBT	170, 284
ACM	61-63	GGA	46, 256, 297
2ACN	55	GGC	47, 257, 298
ACO	64-65	GPL3	276, 313
ACO-90	66	GRC	206, 236, 303
5ACR	340	GRF	181, 285
AGC	167, 280	GRM	181, 285
AH	75	GS	277
AK	113, 165	GSR	277
AS	69-71	GTA	116, 137
ASK	178, 293	GTC	119, 139
ASL	57	GTT	118, 138
AU	129	GT2	120, 140
BGC	208-209, 266-267, 305	GT4T	121, 141
BGCS	269	GTA/GTT KIT	122
BGDB	210, 368, 306	GUB	275, 312
BGRC	204, 261, 301	H	183
C	355	Hardware	383
CA	136	Heat Shrink	3159-322
Cable Ties	364-368	HH-10N	338
CAN	212, 279, 359	HL	199
CCL	34-39	H2L	201
CCS	45	H3L	202
CGBL	283, 314	HT	76
CGRC	203, 260, 301	HW	352
CL	197-198, 200	2IACL	68
CLND	23-28	IACL	67
CLNF	29-30	IDT-6	333
CLNS	14-16	IDT-6H	334
CLNU	31	IDTB-6-LIO	324
CLWD	17-22	IK	108, 213
CLWN	33	IK3	109, 214
CLWS	11-13	IKB	111, 216
CO	189-190	IKS	112, 217
Compression Dies	85-87, 346-348	ILC-10-N	326
Compression Index	78-84, 339-345	ILC-12-N	331
Cool Seal	89	ILC-12H-N	332
COPP	191	ILC-15H	335
CP	188	ILCB-12-LIO	325
CPM	58-60	ILD	85, 346
CPML	58-60	Ilscos	94-105
CRAM	40-41	Ilscos Kits	93
Crimp 'N Seal	90-92	Ilscos Tools	106
CSWD	5-10	IPC	115, 164, 231-232
CSWN	32	LDA	156, 246
CSWS	2-4	LDAU	152, 242
CT	43	LDB	156, 246
CTL	44	LDBU	152, 242
CTR	351	LO	185
DCGC	207, 265	LO-S	186
DBA	114, 166	LU	196
DBA-S	114, 166	LY	187
DBK	178, 293		
D167	211, 278, 358		
DE-OX	361		
DR	352		
Duct Seal	362		
E	183		
E (Screws)	212, 279, 359		
ELT	49, 259, 299		



Catalog No.	Page No.
M	356-357
Merchandising	369
MGTT	123, 142
MIS	316
MT-25	327
MU	196
N	195
NB	176, 286, 360
NBW	363
ND	329-330
N-174	212, 279, 359
P840	74
PB	132
PBT	220
PBTD	221-222
PBTF	226-228
PBTM	225
PBTO	220
PBTS	223-224
PCT	125, 229
PDA	157, 247
PDB	158-163, 248-253
PDBU	153-155, 243-245
PDC	157, 247
PDE	146, 236
PDH	144-145, 234-235
PDL	147, 237
PDM	150-151, 240-241
PDS	148-149, 238-239
PEC	172
PED-Z	171
PED-CP	173
PED-SS	296
PED-X	172
PET	174
PG	180
PICS	73
PSA-Z	172
PTA	124, 143
PTT	175
R-16	212, 279, 359
RLT	77, 264, 304
SAU	182
SAS	182
2SC	194
SGB	168, 281
SGC	167, 280
SK	110, 215
SLS	182
SLU	182
SLU-DB	182, 300
SLUH	184
Solder Lugs	42
SPA	135
SPAR	117, 230

Catalog No.	Page No.
SPD	272-273, 309-310
SPS	270-271, 307-308
SRC	205, 262, 302
SS	179, 295
SSK	179, 295
SSKC	179, 295
SX	193
T	288-291
TA	128
T3A	130
T4A4	131
TC	192
Technical Information	371-385
TK	352
TLK	133
Torque Index	218, 382
TS	352
TTGC	274, 311
TW	352
Tool Accessories	349
Tools	324-353
UCS	72
ULT	48, 258
USGL	134
USPA-SS	177, 294
VT	186
WC	352
WR	352
WS	106, 350
XT	187
XT-DB	187, 300
21000	317
22000	319
23000	318
24000	320
25000	320
26000	321
27000	322, 353
30000	92
31000	90-92
44000	94-104
45000	99, 102, 104-105
94130	106, 350
94145	106, 350
94285	328
94502	322, 353
94504	322, 353
99200	316

Compression

<p>CSWS</p> <p>2 - 4</p>	<p>CSWD</p> <p>5 - 10</p>	<p>CLWS</p> <p>11 - 13</p>	<p>CLNS</p> <p>14 - 16</p>	<p>CLWD</p> <p>17 - 22</p>	<p>CLND</p> <p>23 - 28</p>
<p>CLNF</p> <p>29 - 30</p>	<p>CLNU</p> <p>31</p>	<p>CSWN</p> <p>32</p>	<p>CLWN</p> <p>33</p>	<p>CCL</p> <p>34 - 39</p>	<p>CRAM</p> <p>40 - 41</p>
<p>SOLDER LUGS</p> <p>42</p>	<p>CT</p> <p>43</p>	<p>CTL</p> <p>44</p>	<p>CCS</p> <p>45</p>	<p>GGA</p> <p>46</p>	<p>GGC</p> <p>47</p>
<p>ULT</p> <p>48</p>	<p>ELT</p> <p>49</p>	<p>ALNN</p> <p>50</p>	<p>ACL, ACN</p> <p>51 - 54</p>	<p>2ACL, 2ACN</p> <p>55 - 56</p>	<p>ASL</p> <p>57</p>
<p>CPM, CPML</p> <p>58 - 60</p>	<p>ACM</p> <p>61 - 63</p>	<p>ACO</p> <p>64 - 65</p>	<p>ACO-90</p> <p>66</p>	<p>IACL</p> <p>67</p>	<p>2IACL</p> <p>68</p>
<p>AS</p> <p>69 - 71</p>	<p>UCS</p> <p>72</p>	<p>PICS</p> <p>73</p>	<p>P840</p> <p>74</p>	<p>AH</p> <p>75</p>	<p>HT</p> <p>76</p>
<p>RLT</p> <p>77</p>	<p>COMPRESSION DIE INDEX</p> <p>78 - 87</p>				

A


TYPE CSWS

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Dimensions					Die Color Code	Die Index	O.D.	I.D.
						A	B	C	D	G				
CSWS-8-10	#8 AWG	#8 FLEX	-	10	0.219	0.562	0.500	1.257	0.374	0.258	Red	I-21	0.272	0.179
CSWS-8-14	#8 AWG	#8 FLEX	-	1/4	0.281	0.680	0.500	1.375	0.486	0.320	Red	I-21	0.272	0.179
CSWS-8-516	#8 AWG	#8 FLEX	-	5/16	0.343	0.875	0.500	1.570	0.532	0.352	Red	I-21	0.272	0.179
CSWS-8-38	#8 AWG	#8 FLEX	-	3/8	0.406	0.875	0.500	1.570	0.593	0.414	Red	I-21	0.272	0.179
CSWS-6-10	#6 AWG	#6 FLEX	-	10	0.219	0.562	0.500	1.257	0.411	0.258	Blue	I-24	0.320	0.225
CSWS-6-14	#6 AWG	#6 FLEX	-	1/4	0.281	0.680	0.500	1.375	0.411	0.320	Blue	I-24	0.320	0.225
CSWS-6-516	#6 AWG	#6 FLEX	-	5/16	0.343	0.875	0.500	1.570	0.532	0.352	Blue	I-24	0.320	0.225
CSWS-6-38	#6 AWG	#6 FLEX	-	3/8	0.406	0.875	0.500	1.570	0.593	0.414	Blue	I-24	0.320	0.225
CSWS-6-12	#6 AWG	#6 FLEX	-	1/2	0.562	1.250	0.500	1.945	0.750	0.546	Blue	I-24	0.320	0.225
CSWS-4-10	#4 AWG	-	4-6 AWG	10	0.219	0.562	0.500	1.296	0.486	0.258	Gray	I-29	0.343	0.250
CSWS-4-14	#4 AWG	-	4-6 AWG	1/4	0.281	0.680	0.500	1.414	0.486	0.320	Gray	I-29	0.343	0.250
CSWS-4-516	#4 AWG	-	4-6 AWG	5/16	0.343	0.875	0.500	1.609	0.486	0.352	Gray	I-29	0.343	0.250
CSWS-4-38	#4 AWG	-	4-6 AWG	3/8	0.406	0.875	0.500	1.609	0.593	0.414	Gray	I-29	0.343	0.250
CSWS-4-12	#4 AWG	-	4-6 AWG	1/2	0.562	1.250	0.500	1.984	0.750	0.546	Gray	I-29	0.343	0.250
CSWS-3-10	#3 AWG	#4 FLEX	3-6 AWG	10	0.219	0.562	0.625	1.442	0.532	0.258	White	I-29	0.375	0.275
CSWS-3-14	#3 AWG	#4 FLEX	3-6 AWG	1/4	0.281	0.680	0.625	1.560	0.532	0.320	White	I-29	0.375	0.275
CSWS-3-516	#3 AWG	#4 FLEX	3-6 AWG	5/16	0.343	0.875	0.625	1.755	0.532	0.352	White	I-29	0.375	0.275
CSWS-3-38	#3 AWG	#4 FLEX	3-6 AWG	3/8	0.406	0.875	0.625	1.755	0.593	0.414	White	I-29	0.375	0.275
CSWS-3-12	#3 AWG	#4 FLEX	3-6 AWG	1/2	0.562	1.250	0.625	2.130	0.750	0.546	White	I-29	0.375	0.275
CSWS-2-10	#2 AWG	-	2-6 AWG	10	0.219	0.562	0.625	1.473	0.599	0.258	Brown	I-33	0.421	0.312
CSWS-2-14	#2 AWG	-	2-6 AWG	1/4	0.281	0.680	0.625	1.591	0.599	0.320	Brown	I-33	0.421	0.312
CSWS-2-516	#2 AWG	-	2-6 AWG	5/16	0.343	0.875	0.625	1.786	0.599	0.352	Brown	I-33	0.421	0.312
CSWS-2-38	#2 AWG	-	2-6 AWG	3/8	0.406	0.875	0.625	1.786	0.599	0.414	Brown	I-33	0.421	0.312
CSWS-2-12	#2 AWG	-	2-6 AWG	1/2	0.562	1.250	0.625	2.161	0.750	0.546	Brown	I-33	0.421	0.312
CSWS-1-10	#1 AWG	#2 FLEX	1-6 AWG	10	0.219	0.562	0.625	1.517	0.673	0.258	Green	I-37	0.468	0.359
CSWS-1-14	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	0.875	0.625	1.830	0.673	0.320	Green	I-37	0.468	0.359
CSWS-1-516	#1 AWG	#2 FLEX	1-6 AWG	5/16	0.343	0.875	0.625	1.830	0.673	0.352	Green	I-37	0.468	0.359
CSWS-1-38	#1 AWG	#2 FLEX	1-6 AWG	3/8	0.406	0.875	0.625	1.830	0.673	0.414	Green	I-37	0.468	0.359
CSWS-1-12	#1 AWG	#2 FLEX	1-6 AWG	1/2	0.562	1.250	0.625	2.205	0.750	0.546	Green	I-37	0.468	0.359
CSWS-1/0-10	1/0 AWG	#1 FLEX	1/0-6 AWG	10	0.219	0.562	0.750	1.668	0.738	0.258	Pink	I-42	0.515	0.390
CSWS-1/0-14	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	0.875	0.750	1.981	0.738	0.320	Pink	I-42	0.515	0.390
CSWS-1/0-516	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	0.875	0.750	1.981	0.738	0.352	Pink	I-42	0.515	0.390
CSWS-1/0-38	1/0 AWG	#1 FLEX	1/0-6 AWG	3/8	0.406	0.875	0.750	1.981	0.738	0.414	Pink	I-42	0.515	0.390
CSWS-1/0-12	1/0 AWG	#1 FLEX	1/0-6 AWG	1/2	0.562	1.250	0.750	2.356	0.738	0.546	Pink	I-42	0.515	0.390

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207


TYPE CSWS

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Dimensions					Die Color Code	Die Index	O.D.	I.D.
						A	B	C	D	G				
CSWS-2/0-10	2/0 AWG	1/0 FLEX	2/0-4 AWG	10	0.219	0.562	0.750	1.708	0.811	0.258	Black	I-45	0.562	0.437
CSWS-2/0-14	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	0.875	0.750	2.021	0.811	0.320	Black	I-45	0.562	0.437
CSWS-2/0-516	2/0 AWG	1/0 FLEX	2/0-4 AWG	5/16	0.343	0.875	0.750	2.021	0.811	0.352	Black	I-45	0.562	0.437
CSWS-2/0-38	2/0 AWG	1/0 FLEX	2/0-4 AWG	3/8	0.406	0.875	0.750	2.021	0.811	0.414	Black	I-45	0.562	0.437
CSWS-2/0-12	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/2	0.562	1.250	0.750	2.396	0.811	0.546	Black	I-45	0.562	0.437
CSWS-3/0-10	3/0 AWG	2/0 FLEX	3/0-2 AWG	10	0.219	0.562	0.750	1.751	0.885	0.258	Orange	I-50	0.609	0.484
CSWS-3/0-14	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/4	0.281	0.875	0.750	2.064	0.885	0.320	Orange	I-50	0.609	0.484
CSWS-3/0-516	3/0 AWG	2/0 FLEX	3/0-2 AWG	5/16	0.343	0.875	0.750	2.064	0.885	0.352	Orange	I-50	0.609	0.484
CSWS-3/0-38	3/0 AWG	2/0 FLEX	3/0-2 AWG	3/8	0.406	0.875	0.750	2.064	0.885	0.414	Orange	I-50	0.609	0.484
CSWS-3/0-12	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/2	0.562	1.250	0.750	2.439	0.885	0.546	Orange	I-50	0.609	0.484
CSWS-4/0-14	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	0.875	0.875	2.241	0.999	0.320	Purple	I-54	0.687	0.546
CSWS-4/0-516	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	0.875	0.875	2.241	0.999	0.352	Purple	I-54	0.687	0.546
CSWS-4/0-38	4/0 AWG	3/0 FLEX	4/0-1 AWG	3/8	0.406	0.875	0.875	2.241	0.999	0.414	Purple	I-54	0.687	0.546
CSWS-4/0-12	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.250	0.875	2.616	0.999	0.546	Purple	I-54	0.687	0.546
CSWS-250-516	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	5/16	0.343	0.875	1.063	2.469	1.088	0.352	Yellow	I-62	0.750	0.593
CSWS-250-38	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	0.875	1.063	2.469	1.088	0.414	Yellow	I-62	0.750	0.593
CSWS-250-12	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/2	0.562	1.250	1.063	2.844	1.088	0.546	Yellow	I-62	0.750	0.593
CSWS-300-516	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	5/16	0.343	0.875	1.063	2.525	1.189	0.352	White	I-66	0.812	0.660
CSWS-300-38	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	3/8	0.406	0.875	1.063	2.525	1.189	0.414	White	I-66	0.812	0.660
CSWS-300-12	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	1/2	0.562	1.250	1.063	2.900	1.189	0.546	White	I-66	0.812	0.660
CSWS-300-58	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	5/8	0.656	1.437	1.063	3.087	1.189	0.671	White	I-66	0.812	0.660
CSWS-350-38	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	3/8	0.406	0.875	1.063	2.561	1.291	0.414	Red	I-71	0.890	0.703
CSWS-350-12	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/2	0.562	1.250	1.063	2.936	1.291	0.546	Red	I-71	0.890	0.703
CSWS-350-58	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	5/8	0.656	1.437	1.063	3.123	1.291	0.671	Red	I-71	0.890	0.703
CSWS-400-38	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	3/8	0.406	0.875	1.188	2.730	1.365	0.414	Blue	I-76	0.937	0.750
CSWS-400-12	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	1/2	0.562	1.250	1.188	3.105	1.365	0.546	Blue	I-76	0.937	0.750
CSWS-400-58	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	5/8	0.656	1.437	1.188	3.292	1.365	0.671	Blue	I-76	0.937	0.750

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CSWS

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Dimensions					Die Color Code	Die Index	O.D.	I.D.
						A	B	C	D	G				
CSWS-500-38	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	3/8	0.406	0.875	1.300	2.907	1.535	0.546	Brown	I-87	1.062	0.828
CSWS-500-12	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/2	0.562	1.250	1.300	3.282	1.535	0.414	Brown	I-87	1.062	0.828
CSWS-500-58	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	5/8	0.656	1.437	1.300	3.469	1.535	0.671	Brown	I-87	1.062	0.828
CSWS-600-38	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	3/8	0.406	0.875	1.375	3.059	1.712	0.414	Green	I-94	1.187	0.920
CSWS-600-12	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	1/2	0.562	1.250	1.375	3.434	1.712	0.546	Green	I-94	1.187	0.920
CSWS-600-58	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	5/8	0.656	1.437	1.375	3.621	1.712	0.671	Green	I-94	1.187	0.920
CSWS-650-516	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	5/16	0.343	0.875	1.375	3.119	1.764	0.352	Pink	I-99	1.217	0.958
CSWS-650-38	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	3/8	0.406	0.875	1.375	3.119	1.764	0.414	Pink	I-99	1.217	0.958
CSWS-650-12	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/2	0.562	1.25	1.375	3.494	1.764	0.546	Pink	I-99	1.217	0.958
CSWS-650-58	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	5/8	0.656	1.437	1.375	3.681	1.764	0.671	Pink	I-99	1.217	0.958
CSWS-700-38	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	3/8	0.406	0.875	1.375	3.119	1.816	0.414	Pink	I-99	1.250	0.991
CSWS-700-12	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.250	1.375	3.494	1.816	0.546	Pink	I-99	1.250	0.991
CSWS-700-58	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	5/8	0.656	1.437	1.375	3.681	1.816	0.671	Pink	I-99	1.250	0.991
CSWS-750-38	750kcmil	600 G,H,I,K,M FLEX 646.4 DLO	750 kcmil - 500kcmil	3/8	0.406	0.875	1.500	3.277	1.901	0.414	Black	I-106	1.313	1.031
CSWS-750-12	750kcmil	600 G,H,I,K,M FLEX 646.4 DLO	750kcmil - 500kcmil	1/2	0.562	1.250	1.500	3.652	1.901	0.546	Black	I-106	1.313	1.031
CSWS-750-58	750kcmil	600 G,H,I,K,M FLEX 646.4 DLO	750kcmil - 500kcmil	5/8	0.656	1.437	1.500	3.839	1.901	0.671	Black	I-106	1.313	1.031
CSWS-1000-38	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	3/8	0.406	0.875	1.625	3.525	2.169	0.414	White	I-125	1.500	1.172
CSWS-1000-12	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	1/2	0.562	1.250	1.625	3.900	2.169	0.546	White	I-125	1.500	1.172
CSWS-1000-58	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	5/8	0.656	1.437	1.625	4.087	2.169	0.671	White	I-125	1.500	1.172

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

TYPE CSWD


Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications

A



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CSWD-8-10-58	#8 AWG	#8 FLEX	-	10	0.219	0.625	1.250	0.500	1.945	0.374	0.258	Red	I-21	0.272	0.179
CSWD-8-10-34	#8 AWG	#8 FLEX	-	10	0.219	0.750	1.437	0.500	2.132	0.374	0.258	Red	I-21	0.272	0.179
CSWD-8-14-58	#8 AWG	#8 FLEX	-	1/4	0.281	0.625	1.437	0.500	2.132	0.486	0.320	Red	I-21	0.272	0.179
CSWD-8-14-34	#8 AWG	#8 FLEX	-	1/4	0.281	0.750	1.437	0.500	2.132	0.486	0.320	Red	I-21	0.272	0.179
CSWD-8-14-1	#8 AWG	#8 FLEX	-	1/4	0.281	1.000	1.687	0.500	2.382	0.486	0.320	Red	I-21	0.272	0.179
CSWD-8-38-1	#8 AWG	#8 FLEX	-	3/8	0.406	1.000	1.937	0.500	2.632	0.593	0.414	Red	I-21	0.272	0.179
CSWD-6-10-12	#6 AWG	#6 FLEX	-	10	0.219	0.500	1.250	0.500	1.945	0.411	0.258	Blue	I-24	0.320	0.225
CSWD-6-10-58	#6 AWG	#6 FLEX	-	10	0.219	0.625	1.250	0.500	1.945	0.411	0.258	Blue	I-24	0.320	0.225
CSWD-6-10-1116	#6 AWG	#6 FLEX	-	10	0.219	0.687	1.250	0.500	1.945	0.411	0.258	Blue	I-24	0.320	0.225
CSWD-6-10-34	#6 AWG	#6 FLEX	-	10	0.219	0.750	1.437	0.500	2.132	0.411	0.258	Blue	I-24	0.320	0.225
CSWD-6-14-12	#6 AWG	#6 FLEX	-	1/4	0.281	0.500	1.250	0.500	1.945	0.411	0.320	Blue	I-24	0.320	0.225
CSWD-6-14-58	#6 AWG	#6 FLEX	-	1/4	0.281	0.625	1.437	0.500	2.132	0.411	0.320	Blue	I-24	0.320	0.225
CSWD-6-14-34	#6 AWG	#6 FLEX	-	1/4	0.281	0.750	1.437	0.500	2.132	0.411	0.320	Blue	I-24	0.320	0.225
CSWD-6-14-1	#6 AWG	#6 FLEX	-	1/4	0.281	1.000	1.687	0.500	2.382	0.411	0.320	Blue	I-24	0.320	0.225
CSWD-6-516-34	#6 AWG	#6 FLEX	-	5/16	0.343	0.750	1.687	0.500	2.382	0.532	0.352	Blue	I-24	0.320	0.225
CSWD-6-516-1	#6 AWG	#6 FLEX	-	5/16	0.343	1.000	1.937	0.500	2.632	0.532	0.352	Blue	I-24	0.320	0.225
CSWD-6-38-34	#6 AWG	#6 FLEX	-	3/8	0.406	0.750	1.687	0.500	2.382	0.593	0.414	Blue	I-24	0.320	0.225
CSWD-6-38-78	#6 AWG	#6 FLEX	-	3/8	0.406	0.875	1.937	0.500	2.632	0.593	0.414	Blue	I-24	0.320	0.225
CSWD-6-38-1	#6 AWG	#6 FLEX	-	3/8	0.406	1.000	1.937	0.500	2.632	0.593	0.414	Blue	I-24	0.320	0.225
CSWD-6-12-134	#6 AWG	#6 FLEX	-	1/2	0.562	1.750	3.000	0.500	3.695	0.750	0.546	Blue	I-24	0.320	0.225

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CSWD

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CSWD-4-10-58	#4 AWG	-	4-6 AWG	10	0.219	0.625	1.250	0.500	1.984	0.486	0.258	Gray	I-29	0.343	0.250
CSWD-4-10-34	#4 AWG	-	4-6 AWG	10	0.219	0.750	1.437	0.500	2.171	0.486	0.258	Gray	I-29	0.343	0.250
CSWD-4-10-1	#4 AWG	-	4-6 AWG	10	0.219	1.000	1.687	0.500	2.421	0.486	0.258	Gray	I-29	0.343	0.250
CSWD-4-14-58	#4 AWG	-	4-6 AWG	1/4	0.281	0.625	1.437	0.500	2.171	0.486	0.320	Gray	I-29	0.343	0.250
CSWD-4-14-34	#4 AWG	-	4-6 AWG	1/4	0.281	0.750	1.437	0.500	2.171	0.486	0.320	Gray	I-29	0.343	0.250
CSWD-4-14-1	#4 AWG	-	4-6 AWG	1/4	0.281	1.000	1.687	0.500	2.421	0.486	0.320	Gray	I-29	0.343	0.250
CSWD-4-516-1	#4 AWG	-	4-6 AWG	1/4	0.343	1.000	1.937	0.500	2.671	0.486	0.320	Gray	I-29	0.343	0.250
CSWD-4-38-34	#4 AWG	-	4-6 AWG	3/8	0.406	0.750	1.687	0.500	2.421	0.593	0.414	Gray	I-29	0.343	0.250
CSWD-4-38-1	#4 AWG	-	4-6 AWG	3/8	0.406	1.000	1.937	0.500	2.671	0.593	0.414	Gray	I-29	0.343	0.250
CSWD-4-12-134	#4 AWG	-	4-6 AWG	1/2	0.562	1.750	3.000	0.500	3.734	0.750	0.546	Gray	I-29	0.343	0.250
CSWD-3-14-58	#3 AWG	#4 FLEX	3-6 AWG	1/4	0.281	0.625	1.437	0.625	2.317	0.532	0.320	White	I-29	0.375	0.275
CSWD-3-14-34	#3 AWG	#4 FLEX	3-6 AWG	1/4	0.281	0.750	1.437	0.625	2.317	0.532	0.320	White	I-29	0.375	0.275
CSWD-3-516-1	#3 AWG	#4 FLEX	3-6 AWG	5/16	0.343	1.000	1.937	0.625	2.817	0.532	0.352	White	I-29	0.375	0.275
CSWD-3-38-34	#3 AWG	#4 FLEX	3-6 AWG	3/8	0.406	0.750	1.687	0.625	2.567	0.593	0.414	White	I-29	0.375	0.275
CSWD-3-38-1	#3 AWG	#4 FLEX	3-6 AWG	3/8	0.406	1.000	1.937	0.625	2.817	0.593	0.414	White	I-29	0.375	0.275
CSWD-3-12-134	#3 AWG	#4 FLEX	3-6 AWG	1/2	0.562	1.750	3.000	0.625	3.880	0.750	0.546	White	I-29	0.375	0.275

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207


TYPE CSWD

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CSWD-2-10-34	#2 AWG	-	2-6 AWG	10	0.219	0.750	1.437	0.625	2.348	0.599	0.258	Brown	I-33	0.421	0.312
CSWD-2-14-58	#2 AWG	-	2-6 AWG	1/4	0.281	0.625	1.437	0.625	2.348	0.599	0.320	Brown	I-33	0.421	0.312
CSWD-2-14-34	#2 AWG	-	2-6 AWG	1/4	0.281	0.750	1.437	0.625	2.348	0.599	0.320	Brown	I-33	0.421	0.312
CSWD-2-14-1	#2 AWG	-	2-6 AWG	1/4	0.281	1.000	1.687	0.625	2.598	0.599	0.320	Brown	I-33	0.421	0.312
CSWD-2-516-34	#2 AWG	-	2-6 AWG	5/16	0.343	0.750	1.687	0.625	2.598	0.599	0.352	Brown	I-33	0.421	0.312
CSWD-2-516-1	#2 AWG	-	2-6 AWG	5/16	0.343	1.000	1.937	0.625	2.848	0.599	0.352	Brown	I-33	0.421	0.312
CSWD-2-38-34	#2 AWG	-	2-6 AWG	3/8	0.406	0.750	1.687	0.625	2.598	0.599	0.414	Brown	I-33	0.421	0.312
CSWD-2-38-78	#2 AWG	-	2-6 AWG	3/8	0.406	0.875	1.937	0.625	2.848	0.599	0.414	Brown	I-33	0.421	0.312
CSWD-2-38-1	#2 AWG	-	2-6 AWG	3/8	0.406	1.000	1.937	0.625	2.848	0.599	0.414	Brown	I-33	0.421	0.312
CSWD-2-38-134	#2 AWG	-	2-6 AWG	3/8	0.406	1.750	2.625	0.625	3.536	0.599	0.414	Brown	I-33	0.421	0.312
CSWD-2-12-134	#2 AWG	-	2-6 AWG	1/2	0.562	1.750	3.000	0.625	3.911	0.750	0.546	Brown	I-33	0.421	0.312
CSWD-1-14-58	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	0.625	1.437	0.625	2.392	0.673	0.320	Green	I-37	0.468	0.359
CSWD-1-14-34	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	0.750	1.437	0.625	2.392	0.673	0.320	Green	I-37	0.468	0.359
CSWD-1-14-1	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	1.000	1.687	0.625	2.642	0.673	0.320	Green	I-37	0.468	0.359
CSWD-1-516-78	#1 AWG	#2 FLEX	1-6 AWG	5/16	0.343	0.875	1.687	0.625	2.642	0.673	0.352	Green	I-37	0.468	0.359
CSWD-1-516-1	#1 AWG	#2 FLEX	1-6 AWG	5/16	0.343	1.000	1.937	0.625	2.892	0.673	0.352	Green	I-37	0.468	0.359
CSWD-1-38-1	#1 AWG	#2 FLEX	1-6 AWG	3/8	0.406	1.000	1.937	0.625	2.892	0.673	0.414	Green	I-37	0.468	0.359
CSWD-1-12-134	#1 AWG	#2 FLEX	1-6 AWG	1/2	0.562	1.750	3.000	0.625	3.955	0.750	0.546	Green	I-37	0.468	0.359
CSWD-1/0-14-58	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	0.625	1.437	0.750	2.543	0.738	0.320	Pink	I-42	0.515	0.390
CSWD-1/0-14-34	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	0.750	1.437	0.750	2.543	0.738	0.320	Pink	I-42	0.515	0.390
CSWD-1/0-14-1	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	1.000	1.687	0.750	2.793	0.738	0.320	Pink	I-42	0.515	0.390
CSWD-1/0-516-34	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	0.750	1.687	0.750	2.793	0.738	0.352	Pink	I-42	0.515	0.390
CSWD-1/0-516-78	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	0.875	1.687	0.750	2.793	0.738	0.352	Pink	I-42	0.515	0.390
CSWD-1/0-516-1	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	1.000	1.937	0.750	3.043	0.738	0.352	Pink	I-42	0.515	0.390
CSWD-1/0-38-1	1/0 AWG	#1 FLEX	1/0-6 AWG	3/8	0.406	1.000	1.937	0.750	3.043	0.738	0.414	Pink	I-42	0.515	0.390
CSWD-1/0-38-134	1/0 AWG	#1 FLEX	1/0-6 AWG	3/8	0.406	1.750	2.625	0.750	3.731	0.738	0.414	Pink	I-42	0.515	0.390
CSWD-1/0-12-1	1/0 AWG	#1 FLEX	1/0-6 AWG	1/2	0.562	1.000	2.125	0.750	3.231	0.738	0.546	Pink	I-42	0.515	0.390
CSWD-1/0-12-134	1/0 AWG	#1 FLEX	1/0-6 AWG	1/2	0.562	1.750	3.000	0.750	4.106	0.738	0.546	Pink	I-42	0.515	0.390

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information. For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CSWD

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CSWD-2/0-14-58	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	0.625	1.437	0.750	2.583	0.811	0.320	Black	I-45	0.562	0.437
CSWD-2/0-14-34	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	0.750	1.437	0.750	2.583	0.811	0.320	Black	I-45	0.562	0.437
CSWD-2/0-14-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	1.000	1.687	0.750	2.833	0.811	0.320	Black	I-45	0.562	0.437
CSWD-2/0-516-78	2/0 AWG	1/0 FLEX	2/0-4 AWG	5/16	0.343	0.875	1.687	0.750	2.833	0.811	0.352	Black	I-45	0.562	0.437
CSWD-2/0-516-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	5/16	0.343	1.000	1.937	0.750	3.083	0.811	0.352	Black	I-45	0.562	0.437
CSWD-2/0-38-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	3/8	0.406	1.000	1.937	0.750	3.083	0.811	0.414	Black	I-45	0.562	0.437
CSWD-2/0-38-134	2/0 AWG	1/0 FLEX	2/0-4 AWG	3/8	0.406	1.750	2.625	0.750	3.771	0.811	0.414	Black	I-45	0.562	0.437
CSWD-2/0-12-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/2	0.562	1.000	2.125	0.750	3.271	0.811	0.546	Black	I-45	0.562	0.437
CSWD-2/0-12-134	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/2	0.562	1.750	3.000	0.750	4.146	0.811	0.546	Black	I-45	0.562	0.437
CSWD-3/0-14-58	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/4	0.281	0.625	1.437	0.750	2.626	0.885	0.320	Orange	I-50	0.609	0.484
CSWD-3/0-14-34	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/4	0.281	0.750	1.437	0.750	2.626	0.885	0.320	Orange	I-50	0.609	0.484
CSWD-3/0-516-1	3/0 AWG	2/0 FLEX	3/0-2 AWG	5/16	0.343	1.000	1.937	0.750	3.126	0.885	0.352	Orange	I-50	0.609	0.484
CSWD-3/0-38-1	3/0 AWG	2/0 FLEX	3/0-2 AWG	3/8	0.406	1.000	1.937	0.750	3.126	0.885	0.414	Orange	I-50	0.609	0.484
CSWD-3/0-12-134	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/2	0.562	1.750	3.000	0.750	4.189	0.885	0.546	Orange	I-50	0.609	0.484
CSWD-4/0-14-58	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	0.625	1.437	0.875	2.803	0.999	0.320	Purple	I-54	0.687	0.546
CSWD-4/0-14-34	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	0.750	1.437	0.875	2.803	0.999	0.320	Purple	I-54	0.687	0.546
CSWD-4/0-14-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	1.000	1.687	0.875	3.053	0.999	0.320	Purple	I-54	0.687	0.546
CSWD-4/0-516-34	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	0.750	1.687	0.875	3.053	0.999	0.352	Purple	I-54	0.687	0.546
CSWD-4/0-516-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	1.000	1.937	0.875	3.303	0.999	0.352	Purple	I-54	0.687	0.546
CSWD-4/0-516-134	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	1.750	2.500	0.875	3.866	0.999	0.352	Purple	I-54	0.687	0.546
CSWD-4/0-38-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	3/8	0.406	1.000	1.937	0.875	3.303	0.999	0.414	Purple	I-54	0.687	0.546
CSWD-4/0-38-134	4/0 AWG	3/0 FLEX	4/0-1 AWG	3/8	0.406	1.750	2.625	0.875	3.991	0.999	0.414	Purple	I-54	0.687	0.546
CSWD-4/0-12-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.000	2.125	0.875	3.491	0.999	0.546	Purple	I-54	0.687	0.546
CSWD-4/0-12-114	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.250	2.500	0.875	3.866	0.999	0.546	Purple	I-54	0.687	0.546
CSWD-4/0-12-134	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.750	3.000	0.875	4.366	0.999	0.546	Purple	I-54	0.687	0.546

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207


TYPE CSWD

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CSWD-250-14-34	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/4	0.281	0.750	1.437	1.063	3.031	1.088	0.320	Yellow	I-62	0.750	0.593
CSWD-250-38-1	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	1.00	1.937	1.063	3.531	1.088	0.414	Yellow	I-62	0.750	0.593
CSWD-250-38-134	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	1.750	2.625	1.063	4.219	1.088	0.414	Yellow	I-62	0.750	0.593
CSWD-250-12-114	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/2	0.562	1.250	2.500	1.063	4.094	1.088	0.546	Yellow	I-62	0.750	0.593
CSWD-250-12-134	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/2	0.562	1.750	3.000	1.063	4.594	1.088	0.546	Yellow	I-62	0.750	0.593
CSWD-300-38-1	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	3/8	0.406	1.000	1.937	1.063	3.587	1.189	0.414	White	I-66	0.812	0.660
CSWD-300-12-134	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	1/2	0.562	1.750	3.000	1.063	4.650	1.189	0.546	White	I-66	0.812	0.660
CSWD-350-14-34	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/4	0.281	0.750	1.437	1.063	3.123	1.291	0.320	Red	I-71	0.890	0.703
CSWD-350-516-134	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	5/16	0.343	1.750	2.500	1.063	4.186	1.291	0.352	Red	I-71	0.890	0.703
CSWD-350-38-1	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	3/8	0.406	1.000	1.937	1.063	3.623	1.291	0.414	Red	I-71	0.890	0.703
CSWD-350-12-114	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/2	0.562	1.250	2.500	1.063	4.186	1.291	0.546	Red	I-71	0.890	0.703
CSWD-350-12-134	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/2	0.562	1.750	3.000	1.063	4.686	1.291	0.546	Red	I-71	0.890	0.703
CSWD-400-38-1	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	3/8	0.406	1.000	1.937	1.188	3.792	1.365	0.414	Blue	I-76	0.937	0.750
CSWD-400-38-116	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	3/8	0.406	1.062	1.937	1.188	3.792	1.365	0.414	Blue	I-76	0.937	0.750
CSWD-400-12-134	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	1/2	0.562	1.750	3.000	1.188	4.855	1.365	0.546	Blue	I-76	0.937	0.750
CSWD-500-14-34	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/4	0.281	0.750	1.437	1.300	3.469	1.535	0.320	Brown	I-87	1.062	0.828
CSWD-500-38-1	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	3/8	0.406	1.000	1.937	1.300	3.969	1.535	0.414	Brown	I-87	1.062	0.828
CSWD-500-12-114	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/2	0.562	1.250	2.500	1.300	4.532	1.535	0.546	Brown	I-87	1.062	0.828
CSWD-500-12-134	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/2	0.562	1.750	3.000	1.300	5.032	1.535	0.546	Brown	I-87	1.062	0.828

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CSWD

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CSWD-600-38-1	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	3/8	0.406	1.000	1.937	1.375	4.121	1.712	0.414	Green	I-94	1.187	0.920
CSWD-600-12-134	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	1/2	0.562	1.750	3.000	1.375	5.184	1.712	0.546	Green	I-94	1.187	0.920
CSWD-650-12-134	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/2	0.562	1.750	3.000	1.375	5.244	1.764	0.546	Pink	I-99	1.217	0.958
CSWD-650-12-114	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/2	0.562	1.250	2.500	1.375	4.744	1.764	0.546	Pink	I-99	1.217	0.958
CSWD-650-38-1	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	3/8	0.406	1.000	1.937	1.375	4.181	1.764	0.414	Pink	I-99	1.217	0.958
CSWD-650-38-118	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	3/8	0.406	1.125	2.125	1.375	4.369	1.764	0.414	Pink	I-99	1.217	0.958
CSWD-650-516-1	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/32	0.343	1.000	1.937	1.375	4.181	1.764	0.352	Pink	I-99	1.217	0.958
CSWD-700-38-1	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	3/8	0.406	1.000	1.937	1.375	4.181	1.816	0.414	Pink	I-99	1.250	0.991
CSWD-700-12-114	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.250	2.500	1.375	4.744	1.816	0.546	Pink	I-99	1.250	0.991
CSWD-700-12-134	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.750	3.000	1.375	5.244	1.816	0.546	Pink	I-99	1.250	0.991
CSWD-700-12-178	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.875	3.000	1.375	5.244	1.816	0.546	Pink	I-99	1.250	0.991
CSWD-750-38-1	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	3/8	0.406	1.000	1.937	1.500	4.339	1.901	0.414	Black	I-106	1.313	1.031
CSWD-750-38-118	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	3/8	0.406	1.125	2.125	1.500	4.527	1.901	0.414	Black	I-106	1.313	1.031
CSWD-750-12-112	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	1/2	0.562	1.500	2.625	1.500	5.027	1.901	0.546	Black	I-106	1.313	1.031
CSWD-750-12-134	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	1/2	0.562	1.750	3.000	1.500	5.402	1.901	0.546	Black	I-106	1.313	1.031
CSWD-750-58-112	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	5/8	0.656	1.500	3.000	1.500	5.402	1.901	0.671	Black	I-106	1.313	1.031
CSWD-1000-38-1	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	3/8	0.406	1.000	1.937	1.625	4.587	2.169	0.414	White	I-125	1.500	1.172
CSWD-1000-12-114	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	1/2	0.562	1.250	2.500	1.625	5.150	2.169	0.546	White	I-125	1.500	1.172
CSWD-1000-12-134	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	1/2	0.562	1.750	3.000	1.625	5.650	2.169	0.546	White	I-125	1.500	1.172
CSWD-1000-58-112	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	5/8	0.656	1.500	3.000	1.625	5.650	2.169	0.671	White	I-125	1.500	1.172

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information. For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg. UL File E6207

TYPE CLWS


Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications

A



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Dimensions					Die Color Code	Die Index	O.D.	I.D.
						A	B	C	D	G				
CLWS-8-10	#8 AWG	#8 FLEX	-	10	0.219	0.562	0.812	1.569	0.374	0.258	Red	I-21	0.272	0.179
CLWS-8-14	#8 AWG	#8 FLEX	-	1/4	0.281	0.680	0.812	1.687	0.486	0.320	Red	I-21	0.272	0.179
CLWS-8-516	#8 AWG	#8 FLEX	-	5/16	0.343	0.875	0.812	1.882	0.532	0.352	Red	I-21	0.272	0.179
CLWS-8-38	#8 AWG	#8 FLEX	-	3/8	0.406	0.875	0.812	1.882	0.593	0.414	Red	I-21	0.272	0.179
CLWS-6-10	#6 AWG	#6 FLEX	-	10	0.219	0.562	1.125	1.882	0.411	0.258	Blue	I-24	0.320	0.225
CLWS-6-14	#6 AWG	#6 FLEX	-	1/4	0.281	0.680	1.125	2.000	0.411	0.320	Blue	I-24	0.320	0.225
CLWS-6-516	#6 AWG	#6 FLEX	-	5/16	0.343	0.875	1.125	2.195	0.532	0.352	Blue	I-24	0.320	0.225
CLWS-6-38	#6 AWG	#6 FLEX	-	3/8	0.406	0.875	1.125	2.195	0.593	0.414	Blue	I-24	0.320	0.225
CLWS-6-12	#6 AWG	#6 FLEX	-	1/2	0.562	1.250	1.125	2.570	0.750	0.546	Blue	I-24	0.320	0.225
CLWS-4-10	#4 AWG	-	4-6 AWG	10	0.219	0.562	1.125	1.921	0.486	0.258	Gray	I-29	0.343	0.250
CLWS-4-14	#4 AWG	-	4-6 AWG	1/4	0.281	0.680	1.125	2.039	0.486	0.320	Gray	I-29	0.343	0.250
CLWS-4-516	#4 AWG	-	4-6 AWG	5/16	0.343	0.875	1.125	2.234	0.486	0.352	Gray	I-29	0.343	0.250
CLWS-4-38	#4 AWG	-	4-6 AWG	3/8	0.406	0.875	1.125	2.234	0.593	0.414	Gray	I-29	0.343	0.250
CLWS-4-12	#4 AWG	-	4-6 AWG	1/2	0.562	1.250	1.125	2.609	0.750	0.546	Gray	I-29	0.343	0.250
CLWS-3-10	#3 AWG	#4 FLEX	3-6 AWG	10	0.219	0.562	1.125	1.942	0.532	0.258	White	I-29	0.375	0.275
CLWS-3-14	#3 AWG	#4 FLEX	3-6 AWG	1/4	0.281	0.680	1.125	2.060	0.532	0.320	White	I-29	0.375	0.275
CLWS-3-516	#3 AWG	#4 FLEX	3-6 AWG	5/16	0.343	0.875	1.125	2.255	0.532	0.352	White	I-29	0.375	0.275
CLWS-3-38	#3 AWG	#4 FLEX	3-6 AWG	3/8	0.406	0.875	1.125	2.255	0.593	0.414	White	I-29	0.375	0.275
CLWS-3-12	#3 AWG	#4 FLEX	3-6 AWG	1/2	0.562	1.250	1.125	2.630	0.750	0.546	White	I-29	0.375	0.275
CLWS-2-10	#2 AWG	-	2-6 AWG	10	0.219	0.562	1.125	1.973	0.599	0.258	Brown	I-33	0.421	0.312
CLWS-2-14	#2 AWG	-	2-6 AWG	1/4	0.281	0.680	1.125	2.091	0.599	0.320	Brown	I-33	0.421	0.312
CLWS-2-516	#2 AWG	-	2-6 AWG	5/16	0.343	0.875	1.125	2.286	0.599	0.352	Brown	I-33	0.421	0.312
CLWS-2-38	#2 AWG	-	2-6 AWG	3/8	0.406	0.875	1.125	2.286	0.599	0.414	Brown	I-33	0.421	0.312
CLWS-2-12	#2 AWG	-	2-6 AWG	1/2	0.562	1.250	1.125	2.661	0.750	0.546	Brown	I-33	0.421	0.312
CLWS-1-10	#1 AWG	#2 FLEX	1-6 AWG	10	0.219	0.562	1.375	2.267	0.673	0.258	Green	I-37	0.468	0.359
CLWS-1-14	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	0.875	1.375	2.580	0.673	0.320	Green	I-37	0.468	0.359
CLWS-1-516	#1 AWG	#2 FLEX	1-6 AWG	5/16	0.343	0.875	1.375	2.580	0.673	0.352	Green	I-37	0.468	0.359
CLWS-1-38	#1 AWG	#2 FLEX	1-6 AWG	3/8	0.406	0.875	1.375	2.580	0.673	0.414	Green	I-37	0.468	0.359
CLWS-1-12	#1 AWG	#2 FLEX	1-6 AWG	1/2	0.562	1.250	1.375	2.955	0.750	0.546	Green	I-37	0.468	0.359
CLWS-1/0-10	1/0 AWG	#1 FLEX	1/0-6 AWG	10	0.219	0.562	1.500	2.418	0.738	0.258	Pink	I-42	0.515	0.390
CLWS-1/0-14	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	0.875	1.500	2.731	0.738	0.320	Pink	I-42	0.515	0.390
CLWS-1/0-516	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	0.875	1.500	2.731	0.738	0.352	Pink	I-42	0.515	0.390
CLWS-1/0-38	1/0 AWG	#1 FLEX	1/0-6 AWG	3/8	0.406	0.875	1.500	2.731	0.738	0.414	Pink	I-42	0.515	0.390
CLWS-1/0-12	1/0 AWG	#1 FLEX	1/0-6 AWG	1/2	0.562	1.250	1.500	3.106	0.738	0.546	Pink	I-42	0.515	0.390

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CLWS

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Dimensions					Die Color Code	Die Index	O.D.	I.D.
						A	B	C	D	G				
CLWS-2/0-10	2/0 AWG	1/0 FLEX	2/0-4 AWG	10	0.219	0.562	1.500	2.458	0.811	0.258	Black	I-45	0.562	0.437
CLWS-2/0-14	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	0.875	1.500	2.771	0.811	0.320	Black	I-45	0.562	0.437
CLWS-2/0-516	2/0 AWG	1/0 FLEX	2/0-4 AWG	5/16	0.343	0.875	1.500	2.771	0.811	0.352	Black	I-45	0.562	0.437
CLWS-2/0-38	2/0 AWG	1/0 FLEX	2/0-4 AWG	3/8	0.406	0.875	1.500	2.771	0.811	0.414	Black	I-45	0.562	0.437
CLWS-2/0-12	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/2	0.562	1.250	1.500	3.146	0.811	0.546	Black	I-45	0.562	0.437
CLWS-3/0-10	3/0 AWG	2/0 FLEX	3/0-2 AWG	10	0.219	0.562	1.500	2.501	0.885	0.258	Orange	I-50	0.609	0.484
CLWS-3/0-14	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/4	0.281	0.875	1.500	2.814	0.885	0.320	Orange	I-50	0.609	0.484
CLWS-3/0-516	3/0 AWG	2/0 FLEX	3/0-2 AWG	5/16	0.343	0.875	1.500	2.814	0.885	0.352	Orange	I-50	0.609	0.484
CLWS-3/0-38	3/0 AWG	2/0 FLEX	3/0-2 AWG	3/8	0.406	0.875	1.500	2.814	0.885	0.414	Orange	I-50	0.609	0.484
CLWS-3/0-12	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/2	0.562	1.250	1.500	3.189	0.885	0.546	Orange	I-50	0.609	0.484
CLWS-4/0-14	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	0.875	1.500	2.866	0.999	0.320	Purple	I-54	0.687	0.546
CLWS-4/0-516	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	0.875	1.500	2.866	0.999	0.352	Purple	I-54	0.687	0.546
CLWS-4/0-38	4/0 AWG	3/0 FLEX	4/0-1 AWG	3/8	0.406	0.875	1.500	2.866	0.999	0.414	Purple	I-54	0.687	0.546
CLWS-4/0-12	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.250	1.500	3.241	0.999	0.546	Purple	I-54	0.687	0.546
CLWS-250-516	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	5/16	0.343	0.875	1.688	3.094	1.088	0.352	Yellow	I-62	0.750	0.593
CLWS-250-38	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	0.875	1.688	3.094	1.088	0.414	Yellow	I-62	0.750	0.593
CLWS-250-12	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/2	0.562	1.250	1.688	3.469	1.088	0.546	Yellow	I-62	0.750	0.593
CLWS-300-516	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	5/16	0.343	0.875	2.000	3.462	1.189	0.352	White	I-66	0.812	0.660
CLWS-300-38	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	3/8	0.406	0.875	2.000	3.462	1.189	0.414	White	I-66	0.812	0.660
CLWS-300-12	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	1/2	0.562	1.250	2.000	3.837	1.189	0.546	White	I-66	0.812	0.660
CLWS-350-38	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	3/8	0.406	0.875	2.000	3.498	1.291	0.414	Red	I-71	0.890	0.703
CLWS-350-12	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/2	0.562	1.250	2.000	3.873	1.291	0.546	Red	I-71	0.890	0.703
CLWS-350-58	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	5/8	0.656	1.437	2.000	4.060	1.291	0.671	Red	I-71	0.890	0.703
CLWS-400-38	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	3/8	0.406	0.875	2.125	3.667	1.365	0.414	Blue	I-76	0.937	0.750
CLWS-400-12	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	1/2	0.562	1.250	2.125	4.042	1.365	0.546	Blue	I-76	0.937	0.750
CLWS-400-58	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	5/8	0.656	1.437	2.125	4.229	1.365	0.671	Blue	I-76	0.937	0.750

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207


TYPE CLWS

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Dimensions					Die Color Code	Die Index	O.D.	I.D.
						A	B	C	D	G				
CLWS-500-38	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	3/8	0.406	0.875	2.250	3.857	1.535	0.414	Brown	I-87	1.062	0.828
CLWS-500-12	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/2	0.562	1.250	2.250	4.232	1.535	0.546	Brown	I-87	1.062	0.828
CLWS-500-58	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	5/8	0.656	1.437	2.250	4.419	1.535	0.671	Brown	I-87	1.062	0.828
CLWS-600-38	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	3/8	0.406	0.875	2.687	4.371	1.712	0.414	Green	I-94	1.187	0.920
CLWS-600-12	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	1/2	0.562	1.250	2.687	4.746	1.712	0.546	Green	I-94	1.187	0.920
CLWS-600-58	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	5/8	0.656	1.437	2.687	4.933	1.712	0.671	Green	I-94	1.187	0.920
CLWS-650-516	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/32	0.343	0.875	2.687	4.431	1.764	0.352	Pink	I-99	1.217	0.958
CLWS-650-38	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	3/8	0.406	0.875	2.687	4.431	1.764	0.414	Pink	I-99	1.217	0.958
CLWS-650-12	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/2	0.562	1.25	2.687	4.806	1.764	0.546	Pink	I-99	1.217	0.958
CLWS-650-58	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	5/8	0.656	1.437	2.687	4.993	1.764	0.671	Pink	I-99	1.217	0.958
CLWS-700-38	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	3/8	0.406	0.875	2.687	4.431	1.816	0.414	Pink	I-99	1.250	0.991
CLWS-700-12	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.250	2.687	4.806	1.816	0.546	Pink	I-99	1.250	0.991
CLWS-700-58	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	5/8	0.656	1.437	2.687	4.993	1.816	0.671	Pink	I-99	1.250	0.991
CLWS-750-38	750kcmil	600 G,H,I,K,M FLEX 646.4 DLO	750kcmil - 500kcmil	3/8	0.406	0.875	2.875	4.652	1.901	0.414	Black	I-106	1.313	1.031
CLWS-750-12	750kcmil	600 G,H,I,K,M FLEX 646.4 DLO	750kcmil - 500kcmil	1/2	0.562	1.250	2.875	5.027	1.901	0.546	Black	I-106	1.313	1.031
CLWS-750-58	750kcmil	600 G,H,I,K,M FLEX 646.4 DLO	750kcmil - 500kcmil	5/8	0.656	1.437	2.875	5.214	1.901	0.671	Black	I-106	1.313	1.031
CLWS-1000-38	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	3/8	0.406	0.875	3.000	4.900	2.169	0.414	White	I-125	1.500	1.172
CLWS-1000-12	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	1/2	0.562	1.250	3.000	5.275	2.169	0.546	White	I-125	1.500	1.172
CLWS-1000-58	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	5/8	0.656	1.437	3.000	5.462	2.169	0.671	White	I-125	1.500	1.172

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CLNS

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Dimensions					Die Color Code	Die Index	O.D.	I.D.
						A	B	C	D	G				
CLNS-8-10	#8 AWG	#8 FLEX	-	10	0.219	0.562	0.812	1.569	0.374	0.258	Red	I-21	0.272	0.179
CLNS-8-14	#8 AWG	#8 FLEX	-	1/4	0.281	0.680	0.812	1.687	0.486	0.320	Red	I-21	0.272	0.179
CLNS-8-516	#8 AWG	#8 FLEX	-	5/16	0.343	0.875	0.812	1.882	0.532	0.352	Red	I-21	0.272	0.179
CLNS-8-38	#8 AWG	#8 FLEX	-	3/8	0.406	0.875	0.812	1.882	0.593	0.414	Red	I-21	0.272	0.179
CLNS-6-10	#6 AWG	#6 FLEX	-	10	0.219	0.562	1.125	1.882	0.411	0.258	Blue	I-24	0.320	0.225
CLNS-6-14	#6 AWG	#6 FLEX	-	1/4	0.281	0.680	1.125	2.000	0.411	0.320	Blue	I-24	0.320	0.225
CLNS-6-516	#6 AWG	#6 FLEX	-	5/16	0.343	0.875	1.125	2.195	0.532	0.352	Blue	I-24	0.320	0.225
CLNS-6-38	#6 AWG	#6 FLEX	-	3/8	0.406	0.875	1.125	2.195	0.593	0.414	Blue	I-24	0.320	0.225
CLNS-6-12	#6 AWG	#6 FLEX	-	1/2	0.562	1.250	1.125	2.570	0.750	0.546	Blue	I-24	0.320	0.225
CLNS-4-10	#4 AWG	-	4-6 AWG	10	0.219	0.562	1.125	1.921	0.486	0.258	Gray	I-29	0.343	0.250
CLNS-4-14	#4 AWG	-	4-6 AWG	1/4	0.281	0.680	1.125	2.039	0.486	0.320	Gray	I-29	0.343	0.250
CLNS-4-516	#4 AWG	-	4-6 AWG	5/16	0.343	0.875	1.125	2.234	0.486	0.352	Gray	I-29	0.343	0.250
CLNS-4-38	#4 AWG	-	4-6 AWG	3/8	0.406	0.875	1.125	2.234	0.593	0.414	Gray	I-29	0.343	0.250
CLNS-4-12	#4 AWG	-	4-6 AWG	1/2	0.562	1.250	1.125	2.609	0.750	0.546	Gray	I-29	0.343	0.250
CLNS-3-10	#3 AWG	#4 FLEX	3-6 AWG	10	0.219	0.562	1.125	1.942	0.532	0.258	White	I-29	0.375	0.275
CLNS-3-14	#3 AWG	#4 FLEX	3-6 AWG	1/4	0.281	0.680	1.125	2.060	0.532	0.320	White	I-29	0.375	0.275
CLNS-3-516	#3 AWG	#4 FLEX	3-6 AWG	5/16	0.343	0.875	1.125	2.255	0.532	0.352	White	I-29	0.375	0.275
CLNS-3-38	#3 AWG	#4 FLEX	3-6 AWG	3/8	0.406	0.875	1.125	2.255	0.593	0.414	White	I-29	0.375	0.275
CLNS-3-12	#3 AWG	#4 FLEX	3-6 AWG	1/2	0.562	1.250	1.125	2.630	0.750	0.546	White	I-29	0.375	0.275
CLNS-2-10	#2 AWG	-	2-6 AWG	10	0.219	0.562	1.125	1.973	0.599	0.258	Brown	I-33	0.421	0.312
CLNS-2-14	#2 AWG	-	2-6 AWG	1/4	0.281	0.680	1.125	2.091	0.599	0.320	Brown	I-33	0.421	0.312
CLNS-2-516	#2 AWG	-	2-6 AWG	5/16	0.343	0.875	1.125	2.286	0.599	0.352	Brown	I-33	0.421	0.312
CLNS-2-38	#2 AWG	-	2-6 AWG	3/8	0.406	0.875	1.125	2.286	0.599	0.414	Brown	I-33	0.421	0.312
CLNS-2-12	#2 AWG	-	2-6 AWG	1/2	0.562	1.250	1.125	2.661	0.750	0.546	Brown	I-33	0.421	0.312
CLNS-1-10	#1 AWG	#2 FLEX	1-6 AWG	10	0.219	0.562	1.375	2.267	0.673	0.258	Green	I-37	0.468	0.359
CLNS-1-14	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	0.875	1.375	2.580	0.673	0.320	Green	I-37	0.468	0.359
CLNS-1-516	#1 AWG	#2 FLEX	1-6 AWG	5/16	0.343	0.875	1.375	2.580	0.673	0.352	Green	I-37	0.468	0.359
CLNS-1-38	#1 AWG	#2 FLEX	1-6 AWG	3/8	0.406	0.875	1.375	2.580	0.673	0.414	Green	I-37	0.468	0.359
CLNS-1-12	#1 AWG	#2 FLEX	1-6 AWG	1/2	0.562	1.250	1.375	2.955	0.750	0.546	Green	I-37	0.468	0.359
CLNS-1/0-10	1/0 AWG	#1 FLEX	1/0-6 AWG	10	0.219	0.562	1.500	2.418	0.738	0.258	Pink	I-42	0.515	0.390
CLNS-1/0-14	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	0.875	1.500	2.731	0.738	0.320	Pink	I-42	0.515	0.390
CLNS-1/0-516	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	0.875	1.500	2.731	0.738	0.352	Pink	I-42	0.515	0.390
CLNS-1/0-38	1/0 AWG	#1 FLEX	1/0-6 AWG	3/8	0.406	0.875	1.500	2.731	0.738	0.414	Pink	I-42	0.515	0.390
CLNS-1/0-12	1/0 AWG	#1 FLEX	1/0-6 AWG	1/2	0.562	1.250	1.500	3.106	0.738	0.546	Pink	I-42	0.515	0.390

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

TYPE CLNS


Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications

A



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Dimensions					Die Color Code	Die Index	O.D.	I.D.
						A	B	C	D	G				
CLNS-2/0-10	2/0 AWG	1/0 FLEX	2/0-4 AWG	10	0.219	0.562	1.500	2.458	0.811	0.258	Black	I-45	0.562	0.437
CLNS-2/0-14	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	0.875	1.500	2.771	0.811	0.320	Black	I-45	0.562	0.437
CLNS-2/0-516	2/0 AWG	1/0 FLEX	2/0-4 AWG	5/16	0.343	0.875	1.500	2.771	0.811	0.352	Black	I-45	0.562	0.437
CLNS-2/0-38	2/0 AWG	1/0 FLEX	2/0-4 AWG	3/8	0.406	0.875	1.500	2.771	0.811	0.414	Black	I-45	0.562	0.437
CLNS-2/0-12	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/2	0.562	1.250	1.500	3.146	0.811	0.546	Black	I-45	0.562	0.437
CLNS-3/0-10	3/0 AWG	2/0 FLEX	3/0-2 AWG	10	0.219	0.562	1.500	2.501	0.885	0.258	Orange	I-50	0.609	0.484
CLNS-3/0-14	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/4	0.281	0.875	1.500	2.814	0.885	0.320	Orange	I-50	0.609	0.484
CLNS-3/0-516	3/0 AWG	2/0 FLEX	3/0-2 AWG	5/16	0.343	0.875	1.500	2.814	0.885	0.352	Orange	I-50	0.609	0.484
CLNS-3/0-38	3/0 AWG	2/0 FLEX	3/0-2 AWG	3/8	0.406	0.875	1.500	2.814	0.885	0.414	Orange	I-50	0.609	0.484
CLNS-3/0-12	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/2	0.562	1.250	1.500	3.189	0.885	0.546	Orange	I-50	0.609	0.484
CLNS-4/0-14	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	0.875	1.500	2.866	0.999	0.320	Purple	I-54	0.687	0.546
CLNS-4/0-516	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	0.875	1.500	2.866	0.999	0.352	Purple	I-54	0.687	0.546
CLNS-4/0-38	4/0 AWG	3/0 FLEX	4/0-1 AWG	3/8	0.406	0.875	1.500	2.866	0.999	0.414	Purple	I-54	0.687	0.546
CLNS-4/0-12	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.250	1.500	3.241	0.999	0.546	Purple	I-54	0.687	0.546
CLNS-250-516	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	5/16	0.343	0.875	1.688	3.094	1.088	0.352	Yellow	I-62	0.750	0.593
CLNS-250-38	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	0.875	1.688	3.094	1.088	0.414	Yellow	I-62	0.750	0.593
CLNS-250-12	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/2	0.562	1.250	1.688	3.469	1.088	0.546	Yellow	I-62	0.750	0.593
CLNS-300-516	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	5/16	0.343	0.875	2.000	3.462	1.189	0.352	White	I-66	0.812	0.660
CLNS-300-38	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	3/8	0.406	0.875	2.000	3.462	1.189	0.414	White	I-66	0.812	0.660
CLNS-300-12	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	1/2	0.562	1.250	2.000	3.837	1.189	0.546	White	I-66	0.812	0.660
CLNS-350-38	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	3/8	0.406	0.875	2.000	3.498	1.291	0.414	Red	I-71	0.890	0.703
CLNS-350-12	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/2	0.562	1.250	2.000	3.873	1.291	0.546	Red	I-71	0.890	0.703
CLNS-350-58	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	5/8	0.656	1.437	2.000	4.060	1.291	0.671	Red	I-71	0.890	0.703
CLNS-400-38	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	3/8	0.406	0.875	2.125	3.667	1.365	0.414	Blue	I-76	0.937	0.750
CLNS-400-12	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	1/2	0.562	1.250	2.125	4.042	1.365	0.546	Blue	I-76	0.937	0.750
CLNS-400-58	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	5/8	0.656	1.437	2.125	4.229	1.365	0.671	Blue	I-76	0.937	0.750

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CLNS

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Dimensions					Die Color Code	Die Index	O.D.	I.D.
						A	B	C	D	G				
CLNS-500-38	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	3/8	0.406	0.875	2.250	3.857	1.535	0.414	Brown	I-87	1.062	0.828
CLNS-500-12	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/2	0.562	1.250	2.250	4.232	1.535	0.546	Brown	I-87	1.062	0.828
CLNS-500-58	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	5/8	0.656	1.437	2.250	4.419	1.535	0.671	Brown	I-87	1.062	0.828
CLNS-600-38	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	3/8	0.406	0.875	2.687	4.371	1.712	0.414	Green	I-94	1.187	0.920
CLNS-600-12	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	1/2	0.562	1.250	2.687	4.746	1.712	0.546	Green	I-94	1.187	0.920
CLNS-600-58	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	5/8	0.656	1.437	2.687	4.933	1.712	0.671	Green	I-94	1.187	0.920
CLNS-650-516	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/32	0.343	0.875	2.687	4.431	1.764	0.352	Pink	I-99	1.217	0.958
CLNS-650-38	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	3/8	0.406	0.875	2.687	4.431	1.764	0.414	Pink	I-99	1.217	0.958
CLNS-650-12	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/2	0.562	1.250	2.687	4.806	1.764	0.546	Pink	I-99	1.217	0.958
CLNS-650-58	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	5/8	0.656	1.437	2.687	4.993	1.764	0.671	Pink	I-99	1.217	0.958
CLNS-700-38	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	3/8	0.406	0.875	2.687	4.431	1.816	0.414	Pink	I-99	1.250	0.991
CLNS-700-12	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.250	2.687	4.806	1.816	0.546	Pink	I-99	1.250	0.991
CLNS-700-58	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	5/8	0.656	1.437	2.687	4.993	1.816	0.671	Pink	I-99	1.250	0.991
CLNS-750-38	750kcmil	600 G,H,I,K,M FLEX 646.4 DLO	750kcmil - 500kcmil	3/8	0.406	0.875	2.875	4.652	1.901	0.414	Black	I-106	1.313	1.031
CLNS-750-12	750kcmil	600 G,H,I,K,M FLEX 646.4 DLO	750kcmil - 500kcmil	1/2	0.562	1.250	2.875	5.027	1.901	0.546	Black	I-106	1.313	1.031
CLNS-750-58	750kcmil	600 G,H,I,K,M FLEX 646.4 DLO	750kcmil - 500kcmil	5/8	0.656	1.437	2.875	5.214	1.901	0.671	Black	I-106	1.313	1.031
CLNS-1000-38	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	3/8	0.406	0.875	3.000	4.900	2.169	0.414	White	I-125	1.500	1.172
CLNS-1000-12	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	1/2	0.562	1.250	3.000	5.275	2.169	0.546	White	I-125	1.500	1.172
CLNS-1000-58	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	5/8	0.656	1.437	3.000	5.462	2.169	0.671	White	I-125	1.500	1.172

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207


TYPE CLWD

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLWD-8-10-58	#8 AWG	#8 FLEX	-	10	0.219	0.625	1.250	0.812	2.257	0.374	0.258	Red	I-21	0.272	0.179
CLWD-8-10-34	#8 AWG	#8 FLEX	-	10	0.219	0.750	1.437	0.812	2.444	0.374	0.258	Red	I-21	0.272	0.179
CLWD-8-14-58	#8 AWG	#8 FLEX	-	1/4	0.281	0.625	1.437	0.812	2.444	0.486	0.320	Red	I-21	0.272	0.179
CLWD-8-14-34	#8 AWG	#8 FLEX	-	1/4	0.281	0.750	1.437	0.812	2.444	0.486	0.320	Red	I-21	0.272	0.179
CLWD-8-14-1	#8 AWG	#8 FLEX	-	1/4	0.281	1.000	1.687	0.812	2.694	0.486	0.320	Red	I-21	0.272	0.179
CLWD-8-38-1	#8 AWG	#8 FLEX	-	3/8	0.406	1.000	1.937	0.812	2.944	0.593	0.414	Red	I-21	0.272	0.179
CLWD-6-10-12	#6 AWG	#6 FLEX	-	10	0.219	0.500	1.250	1.125	2.570	0.411	0.258	Blue	I-24	0.320	0.225
CLWD-6-10-58	#6 AWG	#6 FLEX	-	10	0.219	0.625	1.250	1.125	2.570	0.411	0.258	Blue	I-24	0.320	0.225
CLWD-6-10-1116	#6 AWG	#6 FLEX	-	10	0.219	0.687	1.250	1.125	2.570	0.411	0.258	Blue	I-24	0.320	0.225
CLWD-6-10-34	#6 AWG	#6 FLEX	-	10	0.219	0.750	1.437	1.125	2.757	0.411	0.258	Blue	I-24	0.320	0.225
CLWD-6-14-12	#6 AWG	#6 FLEX	-	1/4	0.281	0.500	1.250	1.125	2.570	0.411	0.320	Blue	I-24	0.320	0.225
CLWD-6-14-58	#6 AWG	#6 FLEX	-	1/4	0.281	0.625	1.437	1.125	2.757	0.411	0.320	Blue	I-24	0.320	0.225
CLWD-6-14-34	#6 AWG	#6 FLEX	-	1/4	0.281	0.750	1.437	1.125	2.757	0.411	0.320	Blue	I-24	0.320	0.225
CLWD-6-14-1	#6 AWG	#6 FLEX	-	1/4	0.281	1.000	1.687	1.125	3.007	0.411	0.320	Blue	I-24	0.320	0.225
CLWD-6-516-34	#6 AWG	#6 FLEX	-	5/16	0.343	0.750	1.687	1.125	3.007	0.532	0.352	Blue	I-24	0.320	0.225
CLWD-6-516-1	#6 AWG	#6 FLEX	-	5/16	0.343	1.000	1.937	1.125	3.257	0.532	0.352	Blue	I-24	0.320	0.225
CLWD-6-38-34	#6 AWG	#6 FLEX	-	3/8	0.406	0.750	1.687	1.125	3.007	0.593	0.414	Blue	I-24	0.320	0.225
CLWD-6-38-78	#6 AWG	#6 FLEX	-	3/8	0.406	0.875	1.937	1.125	3.257	0.593	0.414	Blue	I-24	0.320	0.225
CLWD-6-38-1	#6 AWG	#6 FLEX	-	3/8	0.406	1.000	1.937	1.125	3.257	0.593	0.414	Blue	I-24	0.320	0.225
CLWD-6-12-134	#6 AWG	#6 FLEX	-	1/2	0.562	1.750	3.000	1.125	4.320	0.750	0.546	Blue	I-24	0.320	0.225
CLWD-4-10-58	#4 AWG	-	4-6 AWG	10	0.219	0.625	1.250	1.125	2.609	0.486	0.258	Gray	I-29	0.343	0.250
CLWD-4-10-34	#4 AWG	-	4-6 AWG	10	0.219	0.750	1.437	1.125	2.796	0.486	0.258	Gray	I-29	0.343	0.250
CLWD-4-10-1	#4 AWG	-	4-6 AWG	10	0.219	1.000	1.687	1.125	3.046	0.486	0.258	Gray	I-29	0.343	0.250
CLWD-4-14-58	#4 AWG	-	4-6 AWG	1/4	0.281	0.625	1.437	1.125	2.796	0.486	0.320	Gray	I-29	0.343	0.250
CLWD-4-14-34	#4 AWG	-	4-6 AWG	1/4	0.281	0.750	1.437	1.125	2.796	0.486	0.320	Gray	I-29	0.343	0.250
CLWD-4-14-1	#4 AWG	-	4-6 AWG	1/4	0.281	1.000	1.687	1.125	3.046	0.486	0.320	Gray	I-29	0.343	0.250
CLWD-4-516-58	#4 AWG	-	4-6 AWG	5/16	0.343	0.625	1.437	1.125	2.796	0.486	0.352	Gray	I-29	0.343	0.250
CLWD-4-516-34	#4 AWG	-	4-6 AWG	5/16	0.343	0.750	1.687	1.125	3.046	0.486	0.352	Gray	I-29	0.343	0.250
CLWD-4-516-1	#4 AWG	-	4-6 AWG	5/16	0.343	1.000	1.937	1.125	3.296	0.486	0.352	Gray	I-29	0.343	0.250
CLWD-4-38-34	#4 AWG	-	4-6 AWG	3/8	0.406	0.750	1.687	1.125	3.046	0.593	0.414	Gray	I-29	0.343	0.250
CLWD-4-38-1	#4 AWG	-	4-6 AWG	3/8	0.406	1.000	1.937	1.125	3.296	0.593	0.414	Gray	I-29	0.343	0.250
CLWD-4-12-134	#4 AWG	-	4-6 AWG	1/2	0.562	1.750	3.000	1.125	4.359	0.750	0.546	Gray	I-29	0.343	0.250

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CLWD

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLWD-3-14-58	#3 AWG	#4 FLEX	3-6 AWG	1/4	0.281	0.625	1.437	1.125	2.817	0.532	0.320	White	I-29	0.375	0.275
CLWD-3-14-34	#3 AWG	#4 FLEX	3-6 AWG	1/4	0.281	0.750	1.437	1.125	2.817	0.532	0.320	White	I-29	0.375	0.275
CLWD-3-516-58	#3 AWG	#4 FLEX	3-6 AWG	5/16	0.343	0.625	1.437	1.125	2.817	0.532	0.352	White	I-29	0.375	0.275
CLWD-3-516-1	#3 AWG	#4 FLEX	3-6 AWG	5/16	0.343	1.000	1.937	1.125	3.317	0.532	0.352	White	I-29	0.375	0.275
CLWD-3-38-34	#3 AWG	#4 FLEX	3-6 AWG	3/8	0.406	0.750	1.687	1.125	3.067	0.593	0.414	White	I-29	0.375	0.275
CLWD-3-38-1	#3 AWG	#4 FLEX	3-6 AWG	3/8	0.406	1.000	1.937	1.125	3.317	0.593	0.414	White	I-29	0.375	0.275
CLWD-3-12-134	#3 AWG	#4 FLEX	3-6 AWG	1/2	0.562	1.750	3.000	1.125	4.380	0.750	0.546	White	I-29	0.375	0.275
CLWD-2-10-34	#2 AWG	-	2-6 AWG	10	0.219	0.750	1.437	1.125	2.848	0.599	0.258	Brown	I-33	0.421	0.312
CLWD-2-14-58	#2 AWG	-	2-6 AWG	1/4	0.281	0.625	1.437	1.125	2.848	0.599	0.320	Brown	I-33	0.421	0.312
CLWD-2-14-34	#2 AWG	-	2-6 AWG	1/4	0.281	0.750	1.437	1.125	2.848	0.599	0.320	Brown	I-33	0.421	0.312
CLWD-2-14-1	#2 AWG	-	2-6 AWG	1/4	0.281	1.000	1.687	1.125	3.098	0.599	0.320	Brown	I-33	0.421	0.312
CLWD-2-516-58	#2 AWG	-	2-6 AWG	5/16	0.343	0.625	1.687	1.125	3.098	0.599	0.352	Brown	I-33	0.421	0.312
CLWD-2-516-34	#2 AWG	-	2-6 AWG	5/16	0.343	0.750	1.687	1.125	3.098	0.599	0.352	Brown	I-33	0.421	0.312
CLWD-2-516-1	#2 AWG	-	2-6 AWG	5/16	0.343	1.000	1.937	1.125	3.348	0.599	0.352	Brown	I-33	0.421	0.312
CLWD-2-38-58	#2 AWG	-	2-6 AWG	3/8	0.406	0.625	1.687	1.125	3.098	0.599	0.414	Brown	I-33	0.421	0.312
CLWD-2-38-34	#2 AWG	-	2-6 AWG	3/8	0.406	0.750	1.687	1.125	3.098	0.599	0.414	Brown	I-33	0.421	0.312
CLWD-2-38-78	#2 AWG	-	2-6 AWG	3/8	0.406	0.875	1.937	1.125	3.348	0.599	0.414	Brown	I-33	0.421	0.312
CLWD-2-38-1	#2 AWG	-	2-6 AWG	3/8	0.406	1.000	1.937	1.125	3.348	0.599	0.414	Brown	I-33	0.421	0.312
CLWD-2-38-134	#2 AWG	-	2-6 AWG	3/8	0.406	1.750	2.625	1.125	4.036	0.599	0.414	Brown	I-33	0.421	0.312
CLWD-2-12-134	#2 AWG	-	2-6 AWG	1/2	0.562	1.750	3.000	1.125	4.411	0.750	0.546	Brown	I-33	0.421	0.312
CLWD-1-14-58	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	0.625	1.437	1.375	3.142	0.673	0.320	Green	I-37	0.468	0.359
CLWD-1-14-34	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	0.750	1.437	1.375	3.142	0.673	0.320	Green	I-37	0.468	0.359
CLWD-1-14-1	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	1.000	1.687	1.375	3.392	0.673	0.320	Green	I-37	0.468	0.359
CLWD-1-516-78	#1 AWG	#2 FLEX	1-6 AWG	5/16	0.343	0.875	1.687	1.375	3.392	0.673	0.352	Green	I-37	0.468	0.359
CLWD-1-516-1	#1 AWG	#2 FLEX	1-6 AWG	5/16	0.343	1.000	1.937	1.375	3.642	0.673	0.352	Green	I-37	0.468	0.359
CLWD-1-38-1	#1 AWG	#2 FLEX	1-6 AWG	3/8	0.406	1.000	1.937	1.375	3.642	0.673	0.414	Green	I-37	0.468	0.359
CLWD-1-12-134	#1 AWG	#2 FLEX	1-6 AWG	1/2	0.562	1.750	3.000	1.375	4.705	0.750	0.546	Green	I-37	0.468	0.359

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

TYPE CLWD


Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications

A



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLWD-1/0-14-58	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	0.625	1.437	1.500	3.293	0.738	0.320	Pink	I-42	0.515	0.390
CLWD-1/0-14-34	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	0.750	1.437	1.500	3.293	0.738	0.320	Pink	I-42	0.515	0.390
CLWD-1/0-14-1	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	1.000	1.687	1.500	3.543	0.738	0.320	Pink	I-42	0.515	0.390
CLWD-1/0-516-34	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	0.750	1.687	1.500	3.543	0.738	0.352	Pink	I-42	0.515	0.390
CLWD-1/0-516-78	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	0.875	1.687	1.500	3.543	0.738	0.352	Pink	I-42	0.515	0.390
CLWD-1/0-516-1	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	1.000	1.937	1.500	3.793	0.738	0.352	Pink	I-42	0.515	0.390
CLWD-1/0-38-1	1/0 AWG	#1 FLEX	1/0-6 AWG	3/8	0.406	1.000	1.937	1.500	3.793	0.738	0.414	Pink	I-42	0.515	0.390
CLWD-1/0-38-134	1/0 AWG	#1 FLEX	1/0-6 AWG	3/8	0.406	1.750	2.625	1.500	4.481	0.738	0.414	Pink	I-42	0.515	0.390
CLWD-1/0-12-1	1/0 AWG	#1 FLEX	1/0-6 AWG	1/2	0.562	1.000	2.125	1.500	3.981	0.738	0.546	Pink	I-42	0.515	0.390
CLWD-1/0-12-134	1/0 AWG	#1 FLEX	1/0-6 AWG	1/2	0.562	1.750	3.000	1.500	4.856	0.738	0.546	Pink	I-42	0.515	0.390
CLWD-2/0-14-58	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	0.625	1.437	1.500	3.333	0.811	0.320	Black	I-45	0.562	0.437
CLWD-2/0-14-34	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	0.750	1.437	1.500	3.333	0.811	0.320	Black	I-45	0.562	0.437
CLWD-2/0-14-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	1.000	1.687	1.500	3.583	0.811	0.320	Black	I-45	0.562	0.437
CLWD-2/0-516-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	5/16	0.343	1.000	1.937	1.500	3.833	0.811	0.352	Black	I-45	0.562	0.437
CLWD-2/0-38-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	3/8	0.406	1.000	1.937	1.500	3.833	0.811	0.414	Black	I-45	0.562	0.437
CLWD-2/0-38-134	2/0 AWG	1/0 FLEX	2/0-4 AWG	3/8	0.406	1.750	2.625	1.500	4.521	0.811	0.414	Black	I-45	0.562	0.437
CLWD-2/0-12-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/2	0.562	1.000	2.125	1.500	4.021	0.811	0.546	Black	I-45	0.562	0.437
CLWD-2/0-12-134	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/2	0.562	1.750	3.000	1.500	4.896	0.811	0.546	Black	I-45	0.562	0.437
CLWD-3/0-14-58	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/4	0.281	0.625	1.437	1.500	3.376	0.885	0.320	Orange	I-50	0.609	0.484
CLWD-3/0-14-34	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/4	0.281	0.750	1.437	1.500	3.376	0.885	0.320	Orange	I-50	0.609	0.484
CLWD-3/0-516-1	3/0 AWG	2/0 FLEX	3/0-2 AWG	5/16	0.343	1.000	1.937	1.500	3.876	0.885	0.352	Orange	I-50	0.609	0.484
CLWD-3/0-38-1	3/0 AWG	2/0 FLEX	3/0-2 AWG	3/8	0.406	1.000	1.937	1.500	3.876	0.885	0.414	Orange	I-50	0.609	0.484
CLWD-3/0-12-134	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/2	0.562	1.750	3.000	1.500	4.939	0.885	0.546	Orange	I-50	0.609	0.484

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CLWD

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLWD-4/0-14-58	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	0.625	1.437	1.500	3.428	0.999	0.320	Purple	I-54	0.687	0.546
CLWD-4/0-14-34	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	0.750	1.437	1.500	3.428	0.999	0.320	Purple	I-54	0.687	0.546
CLWD-4/0-14-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	1.000	1.687	1.500	3.678	0.999	0.320	Purple	I-54	0.687	0.546
CLWD-4/0-516-34	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	0.750	1.687	1.500	3.678	0.999	0.352	Purple	I-54	0.687	0.546
CLWD-4/0-516-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	1.000	1.937	1.500	3.928	0.999	0.352	Purple	I-54	0.687	0.546
CLWD-4/0-516-134	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	1.750	2.500	1.500	4.491	0.999	0.352	Purple	I-54	0.687	0.546
CLWD-4/0-38-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	3/8	0.406	1.000	1.937	1.500	3.928	0.999	0.414	Purple	I-54	0.687	0.546
CLWD-4/0-38-134	4/0 AWG	3/0 FLEX	4/0-1 AWG	3/8	0.406	1.750	2.625	1.500	4.616	0.999	0.414	Purple	I-54	0.687	0.546
CLWD-4/0-12-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.000	2.125	1.500	4.116	0.999	0.546	Purple	I-54	0.687	0.546
CLWD-4/0-12-114	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.250	2.500	1.500	4.491	0.999	0.546	Purple	I-54	0.687	0.546
CLWD-4/0-12-134	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.750	3.000	1.500	4.991	0.999	0.546	Purple	I-54	0.687	0.546
CLWD-250-14-34	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/4	0.281	0.750	1.437	1.688	3.656	1.088	0.320	Yellow	I-62	0.750	0.593
CLWD-250-38-1	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	1.000	1.937	1.688	4.156	1.088	0.414	Yellow	I-62	0.750	0.593
CLWD-250-38-134	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	1.750	2.625	1.688	4.844	1.088	0.414	Yellow	I-62	0.750	0.593
CLWD-250-12-114	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/2	0.562	1.250	2.500	1.688	4.719	1.088	0.546	Yellow	I-62	0.750	0.593
CLWD-250-12-134	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/2	0.562	1.750	3.000	1.688	5.219	1.088	0.546	Yellow	I-62	0.750	0.593
CLWD-300-38-1	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	3/8	0.406	1.000	1.937	2.000	4.524	1.189	0.414	White	I-66	0.812	0.660
CLWD-300-12-134	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	1/2	0.562	1.750	3.000	2.000	5.587	1.189	0.546	White	I-66	0.812	0.660

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207


TYPE CLWD

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLWD-350-14-34	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/4	0.281	0.750	1.437	2.000	4.060	1.291	0.320	Red	I-71	0.890	0.703
CLWD-350-516-134	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	5/16	0.343	1.750	2.500	2.000	5.123	1.291	0.352	Red	I-71	0.890	0.703
CLWD-350-38-1	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	3/8	0.406	1.000	1.937	2.000	4.560	1.291	0.414	Red	I-71	0.890	0.703
CLWD-350-12-114	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/2	0.562	1.250	2.500	2.000	5.123	1.291	0.546	Red	I-71	0.890	0.703
CLWD-350-12-134	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/2	0.562	1.750	3.000	2.000	5.623	1.291	0.546	Red	I-71	0.890	0.703
CLWD-400-38-1	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	3/8	0.406	1.000	1.937	2.125	4.729	1.365	0.414	Blue	I-76	0.937	0.750
CLWD-400-38-116	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	3/8	0.406	1.062	1.937	2.125	4.729	1.365	0.414	Blue	I-76	0.937	0.750
CLWD-400-12-134	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	1/2	0.562	1.750	3.000	2.125	5.792	1.365	0.546	Blue	I-76	0.937	0.750
CLWD-500-14-34	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/4	0.281	0.750	1.437	2.250	4.419	1.535	0.320	Brown	I-87	1.062	0.828
CLWD-500-38-1	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	3/8	0.406	1.000	1.937	2.250	4.919	1.535	0.414	Brown	I-87	1.062	0.828
CLWD-500-12-114	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/2	0.562	1.250	2.500	2.250	5.482	1.535	0.546	Brown	I-87	1.062	0.828
CLWD-500-12-134	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/2	0.562	1.750	3.000	2.250	5.982	1.535	0.546	Brown	I-87	1.062	0.828
CLWD-600-38-1	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	3/8	0.406	1.000	1.937	2.687	5.433	1.712	0.414	Green	I-94	1.187	0.920
CLWD-600-12-134	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	1/2	0.562	1.750	3.000	2.687	6.496	1.712	0.546	Green	I-94	1.187	0.920
CLWD-650-12-114	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/2	0.562	1.250	2.500	2.687	6.056	1.764	0.546	Pink	I-99	1.217	0.958
CLWD-650-12-134	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/2	0.562	1.750	3.000	2.687	6.556	1.764	0.546	Pink	I-99	1.217	0.958
CLWD-650-38-1	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	3/8	0.406	1.000	1.937	2.687	5.493	1.764	0.414	Pink	I-99	1.217	0.958
CLWD-650-38-118	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	3/8	0.406	1.125	2.125	2.687	5.681	1.764	0.414	Pink	I-99	1.217	0.958
CLWD-650-516-1	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/32	0.343	1.000	1.937	2.687	5.493	1.764	0.3515	Pink	I-99	1.217	0.958

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information. For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg. UL File E6207

A


TYPE CLWD

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLWD-700-38-1	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	3/8	0.406	1.000	1.937	2.687	5.493	1.816	0.414	Pink	I-99	1.250	0.991
CLWD-700-38-118	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	3/8	0.406	1.125	2.125	2.687	5.681	1.816	0.414	Pink	I-99	1.250	0.991
CLWD-700-12-112	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.500	2.625	2.687	6.181	1.816	0.546	Pink	I-99	1.250	0.991
CLWD-700-12-134	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.750	3.000	2.687	6.556	1.816	0.546	Pink	I-99	1.250	0.991
CLWD-700-12-178	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.875	3.000	2.687	6.556	1.816	0.546	Pink	I-99	1.250	0.991
CLWD-750-38-1	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	3/8	0.406	1.000	1.937	2.875	5.714	1.901	0.414	Black	I-106	1.313	1.031
CLWD-750-38-118	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	3/8	0.406	1.125	2.125	2.875	5.902	1.901	0.414	Black	I-106	1.313	1.031
CLWD-750-12-112	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	1/2	0.562	1.500	2.625	2.875	6.402	1.901	0.546	Black	I-106	1.313	1.031
CLWD-750-12-134	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	1/2	0.562	1.750	3.000	2.875	6.777	1.901	0.546	Black	I-106	1.313	1.031
CLWD-750-58-112	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	5/8	0.656	1.500	3.000	2.875	6.777	1.901	0.671	Black	I-106	1.313	1.031
CLWD-1000-38-1	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	3/8	0.406	1.000	1.937	3.000	5.962	2.169	0.414	White	I-125	1.500	1.172
CLWD-1000-12-114	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	1/2	0.562	1.250	2.500	3.000	6.525	2.169	0.546	White	I-125	1.500	1.172
CLWD-1000-12-134	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	1/2	0.562	1.750	3.000	3.000	7.025	2.169	0.546	White	I-125	1.500	1.172
CLWD-1000-58-112	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	5/8	0.656	1.500	3.000	3.000	7.025	2.169	0.671	White	I-125	1.500	1.172

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207


TYPE CLND

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLND-8-10-58	#8 AWG	#8 FLEX	-	10	0.219	0.625	1.250	0.812	2.257	0.374	0.258	Red	I-21	0.272	0.179
CLND-8-10-34	#8 AWG	#8 FLEX	-	10	0.219	0.750	1.437	0.812	2.444	0.374	0.258	Red	I-21	0.272	0.179
CLND-8-14-58	#8 AWG	#8 FLEX	-	1/4	0.281	0.625	1.437	0.812	2.444	0.486	0.320	Red	I-21	0.272	0.179
CLND-8-14-34	#8 AWG	#8 FLEX	-	1/4	0.281	0.750	1.437	0.812	2.444	0.486	0.320	Red	I-21	0.272	0.179
CLND-8-14-1	#8 AWG	#8 FLEX	-	1/4	0.281	1.000	1.687	0.812	2.694	0.486	0.320	Red	I-21	0.272	0.179
CLND-8-38-1	#8 AWG	#8 FLEX	-	3/8	0.406	1.000	1.937	0.812	2.944	0.593	0.414	Red	I-21	0.272	0.179
CLND-6-10-12	#6 AWG	#6 FLEX	-	10	0.219	0.500	1.250	1.125	2.570	0.411	0.258	Blue	I-24	0.320	0.225
CLND-6-10-58	#6 AWG	#6 FLEX	-	10	0.219	0.625	1.250	1.125	2.570	0.411	0.258	Blue	I-24	0.320	0.225
CLND-6-10-1116	#6 AWG	#6 FLEX	-	10	0.219	0.687	1.250	1.125	2.570	0.411	0.258	Blue	I-24	0.320	0.225
CLND-6-10-34	#6 AWG	#6 FLEX	-	10	0.219	0.750	1.437	1.125	2.757	0.411	0.258	Blue	I-24	0.320	0.225
CLND-6-14-12	#6 AWG	#6 FLEX	-	1/4	0.281	0.500	1.250	1.125	2.570	0.411	0.320	Blue	I-24	0.320	0.225
CLND-6-14-58	#6 AWG	#6 FLEX	-	1/4	0.281	0.625	1.437	1.125	2.757	0.411	0.320	Blue	I-24	0.320	0.225
CLND-6-14-34	#6 AWG	#6 FLEX	-	1/4	0.281	0.750	1.437	1.125	2.757	0.411	0.320	Blue	I-24	0.320	0.225
CLND-6-14-1	#6 AWG	#6 FLEX	-	1/4	0.281	1.000	1.687	1.125	3.007	0.411	0.320	Blue	I-24	0.320	0.225
CLND-6-516-34	#6 AWG	#6 FLEX	-	5/16	0.343	0.750	1.687	1.125	3.007	0.532	0.352	Blue	I-24	0.320	0.225
CLND-6-516-1	#6 AWG	#6 FLEX	-	5/16	0.343	1.000	1.937	1.125	3.257	0.532	0.352	Blue	I-24	0.320	0.225
CLND-6-38-34	#6 AWG	#6 FLEX	-	3/8	0.406	0.750	1.687	1.125	3.007	0.593	0.414	Blue	I-24	0.320	0.225
CLND-6-38-78	#6 AWG	#6 FLEX	-	3/8	0.406	0.875	1.937	1.125	3.257	0.593	0.414	Blue	I-24	0.320	0.225
CLND-6-38-1	#6 AWG	#6 FLEX	-	3/8	0.406	1.000	1.937	1.125	3.257	0.593	0.414	Blue	I-24	0.320	0.225
CLND-6-12-134	#6 AWG	#6 FLEX	-	1/2	0.562	1.750	3.000	1.125	4.320	0.750	0.546	Blue	I-24	0.320	0.225
CLND-4-10-58	#4 AWG	-	4-6 AWG	10	0.219	0.625	1.250	1.125	2.609	0.486	0.258	Gray	I-29	0.343	0.250
CLND-4-10-34	#4 AWG	-	4-6 AWG	10	0.219	0.750	1.437	1.125	2.796	0.486	0.258	Gray	I-29	0.343	0.250
CLND-4-10-1	#4 AWG	-	4-6 AWG	10	0.219	1.000	1.687	1.125	3.046	0.486	0.258	Gray	I-29	0.343	0.250
CLND-4-14-58	#4 AWG	-	4-6 AWG	1/4	0.281	0.625	1.437	1.125	2.796	0.486	0.320	Gray	I-29	0.343	0.250
CLND-4-14-34	#4 AWG	-	4-6 AWG	1/4	0.281	0.750	1.437	1.125	2.796	0.486	0.320	Gray	I-29	0.343	0.250
CLND-4-516-34	#4 AWG	-	4-6 AWG	5/16	0.343	0.750	1.687	1.125	3.046	0.486	0.352	Gray	I-29	0.343	0.250
CLND-4-516-1	#4 AWG	-	4-6 AWG	5/16	0.343	1.000	1.937	1.125	3.296	0.486	0.352	Gray	I-29	0.343	0.250
CLND-4-38-34	#4 AWG	-	4-6 AWG	3/8	0.406	0.750	1.687	1.125	3.046	0.593	0.414	Gray	I-29	0.343	0.250
CLND-4-38-1	#4 AWG	-	4-6 AWG	3/8	0.406	1.000	1.937	1.125	3.296	0.593	0.414	Gray	I-29	0.343	0.250
CLND-4-12-134	#4 AWG	-	4-6 AWG	1/2	0.562	1.750	3.000	1.125	4.359	0.750	0.546	Gray	I-29	0.343	0.250

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CLND

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLND-3-14-58	#3 AWG	#4 FLEX	3-6 AWG	1/4	0.281	0.625	1.437	1.125	2.817	0.532	0.320	White	I-29	0.375	0.275
CLND-3-14-34	#3 AWG	#4 FLEX	3-6 AWG	1/4	0.281	0.750	1.437	1.125	2.817	0.532	0.320	White	I-29	0.375	0.275
CLND-3-516-58	#3 AWG	#4 FLEX	3-6 AWG	5/16	0.343	0.625	1.437	1.125	2.817	0.532	0.352	White	I-29	0.375	0.275
CLND-3-516-1	#3 AWG	#4 FLEX	3-6 AWG	5/16	0.343	1.000	1.937	1.125	3.317	0.532	0.352	White	I-29	0.375	0.275
CLND-3-38-34	#3 AWG	#4 FLEX	3-6 AWG	3/8	0.406	0.750	1.687	1.125	3.067	0.593	0.414	White	I-29	0.375	0.275
CLND-3-38-1	#3 AWG	#4 FLEX	3-6 AWG	3/8	0.406	1.000	1.937	1.125	3.317	0.593	0.414	White	I-29	0.375	0.275
CLND-3-12-134	#3 AWG	#4 FLEX	3-6 AWG	1/2	0.562	1.750	3.000	1.125	4.380	0.750	0.546	White	I-29	0.375	0.275
CLND-2-10-34	#2 AWG	-	2-6 AWG	10	0.219	0.750	1.437	1.125	2.848	0.599	0.258	Brown	I-33	0.421	0.312
CLND-2-14-58	#2 AWG	-	2-6 AWG	1/4	0.281	0.625	1.437	1.125	2.848	0.599	0.320	Brown	I-33	0.421	0.312
CLND-2-14-34	#2 AWG	-	2-6 AWG	1/4	0.281	0.750	1.437	1.125	2.848	0.599	0.320	Brown	I-33	0.421	0.312
CLND-2-14-1	#2 AWG	-	2-6 AWG	1/4	0.281	1.000	1.687	1.125	3.098	0.599	0.320	Brown	I-33	0.421	0.312
CLND-2-516-34	#2 AWG	-	2-6 AWG	5/16	0.343	0.750	1.687	1.125	3.098	0.599	0.352	Brown	I-33	0.421	0.312
CLND-2-516-1	#2 AWG	-	2-6 AWG	5/16	0.343	1.000	1.937	1.125	3.348	0.599	0.352	Brown	I-33	0.421	0.312
CLND-2-38-34	#2 AWG	-	2-6 AWG	3/8	0.406	0.750	1.687	1.125	3.098	0.599	0.414	Brown	I-33	0.421	0.312
CLND-2-38-78	#2 AWG	-	2-6 AWG	3/8	0.406	0.875	1.937	1.125	3.348	0.599	0.414	Brown	I-33	0.421	0.312
CLND-2-38-1	#2 AWG	-	2-6 AWG	3/8	0.406	1.000	1.937	1.125	3.348	0.599	0.414	Brown	I-33	0.421	0.312
CLND-2-38-134	#2 AWG	-	2-6 AWG	3/8	0.406	1.750	2.625	1.125	4.036	0.599	0.414	Brown	I-33	0.421	0.312
CLND-2-12-134	#2 AWG	-	2-6 AWG	1/2	0.562	1.750	3.000	1.125	4.411	0.750	0.546	Brown	I-33	0.421	0.312
CLND-1-14-58	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	0.625	1.437	1.375	3.142	0.673	0.320	Green	I-37	0.468	0.359
CLND-1-14-34	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	0.750	1.437	1.375	3.142	0.673	0.320	Green	I-37	0.468	0.359
CLND-1-14-1	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	1.000	1.687	1.375	3.392	0.673	0.320	Green	I-37	0.468	0.359
CLND-1-516-78	#1 AWG	#2 FLEX	1-6 AWG	5/16	0.343	0.875	1.687	1.375	3.392	0.673	0.352	Green	I-37	0.468	0.359
CLND-1-516-1	#1 AWG	#2 FLEX	1-6 AWG	5/16	0.343	1.000	1.937	1.375	3.642	0.673	0.352	Green	I-37	0.468	0.359
CLND-1-38-1	#1 AWG	#2 FLEX	1-6 AWG	3/8	0.406	1.000	1.937	1.375	3.642	0.673	0.414	Green	I-37	0.468	0.359
CLND-1-12-134	#1 AWG	#2 FLEX	1-6 AWG	1/2	0.562	1.750	3.000	1.375	4.705	0.750	0.546	Green	I-37	0.468	0.359

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207


TYPE CLND

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLND-1/0-14-58	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	0.625	1.437	1.500	3.293	0.738	0.320	Pink	I-42	0.515	0.390
CLND-1/0-14-34	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	0.750	1.437	1.500	3.293	0.738	0.320	Pink	I-42	0.515	0.390
CLND-1/0-14-1	1/0 AWG	#1 FLEX	1/0-6 AWG	1/4	0.281	1.000	1.687	1.500	3.543	0.738	0.320	Pink	I-42	0.515	0.390
CLND-1/0-516-34	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	0.750	1.687	1.500	3.543	0.738	0.352	Pink	I-42	0.515	0.390
CLND-1/0-516-78	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	0.875	1.687	1.500	3.543	0.738	0.352	Pink	I-42	0.515	0.390
CLND-1/0-516-1	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	1.000	1.937	1.500	3.793	0.738	0.352	Pink	I-42	0.515	0.390
CLND-1/0-38-1	1/0 AWG	#1 FLEX	1/0-6 AWG	3/8	0.406	1.000	1.937	1.500	3.793	0.738	0.414	Pink	I-42	0.515	0.390
CLND-1/0-38-134	1/0 AWG	#1 FLEX	1/0-6 AWG	3/8	0.406	1.750	2.625	1.500	4.481	0.738	0.414	Pink	I-42	0.515	0.390
CLND-1/0-12-1	1/0 AWG	#1 FLEX	1/0-6 AWG	1/2	0.562	1.000	2.125	1.500	3.981	0.738	0.546	Pink	I-42	0.515	0.390
CLND-1/0-12-134	1/0 AWG	#1 FLEX	1/0-6 AWG	1/2	0.562	1.750	3.000	1.500	4.856	0.738	0.546	Pink	I-42	0.515	0.390
CLND-2/0-14-58	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	0.625	1.437	1.500	3.333	0.811	0.320	Black	I-45	0.562	0.437
CLND-2/0-14-34	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	0.750	1.437	1.500	3.333	0.811	0.320	Black	I-45	0.562	0.437
CLND-2/0-14-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/4	0.281	1.000	1.687	1.500	3.583	0.811	0.320	Black	I-45	0.562	0.437
CLND-2/0-516-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	5/16	0.343	1.000	1.937	1.500	3.833	0.811	0.352	Black	I-45	0.562	0.437
CLND-2/0-38-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	3/8	0.406	1.000	1.937	1.500	3.833	0.811	0.414	Black	I-45	0.562	0.437
CLND-2/0-38-134	2/0 AWG	1/0 FLEX	2/0-4 AWG	3/8	0.406	1.750	2.625	1.500	4.521	0.811	0.414	Black	I-45	0.562	0.437
CLND-2/0-12-1	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/2	0.562	1.000	2.125	1.500	4.021	0.811	0.546	Black	I-45	0.562	0.437
CLND-2/0-12-134	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/2	0.562	1.750	3.000	1.500	4.896	0.811	0.546	Black	I-45	0.562	0.437
CLND-3/0-14-58	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/4	0.281	0.625	1.437	1.500	3.376	0.885	0.320	Orange	I-50	0.609	0.484
CLND-3/0-14-34	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/4	0.281	0.750	1.437	1.500	3.376	0.885	0.320	Orange	I-50	0.609	0.484
CLND-3/0-516-1	3/0 AWG	2/0 FLEX	3/0-2 AWG	5/16	0.343	1.000	1.937	1.500	3.876	0.885	0.352	Orange	I-50	0.609	0.484
CLND-3/0-38-1	3/0 AWG	2/0 FLEX	3/0-2 AWG	3/8	0.406	1.000	1.937	1.500	3.876	0.885	0.414	Orange	I-50	0.609	0.484
CLND-3/0-12-134	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/2	0.562	1.750	3.000	1.500	4.939	0.885	0.546	Orange	I-50	0.609	0.484

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CLND

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Color Code	Die Die Index	O.D.	I.D.
							A	B	C	D	G				
CLND-4/0-14-58	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	0.625	1.437	1.500	3.428	0.999	0.320	Purple	I-54	0.687	0.546
CLND-4/0-14-34	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	0.750	1.437	1.500	3.428	0.999	0.320	Purple	I-54	0.687	0.546
CLND-4/0-14-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/4	0.281	1.000	1.687	1.500	3.678	0.999	0.320	Purple	I-54	0.687	0.546
CLND-4/0-516-34	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	0.750	1.687	1.500	3.678	0.999	0.352	Purple	I-54	0.687	0.546
CLND-4/0-516-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	1.000	1.937	1.500	3.928	0.999	0.352	Purple	I-54	0.687	0.546
CLND-4/0-516-134	4/0 AWG	3/0 FLEX	4/0-1 AWG	5/16	0.343	1.750	2.500	1.500	4.491	0.999	0.352	Purple	I-54	0.687	0.546
CLND-4/0-38-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	3/8	0.406	1.000	1.937	1.500	3.928	0.999	0.414	Purple	I-54	0.687	0.546
CLND-4/0-38-134	4/0 AWG	3/0 FLEX	4/0-1 AWG	3/8	0.406	1.750	2.625	1.500	4.616	0.999	0.414	Purple	I-54	0.687	0.546
CLND-4/0-12-1	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.000	2.125	1.500	4.116	0.999	0.546	Purple	I-54	0.687	0.546
CLND-4/0-12-114	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.250	2.500	1.500	4.491	0.999	0.546	Purple	I-54	0.687	0.546
CLND-4/0-12-134	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.562	1.750	3.000	1.500	4.991	0.999	0.546	Purple	I-54	0.687	0.546
CLND-250-14-34	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/4	0.281	0.750	1.437	1.688	3.656	1.088	0.320	Yellow	I-62	0.750	0.593
CLND-250-38-1	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	1.000	1.937	1.688	4.156	1.088	0.414	Yellow	I-62	0.750	0.593
CLND-250-38-134	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	1.750	2.625	1.688	4.844	1.088	0.414	Yellow	I-62	0.750	0.593
CLND-250-12-114	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/2	0.562	1.250	2.500	1.688	4.719	1.088	0.546	Yellow	I-62	0.750	0.593
CLND-250-12-134	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	1/2	0.562	1.750	3.000	1.688	5.219	1.088	0.546	Yellow	I-62	0.750	0.593
CLND-300-38-1	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	3/8	0.406	1.000	1.937	2.000	4.524	1.189	0.414	White	I-66	0.812	0.660
CLND-300-12-134	300kcmil	250 G,H FLEX	300kcmil - 2/0 AWG	1/2	0.562	1.750	3.000	2.000	5.587	1.189	0.546	White	I-66	0.812	0.660
CLND-350-14-34	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/4	0.281	0.750	1.437	2.000	4.060	1.291	0.320	Red	I-71	0.890	0.703
CLND-350-516-134	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	5/16	0.343	1.750	2.500	2.000	5.123	1.291	0.352	Red	I-71	0.890	0.703
CLND-350-38-1	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	3/8	0.406	1.000	1.937	2.000	4.560	1.291	0.414	Red	I-71	0.890	0.703
CLND-350-12-114	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/2	0.562	1.250	2.500	2.000	5.123	1.291	0.546	Red	I-71	0.890	0.703
CLND-350-12-134	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	1/2	0.562	1.750	3.000	2.000	5.623	1.291	0.546	Red	I-71	0.890	0.703

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools + See pages 79 to 84 for complete tooling information. For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg. UL File E6207


TYPE CLND

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Color Code	Die Die Index	O.D.	I.D.
							A	B	C	D	G				
CLND-400-38-1	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	3/8	0.406	1.000	1.937	2.125	4.729	1.365	0.414	Blue	I-76	0.937	0.750
CLND-400-38-116	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	3/8	0.406	1.062	1.937	2.125	4.729	1.365	0.414	Blue	I-76	0.937	0.750
CLND-400-12-134	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil - 4/0 AWG	1/2	0.562	1.750	3.000	2.125	5.792	1.365	0.546	Blue	I-76	0.937	0.750
CLND-500-14-34	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/4	0.281	0.750	1.437	2.250	4.419	1.535	0.320	Brown	I-87	1.062	0.828
CLND-500-38-1	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	3/8	0.406	1.000	1.937	2.250	4.919	1.535	0.414	Brown	I-87	1.062	0.828
CLND-500-12-114	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/2	0.562	1.250	2.500	2.250	5.482	1.535	0.546	Brown	I-87	1.062	0.828
CLND-500-12-134	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	1/2	0.562	1.750	3.000	2.250	5.982	1.535	0.546	Brown	I-87	1.062	0.828
CLND-600-38-1	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	3/8	0.406	1.000	1.937	2.687	5.433	1.712	0.414	Green	I-94	1.187	0.920
CLND-600-12-134	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	1/2	0.562	1.750	3.000	2.687	6.496	1.712	0.546	Green	I-94	1.187	0.920
CLND-650-12-114	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/2	0.562	1.250	2.500	2.687	6.056	1.764	0.546	Pink	I-99	1.217	0.958
CLND-650-12-134	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/2	0.562	1.750	3.000	2.687	6.556	1.764	0.546	Pink	I-99	1.217	0.958
CLND-650-38-1	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	3/8	0.406	1.000	2.125	2.687	5.493	1.764	0.414	Pink	I-99	1.217	0.958
CLND-650-38-118	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	3/8	0.406	1.125	2.125	2.687	5.681	1.764	0.414	Pink	I-99	1.217	0.958
CLND-650-516-1	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil - 350kcmil	1/32	0.343	1.000	1.937	2.687	5.493	1.764	0.3515	Pink	I-99	1.217	0.958

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CLND

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLND-700-38-1	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	3/8	0.406	1.000	1.937	2.687	5.493	1.816	0.414	Pink	I-99	1.250	0.991
CLND-700-38-118	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	3/8	0.406	1.125	2.125	2.687	5.681	1.816	0.414	Pink	I-99	1.250	0.991
CLND-700-12-112	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.500	2.625	2.687	6.181	1.816	0.546	Pink	I-99	1.250	0.991
CLND-700-12-134	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.750	3.000	2.687	6.556	1.816	0.546	Pink	I-99	1.250	0.991
CLND-700-12-178	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.875	3.000	2.687	6.556	1.816	0.546	Pink	I-99	1.250	0.991
CLND-750-38-1	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	3/8	0.406	1.000	1.937	2.875	5.714	1.901	0.414	Black	I-106	1.313	1.031
CLND-750-38-118	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	3/8	0.406	1.125	2.125	2.875	5.902	1.901	0.414	Black	I-106	1.313	1.031
CLND-750-12-112	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	1/2	0.562	1.500	2.625	2.875	6.402	1.901	0.546	Black	I-106	1.313	1.031
CLND-750-12-134	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	1/2	0.562	1.750	3.000	2.875	6.777	1.901	0.546	Black	I-106	1.313	1.031
CLND-750-58-112	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	5/8	0.656	1.500	3.000	2.875	6.777	1.901	0.671	Black	I-106	1.313	1.031
CLND-1000-38-1	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	3/8	0.406	1.000	1.937	3.000	5.962	2.169	0.414	White	I-125	1.500	1.172
CLND-1000-12-114	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	1/2	0.562	1.250	2.500	3.000	6.525	2.169	0.546	White	I-125	1.500	1.172
CLND-1000-12-134	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	1/2	0.562	1.750	3.000	3.000	7.025	2.169	0.546	White	I-125	1.500	1.172
CLND-1000-58-112	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	5/8	0.656	1.500	3.000	3.000	7.025	2.169	0.671	White	I-125	1.500	1.172

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs change the 4th letter to a B and add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207


TYPE CLNF

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLNF-2/0-12-134	2/0 AWG	1/0 FLEX	2/0-4 AWG	1/2	0.531	1.750	3.000	1.938	5.219	0.813	0.546	Black	I-45	0.562	0.437
CLNF-2/0-38	2/0 AWG	1/0 FLEX	2/0-4 AWG	3/8	0.406	-	0.875	1.938	3.094	0.813	0.414	Black	I-45	0.562	0.437
CLNF-3/0-12-134	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/2	0.531	1.750	3.000	1.938	5.250	0.906	0.546	Orange	I-50	0.609	0.484
CLNF-3/0-12	3/0 AWG	2/0 FLEX	3/0-2 AWG	1/2	0.531	-	1.000	1.938	3.250	0.906	0.546	Orange	I-50	0.609	0.484
CLNF-4/0-12-134	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.531	1.750	3.000	2.125	5.469	1.000	0.546	Purple	I-54	0.687	0.546
CLNF-4/0-12	4/0 AWG	3/0 FLEX	4/0-1 AWG	1/2	0.531	-	1.000	2.125	3.469	1.000	0.546	Purple	I-54	0.687	0.546
CLNF-250-12-134	250kcmil	4/0 FLEX	250kcmil-1/0 AWG	1/2	0.531	1.750	3.000	2.125	5.563	1.090	0.546	Yellow	I-62	0.750	0.593
CLNF-250-12	250kcmil	4/0 FLEX	250kcmil-1/0 AWG	1/2	0.531	-	1.125	2.125	3.688	1.090	0.546	Yellow	I-62	0.750	0.593
CLNF-300-12-134	300kcmil	250 G, H FLEX	300kcmil-2/0 AWG	1/2	0.531	1.750	3.000	2.250	5.937	1.188	0.546	White	I-66	0.812	0.660
CLNF-300-58	300kcmil	250 G, H FLEX	300kcmil-2/0 AWG	5/8	0.656	-	1.125	2.250	3.875	1.188	0.671	White	I-66	0.812	0.660
CLNF-350-12-134	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil-3/0 AWG	1/2	0.531	1.750	3.000	2.563	6.000	1.280	0.546	Red	I-71	0.890	0.703
CLNF-350-58	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil-3/0 AWG	5/8	0.656	-	1.125	2.563	4.125	1.280	0.671	Red	I-71	0.890	0.703
CLNF-400-12-134	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil-4/0 AWG	1/2	0.531	1.750	3.000	2.688	6.313	1.375	0.546	Blue	I-76	0.937	0.750
CLNF-400-58	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil-4/0 AWG	5/8	0.656	-	1.500	2.688	4.813	1.375	0.671	Blue	I-76	0.937	0.750
CLNF-500-12-134	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil-250kcmil	1/2	0.531	1.750	3.000	2.813	6.313	1.531	0.546	Brown	I-87	1.062	0.828
CLNF-500-58	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil-250kcmil	5/8	0.656	-	1.500	2.813	4.813	1.531	0.671	Brown	I-87	1.062	0.828

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

UL File E6207

A


TYPE CLNF

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLNF-600-12-134	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil-250kcmil	1/2	0.531	1.750	3.000	2.875	6.813	1.680	0.546	Green	I-94	1.187	0.920
CLNF-600-58	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil-250kcmil	5/8	0.656	-	1.500	2.875	5.375	1.680	0.671	Green	I-94	1.187	0.920
CLNF-700-12-134	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil-350kcmil	1/2	0.531	1.750	3.000	2.813	6.625	1.844	0.546	Pink	I-99	1.250	0.991
CLNF-700-58	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil-350kcmil	5/8	0.656	-	1.750	2.563	5.375	1.844	0.671	Pink	I-99	1.250	0.991
CLNF-750-12-134	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil-500kcmil	1/2	0.531	1.750	3.000	2.813	6.625	1.906	0.546	Black	I-106	1.313	1.031
CLNF-750-58	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil-500kcmil	5/8	0.656	-	1.938	2.813	5.563	1.906	0.671	Black	I-106	1.313	1.031
CLNF-1000-12-134	1000kcmil	750 G,H, I FLEX 777.7 DLO	1000kcmil-750kcmil	1/2	0.531	1.750	3.000	3.563	7.438	2.188	0.546	White	I-125	1.500	1.172
CLNF-1000-58	1000kcmil	750 G,H, I FLEX 777.7 DLO	1000kcmil-750kcmil	5/8	0.656	-	2.125	3.563	6.563	2.188	0.671	White	I-125	1.500	1.172
CLNF-1111-12-134	1111kcmil	-	-	1/2	0.562	1.750	3.000	3.313	7.438	2.600	0.546	White	IDT-12	1.750	1.458
CLNF-1111-58	1111kcmil	-	-	5/8	0.656	-	2.250	3.563	6.688	2.600	0.671	White	IDT-12	1.750	1.458

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

UL File E6207

TYPE CLNU


Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications

A



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Dimensions			Die Color Code	Die Index	O.D.	I.D.
				A	B	D				
CLNU-6	6 AWG	#6 FLEX	-	3.000	1.130	0.760	Blue	I-24	0.320	0.225
CLNU-4	4 AWG	-	4-6 AWG	3.000	1.130	0.760	White	I-29	0.343	0.250
CLNU-3	3 AWG	#4 FLEX	3-6 AWG	3.000	1.130	0.750	White	I-29	0.375	0.275
CLNU-2	2 AWG	-	2-6 AWG	3.000	1.130	0.740	Brown	I-33	0.421	0.312
CLNU-1	1 AWG	#2 FLEX	1-6 AWG	3.000	1.380	0.740	Green	I-37	0.468	0.359
CLNU-1/0	1/0 AWG	#1 FLEX	1/0-6 AWG	3.000	1.500	0.740	Pink	I-42	0.515	0.390
CLNU-2/0	2/0 AWG	1/0 FLEX	2/0-4 AWG	3.000	1.500	0.810	Black	I-45	0.562	0.437
CLNU-3/0	3/0 AWG	2/0 FLEX	3/0-2 AWG	3.000	1.500	0.890	Orange	I-50	0.609	0.484
CLNU-4/0	4/0 AWG	3/0 FLEX	4/0-1 AWG	3.000	1.500	1.000	Purple	I-54	0.687	0.546
CLNU-250	250kcmil	4/0 FLEX	250kcmil-1/0 AWG	3.000	1.690	1.090	Yellow	I-62	0.750	0.593
CLNU-300	300kcmil	250 G,H FLEX	300kcmil-2/0 AWG	3.000	2.000	1.190	White	I-66	0.812	0.660
CLNU-350	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil-3/0 AWG	3.000	2.000	1.290	Red	I-71	0.890	0.703
CLNU-400	400kcmil	300 G,H,I,K,M FLEX 313.1 DLO	400kcmil-4/0 AWG	3.000	2.130	1.370	Blue	I-76	0.937	0.750
CLNU-500	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil-250kcmil	3.000	2.250	1.530	Brown	I-87	1.062	0.828
CLNU-600	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil-250kcmil	3.000	2.690	1.710	Green	I-94	1.187	0.920
CLNU-650	650kcmil	500 G,H,I,K,M FLEX 535.3 DLO	650kcmil-350kcmil	3.000	2.690	1.760	Pink	I-99	1.217	0.958
CLNU-700	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil-350kcmil	3.000	2.690	1.820	Pink	I-99	1.250	0.991
CLNU-750	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil-500kcmil	3.000	2.880	1.900	Black	I-106	1.313	1.031
CLNU-1000	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil-750kcmil	3.000	3.000	2.170	White	I-125	1.500	1.172

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

For Bent Tangs add "-4" for 45 deg. or "-9" for 90 deg.

UL File E6207

A


TYPE CSWN

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Narrow tang width
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For limited space applications
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CSWN-2-14	#2 AWG	-	2-6 AWG	1/4	0.281	-	0.875	0.625	1.786	0.406	0.320	Brown	I-33	0.421	0.312
CSWN-2-14-58	#2 AWG	-	2-6 AWG	1/4	0.281	0.625	1.437	0.625	2.348	0.406	0.320	Brown	I-33	0.421	0.312
CSWN-1-14	#1 AWG	#2 FLEX	1-6 AWG	1/4	0.281	-	0.875	0.625	1.830	0.453	0.320	Green	I-37	0.468	0.359
CSWN-1/0-516	1/0 AWG	#1 FLEX	1/0-6 AWG	5/16	0.343	-	0.875	0.750	1.981	0.500	0.352	Pink	I-42	0.515	0.390
CSWN-2/0-516	2/0 AWG	1/0 FLEX	2/0-4 AWG	5/16	0.343	-	0.875	0.750	2.021	0.547	0.352	Black	I-45	0.562	0.437
CSWN-3/0-38	3/0 AWG	2/0 FLEX	3/0-2 AWG	3/8	0.406	-	0.875	0.750	2.064	0.594	0.414	Orange	I-50	0.609	0.484
CSWN-4/0-38	4/0 AWG	3/0 FLEX	4/0-1 AWG	3/8	0.406	-	0.875	0.875	2.241	0.672	0.414	Purple	I-54	0.687	0.546
CSWN-250-38-1	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	-	1.937	1.063	3.531	0.735	0.414	Yellow	I-62	0.750	0.593
CSWN-350-38	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	3/8	0.406	-	0.875	1.063	2.561	0.875	0.414	Red	I-71	1.250	0.991
CSWN-350-38-1	350kcmil	250 I,K,M FLEX 262.2 DLO	350kcmil - 3/0 AWG	3/8	0.406	1.000	1.937	1.063	3.623	0.875	0.414	Red	I-71	1.250	0.991
CSWN-500-38	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	3/8	0.406	-	0.875	1.300	2.907	1.047	0.414	Brown	I-87	1.250	0.991
CSWN-600-38	600kcmil	400 G,H,I,K,M FLEX 444.4 DLO	600kcmil - 250kcmil	3/8	0.406	-	0.875	1.375	3.059	1.172	0.414	Green	I-94	1.250	0.991
CSWN-750-38-1	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	3/8	0.406	1.000	1.937	1.500	4.339	1.298	0.414	Black	I-106	1.250	0.991
CSWN-1000-38-1	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	3/8	0.406	1.000	1.937	1.625	4.587	1.485	0.414	White	I-125	1.250	0.991
CSWN-1000-12-134	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	1/2	0.562	1.750	3.000	1.625	5.650	1.485	0.546	White	I-125	1.250	0.991

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

UL File E6207


TYPE CLWN

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Narrow tang width
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For limited space applications
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions					Die Color Code	Die Index	O.D.	I.D.
							A	B	C	D	G				
CLWN-250-38-1	250kcmil	4/0 FLEX	250kcmil - 1/0 AWG	3/8	0.406	-	1.937	1.688	4.156	0.735	0.414	Yellow	I-62	0.750	0.593
CLWN-500-38-1	500kcmil	350 G,H,I,K,M FLEX 373.7 DLO	500kcmil - 250kcmil	3/8	0.406	1.000	1.937	2.250	4.919	1.047	0.414	Brown	I-87	1.062	0.828
CLWN-700-38-1	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	3/8	0.406	1.000	1.937	2.687	5.493	1.235	0.414	Pink	I-99	1.250	0.991
CLWN-700-12-134	700kcmil	500 G,H,I,K,M FLEX 535.3 DLO	700kcmil - 350kcmil	1/2	0.562	1.750	3.000	2.687	6.556	1.235	0.546	Pink	I-99	1.250	0.991
CLWN-750-38-1	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	3/8	0.406	1.000	1.937	2.875	5.714	1.298	0.414	Black	I-106	1.313	1.031
CLWN-750-12-134	750kcmil	600 G,H,I,M FLEX 646.4 DLO	750kcmil - 500kcmil	1/2	0.562	1.750	3.000	2.875	6.777	1.298	0.546	Black	I-106	1.313	1.031
CLWN-1000-38-1	1000kcmil	750 G,H,I FLEX 777.7 DLO	1000kcmil - 750kcmil	3/8	0.406	1.000	1.937	3.000	5.962	1.485	0.414	White	I-125	1.500	1.172

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

+ See pages 79 to 84 for complete tooling information.

UL File E6207

A


TYPE CCL

Features

- Electro-tin plated
- Sight hole
- Solid seamless tang
- Electrolytic copper
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- For copper conductor only
- Rated to 90° C

Benefits

- Provides low contact resistance
- Visual inspection of proper cable insertion
- For performance and strength
- For high conductivity
- Application versatility



Catalog Number	Wire Size	Alt Wire Size	Bolt Size	Tang Length	Tang Width	Tang Thickness	Overall Length	Die Color Code	I.D.	O.D.
CCL-8-10	8 AWG	8 FLEX	#8-#10	0.579	0.445	0.071	1.201	RED	0.185	0.256
CCL-8-14	8 AWG	8 FLEX	1/4	0.579	0.445	0.071	1.201	RED	0.185	0.256
CCL-8-516	8 AWG	8 FLEX	5/16	0.724	0.598	0.059	1.276	RED	0.185	0.256
CCL-8-38	8 AWG	8 FLEX	3/8	0.724	0.598	0.059	1.276	RED	0.185	0.256
CCL-8-12	8 AWG	8 FLEX	1/2	0.858	0.752	0.059	1.480	RED	0.185	0.256

Tooling Information

Catalog Number	Standard Stranded Conductor				Color Code
	ILSCO		Burndy	Thomas & Betts	
	MT-25 Hand Dieless No. of Crimps	ILC-10-N Die No. No. of Crimps	MY29-3 Hand Dieless No. of Crimps	TBM8	
CCL-8	(1)	(3)	(1)	(1)	Red

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL File E6207


TYPE CCL

Features

- Electro-tin plated
- Sight hole
- Solid seamless tang
- Electrolytic copper
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- For copper conductor only
- Rated to 90° C

Benefits

- Provides low contact resistance
- Visual inspection of proper cable insertion
- For performance and strength
- For high conductivity
- Application versatility



Catalog Number	Wire Size	Alt Wire Size	Bolt Size	Tang Length	Tang Width	Tang Thickness	Overall Length	Die Color Code	I.D.	O.D.
CCL-6-10	6 AWG	6 FLEX	#10	0.579	0.445	0.075	1.268	BLUE	0.232	0.299
CCL-6-14	6 AWG	6 FLEX	1/4	0.579	0.445	0.075	1.268	BLUE	0.232	0.299
CCL-6-516	6 AWG	6 FLEX	5/16	0.724	0.598	0.067	1.409	BLUE	0.232	0.299
CCL-6-38	6 AWG	6 FLEX	3/8	0.724	0.598	0.067	1.409	BLUE	0.232	0.299
CCL-6-12	6 AWG	6 FLEX	1/2	0.858	0.752	0.059	1.551	BLUE	0.232	0.299

Tooling Information

Catalog Number	Standard Stranded Conductor				Color Code
	ILSCO		Burndy	Thomas & Betts	
	MT-25 Hand Dieless No. of Crimps	ILC-10-N Die No. No. of Crimps	MY29-3 Hand Dieless No. of Crimps	TBM8	
CCL-6	(1)	(2)	(1)	(1)	Blue

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207

A


TYPE CCL

Features

- Electro-tin plated
- Sight hole
- Solid seamless tang
- Electrolytic copper
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- For copper conductor only
- Rated to 90° C

Benefits

- Provides low contact resistance
- Visual inspection of proper cable insertion
- For performance and strength
- For high conductivity
- Application versatility



Catalog Number	Wire Size	Alt Wire Size	Bolt Size	Tang Length	Tang Width	Tang Thickness	Overall Length	Die Color Code	I.D.	O.D.
CCL-4-10	4 AWG	4 FLEX	#10	0.681	0.516	0.075	1.496	GRAY	0.283	0.362
CCL-4-14	4 AWG	4 FLEX	1/4	0.681	0.516	0.075	1.496	GRAY	0.283	0.362
CCL-4-516	4 AWG	4 FLEX	5/16	0.728	0.626	0.075	1.496	GRAY	0.283	0.362
CCL-4-38	4 AWG	4 FLEX	3/8	0.728	0.626	0.075	1.496	GRAY	0.283	0.362
CCL-4-12	4 AWG	4 FLEX	1/2	0.858	0.752	0.091	1.681	GRAY	0.283	0.362

Tooling Information

Catalog Number	Standard Stranded Conductor				Color Code
	ILSCO		Burndy	Thomas & Betts	
	MT-25 Hand Dieless No. of Crimps	ILC-10-N Die No. No. of Crimps	MY29-3 Hand Dieless No. of Crimps	TBM8	
CCL-4	(1)	(2)	(1)	(2)	Grey

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207


TYPE CCL

Features

- Electro-tin plated
- Sight hole
- Solid seamless tang
- Electrolytic copper
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- For copper conductor only
- Rated to 90° C

Benefits

- Provides low contact resistance
- Visual inspection of proper cable insertion
- For performance and strength
- For high conductivity
- Application versatility



Catalog Number	Wire Size	Alt Wire Size	Bolt Size	Tang Length	Tang Width	Tang Thickness	Overall Length	Die Color Code	I.D.	O.D.
CCL-2-14	2 AWG	3 FLEX	1/4	0.728	0.598	0.094	1.606	BROWN	0.335	0.429
CCL-2-516	2 AWG	3 FLEX	5/16	0.728	0.598	0.094	1.606	BROWN	0.335	0.429
CCL-2-38	2 AWG	3 FLEX	3/8	0.728	0.598	0.094	1.606	BROWN	0.335	0.429
CCL-2-12	2 AWG	3 FLEX	1/2	0.858	0.752	0.102	1.752	BROWN	0.335	0.429
CCL-1-14	1 AWG	2 FLEX	1/4	0.858	0.650	0.098	1.720	GREEN	0.362	0.461
CCL-1-516	1 AWG	2 FLEX	5/16	0.858	0.650	0.098	1.720	GREEN	0.362	0.461
CCL-1-38	1 AWG	2 FLEX	3/8	0.858	0.650	0.098	1.720	GREEN	0.362	0.461
CCL-1-12	1 AWG	2 FLEX	1/2	0.858	0.752	0.102	1.831	GREEN	0.362	0.461

Tooling Information

Catalog Number	Standard Stranded Conductor				Color Code
	ILSCO		Burndy	Thomas & Betts	
	MT-25 Hand Dieless No. of Crimps	ILC-10-N Die No. No. of Crimps	MY29-3 Hand Dieless No. of Crimps	TBM8	
CCL-2	(1)	(2)	(2)	(2)	Brown
CCL-1	(1)	(2)	(2)	(2)	Green

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207

A


TYPE CCL

Features

- Electro-tin plated
- Sight hole
- Solid seamless tang
- Electrolytic copper
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- For copper conductor only
- Rated to 90° C

Benefits

- Provides low contact resistance
- Visual inspection of proper cable insertion
- For performance and strength
- For high conductivity
- Application versatility



Catalog Number	Wire Size	Alt Wire Size	Bolt Size	Tang Length	Tang Width	Tang Thickness	Overall Length	Die Color Code	I.D.	O.D.
CCL-1/0-14	1/0 AWG	1 FLEX	1/4	0.791	0.713	0.110	1.831	PINK	0.406	0.516
CCL-1/0-516	1/0 AWG	1 FLEX	5/16	0.791	0.713	0.110	1.831	PINK	0.406	0.516
CCL-1/0-38	1/0 AWG	1 FLEX	3/8	0.791	0.713	0.110	1.831	PINK	0.406	0.516
CCL-1/0-12	1/0 AWG	1 FLEX	1/2	0.890	0.815	0.110	1.902	PINK	0.406	0.516
CCL-2/0-14	2/0 AWG	1/0 FLEX	1/4	0.929	0.815	0.110	2.055	BLACK	0.461	0.571
CCL-2/0-516	2/0 AWG	1/0 FLEX	5/16	0.929	0.815	0.110	2.055	BLACK	0.461	0.571
CCL-2/0-38	2/0 AWG	1/0 FLEX	3/8	0.929	0.815	0.110	2.055	BLACK	0.461	0.571
CCL-2/0-12	2/0 AWG	1/0 FLEX	1/2	0.929	0.815	0.110	2.055	BLACK	0.461	0.571

Tooling Information

Catalog Number	Standard Stranded Conductor			Color Code
	ILSCO		Thomas & Betts	
	MT-25 Hand Dieless No. of Crimps	ILC-10-N Die No. No. of Crimps	MY29-3 Hand Dieless No. of Crimps	
CCL-1/0	(1)	(2)	(2)	Pink
CCL-2/0	(1)	-	(2)	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207


TYPE CCL

Features

- Electro-tin plated
- Sight hole
- Solid seamless tang
- Electrolytic copper
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- For copper conductor only
- Rated to 90° C

Benefits

- Provides low contact resistance
- Visual inspection of proper cable insertion
- For performance and strength
- For high conductivity
- Application versatility



Catalog Number	Wire Size	Alt Wire Size	Bolt Size	Tang Length	Tang Width	Tang Thickness	Overall Length	Die Color Code	I.D.	O.D.
CCL-3/0-14	3/0 AWG	2/0 FLEX	1/4	0.969	0.894	0.118	2.161	ORANGE	0.512	0.630
CCL-3/0-516	3/0 AWG	2/0 FLEX	5/16	0.969	0.894	0.118	2.161	ORANGE	0.512	0.630
CCL-3/0-38	3/0 AWG	2/0 FLEX	3/8	0.969	0.894	0.118	2.161	ORANGE	0.512	0.630
CCL-3/0-12	3/0 AWG	2/0 FLEX	1/2	0.969	0.894	0.118	2.161	ORANGE	0.512	0.630
CCL-4/0-14	4/0 AWG	3/0 FLEX	1/4	1.071	1.035	0.130	2.382	PURPLE	0.591	0.720
CCL-4/0-516	4/0 AWG	3/0 FLEX	5/16	1.071	1.035	0.130	2.382	PURPLE	0.591	0.720
CCL-4/0-38	4/0 AWG	3/0 FLEX	3/8	1.071	1.035	0.130	2.382	PURPLE	0.591	0.720
CCL-4/0-12	4/0 AWG	3/0 FLEX	1/2	1.071	1.035	0.130	2.382	PURPLE	0.591	0.720

Tooling Information

Catalog Number	Standard Stranded Conductor				Color Code
	ILSCO		Burndy	Thomas & Betts	
	MT-25 Hand Dieless No. of Crimps	ILC-10-N Die No. No. of Crimps	MY29-3 Hand Dieless No. of Crimps	TBM8	
CCL-3/0	(1)	-	(2)	(2)	
CCL-4/0	(2)	-	(2)	(2)	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207

A


TYPE CRAM

Features

- Electro-tin plated
- Sight hole
- Solid seamless tang
- Electrolytic copper
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Visual inspection of proper cable insertion
- For performance and strength
- For high conductivity
- Application versatility



Catalog Number	Alt Wire Size	Wire Size	Bolt Size	Tang Length	Tang Width	Tang Thickness	Overall Length	Die Color Code	I.D.	O.D.
CRA-8-8/10M	8 FLEX	8 AWG	#8-#10	0.579	0.445	0.071	1.201	RED	0.185	0.256
CRA-8-14M	8 FLEX	8 AWG	1/4	0.579	0.445	0.071	1.201	RED	0.185	0.256
CRA-8-516M	8 FLEX	8 AWG	5/16	0.724	0.598	0.059	1.276	RED	0.185	0.256
CRA-8-38M	8 FLEX	8 AWG	3/8	0.724	0.598	0.059	1.276	RED	0.185	0.256
CRA-8-12M	8 FLEX	8 AWG	1/2	0.858	0.752	0.059	1.480	RED	0.185	0.256
CRA-6-10M	6 FLEX	6 AWG	#10	0.579	0.445	0.075	1.268	BLUE	0.232	0.299
CRA-6-14M	6 FLEX	6 AWG	1/4	0.579	0.445	0.075	1.268	BLUE	0.232	0.299
CRA-6-516-M	6 FLEX	6 AWG	5/16	0.724	0.598	0.067	1.409	BLUE	0.232	0.299
CRA-6-38M	6 FLEX	6 AWG	3/8	0.724	0.598	0.067	1.409	BLUE	0.232	0.299
CRA-6-12M	6 FLEX	6 AWG	1/2	0.858	0.752	0.059	1.551	BLUE	0.232	0.299
CRA-4-10M	4 FLEX	4 AWG	#10	0.681	0.516	0.075	1.496	GRAY	0.283	0.362
CRA-4-14M	4 FLEX	4 AWG	1/4	0.681	0.516	0.075	1.496	GRAY	0.283	0.362
CRA-4-516M	4 FLEX	4 AWG	5/16	0.728	0.626	0.075	1.496	GRAY	0.283	0.362
CRA-4-38M	4 FLEX	4 AWG	3/8	0.728	0.626	0.075	1.496	GRAY	0.283	0.362
CRA-4-12M	4 FLEX	4 AWG	1/2	0.858	0.752	0.091	1.681	GRAY	0.283	0.362
CRA-2-14M	2 FLEX	1 AWG	1/4	0.858	0.650	0.098	1.720	GREEN	0.362	0.461
CRA-2-516M	2 FLEX	1 AWG	5/16	0.858	0.650	0.098	1.720	GREEN	0.362	0.461
CRA-2-38M	2 FLEX	1 AWG	3/8	0.858	0.650	0.098	1.720	GREEN	0.362	0.461
CRA-2-12M	2 FLEX	1 AWG	1/2	0.858	0.752	0.102	1.831	GREEN	0.362	0.461

Tooling Information

Flex Size	AWG Size	ILSCO	Burndy
		MT-25 Hand Dieless (A) No. of Crimps	MY29-3 Hand Dieless (A) No. of Crimps
8	8	(1)	(1)
6	6	(1)	(1)
4	4	(1)	(1)
2	1	(1)	(2)

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207


TYPE CRAM

Features

- Electro-tin plated
- Sight hole
- Solid seamless tang
- Electrolytic copper
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Visual inspection of proper cable insertion
- For performance and strength
- For high conductivity
- Application versatility



Catalog Number	Alt Wire Size	Wire Size	Bolt Size	Tang Length	Tang Width	Tang Thickness	Overall Length	Die Color Code	I.D.	O.D.
CRA-1-14M	1 FLEX	1/0 AWG	1/4	0.791	0.713	0.110	1.831	PINK	0.406	0.516
CRA-1-516M	1 FLEX	1/0 AWG	5/16	0.791	0.713	0.110	1.831	PINK	0.406	0.516
CRA-1-38M	1 FLEX	1/0 AWG	3/8	0.791	0.713	0.110	1.831	PINK	0.406	0.516
CRA-1-12M	1 FLEX	1/0 AWG	1/2	0.890	0.815	0.110	1.902	PINK	0.406	0.516
CRA-1/0-14M	1/0 FLEX	2/0 AWG	1/4	0.929	0.815	0.110	2.055	BLACK	0.461	0.571
CRA-1/0-516M	1/0 FLEX	2/0 AWG	5/16	0.929	0.815	0.110	2.055	BLACK	0.461	0.571
CRA-1/0-38M	1/0 FLEX	2/0 AWG	3/8	0.929	0.815	0.110	2.055	BLACK	0.461	0.571
CRA-1/0-12M	1/0 FLEX	2/0 AWG	1/2	0.929	0.815	0.110	2.055	BLACK	0.461	0.571
CRA-2/0-14M	2/0 FLEX	3/0 AWG	1/4	0.969	0.894	0.118	2.161	ORANGE	0.512	0.630
CRA-2/0-516M	2/0 FLEX	3/0 AWG	5/16	0.969	0.894	0.118	2.161	ORANGE	0.512	0.630
CRA-2/0-38-M	2/0 FLEX	3/0 AWG	3/8	0.969	0.894	0.118	2.161	ORANGE	0.512	0.630
CRA-2/0-12M	2/0 FLEX	3/0 AWG	1/2	0.969	0.894	0.118	2.161	ORANGE	0.512	0.630
CRA-3/0-38M	3/0 FLEX	4/0 AWG	3/8	1.071	1.035	0.130	2.382	PURPLE	0.591	0.720
CRA-3/0-12M	3/0 FLEX	4/0 AWG	1/2	1.071	1.035	0.130	2.382	PURPLE	0.591	0.720
CRA-4/0-38M	4/0 FLEX	250 kcmil	3/8	1.228	1.201	0.130	2.614	YELLOW	0.685	0.815
CRA-4/0-12M	4/0 FLEX	250 kcmil	1/2	1.228	1.201	0.130	2.614	YELLOW	0.685	0.815

Tooling Information

Flex Size	AWG Size	ILSCO	Burdy
		MT-25 Hand Dieless (A) No. of Crimps	MY29-3 Hand Dieless (A) No. of Crimps
1	1/0	(1)	(2)
1/0	2/0	(1)	(2)
2/0	3/0	(1)	(2)
3/0	4/0	(2)	(2)
4/0	250 kcmil	(2)	(2)

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207

A

TYPE Solder Lugs

Features

- Manufactured from high strength copper tubing
- Seamless construction
- Clearly marked with wire size
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity
- Won't leak solder
- Provides easy identification
- Application versatility




Fig. 1



Fig. 2

Catalog Number	Old Description	Figure Number	Wire Size	Dimensions								Amp Rating
				B	Bolt Size	C	D	E	F	G	H	
3/16	25A	1	10	9/64	#8	11/64	11/32	15/32	15/16	3/16	1/4	25 Amp
1/4	35A	1	8	3/16	#10	13/64	11/32	1/2	1-1/32	7/32	3/8	35 Amp
5/16	50A	1	6	15/64	#10	13/64	13/32	19/32	1-7/32	1/4	7/16	50 Amp
3/8	70A	1	4	9/32	1/4	9/32	7/16	11/16	1-3/8	9/32	17/32	70 Amp
7/16	90A	1	2	11/32	1/4	9/32	1/2	3/4	1-1/2	11/32	5/8	90 Amp
1/2	125A	1	1/0	25/64	5/16	11/32	9/16	13/16	1-3/4	13/32	3/4	125 Amp
9/16	150A	1	2/0	15/32	3/8	13/32	11/16	15/16	2	7/16	13/16	150 Amp
5/8	175A	1	3/0	33/64	3/8	13/32	25/32	1	2-1/8	1/2	29/32	175 Amp
11/16	225A	1	4/0	9/16	3/8	13/32	27/32	1-5/32	2-3/8	17/32	31/32	225 Amp
13/16	250A	1	250kcmil	43/64	3/8	13/32	31/32	1-1/4	2-21/32	5/8	1-3/16	250 Amp
1-1/8	450A	2	600kcmil	61/64	3/8	13/32	1-1/2	2-1/4	4-7/16	1	1-5/8	450 Amp
1-5/16	550A	2	800kcmil	1-3/32	1/2	17/32	1-13/16	2-1/2	5-1/16	1-1/8	1-15/16	550 Amp
1-7/16	650A	2	1000kcmil	1-7/32	7/8	29/32	2	2-1/2	5-3/8	1-3/16	2-1/8	650 Amp
1-3/4	850A	2	1500kcmil	1-15/32	1	1-1/32	2-3/8	3-1/8	6-5/8	1-7/16	2-5/8	850 Amp

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 Tested to UL 486A/B, UL File E6207


TYPE CT

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Barrel Length	Die Color Code	Die Index	Die Catalog Number	O.D.	I.D.
CT-8	8 AWG	#8 Flex	-	1.125	Red	I-21	ILD-21	0.272	0.179
CT-6	6 AWG	#6 Flex	-	1.750	Blue	I-24	ILD-24	0.320	0.225
CT-4	4 AWG	-	4-6 AWG	1.875	Gray	I-29	ILD-29	0.343	0.250
CT-3	3 AWG	#4 Flex	3-6 AWG	1.750	White	I-29	ILD-29	0.375	0.275
CT-2	2 AWG	-	2-6 AWG	1.875	Brown	I-33	ILD-33	0.421	0.312
CT-1	1 AWG	#2 Flex	1-6 AWG	1.875	Green	I-37	ILD-37	0.468	0.359
CT-1/0	1/0 AWG	#1 Flex	1/0-6 AWG	1.875	Pink	I-42	ILD-42	0.515	0.390
CT-2/0	2/0 AWG	1/0 Flex	2/0-4 AWG	2.000	Black	I-45	ILD-45	0.562	0.437
CT-3/0	3/0 AWG	2/0 Flex	3/0-2 AWG	2.125	Orange	I-50	ILD-50	0.609	0.484
CT-4/0	4/0 AWG	3/0 Flex	4/0-1 AWG	2.125	Purple	I-54	ILD-54	0.687	0.546
CT-250	250kcmil	4/0 Flex	250kcmil-1/0 AWG	2.250	Yellow	I-62	ILD-62	0.750	0.593
CT-300	300kcmil	250 G,H Flex	300kcmil-2/0 AWG	2.250	White	I-66	ILD-66	0.812	0.660
CT-350	350kcmil	250 I,K,M Flex 262.2 DLO	350kcmil-3/0 AWG	2.375	Red	I-71	ILD-71	0.890	0.703
CT-400	400kcmil	300 G,H,I,K,M Flex 313.1 DLO	400kcmil-4/0 AWG	2.500	Blue	I-76	ILD-76	0.937	0.750
CT-500	500kcmil	350 G,H,I,K,M Flex 373.7 DLO	500kcmil-250kcmil	2.875	Brown	I-87	ILD-87	1.062	0.828
CT-600	600kcmil	400 G,H,I,K,M Flex 444.4 DLO	600kcmil-250kcmil	2.875	Green	I-94	ILD-94	1.187	0.920
CT-650	650kcmil	500 G,H,I,K,M Flex 535.3 DLO	650kcmil-350kcmil	2.875	Pink	I-99	ILD-99	1.222	0.962
CT-700	700kcmil	500 G,H,I,K,M Flex 535.3 DLO	700kcmil-350kcmil	3.375	Pink	I-99	ILD-99	1.250	0.991
CT-750	750kcmil	600 G,H,I,M Flex 646.4 DLO	750kcmil-500kcmil	3.375	Black	I-106	ILD-106	1.313	1.031
CT-1000	1000kcmil	750 G,H,I Flex 777.7 DLO	1000kcmil-750kcmil	3.875	White	I-125	ILD-125	1.500	1.172

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

See pages 79 to 84 for complete tooling information.

UL File E6207

A


TYPE CTL

Features

- Manufactured from high strength seamless copper tubing
- Electro-Tin plated
- Chamfered entry
- Color coded
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- UL Listed and CSA Certified with ILSCO and major competitor's compression tools
- UL467 Listed 1/0 AWG - 8 AWG
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- Application versatility
- Reduces inventory requirements
- For grounding and bonding applications



Catalog Number	Wire Size	Alt Wire Size	Expanded* Wire Range	Barrel Length	Die Color Code	Die Index	Die Catalog Number	O.D.	I.D.
CTL-8	8 AWG	#8 Flex	-	1.75	Red	I-21	ILD-21	0.272	0.179
CTL-6	6 AWG	#6 Flex	-	2.375	Blue	I-24	ILD-24	0.320	0.225
CTL-4	4 AWG	-	4-6 AWG	2.375	Gray	I-29	ILD-29	0.343	0.250
CTL-3	3 AWG	#4 Flex	3-6 AWG	2.375	White	I-29	ILD-29	0.375	0.275
CTL-2	2 AWG	-	2-6 AWG	2.625	Brown	I-33	ILD-33	0.421	0.312
CTL-1	1 AWG	#2 Flex	1-6 AWG	2.875	Green	I-37	ILD-37	0.468	0.359
CTL-1/0	1/0 AWG	#1 Flex	1/0-6 AWG	2.875	Pink	I-42	ILD-42	0.515	0.390
CTL-2/0	2/0 AWG	1/0 Flex	2/0-4 AWG	3.125	Black	I-45	ILD-45	0.562	0.437
CTL-3/0	3/0 AWG	2/0 Flex	3/0-2 AWG	3.125	Orange	I-50	ILD-50	0.609	0.484
CTL-4/0	4/0 AWG	3/0 Flex	4/0-1 AWG	3.375	Purple	I-54	ILD-54	0.687	0.546
CTL-250	250kcmil	4/0 Flex	250kcmil-1/0 AWG	3.375	Yellow	I-62	ILD-62	0.750	0.593
CTL-300	300kcmil	250 G,H Flex	300kcmil-2/0 AWG	4.125	White	I-66	ILD-66	0.812	0.660
CTL-350	350kcmil	250 I,K,M Flex 262.2 DLO	350kcmil-3/0 AWG	4.125	Red	I-71	ILD-71	0.890	0.703
CTL-400	400kcmil	300 G,H,I,K,M Flex 313.1 DLO	400kcmil-4/0 AWG	4.375	Blue	I-76	ILD-76	0.937	0.750
CTL-500	500kcmil	350 G,H,I,K,M Flex 373.7 DLO	500kcmil-250kcmil	4.625	Brown	I-87	ILD-87	1.062	0.828
CTL-600	600kcmil	400 G,H,I,K,M Flex 444.4 DLO	600kcmil-250kcmil	4.625	Green	I-94	ILD-94	1.187	0.920
CTL-650	650kcmil	500 G,H,I,K,M Flex 535.3 DLO	650kcmil-350kcmil	4.625	Pink	I-99	ILD-99	1.222	0.962
CTL-700	700kcmil	500 G,H,I,K,M Flex 535.3 DLO	700kcmil-350kcmil	5.875	Pink	I-99	ILD-99	1.250	0.991
CTL-750	750kcmil	600 G,H,I,K,M Flex 646.4 DLO	750kcmil-500kcmil	5.875	Black	I-106	ILD-106	1.313	1.031
CTL-1000	1000kcmil	750 G,H,I Flex 777.7 DLO	1000kcmil-750kcmil	6.125	White	I-125	ILD-125	1.500	1.172

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* When installed with specified dieless tools

See pages 79 to 84 for complete tooling information.

UL File E6207


TYPE CCS

Features

- Manufactured from high strength copper
- Electro-tin plated
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Color coded
- Sight hole
- Flared end
- Rated to 90° C

Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- Application versatility
- Provides visual tooling recommendation for IlSCO or standard industry tools
- Allows visual inspection
- Easy wire insertion



Catalog Number	Wire Size	Color Code	L	O.D.	I.D.
CCS-6	6	Blue	1-1/16	5/16	15/64
CCS-4	4	Grey	1-13/64	23/64	9/32
CCS-2	2	Brown	1-23/64	7/16	21/64
CCS-1	1	Green	1-23/64	15/32	23/64
CCS-1/0	1/0	Pink	1-35/64	33/64	13/32
CCS-2/0	2/0	Black	1-51/64	37/64	15/32
CCS-3/0	3/0	Orange	1-29/32	5/8	33/64
CCS-4/0	4/0	Purple	2	11/16	9/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587

A


TYPE GGA

Features

- Manufactured from high strength copper alloy
- Clearly marked with wire size and die index
- Range taking
- Connector can be adjusted prior to installation
- Non-hazardous installation
- Prefilled with inhibiting compound
- Temperature Rating 90° C

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion. Suitable for direct burial.
- Provides easy identification and tooling recommendation
- Reduces inventory. Six sizes cover a wire range from 500kcmil to #6, and 1/2" to 3/4" ground rods.
- Permits adjustments to be made for misaligned cross grids
- Can be installed in all types of weather with no need for protective equipment or clothing. Does not produce heat or dangerous particles.
- Prevents oxides from forming
- Ensures reliability



Catalog Number	Wire Range				Dimensions						Die Index Number	
	Cable to Cable		Cable to Ground Rod		A	B	C	D	E	F	Side A	Side B
	Side A	Side B	Side A	Side B								
GGA-1	2str-6sol	2str-6sol	-	-	.750	.750	1.090	1.090	.313	2.500	O	O
GGA-2	250kcmil-1str	2str-6sol	1/2 - 5/8 Rod	2str-6sol	.750	.750	1.660	1.090	.313	2.500	997	O
GGA-3	250kcmil-2str	250kcmil-2str	1/2 - 5/8 Rod	250kcmil-2str	.750	.750	1.660	1.660	.500	2.500	997	997
GGA-4	500kcmil-250kcmil	2str-6sol	1/2 - 5/8 Rod	2str-6sol	.750	.750	2.090	1.090	.313	2.500	998	O
GGA-5	500kcmil-250kcmil	250kcmil-2str	5/8 - 3/4 Rod	250kcmil-2str	.750	.750	2.090	1.660	.500	2.500	998	997
GGA-6	500kcmil-250kcmil	500kcmil-250kcmil	5/8 - 3/4 Rod	500kcmil-250kcmil	.750	.750	2.280	2.280	.750	2.500	999/1011	999/1011

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 467, UL File E34440

The GGA Series compression ground grid cross connector can be used to connect a copper ground grid system together or to connect a copper ground grid system to a copper clad ground rod. The GGA Series of compression connectors allow adjustment of each side of the connector prior to installation. The GGA Series of compression connectors are pre-filled with inhibiting compound and are suitable for direct burial.

Notes:

1. ILSCO ILC-12 or ILC-15 Series Tools and ILD Series Dies may be used. Note: Adapter required when using ILC-15 Series Tool. Burndy tools and dies may also be used.
2. When used with ground rods, it is recommended to rough up the end of ground rod where GGA is to be placed. This provides good rotational resistance. Perform a "pre-crimp" on ground rod prior to installing GGA connector. Use an indent type of die such as Burndy's U2CABT (Die Index #348) or UPRECRIMP-12, -58, -34.*
3. Each side of the GGA Series may be rotated around the rod to any desired position before crimping.

* "UPRECRIMP" and "U2CABT" are registered trademarks TM of Burndy/FCI


TYPE GGC

Features

- Manufactured from high strength copper alloy
- Clearly marked with wire size and die index
- Range taking
- Versatile
- Non-hazardous installation
- Prefilled with inhibiting compound
- Temperature Rating 90° C

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion. Suitable for direct burial.
- Provides easy identification and tooling recommendation
- Reduces inventory. Eight sizes cover a wire range from 500kcmil to #6, and 1/2" to 3/4" ground rods.
- Can be used as a tap connector or as a lap splice connector
- Can be installed in all types of weather with no need for protective equipment or clothing. Does not produce heat or dangerous particles.
- Prevents oxides from forming
- Ensures reliability



Catalog Number	Wire Range		Main Ground Rod	Dimensions			Die Index Index
	Main	Tap		A	B	C	
GGC-1	2str-6sol	2str-6sol	-	1.400	.750	.330	0
GGC-2	250kcmil-1/0str 1/2 - 5/8 Rod	2str-4sol	1/2 - 5/8	2.100	.750	.330	997
GGC-3	250kcmil-1/0str 1/2 - 5/8 Rod	2/0str-1/0str	1/2 - 5/8	2.100	.750	.440	997
GGC-4	250kcmil-1/0str 1/2 - 5/8 Rod	250kcmil-3/0str	1/2 - 5/8	2.100	.750	.610	997
GGC-5	500kcmil-250kcmil 5/8 - 3/4 Rod	2str-4sol	5/8 - 3/4	2.600	.750	.330	998
GGC-6	500kcmil-250kcmil 5/8 - 3/4 Rod	2/0str-1/0str	5/8 - 3/4	2.600	.750	.440	998
GGC-7	500kcmil-250kcmil 5/8 - 3/4 Rod	250kcmil-3/0str	5/8 - 3/4	2.600	.750	.610	998
GGC-8	500kcmil-250kcmil 5/8 - 3/4 Rod	500kcmil-350kcmil	5/8 - 3/4	2.900	.750	.840	999/1011

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 467, UL File E34440

NOTE: Hydraulic tools required on all sizes except GGC-1
Dieless tools can not be used

The GGC Series compression ground tap connector can be used as a tap connector to connect copper ground wire to a copper clad ground rod or as a lap splice connector splicing copper conductors together. The GGC Series of compression connectors are pre-filled with inhibiting compound and are suitable for direct burial.

Notes:

1. ILSCO ILC-12 or ILC-15 Series Tools and ILD Series Dies may be used. Note: Adapter required when using ILC-15 Series Tool. Burndy tools and dies may also be used.
2. When used with ground rods, it is recommended to rough up the end of ground rod where GGC is to be placed. This provides good rotational resistance. Perform a "pre-crimp" on ground rod prior to installing GGC connector. Use an indent type of die such as Burndy's U2CABT (Die Index #348) or UPRECRIMP-12, -58, -34.*
3. When using #6 AWG solid wire in the tap side, fold conductor double prior to crimping.
4. When using GGC-4, if 3/0 conductor is used in the tap side, use a minimum of 2/0 conductor in the run side.

* "UPRECRIMP" and "U2CABT" are registered trademarks TM of Burndy/FCI

A


TYPE ULT

Features

- Manufactured from high strength copper alloy
- Clearly marked with wire size and die index
- Range taking
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion
- Provides easy identification and tooling recommendation
- Reduces inventory
- Application versatility



Catalog Number	Copper Wire Range		Die Index	Dimensions		
	Main	Tap		L	W	H
ULT-4-Z	4str-6sol	6str-6sol	BG or 5/8	3/4	15/32	49/64
ULT-5-Z	4str-6sol	4str-4sol	BG or 5/8	3/4	15/32	27/32
ULT-6-Z	2str-2sol	4str-8sol	C	7/8	5/8	1
ULT-7-Z	2str-2sol	2str-2sol	C	7/8	39/64	1-1/16
ULT-12-Z	4/0str-3/0str	4/0str-3/0str	F or D3	1-1/8	1	1-5/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

TYPE ELT

Features

- Manufactured from copper alloy
- Clearly marked with wire size and die index
- Range taking
- UL Listed and CSA Certified for grounding and bonding
- May be used in ground grid applications

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion. Suitable for direct burial
- Provides easy identification and tooling recommendation
- Reduces inventory
- Ensures reliability
- Flexibility in application



Catalog Number	Copper Wire Range		W	Die Index
	Main	Tap		
ELT-1	2str-6sol	2str-6sol	.750	C (U Type)
ELT-4	2/0str-1str	2str-6str	.750	0 (U Type)
ELT-2	2/0str-1str	2/0str-1str	.750	0 (U Type)
ELT-5	250kcmil-3/0str	2/0str-6sol	.750	997 (U Type)
ELT-3	250kcmil-3/0str	250kcmil-3/0str	.900	997 (U Type)
ELT-6	500kcmil-300kcmil	250kcmil-3/0str	.875	1011 (U Type)

Tooling Information

Catalog Number	ILSCO		Burndy		
	ILC-12H-N, ILCB-12-N, ILCB-12-LIO ILC-12-N Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	Y-35 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps
ELT-1	ILD-C (1)	-	C (U Type) (1)	C (U Type) (1)	C (U Type) (1)
ELT-4	ILD-O (1)	-	O (U Type) (1)	O (U Type) (1)	O (U Type) (1)
ELT-2	ILD-O (1)	-	O (U Type) (1)	O (U Type) (1)	O (U Type) (1)
ELT-5	ILD-U997 (1)	-	997 (U Type) (1)	997 (U Type) (1)	997 (U Type) (1)
ELT-3	ILD-U997 (1)	-	997 (U Type) (1)	997 (U Type) (1)	997 (U Type) (1)
ELT-6	ILD-U1011 (1)	ILD-P1011 (2)	-	1011 (U Type) (2)	1011 (U Type) (1)

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 467, UL File E34440

A


TYPE ALNN

Features

- Manufactured from high strength aluminum alloy
- Electro-Tin plated
- Chamfered entry
- Color coded end cap
- Roll marked
- Two bolt hole pattern
- Pre-filled with DE-OX
- Range taking
- Narrow Tang
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- For easy identification and proper location of crimps
- Provides maximum surface contact, secure attachment, and stabilization
- Prevents oxides from forming
- Permits inventories to be kept to a minimum
- Side by side mounting
- Application versatility



Catalog Number	Wire Size	Expanded* Wire Range	Bolt Size	Stud Hole Spacing	Stud Hole Dia.	Dimensions					Die Color Code	Die Index	O.D.	I.D.
						A	B	C	D	G				
ALNN-1000-12-134	1000kcmil	1000kcmil-750kcmil	1/2	1.750	0.563	3.000	2.998	7.5000	1.670	0.546	Brown	P302	1.840	1.180

* When installed with IDT-12-N tool

UL File E6207

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tooling Information

Compression Terminals ASxx and ALxx	ILSCO			Burndy		
	Die Code	ILC-15H, ILC-15, 15 Ton ILC-30H, 30 Ton	IDT-12-N, 15 Ton Dieless	Die Code	PAT 46, Y46, Y46C	Y644M, PAT644, 15 Ton Dieless
1000	ILD-P302	3*	1*	P44ART	3*	1*

Range Taking

Compression Terminals ASxx and ALxx	Standard Wire Size	Expanded Wire Size	No. Crimps for ILSCO IDT-12-N and Burndy Y644M
1000	1000kcmil	1000kcmil - 750kcmil	1*

* For long barrel connectors, add 1 additional crimp


TYPE ACL

Features

- Electro-tin plated
- Manufactured from high strength aluminum alloy
- Chamfered barrel
- Color coded
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Provides visual tooling recommendation for ILSCO or standard industry tools
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Application versatility



Catalog Number	Wire Size	Wire Range When Installed With IDT-12-N Tool	Die Color Code	Bolt Size	Tang Width	Dimensions			Die Index	O.D.	I.D.
						C	E	F			
ACL-8	8	8	Blue	1/4	1/2	9/32	11/16	1-7/16	2	5/16	11/64
ACN-8	8	8	Blue	#10	1/2	13/64	11/16	1-7/16	2	5/16	11/64
ACL-6	6	6	Gray	1/4	1/2	9/32	11/16	1-43/64	3	11/32	3/16
ACL-4	4	4-6	Green	1/4	9/16	9/32	23/32	1-13/16	4	7/16	1/4
ACN-4	4	4-6	Green	5/16	9/16	11/32	23/32	1-13/16	4	7/16	1/4
ACL-2	2	2-6	Pink	1/4	11/16	9/32	23/32	1-7/8	7	17/32	5/16
ACN-2	2	2-6	Pink	5/16	11/16	11/32	23/32	1-7/8	7	17/32	5/16

Tooling Information

Catalog Number	ILSCO								Burdry						Thomas & Betts				Anderson	Color Code	
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LJO Die No. No. of Crimps	IDTB-6 IDTB-6-LJO Dieless No. of Crimps	IDT-6, IDT-6H 6.2 Ton Dieless No. of Crimps	ILC-15H Die No. No. of Crimps	MT-25 Hand No. of Crimps	94285 Left /Rt. Die/Die No. of Crimps	IDT-12-N Dieless No. of Crimps	Y-48B Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	MY29-3 Hand No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps	TBM-8 Hand Tool No. of Crimps		Versa Crimp Dieless No. of Crimps
ACL-8/ ACN-8	ILD-2 (1)	ILD-2 (1)	-	-	ILD-2 (1)	- (1)	M/K (2)	-	-	-	-	-	-	-	24 (1)	24 (2)	-	-	-	-	Blue
ACL-6	ILD-3 (1)	ILD-3 (1)	- (1)	- (1)	ILD-3 (1)	- (1)	K/K (2)	- (1)	346 (1)	346 (1)	346 (1)	346 (1)	- (1)	- (1)	29 (2)	29 (2)	29 (2)	- (2)	- (2)	-	Gray
ACL-4/ ACN-4	ILD-4 (2)	ILD-4 (2)	- (1)	- (1)	ILD-4 (2)	- (1)	H/H (3)	- (1)	375 (1)	375 (1)	375 (1)	375 (1)	- (1)	- (1)	37 (2)	37 (2)	37 (2)	- (2)	- (1)	-	Green
ACL-2/ ACN-2	ILD-7 (1) or ILD-6 (3)	ILD-7 (1) or ILD-6 (3)	- (2)	- (2)	ILD-7 (1) or ILD-6 (3)	- (2)	E/A (3)	- (1)	348 (1)	348 (1)	348 (1)	348 (1)	- (2)	- (1)	42 (2)	42H (4)	42 (2)	- (2)	- (1)	-	Pink

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207

A


TYPE ACL

Features

- Electro-tin plated
- Manufactured from high strength aluminum alloy
- Chamfered barrel
- Color coded
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Provides visual tooling recommendation for ILSCO or standard industry tools
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Application versatility



Catalog Number	Wire Size	Wire Range When Installed With IDT-12-N Tool	Die Color Code	Bolt Size	Tang Width	Dimensions			Die Index	O.D.	I.D.
						C	E	F			
ACL-1	1	1-2	Gold	1/4	3/4	9/32	29/32	2-25/64	7	35/64	23/64
ACN-1	1	1-2	Gold	5/16	3/4	11/32	29/32	2-25/64	7	35/64	23/64
ACL-1/0	1/0	1/0-1	Tan	3/8	7/8	13/32	15/16	2-9/16	8	39/64	25/64
ACN-1/0	1/0	1/0-1	Tan	5/16	7/8	11/32	15/16	2-9/16	8	39/64	25/64
ACL-2/0	2/0	2/0-1	Olive	3/8	31/32	13/32	1	2-5/8	10	43/64	7/16
ACN-2/0	2/0	2/0-1	Olive	1/2	31/32	9/16	1	2-5/8	10	43/64	7/16

Tooling Information

Catalog Number	ILSCO								Burdry						Thomas & Betts				Anderson		Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	IDTB-6 IDTB-6-LIO Dieless No. of Crimps	IDT-6, IDT-6H 6.2 Ton Dieless No. of Crimps	ILC-15H Die No. No. of Crimps	MT-25 Hand Dieless No. of Crimps	94285 Left /Rt. Die/Die No. of Crimps	IDT-12-N Dieless No. of Crimps	Y-48B Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	MY29-3 Hand Dieless No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps	TBM-8 Hand Tool No. of Crimps	Versa Crimp Dieless No. of Crimps	
ACL-1/ ACN-1	ILD-7 (1) or ILD-6 (4)	ILD-7 (1) or ILD-6 (4)	- (2)	- (2)	ILD-7 (1) or ILD-6 (4)	- (2)	E/A (4)	- (1)	- (1)	471 (1)	471 (1)	471 (1)	471 (1)	- (2)	- (1)	45 (3)	45 (3)	45 (3)	- (3)	- (2)	Gold
ACL-1/0/ ACN-1/0	ILD-8 (1)	ILD-8 (1)	- (2)	- (2)	ILD-8 (1)	- (2)	A/C (5)	- (1)	296 (1)	296 (1)	296 (1)	296 (1)	296 (1)	- (2)	- (1)	50 (3)	50 (3)	50 (3)	- (3)	(2)	Tan
ACL-2/0/ ACN-2/0	ILD-10 (1)	ILD-10 (1)	- (2)	- (2)	ILD-10 (1)	- (2)	A/B (4)	- (1)	297 (1)	297 (2)	297 (2)	297 (2)	297 (2)	- (2)	- (1)	54 (3)	54H (6)	54 (3)	- (3)	(2)	Olive

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207


TYPE ACL

Features

- Electro-tin plated
- Manufactured from high strength aluminum alloy
- Chamfered barrel
- Color coded
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Provides visual tooling recommendation for ILSCO or standard industry tools
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Application versatility



Catalog Number	Wire Size	Wire Range When Installed With IDT-12-N Tool	Die Color Code	Bolt Size	Tang Width	Dimensions			Die Index	O.D.	I.D.
						C	E	F			
ACL-3/0	3/0	3/0-1	Ruby	3/8	1-1/16	13/32	1-1/16	2-13/16	10	49/64	1/2
ACN-3/0	3/0	3/0-1	Ruby	1/2	1-1/16	9/16	1-1/16	2-13/16	10	49/64	1/2
ACL-4/0	4/0	4/0-1	White	3/8	1-1/8	13/32	1-1/16	3-3/8	12	55/64	9/16
ACN-4/0	4/0	4/0-1	White	1/2	1-1/8	9/16	1-1/16	3-3/8	12	55/64	9/16
ACL-250	250kcmil	250kcmil-1/0	Red	1/2	1-21/64	17/32	1-1/2	3-7/8	13	59/64	39/64
ACL-300	300kcmil	300kcmil-2/0	Blue	1/2	1-7/16	17/32	1-1/2	4-1/16	14	1-1/64	21/32
ACL-350	350kcmil	350kcmil-3/0	Brown	1/2	1-9/16	17/32	1-1/2	4-3/32	14	1-1/8	23/32

Tooling Information

Catalog Number	ILSCO								Burdly						Thomas & Betts				Anderson		Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	IDTB-6 IDTB-6-LIO Dieless No. of Crimps	IDT-6, IDT-6H 6.2 Ton Dieless No. of Crimps	ILC-15H Die No. No. of Crimps	MT-25 Hand No. of Crimps	94285 Left / Rt. Die / Die No. of Crimps	IDT-12-N Dieless No. of Crimps	Y-48B Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	MY29-3 Hand Dieless No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps	TBM-8 Hand Tool No. of Crimps	Versa Crimp Dieless No. of Crimps	
ACL-3/0 ACN-3/0	ILD-10 (2)	ILD-10 (2)	- (3)	- (3)	ILD-10 (2)	- (2)	A/A (4)	- (1)	467 (1)	467 (2)	467 (2)	467 (2)	467 (2)	- (2)	- (1)	60 (3)	60 (3)	60 (3)	- (3)	- (2)	Ruby
ACL-4/0 ACN-4/0	ILD-12 (1)	ILD-12 (1)	- (3)	- (3)	ILD-12 (1)	- (2)	- (2)	298 (1)	298 (2)	298 (2)	298 (2)	298 (2)	- (2)	- (1)	66H (4)	66 (2)	66 (2)	- (5)	- (3)	White	
ACL-250	ILD-13 (2)	ILD-13 (2)	- (3)	- (3)	ILD-13 (2)	- (2)	- (2)	324 (1)	324 (2)	324 (2)	324 (2)	324 (2)	- (1)	- (1)	71H (4)	71H (2)	71 (2)	- (5)	- (3)	Red	
ACL-300	ILD-14 (2)	ILD-14 (2)	- (4)	- (4)	ILD-14 (2)	- (2)	- (2)	470 (1)	470 (2)	470 (2)	470 (2)	470 (2)	- (1)	- (1)	76H (4)	76 (2)	76 (2)	- (5)	- (3)	Blue	
ACL-350	ILD-14 (2)	ILD-14 (2)	- (4)	- (4)	ILD-14 (2)	- (2)	- (2)	299 (1)	299 (2)	299 (2)	299 (2)	299 (2)	- (1)	- (1)	87H (4)	87H (4)	87 (2)	- (6)	- (3)	Brown	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207

A


TYPE ACL

Features

- Electro-tin plated
- Manufactured from high strength aluminum alloy
- Chamfered barrel
- Color coded
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Provides visual tooling recommendation for ILSCO or standard industry tools
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Application versatility



Catalog Number	Wire Size	Wire Range When Installed With IDT-12-N Tool	Die Color Code	Bolt Size	Tang Width	Dimensions			Die Index	O.D.	I.D.
						C	E	F			
ACL-400	400kcmil	400kcmil-4/0	Green	1/2	1-5/8	17/32	1-9/16	4-7/8	16	1-3/16	49/64
ACL-500	500kcmil	500kcmil-4/0	Pink	1/2	1-13/16	17/32	1-9/16	4-7/8	16A	1-21/64	55/64
ACL-600	600kcmil	600kcmil-250kcmil	Black	5/8	1-15/16	21/32	2	5-3/8	17	1-21/64	59/64
ACL-700	700kcmil	700kcmil-350kcmil	Purple	5/8	2-1/16	21/32	2-3/32	5-21/32	17	1-13/32	1
ACL-750	750kcmil	750kcmil-500kcmil	Yellow	5/8	2-3/16	21/32	2-3/32	5-21/32	18	1-29/64	1-1/32
ACL-1000	1000kcmil	1000kcmil-750kcmil	Brown	5/8	2-1/2	21/32	2-1/4	6-5/8	20	1-53/64	1-3/16

Tooling Information

Catalog Number	ILSCO						Burdny						Thomas & Betts				Anderson	Color Code
	ILC-12-N Die No. No. of Crimps	ILCB-12-N Die No. No. of Crimps	IDTB-6 Dieless No. of Crimps	IDT-6, IDT-6H 6.2 Ton Dieless No. of Crimps	ILC-15H Die No. No. of Crimps	IDT-12-N Dieless No. of Crimps	Y-48B Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 40 Ton Die Index No. of Crimps	21940 Hand Die Index No. of Crimps	TBM-8 Tool No. of Crimps	Versa Crimp Dieless No. of Crimps	
ACL-400	ILD-16 (3)	ILD-16 (3)	- (4)	- (4)	ILD-16 (3)	- (2)	472 (2)	472 (4)	472 (4)	472 (4)	- (1)	94H (4)	94H (4)	94 (2)	-	- (4)	Green	
ACL-500	ILD-16A (3)	ILD-16A (3)	- (4)	- (4)	ILD-16A (3)	- (2)	300 (2)	300 (4)	300 (4)	300 (4)	- (1)	99H (4)	99H (4)	99 (2)	-	- (4)	Pink	
ACL-600	ILD-17 (4)	ILD-17 (4)	- (4)	- (4)	ILD-17 (4)	- (2)	473 (2)	473 (4)	473 (4)	473 (4)	- (1)	106H (4)	106 (2)	106 (2)	-	- (4)	Black	
ACL-700	ILD-17 (4)	ILD-17 (4)	- (4)	- (4)	ILD-17 (4)	- (2)	936 (2)	- (4)	936 (4)	936 (4)	- (1)	112H (4)	112H (4)	112 (2)	-	-	Purple	
ACL-750	ILD-18 (5)	ILD-18 (5)	- (4)	- (4)	ILD-18 (5)	- (2)	936 (2)	- (4)	936 (4)	936 (4)	- (1)	115H (4)	115H (4)	115 (2)	-	-	Yellow	
ACL-1000	-	-	-	-	- (3)	- (2)	302 (2)	-	-	-	- (1)	-	140H (4)	140 (2)	-	-	Brown	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207


TYPE 2ACL

Features

- Electro-tin plated
- Manufactured from high strength aluminum alloy
- Chamfered barrel
- Color coded
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Provides visual tooling recommendation for ILSCO or standard industry tools
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Application versatility



Catalog No.	Wire Size	Wire Range When Installed With IDT-12-N Tool	Die Color Code	Bolt Size	Tang Width	Dimensions				Die Index	O.D.	I.D.
						C	E	F	J			
2ACL-1/0	1/0	1/0-1	Tan	3/8 (2)	7/8	13/32(2)	1-7/8	3-15/32	1	8	39/64	25/64
2ACN-1/0	1/0	1/0-1	Tan	1/2 (2)	7/8	17/32(2)	3	4-5/8	1-3/4	8	39/64	25/64
2ACL-2/0	2/0	2/0-1	Olive	1/2 (2)	31/32	9/16(2)	3-3/8	5	1-3/4	10	43/64	7/16
2ACL-3/0	3/0	3/0-1	Ruby	1/2 (2)	1-1/16	9/16(2)	3-3/8	5-5/32	1-3/4	10	49/64	1/2
2ACL-4/0	4/0	4/0-1	White	1/2 (2)	1-1/8	9/16(2)	3-3/8	5-5/8	1-3/4	12	55/64	9/16
2ACL-250	250kcmil	250kcmil-1/0	Red	1/2 (2)	1-21/64	9/16(2)	3-3/8	5-3/4	1-3/4	13	59/64	39/64
2ACL-300	300kcmil	300kcmil-2/0	Blue	1/2 (2)	1-7/16	9/16(2)	3-3/8	5-15/16	1-3/4	14	1-1/64	21/32

Tooling Information

Catalog Number	ILSCO								Burdyn						Thomas & Betts				Anderson	Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	IDTB-6 IDTB-6-LIO Dieless No. of Crimps	IDT-6, IDT-6H 6.2 Ton Dieless No. of Crimps	ILC-15H Die No. No. of Crimps	MT-25 Hand Dieless No. of Crimps	94285 Left/ Rt. Die/ Die No. of Crimps	IDT-12-N Dieless No. of Crimps	Y-48B Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	MY29-3 Hand Dieless No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps	TBM-8 Hand Tool No. of Crimps	
2ACL-1/0	ILD-8 (1)	ILD-8 (1)	- (2)	- (2)	ILD-8 (1)	- (2)	A/C (5)	296 (1)	296 (1)	296 (1)	296 (1)	296 (1)	- (2)	- (1)	50 (3)	50 (3)	50 (3)	- (3)	- (2)	Tan
2ACL-2/0	ILD-10 (1)	ILD-10 (1)	- (2)	- (2)	ILD-10 (1)	- (2)	A/B (4)	297 (1)	297 (2)	297 (2)	297 (2)	297 (2)	- (2)	- (1)	54 (3)	54H (6)	54 (3)	- (3)	- (2)	Olive
2ACL-3/0	ILD-10 (2)	ILD-10 (2)	- (3)	- (3)	ILD-10 (2)	- (2)	A/A (4)	467 (1)	467 (2)	467 (2)	467 (2)	467 (2)	- (2)	- (1)	60 (3)	60 (3)	60 (3)	- (3)	- (2)	Ruby
2ACL-4/0	ILD-12 (1)	ILD-12 (1)	- (3)	- (3)	ILD-12 (1)	- (2)	- (2)	298 (1)	298 (2)	298 (2)	298 (2)	298 (2)	- (2)	- (1)	66H (4)	66 (2)	66 (2)	- (5)	- (3)	White
2ACL-250	ILD-13 (2)	ILD-13 (2)	- (3)	- (3)	ILD-13 (2)	- (2)	- (2)	324 (1)	324 (2)	324 (2)	324 (2)	324 (2)	- (2)	- (1)	71H (4)	71H (4)	71 (2)	- (5)	- (3)	Red
2ACL-300	ILD-14 (2)	ILD-14 (2)	- (4)	- (4)	ILD-14 (2)	- (2)	- (2)	470 (1)	470 (2)	470 (2)	470 (2)	470 (2)	- (2)	- (1)	76H (4)	76 (2)	76 (2)	- (5)	- (3)	Blue

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207

A


TYPE 2ACL

Features

- Electro-tin plated
- Manufactured from high strength aluminum alloy
- Chamfered barrel
- Color coded
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Provides visual tooling recommendation for ILSCO or standard industry tools
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Application versatility



Catalog No.	Wire Size	Wire Range When Installed With IDT-12-N Tool	Die Color Code	Bolt Size	Tang Width	Dimensions				Die Index	O.D.	I.D.
						C	E	F	J			
2ACL-350	350kcmil	350kcmil-3/0	Brown	1/2 (2)	1-9/16	9/16(2)	3-3/8	5-31/32	1-3/4	14	1-1/8	23/32
2ACL-400	400kcmil	400kcmil-4/0	Green	1/2 (2)	1-5/8	9/16(2)	3-3/8	6-11/16	1-3/4	16	1-3/16	49/64
2ACL-500	500kcmil	500kcmil-4/0	Pink	1/2 (2)	1-13/16	9/16(2)	3-3/8	6-11/16	1-3/4	16A	1-21/64	55/64
2ACL-600	600kcmil	600kcmil-250kcmil	Black	1/2 (2)	1-15/16	9/16(2)	3-3/8	6-3/4	1-3/4	17	1-21/64	59/64
2ACL-700	700kcmil	700kcmil-350kcmil	Purple	1/2 (2)	2-1/16	9/16(2)	3-3/8	6-15/16	1-3/4	17	1-13/32	1
2ACL-750	750kcmil	750kcmil-500kcmil	Yellow	1/2 (2)	2-1/16	9/16(2)	3-3/8	6-15/16	1-3/4	18	1-29/64	1-1/32
2ACL-1000	1000kcmil	1000kcmil-750kcmil	Brown	1/2 (2)	2-1/2	9/16(2)	3-3/8	7-3/4	1-3/4	20	1-53/64	1-3/16

Tooling Information

Catalog Number	ILSCO								Burdny						Thomas & Betts				Anderson	Color Code	
	ILC-12-N Die No. No. of Crimps	ILCB-12-N Die No. No. of Crimps	IDTB-6 Dieless No. of Crimps	IDT-6, IDT-6H 6.2 Ton Dieless No. of Crimps	ILC-15H Die No. No. of Crimps	MT-25 Hand Dieless No. of Crimps	94285 Left/ Rt. Die No. of Crimps	IDT-12-N Dieless No. of Crimps	Y-48B Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	MY29-3 Hand Dieless No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps	TBM-8 Hand Tool No. of Crimps		Versa Crimp Dieless No. of Crimps
2ACL-350	ILD-14 (2)	ILD-14 (2)	- (4)	- (4)	ILD-14 (2)	-	-	- (2)	299 (1)	299 (2)	299 (2)	299 (2)	299 (2)	-	- (1)	87H (4)	87H (4)	87 (2)	87H (6)	- (3)	Brown
2ACL-400	ILD-16 (3)	ILD-16 (3)	- (4)	- (4)	ILD-16 (3)	-	-	- (2)	472 (2)	472 (4)	472 (4)	472 (4)	472 (4)	-	- (1)	94H (4)	94H (4)	94 (2)	- (4)	- (4)	Green
2ACL-500	ILD-16A (3)	ILD-16A (3)	- (4)	- (4)	ILD-16A (3)	-	-	- (2)	300 (2)	300 (4)	300 (4)	300 (4)	300 (4)	-	- (1)	99H (4)	99H (4)	99 (2)	- (4)	- (4)	Pink
2ACL-600	ILD-17 (4)	ILD-17 (4)	- (4)	- (4)	ILD-17 (4)	-	-	- (2)	473 (2)	473 (4)	473 (4)	473 (4)	473 (4)	-	- (1)	106H (4)	106 (2)	106 (2)	- (4)	- (4)	Black
2ACL-700	ILD-17 (4)	ILD-17 (4)	- (4)	- (4)	ILD-17 (4)	-	-	- (2)	936 (2)	-	936 (4)	936 (4)	936 (4)	-	- (1)	112H (4)	112H (4)	112 (2)	-	-	Purple
2ACL-750	ILD-18 (5)	ILD-18 (5)	- (4)	- (4)	ILD-18 (5)	-	-	- (2)	936 (2)	-	936 (4)	936 (4)	936 (4)	-	- (1)	115H (4)	115H (4)	115 (2)	-	-	Yellow
2ACL-1000	-	-	-	-	- (3)	-	-	- (2)	302 (2)	-	-	-	-	-	-	-	140H (4)	140 (2)	-	-	Brown

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207


TYPE
ASL

Features

- Electro-tin plated
- Manufactured from high strength aluminum alloy
- Two sizes cover a wire range from 750 kcmil-1/0
- Unique design
- Versatile
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Can be used with both aluminum and copper terminals
- Permits inventories to be kept to a minimum
- Allows vertical stacking to minimize space requirements
- Can be used with copper and/or aluminum connectors
- Application versatility



Catalog Number	Wire Range	Insulation O.D.	H
ASL-250	250kcmil-1/0	55/64	3/4
ASL-750	750kcmil-1/0	1-3/8	1-1/4

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207


A TYPE CPM

Features

- Barrel manufactured from high strength aluminum alloy
- Pigtail manufactured from high conductivity copper
- Chamfered barrel
- UL Listed and CSA Certified for 600 volts, 90° C
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Supplied with insulating cover
- Rated for full ampacity of incoming conductor

Benefits

- Allows insertion into equipment supplied with either copper or aluminum connectors
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Ensures reliability for copper and aluminum conductors
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Eliminates taping



Catalog Number	Wire Size	Die Color	Copper Pin Size	Dimensions				O.D.	I.D.
				A	B	C	Cover D		
CPM-6	6	Orange	8	1/8	7/8	1-11/32	1-11/16	21/32	3/16
CPM-4	4	Orange	6	3/16	7/8	1-11/32	1-11/16	21/32	1/4
CPM-2	2	Orange	4	15/64	7/8	1-11/32	1-11/16	21/32	5/16
CPM-1	1	Orange	3	17/64	1	1-11/32	1-11/16	21/32	23/64
CPM-1/0	1/0	White	2	19/64	1-1/4	1-19/32	2-3/32	29/32	25/64
CPM-2/0	2/0	White	1	11/32	1-1/4	1-19/32	2-3/32	29/32	7/16
CPM-3/0	3/0	White	1/0	3/8	1-3/8	1-7/8	2-3/32	29/32	1/2

Tooling Information

Catalog Number	ILSCO			Burdny				Thomas & Betts			Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	Y-46 Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps	
CPM-6	ILD-9 (3)	ILD-9 (3)	ILD-9 (3)	297 (2)	297 (2)	297 (2)	297 (2)	50 (2)	50 (2)	50 (2)	Orange
CPM-4	ILD-9 (3)	ILD-9 (3)	ILD-9 (3)	297 (2)	297 (2)	297 (2)	297 (2)	50 (2)	50 (2)	50 (2)	Orange
CPM-2	ILD-9 (3)	ILD-9 (3)	ILD-9 (3)	297 (2)	297 (2)	297 (2)	297 (2)	50 (2)	50 (2)	50 (2)	Orange
CPM-1	ILD-9 (3)	ILD-9 (3)	ILD-9 (3)	297 (2)	297 (2)	297 (2)	297 (2)	50 (2)	50 (2)	50 (2)	Orange
CPM-1/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	324 (2)	324 (2)	324 (2)	324 (2)	76H (4)	76 (2)	76 (2)	White
CPM-2/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	324 (2)	324 (2)	324 (2)	324 (2)	76H (4)	76 (2)	76 (2)	White
CPM-3/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	324 (2)	324 (2)	324 (2)	324 (2)	76H (4)	76 (2)	76 (2)	White

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Dieless crimp tools must not be used to crimp CPM/CPML adaptors. See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E62525


TYPE CPM

Features

- Barrel manufactured from high strength aluminum alloy
- Pigtail manufactured from high conductivity copper
- Chamfered barrel
- UL Listed and CSA Certified for 600 volts, 90° C
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Supplied with insulating cover
- Rated for full ampacity of incoming conductor

Benefits

- Allows insertion into equipment supplied with either copper or aluminum connectors
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Ensures reliability for copper and aluminum conductors
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Eliminates taping



Catalog Number	Wire Size	Die Color	Copper Pin Size	Dimensions				O.D.	I.D.
				A	B	C	Cover D		
CPM-4/0	4/0	White	2/0	13/32	1-3/8	1-7/8	2-3/32	29/32	9/16
CPM-250	250kcmil	Brown	3/0	15/32	1-1/2	2-1/16	2-27/32	1-5/32	39/64
CPM-300	300kcmil	Brown	4/0	17/32	1-5/8	2-1/16	2-27/32	1-5/32	21/32
CPM-350	350kcmil	Brown	4/0	17/32	1-5/8	2-1/16	2-27/32	1-5/32	23/32
CPM-400	400kcmil	Pink	250kcmil	37/64	1-7/8	2-3/32	2-13/32	1-3/8	49/64
CPM-500	500kcmil	Pink	350kcmil	11/16	1-7/8	2-3/32	2-13/32	1-3/8	55/64
CPM-600	600kcmil	Yellow	350kcmil	11/16	1-7/8	2-3/4	3-3/32	1-1/2	59/64

Tooling Information

Catalog Number	ILSCO			Burdny				Thomas & Betts			Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	Y-46 Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps	
CPM-4/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	324 (2)	324 (1)	324 (2)	324 (2)	76H (4)	76 (2)	76 (2)	White
CPM-250	ILD-14 (2*)	ILD-14 (2*)	ILD-14 (2*)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	87H (2)	87H (2)	87 (1)	Brown
CPM-300	ILD-14 (2*)	ILD-14 (2*)	ILD-14 (2*)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	87H (2)	87H (2)	87 (1)	Brown
CPM-350	ILD-14 (2*)	ILD-14 (2*)	ILD-14 (2*)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	87H (2)	87H (2)	87 (1)	Brown
CPM-400	ILD-16A (2*)	ILD-16A (2*)	ILD-16A (2*)	300 (3)	300 (3)	300 (3)	300 (3)	106H (2)	106 (1)	106 (1)	Pink
CPM-500	ILD-16A (2*)	ILD-16A (2*)	ILD-16A (2*)	300 (3)	300 (3)	300 (3)	300 (3)	106H (2)	106 (1)	106 (1)	Pink
CPM-600	ILD-18 (3)	ILD-18 (3)	ILD-18 (3)	936 (3)	936 (3)	936 (3)	936 (3)	115H (3)	115H (3)	115 (2)	Yellow

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*Overlap Crimps Dieless crimp tools must not be used to crimp CPM/CPML adaptors. See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E62525

A


TYPE CPM CPML

Features

- Barrel manufactured from high strength aluminum alloy
- Pigtail manufactured from high conductivity copper
- Chamfered barrel
- UL Listed and CSA Certified for 600 volts, 90° C
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Supplied with insulating cover
- Rated for full ampacity of incoming conductor

Benefits

- Allows insertion into equipment supplied with either copper or aluminum connectors
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Ensures reliability for copper and aluminum conductors
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Eliminates taping



Catalog Number	Wire Range	Die Color	Copper Pin Size	Dimensions				O.D.	I.D.
				A	B	C	Cover D		
CPM-750	750kcmil-700kcmil	Yellow	500kcmil	13/16	2	2-3/4	3-3/32	1-1/2	1-1/32
CPML-500	500kcmil	Pink	350kcmil	11/16	3	2-3/32	2-13/32	1-3/8	55/64
CPML-600	600kcmil	Yellow	350kcmil	11/16	3	2-3/4	3-3/32	1-1/2	59/64
CPML-750	750kcmil-700kcmil	Yellow	500kcmil	13/16	3	2-3/4	3-3/32	1-1/2	1-1/32

Tooling Information

Catalog Number	ILSCO			Burndy				Thomas & Betts			Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	Y-46 Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps	
CPM-750	ILD-18 (3)	ILD-18 (3)	ILD-18 (3)	936 (3)	936 (3)	936 (3)	936 (3)	115H (3)	115H (3)	115 (2)	Yellow
CPML-500	ILD-16A (2*)	ILD-16A (2*)	ILD-16A (2*)	300 (3)	300 (3)	300 (3)	300 (3)	106H (2)	106 (1)	106 (1)	Pink
CPML-600	ILD-18 (3*)	ILD-18 (3*)	ILD-18 (3*)	936 (3)	936 (3)	936 (3)	936 (3)	115H (3)	115H (3)	115 (2)	Yellow
CPML-750	ILD-18 (3*)	ILD-18 (3*)	ILD-18 (3*)	936 (3)	936 (3)	936 (3)	936 (3)	115H (3)	115H (3)	115 (2)	Yellow

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*Overlap Crimps

Dieless crimp tools must not be used to crimp CPM/CPML adaptors.

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E62525


TYPE ACM

Features

- Manufactured from high strength aluminum alloy
- Pin is knurled
- Chamfered barrel
- UL Listed and CSA Certified for 600 volts, 90° C
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Supplied with insulating cover

Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Permits greater surface contact
- Provides easy conductor insertion
- Ensures reliability for aluminum or copper conductors
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Eliminates taping



Catalog Number	Wire Size	Die Color	Pin Size	Dimensions				O.D.	I.D.
				A	B	C	D (cover)		
ACM-6	6	Tan	#4	7/32	11/16	1-13/64	1-3/4	39/64	3/16
ACM-4	4	Tan	#4	1/4	11/16	1-13/64	1-3/4	39/64	1/4
ACM-2	2	Tan	#4	1/4	11/16	1-13/64	1-3/4	39/64	5/16
ACM-1	1	Tan	#3	17/64	27/32	1-13/64	1-3/4	39/64	23/64
ACM-1/0	1/0	White	#2	19/64	27/32	1-3/8	2	55/64	25/64
ACM-2/0	2/0	White	#1	11/32	27/32	1-3/8	2	55/64	7/16

Tooling Information

Catalog Number	ILSCO				Burdry						Thomas & Betts		Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	IDT-12-N Die No. No. of Crimps	Y750 Family Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	13100A 15 Ton Die Index No. of Crimps	
ACM-6	ILD-8 (1)	ILD-8 (1)	ILD-8 (1)	(1)	296 (1)	296 (1)	296 (1)	296 (1)	296 (1)	(1)	45H Gold (2)	45H Gold (2)	Tan
ACM-4	ILD-8 (1)	ILD-8 (1)	ILD-8 (1)	(1)	296 (1)	296 (1)	296 (1)	296 (1)	296 (1)	(1)	45H Gold (2)	45H Gold (2)	Tan
ACM-2	ILD-8 (1)	ILD-8 (1)	ILD-8 (1)	(1)	296 (1)	296 (1)	296 (1)	296 (1)	296 (1)	(1)	45H Gold (2)	45H Gold (2)	Tan
ACM-1	ILD-8 (1)	ILD-8 (1)	ILD-8 (1)	(1)	296 (1)	296 (1)	296 (1)	296 (1)	296 (1)	(1)	45H Gold (2)	45H Gold (2)	Tan
ACM-1/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	(1)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	(1)	66H (2)	66H (2)	White
ACM-2/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	(1)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	(1)	66H (2)	66H (2)	White

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*Overlap Crimps

See stuffer sheet for complete information on tooling. Tested to UL 486A/B, UL File E62525

A


TYPE ACM

Features

- Manufactured from high strength aluminum alloy
- Pin is knurled
- Chamfered barrel
- UL Listed and CSA Certified for 600 volts, 90° C
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Supplied with insulating cover

Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Permits greater surface contact
- Provides easy conductor insertion
- Ensures reliability for aluminum or copper conductors
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Eliminates taping



Catalog Number	Wire Size	Die Color	Pin Size	Dimensions				O.D.	I.D.
				A	B	C	D (cover)		
ACM-3/0	3/0	White	1/0	3/8	1-7/32	1-3/8	2	55/64	1/2
ACM-4/0	4/0	White	2/0	27/64	1-7/32	1-3/8	2	55/64	35/64
ACM-250	250kcmil	Brown	3/0	15/32	1-7/32	1-13/32	2-1/4	1-7/64	39/64
ACM-300	300kcmil	Brown	4/0	17/32	1-11/32	1-13/32	2-1/4	1-7/64	21/32
ACM-350	350kcmil	Brown	250kcmil	37/64	1-11/32	1-13/32	2-1/4	1-7/64	23/32
ACM-400	400kcmil	Pink	300kcmil	5/8	1-39/64	2-1/32	3-1/4	1-21/64	49/64

Tooling Information

Catalog Number	ILSCO				Burdyn						Thomas & Betts		Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	IDT-12-N Die No. No. of Crimps	Y750 Family Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	13100A 15 Ton Die Index No. of Crimps	
ACM-3/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	(1)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	(1)	66H (2)	66H (2)	White
ACM-4/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	(1)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	(1)	66H (2)	66H (2)	White
ACM-250	ILD-14 (1)	ILD-14 (1)	ILD-14 (1)	(1)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	(1)	87H (2)	87H (2)	Brown
ACM-300	ILD-14 (1)	ILD-14 (1)	ILD-14 (1)	(1)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	(1)	87H (2)	87H (2)	Brown
ACM-350	ILD-14 (1)	ILD-14 (1)	ILD-14 (1)	(1)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	(1)	87H (2)	87H (2)	Brown
ACM-400	ILD-16A (2)	ILD-16A (2)	ILD-16A (2)	(1)	300 (3)	300 (3)	300 (3)	300 (3)	300 (3)	(1)	99H (3)	99H (3)	Pink

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*Overlap Crimps

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E62525


TYPE ACM

Features

- Manufactured from high strength aluminum alloy
- Pin is knurled
- Chamfered barrel
- UL Listed and CSA Certified for 600 volts, 90° C
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Supplied with insulating cover

Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Permits greater surface contact
- Provides easy conductor insertion
- Ensures reliability for aluminum or copper conductors
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Eliminates taping



Catalog Number	Wire Size	Die Color	Pin Size	Dimensions				O.D.	I.D.
				A	B	C	D (cover)		
ACM-500	500kcmil	Pink	350kcmil	11/16	1-39/64	2-1/32	3-1/4	1-21/64	55/64
ACM-600	600kcmil	Yellow	400kcmil	47/64	1-41/64	2-1/32	3-1/4	1-15/32	59/64
ACM-750	750kcmil-700kcmil	Yellow	500kcmil	13/16	1-49/64	2-1/32	3-1/4	1-15/32	1-1/32

Tooling Information

Catalog Number	ILSCO				Burdly						Thomas & Betts		Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	IDT-12-N Die No. No. of Crimps	Y750 Family Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	13100A 15 Ton Die Index No. of Crimps	
ACM-500	ILD-16A (2)	ILD-16A (2)	ILD-16A (2)	(1)	300 (3)	300 (3)	300 (3)	300 (3)	300 (3)	(1)	99H (3)	99H (3)	Pink
ACM-600	ILD-18 (3)	ILD-18 (3)	ILD-18 (3)	(1)	936 (3)	936 (3)	936 (3)	936 (3)	936 (3)	(1)	115H (3)	115H (3)	Yellow
ACM-750	ILD-18 (3)	ILD-18 (3)	ILD-18 (3)	(1)	936 (3)	936 (3)	936 (3)	936 (3)	936 (3)	(1)	115H (3)	115H (3)	Yellow

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*Overlap Crimps

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E62525

A



TYPE ACO

Features

- Manufactured from high strength aluminum alloy
- Pin is knurled
- Pin is off center
- Chamfered barrel
- UL Listed and CSA Certified for 600 volts, 90° C
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Supplied with insulating cover

Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Permits greater surface contact
- Allows connectors to be rotated for parallel applications. Multiple conductor lugs hole spacing does NOT permit insertion of straight pin connectors
- Provides easy conductor insertion
- Ensures reliability for aluminum or copper conductors
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Eliminates taping



Catalog Number	Wire Size	Die Color Code	Die Index	Pin Size	Dimensions				O.D.	I.D.
					F	C	A	D (cover)		
ACO-2/0	2/0	White	12	#1	2-7/32	1-3/8	11/32	2	55/64	7/16
ACO-3/0	3/0	White	12	1/0	2-19/32	1-3/8	3/8	2	55/64	1/2
ACO-4/0	4/0	White	12	2/0	2-19/32	1-3/8	27/64	2	55/64	35/64
ACO-250	250kcmil	Brown	14	3/0	2-5/8	1-13/32	15/32	2-1/4	1-7/64	19/32
ACO-300	300kcmil	Brown	14	4/0	2-3/4	1-13/32	17/32	2-1/4	1-7/64	21/32

Cover and connector are packaged together (ONLY).

Tooling Information

Catalog Number	ILSCO				Burdny						Thomas & Betts		Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	IDT-12-N Die No. No. of Crimps	Y750 Family Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	13100A 15 Ton Die Index No. of Crimps	
ACO-2/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	(1)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	(1)	66H (2)	66 (2)	White
ACO-3/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	(1)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	(1)	66H (2)	66 (2)	White
ACO-4/0	ILD-12 (1)	ILD-12 (1)	ILD-12 (1)	(1)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	298 (2*)	(1)	66H (2)	66 (2)	White
ACO-250	ILD-14 (1)	ILD-14 (1)	ILD-14 (1)	(1)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	(1)	87H (2)	87 (2)	Brown
ACO-300	ILD-14 (1)	ILD-14 (1)	ILD-14 (1)	(1)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	(1)	87H (2)	87 (2)	Brown

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Overlap Crimps

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E62525

Aluminum Offset Pigtail Adaptor

Dual Rated

Conductor Range: 1000kcmil-350kcmil


TYPE ACO

Features

- Manufactured from high strength aluminum alloy
- Pin is knurled
- Pin is off center
- Chamfered barrel
- UL Listed and CSA Certified for 600 volts, 90° C
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Supplied with insulating cover

Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Permits greater surface contact
- Allows connectors to be rotated for parallel applications. Multiple conductor lugs hole spacing does NOT permit insertion of straight pin connectors
- Provides easy conductor insertion
- Ensures reliability for aluminum or copper conductors
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Eliminates taping



Catalog Number	Wire Range	Die Color Code	Die Index	Pin Size	Dimensions				O.D.	I.D.
					F	C	A	D (cover)		
ACO-350	350kcmil	Brown	14	250kcmil	2-3/4	1-13/32	37/64	2-1/4	1-7/64	23/32
ACO-500	500kcmil	Pink	16A	350kcmil	3-5/8	2-1/32	11/16	3-1/4	1-21/64	55/64
ACO-600	600kcmil	Yellow	18	400kcmil	3-43/64	2-1/32	47/64	3-1/4	1-15/32	59/64
ACO-750	750kcmil-700kcmil	Yellow	18	500kcmil	3-51/64	2-1/32	13/16	3-1/4	1-15/32	1-1/32
ACO-1000*	1000kcmil-750kcmil	-	-	600kcmil	4-1/32	2-1/32	29/32	-	1-45/64	1-3/16

Cover and connector are packaged together (ONLY).

* Not supplied with cover

Tooling Information

Catalog Number	ILSCO				Burdny						Thomas & Betts		Color Code
	ILC-12-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	IDT-12-N Die No. No. of Crimps	Y750 Family Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	13100A 15 Ton Die Index No. of Crimps	
ACO-350	ILD-14 (1)	ILD-14 (1)	ILD-14 (1)	(1)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	(1)	87H (2)	87 (2)	Brown
ACO-500	ILD-16A (2)	ILD-16A (2)	ILD-16A (2)	(1)	300 (3)	300 (3)	300 (3)	300 (3)	300 (3)	(1)	99H (3)	99H (3)	Pink
ACO-600	ILD-18 (3)	ILD-18 (3)	ILD-18 (3)	(1)	936 (3)	936 (3)	936 (3)	936 (3)	936 (3)	(1)	115H (3)	115H (3)	Yellow
ACO-750	ILD-18 (3)	ILD-18 (3)	ILD-18 (3)	(1)	936 (3)	936 (3)	936 (3)	936 (3)	936 (3)	(1)	115H (3)	115H (3)	Yellow
ACO-1000	-	-	-	(1)	-	-	-	-	-	(1)	-	-	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Overlap Crimps

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E62525

A


TYPE ACO-90

Features

- Manufactured from high strength aluminum alloy
- Pin is bent
- Pin is knurled
- Chamfered barrel
- UL Listed and CSA Certified for 600 volts, 90° C
- Clearly marked with wire size and die index for ILSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in barrel
- Supplied with insulating cover

Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Eliminates the need to bend the conductor. Designed for use in tight applications where room for the required bending radius of the wire is not available
- Permits greater surface contact
- Provides easy conductor insertion
- Ensures reliability for aluminum or copper conductors
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Eliminates taping



Catalog Number	Wire Range	Die Color Code	Die Index	Pin Size	A	B	C	D	E	Cover	O.D.	I.D.
ACO-90-350	350kcmil	Brown	14	250kcmil	2-31/64	2-11/16	1-9/64	9/16	1-21/64	2-1/4	1-7/64	23/32
ACO-90-500	500kcmil	Pink	16A	350kcmil	3-19/64	3-11/64	2-1/32	11/16	1-39/64	3-1/4	1-21/64	55/64

Cover & Connector are packaged together (ONLY).

Tooling Information

Catalog Number	ILSCO				Burdny						Thomas & Betts		Color Code
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	IDT-12-N Die No. No. of Crimps	Y750 Family Die Index No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	13100A 15 Ton Die Index No. of Crimps	
ACO-90-350	ILD-14 (1)	ILD-14 (1)	ILD-14 (2)	(1)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	299 (2*)	(1)	87H (2)	87 (2)	Brown
ACO-90-500	ILD-16A (2)	ILD-16A (2)	ILD-16A (2)	(1)	300 (3)	300 (3)	300 (3)	300 (3)	300 (3)	(1)	99H (3)	99H (3)	Pink

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Overlap Crimps

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E62525

Aluminum Compression Lugs

Dual Rated - Narrow Tang

Conductor Range: 600kcmil-4




TYPE IACL

Features

- Manufactured from high strength aluminum alloy
- Four OD sizes accommodate a wire range from #4 to 600 kcmil
- Chamfered barrel
- Prefilled with DE-OX
- Color coded end caps inserted in barrel and ink marked with die number and number of crimps
- Electro tin plated
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Requires only four installation dies to crimp eleven conductor sizes. Tang width remains constant within an OD size and is designed to fit transformer pads.
- Provides easy conductor insertion
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Provides low contact resistance
- Ensures reliability
- Application versatility



Catalog Number	Wire Size	Wire Range When Installed With IDT-12-N Tool	Tang Width	Bolt Size	Dimensions				IlSCO Die Index	Die Color Code
					D	E	F	C		
IACL-4	4	4-6	29/32	1/2	1-7/16	1-3/32	3	9/16	9	Orange
IACL-2	2	2-6	29/32	1/2	1-7/16	1-3/32	3	9/16	9	Orange
IACL-1/0	1/0	1/0-1	29/32	1/2	1-7/16	1-3/32	3	9/16	9	Orange
IACL-2/0	2/0	2/0-1	29/32	1/2	1-7/16	1-9/32	3-3/16	9/16	12	White
IACL-3/0	3/0	3/0-1	29/32	1/2	1-7/16	1-9/32	3-3/16	9/16	12	White
IACL-4/0	4/0	4/0-1	29/32	1/2	1-7/16	1-9/32	3-3/16	9/16	12	White
IACL-250	250kcmil	250kcmil-1/0	29/32	1/2	1-7/16	1-9/32	3-3/16	9/16	12	White
IACL-300	300kcmil	300kcmil-2/0	1-1/4	1/2	1-3/4	1-5/16	3-11/16	9/16	14	Blue
IACL-350	350kcmil	350kcmil-3/0	1-1/4	1/2	1-3/4	1-5/16	3-11/16	9/16	14	Blue
IACL-500	500kcmil	500kcmil-4/0	1-1/4	1/2	1-3/4	1-5/16	3-11/16	9/16	14	Blue
IACL-600	600kcmil	600kcmil-250kcmil	1-19/32	1/2	3-3/16	1-5/8	5-3/4	9/16	18	Yellow

Tooling Information

Catalog Number	Color	ILSCO					Burdyn								Thomas & Betts			Anderson
		Die Index	ILC-12-N ILC-12H-N 12 Ton	ILCB-12-N ILCB-12-L10	ILC-15H	IDT-12-N Dieless	Die Index	Y34A	Y35	Y39	Y45	Y46	Y48B	Y644M Dieless	Die Index	13642 12 Ton	TBM 15 15 Ton	21940 40 Ton
IACL-4	Orange	9	(3)	(3)	(2)	(1)	297	(2)	(2)	(2)	(2)	(2)	(1)	50	(2)	(2)	(2)	(2)
IACL-2	Orange	9	(3)	(3)	(2)	(1)	297	(2)	(2)	(2)	(2)	(2)	(1)	50	(2)	(2)	(2)	(2)
IACL-1/0	Orange	9	(3)	(3)	(2)	(1)	297	(2)	(2)	(2)	(2)	(2)	(1)	50	(2)	(2)	(2)	(2)
IACL-2/0	White	12	(1)	(1)	(2)	(1)	324	(2)	(2)	(2)	(2)	(2)	(1)	71	(2)	(2)	(2)	(2)
IACL-2/0	White	12	(1)	(1)	(2)	(1)	324	(2)	(2)	(2)	(2)	(2)	(1)	71	(2)	(2)	(2)	(2)
IACL-2/0	White	12	(1)	(1)	(2)	(1)	324	(2)	(2)	(2)	(2)	(2)	(1)	71	(2)	(2)	(2)	(2)
IACL-250	White	12	(1)	(1)	(2)	(1)	324	(2)	(2)	(2)	(2)	(2)	(1)	71	(2)	(2)	(2)	(2)
IACL-300	Blue	14	(2)	(2)	(2)	(1)	299	-	(2)	(2)	(2)	(2)	(1)	87	(2)	(2)	(2)	(2)
IACL-350	Blue	14	(2)	(2)	(2)	(1)	299	-	(2)	(2)	(2)	(2)	(1)	87	(2)	(2)	(2)	(2)
IACL-500	Blue	14	(2)	(2)	(2)	(1)	299	-	(2)	(2)	(2)	(2)	(1)	87	(2)	(2)	(2)	(2)
IACL-600	Yellow	18	(3)	(3)	(3)	(1)	936	-	-	(3)	(3)	(3)	(1)	115	(3)	(3)	(3)	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207

Aluminum Compression Lugs

Dual Rated - Narrow Tang

Conductor Range: 1000kcmil-1/0

A


TYPE 2IACL

Features

- Manufactured from high strength aluminum alloy
- Four OD sizes accommodate a wire range from 1/0 to 1000 kcmil
- Chamfered barrel
- Prefilled with DE-OX
- Color coded end caps inserted in barrel and ink marked with die number and number of crimps
- Electro tin plated
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Requires only four installation dies to crimp eleven conductor sizes. Tang width remains constant within an OD size and is designed to fit transformer pads.
- Provides easy conductor insertion
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Provides low contact resistance
- Ensures reliability
- Application versatility



Catalog Number	Wire Size	Wire Range When Installed With IDT-12-N Tool	Tang Width	Bolt Size	Dimensions					IlSCO Die Index	Die Color Code
					D	E	F	C	J		
2IACL-1/0	1/0	1/0-1	1	1/2	1-1/2	3-1/4	5-3/16	9/16(2)	1-3/4	9	Orange
2IACL-2/0	2/0	2/0-1	1-1/4	1/2	1-7/8	3-1/4	5-3/4	9/16(2)	1-3/4	12	White
2IACL-3/0	3/0	3/0-1	1-1/4	1/2	1-7/8	3-1/4	5-3/4	9/16(2)	1-3/4	12	White
2IACL-4/0	4/0	4/0-1	1-1/4	1/2	1-7/8	3-1/4	5-3/4	9/16(2)	1-3/4	12	White
2IACL-250	250kcmil	250kcmil-1/0	1-1/4	1/2	1-7/8	3-1/4	5-3/4	9/16(2)	1-3/4	12	White
2IACL-300	300kcmil	300kcmil-2/0	1-1/4	1/2	2-3/8	3-1/4	6	9/16(2)	1-3/4	14	Blue
2IACL-350	350kcmil	350kcmil-3/0	1-1/4	1/2	2-3/8	3-1/4	6	9/16(2)	1-3/4	14	Blue
2IACL-500	500kcmil	500kcmil-4/0	1-1/4	1/2	2-3/8	3-1/4	6	9/16(2)	1-3/4	14	Blue
2IACL-600	600kcmil	600kcmil-250kcmil	1-39/64	1/2	3-3/16	3-1/4	7	9/16(2)	1-3/4	18	Yellow
2IACL-750	750kcmil	750kcmil-500kcmil	1-39/64	1/2	3-3/16	3-1/4	7-1/4	9/16(2)	1-3/4	18	Yellow
2IACL-1000	1000kcmil	1000kcmil-750kcmil	1-39/64	1/2	3-3/16	3-1/4	7-1/4	9/16(2)	1-3/4	18	Yellow

Tooling Information

Catalog Number	Color	ILSCO					Burdny								Thomas & Betts			Anderson
		Die Index	ILC-12-N ILC-12H-N 12 Ton	ILCB-12-N ILCB-12-LIO	ILC-15H	IDT-12-N Dieless	Die Index	Y34A	Y35	Y39	Y45	Y46	Y48B	Y644M Dieless	Die Index	13642 12 Ton	TBM 15 15 Ton	21940 40 Ton
2IACL-1/0	Orange	9	(3)	(3)	(2)	(1)	297	(2)	(2)	(2)	(2)	(2)	(1)	50	(2)	(2)	(2)	(2)
2IACL-2/0	White	12	(1)	(1)	(2)	(1)	324	(2)	(2)	(2)	(2)	(2)	(1)	71	(2)	(2)	(2)	(2)
2IACL-2/0	White	12	(1)	(1)	(2)	(1)	324	(2)	(2)	(2)	(2)	(2)	(1)	71	(2)	(2)	(2)	(2)
2IACL-250	White	12	(1)	(1)	(2)	(1)	324	(2)	(2)	(2)	(2)	(2)	(1)	71	(2)	(2)	(2)	(2)
2IACL-2/0	White	12	(1)	(1)	(2)	(1)	324	(2)	(2)	(2)	(2)	(2)	(1)	71	(2)	(2)	(2)	(2)
2IACL-300	Blue	14	(2)	(2)	(2)	(1)	299	-	(2)	(2)	(2)	(2)	(1)	87	(2)	(2)	(2)	(2)
2IACL-350	Blue	14	(2)	(2)	(2)	(1)	299	-	(2)	(2)	(2)	(2)	(1)	87	(2)	(2)	(2)	(2)
2IACL-500	Blue	14	(2)	(2)	(2)	(1)	299	-	(2)	(2)	(2)	(2)	(1)	87	(2)	(2)	(2)	(2)
2IACL-600	Yellow	18	(3)	(3)	(3)	(1)	936	-	-	(3)	(3)	(3)	(1)	115	(3)	(3)	(3)	-
2IACL-750	Yellow	18	(3)	(3)	(3)	(1)	936	-	-	(3)	(3)	(3)	(1)	115	(3)	(3)	(3)	-
2IACL-1000	Yellow	18	-	-	(3)	(1)	936	-	-	(3)	(3)	(3)	(1)	115	(3)	(3)	(3)	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207


TYPE AS

Features

- Electro-tin plated
- Manufactured from high strength aluminum alloy
- Chamfered barrel
- Color coded
- Center wire stop
- Clearly marked with wire size and die index for IlSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in each end
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Provides visual tooling recommendation for IlSCO or standard industry tools
- Prevents dissimilar metals from coming into contact and insures that conductors are fully inserted
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Application versatility



Catalog Number	Wire Size	Wire Range When Installed With IDT-12-N Tool	Die Color Code	L	Die Index	O.D.	I.D.
AS-8	8	8	Blue	1-3/16	2	5/16	5/32
AS-6	6	6	Gray	1-5/8	3	11/32	3/16
AS-4	4	4-6	Green	1-7/8	4	7/16	1/4
AS-2	2	2-6	Pink	2-3/8	7	17/32	5/16
AS-1	1	1-2	Gold	2-3/8	7	35/64	23/64
AS-1/0	1/0	1/0 - 1	Tan	2-3/8	8	39/64	25/64
AS-2/0	2/0	2/0 - 1	Olive	2-1/2	10	43/64	7/16

Tooling Information

Catalog Number	ILSCO								Burdny						Thomas & Betts				Anderson	Color Code
	ILC-12-N Die No. No. of Crimps	ILCB-12-N Die No. No. of Crimps	IDTB-6 Dieless No. of Crimps	IDT-6 6.2 Ton Dieless No. of Crimps	IDT-6H Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	MT-25 Hand Dieless No. of Crimps	94285 Left/Rt. Die/Die No. of Crimps	IDT-12-N Dieless No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	MY29-3 Hand Dieless No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps	TBM-8 Hand Tool No. of Crimps	
AS-8	ILD-2 (1)	ILD-2 (1)	-	-	ILD-2 (1)	-	M/K (2)	-	-	-	-	-	-	-	24	24 (1)	24 (2)	-	-	Blue
AS-6	ILD-3 (1)	ILD-3 (1)	(1)	(1)	ILD-3 (1)	(1)	K/K (2)	(1)	346 (1)	346 (1)	346 (1)	346 (1)	(1)	(1)	29 (2)	29 (2)	29 (2)	(2)	-	Gray
AS-4	ILD-4 (2)	ILD-4 (2)	(1)	(1)	ILD-4 (2)	(1)	H/H (3)	(1)	375 (1)	375 (1)	375 (1)	375 (1)	(1)	(1)	37 (2)	37 (2)	37 (2)	(2)	(1)	Green
AS-2	ILD-7 (1) ILD-6 (3)	ILD-7 (1) ILD-6 (3)	(2)	(2)	ILD-7 (1) ILD-6 (3)	(2)	E/A (3)	(1)	348 (1)	348 (1)	348 (1)	348 (1)	(2)	(1)	42 (2)	42H (4)	42 (2)	(2)	(1)	Pink
AS-1	ILD-7 (1) ILD-6 (4)	ILD-7 (1) ILD-6 (4)	(2)	(2)	ILD-7 (1) ILD-6 (4)	(2)	E/A (4)	(1)	471 (1)	471 (1)	471 (1)	471 (1)	(2)	(1)	45 (3)	45 (3)	45 (3)	(3)	(2)	Gold
AS-1/0	ILD-8 (1)	ILD-8 (2)	(2)	(2)	ILD-8 (2)	(2)	A/C (5)	(1)	296 (1)	296 (1)	296 (1)	296 (1)	(2)	(1)	50 (3)	50 (3)	50 (3)	(3)	(2)	Tan
AS-2/0	ILD-10 (1)	ILD-10 (2)	(2)	(2)	ILD-10 (1)	(2)	A/B (4)	(1)	297 (2)	297 (2)	297 (2)	297 (2)	(2)	(1)	54 (3)	54H (6)	54 (3)	(3)	(2)	Olive

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207

A


TYPE AS

Features

- Electro-tin plated
- Manufactured from high strength aluminum alloy
- Chamfered barrel
- Color coded
- Center wire stop
- Clearly marked with wire size and die index for IlSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in each end
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Provides visual tooling recommendation for IlSCO or standard industry tools
- Prevents dissimilar metals from coming into contact and insures that conductors are fully inserted
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Application versatility



Catalog Number	Wire Size	Wire Range When Installed With IDT-12-N Tool	Die Color Code	L	Die Index	O.D.	I.D.
AS-3/0	3/0	3/0-1	Ruby	2-5/8	10	49/64	1/2
AS-4/0	4/0	4/0-1	White	3-11/16	12	55/64	9/16
AS-250	250kcmil	250kcmil-1/0	Red	3-15/16	13	59/64	39/64
AS-300	300kcmil	300kcmil-2/0	Blue	4-1/16	14	1-1/64	21/32
AS-350	350kcmil	350kcmil-3/0	Brown	5-1/16	14	1-7/64	23/32
AS-400	400kcmil	400kcmil-4/0	Green	5-1/16	16	1-3/16	49/64
AS-500	500kcmil	500kcmil-4/0	Pink	5-1/16	16A	1-5/16	55/64

Tooling Information

Catalog Number	ILSCO								Burdny				Thomas & Betts				Anderson	Color Code		
	ILC-12-N ILC-12H-N Die No. No. of Crimps	ILCB-12-N ILCB-12-LIO Die No. No. of Crimps	IDTB-6 IDTB-6-LIO Dieless No. of Crimps	IDT-6, IDT-6H 6.2 Ton Dieless No. of Crimps	ILC-15H Die No. No. of Crimps	MT-25 Hand Dieless No. of Crimps	94285 Left/Rt. Die/Die No. of Crimps	IDT-12-N Dieless No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	MY29-3 Hand Dieless No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps		TBM-8 Hand Tool No. of Crimps	Versa Crimp Dieless No. of Crimps
AS-3/0	ILD-10 (2)	ILD-10 (2)	- (3)	- (3)	ILD-10 (2)	- (2)	A/A (4)	- (1)	467 (2)	467 (2)	467 (2)	467 (2)	- (2)	- (1)	60 (3)	60 (3)	60 (3)	- (3)	- (2)	Ruby
AS-4/0	ILD-12 (1)	ILD-12 (1)	- (3)	- (3)	ILD-12 (1)	- (2)	- (2)	- (2)	298 (2)	298 (2)	298 (2)	298 (2)	- (2)	- (1)	66H (4)	66 (2)	66 (2)	- (5)	- (3)	White
AS-250	ILD-13 (2)	ILD-13 (2)	- (3)	- (3)	ILD-13 (2)	- (2)	- (2)	- (2)	324 (2)	324 (2)	324 (2)	324 (2)	- (1)	- (1)	71H (4)	71H (4)	71 (2)	- (5)	- (3)	Red
AS-300	ILD-14 (2)	ILD-14 (2)	- (4)	- (4)	ILD-14 (2)	- (2)	- (2)	- (2)	470 (2)	470 (2)	470 (2)	470 (2)	- (1)	- (1)	76H (4)	76 (2)	76 (2)	- (5)	- (3)	Blue
AS-350	ILD-14 (2)	ILD-14 (2)	- (4)	- (4)	ILD-14 (2)	- (2)	- (2)	- (2)	299 (2)	299 (2)	299 (2)	299 (2)	- (1)	- (1)	87H (4)	87H (4)	87 (2)	- (6)	- (3)	Brown
AS-400	ILD-16 (3)	ILD-16 (3)	- (4)	- (4)	ILD-16 (3)	- (2)	- (2)	- (2)	472 (4)	472 (4)	472 (4)	472 (4)	- (1)	- (1)	94H (4)	94H (4)	94 (2)	- (4)	- (4)	Green
AS-500	ILD-16A (3)	ILD-16A (3)	- (4)	- (4)	ILD-16A (3)	- (2)	- (2)	- (2)	300 (4)	300 (4)	300 (4)	300 (4)	- (1)	- (1)	99H (4)	99H (4)	99 (2)	- (4)	- (4)	Pink

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207


TYPE AS

Features

- Electro-tin plated
- Manufactured from high strength aluminum alloy
- Chamfered barrel
- Color coded
- Center wire stop
- Clearly marked with wire size and die index for IlSCO tools, proper number and location of crimps
- Prefilled with DE-OX
- Color coded end caps inserted in each end
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides low contact resistance
- Provides maximum conductivity and excellent crimping characteristics
- Provides easy conductor insertion
- Provides visual tooling recommendation for IlSCO or standard industry tools
- Prevents dissimilar metals from coming into contact and insures that conductors are fully inserted
- Provides easy identification and tooling recommendation
- Prevents oxides from forming
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die
- Application versatility



Catalog Number	Wire Size	Wire Range When Installed With IDT-12-N Tool	Die Color Code	L	Die Index	O.D.	I.D.
AS-600	600kcmil	600kcmil-250kcmil	Black	5-5/16	17	1-5/16	59/64
AS-700	700kcmil	700kcmil-350kcmil	Purple	5-13/16	17	1-13/32	1
AS-750	750kcmil	750kcmil-500kcmil	Yellow	5-13/16	18	1-29/64	1-1/32
AS-1000	1000kcmil	1000kcmil-750kcmil	Brown	7-1/8	20	1-53/64	1-3/16

Tooling Information

Catalog Number	ILSCO						Burdny					Thomas & Betts				Anderson	Color Code
	ILC-12-N Die No. No. of Crimps	ILCB-12-N Die No. No. of Crimps	IDTB-6 Dieless No. of Crimps	IDT-6, IDT-6H 6.2 Ton Dieless No. of Crimps	ILC-15H Die No. No. of Crimps	IDT-12-N Dieless No. of Crimps	Y-35 Die Index No. of Crimps	Y-39 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps	Y644M Dieless No. of Crimps	13642 12 Ton Die Index No. of Crimps	TBM 15 15 Ton Die Index No. of Crimps	21940 40 Ton Die Index No. of Crimps	TBM Hand Tool No. of Crimps	Versa Crimp Dieless No. of Crimps	
AS-600	ILD-17 (4)	ILD-17 (4)	- (4)	- (4)	ILD-17 (4)	- (2)	473 (4)	473 (4)	473 (4)	473 (4)	- (1)	106H (4)	106 (2)	106 (2)	-	- (4)	Black
AS-700	ILD-17 (4)	ILD-17 (4)	- (4)	- (4)	ILD-17 (4)	- (2)	-	936 (4)	936 (4)	936 (4)	- (1)	112H (4)	112H (4)	112 (2)	-	-	Purple
AS-750	ILD-18 (5)	ILD-18 (5)	- (4)	- (4)	ILD-18 (5)	- (2)	-	936 (4)	936 (4)	936 (4)	- (1)	115H (4)	115H (4)	115 (2)	-	-	Yellow
AS-1000	-	-	-	-	- (3)	- (2)	-	-	-	-	- (1)	-	140H (4)	140 (2)	-	-	Brown

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207

A

TYPE UCS

Features

- Manufactured from high strength aluminum alloy, 90° C
- Four OD sizes accommodate a wire range from 1000kcmil to #4
- Chamfered barrel
- Prefilled with DE-OX
- Solid barrier in center
- Color coded end caps inserted in barrel

Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Requires only four installation dies to crimp fourteen conductor sizes.
- Provides easy conductor insertion
- Prevents oxides from forming
- Prevents dissimilar metals from coming into contact
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die



Catalog Number	Wire Range	Dimensions			Installing Dies	Die Index
		L	O.D.	I.D.		
UCS-4-Z	4	3"	41/64	9/32	BG, 5/8, 8A	9
UCS-2-Z	2	3"	41/64	11/32	BG, 5/8, 8A	9
UCS-1/0-Z	1/0	3"	41/64	27/64	BG, 5/8, 8A	9
UCS-2/0-Z	2/0	4"	29/32	7/16	249, 840, TX, 76, 11A	13
UCS-3/0-Z	3/0	4"	29/32	1/2	249, 840, TX, 76, 11A	13
UCS-4/0-Z	4/0	4"	29/32	9/16	249, 840, TX, 76, 11A	13
UCS-250-Z	250kcmil	4"	29/32	19/32	249, 840, TX, 76, 11A	13
UCS-300-Z	300kcmil	5"	1-5/32	21/32	299, 655, 705, 1-1/8, 13A	14
UCS-350-Z	350kcmil	5"	1-5/32	45/64	299, 655, 705, 96, 1-1/8, 13A	14
UCS-500-Z	500kcmil	5"	1-5/32	27/32	299, 655, 705, 96, 1-1/8, 13A	14
UCS-600-Z	600kcmil	6"	1-39/64	59/64	301, 1-1/2, 140	18
UCS-700/750-Z	750kcmil - 700kcmil	6"	1-39/64	1-1/32	301, 1-1/2, 140, 72H	18
UCS-1000-Z	1000kcmil	7"	1-39/64	1-3/16	301, 1-1/2, 140, 72H	18

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)


TYPE PICS

Features

- Pre-insulated
- Concave polyethylene end caps
- Dual rated
- Meets ANSI C119.4 requirements
- RUS Listed
- Die Index 5/8 or BG

Benefits

- Fast, easy installation
- Seal out dirt but are easily pierced when inserting conductor
- For use with aluminum-aluminum and aluminum-copper conductors
- Ensures reliability



Catalog Number	End "A"					End "B"					Color Code
	Conductor Range				Color Code	Conductor Range					
	ACSR	AWG	Diameter			ACSR	AWG	Diameter			
			max.	min.			max.	min.			
PICS-61	-	6 sol - 8 str	0.162	0.144	Green	-	6 sol - 8 str	0.162	0.144	Green	
PICS-62	6	4 sol - 6 str	0.204	0.184	Blue	-	8 sol - 10 str	0.128	0.114	Brown	
PICS-63	6	4 sol - 6 str	0.204	0.184	Blue	-	6 sol - 8 str	0.162	0.144	Green	
PICS-64	6	4 sol - 6 str	0.204	0.184	Blue	6	4 sol - 6 str	0.204	0.184	Blue	
PICS-65	4	2 sol - 3-4 str	0.258	0.213	Orange	-	8 sol - 10 str	0.128	0.114	Brown	
PICS-66	4	2 sol - 3-4 str	0.258	0.213	Orange	-	6 sol - 8 str	0.162	0.144	Green	
PICS-67	4	2 sol - 3-4 str	0.258	0.213	Orange	6	4 sol - 6 str	0.204	0.184	Blue	
PICS-68	4	2 sol - 3-4 str	0.258	0.213	Orange	4	2 sol - 3-4 str	0.258	0.213	Orange	
PICS-70	2	1-2 str	0.328	0.268	Red	-	6 sol - 8 str	0.162	0.144	Green	
PICS-71	2	1-2 str	0.328	0.268	Red	6	4 sol - 6 str	0.204	0.184	Blue	
PICS-72	2	1-2 str	0.328	0.268	Red	4	2 sol - 3-4 str	0.258	0.213	Orange	
PICS-73	2	1-2 str	0.328	0.268	Red	2	1-2 str	0.328	0.268	Red	
PICS-75	1/0	1/0	0.398	0.368	Yellow	6	4 sol - 6 str	0.204	0.184	Blue	
PICS-76	1/0	1/0	0.398	0.368	Yellow	4	2 sol - 3-4 str	0.258	0.213	Orange	
PICS-77	1/0	1/0	0.398	0.368	Yellow	2	2-1 str	0.328	0.268	Red	
PICS-78	1/0	1/0	0.398	0.368	Yellow	-	1/0	0.398	0.368	Yellow	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

A



TYPE P840

Features

- Pre-insulated
- Concave polyethylene end caps
- Dual rated
- Meets ANSI C119.4 requirements
- RUS Listed
- Die Index 840

Benefits

- Fast, easy installation
- Seal out dirt but are easily pierced when inserting conductor
- For use with aluminum-aluminum and aluminum-copper conductors
- Ensures reliability



Catalog Number	End "A"					End "B"					Color Code
	Conductor Range				Color Code	Conductor Range					
	ACSR	AWG	Diameter			ACSR	AWG	Diameter			
			max.	min.				max.	min.		
PICS-834	1/0	2/0 (compact) or 1/0	0.398	0.365	Yellow	4	2 sol - 3-4 str	0.258	0.213	Orange	
PICS-835	1/0	2/0 (compact) or 1/0	0.398	0.365	Yellow	2	1-2 str	0.328	0.268	Red	
PICS-836	1/0	2/0 (compact) or 1/0	0.398	0.365	Yellow	1/0	2/0 (compact) or 1/0	0.398	0.365	Yellow	
PICS-844	2/0	3/0 (compact) or 2/0	0.448	0.414	Gray	4	2 sol - 3-4 str	0.258	0.213	Orange	
PICS-845	2/0	3/0 (compact) or 2/0	0.448	0.414	Gray	2	1-2 str	0.328	0.268	Red	
PICS-846	2/0	3/0 (compact) or 2/0	0.448	0.414	Gray	1/0	2/0 (compact) or 1/0	0.398	0.365	Yellow	
PICS-847	2/0	3/0 (compact) or 2/0	0.448	0.414	Gray	2/0	3/0 (compact) or 2/0	0.448	0.414	Gray	
PICS-854	3/0	4/0 (compact) or 3/0	0.502	0.464	Black	4	2 sol - 3-4 str	0.258	0.213	Orange	
PICS-855	3/0	4/0 (compact) or 3/0	0.502	0.464	Black	2	1-2 str	0.328	0.268	Red	
PICS-856	3/0	4/0 (compact) or 3/0	0.502	0.464	Black	1/0	2/0 (compact) or 1/0	0.398	0.365	Yellow	
PICS-857	3/0	4/0 (compact) or 3/0	0.502	0.464	Black	2/0	3/0 (compact) or 2/0	0.448	0.414	Gray	
PICS-858	3/0	4/0 (compact) or 3/0	0.502	0.464	Black	3/0	4/0 (compact) or 3/0	0.502	0.464	Black	
PICS-864	4/0	4/0	0.564	0.522	Pink	4	2 sol - 3-4 str	0.258	0.213	Orange	
PICS-865	4/0	4/0	0.564	0.522	Pink	2	1-2 str	0.328	0.268	Red	
PICS-866	4/0	4/0	0.564	0.522	Pink	1/0	1/0	0.398	0.365	Yellow	
PICS-867	4/0	4/0	0.564	0.522	Pink	2/0	3/0 (compact) or 2/0	0.448	0.414	Gray	
PICS-868	4/0	4/0	0.564	0.522	Pink	3/0	4/0 (compact) or 3/0	0.502	0.464	Black	
PICS-869	4/0	4/0	0.564	0.522	Pink	4/0	4/0	0.564	0.522	Pink	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE AH

Features

- Prefilled with oxide inhibitor
- Color coded
- Manufactured from high strength aluminum alloy
- UL Listed
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides corrosion resistance
- Provides visual recommendation for ILSCO or standard industry tools
- Provides maximum conductivity and excellent crimping characteristics
- Ensures reliability for copper or aluminum conductors
- Application versatility



Catalog Number	Wire Range		IlSCO Compression Tool	Die Index	L	W
	Main	Tap				
AH-1	1/0 str - 6 str	1 str - 6 str	ND-58/ND-60	0	1.62	1.78
AH-2	4/0 str - 1 str	1 str - 6 str	ND-58/ND-60	D3	1.88	2.31
AH-3	4/0 str - 3/0 str	4/0 str - 3/0 str	ND-58/ND-60	D3	2.50	2.50
AH-4	4/0 str - 1 str	2/0 str - 1 str	ND-58/ND-60	D3	2.50	2.38
AH-5	400kcmil - 4/0 str	400kcmil - 4/0 str	ILC-15H*	N	3.50	3.09
AH-6	500kcmil - 4/0 str	2/0 str - 6 str	ILC-15H*	N	2.00	2.84
AH-8	600kcmil - 350kcmil	350kcmil - 2/0 str	ILC-15H*	KR	3.50	4.50
AH-10	1000kcmil Compact - 600kcmil AL 750kcmil - 600kcmil CU	350kcmil - 2/0 str	ILC-15H*	KR	3.50	4.62
AH-11	1000kcmil Compact - 600kcmil AL 750kcmil - 600kcmil CU	600kcmil - 350kcmil	ILC-15H*	KR	4.62	4.75

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*Other hydraulic tools can be used. See stuffer sheet for complete information on tooling.

Tested to UL 486A/B, UL File E6207



A TYPE HT

Features

- Serrated interior
- Prefilled with oxide inhibitor
- Installed with industry standard "O" and "D" dies
- Manufactured from high strength aluminum alloy
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Assures positive mating with cable strands when compressed
- Provides corrosion resistance
- Provides convenient die selection
- Provides maximum conductivity and excellent crimping characteristics
- Application versatility



Catalog Number	Wire Range										Program Number	Connector Die	No. of Crimps		Dimensions		
	Standard Wire						Compact Wire						Mech. Tool	Hyd. Tool	L	W	H
	A Groove ACSR		sol		B Groove		A Groove ACSR		B Groove ACSR								
HT-6	2, 3, 4, 6, -	1, 2, 3, 4, 6, -	1, 2, 3, 4, 6, -	2, 3, 4, 6, -	1, 2, 3, 4, 6, -	1, 2, 3, 4, 6, -	1, 2, 3, 4, 6, -	1, 2, 3, 4, 6, -	1, 2, 3, 4, 6, -	1, 2, 3, 4, 6, -	1	O O O O O	4 4 4 4 4	2 2 2 2 2	1-1/2	23/32	1-23/32
HT-8	1/0, 1, 2, 3, -	2/0, 1/0, 1, 2, -	3/0, 2/0, 1/0, 1, -	2, 3, 4, 6, -	1, 2, 3, 4, 6, -	1/0, 1, 2, 3, 4, 6, -	2/0, 1/0, 1, 2, -	2/0, 1/0, 1, 2, -	1, 2, 3, 4, 6, -	1, 2, 3, 4, 6, -	2	O O O O O	5 5 5 5 5	2 2 2 2 2	1-1/2	45/64	1-25/32
HT-2	2/0, 1/0, -	3/0, 2/0, -	-	2, 3, 4, 6, -	1, 2, 3, 4, 6, -	1/0, 1, 2, 3, 4, 6, -	3/0, 2/0, -	3/0, -	1, 2, 4, 6, -	1, 2, 4, 6, -	3	D3 D3 D3 D3	5 5 5 5	2 2 2 2	1-7/8	13/16	2-3/16
HT-4	2/0, 1/0, 1, -	3/0, 2/0, 1/0, -	-	2/0, 1/0, 1, -	3/0, 2/0, 1/0, -	-	3/0, 2/0, 1/0, -	3/0, 2/0, 1/0, -	3/0, 2/0, 1/0, -	3/0, 2/0, 1/0, -	4	D3 D3 D3	6 6 6	2 2 2	1-7/8	57/64	2-17/64
HT-3	4/0, 3/0, -	4/0, -	-	2, 3, 4, 6, -	1, 2, 3, 4, 6, -	1/0, 1, 2, 3, 4, 6, -	266, 250, 4/0, -	266, 250, 4/0, -	1, 2, 4, 6, -	1, 2, 4, 6, -	5	D3 D3 D3 D3	5 5 5 5	2 2 2 2	1-7/8	53/64	2-1/4
HT-5	4/0, 3/0, -	4/0, 3/0, -	-	2/0, 1/0, -	2/0, 1/0, -	-	266, 4/0, 3/0, -	266, 250, 4/0, -	2/0, 1/0, -	3/0, 2/0, 1/0, -	6	D3 D3 D3	7 7 7	3 3 3	2-1/4	53/64	2-3/8
HT-7	4/0, 3/0, -	4/0, 3/0, -	-	4/0, 3/0, -	4/0, 3/0, -	-	266, 4/0, 3/0, -	266, 250, 4/0, -	266, 4/0, 3/0, -	266, 250, 4/0, -	7	D3 D3 D3	7 7 7	3 3 3	2-1/2	7/8	2-1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Consult factory for tool and die information.


TYPE RLT

Features

- Prefilled with oxide inhibitor and bagged
- Clearly marked with wire size and die index
- UL Listed and CSA Certified for direct burial in earth or concrete
- Range taking
- Manufactured from high strength copper alloy

Benefits

- Prevents oxides from forming
- Provides easy identification and tooling recommendation
- Ensures reliability
- Reduces inventory
- Provides maximum conductivity and eliminates the possibility of corrosion



Catalog Number	Ground Rod Size	Wire Range	Die Index	Dimensions	
				H	L
RLT-2	1/2	2 (.292 Dia.) - 2/0 (.419 Dia.)	998/1011	1.94	.88
RLT-3	5/8	2 (.292 Dia.) - 2/0 (.419 Dia.)	998/1011	1.97	.88
RLT-4	3/4	2 (.292 Dia.) - 2/0 (.419 Dia.)	998/1011	2.19	.88
RLT-5	1/2	4/0 (.528 Dia.) - 250kcmil (.575 Dia.)	998/1011	1.94	.88
RLT-6	5/8	4/0 (.528 Dia.) - 250kcmil (.575 Dia.)	998/1011	2.14	.88
RLT-7	3/4	4/0 (.528 Dia.) - 250kcmil (.575 Dia.)	998/1011	2.19	.88
RLT-8	5/8	300kcmil (.630 Dia.) - 500kcmil (.813 Dia.)	998/1011	2.14	.88
RLT-9	3/4	300kcmil (.630 Dia.) - 500kcmil (.813 Dia.)	998/1011	2.44	.88

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587

A

Tooling Information

Compression Terminals ASxx and ALxx	ILSCO TOOLS			BURNDY TOOLS		
	Die Code	ILC-15H, ILC-15 15 Ton ILC-30H 30 Ton	IDT-12-N 15 Ton Dieless	Die Code	Y46, Y46C	Y644M, PAT644 15 Ton Dieless
1000	(P) 302	3*	1*	P44ART	3*	1*

RANGE TAKING

Lug Size	Standard Wire Size	Expanded Wire Size	No. Crimps for ILSCO IDT-12-N and Burndy Y644M
1000	1000kcmil	1000kcmil-750kcmil	1*

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* See note d) below

- a) The ASxx and ALxx connectors are marked with the die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly space or connector.
- b) Dieless tools are not color coded or do not contain the die index.
- c) Strip length = Barrel Length + 1/16 inch.
- d) For long barrel connectors, add 1 additional crimp.



Series CS, CL Compression Connectors for Class B/C Copper Wire Only



ILSCO TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire
Hydraulic Tools

A

Lug Size	Class B/C Wire Size	Color Code	Die Index	Manual Hand Tools						IDT-6, IDT-6H 6.2 Ton Dieless, IDTB-6, IDTB-6-LIO 6.2 Ton Dieless Battery	ILC-12-N, ILC-12H-N, ILC-12, ILC-12H, ILC-14, ILC-14H 12 Ton, ILCB-12-N, ILCB-12, ILCB-12-LIO 12 Ton Battery	IDT-12-N 15 Ton Dieless	IDT-12, IDT-12H, IDTB-12 11 Ton Dieless	ILC-15H 15 Ton, ILC-30H 30 Ton	ILC-750
				94285			MT-25	ILC-10-N							
				Left Die	Right Die	Crimps	Crimps	Index	Crimps						
8	8 AWG	Red	21	M	K	2	1	Red	1					1	1
6	6 AWG	Blue	24	K	K	2	1	Blue	2	1	1			1	1
5	5 AWG	Blue	24	K	K	2	1	Blue	2	1	1			1	1
4	4 AWG	Gray	29	K	K	2	1	Gray	2	1	1	1	1	1	1
3	3 AWG	White	29	K	K	2	1	Gray	2	1	1	1	1	1	1
2	2 AWG	Brown	33	H	H	2	2	Brown	2	1	1	1	1	1	1
1	1 AWG	Green	37	H	H	2	2	Green	2	1	1	1	1	1	1
1/0	1/0 AWG	Pink	42	E	A	2	2	Pink	4	1	1	1	1	1	1
2/0	2/0 AWG	Black	45	E	A	3	2			1	1	1	1	1	1
3/0	3/0 AWG	Orange	50	A	C	3	2			2	1	1	1	1	1
4/0	4/0 AWG	Purple	54	A	B	3	2			2	1	1	1	1	1
250	250kcmil	Yellow	62	A	A	3	2			2	1	1	1	1	1
300	300kcmil	White	66							2	2	1	1	2	2
350	350kcmil	Red	71							2	2	1	1	2	2
400	400kcmil	Blue	76							2	2	1	1	2	2
500	500kcmil	Brown	87							2	2	1	1	2	2
600	600kcmil	Green	94							2	2	1	1	2	2
700	700kcmil	Pink	99							3	2	1	1	2	2
750	750kcmil	Black	106							3	2	1	1	2	2
1000	1000kcmil	White	125								2	1	1	2	2

RANGE TAKING

Lug Size	Standard Wire Size	Expanded Wire Size	No. Crimps for ILSCO IDT-12, IDT-12-N and Burndy Y644M, PAT644	No. Crimps for ILSCO IDTB-6, IDTB-6-LIO, IDT-6 and IDT-6H
4	4 AWG	4 - 6 AWG		1
3	3 AWG	3 - 6 AWG	1	1
2	2 AWG	2 - 6 AWG	1	1
1	1 AWG	1 - 6 AWG	1	1
1/0	1/0 AWG	1/0 - 6 AWG	1	1
2/0	2/0 AWG	2/0 - 4 AWG	1	1
3/0	3/0 AWG	3/0 - 2 AWG	1	2
4/0	4/0 AWG	4/0 - 1 AWG	1	2
250	250kcmil	250kcmil - 1/0 AWG	1	2
300	300kcmil	300kcmil - 2/0 AWG	1	2
350	350kcmil	350kcmil - 3/0 AWG	1	2
400	400kcmil	400kcmil - 4/0 AWG	1	2
500	500kcmil	500kcmil - 250kcmil	1	2
600	600kcmil	600kcmil - 250kcmil	1	2
700	700kcmil	700kcmil - 350kcmil	1	3
750	750kcmil	750kcmil - 500kcmil	1	3
1000	1000kcmil	1000kcmil - 750kcmil	1	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL Listed and CSA Certified when installed with tools and dies shown above

- Connectors are marked with color, die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- Strip Length = Barrel Length + 1/16 Inch
- For long barrel connectors double the amount of crimps indicated on chart except for 1000kcmil add only one additional crimp.



ILSCO TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire

Hydraulic Tools

Lug Size	Class B/C Wire Size	Color Code	Die Index	Manual Hand Tools						IDT-6, IDT-6H 6.2 Ton Dieless, IDTB-6 IDTB-6-LIO 6.2 Ton Dieless Battery	ILC-12-N, ILC-12H-N, ILC-12, ILC-12H, ILC-14, ILC-14H 12 Ton, ILCB-12-N, ILCB-12, ILCB-12-LIO 12 Ton Battery	IDT-12-N 15 Ton Dieless	IDT-12, IDTB-12 11 Ton Dieless	ILC-15H 15 Ton, ILC-30H 30 Ton
				94285			MT-25	ILC-10-N						
				Left Die	Right Die	Crimps	Crimps	Index	Crimps					
8	8 AWG	Red	21	M	K	2	1	Red	1				1	
6	6 AWG	Blue	24	K	K	2	1	Blue	2	1		1	1	
5	5 AWG	Blue	24	K	K	2	1	Blue	2	1		1	1	
4	4 AWG	Gray	29	K	K	2	1	Gray	2	1	1	1	1	
3	3 AWG	White	29	K	K	2	1	Gray	2	1	1	1	1	
2	2 AWG	Brown	33	H	H	2	2	Brown	2	1	1	1	1	
1	1 AWG	Green	37	H	H	2	2	Green	2	1	1	1	1	
1/0	1/0 AWG	Pink	42	E	A	2	2	Pink	4	1	1	1	1	
2/0	2/0 AWG	Black	45	E	A	3	2			1	1	1	1	
3/0	3/0 AWG	Orange	50	A	C	3	2			2	1	1	1	
4/0	4/0 AWG	Purple	54	A	B	3	2			2	1	1	1	
250	250kcmil	Yellow	62	A	A	3	2			2	1	1	1	
300	300kcmil	White	66							2	2	1	2	
350	350kcmil	Red	71							2	2	1	2	
400	400kcmil	Blue	76							2	2	1	2	
500	500kcmil	Brown	87							2	2	1	2	
600	600kcmil	Green	94							2	2	1	2	
700	700kcmil	Pink	99							3	2	1	2	
750	750kcmil	Black	106							3	2	1	2	
1000	1000kcmil	White	125								2	1	2	

RANGE TAKING

Lug Size	Standard Wire Size	Expanded Wire Size	No. Crimps for ILSCO IDT-12, IDT-12-N and Burndy Y644M, PAT644	No. Crimps for ILSCO IDTB-6, IDTB-6-LIO, IDT-6 and IDT-6H
4	4 AWG	4 - 6 AWG		1
3	3 AWG	3 - 6 AWG	1	1
2	2 AWG	2 - 6 AWG	1	1
1	1 AWG	1 - 6 AWG	1	1
1/0	1/0 AWG	1/0 - 6 AWG	1	1
2/0	2/0 AWG	2/0 - 4 AWG	1	1
3/0	3/0 AWG	3/0 - 2 AWG	1	2
4/0	4/0 AWG	4/0 - 1 AWG	1	2
250	250kcmil	250kcmil - 1/0 AWG	1	2
300	300kcmil	300kcmil - 2/0 AWG	1	2
350	350kcmil	350kcmil - 3/0 AWG	1	2
400	400kcmil	400kcmil - 4/0 AWG	1	2
500	500kcmil	500kcmil - 250kcmil	1	2
600	600kcmil	600kcmil - 250kcmil	1	2
700	700kcmil	700kcmil - 350kcmil	1	3
750	750kcmil	750kcmil - 500kcmil	1	3
1000	1000kcmil	1000kcmil - 750kcmil	1	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL Listed and CSA Certified when installed with tools and dies shown above

- a) Number of crimps shown on chart must be on each end of the CT splicer connectors.
- b) The CT connectors are marked with color, the die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- c) The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- d) For long barrel (CTL) connectors add one additional crimp to each side of barrel.

ILSCO TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire



Hydraulic Tools

Lug Size	Fine Strand Wire Size	Approved Wire Classes	Color Code	Die Index	Manual Hand Tools					Hydraulic Tools					
					94285			ILC-10-N		IDT-6, IDT-6H 6.2 Ton Dieless, IDTB-6 IDTB-6-LIO 6.2 Ton Dieless Battery	ILC-12-N, ILC-12H-N, ILC-12, ILC-12H, ILC-14, ILC-14H 12 Ton, ILCB-12-N, ILCB-12, ILCB-12-LIO 12 Ton Battery	IDT-12-N 15 Ton Dieless	IDT-12, IDT-12H, IDTB-12 11 Ton Dieless	ILC-15H 15 Ton, ILC-30H 30 Ton	ILC-750
					Left Die	Right Die	Crimps	Index	Crimps						
8	8	G,H,I,K,M,DLO	Red	21				Red	1		1			1	1
5	6	G,H,I,K,M,DLO	Blue	24				Blue	2		1			1	1
3	4	G,H,I,K,M,DLO	White	29	K	K	2	Gray	2	1	1	1	1	1	1
1	2	G,H,I,K,M,DLO	Green	37	H	H	2	Green	2	1	1	1	1	1	1
1/0	1	G,H,I,K,M,DLO	Pink	42	H	H	2	Pink	4	1	1	1	1	1	1
2/0	1/0	G,H,I,K,M,DLO	Black	45	E	A	3			1	1	1	1	1	1
3/0	2/0	G,H,I,K,M,DLO	Orange	50	E	A	3			1	1	1	1	1	1
4/0	3/0	G,H,I,K,M,DLO	Purple	54	A	B	3			1	1	1	1	1	1
250	4/0	G,H,I,K,M,DLO	Yellow	62	A	B	3			1	1	1	1	1	1
300	250	G,H	White	66						1	2	1	1	2	2
350	250	I,K,M	Red	71						1	2	1	1	2	2
350	262	DLO	Red	71						1	2	1	1	2	2
400	300	G,H,I,K,M	Blue	76						2	2	1	1	2	2
400	313	DLO	Blue	76						2	2	1	1	2	2
500	350	G,H,I,K,M	Brown	87						2	2	1	1	2	2
500	373	DLO	Brown	87						2	2	1	1	2	2
600	400	G,H,I,K,M	Green	94						2	2	1	1	2	2
600	444	DLO	Green	94						2	2	1	1	2	2
700	500	G,H,I,K,M	Pink	99						3	2	1	1	2	2
700	535	DLO	Pink	99						3	2	1	1	2	2
750	600	G,H,I,M	Black	106						3	2	1	1	2	2
750	646	DLO	Black	106						3	2	1	1	2	2
1000	750	G,H,I	White	125							3	1	1	3	
1000	777	DLO	White	125							3	1	1	3	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL Listed and CSA Certified when installed with tools and dies shown above

- a) Connectors are marked with color, die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- b) The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- c) Strip Length = Barrel Length + 1/16 Inch
- d) For long barrel connectors double the amount of crimps indicated on chart except for 1000kcmil add only one additional crimp.

ILSCO TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire

Hydraulic Tools

Lug Size	Fine Strand Wire Size	Approved Wire Classes	Color Code	Die Index	Manual Hand Tools					IDT-6, IDT-6H 6.2 Ton Dieless, IDTB-6 ICB-6-LIO 6.2 Ton Dieless Battery	ILC-12-N, ILC-12H-N, ILC-12, ILC-12H, ILC-14, ILC-14H 12 Ton, ILCB-12-N, ILCB-12, ILCB-12-LIO 12 Ton Battery	IDT-12-N 15 Ton Dieless	IDT-12H, IDTB-12 11 Ton Dieless	ILC-15H 15 Ton, ILC-30H 30 Ton						
					94285			ILC-10-N							Crimps	Crimps	Crimps	Crimps	Crimps	Crimps
					Left Die	Right Die	Crimps	Index	Crimps											
8	8	G,H,I,K,M,DLO	Red	21	M	K	2	Red	1		1			1						
5	6	G,H,I,K,M,DLO	Blue	24	K	K	2	Blue	2		1			1						
3	4	G,H,I,K,M,DLO	White	29	K	K	2	Gray	2	1	1			1						
1	2	G,H,I,K,M,DLO	Green	37	H	H	2	Green	2	1	1	1	1	1						
1/0	1	G,H,I,K,M,DLO	Pink	42	H	H	2	Pink	4	1	1	1	1	1						
2/0	1/0	G,H,I,K,M,DLO	Black	45	E	A	3			1	1	1	1	1						
3/0	2/0	G,H,I,K,M,DLO	Orange	50	E	A	3			2	1	1	1	1						
4/0	3/0	G,H,I,K,M,DLO	Purple	54	A	B	3			2	1	1	1	1						
250	4/0	G,H,I,K,M,DLO	Yellow	62	A	B	3			2	1	1	1	1						
300	250	G,H	White	66						2	2	1	1	2						
350	250	I,K,M	Red	71						2	2	1	1	2						
350	262	DLO	Red	71						2	2	1	1	2						
400	300	G,H,I,K,M	Blue	76						2	2	1	1	2						
400	313	DLO	Blue	76						2	2	1	1	2						
500	350	G,H,I,K,M	Brown	87						2	2	1	1	2						
500	373	DLO	Brown	87						2	2	1	1	2						
600	400	G,H,I,K,M	Green	94						2	2	1	1	2						
600	444	DLO	Green	94						2	2	1	1	2						
700	500	G,H,I,K,M	Pink	99						3	3	1	1	3						
700	535	DLO	Pink	99						3	3	1	1	3						
750	600	G,H,I,M	Black	106						3	3	1	1	3						
750	646	DLO	Black	106						3	3	1	1	3						
1000	750	G,H,I	White	125							3	1	1	3						
1000	777	DLO	White	125							3	1	1	3						

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL Listed and CSA Certified when installed with tools and dies shown above

- a) Number of crimps shown on chart must be on each end of the CT splicer connectors.
- b) The CT connectors are marked with color, the die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- c) The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- d) For long barrel (CTL) connectors add one additional crimp to each side of barrel.

COMPETITOR'S TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire

A

Lug Size	Class B/C Wire Size	Anderson		Burdny							T&B				Greenlee					
		VC6-FT, VC6-FTR, VC6-FT-BP, VC7-FT, VC7-FTR Dieless		PAT81KFT, Y81KFT, Y81KFTMBH Dieless		‡ Y644M, PAT644 Dieless		Y35, Y35BH, Y39, Y750, Y750BH, PAT750		Y46, Y46C Requires Die Adaptor		TBM25S		13100A, TBM14M, TBM14BSCR		K111		HK06FT, RK06FT, EK06FT Dieless		1990 Dieless
		Crimps	Index	Crimps	Crimps	Crimps	Die Part	Crimps	Die Part	Crimps	Index	Crimps	Die Part	Crimps	Index	Crimps	Crimps	Crimps		
8	8 AWG	1	Red	1	1		U8CRT	1	U8CRT	1	Red	1	15520	1	Red	1				
6	6 AWG	1	Blue	1	1		U5CRT	1	U5CRT	1	Blue	1	15522	1	Blue	2	1			
5	5 AWG	1	Blue	1	1		U5CRT	1	U5CRT	1	Blue	1	15522	1	Blue	2	1			
4	4 AWG	1	Gray	2	1	1	U4CRT	1	U4CRT	1	Gray	2	15527-CK	1	Gray	2	1	1		
3	3 AWG	1	White	2	1	1	U3CRT	1	U3CRT	1					Gray	2	1	1		
2	2 AWG	1	Brown	2	1	1	U2CRT	1	U2CRT	1	Brown	2	15528	1	Brown	2	1	1		
1	1 AWG	1			1	1	U1CRT-1	1	U1CRT-1	1			15513-CK	1	Green	2	1	1		
1/0	1/0 AWG	1			1	1	U25RT	1	U25RT	1			15508	1	Pink	4	1	1		
2/0	2/0 AWG	1			1	1	U26RT	1	U26RT	1			15526	1			1	1		
3/0	3/0 AWG	1			1	1	U27RT	1	U27RT	1			15530	1			2	1		
4/0	4/0 AWG	1			1	1	U28RT	1	U28RT	1			15511	1			2	1		
250	250kcmil	2			2	1	U29RT	1	U29RT	1			15510-CK	1			2	1		
300	300kcmil	2			2	1	U30RT	2	U30RT	2			15534	2			2	1		
350	350kcmil	3*			2	1	U31RT	2	U31RT	2			15514-CK	2			2	1		
400	400kcmil	3*			2	1	U32RT	2	U32RT	2			15512	2			2	1		
500	500kcmil	3*			2	1	U34RT	2	U34RT	2			15506	2			2	1		
600	600kcmil	4*			2	1	U36RT	2	U36RT	2			15536-CK	2			2	1		
700	700kcmil	4*			3	1	U38RT	2	U38RT	2			15505	2			3	1		
750	750kcmil	4*			3	1	U39RT	2	U39RT	2			15515-CK	2			3	1		
1000	1000kcmil				3	1			P44RT	3			15504	2				1		

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Dieless* - Crimps will overlap

UL Listed and CSA Certified when installed with tools and dies shown above

- a) Connectors are marked with color, die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- b) The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- c) Consult manufacturers data for catalog numbers of dies for each tool.
- d) Strip Length = Barrel Length + 1/16 Inch
- e) For long barrel connectors double the amount of crimps indicated on chart except for 1000kcmil add only one additional crimp.

‡ Allows expanded wire range to be used.

A

COMPETITOR'S TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire

Lug Size	Fine Strand Wire Size	Approved Wire Classes	Anderson		Burdny						T&B				Greenlee				
			VC6-FT, VC6-FTR, VC6-FT-BP, VC7-FT, VC7-FTR Dieless		PAT81KFT, Y81KFT, Y81KFTMBH Dieless		‡ Y644M, PAT644 Dieless	Y35, Y35BH, Y39, Y750, Y750BH, PAT750	Y46, Y46C Requires Die Adaptor		TBM25S		13100A, TBM14M, TBM14BSCR		K111		HK06FT, RK06FT, EK06FT Dieless		1990 Dieless
			Crimps	Index	Crimps	Crimps	Crimps	Die Part	Crimps	Die Part	Crimps	Index	Crimps	Die Part	Crimps	Index	Crimps	Crimps	Crimps
8	8	G,H,I,K,M,DLO	1	Red	1	1		U8CRT	1	U8CRT	1	Red	1	15520	1	Red	1		
5	6	G,H,I,K,M,DLO	1	Blue	2	1		U5CRT	1	U5CRT	1	Blue	2	15522	1	Blue	2		
3	4	G,H,I,K,M,DLO	1	Gray	2	1	1	U4CRT	1	U4CRT	1	Gray	2	15528	1	Gray	2	1	1
1	2	G,H,I,K,M,DLO	1	Brown	2	1	1	U2CRT	1	U2CRT	1	Brown	3	15513-CK	1	Green	2	1	1
1/0	1	G,H,I,K,M,DLO	1			1	1	U1CRT-1	1	U1CRT-1	1			15508	1	Pink	4	1	1
2/0	1/0	G,H,I,K,M,DLO	1			1	1	U25RT	1	U25RT	1			15526	1			1	1
3/0	2/0	G,H,I,K,M,DLO	2			2	1	U26RT	1	U26RT	1			15530	1			1	1
4/0	3/0	G,H,I,K,M,DLO	2			2	1	U27RT	1	U27RT	1			15511	1			1	1
250	4/0	G,H,I,K,M,DLO	2			2	1	U28RT	1	U28RT	1			15510-CK	2			1	1
300	250	G,H	2			2	1	U29RT	2	U29RT	2			15534	2			1	1
350	250	I,K,M	3*			2	1	U30RT	2	U30RT	2				2			1	1
350	262	DLO	3*			2	1		2		2				2			1	1
400	300	G,H,I,K,M	3*			2	1	U31RT	2	U31RT	2			15514-CK	2			2	1
400	313	DLO	3*			2	1		2		2				2			2	1
500	350	G,H,I,K,M	3*			2	1	U32RT	2	U32RT	2			15512	2			2	1
500	373	DLO	3*			2	1		2		2			15517	2			2	1
600	400	G,H,I,K,M	4*			2	1	U34RT	2	U34RT	2			15536-CK	2			2	1
600	444	DLO	4*			2	1		2		2				2			2	1
700	500	G,H,I,K,M	4*			3	1	U38XRT	2	U38XRT	2			15505	2			3	1
700	535	DLO	4*			3	1		2		2				2			3	1
750	600	G,H,I,M	4*			3	1	U39RT	2	U39RT	2			15515-CK	2			3	1
750	646	DLO	4*			3	1		2		2				2			3	1
1000	750	G,H,I				3	1			U44XRT	3			15504	3				1
1000	777	DLO				3	1				3				3				1

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Dieless* - Crimps will overlap

UL Listed and CSA Certified when installed with tools and dies shown above

- Connectors are marked with color, die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- Strip Length = Barrel Length + 1/16 Inch
- For long barrel connectors double the amount of crimps indicated on chart except for 1000kcmil add only one additional crimp.

‡ Allows expanded wire range to be used.



Compressor Dies For ILC-12-N, ILC-12H-N, ILCB-12-N, ILC-15H, ILC-12, ILC-12H, ILC-14, ILC-14H, ILCB-12, ILCB-12-LIO, ILC-15, ILC-750

Catalog Number	Wire Size		
	Aluminum Terminals and Splices	ACM and ACO Pin Connectors	CPM Pin Connectors
ILD-1			
ILD-2	8		
ILD-3	6		
ILD-4	4		
ILD-5			
ILD-6			
ILD-7	2, 1		
ILD-8	1/0	6, 4, 2, 1	
ILD-9	6, 4, 2, 1		
ILD-10	2/0, 3/0		
ILD-11			
ILD-12	4/0	1/0, 2/0, 3/0, 4/0	1/0, 2/0, 3/0, 4/0
ILD-13	250kcmil		
ILD-14	300kcmil, 350kcmil	250kcmil, 300kcmil, 350kcmil	250kcmil, 300kcmil, 350kcmil
ILD-15			
ILD-16	400kcmil		
ILD-16A	*500kcmil	400kcmil, 500kcmil	400kcmil, 500kcmil
ILD-17	*600kcmil, *700kcmil		
ILD-18	*700kcmil	600kcmil, 750kcmil	600 kcmil, 750kcmil
ILD-20	1000kcmil		
ILD-P302	‡1000kcmil		

* Cannot be used on Sleeves with ILC-12-N, ILC-12H-N, ILC-12 and ILC-12H tools

‡ For use on ALNN-1000-12-134



Compressor Dies For ILC-12, ILC-12-N, ILC-12H, ILC-12H-N, ILCB-12, ILCB-12-N, ILCB-12-LIO, ILC-14, ILC-14H, ILC-15, ILC-15H, ILC-750

Catalog Number	Class B/C Copper Wire Only	Fine Strand Copper Wire Only
	Series CS, CL, CT, CTL	Series CS, CL, CT, CTL
ILD-21	8 AWG	8 FLEX CLASS G,H,I,K,M,DLO
ILD-24	6 AWG, 5 AWG	6 FLEX CLASS G,H,I,K,M,DLO
ILD-29	4-3 AWG	4 FLEX CLASS G,H,I,K,M,DLO
ILD-33	2 AWG	-
ILD-37	1 AWG	2 FLEX CLASS G,H,I,K,M,DLO
ILD-42	1/0 AWG	1 FLEX CLASS G,H,I,K,M,DLO
ILD-45	2/0 AWG	1/0 FLEX CLASS G,H,I,K,M,DLO
ILD-50	3/0 AWG	2/0 FLEX CLASS G,H,I,K,M,DLO
ILD-54	4/0 AWG	3/0 FLEX CLASS G,H,I,K,M,DLO
ILD-62	250kcmil	4/0 FLEX CLASS G,H,I,K,M,DLO
ILD-66	300kcmil	250 G,H
ILD-71	350kcmil	250 I,K,M, 262 DLO
ILD-76	400kcmil	300 G,H,I,K,M, 313 DLO
ILD-87	500kcmil	350 G,H,I,K,M, 373 DLO
ILD-94	600kcmil	400 G,H,I,K,M, 444 DLO
ILD-99	700kcmil	500 G,H,I,K,M, 535 DLO
ILD-106	750kcmil	600 G,H,I,M, 646 DLO
ILD-125	1000kcmil	750 G,H,I, 777 DLO

A

TYPE W DIES FOR ND-60 ND-58



Catalog Number	For Use With	
	Aluminum Compression Connectors	Copper Compression Connectors
ND-0	HT-1, HT-2, AH-1	GGC-1, GGA-1, GGA-2, GGA-4
ND-BG	PICS-61 thru PICS-78	ULT-4, ULT-5
ND-C		ULT-6, ULT-7
ND-K-840	UCS-2/0, UCS-3/0, UCS-4/0, UCS-250, PICS-834 thru PICS-869	

FOR TYPE
ILC-15
ILC-15H
ILC-750



Figure 1



Figure 2

Catalog Number	Figure Number	For Use With	
		Aluminum Compression Connectors	Copper Compression Connectors
ILD-K-840*+	1	UCS-2/0, UCS-3/0, UCS-4/0, UCS-250, PICS-834 thru PICS-869	
ILD-C*+	1		ULT-6, ULT-7, ELT-1
ILD-D ₃ *+	1	HT-2, HT-3, HT-4, HT-5, HT-7, AH-2, AH-3, AH-4	ULT-12
ILD-0*	1	HT-1, HT-6, HT-8, AH-1	GGA-1, GGA-1, GGA-2, GGA-4, ELT-2, ELT-4
ILD-N*+	1	AH-5, AH-6, AH-7	
ILD-KR+	2	AH-8, AH-9, AH-10, AH-11, AH-12	AH-10, AH-11, AH-12
ILD-U997*+	1		GGA-2, GGA-3, GGA-5, GGC-2, GGC-3, GGC-4, ELT-3, ELT-5
ILD-U998+	1		GGA-4, GGA-5, GGC-5, GGC-6, GGC-7, RLT
ILD-P998	2	Can only be used with ILC-15 or ILC-15H	GGA-4, GGA-5, GGC-5, GGC-6, GGC-7, RLT
ILD-P999	2	Can only be used with ILC-15 or ILC-15H	GGA-6, GGC-8
ILD-U1011+	1		GGA-6, GGC-8, ELT-6, RLT
ILD-P1011°	2		GGA-6, GGC-8, RLT
ILD-UBG	1	PICS-61 thru PICS-78	ULT-4, ULT-5
ILD-P302	1	ALNN	

* May also be used with ILC-12-N, ILC-12H-N, ILCB-12-N, ILC-12, ILC-12H, ILCB-12
+ Must be used with ILDPADP when using ILC-15, must be used with ILDPADP when using ILC-15H
o Must be used with ILDPADP when using ILC-15H

Die Adaptors

FOR TYPE
ILC-15
ILC-15H



Figure 1



Figure 2



Figure 3

Catalog Number	Figure Number	Description
ILD-ADP	1	Permits ILDPADP-1 to ILDPADP-18 to be inserted in ILC-15 tool
ILD-UADP	2	Permits ILDPADP-1 to ILDPADP-18 to be inserted in ILC-15H tool
ILD-PADP	3	Permits "P" style dies to be inserted in ILC-15H tool

<p>COOL SEAL</p>  <p>89</p>	<p>CRIMP 'N SEAL Rings</p>  <p>90</p>	<p>CRIMP 'N SEAL Forks, Splices, Disconnects, Bullets</p>  <p>91 - 92</p>
<p>ILSCON KITS</p>  <p>93</p>	<p>ILSCONS Non-Insulated Ring Terminals</p>  <p>94 - 97</p>	<p>ILSCONS Vinyl Ring Terminals</p>  <p>98 - 99</p>
<p>ILSCONS High Temperature Rings</p>  <p>100</p>	<p>ILSCONS Non-Insulated Fork Terminals</p>  <p>101</p>	<p>ILSCONS Vinyl Insulated Forks</p>  <p>102</p>
<p>ILSCONS Non-Insulated Splices</p>  <p>103</p> <p>ILSCONS Vinyl Splices</p>  <p>104</p>	<p>ILSCONS Disconnects and Flag Terminals</p>  <p>105</p>	<p>ILSCON TOOLS</p>  <p>106</p>



COOL SEAL[®] BY FTZ INDUSTRIES

FTZ's patented Cool Seal[®] is the most innovative and cost effective sealed electrical connector to hit the market in 25 years. A heat-less, solderless terminal, it utilizes revolutionary anaerobic sealant technology that installs in a fraction of the time of comparable heat seal connectors. Simply strip the wire and crimp, activating the sealant, to create an environmentally sealed connection. The innovative new sealant prevents the ingress of moisture and air, the nylon insulation provides maximum abrasion and puncture resistance, while the seamless, 99.9% ETP copper connector offers optimal electrical conductivity. Requiring no heat, the Cool Seal[®] will reduce overall costs by eliminating the need for torches or heat guns, reducing the installation time, and improving productivity.


A1



FEATURES & BENEFITS

- Seals Out Moisture Causing Corrosion
- A Heat-Less/Solderless Connection
- Patented Anaerobic Technology
- Simply Strip and Crimp
- Installs in a Fraction of the Time of Comparable Heat Shrink Terminals
- Improved Productivity
- No Heat Tools Required
- Nylon Insulation
- 99.9% ETP Copper Terminal
- **Cool Seal[®] Butt Splice Part Numbers:**
33130(22-18GA); 33330(16-14GA); 33430(12-10GA)

Installs with FTZ Tools:



94145



94130

Crimp 'N Seal®


Waterproof Heat Shrink Connectors

FTZ Industries manufactures the most comprehensive and highest quality line of Crimp 'N Seal® heat shrinkable connectors on the market today. The company that first brought you heat shrinkable connectors over two decades ago has more than tripled the number of connectors available. Do not be fooled by imitations. No matter how it's spelled, if it does not say Crimp 'N Seal® it's not the original.

- **Seamless Tubular Splices** insures mechanical and electrical integrity under severe conditions and can be crimped on any side
- **Brazed Seam Terminals** brazed seam will not split open under the most extreme installation and operating conditions
- **Heat Shrinkable Tubing** 3:1 dual wall tubing with adhesive lining provides a waterproof seal with durable abrasion resistance and unequalled strain relief.
- **Polyolefin or Clear Seal** the most complete heat shrinkable connector offering is now stocked in two styles
- **Packaged or Bulk** available in convenient packaged quantities or order in bulk and save
- **UL File #E 6207**
- **Maximum Performance** Up to 600 volts, 90°C



A1



TYPE CNS

Insulated Ring Terminals



Catalog Number	Wire Range	Stud Size	Maximum Wire Insulation
31112-B10	18-22	6	.170
31113-B10	18-22	8	.170
31114-B10	18-22	10	.170
31115-B10	18-22	1/4"	.170
31312-B10	14-16	6	.190
31313-B10	14-16	8	.190
31314-B10	14-16	10	.190
31315-B10	14-16	1/4"	.190
31316-B10	14-16	5/16"	.190
31317-B10	14-16	3/8"	.190
31413-B10	10-12	8	.240
31414-B10	10-12	10	.240
31415-B10	10-12	1/4"	.240
31417-B10	10-12	3/8"	.240
31419-B10	10-12	1/2"	.240
31514-B5	8	10	.310
31515-B5	8	1/4"	.310
31517-B5	8	3/8"	.310
31519-B5	8	1/2"	.310

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Can be supplied in bulk. Consult factory for part number.

UL File E158587



TYPE CNS

Features

- Dual wall tubing
- Color coded
- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- UL Listed and CSA Certified for 600 volts, 90°C
- Serrated barrel
- Packaged in convenient small quantities

Benefits

- Irradiated, thermally stabilized, high density polyolefin has inner wall of hot melt adhesive to insure watertight seal
- Provides easy wire range identification. #22-18 AWG Red, #16-14 AWG Blue, #12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Ensures reliability for copper conductor
- "V" grooves inside barrel securely grip wire and prevent pullout
- Can be displayed on merchandise racks

A1

Spades/Forks



Catalog Number	Wire Range	Stud Size	Style	Maximum Wire Insulation
31122-B10	18-22	6	-	.170
31123-B10	18-22	8	-	.170
31124-B10	18-22	10	-	.170
31322-B10	14-16	6	-	.190
31323-B10	14-16	8	-	.190
31324-B10	14-16	10	-	.190
31422-B10	10-12	6	-	.240
31423-B10	10-12	8	-	.240
31424-B10	10-12	10	-	.240

Flanged Forks



Catalog Number	Wire Range	Stud Size	Style	Maximum Wire Insulation
31122FL-B10	18-22	6	-	.170
31123FL-B10	18-22	8	-	.170
31124FL-B10	18-22	10	-	.170
31322FL-B10	14-16	6	-	.190
31323FL-B10	14-16	8	-	.190
31324FL-B10	14-16	10	-	.190
31422FL-B10	10-12	6	-	.240
31423FL-B10	10-12	8	-	.240
31424FL-B10	10-12	10	-	.240

TYPE CNS

A1

Features

- Dual wall tubing
- Color coded
- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- UL Listed and CSA Certified for 600 volts, 90°C
- Serrated barrel
- Packaged in convenient small quantities

Benefits

- Irradiated, thermally stabilized, high density polyolefin has inner wall of hot melt adhesive to insure watertight seal
- Provides easy wire range identification. #22-18 AWG Red, #16-14 AWG Blue, #12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Ensures reliability for copper conductor
- "V" grooves inside barrel securely grip wire and prevent pullout
- Can be displayed on merchandise racks

Butt Splices



Catalog Number	Wire Range	Maximum Wire Insulation
31130-B10	18-22	.170
31330-B10	14-16	.190
31430-B10	10-12	.240
31530-B5	8	.310

Quick Disconnects



Catalog Number	Wire Range	Tab Size	Style	Maximum Wire Insulation
30185-B10	18-22	.187 x .020	Male	.170
30195-B10	18-22	.187 x .020	Female	.170
30187-B10	18-22	.250 x .032	Male	.170
30197-B10	18-22	.250 x .032	Female	.170
30385-B10	14-16	.187 x .020	Male	.190
30395-B10	14-16	.187 x .020	Female	.190
30387-B10	14-16	.250 x .032	Male	.190
30397-B10	14-16	.250 x .032	Female	.190
30487-B10	10-12	.250 x .032	Male	.240
30497-B10	10-12	.250 x .032	Female	.240

Bullets/Receptacles



Catalog Number	Wire Range	Style	Maximum Wire Insulation
31369-B10	14-16	Male	.190
30379-B10	14-16	Female	.190

TYPE
ILSCONS**Features**

- Crimp 'N Seal heat shrink connector kits provide a convenient and durable assortment of our most popular terminals.

A1**Crimp 'N Seal® Splice Kit****Catalog Number 99102 Polyolefin Crimp 'N Seal®**

A handy kit that includes our high quality ratchet crimp tool and our three most popular splices.

Kit Includes:

15	22-18 CNS Butt Splice	15	12-10 CNS Butt Splice
15	16-14 CNS Butt Splice	1	94130 CNS Ratchet Crimp Tool

**Crimp 'N Seal® Terminal Kit****Catalog Number 99300 Polyolefin Crimp 'N Seal®**

A versatile kit with everything you need to cut, crimp, heat and seal your connection.

Kit Includes:

15	22-18 CNS Butt Splice	20	16-14 1/4" Stud Ring Terminal
15	16-14 CNS Butt Splice	10	16-14 Fully Insulated Male Disc.
15	12-10 CNS Butt Splice	10	16-14 Fully Insulated Female Disc.
20	22-18 #10 Stud Ring Terminal	1	94145 Multi-Purpose Crimp Tool
20	16-14 #10 Stud Ring Terminal	1	94700 Shrink Jet Butane Heat Tool
20	12-10 #10 Stud Ring Terminal		

ILSCO Non-Insulated Ring Terminals

RoHS
Compliant

UL
LISTED
8M24




TYPE ILSCONS

Features

- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- Packaged in convenient small quantities
- UL Listed and CSA Certified, 90° C

Benefits

- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor



Catalog Number	Wire Range	Stud Size	Dimensions	
			L	W
44100-B20	18-22	4	.45	.20
44101-B20	18-22	6	.62	.25
44102-B20	18-22	8	.75	.31
44103-B20	18-22	10	.75	.31
44104-B20	18-22	1/4	.94	.47
44105-B20	18-22	5/16	.94	.47
44106-B20	18-22	3/8	.97	.53
44110-B20	14-16	4	.95	.25
44111-B20	14-16	6	.71	.31
44112-B20	14-16	8	.71	.31
44113-B20	14-16	10	.71	.31
44114-B20	14-16	1/4	.94	.46
44115-B20	14-16	5/16	.94	.46
44116-B20	14-16	3/8	.97	.53

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Can be supplied in bulk. Consult factory for part number. UL File E158587

ILSCO Non-Insulated Ring Terminals

RoHS
Compliant

UL
LISTED
8M24



TYPE ILSCONS


Features

- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- Packaged in convenient small quantities
- UL Listed and CSA Certified, 90° C

Benefits

- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor

A1



Catalog Number	Wire Range	Stud Size	Dimensions	
			L	W
44120-B20	10-12	6	.90	.37
44121-B20	10-12	8	.90	.37
44122-B20	10-12	10	.90	.37
44123-B20	10-12	1/4	1.01	.52
44124-B20	10-12	5/16	1.01	.52
44125-B20	10-12	3/8	1.01	.59
44126-B20	10-12	7/16	1.13	.71
44127-B20	10-12	1/2	1.13	.71
44130-B10	8	10	1.20	.59
44131-B10	8	1/4	1.20	.59
44140-B10	6	10	1.18	.47
44141-B10	6	1/4	1.18	.47
44142-B10	6	5/16	1.26	.63
44143-B10	6	3/8	1.26	.63

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Can be supplied in bulk. Consult factory for part number. UL File E158587



ILSCO Non-Insulated Ring Terminals




TYPE ILSCONS

Features

- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- Packaged in convenient small quantities
- UL Listed and CSA Certified, 90° C

Benefits

- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor



Catalog Number	Wire Range	Stud Size	Dimensions	
			L	W
44150-B10	4	10	1.30	.66
44151-B10	4	1/4	1.30	.66
44152-B10	4	5/16	1.30	.66
44153-B10	4	3/8	1.30	.66
44154-B10	4	7/16	1.30	.66
44155-B10	4	1/2	1.90	.88
44160-B10	2	10	1.55	.60
44161-B10	2	1/4	1.55	.60
44162-B10	2	5/16	1.55	.70
44163-B10	2	3/8	1.55	.70
44164-B10	2	7/16	1.55	.81
44165-B10	2	1/2	1.93	.81
44170-B2	1/0	1/4	1.93	.88
44171-B2	1/0	5/16	1.93	.88
44172-B2	1/0	3/8	1.93	.88
44173-B2	1/0	7/16	1.93	.88
44174-B2	1/0	1/2	1.93	.88

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Can be supplied in bulk. Consult factory for part number. UL File E158587

ILSCO Non-Insulated Ring Terminals



TYPE ILSCONS


Features

- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- Packaged in convenient small quantities
- UL Listed and CSA Certified, 90° C

Benefits

- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor

A1



Catalog Number	Wire Range	Stud Size	Dimensions	
			L	W
44180-B2	2/0	1/4	1.93	.88
44181-B2	2/0	5/16	1.93	.88
44182-B2	2/0	3/8	1.93	.88
44183-B2	2/0	7/16	1.93	.88
44184-B2	2/0	1/2	1.93	.88
44190-B2	3/0	1/4	1.97	.93
44191-B2	3/0	5/16	1.97	.93
44192-B2	3/0	3/8	1.97	.93
44193-B2	3/0	7/16	1.97	.93
44194-B2	3/0	1/2	1.97	.93
44195-B2	4/0	5/16	2.17	1.08
44196-B2	4/0	3/8	2.17	1.08
44197-B2	4/0	7/16	2.17	1.08
44198-B2	4/0	1/2	2.17	1.08

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Can be supplied in bulk. Consult factory for part number.

UL File E158587



ILSCO Vinyl Insulated Ring Terminals




TYPE ILSCONS

Features

- Color coded
- Manufactured from high strength copper alloy
- Electro-tin plated
- Vinyl insulation
- Packaged in convenient small quantities
- UL Listed and CSA Certified for 600 volts, 90° C

Benefits

- Provides easy wire range identification
#22-18 AWG Red
#16-14 AWG Blue
#12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor



Catalog Number	Wire Range	Stud Size	Dimensions		Maximum Wire Insulated Diameter
			L	W	
44200-B10	18-22	4	.74	.22	.145
44201-B10	18-22	6	.91	.31	.145
44202-B10	18-22	8	.91	.31	.145
44203-B10	18-22	10	.91	.31	.145
44204-B10	18-22	1/4	1.10	.46	.145
44205-B10	18-22	5/16	1.14	.53	.145
44206-B10	18-22	3/8	1.14	.53	.145
44210-B10	14-16	4	.80	.25	.175
44211-B10	14-16	6	.88	.25	.175
44212-B10	14-16	8	.94	.31	.175
44213-B10	14-16	10	.94	.31	.175
44214-B10	14-16	1/4	1.06	.53	.175
44215-B10	14-16	5/16	1.06	.53	.175
44216-B10	14-16	3/8	1.06	.53	.175
44220-B10	10-12	6	.95	.28	.255
44221-B10	10-12	8	.95	.28	.255
44222-B10	10-12	10	1.00	.38	.255
44223-B10	10-12	1/4	1.22	.53	.255
44224-B10	10-12	3/8	1.33	.53	.255
44225-B10	10-12	7/16	1.46	.71	.255

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Can be supplied in bulk. Consult factory for part number.

UL File E158587



ILSCO Vinyl Insulated Ring Terminals



TYPE ILSCONS


Features

- Color coded
- Manufactured from high strength copper alloy
- Electro-tin plated
- Vinyl insulation
- Packaged in convenient small quantities
- UL Listed and CSA Certified for 600 volts, 90° C

Benefits

- Provides easy wire range identification
 - #22-18 AWG Red
 - #16-14 AWG Blue
 - #12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor

A1



Catalog Number	Wire Range	Stud Size	Dimensions		Maximum Wire Insulated Diameter
			L	W	
44226-B10	10-12	1/2	1.52	.75	.255
44230-B5	8	10	1.28	.47	.385
44231-B5	8	1/4	1.28	.47	.385
44240-B5	6	10	1.62	.47	.440
44241-B5	6	1/4	1.62	.47	.440
44242-B5	6	5/16	1.70	.63	.440
44243-B5	6	3/8	1.70	.63	.440
44250-B5	4	10	1.81	.66	.515
44251-B5	4	1/4	1.81	.66	.515
44252-B5	4	5/16	1.81	.66	.515
44253-B5	4	3/8	1.81	.66	.515
44254-B5	4	7/16	1.81	.66	.515
44255-B5	4	1/2	2.41	.88	.515
45314-P100	14-16	10	.94	.31	.175
45315-P100	14-16	1/4	1.06	.53	.175
45316-P100	14-16	5/16	1.06	.53	.175
45316N-P100*	14-16	5/16	1.06	.53	.175
45317-P100	14-16	3/8	1.06	.53	.175
45414-P50	10-12	10	1.00	.38	.255
45415-P50	10-12	1/4	1.22	.53	.255
45416-P50	10-12	5/16	1.46	.71	.255
45417-P50	10-12	3/8	1.33	.53	.255

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Nylon Insulated Ring Can be supplied in bulk. Consult factory for part number. UL File E158587



TYPE ILSCONS


Features

- Manufactured from high strength steel alloy
- Electro-tin plated
- Silver solder brazed seam
- Packaged in convenient small quantities
- 900° F 482° C Continuous, 1200° F 649° C Intermittent

Benefits

- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Can be displayed on merchandise racks

A1



Catalog Number	Wire Range	Stud Size	Dimensions	
			L	W
44300-B20	18-22	4-6	.65	.25
44301-B20	18-22	8-10	.69	.31
44302-B20	18-22	12-1/4	.93	.56
44310-B20	14-16	4-6	.65	.25
44311-B20	14-16	8-10	.69	.31
44312-B20	14-16	12-1/4	.90	.46
44320-B20	10-12	4-6	.67	.28
44321-B20	10-12	8-10	.72	.37
44322-B20	10-12	12-1/4	.93	.53
44323-B20	10-12	5/16-3/8	.99	.60
44330-B10	8	12-1/4	.95	.47
44340-B10	6	5/16-3/8	1.22	.63

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Can be supplied in bulk. Consult factory for part number.

ILSCO Non-Insulated Fork Terminals

RoHS
Compliant

UL
LISTED
8M24



TYPE ILSCONS


Features

- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- Packaged in convenient small quantities
- UL Listed and CSA Certified, 90° C

Benefits

- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor

A1



Catalog Number	Wire Range	Stud Size	Dimensions	
			L	W
44400-B20	18-22	4	.68	.25
44401-B20	18-22	6	.68	.25
44402-B20	18-22	8	.68	.30
44403-B20	18-22	10	.68	.32
44410-B20	14-16	4	.68	.25
44411-B20	14-16	6	.68	.25
44412-B20	14-16	8	.68	.25
44413-B20	14-16	10	.68	.30
44414-B20	14-16	1/4	.90	.32
44420-B20	10-12	6	.73	.28
44421-B20	10-12	8	.73	.32
44422-B20	10-12	10	.73	.32
44423-B20	10-12	1/4	.94	.43

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Can be supplied in bulk. Consult factory for part number.

UL File E158587



ILSCO Vinyl Insulated Fork Terminals



TYPE ILSCONS



Features

- Color coded
- Manufactured from high strength copper alloy
- Electro-tin plated
- Vinyl insulation
- Packaged in convenient small quantities
- UL Listed and CSA Certified for 600 volts, 90° C

Benefits

- Provides easy wire range identification
#22-18 AWG Red
#16-14 AWG Blue
#12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor

A1



Catalog Number	Wire Range	Stud Size	Dimensions		Maximum Wire Insulated Diameter
			L	W	
44500-B10	18-22	4	.88	.25	.145
44501-B10	18-22	6	.88	.29	.145
44502-B10	18-22	8	.88	.31	.145
44503-B10	18-22	10	.88	.31	.145
44511-B10	14-16	6	.88	.29	.175
44512-B10	14-16	8	.88	.31	.175
44513-B10	14-16	10	.88	.31	.175
44514-B10	14-16	1/4	1.10	.43	.175
44520-B10	10-12	6	1.06	.28	.255
44521-B10	10-12	8	1.06	.28	.255
44522-B10	10-12	10	1.06	.28	.255
44523-B10	10-12	1/4	1.24	.43	.255
45322FL-P100*	14-16	6	.88	.29	.175
45323FL-P100*	14-16	8	.88	.31	.175
45324FL-P100*	14-16	10	.88	.31	.175
45423FL-P50*	10-12	8	1.06	.28	.255
45424FL-P50*	10-12	10	1.06	.28	.255

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Flanged Fork

Can be supplied in bulk. Consult factory for part number.

UL File E158587



ILSCO Non-Insulated Splices



TYPE ILSCONS

Features

- Manufactured from high strength copper alloy
- Electro-tin plated
- Packaged in convenient small quantities
- UL Listed and CSA Certified, 90° C

Benefits

- Provides maximum conductivity
- Provides low contact resistance
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor

A1



Fig. 1




Fig. 2

Catalog Number	Figure Number	Wire Range	L
44600-B20	1	18-22	.33
44610-B20	1	14-16	.33
44620-B20	1	10-12	.33
44630-B10	1	8	.38
44640-B10	1	6	.46
44650-B10	1	4	.54
44800-B20	2	18-22	.63
44810-B20	2	14-16	.63
44820-B20	2	10-12	.82
44830-B10	2	8	.77
44840-B10	2	6	1.02
44850-B10	2	4	1.20

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Can be supplied in bulk. Consult factory for part number.

UL File E158587



TYPE ILSCONS

A1

Features

- Color coded
- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- Vinyl insulation
- Packaged in convenient small quantities
- UL Listed and CSA Certified for 600 volts, 90° C

Benefits

- Provides easy wire range identification
#22-18 AWG Red
#16-14 AWG Blue
#12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor



Fig. 1




Fig. 2

Catalog Number	Figure Number	Wire Range	L	Maximum Wire Insulated Diameter	Connector Type
44700-B10	1	18-22	.76	.145	Parallel Splice
44710-B10	1	14-16	.76	.175	Parallel Splice
44720-B10	1	10-12	.83	.255	Parallel Splice
44730-B5	1	8	1.05	.385	Parallel Splice
44740-B5	1	6	1.19	.440	Parallel Splice
44750-B5	1	4	1.41	.515	Parallel Splice
44900-B10	2	18-22	.95	.145	Butt Splice
44910-B10	2	14-16	1.02	.175	Butt Splice
44920-B10	2	10-12	1.01	.255	Butt Splice
44930-B5	2	8	1.46	.385	Butt Splice
44940-B5	2	6	1.80	.440	Butt Splice
44950-B5	2	4	1.95	.515	Butt Splice
45130-P100	1	18-22	.76	.145	Vinyl Insulated Splice
45330-P100	1	14-16	.76	.175	Vinyl Insulated Splice
45430-P50	1	10-12	.83	.255	Vinyl Insulated Splice

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Can be supplied in bulk. Consult factory for part number.

UL File E158587

TYPE ILSCONS

Features

- Color coded
- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- Vinyl insulation
- Packaged in convenient small quantities
- Insulated connectors are rated for 600 volts, 90° C

Benefits

- Provides easy wire range identification
#22-18 AWG Red
#16-14 AWG Blue
#12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Can be displayed on merchandise racks
- Ensures reliability for copper conductor

A1



Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Wire Range	Stud Size	Type	Width	Thickness	Length	Connector Type
45100-B10	1	18-22	-	Female	1/4	-	-	Disconnects - Insulated - Male - Female - Brass Sleeve - Vinyl Insulation
45101-B10	1	18-22	-	Male	1/4	-	-	
45110-B10	1	14-16	-	Female	1/4	-	-	Disconnects - Insulated - Male - Female - Brass Sleeve - Vinyl Insulation
45111-B10	1	14-16	-	Male	1/4	-	-	
45120-B10	1	10-12	-	Female	1/4	-	-	Disconnects - Insulated - Male - Female - Brass Sleeve - Vinyl Insulation
45121-B10	1	10-12	-	Male	1/4	-	-	
45112-B10	1	14-16	-	Female	3/16	-	-	Disconnects - Insulated - Male - Female - Brass Sleeve - Vinyl Insulation
45113-B10	1	14-16	-	Male	3/16	-	-	
45200-B10	2	18-22	-	Female	1/4	-	-	Disconnects - Uninsulated - Male - Female
45201-B10	2	18-22	-	Male	1/4	-	-	
45210-B10	2	14-16	-	Female	1/4	-	-	Disconnects - Uninsulated - Male - Female
45211-B10	2	14-16	-	Male	1/4	-	-	
45220-B10	2	10-12	-	Female	1/4	-	-	Disconnects - Uninsulated - Male - Female
45221-B10	2	10-12	-	Male	1/4	-	-	
45212-B10	2	14-16	-	Female	3/16	-	-	Disconnects - Uninsulated - Male - Female
45213-B10	2	14-16	-	Male	3/16	-	-	
45300-B10	3	18-22	10	-	21/32	-	3/8	Ring Flag Terminals - Uninsulated
45310-B10	3	14-16	10	-	11/16	-	3/8	Ring Flag Terminals - Uninsulated
45320-B10	3	10-12	10	-	11/16	-	3/8	Ring Flag Terminals - Uninsulated
45400-B10	4	18-22	-	-	.187	.016	.46	Female Quick-Slide Flag Terminals - Uninsulated
45401-B10	4	18-22	-	-	.250	.030	.50	Female Quick-Slide Flag Terminals - Uninsulated
45410-B10	4	14-16	-	-	.187	.016	.49	Female Quick-Slide Flag Terminals - Uninsulated
45411-B10	4	14-16	-	-	.250	.030	.51	Female Quick-Slide Flag Terminals - Uninsulated
45420-B10	4	10-12	-	-	.250	.030	.61	Female Quick-Slide Flag Terminals - Uninsulated
45393-P100	1	14-16	-	Female	1/4	-	-	Vinyl Insulated Disconnect
45483-P50	1	10-12	-	Male	1/4	-	-	Vinyl Insulated Disconnect
45493-P50	1	10-12	-	Female	1/4	-	-	Vinyl Insulated Disconnect

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Can be supplied in bulk. Consult factory for part number.



A1

TYPE
94130
**Controlled-Cycle
 Crimper**

- Features**
- Dieless tool
 - Ratchet mechanism
 - Compound action
 - Cushion grip handles
 - Crimps insulated wire terminals
 - Wire Range: 10-22 AWG, Weight .8 lb

- Benefits**
- No need to purchase and maintain dies
 - Assures proper crimp force every time
 - Delivers maximum crimp force with minimum effort
 - Provides user comfort
 - Provides flexibility in use



TYPE
94145
**Multi Purpose
 Crimp Tool**

- Features**
- Heavy duty carbon steel construction
 - Comfort grip handles
 - Spring loaded action
 - Safety lock mechanism
 - Color coded crimp nest
 - Crimp nest
 - Wire cutter
 - Machine screw cutters
 - Wire stripper/wire gauge


- Benefits**
- Provides durable rugged reliability
 - Provides user comfort
 - Enables multiple crimps
 - Provides for compact storage
 - For insulated terminals
 - For uninsulated terminals
 - Easily cuts solid and stranded wire
 - Cuts and rethreads 4-40, 6-32, 8-32, 10-24, and 10-32 machine screws
 - 26-8 AWG



TYPE
WS-1
Wire Stripper

- Features**
- Cushion grip handles
 - Crimp die
 - Wire strip gauge
 - Plier nose
 - Wire loop holes
 - Wire cutter
 - "Open" spring
 - Metric markings
 - Precision stripping
 - Wire crimp range: 14-18 AWG


- Benefits**
- Eases pressure on hands when working for long periods or with larger conductor
 - Built in crimp die allows you to crimp insulated terminals from 18AWG to 14AWG
 - Convenient stamped wire strip gauge makes it easy to strip conductors to specific length consistently
 - Flat plier nose allows you to conveniently punch and twist knock outs
 - Built in looping holes allow you to conveniently bend eye loop into end of conductor
 - Built in cutter is precision ground to cut small conductor copper intended to be stripped (Strips #10 - 18 AWG)
 - Conveniently holds tool in open position to facilitate wire insertion
 - Metric markings provide for use of tool on products that have been sized metrically
 - Precision ground wire stripping holes provide a clean cutting and stripping action of insulation



All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

**Put More Money in Your Pocket
with these Labor Savers!**


KUP-L-Tap® Insulation Piercing Connectors



- Fully insulated – Work it Hot
- Versatile – Dual Rated
- Dependable – UL Listed, CSA Certified
- Time Saver – No stripping, no wire brushing, no oxide inhibitor, no taping
- Convenient – Wire Range 750kcmil-14

CLEAR TAP®

Insulated Multi-Tap Connectors



- Fully insulated – No taping
- Versatile – Dual Rated, Two-sided entry splice or tap
- Dependable – UL Listed
- Time Saver – Captive pressure screws in “Quick Start” position, no taping, Self-closing openings eliminate lost plugs and caps
- Convenient – Wire Range 800kcmil-14

IK  108	IK3  109	
SK  110	IKB  111	
IKS  112	AK  113	
DBA, DBA-S  114	IPC  115	
GTA  116	SPAR  117	
GTT  118	GTC  119	GT2  120
GT4T  121	GTA/GTT KIT  122	MGTT  123
PTA  124	PCT  125	


TYPE IK

Features

- Manufactured from high strength copper alloy
- Precision tooled threads
- UL 467 Listed for Grounding and Bonding 500kcmil thru 8
- CSA Certified for Grounding and Bonding 250kcmil thru 8
- RUS Accepted 8 thru 1/0 AWG
- For use with copper conductor types: Solid, Compact, Compressed, Concentric
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and high breakage resistance
- Allows maximum torque to be applied
- Suitable for direct burial in earth and concrete
- Application versatility



Catalog Number	Range For Equal Main & Tap	Min. Tap With One Max. Main	Max. Cond Copperweld		Rebar With 6 or 8 AWG	Wire Diameter	Dimensions				Recommended Torque (IN-LB)
			Str	Type A			A	B	C	D	
IK-10	10str - 16str	16str	-	-	N/A	.057 - .125	.125	0.344	0.500	0.719	80
IK-8	8str - 16str	16str	-	-	N/A	.057 - .145	.145	0.375	0.500	0.844	80
IK-6	6sol - 10sol	16sol	-	-	N/A	.102 - .162	.165	0.500	0.625	1.047	165
IK-4	4sol - 8sol	16sol	3 No. 12	8A	N/A	.128 - .204	.215	0.562	0.688	1.047	165
IK-3	2sol - 6sol	12sol	3 No. 9	5A	N/A	.162 - .258	.328	0.688	0.812	1.312	275
IK-2	2str - 6sol	14str	3 No. 7	3A	N/A	.162 - .292	.328	0.688	0.812	1.312	275
IK-1/0	1/0str - 4sol	14sol	3 No. 6	2A	N/A	.204 - .375	.377	0.750	0.875	1.641	385
IK-2/0	2/0str - 2sol	14str	3 No. 5	-	#3 (3/8)	.258 - .418	.420	0.812	1.000	1.812	385
IK-3/0	3/0str - 2sol	12sol	7 No. 7	-	N/A	.258 - .470	0.466	0.875	1.125	2.000	500
IK-250	250kcmil - 1/0sol	10sol	7 No. 5	-	#4 (1/2)	.325 - .575	0.579	1.000	1.312	2.078	650
IK-350	350kcmil - 4/0str	8sol	19 No. 7	-	#5 (5/8)	.528 - .682	0.746	1.500	1.625	2.625	650
IK-500	500kcmil - 250kcmil	8sol	19 No. 6	-	#6 (3/4)	.575 - .815	0.834	1.625	1.812	3.000	825
IK-750	750kcmil - 350kcmil	8sol	19 No. 5	-	N/A	.682 - .999	1.030	1.938	2.125	3.750	1000
IK-1000	1000kcmil - 500kcmil	8sol	-	-	N/A	.815 - 1.153	1.222	2.250	2.500	4.000	1100

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207

ILSCO Three Wire Copper Split Bolts




TYPE IK3

Features

- Manufactured from high strength copper alloy
- Precision tooled threads
- UL 467 Listed and CSA Certified for Grounding and Bonding
- RUS Accepted
- For use with copper conductor types: Solid, Compact, Compressed, Concentric
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and high breakage resistance
- Allows maximum torque to be applied
- Suitable for direct burial in earth and concrete
- Application versatility



B

Catalog Number	Range For Equal Main & Tap	Min. Tap With One Max. Main	Max Cond Copperweld		Wire Diameter Range	Dimensions				Recommended Torque (IN-LB)
			Str	Type A		A	B	C	D	
IK3-8	8str - 16str	16str	-	-	.057 - .145	0.144	0.375	0.500	0.844	80
IK3-6	6sol - 10sol	16sol	-	-	.102 - .162	0.166	0.500	0.625	1.109	165
IK3-4	4sol - 8sol	16sol	3 No. 12	8A	.128 - .204	0.217	0.562	0.688	1.266	165
IK3-2	2str - 6sol	14str	3 No. 7	3A	.162 - .258	0.326	0.688	0.812	1.547	275

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207



ILSCO Tin Plated Copper Split Bolts



TYPE SK


Features

- Manufactured from high strength copper alloy
- Electro-tin plated bolt, nut, spacer and pressure bar
- Precision tooled threads
- SK-10, SK-8, SK3, SK-2 SK-1/0, SK-2/0 are RUS Accepted
- For use with copper conductor types: Solid, Compact, Compressed, Concentric
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- For aluminum conductor consult factory
- Rated to 90° C

Benefits

- Provides maximum conductivity and high breakage resistance
- Provides low contact resistance
- Application versatility

B



Catalog Number	Range For Equal Main & Tap	Min. Tap With One Max. Main	Max Cond Copperweld		Wire Diameter Range	Dimensions				Recommended Torque (IN-LB)
			Str	Type A		A	B	C	D	
SK-10	10str - 16str	16str	-	-	.057 - .116	.144	0.375	0.500	0.844	80
SK-8	8str - 16str	16str	-	-	.057 - .145	0.144	0.375	0.500	0.844	80
SK-6 +	8str - 14str	14str	-	-	.073 - .146	.166	0.500	0.625	1.109	165
SK-4 +	6str - 10str	10sol	3 No. 12	8A	.116 - .184	0.217	0.562	0.688	1.266	165
SK-3 +	4str - 8sol AL 2sol - 8sol CU	8sol AL 8sol CU	3 No. 9	5A	.128 - .258	0.326	0.688	0.812	1.547	275
SK-2 +	2str - 8sol	8sol	3 No. 7	3A	.128 - .316	0.326	0.688	0.812	1.547	275
SK-1/0	1/0str - 6sol	10sol	3 No. 6	-	.162 - .375	0.376	0.750	0.875	1.641	385
SK-2/0	2/0str - 6str	10sol	3 No. 5	-	.184 - .419	.420	0.812	1.000	1.812	385
SK-3/0	3/0str - 4str	6sol	7 No. 7	-	.198 - .470	0.466	0.875	1.125	2.000	500
SK-250	250kcmil - 4str	4str	7 No. 5	-	.232 - .575	0.577	1.000	1.312	2.328	650
SK-350	350kcmil - 3/0str	1sol	19 No. 7	-	.447 - .682	0.746	1.500	1.625	2.625	650
SK-500	500kcmil - 3/0str	1/0str	19 No. 6	-	.447 - .815	0.834	1.625	1.812	3.000	825
SK-750	750kcmil - 250kcmil	2/0str	19 No. 5	-	.563 - .999	1.030	1.938	2.125	3.750	1000
SK-1000	1000kcmil - 350kcmil	4/0str	-	-	.682 - 1.162	1.222	2.250	2.500	4.000	1100

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 + AL9CU
 UL File E12822



ILSCO Copper Two Bolt Connectors

RoHS
Compliant




TYPE IKB

Features

- Manufactured from high strength copper alloy
- Two bolt design
- Longer peened bolt
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- For copper conductor only
- Rated to 90° C

Benefits

- Allows maximum conductivity and high breakage resistance
- Allows maximum pressure to be applied directly to the conductor strands
- Permits a swivel action for easier installation
- Application versatility



B

Catalog Number	Copper Wire Range		Dimensions		
	Main	Tap	C	H	W
IKB-4/0 +	1/0-4/0	4/0-10	1.10	1.97	1.72
IKB-350 +	350kcmil-250kcmil	350kcmil-10	1.38	2.48	2.14
IKB-500	500kcmil-400kcmil	500kcmil-10	1.50	2.80	2.25
IKB-800	800kcmil-400kcmil	800kcmil-3/0	1.62	3.32	2.50
IKB-1000	1000kcmil-500kcmil	1000kcmil-3/0	2.00	3.78	3.03

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

+ RUS Listed

Tested to UL 486A/B, UL File E6207



TYPE IKS


Features

- Manufactured from high strength copper alloy
- Electro-tin plated
- Two bolt design
- Longer peened bolt
- Serrated spacer bar
- For copper conductor only

Benefits

- Allows maximum conductivity and high breakage resistance
- Provides low contact resistance
- Allows maximum pressure to be applied directly to the conductor strands
- Permits a swivel action for easier installation
- Makes a secure connection

B



Catalog Number	Wire Range		Dimensions		
	Main	Tap	C	H	W
IKS-4/0	4/0-1/0	4/0-6	1.12	2.31	1.72
IKS-350	350kcmil-250kcmil	350kcmil-6	1.38	2.62	2.12
IKS-500	500kcmil-400kcmil	500kcmil-4	1.50	3.00	2.26
IKS-800	800kcmil-400kcmil	800kcmil-4/0	1.62	3.50	2.50
IKS-1000	1000kcmil-500kcmil	1000kcmil-4/0	2.00	4.03	3.03

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)


TYPE AK

Features

- Manufactured from heat treated aluminum alloy
- Triangular edges
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Electro-tin plated
- Spacer bar
- Hex Head
- Rated to 90° C

Benefits

- Provides maximum conductivity and strength for copper and aluminum conductors
- Bite into the conductor to break through surface oxides which eliminates wire brushing
- Application versatility
- Provides low contact resistance
- Separates dissimilar metals which prevents galvanic corrosion
- Provides ease of installation with standard wrenches



Catalog Number	Wire Range		Recommended Tightening Torque	Dimensions		
	Main	Tap		B	C	D
AK-6	6 str-10 sol	6 str-10 sol	165	.56	.75	1.88
AK-4	4 str-8 sol	4 str-10 sol	165	.62	.81	1.38
AK-2	2 str-6 str Compact	2 str-8 str	275	.69	.94	1.58
AK-1/0	1/0 str-2 str Compact	1/0 str-8 str	385	.75	1.00	1.92
AK-2/0	2/0 str-2 str Compact	2/0 str-8 str	385	.88	1.12	1.92
AK-4/0	4/0 str-2 str Compact	4/0 str-6 str	500	1.13	1.49	2.54
AK-350	350kcmil-1/0 str Compact	350kcmil-4 str	650	1.50	1.69	3.24
AK-500	500kcmil-400kcmil Compact	500kcmil-2 str Compact	825	1.73	2.00	3.62

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 DE-OX Inhibitor is recommended for all aluminum terminations.
 UL File E9998

B

TYPE DBA DBA-S

Features

- Manufactured from high strength aluminum alloy
- Heat treated
- Wax plated
- Neoprene washers
- Range taking
- Re-usable
- Type DBA-S - Spacer bar

Benefits

- Type DBA - Suitable for copper to copper or aluminum to aluminum conductors
- Type DBA-S - Suitable for copper and/or aluminum conductors in any combination
- Provides maximum strength
- Provides low contact resistance
- Hold the bolts captive and eliminates the possibility of loose hardware
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Separates dissimilar metals




Fig. 1

Fig. 2

Catalog Number	Figure Number	Wire Range		Dimensions		
		Main	Tap	C	W	H
DBA-2/0	1	2/0-2	2/0-10	1-1/8	1-5/8	1-5/8
DBA-250	1	250kcmil-1/0	250kcmil-10	1-5/16	2	2
DBA-350	1	350kcmil-4/0	350kcmil-10	1-9/16	2-11/32	2-1/4
DBA-500	1	500kcmil-350kcmil	500kcmil-10	1-3/4	2-1/2	2-3/4
DBA-800	1	800kcmil-400kcmil	800kcmil-3/0	1-7/8	2-7/8	3
DBA-1000	1	1000kcmil-500kcmil	1000kcmil-3/0	2-1/4	3-3/16	3-1/2
DBA-2/0S	2	2/0-2	2/0-10	1-1/8	1-5/8	1-5/8
DBA-250S	2	250kcmil-1/0	250kcmil-10	1-5/16	2	2
DBA-350S	2	350kcmil-4/0	350kcmil-10	1-9/16	2-11/32	2-1/4
DBA-500S	2	500kcmil-350kcmil	500kcmil-10	1-3/4	2-1/2	2-3/4
DBA-800S	2	800kcmil-400kcmil	800kcmil-3/0	1-7/8	2-7/8	3
DBA-1000S	2	1000kcmil-500kcmil	1000kcmil-3/0	2-1/4	3-3/16	3-1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.

TYPE IPC



Features

- Body is molded from tough, resilient glass-filled nylon
 - Compact design
 - Tin plated copper contact teeth
 - Insulation piercing
 - Perforated end tabs
 - Pre-filled with silicone lubricant
 - Versatile
 - Increased safety
- Horizontal line grid
 - Temperature rating 90° C

Benefits

- Provides high degree of breakage resistance and long dependable use
- Saves space
- Easily penetrates most types of insulation
- No need to strip the conductor which saves installation time
- Break out easily by hand
- Prevents oxidation and moisture from entering the contact area
- Can be used as a splice or tap connector
- Contains no external energized parts. Can be installed "hot" on energized conductors providing tap conductor is not under load.
- Provides a visual guide for proper installation of conductors




Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Wire Range		Volts	Current Rating		Dimensions			Torque Ft. Lbs.	Bolt Head Size
		Main	Tap		CU	AL	L	W	H		
IPC-1/0-2	3	1/0-8	2-8	300 (480 Grounded Y System)	130	100	1-7/32	1-15/32	2-5/16	16	1/2
IPC-4/0-6	2	4/0-4	6-14	600	75	60	1-27/64	1	1-7/8	13	1/2
IPC-4/0-2/0	3	4/0-2	2/0-6	600	195	150	1-21/32	1-7/8	2-7/8	25	1/2
IPC-250-4/0	2	250kcmil-1	4/0-6	600	260	205	1-7/8	2-11/32	3-11/32	30	5/8
IPC-350-4/0	3	350kcmil-4/0	4/0-10	300 (480 Grounded Y System)	260	205	1-43/64	2-7/16	3-1/8	25	5/8
IPC-350-350	4	350kcmil-4/0	350kcmil-4/0	300 (480 Grounded Y System)	350	280	2-43/64	2-23/32	3-1/4	25	5/8
IPC-500-12	1	500kcmil-250kcmil	10-12	300 (480 Grounded Y System)	40	35	1-43/64	2-7/16	3-1/4	25	5/8
IPC-500-250	1	500kcmil-250kcmil	250kcmil-4	600	290	230	2-27/64	2-29/32	3-3/4	55	5/8-11/16
IPC-500-500	1	500kcmil-300kcmil	500kcmil-250kcmil	600	430	350	3-3/16	3-5/8	5	75	7/8-7/8
IPC-750-500	1	750kcmil-500kcmil	500kcmil-350kcmil	600	430	350	3-3/16	3-5/8	5	75	7/8-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

B

TYPE GTA

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Listed and CSA Certified for 600 volts, 90° C
- Compact design
- Range taking
- Re-usable
- Lay-in main conductor
- Insulating cover available

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Ensures reliability for copper or aluminum conductors
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cable
- Eliminates taping

B




Fig. 1



Fig. 2



Catalog Number	Figure Number	Wire Range		Dimensions			Hex Size	
		Main	Tap	L	W	H	Main	Tap
GTA-2-2	1	2-12 str	2-12 AL 2-14 CU	1-1/4	9/16	1	Slot	Slot
GTA-0-0	1	1/0-2	1/0-12 AL 1/0-14 CU	1-9/16	3/4	1-1/8	Slot	Slot
GTA-250-0	1	250kcmil-1/0	1/0-12 AL 1/0-14 CU	2	15/16	1-7/16	5/16	Slot
GTA-250-250	1	250kcmil-1/0	250kcmil-6	2-1/8	15/16	1-7/16	5/16	5/16
GTA-350-350	1	350kcmil-4/0	350kcmil-6	2-7/16	1	1-11/16	3/8	3/8
GTA-500-500	1	500kcmil-350kcmil	500kcmil-2	2-15/16	1-1/4	2	3/8	3/8
GTA-750-500	1	750kcmil-500kcmil	500kcmil-2	3-3/8	1-5/16	2-7/16	3/8	3/8
GTA-750-750	2	750kcmil-500kcmil	750kcmil-1/0	3-3/8	2-5/8	2-7/16	1/2	1/2
GTA-1000-500	1	1000kcmil-750kcmil	500kcmil-2	3-3/8	1-15/16	2-7/16	1/2	3/8

Note: If ordering with cover, add suffix W/C to catalog number.

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Insulating covers are available for most connector sizes.

See page 119 for additional information on covers

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207


TYPE SPAR

Features

- Transparent flexible insulating cover
- Range adjustable trim-to-fit tip
- Unique shape and compact design
- Connector, cover and cable tie packaged together
- UL Listed and CSA Certified for 600 volts
- Dual Rated

Benefits

- No taping and allows visual inspection of splice
- Ensures proper fit of cover to cable
- Provides ease of installation, versatility and serviceability of connections made in tight spaces
- Provides ease of ordering
- Ensures reliability
- Use with copper or aluminum conductor



B

Catalog Number	Wire Range	Dimensions			Screw Size & Shape
		L	W	H	
SPAR-4	4-14	3.30	1.55	.76	slotted
SPAR-2	2-14	3.83	1.75	.95	slotted
SPAR-1/0	1/0-14	4.80	1.94	1.14	3/16" socket head
SPAR-250	250kcmil-6	5.67	2.41	1.29	5/16" socket head
SPAR-350	350kcmil-10	6.17	3.29	1.79	5/16" socket head
SPAR-500	500kcmil-4	7.94	3.66	2.28	3/8" socket head

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Not suitable for direct burial.

DE-OX Oxide Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

TYPE GTT

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Listed and CSA Certified for 600 volts, 90° C
- Compact design
- Range taking
- Re-usable
- Lay-in main conductor
- Insulating cover available

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Ensures reliability for copper or aluminum conductors
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cable
- Eliminates taping

B




Fig. 1



Fig. 2



Catalog Number	Figure Number	Wire Range		Dimensions			Hex Size	
		Main	Tap	L	W	H	Main	Tap
GTT-2-2	1	2-12 str	2-12 AL 2-14 CU	1-1/4	9/16	1	Slot	Slot
GTT-0-0	1	1/0-2	1/0-12 AL 1/0-14 CU	1-9/16	3/4	1-1/8	Slot	Slot
GTT-250-0	1	250kcmil-1/0	1/0-12 AL 1/0-14 CU	2	7/8	1-7/16	5/16	Slot
GTT-250-250	1	250kcmil-1/0	250kcmil-6	2-1/8	7/8	1-7/16	5/16	5/16
GTT-350-350	1	350kcmil-4/0	350kcmil-6	2-7/16	1	1-11/16	3/8	3/8
GTT-500-500	1	500kcmil-350kcmil	500kcmil-2	2-15/16	1-1/4	2	3/8	3/8
GTT-750-500	1	750kcmil-500kcmil	500kcmil-2	3-3/8	1-1/4	2-7/16	3/8	3/8
GTT-750-750	2	750kcmil-500kcmil	750kcmil-600kcmil	3-3/8	2-3/8	2-7/16	1/2	EH 3/4

Note: If ordering with cover, add suffix W/C to catalog number.

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

EH-External Hex

Insulating covers are available for most connector sizes.

See page 119 for additional information on covers

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

TYPE GTC

Features

- Snap closure
- Color coded
- UL Listed and CSA Certified for 600 volts, 90° C except for GTPC-750-750 and GTTC-750-750

Benefits

- Installs quickly and saves labor time by eliminating taping
- Provides ease of identification in the field
- Ensures reliability



Fig. 1



Fig. 2



Fig. 3

B

Catalog Number	Figure Number	Color	Dimensions			Used with Connector
			L	W	H	
GTC-2	1	Black	2-1/4	1-13/16	1-1/4	GTA-2-2: GTT-2-2
GTC-0	1	Black	2-1/2	2-3/32	1-3/8	GTA-0-0: GTT-0-0
GTC-250-350	1	Black	3-61/64	3-1/32	2	GTA-250-0: GTA-250-250 GTA-350-350 GTT-250-0: GTT-250-250 GTT-350-350
GTC-500	1	Black	4-1/8	3-1/16	2-31/32	GTA-500-500 GTT-500-500
GTC-750-500	1	Black	4-7/8	3-1/8	2-23/32	GTA-750-500 GTT-750-500
GTPC-750-750*	2	Black	4-7/8	4	2-7/8	GTA-750-750
GTTC-750-750*	3	Black	5-3/4	4-1/4	3-1/16	GTT-750-750

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Not UL Listed or CSA Certified

Tested to UL 486A/B, UL File E6207



TYPE GT2

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Listed for 600 volts, 90° C
- Compact design
- Range taking
- Re-usable
- Lay-in main conductor
- Supplied with cover

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Ensures reliability for copper or aluminum conductors
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cable
- Eliminates taping



Catalog Number	Wire Range Main & Tap	No. of Taps	Dimensions			Hex Size
			L	W	H	
GT2-250-W/C	250kcmil-2	2	31/32	2-9/32	1-15/16	5/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.
Tested to UL 486A/B, UL File E6207

TYPE GT4T

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Listed and CSA Certified for 600 volts, 90° C
- Compact design
- Range taking
- Re-usable
- Lay-in main conductor
- Insulating cover available

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Ensures reliability for copper or aluminum conductors
- Can make up to four taps off a single main which saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cable
- Eliminates taping




Fig. 1

Fig. 2

Catalog Number	Figure Number	Wire Range		No. of Taps	Dimensions			Hex Size	
		Main	Tap		L	W	H	Main	Tap
GT4T-250-2-1*	1	250kcmil-1/0	2-12 AL, 2-14 CU	4	2-3/16	1-1/8	1-35/64	5/16	Slot
GT4T-250-2-2*	2	250kcmil-1/0	2-12 AL, 2-14 CU	4	2-3/16	1-1/8	1-35/64	5/16	Slot
GT4T-350-2-1†	1	350kcmil-4/0	2-12 AL, 2-14 CU	4	2-17/32	1-1/8	1-17/32	3/8	Slot
GT4T-350-2-2*	2	350kcmil-4/0	2-12 AL, 2-14 CU	4	2-17/32	1-1/8	1-17/32	3/8	Slot
GT4T-500-2-1†	1	500kcmil-350kcmil	2-12 AL, 2-14 CU	4	2-31/32	1-1/4	1-11/16	3/8	Slot
GT4T-500-2-2†	2	500kcmil-350kcmil	2-12 AL, 2-14 CU	4	2-31/32	1-1/4	1-11/16	3/8	Slot
GT4T-500-0-1†	1	500kcmil-350kcmil	1/0-12 AL, 1/0-14 CU	4	2-31/32	1-1/4	1-11/16	3/8	Slot
GT4T-500-0-2†	2	500kcmil-350kcmil	1/0-12 AL, 1/0-14 CU	4	2-31/32	1-1/4	1-11/16	3/8	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* GTC-250-350 Cover can be used. See page 119.

† GTC-500 can be used. See page 119.

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

B

ILSCO Tap Connector Kits - Dual Rated

RoHS
Compliant

UL
LISTED
453G

CSA
LR-29601

TYPE GTA/GTT KITS

Features

- Kit includes connector, cover and 5cc DE-OX tube
- Manufactured from high strength aluminum alloy
- Cover has snap closure
- UL Listed and CSA Certified for 600 volts, 90° C

Benefits

- Saves time, convenient
- Suitable for use with copper or aluminum conductors
- Installs quickly, eliminates taping
- Ensures reliability



Fig. 1



Fig. 2




Fig. 3




Fig. 4

Catalog Number	Figure Number	Wire Range		No. of Taps	Dimensions			Hex Size	
		Main	Tap		L	W	H	Main	Tap
GTA-0-0-KIT	1	1/0-2	1/0-12 AL, 1/0-14 CU	1	3/4	1-7/16	1-1/8	Slot	Slot
GTA-2-2-KIT	1	2-12	2-12 AL, 2-14 CU	1	9/16	1-1/8	1	Slot	Slot
GTA-250-0-KIT	1	250kcmil-1/0	1/0-12 AL, 1/0-14 CU	1	7/8	2	1-7/16	5/16	Slot
GTA-250-250-KIT	1	250kcmil-1/0	250kcmil-6	1	7/8	2	1-7/16	5/16	5/16
GTT-0-0-KIT	2	1/0-2	1/0-12 AL, 1/0-14 CU	1	3/4	1-9/16	1-1/8	Slot	Slot
GTT-2-2-KIT	2	2-12	2-12 AL, 2-14 CU	1	9/16	1-1/4	1	Slot	Slot
GTT-250-0-KIT	2	250kcmil-1/0	1/0-12 AL, 1/0-14 CU	1	7/8	2	1-7/16	5/16	Slot
GTT-250-250-KIT	2	250kcmil-1/0	250kcmil-6	1	7/8	2-1/8	1-7/16	5/16	5/16
GT2-250-KIT	3	250kcmil-2	250kcmil-2	2	1-3/4	3-1/4	2-1/2	5/16	5/16
GT4T-250-2-2-KIT	4	250kcmil-1/0	2-12 AL, 2-14 CU	4	2-1/4	1	1-11/16	5/16	Slot
GT4T-350-2-2-KIT	4	350kcmil-4/0	2-12 AL, 2-14 CU	4	2-7/16	1	1-3/4	3/8	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Note: Covers are for indoor use only.

Tested to UL 486A/B, UL File E6207


TYPE MGTT

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Dual-Rated
- Compact design
- Range taking
- Re-usable
- Lay-in main conductor

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Can be used with copper and/or aluminum conductors
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cable



B

Catalog Number	Wire Range		No. of Tap Openings	Dimensions			Hex Size	
	Main	Tap		L	W	H	Main	Tap
M2GTT-250-250	250kcmil-1/0	250kcmil-6	2	2	1-3/4	1-5/8	5/16	5/16
M2GTT-350-350	350kcmil-4/0	350kcmil-6	2	2-1/4	2	1-11/16	5/16	5/16
M3GTT-350-350	350kcmil-4/0	350kcmil-6	3	2-1/4	3	1-11/16	5/16	5/16
M2GTT-500-500	500kcmil-350kcmil	500kcmil-2	2	2-3/4	2-3/8	1-13/16	3/8	3/8
M3GTT-500-500	500kcmil-350kcmil	500kcmil-2	3	2-3/4	3-1/2	1-13/16	3/8	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.

TYPE PTA

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Listed and CSA Certified for 600 volts, 90° C
- Compact design
- Range taking
- Re-usable
- Lay-in main conductors
- Supplied with insulating cover

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Ensures reliability for copper or aluminum conductors
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cables
- Eliminates taping



Fig. 1



Fig. 2



Fig. 3

Catalog Number Connector	Figure Number	Main Wire Range	Bottom Tap Range	Dimensions			Hex Size	
				H	W	D	Main	Tap
PTA2-500-500-W/C	1	Two: 500kcmil-250kcmil	Two: 500kcmil-4	3-15/16	3-1/2	1-1/4	3/8	3/8
PTA2-750-500-W/C	1	Two: 750kcmil-350kcmil	Two: 500kcmil-4	3-5/8	4-3/32	1-5/16	3/8	3/8
PTA4-750-500-W/C	2	Four: 750kcmil-350kcmil	Two: 500kcmil-4	5-7/8	4-3/32	1-5/16	3/8	3/8
PTA26-500-4/0*+	3	Two: 500kcmil-4/0	Four: 4/0-6 Two: 2-14	3-15/16	3-1/2	1-1/4	3/8	5/16 Slotted

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Note: W/C indicates product is supplied with insulating cover.

* Not CSA Certified.

+ Cover must be ordered separately. For non UL cover, order 1 each RO614W00A and RO615W00A.

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

TYPE PCT

Features

- Transparent flexible insulating cover
- Captive pressure screws
- Self-closing openings
- Access from both sides of connector
- Broad wire range: 800kcmil-14
- UL Listed for 600 volts, 90° C
- Dual Rated

Benefits

- No taping and allows visual inspection of connection
- No wasted time finding screws
- No lost or loose caps and plugs
- Provides greater versatility
- Reduces inventory
- Ensures reliability
- For copper or aluminum conductor




Fig. 1 (Patented)




Fig. 2

Catalog Number	Figure No.	No. Of Ports	Wire Range	Ampere Rating	Dimensions			Hex Size
					L	W	H	
PCT-2-4	1	2	4-14	95	1.46	1.57	1.43	slot
PCT-4-4	1	4	4-14	95	2.46	1.57	1.43	slot
PCT-6-4	1	6	4-14	95	3.46	1.57	1.43	slot
PCT-8-4	1	8	4-14	95	4.46	1.57	1.43	slot
PCT-2-2/0	2	2	2/0-14	195	2.61	2.30	1.97	3/16
PCT-4-2/0	2	4	2/0-14	195	4.30	2.30	1.97	3/16
PCT-6-2/0	2	6	2/0-14	195	5.98	2.30	1.97	3/16
PCT-8-2/0	2	8	2/0-14	195	7.67	2.30	1.97	3/16
PCT-2-4/0	2	2	4/0-6	260	2.33	2.49	2.25	5/16
PCT-4-4/0	2	4	4/0-6	260	4.19	2.49	2.25	5/16
PCT-6-4/0	2	6	4/0-6	260	6.05	2.49	2.25	5/16
PCT-8-4/0	2	8	4/0-6	260	7.91	2.49	2.25	5/16
PCT-2-350	2	2	350 kcmil-6	350	2.75	2.69	2.65	5/16
PCT-4-350	2	4	350 kcmil-6	350	5.06	2.69	2.65	5/16
PCT-6-350	2	6	350 kcmil-6	350	7.37	2.69	2.65	5/16
PCT-8-350	2	8	350 kcmil-6	350	9.68	2.69	2.65	5/16
PCT-2-600	2	2	600 kcmil-4	475	3.17	3.20	3.27	3/8
PCT-4-600	2	4	600 kcmil-4	475	5.73	3.20	3.27	3/8
PCT-6-600	2	6	600 kcmil-4	475	8.29	3.20	3.27	3/8
PCT-8-600	2	8	600 kcmil-4	475	10.86	3.20	3.27	3/8
PCT-2-800	2	2	800kcmil-250kcmil	555	3.91	3.34	3.30	1/2
PCT-4-800	2	4	800kcmil-250kcmil	555	7.03	3.34	3.30	1/2
PCT-6-800	2	6	800kcmil-250kcmil	555	10.15	3.34	3.30	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Not suitable for direct burial.

Tested to UL 486A/B, UL File E6207

<p>TA</p>  <p>128</p>	<p>AU</p>  <p>129</p>	<p>T3A</p>  <p>130</p>	<p>T4A4</p>  <p>131</p>	<p>PB</p>  <p>132</p>	<p>TLK</p>  <p>133</p>
<p>USGL</p>  <p>134</p>	<p>SPA</p>  <p>135</p>	<p>CA</p>  <p>136</p>	<p>GTA</p>  <p>137</p>	<p>GTT</p>  <p>138</p>	<p>GTC</p>  <p>139</p>
<p>GT2</p>  <p>140</p>	<p>GT4T</p>  <p>141</p>	<p>MGTT</p>  <p>142</p>	<p>PTA</p>  <p>143</p>	<p>PDH</p>  <p>144 - 145</p>	<p>PDE</p>  <p>146</p>
<p>PDL</p>  <p>147</p>	<p>PDS</p>  <p>148 - 149</p>	<p>PDM</p>  <p>150 - 151</p>	<p>LDAU, LDBU</p>  <p>152</p>	<p>PDBU</p>  <p>153 - 155</p>	<p>LDA, LDB</p>  <p>156</p>
<p>PDA, PDC</p>  <p>157</p>	<p>PDB</p>  <p>158 - 163</p>	<p>IPC</p>  <p>164</p>	<p>AK</p>  <p>165</p>	<p>DBA/DBA-S</p>  <p>166</p>	<p>AGC</p>  <p>167</p>
<p>SGC</p>  <p>167</p>	<p>SGB</p>  <p>168</p>	<p>GBL</p>  <p>169</p>	<p>GBT</p>  <p>170</p>	<p>PED-Z</p>  <p>171</p>	<p>PED-X, PSA-Z</p>  <p>172</p>
<p>PEC</p>  <p>172</p>	<p>PED-CP</p>  <p>173</p>	<p>PET</p>  <p>174</p>	<p>PTT</p>  <p>175</p>	<p>NB</p>  <p>176</p>	<p>USPA-SS</p>  <p>177</p>
<p>DBK</p>  <p>178</p>	<p>ASK</p>  <p>178</p>	<p>SS, SSK, SSKC</p>  <p>179</p>	<p>PG</p>  <p>180</p>	<p>GRM</p>  <p>181</p>	<p>GRF</p>  <p>181</p>

Mechanical Copper

<p>SLU/SAU 182</p>	<p>SLS/SAS 182</p>	<p>E 183</p>	<p>H 183</p>	<p>SLUH 184</p>	<p>LO 185</p>
<p>VT/LO-S 186</p>	<p>XT 187</p>	<p>LY 187</p>	<p>CP 188</p>	<p>CO 189 - 190</p>	<p>COPP 191</p>
<p>TC 192</p>	<p>SX 193</p>	<p>2SC 194</p>	<p>N 195</p>	<p>MU 196</p>	<p>LU 196</p>
<p>CL 197 - 198</p>	<p>HL 199</p>	<p>CL 200</p>	<p>CL 200</p>	<p>H2L 201</p>	<p>H3L 202</p>
<p>CGRC 203</p>	<p>BGRC 204</p>	<p>SRC 205</p>	<p>GRC 206</p>	<p>DCGC 207</p>	<p>BGC 208 - 209</p>
<p>BGDB 210</p>	<p>D167 211</p>	<p>CAN 212</p>	<p>N-174 212</p>	<p>IK 213</p>	<p>IK3 214</p>
		<p>SK 215</p>	<p>IKB 216</p>	<p>IKS 217</p>	<p>TORQUE INDEX 218</p>



TYPE TA

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Chamfered wire entry
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- Application versatility



Catalog Number	Figure Number	Wire Range	Bolt Size	Dimensions										Hex Size
				C	E	F	G	H	J	K	R	T		
TA-6-S	1	4-14	1/4	17/64	11/16	1-1/16	1/4	1/2	-	3/32	1/2	41/64	S	
TA-2	1	One: 2-14 Two: 10-14 CU 10-12 AL	1/4	17/64	11/16	1-5/32	5/16	1/2	-	7/64	9/16	3/4	S	
TA-0	1	One: 1/0-14 Two: 4-12	1/4	17/64	27/32	1-15/32	7/16	5/8	-	3/16	25/32	29/32	S	
TA-2/0	2	2/0-14	1/4	17/64	27/32	1-15/32	7/16	5/8	-	3/16	25/32	1-1/32	3/16	
TA-250	2	250kcmil-6	5/16	21/64	1	2	15/32	1	-	1/4	1-1/8	1-21/64	5/16	
TA-300	2	300kcmil-6	1/4	9/32	1	2	1/2	55/64	-	1/4	1-1/8	1-11/32	5/16	
TA-350	2	350kcmil-6	3/8	13/32	1-1/8	2-1/4	1/2	1-1/8	-	1/4	1-1/4	1-29/64	3/8	
TA-500	2	500kcmil-4	3/8	13/32	1-19/32	2-13/16	7/8	1-1/2	-	5/16	1-13/16	1-13/16	3/8	
TA-500-S	3	One: 600kcmil-4 Two: 250kcmil-1/0	3/8	13/32	1-1/2	2-13/16	5/8	1-5/16	-	5/16	1-13/16	2-3/16	1/2	
TA-600	2	600kcmil-2	3/8	13/32	1-13/16	3-3/16	7/8	1-1/2	-	7/16	1-9/16	1-31/32	1/2	
TA-800	2	800kcmil-300kcmil	5/8	21/32	1-3/4	3-3/8	7/8	1-3/4	-	1/2	1-15/16	2-15/64	1/2	
TA-800-S	4	800kcmil-3/0	5/8	21/32	1-3/4	3-1/4	11/16	1-5/16	-	1/2	1-13/16	2-3/16	1/2	
TA-1000	2	1000kcmil-350kcmil	5/8	21/32	1-3/4	3-3/8	7/8	1-3/4	-	1/2	1-15/16	2-25/64	9/16	
TA-1000-S	4	1000kcmil-500kcmil	5/8	21/32	1-3/4	3-1/4	11/16	1-7/16	-	1/2	1-13/16	2-3/16	9/16	
TA-350-2NS	5	350kcmil-6	1/2	9/16	3	4-5/16	5/8	1-1/8	1-3/4	5/16	1-3/8	1-29/64	3/8	
TA-600-2NS	5	600kcmil-2	1/2	9/16	3-5/16	4-11/16	5/8	1-1/2	1-3/4	7/16	1-3/8	1-59/64	1/2	
TA-800-2NS	5	800kcmil-300kcmil	1/2	9/16	3-1/8	4-3/4	5/8	1-3/4	1-3/4	1/2	1-15/16	2-3/16	1/2	
TA-1000-2NS	5	1000kcmil-500kcmil	1/2	9/16	3-1/8	4-3/4	5/8	1-3/4	1-3/4	1/2	1-15/16	2-27/64	9/16	
TA-350-2N	6	350kcmil-6	1/2	9/16	3-1/4	5-1/2	5/8	1-1/4	1-3/4	3/8	1-1/2	1-21/32	(2)3/8	
TA-600-2N	6	600kcmil-2	1/2	9/16	3-1/4	5-1/2	5/8	1-3/8	1-3/4	3/8	1-1/2	1-31/32	(2)3/8	
TA-800-2N	6	800kcmil-300kcmil	1/2	9/16	3-5/8	5.97	5/8	1-1/2	1-3/4	1/2	1.813	2-15/64	(2)1/2	
TA-1000-2N	6	1000kcmil-350kcmil	1/2	9/16	3-5/8	5.97	5/8	1-5/8	1-3/4	1/2	1.813	2-25/64	(2)1/2	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

TYPE AU

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Chamfered wire entry
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- Application versatility




Fig. 1



Fig. 2



Fig. 3



Fig. 4



Catalog Number	Figure Number	Wire Range	Bolt Size	Dimensions									Hex Size
				C	E	F	G	H	J	K	R	T	
AU-0	1	Two: 1/0-14	1/4	17/64	27/32	1-15/32	7/16	1-1/8	-	3/16	51/64	29/32	S
AU-2/0	2	Two: 2/0-14	1/4	17/64	27/32	1-15/32	27/64	1-1/4	-	3/16	51/64	1-1/32	3/16
AU-250	2	Two: 250kcmil-6	3/8	25/64	1-9/16	2-9/16	7/8	1-21/32	-	1/4	1-3/16	1-9/32	5/16
AU-350	2	Two: 350kcmil-6	1/2	9/16	1-3/4	2-7/8	7/8	1-57/64	-	1/4	1-1/4	1-3/8	5/16
AU-600	2	Two: 600kcmil-2	1/2	17/32	1-13/16	3-3/16	5/8	2-13/32	-	7/16	1-9/16	1-31/32	1/2
AU-800	2	Two: 800kcmil-300kcmil	5/8	21/32	1-3/4	3-3/8	7/8	3-3/16	-	1/2	1-15/16	2-15/64	1/2
AU-1000	2	Two: 1000kcmil-500kcmil	5/8	21/32	1-3/4	3-3/8	7/8	3-3/16	-	1/2	1-15/16	2-25/64	9/16
AU-600-2NS	3	Two: 600kcmil-2	1/2	9/16	3-5/16	4-11/16	5/8	2-13/32	1-3/4	7/16	1-3/8	2-3/64	1/2
AU-800-2NS	3	Two: 800kcmil-300kcmil	1/2	9/16	3-1/8	4-3/4	5/8	3-3/16	1-3/4	1/2	1-15/16	2-3/16	1/2
AU-1000-2NS	3	Two: 1000kcmil-500kcmil	1/2	9/16	3-1/8	4-3/4	5/8	3-3/16	1-3/4	1/2	1-5/8	2-33/64	9/16
AU-350-2N	3	Two: 350kcmil-6	1/2	9/16	3	4-5/16	5/8	2	1-3/4	5/16	1-3/8	1-29/64	5/16
AU-350-N*	4	Two: 350kcmil-6	1/2	9/16	3-1/4	5-1/2	5/8	2-3/4	1-3/4	3/8	1-1/2	1-31/32	5/16
AU-600-2N*	4	Two: 600kcmil-2	1/2	9/16	3-1/4	5-1/2	5/8	2-3/4	1-3/4	3/8	1-1/2	1-31/32	1/2
AU-800-2N*	4	Two: 800kcmil-300kcmil	1/2	9/16	3-5/8	5-31/32	5/8	3	1-3/4	1/2	1-13/16	2-15/64	1/2
AU-1000-2N*	4	Two: 1000kcmil-500kcmil	1/2	9/16	3-5/8	5-31/32	5/8	3-1/4	1-3/4	1/2	1-13/16	2-25/64	9/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

* Mounting hole spacing from side to side, hole to hole is .875

TYPE T3A

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro tin plated
- Chamfered wire entry
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Must be mounted with a minimum of 2 bolts
- Rated to 90° C

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- Application versatility




Fig. 1



Fig. 2



Fig. 3

Catalog Number	Figure Number	Wire Range	Bolt Size	Dimensions									Hex Size
				C	E	F	G	H	J	K	R	T	
T3A2-2	1	Three: 2-14	5/16	11/32	1-11/16	2-3/16	11/32	1-19/32	7/8	3/16	5/8	13/16	Slot
T3A2-0	1	Three: 1/0-14	3/8	7/16	2-5/32	2-29/32	11/32	1-15/16	1	1/4	7/8	15/16	Slot
T3A2-3/0N	1	Three: 3/0-6	1/2	9/16	3	3-7/8	5/8	2-13/16	1-3/4	5/16	1-1/8	1-1/2	5/16
T3A2-250N	1	Three: 250kcmil-6	1/2	9/16	3	4	5/8	2-13/16	1-3/4	5/16	1-3/16	1-17/32	5/16
T3A2-350N	1	Three: 350kcmil-6	1/2	9/16	3	4-5/16	5/8	3	1-3/4	5/16	1-3/8	1-17/32	5/16
T3A2-600N*	3	Three: 600kcmil-2	1/2	9/16	3-1/4	5-1/2	5/8	3-1/2	1-3/4	3/8	1-1/2	1-49/64	3/8
T3A2-800N*	3	Three: 800kcmil-350kcmil	1/2	9/16	3-5/8	5-31/32	5/8	4-1/8	1-3/4	1/2	1-13/16	2-21/64	5/16
T3A2-1000N*	3	Three: 1000kcmil-500kcmil	1/2	9/16	3-5/8	5-31/32	5/8	4-7/8	1-3/4	1/2	1-13/16	2-21/64	3/8
T3A4-2	2	Three: 2-14	5/16	11/32	1-11/16	2-3/16	11/32	1-19/32	7/8	3/16	5/8	13/16	Slot
T3A4-0	2	Three: 1/0-14	3/8	7/16	2-5/32	2-29/32	11/32	1-15/16	1	1/4	7/8	15/16	Slot
T3A4-3/0N	2	Three: 3/0-6	1/2	9/16	3	3-7/8	5/8	2-13/16	1-3/4	5/16	1-1/8	1-1/2	5/16
T3A4-250N	2	Three: 250kcmil-6	1/2	9/16	3	4	5/8	2-13/16	1-3/4	5/16	1-3/16	1-17/32	5/16
T3A4-350N	2	Three: 350kcmil-6	1/2	9/16	3	4-5/16	5/8	3	1-3/4	5/16	1-3/8	1-17/32	5/16
T3A4-600N*	3	Three: 600kcmil-2	1/2	9/16	3-1/4	5-1/2	5/8	3-1/2	1-3/4	3/8	1-1/2	1-49/64	1/2
T3A4-800N*	3	Three: 800kcmil-350kcmil	1/2	9/16	3-5/8	5-31/32	5/8	4-1/8	1-3/4	1/2	1-13/16	2-21/64	1/2
T3A4-1000N*	3	Three: 1000kcmil-500kcmil	1/2	9/16	3-5/8	5-31/32	5/8	4-7/8	1-3/4	1/2	1-13/16	2-21/64	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

* Mounting hole spacing from side to side, hole to hole is .875

TYPE T4A4

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Chamfered wire entry
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Must be mounted with a minimum of 4 bolts
- Rated to 90° C

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- Application versatility




Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Wire Range	Bolt Size	Dimensions										Hex Size
				C	E	F	G	H	J	K	R	T		
T4A4-250N*	1	250kcmil-6	1/2	9/16	3	4	5/8	3-49/64	1-3/4	5/16	1-3/16	1-17/32	5/16	
T4A4-350N*	1	350kcmil-6	1/2	9/16	3	4-5/16	5/8	4-1/64	1-3/4	5/16	1-3/8	1-17/32	5/16	
T4A4-600N*	3	600kcmil-2	1/2	9/16	3-1/4	5-1/2	5/8	5	1-3/4	3/8	1-1/2	1-7/8	1/2	
T4A4-800N*	2	800kcmil-350kcmil	1/2	9/16	3-5/8	5-31/32	5/8	6	1-3/4	1/2	1-13/16	2-13/64	1/2	
T4A4-1000N*	4	1000kcmil-350kcmil	1/2	9/16	3-5/8	5-31/32	5/8	6-1/2	1-3/4	1/2	1-13/16	2-13/64	1/2	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

* Mounting hole spacing from side to side, hole to hole is .875

TYPE PB

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Chamfered wire entry
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Stacked design
- Rated to 90° C

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- Application versatility
- Saves space and reduces installation time




Fig. 1 Fig. 2 Fig. 3 Fig. 4 Fig. 5 Fig. 6 Fig. 7 Fig. 8

Catalog Number	Figure Number	Wire Range	Bolt Size	Dimensions									Hex Size
				C	E	F	G	H	J	K	R	T	
PB2-300	1	300kcmil-6	5/16	21/64	1	3	15/32	1	-	5/16	2	2-5/16	5/16
PB2-500	2	500kcmil-4/0	1/4	9/32	1-11/16	2-29/32	1/4	1-7/16	11/16	5/8	2-3/8	1-27/64	3/8
PB2-600	4	600kcmil-2	3/8	13/32	2-11/32	4-29/32	3/8	1-1/2	1-3/8	5/8	3	3-29/64	1/2
PB3-600	6	600kcmil-2	3/8	13/32	2-11/32	4-29/32	3/8	2-15/32	1-3/8	5/8	3	3-29/64	1/2
PB4-600	8	600kcmil-2	3/8	13/32	2-11/32	4-29/32	3/8	2-15/32	1-3/8	5/8	3	3-29/64	1/2
PB2-750	4	750kcmil-1/0	3/8	13/32	2-11/32	4-29/32	3/8	1-11/16	1-3/8	5/8	3	3-29/64	1/2
PB4-750	8	750kcmil-1/0	3/8	13/32	2-11/32	4-29/32	3/8	2-5/8	1-3/8	5/8	3	3-29/64	1/2
PB3-600-2N	5	600kcmil-2	1/2	9/16	3-1/8	5-11/16	3/8	2-15/32	1-3/4	3/4	3	3-29/64	1/2
PB2-600-2N	3	600kcmil-2	1/2	9/16	3-1/8	5-11/16	3/8	1-1/2	1-3/4	3/4	3	3-29/64	1/2
PB2-750-2N	3	750kcmil-1/0	1/2	9/16	3-1/8	5-11/16	3/8	1-11/16	1-3/4	3/4	3	3-29/64	1/2
PB4-600-2N	7	600kcmil-2	1/2	9/16	3-1/8	5-11/16	3/8	2-15/32	1-3/4	3/4	3	3-29/64	1/2
PB4-750-2N	7	750kcmil-1/0	1/2	9/16	3-1/8	5-11/16	3/8	3-1/16	1-3/4	3/4	3	3-29/64	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 DE-OX Inhibitor is recommended for all aluminum terminations.
 Tested to UL 486A/B, UL File E6207

ILSCO Transformer Lug Kits - Dual Rated

RoHS
Compliant

UL
LISTED
453G

SA
LR-2960¹

TYPE TLK

Features

- Connectors manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Chamfered wire entry
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Kit includes all required hardware
- Rated to 90° C

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- Application versatility



C

Catalog Number	XFMR KVA Size	Lugs in Kit	Bolts in Kit
TLK-1	15-37 1/2 1-Phase, 15-45 3-Phase	Eight TA-2, Four TA-250	Eight 1/4-20 x 3/4 Bolts, Eight 1/4-20 Flange Nuts
TLK-2	50-75 1-Phase, 75-112 1/2 3-Phase	Twelve TA-250	Eight 1/4-20 x 3/4 Bolts, Eight 1/4-20 x 1-3/4 Bolts and Sixteen 1/4-20 Flange Nuts
TLK-3	100-167 1-Phase, 150-300 3-Phase	Three TA-250 and Twenty-two TA-600	Three 1/4-20 x 3/4 Bolts, Three 1/4-20 nuts, Sixteen 3/8-16-2 Bolts, Sixteen 3/8-16 Flange Nuts, Sixteen 3/8 flat washer
TLK-4	500 3-Phase	Twenty-nine TA-600	Eighteen 3/8-16 x 2 Bolts and Eighteen 3/8-16 Flange Nuts

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Dimensional data for connectors see Type TA.

DE-OX Inhibitor is recommended for all aluminum terminations.





TYPE USGL

Features

- Compact, lay-in design
- Manufactured from high strength 6061-T6 aluminum for strength and conductivity
- High strength aluminum 5/16" drive torque screw
- Clear plated coating
- Designed for installation on standard NEMA mounting holes
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- 1-3/4" NEMA spacing on mounting holes
- Rated to 90° C

Benefits

- Solves the problem of trying to bend larger size cables into place
- Dual rated for aluminum or copper conductors
- Enables range taking
- Provides low contact resistance
- Conforms to industry standards
- Application versatility
- Industry standard



Catalog Number	Number of Mtg. Holes	Number of Ports	Wire Range	Mounting Bolt Size	Dimensions			Hex Size
					Width	Length	Height	
USGL-350R21	2	1	350 kcmil-6	1/2	1.50	4.69	1.56	5/16
USGL-350R42	4	2	350 kcmil-6	1/2	2.75	4.69	1.56	5/16
USGL-350R43	4	3	350 kcmil-6	1/2	4.00	4.69	1.56	5/16
USGL-350R64	6	4	350 kcmil-6	1/2	5.25	4.69	1.56	5/16
USGL-350R86	8	6	350 kcmil-6	1/2	7.75	4.69	1.56	5/16
USGL-350R128	12	8	350 kcmil-6	1/2	10.25	4.69	1.56	5/16
USGL-600R21	2	1	600 kcmil-2	1/2	1.68	5.35	1.69	5/16
USGL-600R42	4	2	600 kcmil-2	1/2	3.08	5.35	1.69	5/16
USGL-600R63	6	3	600 kcmil-2	1/2	4.81	5.35	1.69	5/16
USGL-600R84	8	4	600 kcmil-2	1/2	6.45	5.35	1.69	5/16
USGL-600R106	10	6	600 kcmil-2	1/2	8.69	5.35	1.69	5/16
USGL-600R148	14	8	600 kcmil-2	1/2	11.70	5.35	1.69	5/16
USGL-750R21	2	1	750 kcmil-1/0	1/2	1.76	5.97	1.81	5/16
USGL-750R42	4	2	750 kcmil-1/0	1/2	3.31	5.97	1.81	5/16
USGL-750R63	6	3	750 kcmil-1/0	1/2	4.88	5.97	1.81	5/16
USGL-750R84	8	4	750 kcmil-1/0	1/2	6.45	5.97	1.81	5/16
USGL-750R126	12	6	750 kcmil-1/0	1/2	9.95	5.97	1.81	5/16
USGL-750R148	14	8	750 kcmil-1/0	1/2	12.30	5.97	1.81	5/16
USGL-1000R21	2	1	1000 kcmil-1/0	1/2	2.00	6.19	1.88	5/16
USGL-1000R22	2	2	1000 kcmil-1/0	1/2	3.68	6.19	1.88	5/16
USGL-1000R42	4	2	1000 kcmil-1/0	1/2	3.68	6.19	1.88	5/16
USGL-1000R43	4	3	1000 kcmil-1/0	1/2	5.37	6.19	1.88	5/16
USGL-1000R63	6	3	1000 kcmil-1/0	1/2	5.37	6.19	1.88	5/16
USGL-1000R84	8	4	1000 kcmil-1/0	1/2	7.06	6.19	1.88	5/16
USGL-1000R126	12	6	1000 kcmil-1/0	1/2	10.44	6.19	1.88	5/16
USGL-1000R168	16	8	1000 kcmil-1/0	1/2	13.81	6.19	1.88	5/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Add T for tin plated, P for Pre-filled with De-Ox


TYPE SPA

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Chamfered wire entry
- Rounded bottoms
- Large screw diameters
- Wire stop in center
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- Facilitates taping
- Ensures all wire strands are held securely
- Prevents dissimilar metals coming into contact
- Application versatility



Catalog Number	Wire Range	Dimensions			Number of Screws	Screw Diameter	Hex Size
		L	W	H			
SPA-2	2-14	1-3/16	29/64	9/16	2	3/8	Slot
SPA-0	1/0-14	1-29/32	5/8	11/16	2	7/16	3/16
SPA-250	250kcmil-6	2-5/16	7/8	1	2	5/8	5/16
SPA-350	350kcmil-10	2-15/32	1	1-1/4	2	11/16	5/16
SPA-500	500kcmil-4	3-7/8	1-1/8	1-5/8	2	13/16	3/8
SPA-750	750kcmil-250kcmil	5-7/16	1-3/8	1-3/4	4	15/16	1/2
SPA-1000	1000kcmil-500kcmil	8-11/16	1-3/4	1-3/4	6	1-1/8	9/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 DE-OX Inhibitor is recommended for all aluminum terminations.
 Tested to UL 486A/B, UL File E6207

TYPE CA

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Recognized for 75° C and CSA Certified
- Design includes bossed mounting holes
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Acts as an anti-rotation device and prevents connector from turning
- Application versatility

Fig. 1 & 2 Bottom View





Fig. 3 Bottom view (mounting configuration)

Catalog Number	Figure Number	Wire Range	Dimensions			Style and Size of Boss	Flat Bottom	Bossed Hole Tapped	Two Mounting Holes Tapped	Hex Size
			L	W	H					
CA4SP	1	2-14 CU 2-12 AL	15/32	1/2	23/32	Sq. .229	-	10-32	-	Slot
CA4RP	1	2-14 CU 2-12 AL	15/32	1/2	23/32	Rd. .229	-	10-32	-	Slot
CA5SP	2	1/0-14 CU 1/0-12 AL	5/8	9/16	11/16	Sq. .229	-	10-32	-	Slot
CA5RP	2	1/0-14 CU 1/0-12 AL	5/8	9/16	11/16	Rd. .229	-	10-32	-	Slot
CA6RP	3	250kcmil-6	1	13/16	1	Rd. .285	-	1/4-20	-	5/16
CA7	4	500kcmil-1/0	1-3/8	1-15/64	1-13/32	-	YES	-	1/4-20	3/8
CA8	4	750kcmil-500kcmil	1-15/16	1-3/8	1-3/4	-	YES	-	5/16-18	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 DE-OX Oxide Inhibitor is recommended for all aluminum terminations.
 Tested to UL 486A/B, UL File E6207

TYPE GTA

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Listed and CSA Certified for 600 volts, 90° C
- Compact design
- Range taking
- Re-usable
- Lay-in main conductor
- Insulating cover available

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Ensures reliability for copper or aluminum conductors
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cable
- Eliminates taping




Fig. 1



Fig. 2



Catalog Number	Figure Number	Wire Range		Dimensions			Hex Size	
		Main	Tap	L	W	H	Main	Tap
GTA-2-2	1	2-12 str	2-12 AL 2-14 CU	1-1/4	9/16	1	Slot	Slot
GTA-0-0	1	1/0-2	1/0-12 AL 1/0-14 CU	1-9/16	3/4	1-1/8	Slot	Slot
GTA-250-0	1	250kcmil-1/0	1/0-12 AL 1/0-14 CU	2	15/16	1-7/16	5/16	Slot
GTA-250-250	1	250kcmil-1/0	250kcmil-6	2-1/8	15/16	1-7/16	5/16	5/16
GTA-350-350	1	350kcmil-4/0	350kcmil-6	2-7/16	1	1-11/16	3/8	3/8
GTA-500-500	1	500kcmil-350kcmil	500kcmil-2	2-15/16	1-1/4	2	3/8	3/8
GTA-750-500	1	750kcmil-500kcmil	500kcmil-2	3-3/8	1-5/16	2-7/16	3/8	3/8
GTA-750-750	2	750kcmil-500kcmil	750kcmil-1/0	3-3/8	2-5/8	2-7/16	1/2	1/2
GTA-1000-500	1	1000kcmil-750kcmil	500kcmil-2	3-3/8	1-15/16	2-7/16	1/2	3/8

Note: If ordering with cover, add suffix W/C to catalog number.

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Insulating covers are available for most connector sizes.

See page 139 for additional information on covers

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

TYPE GTT

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Listed and CSA Certified for 600, 90° C
- Compact design
- Range taking
- Re-usable
- Lay-in main conductor
- Insulating cover available

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Ensures reliability for copper or aluminum conductors
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cable
- Eliminates taping




Fig. 1



Fig. 2



Catalog Number	Figure Number	Wire Range		Dimensions			Hex Size	
		Main	Tap	L	W	H	Main	Tap
GTT-2-2	1	2-12 str	2-12 AL 2-14 CU	1-1/4	9/16	1	Slot	Slot
GTT-0-0	1	1/0-2	1/0-12 AL 1/0-14 CU	1-9/16	3/4	1-1/8	Slot	Slot
GTT-250-0	1	250kcmil-1/0	1/0-12 AL 1/0-14 CU	2	7/8	1-7/16	5/16	Slot
GTT-250-250	1	250kcmil-1/0	250kcmil-6	2-1/8	7/8	1-7/16	5/16	5/16
GTT-350-350	1	350kcmil-4/0	350kcmil-6	2-7/16	1	1-11/16	3/8	3/8
GTT-500-500	1	500kcmil-350kcmil	500kcmil-2	2-15/16	1-1/4	2	3/8	3/8
GTT-750-500	1	750kcmil-500kcmil	500kcmil-2	3-3/8	1-1/4	2-7/16	3/8	3/8
GTT-750-750	2	750kcmil-500kcmil	750kcmil-600kcmil	3-3/8	2-3/8	2-7/16	1/2	EH 3/4

Note: If ordering with cover, add suffix W/C to catalog number.

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

EH-External Hex

Insulating covers are available for most connector sizes.

See page 139 for additional information on covers

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

ILSCO Insulating Covers For GTA-GTT

RoHS
Compliant

UL
LISTED
453G

CSA
LR-29601

TYPE GTC

Features

- Snap closure
- Color coded
- UL Listed and CSA Certified for 600 volts, 90° C except for GTPC-750-750 and GTTC-750-750

Benefits

- Installs quickly and saves labor time by eliminating taping
- Provides ease of identification in the field
- Ensures reliability



Fig. 1



Fig. 2



Fig. 3

Catalog Number	Figure Number	Color	Dimensions			Used with Connector
			L	W	H	
GTC-2	1	Black	2-1/4	1-13/16	1-1/4	GTA-2-2: GTT-2-2
GTC-0	1	Black	2-1/2	2-3/32	1-3/8	GTA-0-0: GTT-0-0
GTC-250-350	1	Black	3-61/64	3-1/32	2	GTA-250-0: GTA-250-250 GTA-350-350 GTT-250-0: GTT-250-250 GTT-350-350
GTC-500	1	Black	4-1/8	3-1/16	2-31/32	GTA-500-500 GTT-500-500
GTC-750-500	1	Black	4-7/8	3-1/8	2-23/32	GTA-750-500 GTT-750-500
GTPC-750-750*	2	Black	4-7/8	4	2-7/8	GTA-750-750
GTTC-750-750*	3	Black	5-3/4	4-1/4	3-1/16	GTT-750-750

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Not UL Listed or CSA Certified

Tested to UL 486A/B, UL File E6207

C





TYPE GT2

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Listed for 600 volts, 90° C
- Compact design
- Range taking
- Re-usable
- Lay-in main conductor
- Supplied with cover

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Ensures reliability for copper or aluminum conductors
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cable
- Eliminates taping



Catalog Number	Wire Range Main & Tap	No. of Taps	Dimensions			Hex Size
			L	W	H	
GT2-250-W/C	250kcmil-2	2	31/32	2-9/32	1-15/16	5/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.
Tested to UL 486A/B, UL File E6207

TYPE GT4T

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Listed and CSA Certified for 600 volts, 90° C
- Compact design
- Range taking
- Re-usable
- Lay-in main conductor
- Insulating cover available

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Ensures reliability for copper or aluminum conductors
- Can make up to four taps off a single main which saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cable
- Eliminates taping





Fig. 1

Fig. 2

Catalog Number	Figure Number	Wire Range		No. of Taps	Dimensions			Hex Size	
		Main	Tap		L	W	H	Main	Tap
GT4T-250-2-1*	1	250kcmil-1/0	2-12 AL, 2-14 CU	4	2-3/16	1-1/8	1-35/64	5/16	Slot
GT4T-250-2-2*	2	250kcmil-1/0	2-12 AL, 2-14 CU	4	2-3/16	1-1/8	1-35/64	5/16	Slot
GT4T-350-2-1†	1	350kcmil-4/0	2-12 AL, 2-14 CU	4	2-17/32	1-1/8	1-17/32	3/8	Slot
GT4T-350-2-2*	2	350kcmil-4/0	2-12 AL, 2-14 CU	4	2-17/32	1-1/8	1-17/32	3/8	Slot
GT4T-500-2-1†	1	500kcmil-350kcmil	2-12 AL, 2-14 CU	4	2-31/32	1-1/4	1-11/16	3/8	Slot
GT4T-500-2-2†	2	500kcmil-350kcmil	2-12 AL, 2-14 CU	4	2-31/32	1-1/4	1-11/16	3/8	Slot
GT4T-500-0-1†	1	500kcmil-350kcmil	1/0-12 AL, 1/0-14 CU	4	2-31/32	1-1/4	1-11/16	3/8	Slot
GT4T-500-0-2†	2	500kcmil-350kcmil	1/0-12 AL, 1/0-14 CU	4	2-31/32	1-1/4	1-11/16	3/8	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* GTC-250-350 Cover can be used. See page 139.

† GTC-500 Cover can be used. See page 139.

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207




TYPE MGTT

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Dual-Rated
- Compact design
- Range taking
- Re-usable
- Lay-in main conductor

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Can be used with copper and/or aluminum conductors
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cable



Catalog Number	Wire Range		No. of Tap Openings	Dimensions			Hex Size	
	Main	Tap		L	W	H	Main	Tap
M2GTT-250-250	250kcmil-1/0	250kcmil-6	2	2	1-3/4	1-5/8	5/16	5/16
M2GTT-350-350	350kcmil-4/0	350kcmil-6	2	2-1/4	2	1-11/16	5/16	5/16
M3GTT-350-350	350kcmil-4/0	350kcmil-6	3	2-1/4	3	1-11/16	5/16	5/16
M2GTT-500-500	500kcmil-350kcmil	500kcmil-2	2	2-3/4	2-3/8	1-13/16	3/8	3/8
M3GTT-500-500	500kcmil-350kcmil	500kcmil-2	3	2-3/4	3-1/2	1-13/16	3/8	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.

TYPE PTA

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- UL Listed and CSA Certified for 600 volts, 90° C
- Compact design
- Range taking
- Re-usable
- Lay-in main conductors
- Supplied with insulating cover

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Ensures reliability for copper or aluminum conductors
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- No need to break the feeder cables
- Eliminates taping



Fig. 1



Fig. 2



Fig. 3



Catalog Number Connector	Figure Number	Main Wire Range	Bottom Tap Wire Range	Dimensions			Hex Size	
				H	W	D	Main	Tap
PTA2-500-500-W/C	1	Two: 500kcmil-250kcmil	Two: 500kcmil-4	3-15/16	3-1/2	1-1/4	3/8	3/8
PTA2-750-500-W/C	1	Two: 750kcmil-350kcmil	Two: 500kcmil-4	3-5/8	4-3/32	1-5/16	3/8	3/8
PTA4-750-500-W/C	2	Four: 750kcmil-350kcmil	Two: 500kcmil-4	5-7/8	4-3/32	1-5/16	3/8	3/8
PTA26-500-4/0*+	3	Two: 500kcmil-4/0	Four: 4/0-6 Two: 2-14	3-15/16	3-1/2	1-1/4	3/8	5/16 Slotted

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Note: W/C indicates product is supplied with insulating cover.

* Not CSA Certified.

+ Cover must be ordered separately. For non UL cover, order 1 each RO614W00A and RO615W00A.

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

TYPE PDH

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- UL 1059 Recognized 90° C 600 Volts and CSA Certified
- Electro-tin plated
- High Short Circuit Rating 100K RMS SYM Amps
- For use with building code or flexible conductor

Benefits

- Suitable for use with either copper or aluminum conductors
- Ensures reliability
- Provides low contact resistance
- Added protection






Fig. 1

Fig. 2

Fig. 3

Catalog Number	Fig. No.	Amps	Rated Conductor Range		High SCCR Conditions								SCCR RMS SYM Amps	Volts Max	Dimensions (in.)						Cover ID
					Suitable Conductors Per Pole		Overcurrent Protection Fuse Required Class/Max Amp Rating†								A	B	C	D	E	F w/cover	
			Line	Load	Line	Load	J	T	RK1	RK5	G	CC									
PDH-11-2-1*	1	115	(1) 2-14	(1) 2-14	(1) 2-6	(1) 2-6	200	200	200	100	60	30	200,000	600	0.83	2.29	1.53	-	1.93	1.60	C-2-1
PDH-11-2-2*	1	115	(1) 2-14	(1) 2-14	(1) 2-6	(1) 2-6	200	200	200	100	60	30	200,000	600	1.46	2.29	1.53	-	1.93	1.60	C-2-2
PDH-11-2-3*	1	115	(1) 2-14	(1) 2-14	(1) 2-6	(1) 2-6	200	200	200	100	60	30	200,000	600	2.10	2.29	1.53	1.27	1.93	1.60	C-2-3
PDH-11-2-4*	1	115	(1) 2-14	(1) 2-14	(1) 2-6	(1) 2-6	200	200	200	100	60	30	200,000	600	2.75	2.29	1.53	1.92	1.93	1.60	C-2-4
PDH-14-2-1*	1	115	(1) 2-14	(4) 10-18	(1) 2-6	(4) 10-14	200	200	200	100	60	30	200,000	600	0.83	2.29	1.53	-	1.93	1.60	C-2-1
PDH-14-2-2*	1	115	(1) 2-14	(4) 10-18	(1) 2-6	(4) 10-14	200	200	200	100	60	30	200,000	600	1.46	2.29	1.53	-	1.93	1.60	C-2-2
PDH-14-2-3*	1	115	(1) 2-14	(4) 10-18	(1) 2-6	(4) 10-14	200	200	200	100	60	30	200,000	600	2.10	2.29	1.53	1.27	1.93	1.60	C-2-3
PDH-14-2-4*	1	115	(1) 2-14	(4) 10-18	(1) 2-6	(4) 10-14	200	200	200	100	60	30	200,000	600	2.75	2.29	1.53	1.92	1.93	1.60	C-2-4
PDH-11-2/0-1	2	175	(1) 2/0-14	(1) 2/0-14	(1) 2/0-6	(1) 2/0-6	200	200	200	100	60	30	100,000	600	1.00	3.00	2.42	-	2.25	2.57	-
PDH-11-2/0-2	2	175	(1) 2/0-14	(1) 2/0-14	(1) 2/0-6	(1) 2/0-6	200	200	200	100	60	30	100,000	600	1.82	3.00	2.42	0.81	2.25	2.57	-
PDH-11-2/0-3	2	175	(1) 2/0-14	(1) 2/0-14	(1) 2/0-6	(1) 2/0-6	200	200	200	100	60	30	100,000	600	2.55	3.00	2.42	1.63	2.25	2.57	-
PDH-11-2/0-A‡	2	175	(1) 2/0-14	(1) 2/0-14	(1) 2/0-6	(1) 2/0-6	200	200	200	100	60	30	100,000	600	0.89	3.00	2.42	-	2.25	-	NA
PDH-14-2/0-1	2	175	(1) 2/0-14	(4) 4-14	(1) 2/0-6	(4) 4-14	200	200	200	100	60	30	100,000	600	1.00	3.00	2.42	-	2.25	2.57	-
PDH-14-2/0-2	2	175	(1) 2/0-14	(4) 4-14	(1) 2/0-6	(4) 4-14	200	200	200	100	60	30	100,000	600	1.82	3.00	2.42	0.81	2.25	2.57	-
PDH-14-2/0-3	2	175	(1) 2/0-14	(4) 4-14	(1) 2/0-6	(4) 4-14	200	200	200	100	60	30	100,000	600	2.55	3.00	2.42	1.63	2.25	2.57	-
PDH-14-2/0-A‡	2	175	(1) 2/0-14	(4) 4-14	(1) 2/0-6	(4) 4-14	200	200	200	100	60	30	100,000	600	0.89	3.00	2.42	-	2.25	-	NA
PDH-12-350-1	3	310	(1) 350-6	(2) 2/0-14	(1) 350-3/0	(1) 2/0-1	600	600	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-12-350-2	3	310	(1) 350-6	(2) 2/0-14	(1) 350-3/0	(1) 2/0-1	600	600	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-12-350-3	3	310	(1) 350-6	(2) 2/0-14	(1) 350-3/0	(1) 2/0-1	600	600	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-14-400-1	3	335	(1) 400-6	(4) 2-14	(1) 400-3/0	(4) 2-8	400	400	400	100	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-14-400-2	3	335	(1) 400-6	(4) 2-14	(1) 400-3/0	(4) 2-8	400	400	400	100	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-14-400-3	3	335	(1) 400-6	(4) 2-14	(1) 400-3/0	(4) 2-8	400	400	400	100	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-26-2/0-1	3	350	(2) 2/0-14	(6) 4-14	(1) 2/0-2	(6) 4-8	400	400	400	100	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-26-2/0-2	3	350	(2) 2/0-14	(6) 4-14	(1) 2/0-2	(6) 4-8	400	400	400	100	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-26-2/0-3	3	350	(2) 2/0-14	(6) 4-14	(1) 2/0-2	(6) 4-8	400	400	400	100	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-14A-500-1	3	380	(1) 500-4	(3) 2-14 (1) 350-6	(1) 500-3/0	(4) 350-6	600	600	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-14A-500-2	3	380	(1) 500-4	(3) 2-14 (1) 350-6	(1) 500-3/0	(4) 350-6	600	600	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-14A-500-3	3	380	(1) 500-4	(3) 2-14 (1) 350-6	(1) 500-3/0	(4) 350-6	600	600	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-11-600-1	3	420	(1) 600-2	(1) 600-2	(1) 600-2	(1) 600-2	400	400	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-11-600-2	3	420	(1) 600-2	(1) 600-2	(1) 600-2	(1) 600-2	400	400	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-11-600-3	3	420	(1) 600-2	(1) 600-2	(1) 600-2	(1) 600-2	400	400	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Cover not standard, available as an option. ‡ Adder Block, cover not available.

† For further details on conductors, fuse ratings, and additional SCCR ratings please refer to product data sheets.

TYPE PDH

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- UL 1059 Recognized 90° C 600 Volts and CSA Certified
- Electro-tin plated
- High Short Circuit Rating 100K RMS SYM Amps
- For use with building code or flexible conductor

Benefits

- Suitable for use with either copper or aluminum conductors
- Ensures reliability
- Provides low contact resistance
- Added protection




Fig. 3




Fig. 4



Catalog Number	Fig. No.	Amps	Rated Conductor Range		High SCCR Conditions								SCCR RMS SYM Amps	Volts Max	Dimensions (in.)						Cover ID
					Suitable Conductors Per Pole		Overcurrent Protection Fuse Required Class/Max Amp Rating†								A	B	C	D	E	F w/cover	
					Line	Load	J	T	RK1	RK5	G	CC									
PDH-18-600-1	3	420	(1) 600-2	(8) 2-14	(1) 600-3/0	(8) 2-8	400	400	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-18-600-2	3	420	(1) 600-2	(8) 2-14	(1) 600-3/0	(8) 2-8	400	400	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-18-600-3	3	420	(1) 600-2	(8) 2-14	(1) 600-3/0	(8) 2-8	400	400	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-112-600-1	3	420	(1) 600-2	(12) 4-14	(1) 600-3/0	(12) 4-8	600	600	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-112-600-2	3	420	(1) 600-2	(12) 4-14	(1) 600-3/0	(12) 4-8	600	600	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-112-600-3	3	420	(1) 600-2	(12) 4-14	(1) 600-3/0	(12) 4-8	600	600	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-19A-600-1	3	420	(1) 600-2	(6) 2-14 (3) 1/0-14	(1) 600-3/0	(9) 1/0-8	600	600	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-19A-600-2	3	420	(1) 600-2	(6) 2-14 (3) 1/0-14	(1) 600-3/0	(9) 1/0-8	600	600	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-19A-600-3	3	420	(1) 600-2	(6) 2-14 (3) 1/0-14	(1) 600-3/0	(9) 1/0-8	600	600	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-22-250-1	3	510	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	600	600	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-22-250-2	3	510	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	600	600	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-22-250-3	3	510	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	600	600	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-28-250-1	3	510	(2) 250-1/0	(8) 2-14	(2) 250-1/0	(8) 2-14	600	600	600	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-28-250-2	3	510	(2) 250-1/0	(8) 2-14	(2) 250-1/0	(8) 2-14	600	600	600	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-28-250-3	3	510	(2) 250-1/0	(8) 2-14	(2) 250-1/0	(8) 2-14	600	600	600	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-212-250-1	3	510	(2) 250-1/0	(12) 4-14	(2) 250-1/0	(12) 4-14	600	600	600	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-212-250-2	3	510	(2) 250-1/0	(12) 4-14	(2) 250-1/0	(12) 4-14	600	600	600	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-212-250-3	3	510	(2) 250-1/0	(12) 4-14	(2) 250-1/0	(12) 4-14	600	600	600	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-22-350-1*	4	620	(2) 350-4	(2) 350-4	(2) 350-4	(2) 350-4	450	450	400	200	60	30	100,000	600	3.17	5.50	3.12	-	4.75	3.18	C-6-1
PDH-22-350-2*	4	620	(2) 350-4	(2) 350-4	(2) 350-4	(2) 350-4	450	450	400	200	60	30	100,000	600	5.85	5.50	3.12	2.69	4.75	3.18	C-6-2
PDH-22-350-3*	4	620	(2) 350-4	(2) 350-4	(2) 350-4	(2) 350-4	450	450	400	200	60	30	100,000	600	8.54	5.50	3.12	5.38	4.75	3.18	C-6-3
PDH-22-500-1*	4	760	(2) 500-4	(2) 500-4	(2) 500-4	(2) 500-4	600	600	400	200	60	30	100,000	600	3.17	5.50	3.12	-	4.75	3.18	C-6-1
PDH-22-500-2*	4	760	(2) 500-4	(2) 500-4	(2) 500-4	(2) 500-4	600	600	400	200	60	30	100,000	600	5.85	5.50	3.12	2.69	4.75	3.18	C-6-2
PDH-22-500-3*	4	760	(2) 500-4	(2) 500-4	(2) 500-4	(2) 500-4	600	600	400	200	60	30	100,000	600	8.54	5.50	3.12	5.38	4.75	3.18	C-6-3
PDH-28-500-1*	4	760	(2) 500-6	(8) 2/0-14	(2) 500-250	(8) 2/0-14	600	600	400	200	60	30	100,000	600	3.17	5.50	3.12	-	4.75	3.18	C-6-1
PDH-28-500-2*	4	760	(2) 500-6	(8) 2/0-14	(2) 500-250	(8) 2/0-14	600	600	400	200	60	30	100,000	600	5.85	5.50	3.12	2.69	4.75	3.18	C-6-2
PDH-28-500-3*	4	760	(2) 500-6	(8) 2/0-14	(2) 500-250	(8) 2/0-14	600	600	400	200	60	30	100,000	600	8.54	5.50	3.12	5.38	4.75	3.18	C-6-3
PDH-212-500-1*	4	760	(2) 500-6	(12) 4-14	(2) 500-250	(12) 4-8	400	400	400	200	60	30	100,000	600	3.17	5.50	3.12	-	4.75	3.18	C-6-1
PDH-212-500-2*	4	760	(2) 500-6	(12) 4-14	(2) 500-250	(12) 4-8	400	400	400	200	60	30	100,000	600	5.85	5.50	3.12	2.69	4.75	3.18	C-6-2
PDH-212-500-3*	4	760	(2) 500-6	(12) 4-14	(2) 500-250	(12) 4-8	400	400	400	200	60	30	100,000	600	8.54	5.50	3.12	5.38	4.75	3.18	C-6-3

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Cover not standard, available as an option.

† For further details on conductors, fuse ratings, and additional SCCR ratings please refer to product data sheets.


TYPE PDE

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- UL Listed 75° C and CSA Certified, 600 volts
- Electro-tin plated
- High Short Circuit Rating 100K RMS SYM Amps
- For use with building code or flexible conductor

Benefits

- Suitable for use with either copper or aluminum conductors
- Ensures reliability
- Provides low contact resistance
- Added protection



C

Catalog Number	Amps (CU Wire)	Rated Conductor Range		High SCCR Conditions								SCCR RMS SYM Amps	Volts Max	Dimensions (in.)				
				Suitable Conductors Per Pole		Overcurrent Protection Fuse Required Class/Max Amp Rating								A	B	C	D	E
				Line	Load	J	T	RK1	RK5	G	CC							
PDE-11-3/0	200	(1) 3/0-14	(1) 3/0-14	(1) 3/0-8	(1) 3/0-8	225	225	200	60	60	30	100,000	600	1.20	3.61	2.71	.56	3.00
PDE-11-3/0-CU	200	(1) 3/0-14	(1) 3/0-14	(1) 3/0-8	(1) 3/0-8	225	225	200	60	60	30	100,000	600	1.20	3.61	2.71	.56	3.00
PDE-14-3/0	200	(1) 3/0-14	(4) 2-14	(1) 3/0-8	(4) 2-14	225	225	200	60	60	30	100,000	600	1.20	3.61	2.71	.56	3.00
PDE-14-3/0-CU	200	(1) 3/0-14	(4) 2-14	(1) 3/0-8	(4) 2-14	225	225	200	60	60	30	100,000	600	1.20	3.61	2.71	.56	3.00
PDE-18-400†	335	(1) 400-6 (1) 2/0-14	(8) 2-16	(1) 400-3/0	(8) 2-8	400	400	400	200	60	30	100,000	600	2.27	4.39	3.14	1.11	3.75
PDE-18-400-CU†	335	(1) 400-6 (1) 2/0-14	(8) 2-16	(1) 400-3/0	(8) 2-8	400	400	400	200	60	30	100,000	600	2.27	4.39	3.14	1.11	3.75
PDE-22-250†	510	(2) 250-6	(2) 250-6	(2) 250-1/0	(2) 250-1/0	400	400	400	200	60	30	100,000	600	2.27	4.39	3.14	1.11	3.75
PDE-22-250-CU†	510	(2) 250-6	(2) 250-6	(2) 250-1/0	(2) 250-1/0	400	400	400	200	60	30	100,000	600	2.27	4.39	3.14	1.11	3.75

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

All PDE blocks are single pole and snap together for 2 and 3 pole configurations

† For further details on conductors, fuse ratings, and additional SCCR ratings please refer to product data sheets.

‡ UL Recognized.


TYPE PDL

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- UL Listed 75° C and CSA Certified, 600 volts
- Electro-tin plated
- High Short Circuit Rating 100K RMS SYM Amps
- For use with building code or flexible conductor

Benefits

- Suitable for use with either copper or aluminum conductors
- Ensures reliability
- Provides low contact resistance
- Added protection



Catalog Number	Amps (CU Wire)	Rated Conductor Range		High SCCR Conditions								SCCR RMS SYM Amps	Volts Max	Dimensions (in.)				
				Suitable Conductors Per Pole		Overcurrent Protection Fuse Required Class/Max Amp Rating								A	B	C	D	E
				Line	Load	J	T	RK1	RK5	G	CC							
PDL-11-2/0-3	175	(1) 2/0-14	(1) 2/0-14	(1) 2/0-6	(1) 2/0-6	200	200	200	100	60	30	100,000	600	4.25	3.00	3.05	1.63	2.25
PDL-14-2/0-3	175	(1) 2/0-14	(4) 4-14	(1) 2/0-6	(4) 4-14	200	200	200	100	60	30	100,000	600	4.25	3.00	3.05	1.63	2.25
PDL-16-2/0-3	175	(1) 2/0-14	(6) 4-14	(1) 2/0-6	(6) 4-14	200	200	200	100	60	30	100,000	600	4.25	3.00	3.05	1.63	2.25
PDL-16-400-3	335	(1) 400-6	(6) 2-14	(1) 400-3/0	(6) 2-8	400	400	400	100	60	30	100,000	600	6.00	5.50	3.96	3.25	4.75
PDL-112-600-3	335	(1) 600-2	(12) 4-14	(1) 600-3/0	(12) 4-8	600	600	400	200	60	30	100,000	600	6.00	5.50	3.96	3.25	4.75
PDL-19A-600-3	335	(1) 600-2	(3) 1/0-14 (6) 2-14	(1) 600-3/0	(9) 1/0-8	600	600	400	200	60	30	100,000	600	6.00	5.50	3.96	3.25	4.75

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

PDL Distribution Blocks are also UL listed with high SCCR ratings with certain Circuit Breaker Combinations - consult factory.

† For further details on conductors, fuse ratings, and additional SCCR ratings please refer to product data sheets.



TYPE PDS

Features

- Connector, copper, tin plated
- Stud, brass, tin plated
- UL Recognized 75° C and CSA Certified
- Insulator base adders available
- Din rail or panel mountable
- Rated for 600 volts

Benefits

- Rated for copper conductor
- Intended for wires terminated with crimp lugs
- Ensures reliability
- Easily snap together to create variable pole power blocks



C

Catalog Number	Rated Amps	Conductor Range		Stud Ctr to Ctr	Line In	Line Out	Dimensions						Cover ID
		Line	Load				A	B	C	D	E	F w/cover	
PDS-11-KE-1†	230	(1) 3/8-16 X 1-3/16	(1) 1/4-20 x 1-3/16	-	Stud	Stud	1.94	4.00	2.61	-	3.38	3.38	C-4-1
PDS-11-KE-2†	230	(1) 3/8-16 X 1-3/16	(1) 1/4-20 x 1-3/16	-	Stud	Stud	3.47	4.00	2.61	1.53	3.38	3.38	C-4-2
PDS-11-KE-3†	230	(1) 3/8-16 X 1-3/16	(1) 1/4-20 x 1-3/16	-	Stud	Stud	5.00	4.00	2.61	3.06	3.38	3.38	C-4-3
PDS-11-PP-1	230	(1) 3/8-16 x 1-7/16	(1) 3/8-16 x 1-7/16	-	Stud	Stud	2.29	4.75	2.90	-	4.13	4.13	C-5-1
PDS-11-PP-2	230	(1) 3/8-16 x 1-7/16	(1) 3/8-16 x 1-7/16	-	Stud	Stud	4.17	4.75	2.90	1.88	4.13	4.13	C-5-2
PDS-11-PP-3	230	(1) 3/8-16 x 1-7/16	(1) 3/8-16 x 1-7/16	-	Stud	Stud	6.05	4.75	2.90	3.76	4.13	4.13	C-5-3
PDS-12-PC-1	260	(1) 3/8-16 x 1-7/16	(2) 1/4-20 x 9/16	.750	Stud	Stud	2.29	4.75	2.90	-	4.13	4.13	C-5-1
PDS-12-PC-2	260	(1) 3/8-16 x 1-7/16	(2) 1/4-20 x 9/16	.750	Stud	Stud	4.17	4.75	2.90	1.88	4.13	4.13	C-5-2
PDS-12-PC-3	260	(1) 3/8-16 x 1-7/16	(2) 1/4-20 x 9/16	.750	Stud	Stud	6.05	4.75	2.90	3.76	4.13	4.13	C-5-3
PDS-12-PG-1	360	(1) 3/8-16 x 1-7/16	(2) 1/4-20 X 1-7/16	1.125	Stud	Stud	3.17	5.50	3.12	-	4.75	4.75	C-6-1
PDS-12-PG-2	360	(1) 3/8-16 x 1-7/16	(2) 1/4-20 X 1-7/16	1.125	Stud	Stud	5.85	5.50	3.12	2.69	4.75	4.75	C-6-2
PDS-12-PG-3	360	(1) 3/8-16 x 1-7/16	(2) 1/4-20 X 1-7/16	1.125	Stud	Stud	8.54	5.50	3.12	5.38	4.75	4.75	C-6-3
PDS-12-PP-1	360	(1) 3/8-16 x 1-7/16	(2) 3/8-16 x 1-7/16	1.125	Stud	Stud	3.17	5.50	3.12	-	4.75	4.75	C-6-1
PDS-12-PP-2	360	(1) 3/8-16 x 1-7/16	(2) 3/8-16 x 1-7/16	1.125	Stud	Stud	5.85	5.50	3.12	2.69	4.75	4.75	C-6-2
PDS-12-PP-3	360	(1) 3/8-16 x 1-7/16	(2) 3/8-16 x 1-7/16	1.125	Stud	Stud	8.54	5.50	3.12	5.38	4.75	4.75	C-6-3
PDS-11-RR-1	410	(1) 1/2-13 x 1-7/16	(1) 1/2-13 x 1-7/16	-	Stud	Stud	3.17	5.50	3.12	-	4.75	4.75	C-6-1
PDS-11-RR-2	410	(1) 1/2-13 x 1-7/16	(1) 1/2-13 x 1-7/16	-	Stud	Stud	5.85	5.50	3.12	2.69	4.75	4.75	C-6-2
PDS-11-RR-3	410	(1) 1/2-13 x 1-7/16	(1) 1/2-13 x 1-7/16	-	Stud	Stud	8.54	5.50	3.12	5.38	4.75	4.75	C-6-3
PDS-11-HH-1	840	(1) 3/8-16 x 1	(1) 3/8-16 x 1	-	Stud	Stud	2.29	4.75	2.90	-	4.13	4.13	C-5-1
PDS-11-HH-2	840	(1) 3/8-16 x 1	(1) 3/8-16 x 1	-	Stud	Stud	4.17	4.75	2.90	1.88	4.13	4.13	C-5-2
PDS-11-HH-3	840	(1) 3/8-16 x 1	(1) 3/8-16 x 1	-	Stud	Stud	6.05	4.75	2.90	3.76	4.13	4.13	C-5-3

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG) For further details on conductor classes please refer to product data sheets

UL1059 terminal block standard file No. E84782 CSA certified CSA c22.2 No. 158, File number MC 249467 (wire classes B & C only)

† Connector aluminum, tin plated

TYPE PDS

Features

- Connector, copper, tin plated
- Stud, brass, tin plated
- UL Recognized 75° C and CSA Certified
- Insulator base adders available
- Din rail or panel mountable
- Rated for 600 volts

Benefits

- Rated for copper conductor
- Intended for wires terminated with crimp lugs
- Ensures reliability
- Easily snap together to create variable pole power blocks





Fig. 1




Fig. 2



Catalog Number	Fig. No.	Amps	Rated Conductor Range		Stud Ctr to Ctr	Line In	Line Out	Dimensions						Cover ID
			Line	Load				A	B	C	D	E	F w/cover	
PDS-11-UU-A*	1	200	(1) M6 x 15	(1) M6 x 15	-	Metric	Metric	1.00	3.00	2.42	-	2.25	-	NA
PDS-11-UU-1	1	200	(1) M6 x 15	(1) M6 x 15	-	Metric	Metric	1.00	3.00	2.42	-	2.25	2.57	-
PDS-11-UU-2	1	200	(1) M6 x 15	(1) M6 x 15	-	Metric	Metric	1.82	3.00	2.42	0.81	2.25	2.57	-
PDS-11-UU-3	1	200	(1) M6 x 15	(1) M6 x 15	-	Metric	Metric	2.55	3.00	2.42	1.62	2.25	2.57	-
PDS-11-CC-A*	1	200	(1) 1/4-20 x 9/16	(1) 1/4-20 x 9/16	-	Stud	Stud	1.00	3.00	2.42	-	2.25	-	NA
PDS-11-CC-1	1	200	(1) 1/4-20 x 9/16	(1) 1/4-20 x 9/16	-	Stud	Stud	1.00	3.00	2.42	-	2.25	2.57	-
PDS-11-CC-2	1	200	(1) 1/4-20 x 9/16	(1) 1/4-20 x 9/16	-	Stud	Stud	1.82	3.00	2.42	0.81	2.25	2.57	-
PDS-11-CC-3	1	200	(1) 1/4-20 x 9/16	(1) 1/4-20 x 9/16	-	Stud	Stud	2.55	3.00	2.42	1.62	2.25	2.57	-
PDS-11-SS-1	2	310	(1) M10 x 30	(1) M10 x 30	-	Metric	Metric	1.96	4.00	3.33	-	3.38	3.49	-
PDS-11-SS-2	2	310	(1) M10 x 30	(1) M10 x 30	-	Metric	Metric	3.66	4.00	3.33	1.70	3.38	3.49	-
PDS-11-SS-3	2	310	(1) M10 x 30	(1) M10 x 30	-	Metric	Metric	5.36	4.00	3.33	3.40	3.38	3.49	-
PDS-11-KK-1	2	310	(1) 3/8-16 x 1-3/16	(1) 3/8-16 x 1-3/16	-	Stud	Stud	1.96	4.00	3.33	-	3.38	3.49	-
PDS-11-KK-2	2	310	(1) 3/8-16 x 1-3/16	(1) 3/8-16 x 1-3/16	-	Stud	Stud	3.66	4.00	3.33	1.70	3.38	3.49	-
PDS-11-KK-3	2	310	(1) 3/8-16 x 1-3/16	(1) 3/8-16 x 1-3/16	-	Stud	Stud	5.36	4.00	3.33	3.40	3.38	3.49	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

For further details on conductor classes please refer to product data sheets

UL1059 terminal block standard file No. E84782 CSA certified CSA c22.2 No. 158, File number MC 249467 (wire classes B & C only)

* Cover not available for adder blocks

- Indicates that snap on cover is standard

TYPE PDM

Features

- Connector, high conductive aluminium, tin plated
- Brass, tin plated stud
- UL Recognized 75° C and CSA Certified
- Insulator base adders available
- Panel Mountable
- Rated for 600 volts

Benefits

- Rated for copper and aluminum conductor
- Intended for wires terminated with crimp lugs
- Ensures Reliability
- Easily snap together to create variable pole power blocks





Fig. 1




Fig. 2

Catalog Number	Fig. No.	Amps	Rated Conductor Range		Stud Ctr to Ctr	Line In	Line Out	MAX AIC	Dimensions						Cover ID
			Line	Load					A	B	C	D	E	F w/cover	
PDM-11-2/0F-1	1	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1-3/8	-	Lug	Stud	-	1.94	4.00	2.61	-	3.38	3.38	C-4-1
PDM-11-2/0F-2	1	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1-3/8	-	Lug	Stud	-	3.47	4.00	2.61	1.53	3.38	3.38	C-4-2
PDM-11-2/0F-3	1	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1-3/8	-	Lug	Stud	-	5.00	4.00	2.61	3.06	3.38	3.38	C-4-3
PDM-11-350J-1	1	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/8	-	Lug	Stud	65KA	1.94	4.00	2.61	-	3.38	3.38	C-4-1
PDM-11-350J-2	1	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/8	-	Lug	Stud	65KA	3.47	4.00	2.61	1.53	3.38	3.38	C-4-2
PDM-11-350J-3	1	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/8	-	Lug	Stud	65KA	5.00	4.00	2.61	3.06	3.38	3.38	C-4-3
PDM-12-500D-1	1	380	(1) 500 kcmil-#4 Awg	(2) 1/4-20 x 1-1/16	.750	Lug	Stud	-	2.29	4.75	2.90	-	4.13	4.13	C-5-1
PDM-12-500D-2	1	380	(1) 500 kcmil-#4 Awg	(2) 1/4-20 x 1-1/16	.750	Lug	Stud	-	4.17	4.75	2.90	1.88	4.13	4.13	C-5-2
PDM-12-500D-3	1	380	(1) 500 kcmil-#4 Awg	(2) 1/4-20 x 1-1/16	.750	Lug	Stud	-	6.05	4.75	2.90	3.76	4.13	4.13	C-5-3
PDM-11-500N-1	1	380	(1) 500 kcmil-#4 Awg	(1) 3/8-16 x 1-5/16	-	Lug	Stud	-	2.29	4.75	2.90	-	4.13	4.13	C-5-1
PDM-11-500N-2	1	380	(1) 500 kcmil-#4 Awg	(1) 3/8-16 x 1-5/16	-	Lug	Stud	-	4.17	4.75	2.90	1.88	4.13	4.13	C-5-2
PDM-11-500N-3	1	380	(1) 500 kcmil-#4 Awg	(1) 3/8-16 x 1-5/16	-	Lug	Stud	-	6.05	4.75	2.90	3.76	4.13	4.13	C-5-3
PDM-21-500Q-1	1	760	(2) 500 kcmil-#4 Awg	(1) 1/2-13 x 1-5/16	-	Lug	Stud	-	3.17	5.50	3.12	-	4.75	4.75	C-6-1
PDM-21-500Q-2	1	760	(2) 500 kcmil-#4 Awg	(1) 1/2-13 x 1-5/16	-	Lug	Stud	-	5.85	5.50	3.12	2.69	4.75	4.75	C-6-2
PDM-21-500Q-3	1	760	(2) 500 kcmil-#4 Awg	(1) 1/2-13 x 1-5/16	-	Lug	Stud	-	8.54	5.50	3.12	5.38	4.75	4.75	C-6-3
PDM-22-500N-1	1	760	(2) 500 kcmil-#4 Awg	(2) 3/8-16 x 1-5/16	1.160	Lug	Stud	-	3.17	5.50	3.12	-	4.75	4.75	C-6-1
PDM-22-500N-2	1	760	(2) 500 kcmil-#4 Awg	(2) 3/8-16 x 1-5/16	1.160	Lug	Stud	-	5.85	5.50	3.12	2.69	4.75	4.75	C-6-2
PDM-22-500N-3	1	760	(2) 500 kcmil-#4 Awg	(2) 3/8-16 x 1-5/16	1.160	Lug	Stud	-	8.54	5.50	3.12	5.38	4.75	4.75	C-6-3
PDM-11-2A-1	2	115	(1) #2-#14 Awg	(1) 10-32 x .60	-	Lug	Stud	-	0.83	2.29	1.53	-	2.07	2.07	C-2-1
PDM-11-2A-2	2	115	(1) #2-#14 Awg	(1) 10-32 x .60	-	Lug	Stud	-	1.46	2.29	1.53	-	2.07	2.07	C-2-2
PDM-11-2A-3	2	115	(1) #2-#14 Awg	(1) 10-32 x .60	-	Lug	Stud	-	2.10	2.29	1.53	1.27	2.07	2.07	C-2-3
PDM-11-2A-4	2	115	(1) #2-#14 Awg	(1) 10-32 x .60	-	Lug	Stud	-	2.75	2.29	1.53	1.93	2.07	2.07	C-2-4
PDM-11-2/0T-A**	2	175	(1) 2/0-#14 Awg	(1) M6 x 13	-	Lug	Metric	-	1.00	3.00	2.42	-	2.25	-	NA
PDM-11-2/0T-1‡	2	175	(1) 2/0-#14 Awg	(1) M6 x 13	-	Lug	Metric	-	1.00	3.00	2.42	-	2.25	2.57	-
PDM-11-2/0T-2‡	2	175	(1) 2/0-#14 Awg	(1) M6 x 13	-	Lug	Metric	-	1.82	3.00	2.42	0.81	2.25	2.57	-
PDM-11-2/0T-3‡	2	175	(1) 2/0-#14 Awg	(1) M6 x 13	-	Lug	Metric	-	2.55	3.00	2.42	1.63	2.25	2.57	-
PDM-11-2/0B-A*	2	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1/2	-	Lug	Stud	100KA	1.00	3.00	2.42	-	2.25	-	NA
PDM-11-2/0B-1	2	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1/2	-	Lug	Stud	100KA	1.00	3.00	2.42	-	2.25	2.57	-
PDM-11-2/0B-2	2	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1/2	-	Lug	Stud	100KA	1.82	3.00	2.42	0.81	2.25	2.57	-
PDM-11-2/0B-3	2	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1/2	-	Lug	Stud	100KA	2.55	3.00	2.42	1.63	2.25	2.57	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG) For further details on conductor classes please refer to product data sheets
 UL1059 terminal block standard file No. E84782 CSA certified CSA c22.2 No. 158, File number MC 249467 (wire classes B & C only)

* Cover not available for adder blocks

- Indicates that snap on cover is standard ‡ Steel Stud



TYPE PDM

Features

- Connector, high conductive aluminium, tin plated
- Brass, tin plated stud
- UL Recognized 75° C and CSA Certified
- Insulator base adders available
- Panel Mountable
- Rated for 600 volts

Benefits

- Rated for copper and aluminum conductor
- Intended for wires terminated with crimp lugs
- Ensures Reliability
- Easily snap together to create variable pole power blocks



Catalog Number	Amps	Rated Conductor Range		Stud Ctr to Ctr	Line In	Line Out	MAX AIC	Dimensions						Cover ID
		Line	Load					A	B	C	D	E	F w/cover	
PDM-11-350S-1	310	(1) 350 kcmil-#6 Awg	(1) M10 x 30	-	Lug	Metric	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-11-350S-2	310	(1) 350 kcmil-#6 Awg	(1) M10 x 30	-	Lug	Metric	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-11-350S-3	310	(1) 350 kcmil-#6 Awg	(1) M10 x 30	-	Lug	Metric	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-11-350M-1	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/4	-	Lug	Stud	65KA	1.96	4.00	3.33	-	3.38	3.49	-
PDM-11-350M-2	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/4	-	Lug	Stud	65KA	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-11-350M-3	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/4	-	Lug	Stud	65KA	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-18-S2-1	510	(1) M10 x 30	(8) #2-#14 Awg	-	Metric	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-18-S2-2	510	(1) M10 x 30	(8) #2-#14 Awg	-	Metric	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-18-S2-3	510	(1) M10 x 30	(8) #2-#14 Awg	-	Metric	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-112-S4-1	510	(1) M10 x 30	(12) #4-#14 Awg	-	Metric	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-112-S4-2	510	(1) M10 x 30	(12) #4-#14 Awg	-	Metric	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-112-S4-3	510	(1) M10 x 30	(12) #4-#14 Awg	-	Metric	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-14-S2/0-1	510	(1) M10 x 30	(4) 2/0-#14 Awg	-	Metric	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-14-S2/0-2	510	(1) M10 x 30	(4) 2/0-#14 Awg	-	Metric	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-14-S2/0-3	510	(1) M10 x 30	(4) 2/0-#14 Awg	-	Metric	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-18-K2-1	510	(1) 3/8-16 x 1-3/16	(8) #2-#14 Awg	-	Stud	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-18-K2-2	510	(1) 3/8-16 x 1-3/16	(8) #2-#14 Awg	-	Stud	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-18-K2-3	510	(1) 3/8-16 x 1-3/16	(8) #2-#14 Awg	-	Stud	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-112-K4-1	510	(1) 3/8-16 x 1-3/16	(12) #4-#14 Awg	-	Stud	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-112-K4-2	510	(1) 3/8-16 x 1-3/16	(12) #4-#14 Awg	-	Stud	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-112-K4-3	510	(1) 3/8-16 x 1-3/16	(12) #4-#14 Awg	-	Stud	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-14-K2/0-1	510	(1) 3/8-16 x 1-3/16	(4) 2/0-#14 Awg	-	Stud	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-14-K2/0-2	510	(1) 3/8-16 x 1-3/16	(4) 2/0-#14 Awg	-	Stud	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-14-K2/0-3	510	(1) 3/8-16 x 1-3/16	(4) 2/0-#14 Awg	-	Stud	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

For further details on conductor classes please refer to product data sheets

UL1059 terminal block standard file No. E84782 CSA certified CSA c22.2 No. 158, File number MC 249467 (wire classes B & C only)

- Indicates that snap on cover is standard

TYPE

LDAU

LDBU

Features

- Modular design
- Easy to assemble
- UL listed 90° C 600 Volts
- Electro-tin plated 6061-T6 aluminum alloy
- Multiple conductor capability

Benefits

- Simplifies stocking. Combines any number of blocks with multiple conductor ranges into the specific configuration required for the job.
- Unique locking feature allows individual blocks to be combined quickly without special tools
- Ensures reliability
- Suitable for use with both copper and aluminum conductors in any combination
- Individual blocks supplied in a variety of configurations with one or two main cable ports and four, six, or twelve taps. All are range taking.



Fig. 1






Fig. 2

Catalog Number	Figure Number	Connector		Primary			Secondary			Ampere
		Primary	Secondary	Wire Range	Openings Per Pole	Hex Size	Wire Range	Openings Per Pole	Hex Size	Rating Per Pole
LDBU-112-350	1			350kcmil-6	1	3/8	4-14	12	Slot	310
LDAU-112-350	2			350kcmil-6	1	3/8	4-14	12	Slot	310
LDBU-112A-350	1			350kcmil-6	1	3/8	4-14	12	Slot	310
LDAU-112A-350	2			350kcmil-6	1	3/8	4-14	12	Slot	310
LDBU-16-350	1			350kcmil-6	1	3/8	2/0-14	6	3/16	310
LDAU-16-350	2			350kcmil-6	1	3/8	2/0-14	6	3/16	310
LDBU-16-500	1			500kcmil-4	1	3/8	2/0-14	6	3/16	380
LDAU-16-500	2			500kcmil-4	1	3/8	2/0-14	6	3/16	380
LDBU-26-350	1			350kcmil-6	2	3/8	2/0-14	6	3/16	620
LDAU-26-350	2			350kcmil-6	2	3/8	2/0-14	6	3/16	620
LDBU-212-4/0	1			4/0-6	2	1/4	4-14	12	Slot	460
LDAU-212-4/0	2			4/0-6	2	1/4	4-14	12	Slot	460
LDBU-212-500	1			500kcmil-4	2	3/8	4-14	12	Slot	760
LDAU-212-500	2			500kcmil-4	2	3/8	4-14	12	Slot	760
LDBU-26-500	1			500kcmil-4	2	3/8	2/0-14	6	3/16	760
LDAU-26-500	2			500kcmil-4	2	3/8	2/0-14	6	3/16	760
LDBU-24-500	1			500kcmil-4	2	3/8	4/0-6	4	5/16	760
LDAU-24-500	2			500kcmil-4	2	3/8	4/0-6	4	5/16	760
LDBU-11-500	1			500kcmil-4	1	3/8	500kcmil-4	1	3/8	380
LDAU-11-500	2			500kcmil-4	1	3/8	500kcmil-4	1	3/8	380
LDBU-22-350	1			350kcmil-6	2	3/8	350kcmil-6	2	3/8	620
LDAU-22-350	2			350kcmil-6	2	3/8	350kcmil-6	2	3/8	620
LDBU-22-500	1			500kcmil-4	2	3/8	500kcmil-4	2	3/8	760
LDAU-22-500	2			500kcmil-4	2	3/8	500kcmil-4	2	3/8	760

Side Panel can be ordered separately Cat. No. LDS-1

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 1953, UL File E112158



Dimensions

A	B	C	D=Dia.	E	F	G	H	J = Cover	K	L	M	N
3	5-1/2	3-7/16	.28 Slot	1-1/2	5/16	4-7/8	1/4	1/2	4.75	2.69	.38	1.50

TYPE PDBU

Features

- Lay-In primary cable ports
- Valox insulating base
- UL 1953 Listed for 600 volts
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy

Benefits

- Designed for feed through of two primary conductors and up to six taps with no need to break the main feeder cable
- Provides a high degree of impact resistance with superior insulating qualities
- Ensures reliability
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors




C

Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole			Primary	Secondary
	PDBU-26-750-1			750kcmil-250kcmil	2	250kcmil-6			6	950

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 1953, UL File E112158



Block Size	No. of Poles	Dimensions							
		A	B	C	D	E	F	G	H
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16

* Valox® is a registered trade name of the General Electric Company.

TYPE PDBU

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Valox* insulating base
- UL 1953 Listed 90° C 600 volts
- Electro-tin plated

Benefits

- Reliable use for copper conductor only
- Provides a high degree of impact resistance with superior insulating qualities
- Ensures reliability
- Provides low contact resistance



C


Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Block Size	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Valox® is a registered trade name of the General Electric Company.

A versatile tap hole, wire range 8-14 AWG included on the connector.

Tested to UL 1953, UL File E112158



Block Size	No. of Poles	Dimensions									
		A	B	C	D	E	F	G	H	J	K
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16	9/32	9/16

TYPE PDBU

Features

- Multiple taps
- Valox* insulating base
- UL 1953 Listed 90° C 600 Volts
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy
- Short Circuit Rating 10K RMS SYM Amps

Benefits

- Three different connector configurations provide a wide range of tapping capabilities for up to four primary conductors
- Provides a high degree of impact resistance with superior insulating qualities
- Ensures reliability
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors
- Added protection



Fig. 1



Fig. 2











Fig. 3



Fig. 4

C


Catalog Number	Figure Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number of Poles	Block Size	Hex Size	
		Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
PDBU-428-500-1	1			500kcmil-4	4	4-14	28	1520	1	W	3/8	Slot
PDBU-49-500-1	2			500kcmil-4	4	350kcmil-6 4/0-6	6 3	1520	1	W	3/8	3/8 5/16
PDBU-55-500-1	4			500kcmil-3/0	5	500kcmil-3/0	5	1600	1	W	3/8	3/8
PDBU-412-500-1	3			500kcmil-4	4	4/0-6	12	1520	1	W	3/8	5/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Valox® is a registered trade name of the General Electric Company.

° A versatile tap hole, wire range 8-14 AWG included on the connector.

Tested to UL 1953, UL File E112158



Block Size	No. of Poles	Dimensions									
		A	B	C	D	E	F	G	H	J	K
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16	9/32	9/16

TYPE

LDA

LDB

Features

- Modular design
- Easy to assemble
- UL Recognized 90° C 600 Volts and is CSA Certified
- Electro-tin plated 6061-T6 aluminum alloy
- Clear cover
- Multiple conductor capability

Benefits

- Simplifies stocking. Combines any number of blocks with multiple conductor ranges into the specific configuration required for the job.
- Unique locking feature allows individual blocks to be combined quickly without special tools
- Ensures reliability
- Suitable for use with both copper and aluminum conductors in any combination
- Permits visual inspection
- Individual blocks supplied in a variety of configurations with one or two main cable ports and four, six, or twelve taps. All are range taking.



Fig. 1






Fig. 2

Catalog Number	Figure Number	Connector		Primary			Secondary			Ampere
		Primary	Secondary	Wire Range	Openings Per Pole	Hex Size	Wire Range	Openings Per Pole	Hex Size	Rating Per Pole
LDB-112-350	1			350kcmil-6	1	3/8	4-14	12	Slot	310
LDA-112-350	2			350kcmil-6	1	3/8	4-14	12	Slot	310
LDB-112A-350	1			350kcmil-6	1	3/8	4-14	12	Slot	310
LDA-112A-350	2			350kcmil-6	1	3/8	4-14	12	Slot	310
LDB-16-350	1			350kcmil-6	1	3/8	2/0-14	6	3/16	310
LDA-16-350	2			350kcmil-6	1	3/8	2/0-14	6	3/16	310
LDB-16-500	1			500kcmil-4	1	3/8	2/0-14	6	3/16	380
LDA-16-500	2			500kcmil-4	1	3/8	2/0-14	6	3/16	380
LDB-26-350	1			350kcmil-6	2	3/8	2/0-14	6	3/16	620
LDA-26-350	2			350kcmil-6	2	3/8	2/0-14	6	3/16	620
LDB-212-4/0	1			4/0-6	2	1/4	4-14	12	Slot	460
LDA-212-4/0	2			4/0-6	2	1/4	4-14	12	Slot	460
LDB-212-500	1			500kcmil-4	2	3/8	4-14	12	Slot	760
LDA-212-500	2			500kcmil-4	2	3/8	4-14	12	Slot	760
LDB-26-500	1			500kcmil-4	2	3/8	2/0-14	6	3/16	760
LDA-26-500	2			500kcmil-4	2	3/8	2/0-14	6	3/16	760
LDB-24-500	1			500kcmil-4	2	3/8	4/0-6	4	5/16	760
LDA-24-500	2			500kcmil-4	2	3/8	4/0-6	4	5/16	760
LDB-11-500	1			500kcmil-4	1	3/8	500kcmil-4	1	3/8	380
LDA-11-500	2			500kcmil-4	1	3/8	500kcmil-4	1	3/8	380
LDB-22-350	1			350kcmil-6	2	3/8	350kcmil-6	2	3/8	620
LDA-22-350	2			350kcmil-6	2	3/8	350kcmil-6	2	3/8	620
LDB-22-500	1			500kcmil-4	2	3/8	500kcmil-4	2	3/8	760
LDA-22-500	2			500kcmil-4	2	3/8	500kcmil-4	2	3/8	760

Side Panel can be ordered separately Cat. No. LDS-1

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 1059, UL File E84782



Dimensions

A	B	C	D=Dia.	E	F	G	H	J = Cover	K	L	M	N
3	5-1/2	3-7/16	.28 Slot	1-1/2	5/16	4-7/8	1/4	1/2	4.75	2.69	.38	1.50

TYPE PDA PDC

Features

- Modular design
- Easy to assemble
- UL Recognized 90° C 600 Volts and is CSA Certified
- Electro-tin plated
- Lexan® insulating base
- Manufactured from high strength 6061-T6 aluminum alloy

Benefits

- Simplifies stocking. Combines any number of blocks with multiple conductor ranges into the specific configuration required for the job.
- Unique locking feature allows individual blocks to be combined quickly without special tools
- Ensures reliability
- Provides low contact resistance
- Provides a high degree of impact resistance with superior insulating qualities
- Suitable for use with either copper or aluminum conductors



Fig. 1



Fig. 2



Fig. 3



Fig. 4


Catalog Number	Figure Number	Connector		Primary		Secondary		Ampere Rating Per Pole	No. of Poles	Hex Size	
		Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole			Primary	Secondary
PDC-14-2/0-1	1			2/0-14	1	4-14	4	175	1	3/16	Slot
PDA-14-2/0-1	2			2/0-14	1	4-14	4	175	Adder	3/16	Slot
PDC-11-2/0-1	3			2/0-14	1	2/0-14	1	175	1	3/16	3/16
PDA-11-2/0-1	4			2/0-14	1	2/0-14	1	175	Adder	3/16	3/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Covers available 1-10 Poles. Specify length.

*Lexan is a registered trademark of SABIC INNOVATIVE PLASTICS HOLDINGS BV.

Tested to UL 1059, UL File E84782



Block Size	No. of Poles	Dimensions						
		A	B	C	D	E	F	G
S	1	1.05	1.94	2.88	2.25	.31	.53	.80
S	2	1.85	1.94	2.88	2.25	.31	.53	.80

"A" Dimension increases by .80 per additional pole.

TYPE PDB

Features

- Range taking
- Valox* insulating base
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy
- UL Recognized rated 90° C and is CSA Certified, rated for 600 volts

Benefits

- Provides great flexibility in using the connector as an in line splice or to reduce conductor size
- Provides a high degree of impact resistance with superior insulating qualities
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors
- Ensures reliability



C

Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Block Size	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
PDB-16-2/0-1			2/0-12	1	4-14	6	175	1	M	3/16	Slot
PDB-16-2/0-2			2/0-12	1	4-14	6	175	2	M	3/16	Slot
PDB-16-2/0-3			2/0-12	1	4-14	6	175	3	M	3/16	Slot
PDB-26-2/0-1			2/0-12	2	2-14	6	350	1	M	3/16	Slot
PDB-26-2/0-2			2/0-12	2	2-14	6	350	2	M	3/16	Slot
PDB-26-2/0-3			2/0-12	2	2-14	6	350	3	M	3/16	Slot
PDB-112-350-1			350kcmil-6	1	4-14	12	310	1	L	3/8	Slot
PDB-112-350-2			350kcmil-6	1	4-14	12	310	2	L	3/8	Slot
PDB-112-350-3			350kcmil-6	1	4-14	12	310	3	L	3/8	Slot
PDB-112A-350-1			350kcmil-6	1	4-14	12	310	1	M	3/8	Slot
PDB-112A-350-2			350kcmil-6	1	4-14	12	310	2	M	3/8	Slot
PDB-112A-350-3			350kcmil-6	1	4-14	12	310	3	M	3/8	Slot
PDB-14-500-1			500kcmil-4	1	2/0-14	4	380	1	M	3/8	3/16
PDB-14-500-2			500kcmil-4	1	2/0-14	4	380	2	M	3/8	3/16
PDB-14-500-3			500kcmil-4	1	2/0-14	4	380	3	M	3/8	3/16
PDB-16-350-1			350kcmil-6	1	2/0-14	6	310	1	L	3/8	3/16
PDB-16-350-2			350kcmil-6	1	2/0-14	6	310	2	L	3/8	3/16
PDB-16-350-3			350kcmil-6	1	2/0-14	6	310	3	L	3/8	3/16
PDB-162-500-1			500kcmil-4	1	2-14	6	380	1	M	3/8	Slot
PDB-162-500-2			500kcmil-4	1	2-14	6	380	2	M	3/8	Slot
PDB-162-500-3			500kcmil-4	1	2-14	6	380	3	M	3/8	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Valox® is a registered trade name of the General Electric Company.

Tested to UL 1059, UL File E84782




Fig. 1




Fig. 2




Fig. 3

Dimensions

Block Size	Number Of Poles	Figure Number	A	B	C	D	E	F	G	H	J	K
M	1	1	1-27/32	4	2-5/8	31/32	-	5/16	3-3/8	3/8	13/64	13/32
M	2	2	3-13/32	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
M	3	3	5	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
L	1	1	3	5-1/2	3-1/2	1-1/2	-	3/8	4-3/4	7/16	9/32	1/2
L	2	2	5-11/16	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2
L	3	3	8-3/8	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2

TYPE PDB

Features

- Range taking
- Valox* insulating base
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy
- UL Recognized rated 90° C and is CSA Certified, rated for 600 volts

Benefits

- Provides great flexibility in using the connector as an in line splice or to reduce conductor size
- Provides a high degree of impact resistance with superior insulating qualities
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors
- Ensures reliability



Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Block Size	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
PDB-212-4/0-1			4/0-6	2	4-14	12	460	1	M	3/8	Slot
PDB-212-4/0-2			4/0-6	2	4-14	12	460	2	M	3/8	Slot
PDB-212-4/0-3			4/0-6	2	4-14	12	460	3	M	3/8	Slot
PDB-26-350-1			350kcmil-6	2	2/0-14	6	620	1	L	3/8	3/16
PDB-26-350-2			350kcmil-6	2	2/0-14	6	620	2	L	3/8	3/16
PDB-26-350-3			350kcmil-6	2	2/0-14	6	620	3	L	3/8	3/16
PDB-16-500-1			500kcmil-4	1	2/0-14	6	380	1	L	3/8	3/16
PDB-16-500-2			500kcmil-4	1	2/0-14	6	380	2	L	3/8	3/16
PDB-16-500-3			500kcmil-4	1	2/0-14	6	380	3	L	3/8	3/16
PDB-212-500-1			500kcmil-4	2	4-14	12	760	1	L	3/8	Slot
PDB-212-500-2			500kcmil-4	2	4-14	12	760	2	L	3/8	Slot
PDB-212-500-3			500kcmil-4	2	4-14	12	760	3	L	3/8	Slot
PDB-24-500-1			500kcmil-4	2	4/0-6	4	760	1	L	3/8	5/16
PDB-24-500-2			500kcmil-4	2	4/0-6	4	760	2	L	3/8	5/16
PDB-24-500-3			500kcmil-4	2	4/0-6	4	760	3	L	3/8	5/16
PDB-26-500-1			500kcmil-4	2	2/0-14	6	760	1	L	3/8	3/16
PDB-26-500-2			500kcmil-4	2	2/0-14	6	760	2	L	3/8	3/16
PDB-26-500-3			500kcmil-4	2	2/0-14	6	760	3	L	3/8	3/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Valox® is a registered trade name of the General Electric Company.

Tested to UL 1059, UL File E84782




Fig. 1




Fig. 2




Fig. 3

Dimensions

Block Size	Number Of Poles	Figure Number	A	B	C	D	E	F	G	H	J	K
M	1	1	1-27/32	4	2-5/8	31/32	-	5/16	3-3/8	3/8	13/64	13/32
M	2	2	3-13/32	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
M	3	3	5	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
L	1	1	3	5-1/2	3-1/2	1-1/2	-	3/8	4-3/4	7/16	9/32	1/2
L	2	2	5-11/16	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2
L	3	3	8-3/8	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2


TYPE PDB

Features

- Multiple taps
- Range taking
- Valox* insulating base
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy
- UL Recognized rated 90° C and is CSA Certified, rated for 600 volts

Benefits

- Depending on product selected, up to twelve taps can be taken from one or two mains
- Provides tapping flexibility over a broad wire range
- Provides a high degree of impact resistance with superior insulating qualities
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors
- Ensures reliability






C

Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Block Size	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
PDB-11-2/0-1			2/0-14	1	2/0-14	1	175	1	M		
PDB-11-2/0-2			2/0-14	1	2/0-14	1	175	2	M	3/16	3/16
PDB-11-2/0-3			2/0-14	1	2/0-14	1	175	3	M		
PDB-11-350-1			350kcmil-6	1	350kcmil-6	1	310	1	M		
PDB-11-350-2			350kcmil-6	1	350kcmil-6	1	310	2	M	3/8	3/8
PDB-11-350-3			350kcmil-6	1	350kcmil-6	1	310	3	M		
PDB-11-500-1			500kcmil-4	1	500kcmil-4	1	380	1	L		
PDB-11-500-2			500kcmil-4	1	500kcmil-4	1	380	2	L	3/8	3/8
PDB-11-500-3			500kcmil-4	1	500kcmil-4	1	380	3	L		
PDB-22-2/0-1			2/0-14	2	2/0-14	2	350	1	M		
PDB-22-2/0-2			2/0-14	2	2/0-14	2	350	2	M	3/16	3/16
PDB-22-2/0-3			2/0-14	2	2/0-14	2	350	3	M		
PDB-22-350-1			350kcmil-6	2	350kcmil-6	2	620	1	L		
PDB-22-350-2			350kcmil-6	2	350kcmil-6	2	620	2	L	3/8	3/8
PDB-22-350-3			350kcmil-6	2	350kcmil-6	2	620	3	L		
PDB-22-500-1			500kcmil-4	2	500kcmil-4	2	760	1	L		
PDB-22-500-2			500kcmil-4	2	500kcmil-4	2	760	2	L	3/8	3/8
PDB-22-500-3			500kcmil-4	2	500kcmil-4	2	760	3	L		

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Valox® is a registered trade name of the General Electric Company.

Tested to UL 1059, UL File E84782



Dimensions

Block Size	Number Of Poles	Figure Number	A	B	C	D	E	F	G	H	J	K
M	1	1	1-27/32	4	2-5/8	31/32	-	5/16	3-3/8	3/8	13/64	13/32
M	2	2	3-13/32	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
M	3	3	5	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
L	1	1	3	5-1/2	3-1/2	1-1/2	-	3/8	4-3/4	7/16	9/32	1/2
L	2	2	5-11/16	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2
L	3	3	8-3/8	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2

TYPE PDB

Features

- Lay-In primary cable ports
- Valox insulating base
- Clear cover
- UL 1059 Recognized and CSA Certified for 600 volts
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy

Benefits

- Designed for feed through of two primary conductors and up to six taps with no need to break the main feeder cable
- Provides a high degree of impact resistance with superior insulating qualities
- Permits visual inspection
- Ensures reliability
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors




C

Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole			Primary	Secondary
	PDB-26-750-1			750kcmil-250kcmil	2	250kcmil-6			6	950

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 1059, UL File E84782



Block Size	No. of Poles	Dimensions							
		A	B	C	D	E	F	G	H
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16

* Valox® is a registered trade name of the General Electric Company.

TYPE PDB

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Valox* insulating base
- UL 1059 Recognized 90° C 600 volts
- Electro-tin plated
- Clear cover

Benefits


- Reliable use for copper conductor only
- Provides a high degree of impact resistance with superior insulating qualities
- Ensures reliability
- Provides low contact resistance
- Provides visual inspection



C

Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Block Size	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
										Primary	Secondary
PDB-55-600-1			600kcmil-250kcmil	5	600kcmil-250kcmil	5	1900	1	W	3/8	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 Valox® is a registered trade name of the General Electric Company.
 A versatile tap hole, wire range 8-14 AWG included on the connector.
 Tested to UL 1059, UL File E84782



Block Size	No. of Poles	Dimensions									
		A	B	C	D	E	F	G	H	J	K
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16	9/32	9/16

TYPE PDB

Features

- Multiple taps
- Valox* insulating base
- Clear cover
- UL 1059 Recognized 90° C 600 Volts and is CSA Certified
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy

Benefits

- Three different connector configurations provide a wide range of tapping capabilities for up to four primary conductors
- Provides a high degree of impact resistance with superior insulating qualities
- Permits visual inspection
- Ensures reliability
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Catalog Number	Figure Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number of Poles	Block Size	Hex Size	
		Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
PDB-428-500-1	1			500kcmil-4	4	4-14	28	1520	1	W	3/8	Slot
PDB-49-500-1	2			500kcmil-4	4	350kcmil-6 4/0-6	6 3	1520	1	W	3/8	3/8 5/16
‡ PDB-55-500-1	4			500kcmil-3/0	5	500kcmil-3/0	5	1600	1	W	3/8	3/8
PDB-412-500-1	3			500kcmil-4	4	4/0-6	12	1520	1	W	3/8	5/16


All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Valox® is a registered trade name of the General Electric Company.

° A versatile tap hole, wire range 8-14 AWG included on the connector.

‡ Not CSA Certified

Tested to UL 1059, UL File E84782



Block Size	No. of Poles	Dimensions									
		A	B	C	D	E	F	G	H	J	K
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16	9/32	9/16

TYPE IPC



Features

- Body is molded from tough, resilient glass-filled nylon
 - Compact design
 - Tin plated copper contact teeth
 - Insulation piercing
 - Perforated end tabs
 - Pre-filled with silicone lubricant
 - Versatile
 - Increased safety
- Horizontal line grid
 - Temperature rating 90° C

Benefits

- Provides high degree of breakage resistance and long dependable use
- Saves space
- Easily penetrates most types of insulation
- No need to strip the conductor which saves installation time
- Break out easily by hand
- Prevents oxidation and moisture from entering the contact area
- Can be used as a splice or tap connector
- Contains no external energized parts. Can be installed "hot" on energized conductors providing tap conductor is not under load.
- Provides a visual guide for proper installation of conductors




Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Wire Range		Volts	Current Rating		Dimensions			Torque Ft. Lbs.	Bolt Head Size
		Main	Tap		CU	AL	L	W	H		
IPC-1/0-2	3	1/0-8	2-8	300 (480 Grounded Y System)	130	100	1-7/32	1-15/32	2-5/16	16	1/2
IPC-4/0-6	2	4/0-4	6-14	600	75	60	1-27/64	1	1-7/8	13	1/2
IPC-4/0-2/0	3	4/0-2	2/0-6	600	195	150	1-21/32	1-7/8	2-7/8	25	1/2
IPC-250-4/0	2	250kcmil-1	4/0-6	600	260	205	1-7/8	2-11/32	3-11/32	30	5/8
IPC-350-4/0	3	350kcmil-4/0	4/0-10	300 (480 Grounded Y System)	260	205	1-43/64	2-7/16	3-1/8	25	5/8
IPC-350-350	4	350kcmil-4/0	350kcmil-4/0	300 (480 Grounded Y System)	350	280	2-43/64	2-23/32	3-1/4	25	5/8
IPC-500-12	1	500kcmil-250kcmil	10-12	300 (480 Grounded Y System)	40	35	1-43/64	2-7/16	3-1/4	25	5/8
IPC-500-250	1	500kcmil-250kcmil	250kcmil-4	600	290	230	2-27/64	2-29/32	3-3/4	55	5/8-11/16
IPC-500-500	1	500kcmil-300kcmil	500kcmil-250kcmil	600	430	350	3-3/16	3-5/8	5	75	7/8-7/8
IPC-750-500	1	750kcmil-500kcmil	500kcmil-350kcmil	600	430	350	3-3/16	3-5/8	5	75	7/8-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 486A/B, UL File E6207

ILSCO Aluminum Split Bolt - Dual Rated




TYPE AK

Features

- Manufactured from heat treated aluminum alloy
- Triangular edges
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Electro-tin plated
- Spacer bar
- Hex Head
- Rated to 90° C

Benefits

- Provides maximum conductivity and strength for copper and aluminum conductors
- Bite into the conductor to break through surface oxides which eliminates wire brushing
- Application versatility
- Provides low contact resistance
- Separates dissimilar metals which prevents galvanic corrosion
- Provides ease of installation with standard wrenches



Catalog Number	Wire Range		Recommended Tightening Torque	Dimensions		
	Main	Tap		B	C	D
AK-6	6 str-10 sol	6 str-10 sol	165	.56	.75	1.88
AK-4	4 str-8 sol	4 str-10 sol	165	.62	.81	1.38
AK-2	2 str-6 str Compact	2 str-8 str	275	.69	.94	1.58
AK-1/0	1/0 str-2 str Compact	1/0 str-8 str	385	.75	1.00	1.92
AK-2/0	2/0 str-2 str Compact	2/0 str-8 str	385	.88	1.12	1.92
AK-4/0	4/0 str-2 str Compact	4/0 str-6 str	500	1.13	1.49	2.54
AK-350	350kcmil-1/0 str Compact	350kcmil-4 str	650	1.50	1.69	3.24
AK-500	500kcmil-400kcmil Compact	500kcmil-2 str Compact	825	1.73	2.00	3.62

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.

UL File E9998



TYPE DBA DBA-S

Features

- Manufactured from high strength aluminum alloy
- Heat treated
- Wax plated
- Neoprene washers
- Range taking
- Re-usable
- Type DBA-S - Spacer bar

Benefits

- Type DBA - Suitable for copper to copper or aluminum to aluminum conductors
- Type DBA-S - Suitable for copper and/or aluminum conductors in any combination
- Provides maximum strength
- Provides low contact resistance
- Hold the bolts captive and eliminates the possibility of loose hardware
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Separates dissimilar metals




Fig. 1

Fig. 2

Catalog Number	Figure Number	Wire Range		Dimensions		
		Main	Tap	C	W	H
DBA-2/0	1	2/0-2	2/0-10	1-1/8	1-5/8	1-5/8
DBA-250	1	250kcmil-1/0	250kcmil-10	1-5/16	2	2
DBA-350	1	350kcmil-4/0	350kcmil-10	1-9/16	2-11/32	2-1/4
DBA-500	1	500kcmil-350kcmil	500kcmil-10	1-3/4	2-1/2	2-3/4
DBA-800	1	800kcmil-400kcmil	800kcmil-3/0	1-7/8	2-7/8	3
DBA-1000	1	1000kcmil-500kcmil	1000kcmil-3/0	2-1/4	3-3/16	3-1/2
DBA-2/0S	2	2/0-2	2/0-10	1-1/8	1-5/8	1-5/8
DBA-250S	2	250kcmil-1/0	250kcmil-10	1-5/16	2	2
DBA-350S	2	350kcmil-4/0	350kcmil-10	1-9/16	2-11/32	2-1/4
DBA-500S	2	500kcmil-350kcmil	500kcmil-10	1-3/4	2-1/2	2-3/4
DBA-800S	2	800kcmil-400kcmil	800kcmil-3/0	1-7/8	2-7/8	3
DBA-1000S	2	1000kcmil-500kcmil	1000kcmil-3/0	2-1/4	3-3/16	3-1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.

ILSCO Dual Rated Ground Clamp

RoHS
Compliant

UL
LISTED
667P

TYPE
AGC
SGC

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Clear plated
- Versatile
- Range taking
- SGC Lay-In feature

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Effectively grounds aluminum or copper conductors to copper water pipe, galvanized pipe or steel conduit
- Three sizes cover a range from 1/2" to 4" pipe with a ground wire range of 250kcmil - #14 which reduces inventory
- Provides ease of installation for long ground wire runs




Fig. 1



Fig. 2



Fig. 3

C

Catalog Number	Figure Number	Pipe Size	Rebar Size	Ground Wire Range	Screw Type	Dimensions		Hex Size
						L	W	
AGC-1	1	1/2-3/4-1	4, 5, 6	1/0-14	Slot	2-1/4	11/16	Slot
AGC-2	2	1 1/4-1 1/2-2	-	250kcmil-6	Hex Socket	3-3/4	13/16	5/16
AGC-4	2	2 1/2-3-3 1/2-4	-	250kcmil-6	Hex Socket	6-5/16	1	5/16
SGC-1/0*	3	1/2-3/4-1"	-	1/0-14	Slot	2-1/4	11/16	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 DE-OX Inhibitor is recommended for all aluminum terminations.
 * Typical application would be grounding computer floor room system.
 UL File E34440



ILSCO Dual Rated Lay-In Ground Lug





TYPE SGB

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Lay-in feature
- Stainless steel hardware
- Serrations in conductor wire way
- Unique clamp design
- 1/4" max frame thickness
- Meets ASTM B117-09

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- For corrosion resistance, greater torque and ease of installation
- Cuts oxidation
- No holes to be drilled for mounting
- Mount to solar panel frames
- Resistance to outdoor salt spray



Catalog Number	Ground Wire Range	Dimensions		
		L	W	H
SGB-4	4-14	1.375	.500	.940

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL 467 for grounding and bonding.

UL File E34440

DE-OX Inhibitor is recommended for all aluminum terminations.

TYPE GBL

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Lay-in feature

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation




Fig. 1



Fig. 2

Catalog Number	Figure Number	Ground Wire Range	Bolt Size	Dimensions							Hex Size
				C	D	E	F	G	H	T	
*GBL-4	1	4-14	10	7/32	5/8	31/64	1-3/32	13/64	25/64	51/64	Slot
+GBL-4SS	1	4-14	10	7/32	5/8	31/64	1-3/32	13/64	25/64	51/64	Slot
GBL-1/0	1	1/0-14	1/4	9/32	51/64	27/32	1-5/8	7/16	5/8	1-5/32	Slot
GBL-250	2	250kcmil-6	1/4	9/32	31/64	1	2-3/16	29/64	7/8	1-23/32	7/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL File E34440

* UL 467 and UL 486A/B Listed

+ UL 467 Listed

+ Supplied with stainless steel hardware. Meets ASTM B117-09 and is resistant to outdoor salt spray.

DE-OX Inhibitor is recommended for all aluminum terminations.

C

TYPE GBT

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Approved for UL 467 (Grounding & Bonding)
- Lay in style
- No mounting required
- 4 Taps (#2-14) stranded or solid
- Stainless steel screws
- Serrations in conductor wire way
- Patented

Benefits

- For use with copper and aluminum conductors
- Meets NEC 250.94 installation requirements
- Eliminates the need to cut or splice into existing conductor
- Allows fast simple installation on ground conductor below meter
- For bonding multiple communication systems (Phone, TV, Cable, etc.)
- For corrosion resistance
- Cuts oxidation



Fig. 1



Fig. 2




Fig. 3

Catalog Number	Figure Number	Wire Range Main	Wire Range Tap	Length	Width	Height	Hex Size	
							Main	Tap
GBT-1/0	1	1/0-8	2-14str-sol	2.250	1.125	1.160	S	S
GBT-250	1	250kcmil-8str - 1/0-8sol	2-14str-sol	2.250	1.375	1.587	7/32	S
GBT-1/0-M	2	1/0-8	2-14str-sol	2.250	1.750	1.160	S	S
GBT-1/0-M-W/C	3	1/0-8	2-14str-sol	2.730	3.930	2.110	S	S

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E34440


TYPE PED-Z

Features

- Available in two, four, six, or eight conductor configurations in four wire ranges
- Manufactured from high strength 6061-T6 aluminum alloy
- Compact size
- Rated for 600 volts, 90° C

Benefits

- Provides multiple conductor installation for a wide range of conductors
- Suitable for use with either copper or aluminum conductors
- Suitable for pedestal applications



Catalog Number	Connector Design	Number Of Ports	Wire Range	Dimensions			Hex Size
				L	W	H	
PED-2-2/0-Z		2	2/0-14	2.09	.56	.73	3/16
PED-4-2/0-Z		4	2/0-14	3.78	.56	.73	3/16
PED-6-2/0-Z		6	2/0-14	5.46	.56	.73	3/16
PED-8-2/0-Z		8	2/0-14	7.15	.56	.73	3/16
PED-2-4/0-Z		2	4/0-6	1.78	.75	1.00	5/16
PED-4-4/0-Z		4	4/0-6	3.64	.75	1.00	5/16
PED-6-4/0-Z		6	4/0-6	5.50	.75	1.00	5/16
PED-8-4/0-Z		8	4/0-6	7.36	.75	1.00	5/16
PED-2-350-Z		2	350kcmil-6	2.22	1.00	1.25	5/16
PED-4-350-Z		4	350kcmil-6	4.53	1.00	1.25	5/16
PED-6-350-Z		6	350kcmil-6	6.84	1.00	1.25	5/16
PED-8-350-Z		8	350kcmil-6	9.15	1.00	1.25	5/16
PED-2-600-Z		2	600kcmil-4	2.47	1.25	1.63	3/8
PED-4-600-Z		4	600kcmil-4	5.03	1.25	1.63	3/8
PED-6-600-Z		6	600kcmil-4	7.59	1.25	1.63	3/8
PED-8-600-Z		8	600kcmil-4	10.16	1.25	1.63	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Covers not available. DE-OX Inhibitor is recommended for all aluminum terminations.

TYPE
PED-X
PSA-Z
PEC

Features

- Available in four, six, or eight conductor configurations in four wire ranges
- Plastisol insulating cover available with a nominal thickness of 156 Mils
- Manufactured from high strength 6061-T6 aluminum alloy
- Compact size

Benefits

- Provides multiple conductor installation for a wide range of conductors
- Eliminates the need for taping. Plastisol covers have dielectric strength of 120 volts per Mil
- Suitable for use with either copper or aluminum conductors
- Suitable for pedestal applications




Fig. 1




Fig. 2



C

Catalog Number	Figure Number	Wire Range	No. of Cond.	Dimensions			Hex Size	Recommended Torque	Insulating Cover
				L	W	H			
PED-4-350-X	1	350kcmil-10	4	3-7/8	1	1-3/8	5/16	350	PEC-4-350
PED-6-350-X	1	350kcmil-10	6	5-11/16	1	1-3/8	5/16	350	PEC-6-350
PED-8-350-X	1	350kcmil-10	8	7-1/2	1	1-3/8	5/16	350	PEC-8-350
PED-4-500-X	1	500kcmil-10	4	4-3/4	1	1-5/8	5/16	450	PEC-4-500
PED-6-500-X	1	500kcmil-10	6	7-1/4	1	1-5/8	5/16	450	PEC-6-500
PED-8-500-X	1	500kcmil-10	8	9-11/16	1	1-5/8	5/16	450	PEC-8-500
PSA-4-750-Z	2	750kcmil-1/0	4	6-9/16	2	2-1/2	3/8	500	PSC-4-750
PSA-6-750-Z	2	750kcmil-1/0	6	9-7/8	2	2-1/2	3/8	500	PSC-6-750
PSA-8-750-Z	2	750kcmil-1/0	8	13-3/16	2	2-1/2	3/8	500	PSC-8-750

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 DE-OX Inhibitor is recommended for all aluminum terminations.


TYPE PED-CP

Features

- Available in three, four, five, and six conductor configurations in two wire ranges
- Connector is encapsulated in 125 Mils of clear PVC rated at 1000 amps
- Manufactured from high strength 6061-T6 aluminum alloy

Benefits

- Provides multiple conductor installation for a broad wire range
- Clear cover allows visual inspection of conductors during installation. Removable caps permit easy access to conductor ports and set screws. No taping is required.
- Suitable for use with either copper or aluminum conductors.



Catalog Number	Wire Range	Number of Conductors	Dimensions			Hex Size	Recommended Torque-Inch Lbs.
			L	W	H		
PED3-350-CP-Z	350kcmil-10	3	3.406	2-1/4	2-1/8	5/16	350
PED4-350-CP-Z	350kcmil-10	4	4.562	2-1/4	2-1/8	5/16	350
PED5-350-CP-Z	350kcmil-10	5	5.718	2-1/4	2-1/8	5/16	350
PED6-350-CP-Z	350kcmil-10	6	6.875	2-1/4	2-1/8	5/16	350

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.


TYPE PET

Features

- Available in four, six, or eight conductor configurations in four wire ranges
- Predrilled 1/2" mounting holes
- Manufactured from high strength 6061-T6 aluminum alloy

Benefits

- Provides multiple conductor installation for a wide range of conductors
- Allows easy attachment. May be bolted back to back for heavy duty applications
- Suitable for use with either copper or aluminum conductors



C

Catalog Number	Wire Range	Number of Conductors	Bolt Size	Diameter of Mounting Hole	Dimensions				Hex Size	Recommended Torque-Inch Lbs.
					H	J	W	L		
PET-4-350-Z	350kcmil-12	4	1/2	9/16	1-3/8	1-3/4	1	6-7/8	5/16	350
PET-6-350-Z	350kcmil-12	6	1/2	9/16	1-3/8	1-3/4	1	8-11/16	5/16	350
PET-8-350-Z	350kcmil-12	8	1/2	9/16	1-3/8	1-3/4	1	10-1/2	5/16	350
PET-4-500-Z	500kcmil-2	4	1/2	9/16	1-5/8	1-3/4	1	7-15/16	5/16	450
PET-6-500-Z	500kcmil-2	6	1/2	9/16	1-1/8	1-3/4	1	10-3/16	5/16	450
PET-8-500-Z	500kcmil-2	8	1/2	9/16	1-5/8	1-3/4	1	12-7/16	5/16	450
PET-4-750-Z	750kcmil-1/0	4	1/2	9/16	1-3/4	1-3/4	1-3/16	8-11/16	3/8	500
PET-6-750-Z	750kcmil-1/0	6	1/2	9/16	1-3/4	1-3/4	1-3/16	11-15/16	3/8	500
PET-8-750-Z	750kcmil-1/0	8	1/2	9/16	1-3/4	1-3/4	1-3/16	13-15/16	3/8	500

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.

TYPE PTT

Features

- Connector manufactured from high strength 6061-T6 aluminum alloy
- Stud manufactured from electrolytic pure copper rod
- Two conductor ports
- Range taking
- Left or Right handed
- Clear Plated

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides maximum conductivity and can be used on equipment with copper or aluminum connectors
- Allows parallel conductors to be connected to equipment supplied with single conductor terminals
- A wide range of conductor sizes can be used in each connector
- Provides ease of installation
- Provides low contact resistance




Fig. 1




Fig. 2

Catalog Number	Figure Number	Wire Range	Number of Conductors	Copper Stud Diameter	Stud Length	Hex Size	Dimensions			Recommended Torque-Inch Lbs.
							L	W	H	
PTT-2R-0-Z	1	1/0-14	2	3/8	3"	3/16	1.87	.75	1.00	200
PTT-2L-0-Z	2	1/0-14	2	3/8	3"	3/16	1.87	.75	1.00	200
PTT-2R-250-Z	1	250kcmil-10	2	1/2	4"	5/16	2.39	.90	1.12	300
PTT-2L-250-Z	2	250kcmil-10	2	1/2	4"	5/16	2.39	.90	1.12	300
PTT-2R-350-Z	1	350kcmil-10	2	5/8	4"	5/16	3.25	1.25	1.25	350
PTT-2L-350-Z	2	350kcmil-10	2	5/8	4"	5/16	3.25	1.25	1.25	350

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.



TYPE NB

Features

- Preassembled, stacked neutral bars
- Available with phenolic base
- Electro-tin plated
- Fabricated from high strength 6061-T6 aluminum alloy

Benefits

- Compact, space saving design offers multiple range taking flexibility and is suitable for grounding applications
- Provides insulation from mounting surface
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors





Fig. 1



Fig. 2




Fig. 3

Catalog Number	Figure Number	Number Of Circuit Taps	Wire Range		Dimensions			Two Tapped Mounting Holes	Hex Size	
			Circuit Taps	Line Loads	Approx. Height with Max. Wire	L	W		Main	Tap
NB-350-12	1	12	14-4	350kcmil-6	1-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-12-W/R16*	2	12	14-4	350kcmil-6	2-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-24	1	24	14-4	350kcmil-6	1-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-24-W/R16*	2	24	14-4	350kcmil-6	2-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-30	1	30	14-4	350kcmil-6	1-17/32	4-3/32	2-17/32	10-32	3/8	Slot
NB-350-30-W/R16*	2	30	14-4	350kcmil-6	2-17/32	4-3/32	2-17/32	10-32	3/8	Slot
NB-350-36	1	36	14-4	350kcmil-6	1-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-36-W/R16*	2	36	14-4	350kcmil-6	2-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-42	1	42	14-4	350kcmil-6	1-17/32	5-11/32	2-17/32	10-32	3/8	Slot
NB-350-42-W/R16*	2	42	14-4	350kcmil-6	2-17/32	5-11/32	2-17/32	10-32	3/8	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Part includes phenolic mounting block R-16

Tested to UL 486A/B, UL File E6207

Catalog Number	Figure Number	Number of Outlets	Wire Range	Length
NB-120	3	120	30 outlets 1/0-14 90 outlets 6-14	36.25"

UL File E6207

TYPE USPA-SS

Features

- Encapsulated in EPDM rubber with a nominal thickness of 125 Mils and a dielectric strength of 240 Volts per Mil
- Pre-marked end inserts
- O-Ring design screw cap inserts
- Connector is produced from high strength 6061-T6 aluminum alloy
- Connector rated for 600 volts, 90° C
- Range taking
- UL Listed and CSA Certified for direct burial in earth or concrete

Benefits

- Completely watertight in line splice. Ready for installation. (not a mold for use with mixed compounds) No taping required. No temperature or humidity restrictions.
- Simply cut end inserts to appropriate marked wire size and insert conductor into connector
- Ensures connector integrity while allowing ease of access to set screws, ensuring excellent sealing
- Suitable for use with either copper or aluminum conductors
- Ensures reliability
- Reduces inventory



Fig. 1



Fig. 2



Fig. 3

Catalog Number	Figure Number	Wire Range		Length	Hex Size	Recommended Torque-Inch Lbs.
		Barrel A	Barrel B			
USPA-350SS-DB +	1	350kcmil-10str	350kcmil-10str	8- 5/8	5/16	350
USPA-500SS-DB	2	500kcmil-10	500kcmil-10	9-13/16	5/16	450
USPA-750SS-DB	3	750kcmil-2	750kcmil-2	9-13/16	5/16	500

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
+ RUS Listed

Tested to UL 486D, UL File E125087

TYPE DBK ASK

Features

- DBK-1 connectors manufactured from electrolytic copper
- All other connectors manufactured from high strength aluminum alloy
- Heavy wall heat shrink tubing with sealant
- Connector and heat shrink packaged together
- Rated for 600 volts, 90° C

Benefits

- Provides maximum conductivity for UF cable
- Provides high conductivity and can be used with either aluminum or copper conductors
- Provides watertight splice. Kits with heat shrink are designed to withstand abrasions due to direct burial in rocky soil.
- Provides ease of ordering
- Ensures reliability



Fig. 1



Fig. 2



Fig. 3

Catalog Number	Figure Number	UF Cable Range		Wire Range	Testing Certification
		Minimum	Maximum		
DBK-1	1	14/2 with Ground	8/3 with Ground	-	
DBK-2	2	-	-	2-8	
DBK-250	2	-	-	250kcmil-1	

Tested to UL 486D, UL File E125087

ABOVE GRADE SPLICE KITS

ASK-2*	3	-	-	2-8	
ASK-250*	3	-	-	250kcmil-1	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*Not UL Listed for direct burial.

Tested to UL 486A/B, UL File E6207

TYPE SS SSK SSKC

Features

- Watertight EPDM rubber splice cover
- Tapered ends
- Ready for installation
- Type SS is cover only supplied with lubricant
- Type SSK kit is supplied with both connector and lubricant

Benefits

- No taping required. Suitable for direct burial
- Fits a wide range of conductor sizes
- Not a mold, can be used in any type of weather. (moisture and humidity are not a factor)
- Can be used with standard aluminum or copper compression from 500kcmil - 6. Lubricant permits easy insertion of conductors into sleeve.
- Supplied with dual-rated mechanical splice connector with a wire range of 350kcmil - 6



Fig. 1



Fig. 2

Catalog Number	Figure Number	Wire Range		L
		Bolted Connector	Compression Sleeves	
SSK-350-Z	1	350kcmil-6	-	5-1/2
SS-350-Z	2	350kcmil-6	500kcmil-6	5-1/2



Catalog Number	Connector Catalog Number	Wire Size	Wire Range When Installed With IDT-12 Tool
SSKC-6-Z	AS-6	6	6
SSKC-4-Z	AS-4	4	4-6
SSKC-2-Z	AS-2	2	2-6
SSKC-1/0-Z	AS-1/0	1/0	1/0-1
SSKC-2/0-Z	AS-2/0	2/0	2/0-1
SSKC-3/0-Z	AS-3/0	3/0	3/0-1
SSKC-4/0-Z	AS-4/0	4/0	4/0-1
SSKC-250-Z	AS-250	250kcmil	250kcmil-1/0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE PG

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Clear plated
- Range taking

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Permits inventories to be kept to a minimum




Fig. 1



Fig. 2



Fig. 3

Catalog Number	Figure Number	Wire Range Both Grooves	Type and Bolt Size	Dimensions		
				L	H	W
PG810-S-Z	1	1/0-8 sol	3/8, Steel	1-1/8	1-5/8	1-3/16
PG620-Z	2	2/0-6 sol	7/16, AL	1-3/8	1-5/8	1-1/4
PG620-S-Z	2	2/0-6 sol	3/8, Steel	1-3/16	1-5/8	1-1/8
PG620-2A-Z	3	2/0-6 sol	3/8, AL	2-7/16	1-5/8	1-1/4
PG620-2S-Z	3	2/0-6 sol	3/8, Steel	2-7/16	1-5/8	1-1/4
PG402-S-Z	2	4/0-2	3/8, Steel	1-1/2	1-3/4	1-3/8
PG402-2S-Z	3	4/0-2	3/8, Steel	3-1/16	1-3/4	1-3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.

TYPE GRM GRF

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Type GRM - Elongated steel stud
- Type GRF - Threaded female design

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of grounding a single conductor to steel structures or to tap a single conductor from bus bar
- Provides ease of installation for a variety of standard stud sizes




Fig. 1




Fig. 2

Catalog Number	Figure Number	Wire Range Single Cable			Dia. Thread	Dimensions			Hex Size
		Max.	Min.	Steel Strand		A	B	L	
GRM-2A	1	2str	12sol/str	5/16	1/4"-20	-	11/16	1-1/4	Slot
GRM-2B	1	2str	12sol/str	5/16	5/16"-18	-	3/8	1-1/4	Slot
GRM-2C	1	2str	12sol/str	5/16	3/8"-16	-	9/16	1-1/4	Slot
GRM-0	1	1/0str	2str	3/8	1/2"-13	-	1	1-9/16	Slot
GRM-250A	1	250kcmil	1/0	9/16	1/2"-13	-	1	2-1/8	5/16
GRM-250B	1	250kcmil	1/0	9/16	5/8"-11	-	1	2-1/8	5/16
GRM-350	1	350kcmil	4/0	-	5/8"-11	-	1	2-1/2	3/8
GRM-500	1	500kcmil	350kcmil	-	3/4"-10	-	1-3/8	2-15/16	3/8
GRM-750	1	750kcmil	500kcmil	-	3/4"-10	-	1-3/8	3-3/8	1/2
GRF-2A	2	2str	12sol/str	5/16	1/4"-20	5/16	-	1-1/4	Slot
GRF-2B	2	2str	12sol/str	5/16	5/16"-18	3/8	-	1-1/4	Slot
GRF-2C	2	2str	12sol/str	5/16	3/8"-16	7/16	-	1-1/4	Slot
GRF-0	2	1/0str	2str	3/8	1/2"-13	1/2	-	1-9/16	Slot
GRF-250A	2	250kcmil	1/0	9/16	1/2"-13	1/2	-	2-1/8	5/16
GRF-250B	2	250kcmil	1/0	9/16	5/8"-11	3/4	-	2-1/8	5/16
GRF-350	2	350kcmil	4/0	-	5/8"-11	3/4	-	2-1/2	3/8
GRF-500	2	500kcmil	350kcmil	-	3/4"-10	7/8	-	2-15/16	3/8
GRF-750	2	750kcmil	500kcmil	-	3/4"-10	7/8	-	3-3/8	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.

TYPE
SLU
SLS
SAS
SAU

Features

- Manufactured from electrolytic copper tubing and strip stock
- Compact design
- Range taking
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- V-bottom collar
- SLU-35DB and SLU-70DB are UL 467 Listed and suitable for direct burial
- Rated to 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Application versatility
- Wires are wedged between arched pressure bar and collar establishing positive contact and firm permanent grip




Fig. 1




Fig. 2



Catalog Number	Screw Type	Figure Number	Wire Range Copper	Bolt Size	Dimensions							Hex Size
					C	D	E	F	G	H	T	
SLU-25	⊖	1	10-14	#6	5/32	9/32	7/16	1	3/16	5/16	21/32	Slot
SLU-35	⊖	1	6-14 & List Comb. (A)	#10	13/64	7/16	15/32	1-3/16	7/32	3/8	3/4	Slot
SLU-35DB	⊖	1	6-14 & List Comb. (A)	#10	13/64	7/16	15/32	1-3/16	7/32	3/8	3/4	Slot
SAU-70	⊖	1	4-14	1/4	17/64	7/16	17/32	1-5/16	1/4	3/8	13/16	Slot
SLU-70	⊖	1	2-8 & List Comb. (B)	1/4	17/64	1/2	21/32	1-17/32	1/4	1/2	1	Slot
SLU-70DB	⊖	1	2-8 & List Comb. (B)	1/4	17/64	1/2	21/32	1-17/32	1/4	1/2	1	Slot
SLU-125	⊖	1	1/0-6	1/4	17/64	5/8	13/16	1-31/32	7/16	5/8	1-11/32	Slot
SLU-175	⊖	1	3/0-4	3/8	13/32	3/4	15/16	2-3/16	7/16	3/4	1-9/16	3/16
SLU-225	⊖	1	4/0-2	5/16	11/32	1	1-5/32	2-5/8	1/2	1	1-13/16	7/32
SLU-300	⊖	1	350kcmil-1/0	3/8	13/32	1-1/4	1-1/2	3-3/16	1/2	1	2-5/8	5/16
SLU-400	⊖	1	500kcmil-1/0	3/8	13/32	1-1/2	1-15/16	4-14	15/16	1-1/2	2-3/4	5/16
SLU-650	⊖	1	1000kcmil-600kcmil	1/2	17/32	1-7/8	1-7/8	4-5/8	1-7/64	2	3-11/16	3/8
SLS-25	⊖	2	10-14	#6	5/32	9/32	19/32	61/64	3/16	5/16	19/32	Slot
SLS-35	⊖	2	6-14 & List Comb. (A)	#10	13/64	7/16	41/64	1-9/64	7/32	3/8	11/16	Slot
SAS-70	⊖	2	4-14	1/4	17/64	7/16	23/32	1-1/4	1/4	1/2	27/32	Slot
SLS-70	⊖	2	2-8 & List Comb. (B)	1/4	17/64	1/2	13/16	1-15/32	1/4	1/2	31/32	Slot
SLS-70-TN*	⊖	2	2-8 & List Comb. (B)	1/4	17/64	1/2	13/16	1-15/32	1/4	1/2	31/32	Slot
SLS-125	⊖	2	1/0-6	1/4	17/64	5/8	1-3/16	1-15/16	7/16	5/8	1-1/4	Slot
SLS-175	⊖	2	3/0-4	3/8	13/32	3/4	1-1/4	2-3/16	7/16	3/4	1-9/16	3/16
SLS-225	⊖	2	4/0-2	5/16	11/32	1	1-7/32	2-3/8	1/2	1	1-21/32	7/32
SLS-300	⊖	2	350kcmil-1/0	3/8	13/32	1-1/4	1-1/2	3-3/16	1/2	1	2-3/8	5/16
SLS-400	⊖	2	500kcmil-1/0	3/8	13/32	1-1/2	2-3/16	3-7/8	15/16	1-1/2	2-9/16	5/16
SLS-650	⊖	2	1000kcmil-600kcmil	1/2	17/32	1-7/8	3	5-1/8	1-3/16	2	3-11/16	3/8

* Tin Plated

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

(A) UL Listed wire combinations: (2) #10; (2) #12; (2) #14; (1) #12 and (1) #14; (1) #10 and (1) #12

(B) UL Listed wire combinations: (1) #8 and (1) #4; (1) #8 and (1) #6; (2) #4; (3) #8; (3) #6; (2) #8 and (1) #4; (2) #8 and (1) #6; (1) #6 and (1) #4; (2) #6

Tested to UL 486A/B, UL File E6207

TYPE E H

Features

- Manufactured from electrolytic copper tubing and strip stock
- Compact design
- Range taking
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- V-bottom collar
- Two mounting holes
- Rated to 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Application versatility
- Wires are wedged between arched pressure bar and collar establishing positive contact and firm permanent grip
- Acts as anti-rotation device and prevents turning in safety switches, control equipment etc.




Fig. 1




Fig. 2

Catalog Number	Figure Number	Wire Range Copper	Bolt Size	Dimensions								Hex Size
				C	D	E	F	G	H	J	T	
E-35	1	6-14 & List Comb. (A)	#10	13/64	7/16	1-1/2	2-1/4	7/32	3/8	1	3/4	Slot
E-70	1	2-8 & List Comb. (B)	1/4	17/64	1/2	1-1/2	2-7/16	1/4	1/2	1	1	Slot
E-125	1	1/0-6	1/4	17/64	5/8	1-7/8	2-15/16	7/16	5/8	1	1-11/32	Slot
E-225	1	4/0-2	5/16	11/32	1	2-5/32	3-19/32	1/2	1	1	1-13/16	7/32
E-300	1	350kcmil-1/0	3/8	13/32	1-1/4	3-11/16	5-11/16	13/16	1	1-7/8	2-5/8	5/16
E-400	1	500kcmil-1/0	3/8	13/32	1-1/2	3-13/16	6	15/16	1-1/2	1-3/4	2-3/4	5/16
E-650	1	1000kcmil-600kcmil	1/2	17/32	1-7/8	3-9/16	6-1/4	1-3/16	2	1-3/4	3-11/16	3/8
H-35	2	6-14 & List Comb. (A)	#10	13/64	7/16	1-5/8	2-1/8	7/32	3/8	1	11/16	Slot
H-70	2	2-8 & List Comb. (B)	1/4	17/64	1/2	1-7/8	2-1/2	1/4	1/2	1	31/32	Slot
H-225	2	4/0-2	5/16	11/32	1	2-7/32	3-3/8	1/2	1	1	1-21/32	7/32
H-400	2	500kcmil-1/0	3/8	13/32	1-1/2	3-15/16	5-5/8	15/16	1-1/2	1-3/4	2-9/16	5/16
H-650	2	1000kcmil-600kcmil	1/2	17/32	1-7/8	4-3/4	6-7/8	1-3/16	2	1-3/4	3-11/16	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

(A) UL Listed wire combinations: (2) #10; (2) #12; (2) #14; (1) #12 and (1) #14; (1) #10 and (1) #12

(B) UL Listed wire combinations: (1) #8 and (1) #4; (1) #8 and (1) #6; (2) #4; (3) #8; (3) #6; (2) #8 and (1) #4; (2) #8 and (1) #6; (1) #6 and (1) #4; (2) #6

Tested to UL 486A/B, UL File E6207


TYPE SLUH

Features

- Manufactured from electrolytic copper tubing and strip stock
- Compact design
- Range taking
- Re-usable
- Electro-tin plated
- Captive tang
- V-bottom collar
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Provides low contact resistance
- Suited for heavy duty applications requiring high torque to withstand vibration and high ambient heat
- Wires are wedged between arched pressure bar and collar establishing positive contact and firm permanent grip
- Application versatility



Catalog Number	Wire Range	Bolt Size	Dimensions							Hex Size
			C	D	E	F	G	H	T	
SLUH-35	6-14	#10	13/64	7/16	1/2	1-1/8	7/32	3/8	11/16	Slot
SLUH-90	2-14	1/4	17/64	9/16	5/8	1-31/64	1/4	1/2	27/32	Slot
SLUH-125	1/0-8	1/4	17/64	11/16	13/16	1-7/8	7/16	5/8	63/64	Slot
SLUH-225	250kcmil-6	5/16	11/32	1	1-5/32	2-7/16	1/2	1	1-17/64	1/4
SLUH-300	350kcmil-1/0	3/8	13/32	1-3/16	1-1/2	3-1/16	1/2	1	2-1/4	5/16
SLUH-400	500kcmil-1/0	3/8	13/32	1-3/8	1-15/16	3-13/16	15/16	1-1/2	2-15/32	5/16
SLUH-650	1000kcmil-4/0	1/2	17/32	1-57/64	1-7/8	4-5/16	1-3/16	2	3-3/32	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG) Tested to UL 486A/B, UL File E6207

Conductor Class - Fine Stranded

	B	C	G	H	I	K	M	Locomotive Cable
	-	-	14/49	-	-	14/41	14/104	14/19
	14/7	14/19	12/49	-	-	12/65	12/168	12/19
	12/7	12/19	-	-	-	-	-	-
	10/7	10/19	10/49	-	10/26	10/104	10/259	10/27
	-	-	8/49	8/133	8/41	8/168	8/420	8/37
	8/7	8/19	-	-	-	-	-	-
	6/7	6/19	-	-	-	-	-	-
	4/7	4/19	6/49	6/133	6/63	6/266	6/665	6/61
	3/7	3/19	4/49	4/133	4/105	4/420	4/1064	4/105
	2/7	2/19	3/49	3/133	3/133	3/532	3/1323	3/125
	1/19	1/37	2/49	2/133	2/161	2/665	2/1666	2/150
	1/0/19	1/0-37	1/133	1/259	1/210	1/836	1/2107	1/225
	2/0-19	2/0-37	1/0-133	1/0-259	-	-	1/0/2646	1/0/275
	3/0-19	3/0-37	2/0-133	2/0-259	1/0/266	1/0/1064	-	2/0/325
	/0-19	4/0-37	3/0-133	3/0-259	2/0/342	2/0/1323	2/0/3325	-
	250kcmil/37	250kcmil/61	-	-	3/0/418	3/0/1666	3/0/4256	3/0/450
	300kcmil/37	300kcmil/61	4/0-133	4/0-259	4/0/532	-	-	222.2kcmil/550
	350kcmil/37	350kcmil/61	250kcmil/259	250kcmil/427	250kcmil/637	4/0/2107	4/0/5320	262.6kcmil/650
	400kcmil/37	400kcmil/61	300kcmil/259	300kcmil/427	300kcmil/735	250kcmil/2499	250kcmil/6384	313.1kcmil/775
	500kcmil/37	500kcmil/61	350kcmil/259	350kcmil/427	350kcmil/882	300kcmil/2989	300kcmil/7581	-
	-	-	400kcmil/259	400kcmil/427	400kcmil/980	350kcmil/3458	350kcmil/8806	373.7kcmil/925
	600kcmil/61	600kcmil/91	-	-	-	-	-	444kcmil/1100
	700kcmil/61	700kcmil/91	500kcmil/259	500kcmil/427	500kcmil/1225	450kcmil/4522	450kcmil/11396	535.3kcmil/1325
	750kcmil/61	750kcmil/91	550kcmil/259	500kcmil/703	550kcmil/1372	500kcmil/5054	500kcmil/12691	-
	-	-	600kcmil/259	500kcmil/703	600kcmil/1470	550kcmil/5453	550kcmil/13664	646.4kcmil/1591
	1000kcmil/61	1000kcmil/91	750kcmil/259	500kcmil/703	650kcmil/1596	600kcmil/5985	600kcmil/14945	-

TYPE LO

Features

- Manufactured from electrolytic seamless copper tubing
- Compact design
- Range taking
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Application versatility




Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Bolt Size	Wire Range	Dimensions							Hex Size
				C	D	E	F	G	H	T	
LO-4	1	1/4	4-14	17/64	3/4	5/8	1-3/8	9/32	1/2	25/32	Slot
LO-0	2	1/4	1/0-14	9/32	11/16	27/32	1-3/4	13/32	3/4	11/16	Slot
LO-250	4	5/16	250kcmil-6	21/64	1	1-1/4	2-9/32	7/16	63/64	7/8	3/8
LO-350SH	3	1/2	350kcmil-4	17/32	7/8	1	2-7/32	1/2	1-1/8	1-3/16	3/8
LO-350STD	3	3/8	350kcmil-4	13/32	1-1/4	1-1/8	2-5/8	1/2	1-1/8	1-1/16	3/8
LO-500	4	3/8	500kcmil-4/0	25/64	1-1/4	1-9/16	3-5/16	7/8	1-1/2	1-1/2	3/8
LO-600	4	3/8	600kcmil-1	13/32	1-7/16	1-11/16	3-5/8	7/8	1-1/2	1-1/2	3/8
LO-1000	4	1/2	1000kcmil-500kcmil	17/32	1-17/32	1-7/8	3-15/16	27/32	2	2-1/16	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

TYPE


VT LO-S

Features

- Manufactured from electrolytic seamless copper tubing
- Compact design
- Range taking
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Application versatility



Catalog Number	Wire Range	Bolt Size	Dimensions								Hex Size
			C	D	E	F	G	H	J	T	
VT-4-S	4-14	#10	15/64	9/16	1	1-3/4	1/4	1/2	1/2	25/32	Slot
LO-0-S	1/0-14	1/4	9/32	11/16	1-9/16	2-1/2	3/8	3/4	7/8	19/32	Slot
LO-250-S	250kcmil-6	3/8	13/32	1	1-3/4	3-3/32	3/8	1	1	7/8	3/8
LO-350-S	350kcmil-4	3/8	7/16	7/8	2	3-1/2	3/8	1-1/8	1-1/16	1-1/4	3/8
LO-600-S	600kcmil-1	1/2	9/16	1-7/16	2	3-7/8	3/8	1-1/4	1-1/16	1-1/2	3/8
LO-1000-S	1000kcmil-500kcmil	1/2	9/16	1-9/16	2-1/2	4-1/2	3/8	1-5/8	1-3/16	2-1/16	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

TYPE XT LY

Features

- Manufactured from electrolytic copper tubing and strip stock
- Compact design
- Range taking
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- XT-6DB and XT-4DB are UL 467 Listed and suitable for direct burial
- Rated to 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Application versatility




Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Wire Range	Bolt Size	Dimensions								Hex Size
				C	D	E	F	G	H	T		
XT-10	3	10-14	#6	5/32	9/32	17/32	7/8	3/16	5/16	17/32	Slot	
XT-6 ‡	4	6-18	#10	13/64	3/8	17/32	1	7/32	3/8	3/4	Slot	
XT-6DB	3	6-14	#10	13/64	3/8	17/32	1	7/32	3/8	3/4	Slot	
XT-4	3	4-14 & List Comb. (A)	1/4	17/64	1/2	5/8	1-1/8	1/4	1/2	5/8	Slot	
XT-4DB	3	4-14 & List Comb. (A)	1/4	17/64	1/2	5/8	1-1/8	1/4	1/2	5/8	Slot	
XT-0	3	1/0-6 & List Comb. (B)	1/4	17/64	5/8	29/32	1-17/32	7/16	5/8	1	Slot	
XT-40	1	4/0-6	5/16	11/32	1	1-1/16	2-3/16	9/16	.81	1-5/8	EH 5/8	
XT-500*+	1	500kcmil-2/0	3/8	7/16	1-3/8	1-11/16	3-3/16	7/8	1-1/2	2-9/16	EH 3/4	
LY-250-S+	2	250kcmil-6	1/4	17/64	1	13/16	1-13/16	3/8	1	1	3/8	
LY-600	2	600kcmil-1/0 (C)	3/8	13/32	1-7/16	1-7/8	3-5/16	7/8	1-1/2	1-3/8	3/8	
LY-600-S	2	600kcmil-1/0 (C)	5/16	21/64	1-7/16	1-1/8	2-9/16	1/2	1-3/8	1-3/8	3/8	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*Furnished with Pressure Plate

+ EH External Hex

‡ UL 467 Listed for grounding and bonding. Not rated for direct burial.

(A) UL Listed wire combinations: (2) #14; (2) #12; (2) #10; (2) #8 and (4) #16

(B) UL Listed wire combinations: (2) #6 and (2) #8

(C) UL Listed wire combinations: (2) #4/0; (2) #3/0; (2) #2/0, and (2) #1/0

Tested to UL 486A/B, UL File E6207

ILSCO Copper Post Connectors

RoHS
Compliant

UL
LISTED
453G
SA
LR-29601


TYPE CP

Features

- Manufactured from high conductivity copper alloy
- Compact design
- Range taking
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides long lasting reliable contact
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Application versatility



Catalog Number	Wire Range	Bolt Size	Stud Hole Size	Dimensions			Hex Size
				L	W	H	
CP-8	8-14	10	13/64	51/64	3/8	27/64	Slot
CP-4	4-14	1/4	17/64	1-3/32	17/32	35/64	Slot
CP-0	1/0-8	5/16	11/32	1-1/2	3/4	5/8	1/4
CP-250	250kcmil-6	3/8	13/32	1-31/32	15/16	1-1/16	1/4
CP-500*	500kcmil-4/0	1/2	17/32	2-31/32	1-3/8	1-7/16	3/8
CP-1000*	1000kcmil-500kcmil	1/2	17/32	3-31/32	2-1/32	2-3/16	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Not CSA Certified

Tested to UL 486A/B, UL File E6207

TYPE CO

Features

- Manufactured from electrolytic seamless copper tubing
- Compact design
- Range taking
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Bossed mounting holes
- Rated for 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Application versatility
- Acts as an anti-rotation device and prevents the connector from turning



Catalog Number	Figure Number	Wire Range	Dimensions							
			L	W	Height With Maximum Wire	Bossed Mounting Hole Tapped	Style Boss And Outside Dimensions	Top Hole Tapped	Top Hole And Inner Side Walls Tapped	Bottom Clearance Hole
CO3RP	1	6-14	3/8	11/32	21/32	8-32	Round .216-.220	1/4-28	-	-
CO3SP	1	6-14	3/8	11/32	21/32	10-32	Square .216-.220	1/4-28	-	-
CO4RP	2	4-14	15/32	29/64	19/32	10-32	Round .227-.231	5/16-24	-	-
CO4SP	2	4-14	15/32	29/64	19/32	10-32	Square .227-.231	5/16-24	-	-
CO4CW	3	4-14	15/32	29/64	3/4	-	-	-	3/8-27	.203
CO4CP	8	4-14	15/32	29/64	21/32	-	-	5/16-24	-	.265
CO4DD	5	4-14	29/32	29/64	19/32	10-32	Round .227-.231	5/16-24	-	-
CO4-3	6	4-14	1-29/64	29/64	19/32	10-32	Square .227-.231	5/16-24	-	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

TYPE CO

Features

- Manufactured from electrolytic seamless copper tubing
- Compact design
- Range taking
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Bossed mounting holes
- Rated for 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Application versatility
- Acts as an anti-rotation device and prevents the connector from turning



Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Wire Range	Dimensions							
			L	W	Height With Maximum Wire	Bossed Mounting Hole Tapped	Style Boss And Outside Dimensions	Top Hole Tapped	Top Hole And Inner Side Walls Tapped	Bottom Clearance Hole
CO5RP	1	1/0-6	5/8	9/16	29/32	10-32	Round .227-.231	3/8-27	-	-
CO5SP	1	1/0-6	5/8	9/16	29/32	10-32	Square .227-.231	3/8-27	-	-
CO5CW	1	1-14	5/8	17/32	3/4	-	-	-	7/16-20	.205
CO5SW	2	1/0-14	5/8	17/32	11/16	12-24	Square .248-.252	-	7/16-20	-
CO6RP	3	4/0-2	1	13/16	1-9/16	1/4-20	Round .2825-.2875	9/16-24	-	-
CO7	4	500kcmil-1/0	1-3/8	1-1/8	2-3/8	1/4-20	Round .3025-.3225	5/8-18	-	-
CO8	4	1000kcmil-250kcmil	1-15/16	1-33/64	3-1/2	5/16-18	Round .365-.380	3/4-16	-	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

TYPE CO-PP

Features

- Manufactured from electrolytic seamless copper tubing
- Compact design
- Range taking
- Re-usable
- Bossed mounting holes
- Pressure plate
- Electro Tin Plated
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Acts as an anti-rotation device and prevents the connector from turning
- Prevents screw damage to the conductor
- Provides low contact resistance
- Application versatility




Fig. 1



Fig. 2

Catalog Number	Figure Number	Wire Range	Dimensions					
			L	W	H	Bottom Boss Size Outside	Bottom Boss Tapped	Set Screw In Top
CO4RPP*	1	4-14	9/16	29/64	41/64	Round .227-.231	10-32	5/16-24 Steel Headless
D-2742+	1	1/0-6	47/64	9/16	61/64	Round .227-.231	10-32	3/8-27 Steel Headless
D-2741+	1	1/0-6	47/64	9/16	61/64	Square .227-.231	10-32	3/8-27 Steel Headless
D-2740+	2	4/0-2	1-9/64	13/16	1-5/8	Round .2825-.2875	1/4-20	9/16-24 Steel Hex Head
D-2738+	2	500kcmil-1/0	1-21/32	1-1/8	2-3/8	Round .3025-.3225	1/4-20	5/8-18 Steel-Cap Hex Head
D-2739+	2	1000kcmil-500kcmil	2-1/4	1-33/64	3-1/2	Round .365-.380	5/16-18	3/4-16 Steel-Cap Hex Head

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* UL Recognized for both aluminum and copper conductor, 75° C rating

+ UL Recognized for copper conductors only

Tested to UL 486A/B, UL File E6207


TYPE TC

Features

- Manufactured from solid copper alloy
- Compact design
- Range taking
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Provides maximum conductivity and strength
- Space saving
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Application versatility



C

Catalog Number	Wire Range	Bolt Size	Hole Dia.	Dimensions			Hex Size
				L	W	H	
TC-6	6-14, (2) #8	#10	13/64	13/16	5/16	1/2	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

ILSCO Copper Service Entrance Mechanical Lugs

RoHS
Compliant


TYPE SX

Features

- Manufactured from high strength copper tubing
- Compact design
- Versatile

Benefits

- Provides maximum conductivity for copper conductors
- Requires very little space
- Can be installed with either screwdriver, wrench, or pliers



C

Catalog Number	Wire Range	Dimensions		
		L	W	H
SX-12	12str	9/32	1/4	3/8
SX-10-8	8-10str	5/16	1/4	31/64
SX-6+	6str	7/16	11/32	11/16
SX-4+	4str	1/2	13/32	25/32
SX-2	2str	3/4	31/64	15/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
+ RUS Listed



ILSCO Copper Splicer/Reducer

RoHS
Compliant

UL
LISTED
453G

TYPE 2SC


Features

- Manufactured from electrolytic seamless copper tubing
- Compact design
- Range taking
- Re-usable
- V-bottom collar with serrations
- Two screw design
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Wires are held securely between set screws and v-bottom providing superior pullout strength
- For light duty applications
- Application versatility

C



Catalog Number	Wire Range	Dimensions			Screw	Hex Size
		L	W	H		
2SC-35	6-14	7/8	21/64	11/16	Slotted Headless	Slot
2SC-50	4-14	7/8	3/8	3/4	Slotted Headless	Slot
2SC-70	2-4	1	15/32	29/32	Slotted Headless	Slot
2SC-125	2/0-1/0	1-1/16	39/64	13/16	Slotted Hex Head	Slot
2SC-225	250kcmil-3/0	2-5/16	49/64	1-7/16	Hex Head	7/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

ILSCO Copper Splicer/Reducer




TYPE N

Features

- Manufactured from electrolytic copper tubing and strip stock
- Compact design
- Range taking
- Re-usable
- V-bottom collar
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Wires are wedged between arched pressure bar and collar establishing positive contact and firm permanent grip
- Application versatility



C

Catalog Number	Wire Range	Dimensions				Hex Size
		D	F	H	T	
N-25	10-14	9/32	13/16	1-4	19/32	Slot
N-35	6-14 & List Combination (A)	7/16	1-3/16	3/8	11/16	Slot
N-70	2-8 & List Combination (B)	1/2	1-3/8	1/2	31/32	Slot
N-225	4/0-2	1	2-9/16	1	1-21/32	7/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

(A) UL Listed wire combinations: (2) #10; (2) #12; (2) #14; (1) #12 and (1) #14; (1) #10 and (1) #12

(B) UL Listed wire combinations: (1) #8 and (1) #4; (1) #8 and (1) #6; (2) #4; (3) #8; (3) #6; (2) #8 and (1) #4; (2) #8 and (1) #6; (1) #6 and (1) #4; (2) #6

Tested to UL 486A/B, UL File E6207



TYPE MU LU

Features

- Manufactured from electrolytic copper tubing and strip stock
- Compact design
- Range taking
- Re-usable
- V-bottom collar (Type LU)
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Wires are wedged between arched pressure bar and collar establishing positive contact and firm permanent grip
- Application versatility




Fig. 1




Fig. 2

Catalog Number	Figure Number	Wire Range	Bolt Size	Collar Style	Dimensions								Hex Size
					C	D	E	F	G	H	K	T	
MU-250	1	Two: 250kcmil-6	3/8	Square	25/64	1	1-9/16	2-15/16	7/8	1-1/2	1-5/8	15/16	1/4
MU-350	1	Two: 350kcmil-1/0	1/2	Round	9/16	1-9/16	1-13/16	3-5/16	7/8	1-3/4	1-7/8	1-9/16	3/8
MU-600	1	Two: 600kcmil-4/0	1/2	Round	9/16	1-1/4	1-13/16	3-5/8	7/8	2-1/4	2-1/2	1-3/4	3/8
LU-2	2	Two: 4/0-2	3/8	V-bottom	13/32	1	1-15/16	3-11/32	15/16	1-1/2	1-5/8	1-7/8	7/32
LU-4	2	Two: 350kcmil-1/0	3/8	V-bottom	13/32	1-1/4	1-3/4	3-1/2	21/32	1-3/4	2	2-7/32	5/16
LU-6	2	Two: 500kcmil-1/0	1/2	V-bottom	17/32	1-1/2	2-3/16	4-7/16	27/32	2	2-1/4	2-9/16	5/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207


TYPE CL

Features

- Range taking
- Easily installed with a key wrench
- Convenient peep hole
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Permits inventories to be kept to a minimum
- Time savings
- Easy inspection
- Provides efficient use and flexibility in the field
- Application versatility



Catalog Number	Wire Range	Dimensions						
		G	A	B	C	D	J	F
CL-1-8†	8-14	1/4	1-1/8	9/16	1/2	1/8	17/32	9/32
CL-1-4†	4-8	1/4	1-1/8	5/8	1/2	1/8	17/32	9/32
CL-1-1	1-4	1/4	1-5/8	13/16	5/8	7/32	1	11/32
CL-1-2/0	2/0-1	3/8	1-15/16	1	13/16	1/4	1-3/16	7/16
CL-1-4/0	4/0-2/0	3/8	2-3/8	1-1/4	1	9/32	1-13/32	17/32
CL-1-300	300kcmil-4/0	1/2	2-3/4	1-1/2	1-3/16	5/16	1-17/32	5/8
CL-1-500	500kcmil-300kcmil	1/2	3-1/16	1-11/16	1-3/8	11/32	1-13/16	3/4
CL-1-750	750kcmil-500kcmil	1/2	3-25/32	2-3/16	1-5/8	13/32	2-1/8	1
CL-1-1000	1000kcmil-750kcmil	5/8	4-5/16	2-15/32	1-7/8	15/32	2-11/32	1-3/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

† With Filister head screw. All other, hex socket screw.

UL File E158587

C


TYPE CL

Features

- Range taking
- Easily installed with a key wrench
- Convenient peep hole
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Permits inventories to be kept to a minimum
- Time savings
- Easy inspection
- Provides efficient use and flexibility in the field
- Application versatility



C

Catalog Number	Wire Range	Dimensions							
		G	A	B	C	D	J	F	H
CL-1-2/0N	2/0-1	1/2	3-15/16	3	1	1/4	11/16	9/16	1-3/4
CL-1-4/0N	4/0-2/0	1/2	4-1/8	3	1	9/32	1-9/32	9/16	1-3/4
CL-1-300N	300kcmil-4/0	1/2	4-3/16	3	1-3/16	5/16	1-15/32	9/16	1-3/4
CL-1-500N	500kcmil-300kcmil	1/2	4-7/8	3-1/2	1-3/8	11/32	1-13/16	9/16	1-3/4
CL-1-750N	750kcmil-500kcmil	1/2	5-3/32	3-1/2	1-3/4	13/32	2-1/8	9/16	1-3/4
CL-1-1000N	1000kcmil-750kcmil	1/2	5-1/4	3-1/2	3	15/32	2-1/8	9/16	1-3/4

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Furnished with bolt holes and spacing to fit equipment supplied with NEMA type connector mounting pads.
UL File E158587

TYPE HL

Features

- Manufactured from high strength cast bronze
- Range taking
- Re-usable
- Pressure pad/saddle
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Provides maximum conductivity and a high degree of breakage resistance
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Provides positive grip and low contact resistance.
- Application versatility




Fig. 1



Fig. 2

Catalog Number	Figure Number	Wire Range	Bolt Size	Dimensions								
				A	C	E	F	G	H	J	K	
HL4-1	1	4 str-8 sol	1/4	9/16	9/32	5/8	1-1/4	5/16	5/8	-	3/16	
HL8-1	1	1str-4 sol	1/4	3/4	9/32	11/16	1-9/16	11/32	11/16	-	7/32	
HL13-1	1	2/0 str-1 str	3/8	13/16	13/32	7/8	1-7/8	7/16	7/8	-	7/32	
HL21-1	1	4/0 str-2/0 str	3/8	1	7/16	1	2-3/16	1/2	1	-	1/4	
HL30-1	1	300kcmil-4/0 str	1/2	1-1/16	9/16	1-1/4	2-1/2	5/8	1-1/4	-	5/16	
HL35-1	1	350kcmil-250kcmil	1/2	1-3/16	9/16	1-1/4	2-9/16	5/8	1-1/4	-	5/16	
HL50-1	1	500kcmil-300kcmil	1/2	1-3/8	9/16	1-1/2	3	3/4	1-3/8	-	11/32	
HL75-1	1	750kcmil-500kcmil	5/8	1-5/8	11/16	1-3/4	3-7/16	7/8	1-3/4	-	3/8	
HL35-2N	2	350kcmil-250kcmil	1/2	1-1/2	9/16	3	4-1/4	5/8	3	1-3/4	5/16	
HL50-2N	2	500kcmil-300kcmil	1/2	1-1/2	9/16	3	4-7/16	5/8	3	1-3/4	11/32	
HL75-2N	2	750kcmil-500kcmil	1/2	1-5/8	9/16	3	4-11/16	5/8	3	1-3/4	3/8	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587

TYPE CL

Features

- Range taking
- Easily installed with a key wrench
- Convenient peep hole
- Re-usable
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Permits inventories to be kept to a minimum
- Time savings
- Easy inspection
- Provides efficient use and flexibility in the field
- Application versatility




Fig. 1




Fig. 2




Fig. 3




Fig. 4

Catalog Number	Figure Number	Wire Range	Dimensions								
			G	A	B	C	D	E	F	H	J
CL-2-8†	1	8-14	1/4	2-3/16	1-3/4	5/8	1/8	11/16	9/32	5/8	15/32
CL-2-4†	1	4-8	1/4	2-1/2	2	1	1/8	1	9/32	5/8	17/32
CL-2-1	1	1-4	3/8	2-13/16	2	1-1/4	7/32	1-1/4	7/16	1	19/32
CL-2-2/0	1	2/0-1	1/2	4-7/16	3-1/2	1-1/2	1/4	1-9/16	5/8	1-3/4	13/32
CL-2-4/0	1	4/0-2/0	1/2	4-5/8	3-1/2	1-3/4	9/32	1-3/4	5/8	1-3/4	15/16
CL-2-300	1	300kcmil-4/0	1/2	4-3/4	3-1/2	2	5/16	2-1/8	5/8	13-3/4	1-9/16
CL-2-500	1	500kcmil-300kcmil	1/2	5-3/8	3-15/16	2-1/2	11/32	2-1/2	5/8	1-3/4	1-13/16
CL-2-700	2	700kcmil-500kcmil	1/2	5-19/32	4	4	13/32	2-15/16	5/8	1-3/4	2-1/8
CL-2-1000	2	1000kcmil-750kcmil	1/2	5-27/32	4	4	15/32	3-1/4	5/8	1-3/4	2-11/32
CL-3-4/0	3	4/0-2/0	1/2	4-5/8	3-3/8	2-1/2	9/32	2-3/4	5/8	1-3/4	15/16
CL-3-300	3	300kcmil-4/0	1/2	4-3/4	3-1/2	3	5/16	3-1/4	5/8	1-3/4	1-17/32
CL-3-500	4	500kcmil-300kcmil	1/2	5-3/8	4	4	11/32	3-3/4	5/8	1-3/4	1-13/16
CL-3-750	4	750kcmil-500kcmil	1/2	5-19/32	4	4	13/32	4-3/8	5/8	1-3/4	2-1/8
CL-3-1000	4	1000kcmil-750kcmil	1/2	5-27/32	4	4	15/32	4-13/16	5/8	1-3/4	2-11/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

† With Filister Head Screw

UL File E158587

TYPE H2L

Features

- Manufactured from high strength cast bronze
- Range taking
- Re-usable
- Compact design
- Pressure pad/saddle
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Provides maximum conductivity and a high degree of breakage resistance
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Requires less space than two individual connectors
- Provides positive grip and low contact resistance
- Application versatility




Fig. 1




Fig. 2

Catalog Number	Figure Number	Wire Range		Bolt Size	Dimensions							
		Minimum	Maximum		C	D	E	F	G	H	J	K
H2L-13-1	1	1 str	2/0 str	1/2	9/16	1-5/8	1-1/2	2-1/2	3/4	1-5/8	-	7/32
H2L-21-1	1	2/0 str	4/0 str	1/2	9/16	1-3/4	1-3/4	2-15/16	7/8	1-7/8	-	5/16
H2L-21-2N	2	2/0 str	4/0 str	1/2	9/16	1-3/4	3	4-3/16	5/8	1-7/8	1-3/4	5/16
H2L-30-2N	2	4/0 str	300kcmil	1/2	9/16	2	3	4-3/8	5/8	2	1-3/4	5/16
H2L-35-2N	2	250kcmil	350kcmil	1/2	9/16	2-1/8	3	4-7/16	5/8	2-1/4	1-3/4	5/16
H2L-50-2N	2	300kcmil	500kcmil	1/2	9/16	2-7/16	3	4-1/2	5/8	2-1/2	1-3/4	3/8
H2L-75-2N	2	500kcmil	750kcmil	1/2	9/16	3-1/16	3	4-11/16	5/8	3	1-3/4	7/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587


TYPE H3L

Features

- Manufactured from high strength cast bronze
- Range taking
- Re-usable
- Compact design
- Pressure pad/saddle
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated for 90° C

Benefits

- Provides maximum conductivity and a high degree of breakage resistance
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Requires less space than three individual connectors
- Provides positive grip and low contact resistance
- Application versatility



Catalog Number	Wire Range		Bolt Size	Dimensions							
	Minimum	Maximum		C	D	E	F	G	H	J	K
H3L-21-2N	2/0 str	4/0 str	1/2	9/16	2-5/8	3	4-3/16	5/8	1-7/8	1-3/4	5/16
H3L-30-2N	4/0 str	300kcmil	1/2	9/16	3-1/16	3	4-3/8	5/8	2-3/8	1-3/4	5/16
H3L-35-2N	250kcmil	350kcmil	1/2	9/16	3-3/16	3	4-7/16	5/8	2-3/8	1-3/4	5/16
H3L-50-2N	300kcmil	500kcmil	1/2	9/16	3-5/8	3	4-1/2	5/8	2-1/2	1-3/4	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587


TYPE CGRC

Features

- Manufactured from cast bronze
- Supplied with stainless steel hardware
- Suitable for grounding and bonding in applications such as swimming pools and spas
- Copper conductor only

Benefits

- Ensures maximum strength and durability
- Suitable for direct burial in earth or concrete



Catalog Number	Ground Rod Size	Rebar Size	Ground Rod Wire Range	Rebar Wire Range	Dimensions		
					L	W	H
CGRC-38 +	3/8	#3	4-10	4-10	1/2	11/16	1
CGRC-48	1/2	#4	2-10	2-10	9/16	27/32	1-3/16
CGRC-58	5/8	#5	2-10	4-10	9/16	15/16	1-9/32
CGRC-68	3/4	#6	2-10	4-10	9/16	1-1/16	1-13/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Plain copper finish.

Tested to UL 467, UL File E34440

+ Not UL Listed or CSA Certified

ILSCO Cast Bronze Ground Rod Clamps

RoHS
Compliant

UL
LISTED
667P

SA
LR-29601


TYPE BGRC

Features

- Manufactured from cast bronze
- Supplied with stainless steel or silicone bronze hardware
- Copper conductor only

Benefits

- Ensures maximum strength and durability
- Suitable for direct burial in earth or concrete



Catalog Number	Ground Rod Size	Rebar Size	Ground Rod Wire Range	Rebar Wire Range	Dimensions		
					L	W	H
BGRC-48	1/2	-	2-10	-	7/8	3/4	1-1/4
BGRC-58	5/8	#5	1/0-8	1/0-8	1-1/32	29/32	1-13/32
BGRC-68	3/4	-	1/0-8	-	1	1	1-5/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 467, UL File E34440

ILSCO Cast Bronze Ground Rod Clamp

RoHS
Compliant



TYPE
SRC

Features

- Manufactured from bronze alloy
- Stainless steel bolt
- UL Listed for both copper clad and galvanized ground rods
- Range taking

Benefits

- Provides maximum strength and superior conductivity
- For direct burial
- Ensures reliability
- Reduces inventory requirement



C

Catalog Number	Ground Rod Size	Ground Rod Wire Range	Dimensions		
			L	W	H
SRC-1/0	3/8, 1/2, 5/8 3/4	10 sol - 1/0 str 8 sol - 1/0 str	13/16	1	1-1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL File E198108



ILSCO Ground Rod Clamps

RoHS
Compliant

UL
LISTED
667P

SA
LR-29601


TYPE GRC

Features

- Manufactured from seamless bronze tubing
- Supplied with silicon bronze screw
- Suitable for grounding and bonding in applications such as swimming pools and spas
- Copper conductor only

Benefits

- Provides maximum strength and superior conductivity
- Ground rod clamp is suitable for direct burial in earth or concrete



C

Catalog Number	Ground Rod Size	Ground Wire Range	Rebar Size	Rebar Wire Range	Dimensions	
					L	W
GRC-38	3/8	4-10	#3	4-10	5/8	5/8
GRC-58+	5/8	2-8	-	-	15/16	7/8
GRC-68	3/4, 5/8	2-8 for 3/4 rod, 1/0-8 for 5/8 rod	#5	1/0-8	1	1
GRC-75*	3/4	3/0-8	-	-	3/4	1-5/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Plain copper finish.

+ RUS Listed.

* Not UL Listed.

Tested to UL 467, UL File E34440

ILSCO Die Cast Ground Clamp

RoHS
Compliant

UL
LISTED
8M24


TYPE DCGC

Features

- Manufactured from die cast zinc alloy
- Assembled with zinc plated steel hardware
- Copper conductor only

Benefits

- Provides maximum durability while providing economy
- Provides corrosion resistance



Catalog Number	Conduit Size	Ground Wire Range	L	W	H
DCGC-1	1/2, 3/4, 1	2-8	2-13/64	1-3/8	1-1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587

C



ILSCO Cast Brass Ground Clamp




TYPE BGC

Features

- Manufactured from cast brass
- Type BGC-DB supplied with stainless steel or silicon bronze hardware
- Copper conductor only

Benefits

- Provides maximum conductivity and strength
- BGC-1DB and BGC-2DB are suitable for direct burial in earth or concrete. Can be used to ground swimming pools and spas.



C

Catalog Number	Pipe Size	Ground Wire Range	Dimensions		
			L	W	H
BGC-1	1/2, 3/4, 1	2-10	2-9/32	1-7/16	1-1/2
BGC-2	1-1/4, 1-1/2, 2	2-10	3-9/16	2-1/4	2
BGC-1DB*	1/2, 3/4, 1	2-10	2-9/32	1-7/16	1-1/2
BGC-2DB*	1-1/4, 1-1/2, 2	2-10	3-8/16	2-1/4	2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Suitable for direct burial in earth or concrete

UL File E158587

ILSCO Cast Bronze Ground Clamps

RoHS
Compliant

UL
LISTED
8M24

TYPE BGC

Features

- Manufactured from cast bronze
- Versatile

- Copper conductor only

Benefits

- Provides maximum conductivity and strength
- Type BGC supplied with conduit hub for 1/2"-1" rigid conduit; type BGC-A can be used for bare or armoured cable




Fig. 1




Fig. 2

Catalog Number	Figure Number	Pipe Size	Conduit Hub Size	Wire Range	Dimensions		
					H	W	L
BGC1-50	1	1/2-1	1/2	4str-8sol	1-1/2	1-1/32	2-1/4
BGC1-75	1	1/2-1	3/4	4str-8sol	1-1/2	1-1/32	2-1/4
BGC1-10	1	1/2-1	1	4str-8sol	1-1/2	1-1/32	2-1/4
BGC2-50	1	1-1/4-2	1/2	4str-8sol	2	1-3/4	3-19/32
BGC2-75	1	1-1/4-2	3/4	4str-8sol	2	1-3/4	3-19/32
BGC2-10	1	1-1/4-2	1	4str-8sol	2	1-3/4	3-19/32
BGC-1A*	2	1/2-1	-	4str-8sol	1-1/2	1-3/8	2-1/4
BGC-2A	2	1-1/4-2	-	4str-8sol	2	2-3/32	3-19/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* CSA Certified

UL File E158587

C



ILSCO Cast Bronze Ground Clamps

RoHS
Compliant

UL
LISTED
8M24

TYPE BGDB

Features

- Manufactured from bronze alloy
- UL Listed for direct burial in earth or concrete
- Lay-In feature

Benefits

- Ensures maximum strength and superior conductivity
- Ensures reliability
- Reduces installation time




Fig. 1

Fig. 2

Fig. 3

Fig. 4

Fig. 5

Catalog Number	Figure Number	Pipe Size	Rebar Size	Ground Rod Size	Ground Wire Range	Screw Material	Dimensions	
							L	W
BGC-2T-DB*	1	1/2-1	3/8-1	1/2-1	2str-10sol	silicon bronze	2-3/4	2-1/4
BGC-2P-DB*	2	1/2-1	3/8-1	1/2-1	2str-10sol	silicon bronze	2-3/4	2-1/4
BGC-2PS-DB+	3	1/2-1	3/8-1	1/4-1	2str-10sol 2 #8sol	stainless steel	2-1/4	2-1/4
BGC-4/0P-DB=##	4	1/2-1	3/8-1	1/2-1	4/0-8str	stainless steel	3	2-1/4
BGC-4/0S-DB=##	5	1/2-1	3/8-1	1/2-1	4/0-8str	stainless steel	2-3/4	2-1/4

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* UL File E207816

+ UL File E198108

= UL File E178441

Not RoHS compliant


TYPE D167

Features

- Manufactured from high strength copper tubing
- Range taking
- UL Recognized for 600 volts

Benefits

- Provides maximum conductivity
- A wide range of conductor sizes can be used in the same connector
- Ensures reliability for copper conductor



Catalog Number	Number Of Taps	Wire Range		Dimensions					Mounting Hole Positions	
		Main	Tap	L	Height With Maximum Wire	W	Bolt Size	Two Mounting Holes	From End Of Bar To First Mounting Hole	Distance Between Holes
D167-4	4	4-14	6-14	2-3/4	3/4	11/32	#10	13/64	.581 (2nd hole)	1.98
D167-6	6	4-14	6-14	3-1/2	3/4	11/32	#10	13/64	.978 (3rd hole)	1.98
D167-8	8	4-14	6-14	4-7/16	3/4	11/32	#10	13/64	1.375 (4th hole)	1.98
D167-10	10	4-14	6-14	5-1/8	3/4	11/32	#10	13/64	1.772 (5th hole)	1.98
D167-12	12	4-14	6-14	5-15/16	3/4	11/32	#10	13/64	2.169 (6th hole)	1.98
D167-14	14	4-14	6-14	6-23/32	3/4	11/32	#10	13/64	2.566 (7th hole)	1.98

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

TYPE CAN

Features

- Manufactured from high strength copper tubing
- Compact design
- Range taking
- Circuit bars inserted at a 20 angle
- Copper conductor only

Benefits

- Provides maximum conductivity
- Up to 42 circuit taps can be made in just 5 1/2" of space
- A wide range of conductor sizes can be used in the same connector
- Provides easy wire insertion




Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Number Of Taps	Wire Range		Dimensions			
			Main	Tap	L	Height With Maximum Wire	W	Two Tapped Mounting Holes
CAN-300	1	24	250kcmil-6	6-14	2-5/16	1-5/16	5-1/8	10-32
CAN-301	1	30	250kcmil-6	6-14	3	1-5/16	4-13/32	10-32
CAN-302	1	36	250kcmil-6	6-14	3	1-5/16	5-1/8	10-32
CAN-303	1	42	250kcmil-6	6-14	3	1-7/16	5-1/2	10-32
R-16	2	Mounting block of general purpose (phenolic black) suitable for mounting any of CAN Neutrals. 2-1/2" wide x 2-1/2" long x 1" thick.						
E-223	3	10-32 x 1/2" round head steel machine screws for fastening neutrals to mounting blocks. (Use lock washer to provide rigid assembly.)						
E-153	3	1/4-28 wire pressure screw 7/16" long. Screw is steel, zinc plated and chromate dipped.						
N-174	4	Supplied in 5' 9" lengths. Approximately 174 outlets. Wire range 14-6.						

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207


TYPE IK

Features

- Manufactured from high strength copper alloy
- Precision tooled threads
- UL 467 Listed for Grounding and Bonding 500kcmil thru 8
- CSA Certified for Grounding and Bonding 250kcmil thru 8
- RUS Accepted 8 thru 1/0 AWG
- For use with copper conductor types: Solid, Compact, Compressed, Concentric
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and high breakage resistance
- Allows maximum torque to be applied
- Suitable for direct burial in earth and concrete
- Application versatility



Catalog Number	Range For Equal Main & Tap	Min. Tap With One Max. Main	Max. Cond Copperweld		Rebar With 6 or 8 AWG	Wire Diameter	Dimensions				Recommended Torque (IN-LB)
			Str	Type A			A	B	C	D	
IK-10	10str - 16str	16str	-	-	N/A	.057 - .125	.125	0.344	0.500	0.719	80
IK-8	8str - 16str	16str	-	-	N/A	.057 - .145	.145	0.375	0.500	0.844	80
IK-6	6sol - 10sol	16sol	-	-	N/A	.102 - .162	.165	0.500	0.625	1.047	165
IK-4	4sol - 8sol	16sol	3 No. 12	8A	N/A	.128 - .204	.215	0.562	0.688	1.047	165
IK-3	2sol - 6sol	12sol	3 No. 9	5A	N/A	.162 - .258	.328	0.688	0.812	1.312	275
IK-2	2str - 6sol	14str	3 No. 7	3A	N/A	.162 - .292	.328	0.688	0.812	1.312	275
IK-1/0	1/0str - 4sol	14sol	3 No. 6	2A	N/A	.204 - .375	.377	0.750	0.875	1.641	385
IK-2/0	2/0str - 2sol	14str	3 No. 5	-	#3 (3/8)	.258 - .418	.420	0.812	1.000	1.812	385
IK-3/0	3/0str - 2sol	12sol	7 No. 7	-	N/A	.258 - .470	0.466	0.875	1.125	2.000	500
IK-250	250kcmil - 1/0sol	10sol	7 No. 5	-	#4 (1/2)	.325 - .575	0.579	1.000	1.312	2.078	650
IK-350	350kcmil - 4/0str	8sol	19 No. 7	-	#5 (5/8)	.528 - .682	0.746	1.500	1.625	2.625	650
IK-500	500kcmil - 250kcmil	8sol	19 No. 6	-	#6 (3/4)	.575 - .815	0.834	1.625	1.812	3.000	825
IK-750	750kcmil - 350kcmil	8sol	19 No. 5	-	N/A	.682 - .999	1.030	1.938	2.125	3.750	1000
IK-1000	1000kcmil - 500kcmil	8sol	-	-	N/A	.815 - 1.153	1.222	2.250	2.500	4.000	1100

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207

ILSCO Three Wire Copper Split Bolts




TYPE IK3

Features

- Manufactured from high strength copper alloy
- Precision tooled threads
- UL 467 Listed and CSA Certified for Grounding and Bonding
- RUS Accepted
- For use with copper conductor types: Solid, Compact, Compressed, Concentric
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and high breakage resistance
- Allows maximum torque to be applied
- Suitable for direct burial in earth and concrete
- Application versatility



Catalog Number	Range For Equal Main & Tap	Min. Tap With One Max. Main	Max Cond Copperweld		Wire Diameter Range	Dimensions				Recommended Torque (IN-LB)
			Str	Type A		A	B	C	D	
IK3-8	8str - 16str	16str	-	-	.057 - .145	0.144	0.375	0.500	0.844	80
IK3-6	6sol - 10sol	16sol	-	-	.102 - .162	0.166	0.500	0.625	1.109	165
IK3-4	4sol - 8sol	16sol	3 No. 12	8A	.128 - .204	0.217	0.562	0.688	1.266	165
IK3-2	2str - 6sol	14str	3 No. 7	3A	.162 - .258	0.326	0.688	0.812	1.547	275

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E6207

ILSCO Tin Plated Copper Split Bolts




TYPE SK

Features

- Manufactured from high strength copper alloy
- Electro-tin plated bolt, nut, spacer and pressure bar
- Precision tooled threads
- SK-10, SK-8, SK3, SK-2 SK-1/0, SK-2/0 are RUS Accepted
- For use with copper conductor types: Solid, Compact, Compressed, Concentric
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- For aluminum conductor consult factory
- Rated to 90° C

Benefits

- Provides maximum conductivity and high breakage resistance
- Provides low contact resistance
- Application versatility



C

Catalog Number	Range For Equal Main & Tap	Min. Tap With One Max. Main	Max Cond Copperweld		Wire Diameter Range	Dimensions				Recommended Torque (IN-LB)
			Str	Type A		A	B	C	D	
SK-10	10str - 16str	16str	-	-	.057 - .116	.144	0.375	0.500	0.844	80
SK-8	8str - 16str	16str	-	-	.057 - .145	0.144	0.375	0.500	0.844	80
SK-6	8str - 14str	14str	-	-	.073 - .146	.166	0.500	0.625	1.109	165
SK-4	6str - 10str	10sol	3 No. 12	8A	.116 - .184	0.217	0.562	0.688	1.266	165
SK-3	4str - 8sol AL 2sol - 8sol CU	8sol AL 8sol CU	3 No. 9	5A	.128 - .258	0.326	0.688	0.812	1.547	275
SK-2	2str - 8sol	8sol	3 No. 7	3A	.128 - .316	0.326	0.688	0.812	1.547	275
SK-1/0	1/0str - 6sol	10sol	3 No. 6	-	.162 - .375	0.376	0.750	0.875	1.641	385
SK-2/0	2/0str - 6str	10sol	3 No. 5	-	.184 - .419	.420	0.812	1.000	1.812	385
SK-3/0	3/0str - 4str	6sol	7 No. 7	-	.198 - .470	0.466	0.875	1.125	2.000	500
SK-250	250kcmil - 4str	4str	7 No. 5	-	.232 - .575	0.577	1.000	1.312	2.328	650
SK-350	350kcmil - 3/0str	1sol	19 No. 7	-	.447 - .682	0.746	1.500	1.625	2.625	650
SK-500	500kcmil - 3/0str	1/0str	19 No. 6	-	.447 - .815	0.834	1.625	1.812	3.000	825
SK-750	750kcmil - 250kcmil	2/0str	19 No. 5	-	.563 - .999	1.030	1.938	2.125	3.750	1000
SK-1000	1000kcmil - 350kcmil	4/0str	-	-	.682 - 1.162	1.222	2.250	2.500	4.000	1100

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E12822



ILSCO Copper Two Bolt Connectors

RoHS
Compliant




TYPE IKB

Features

- Manufactured from high strength copper alloy
- Two bolt design
- Longer peened bolt
- Suitable for use in circuits rated 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- For copper conductor only
- Rated to 90° C

Benefits

- Allows maximum conductivity and high breakage resistance
- Allows maximum pressure to be applied directly to the conductor strands
- Permits a swivel action for easier installation
- Application versatility



C

Catalog Number	Copper Wire Range		Dimensions		
	Main	Tap	C	H	W
IKB-4/0 +	1/0-4/0	4/0-10	1.10	1.97	1.72
IKB-350 +	350kcmil-250kcmil	350kcmil-10	1.38	2.48	2.14
IKB-500	500kcmil-400kcmil	500kcmil-10	1.50	2.80	2.25
IKB-800	800kcmil-400kcmil	800kcmil-3/0	1.62	3.32	2.50
IKB-1000	1000kcmil-500kcmil	1000kcmil-3/0	2.00	3.78	3.03

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

+ RUS Listed

Tested to UL 486A/B, UL File E6207

ILSCO Two Bolt Connectors

RoHS
Compliant


TYPE IKS

Features

- Manufactured from high strength copper alloy
- Electro-tin plated
- Two bolt design
- Longer peened bolt
- Serrated spacer bar
- For copper conductor only

Benefits

- Allows maximum conductivity and high breakage resistance
- Provides low contact resistance
- Allows maximum pressure to be applied directly to the conductor strands
- Permits a swivel action for easier installation
- Makes a secure connection



C

Catalog Number	Wire Range		Dimensions		
	Main	Tap	C	H	W
IKS-4/0	4/0-1/0	4/0-6	1.12	2.31	1.72
IKS-350	350kcmil-250kcmil	350kcmil-6	1.38	2.62	2.12
IKS-500	500kcmil-400kcmil	500kcmil-4	1.50	3.00	2.26
IKS-800	800kcmil-400kcmil	800kcmil-4/0	1.62	3.50	2.50
IKS-1000	1000kcmil-500kcmil	1000kcmil-4/0	2.00	4.03	3.03

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)



TIGHTENING TORQUE VALUES FOR ILSCO MECHANICAL SCREW CONNECTORS

AWG. OR CIRCULAR MILL SIZE	TIGHTENING TORQUE IN INCH POUNDS	
	SCREW DRIVER	EXTERNAL DRIVE WRENCH
14	35	75
12	35	75
10	35	75
8	40	75
6	45	110
4	45	110
2	50	150
1	50	150
1/0	50	180
2/0	50	180
3/0		250
4/0		250
250		325
350		325
500		375
600		375
700		375
750		375
800		500
1000		500

TIGHTENING TORQUE VALUES FOR ILSCO SOCKETHEAD SCREW CONNECTORS

INTERNAL SOCKET SIZE ACROSS FLATS INCHES	TIGHTENING TORQUE IN INCH POUNDS
1/8	45
5/32	100
3/16	120
7/32	150
1/4	200
5/16	275
3/8	375
1/2	500
9/16	600

Please reference the instruction sheet included with your connector for specific torque values.

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

N I M B U S.



PBT



220

PBTO



220

PBTD



221 - 222

PBTS



223 - 224

PBTM



225

PBTF



226 - 228

PCT



229

SPAR



230

TYPE PBT

Features

- Broad wire range: 750kcmil-14
- UL Listed and CSA Certified for 600 volts, 90° C
- Dual rated
- Cold temperature rated to -45° C
- High dielectric strength plastisol
- Black cover
- Removable plugs
- Prefilled with De-ox®

Benefits

- Flexibility in the field
- Ensures reliability
- For copper or aluminum conductor
- Application variability
- Chemical resistant
- UV Rated
- Entry port closure
- Prevents oxides from forming



D

Catalog Number	Figure No.	No. Of Ports	Wire Range	Dimensions			Hex Size
				L	W	H	
PBT-1/0	1	-	1/0-14	3.11	0.94	1.44	3/16
PBT-250	1	-	250kcmil-6	4.28	1.06	2.04	5/16
PBT-350	1	-	350kcmil-6	4.75	1.31	2.43	5/16
PBT-500	1	-	500kcmil-4	5.38	1.44	3.03	3/8
PBT-750	3	-	750kcmil-250kcmil	7.25	1.75	3.31	3/8
PBTO-4	2	2	4-14	1.17	1.25	1.31	1/8
PBTO-1/0	2	2	1/0-14	1.63	1.63	1.63	3/16
PBTO-3/0	2	2	3/0-6	1.89	1.68	1.86	1/4

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Per NEC Article 310-316, allowable ampacities are as follows: #4-95 Amps, 1/0-170 Amps, 3/0-225 Amps, 250-290 Amps, 350-350 Amps, 500-430 Amps, 750-535 Amps

Replacement caps & plugs available. Consult Factory

Tested to UL 486A/B, UL File E6207


TYPE PBTD

Features

- Broad wire range: 750kcmil-14
- UL Listed and CSA Certified for 600 volts, 90° C
- Dual rated
- Cold temperature rated to -45° C
- High dielectric strength plastisol
- Black cover
- Removable plugs
- Prefilled with De-ox®

Benefits

- Flexibility in the field
- Ensures reliability
- For copper or aluminum conductor
- Application variability
- Chemical resistant
- UV Rated
- Entry port closure
- Prevents oxides from forming



Catalog Number	No. Of Ports	Wire Range	Dimensions			Hex Size
			L	W	H	
PBTD-2-4	2	4-14	1.24	1.25	1.42	1/8
PBTD-3-4	3	4-14	1.70	1.25	1.42	1/8
PBTD-4-4	4	4-14	2.16	1.25	1.42	1/8
PBTD-5-4	5	4-14	2.61	1.25	1.42	1/8
PBTD-6-4	6	4-14	3.07	1.25	1.42	1/8
PBTD-2-1/0	2	1/0-14	1.67	1.63	1.63	3/16
PBTD-3-1/0	3	1/0-14	2.29	1.63	1.63	3/16
PBTD-4-1/0	4	1/0-14	2.92	1.63	1.63	3/16
PBTD-5-1/0	5	1/0-14	3.54	1.63	1.63	3/16
PBTD-6-1/0	6	1/0-14	4.17	1.63	1.63	3/16
PBTD-2-3/0	2	3/0-6	1.89	1.68	1.86	1/4
PBTD-3-3/0	3	3/0-6	2.65	1.68	1.86	1/4
PBTD-4-3/0	4	3/0-6	3.42	1.68	1.86	1/4
PBTD-5-3/0	5	3/0-6	4.18	1.68	1.86	1/4
PBTD-6-3/0	6	3/0-6	4.95	1.68	1.86	1/4

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Per NEC Article 310-316, allowable ampacities are as follows: #4-95 Amps, 1/0-170 Amps, 3/0-225 Amps, 250-290 Amps, 350-350 Amps, 600-475 Amps, 750-535 Amps

Consult factory for additional port configurations

Replacement caps & plugs available. Consult Factory

Tested to UL 486A/B, UL File E6207

D


TYPE PBTD

Features

- Broad wire range: 750kcmil-14
- UL Listed and CSA Certified for 600 volts, 90° C
- Dual rated
- Cold temperature rated to -45° C
- High dielectric strength plastisol
- Black cover
- Removable plugs
- Prefilled with De-ox®

Benefits

- Flexibility in the field
- Ensures reliability
- For copper or aluminum conductor
- Application variability
- Chemical resistant
- UV Rated
- Entry port closure
- Prevents oxides from forming



D

Catalog Number	No. Of Ports	Wire Range	Dimensions			Hex Size
			L	W	H	
PBTD-2-250	2	250kcmil-6	2.17	2.13	2.17	5/16
PBTD-3-250	3	250kcmil-6	3.07	2.13	2.17	5/16
PBTD-4-250	4	250kcmil-6	3.96	2.13	2.17	5/16
PBTD-5-250	5	250kcmil-6	4.85	2.13	2.17	5/16
PBTD-6-250	6	250kcmil-6	5.75	2.13	2.17	5/16
PBTD-2-350	2	350kcmil-6	2.51	2.25	2.62	5/16
PBTD-3-350	3	350kcmil-6	3.56	2.25	2.62	5/16
PBTD-4-350	4	350kcmil-6	4.61	2.25	2.62	5/16
PBTD-5-350	5	350kcmil-6	5.67	2.25	2.62	5/16
PBTD-6-350	6	350kcmil-6	6.71	2.25	2.62	5/16
PBTD-2-500	2	600kcmil-4	2.97	2.63	3.04	3/8
PBTD-3-500	3	600kcmil-4	4.12	2.63	3.04	3/8
PBTD-4-500	4	600kcmil-4	5.28	2.63	3.04	3/8
PBTD-5-500	5	600kcmil-4	6.44	2.63	3.04	3/8
PBTD-6-500	6	600kcmil-4	7.59	2.63	3.04	3/8
PBTD-2-750	2	750kcmil-250kcmil	3.47	3.25	3.31	1/2
PBTD-3-750	3	750kcmil-250kcmil	4.89	3.25	3.31	1/2
PBTD-4-750	4	750kcmil-250kcmil	6.32	3.25	3.31	1/2
PBTD-5-750	5	750kcmil-250kcmil	7.74	3.25	3.31	1/2
PBTD-6-750	6	750kcmil-250kcmil	9.16	3.25	3.31	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Per NEC Article 310-316, allowable ampacities are as follows: #4-95 Amps, 1/0-170 Amps, 3/0-225 Amps, 250-290 Amps, 350-350 Amps, 600-475 Amps, 750-535 Amps

Consult factory for additional port configurations

Replacement caps & plugs available. Consult Factory

Tested to UL 486A/B, UL File E6207


TYPE PBTS

Features

- Broad wire range: 750kcmil-14
- UL Listed and CSA Certified for 600 volts, 90° C
- Dual rated
- Cold temperature rated to -45° C
- High dielectric strength plastisol
- Black cover
- Removable plugs
- Prefilled with De-ox®

Benefits

- Flexibility in the field
- Ensures reliability
- For copper or aluminum conductor
- Application variability
- Chemical resistant
- UV Rated
- Entry port closure
- Prevents oxides from forming



Catalog Number	No. Of Ports	Wire Range	Dimensions			Hex Size
			L	W	H	
PBTS-2-4	2	4-14	1.24	1.22	1.42	1/8
PBTS-3-4	3	4-14	1.70	1.22	1.42	1/8
PBTS-4-4	4	4-14	2.16	1.22	1.42	1/8
PBTS-5-4	5	4-14	2.61	1.22	1.42	1/8
PBTS-6-4	6	4-14	3.07	1.22	1.42	1/8
PBTS-2-1/0	2	1/0-14	1.67	1.53	1.63	3/16
PBTS-3-1/0	3	1/0-14	2.29	1.53	1.63	3/16
PBTS-4-1/0	4	1/0-14	2.92	1.53	1.63	3/16
PBTS-5-1/0	5	1/0-14	3.54	1.53	1.63	3/16
PBTS-6-1/0	6	1/0-14	4.17	1.53	1.63	3/16
PBTS-2-3/0	2	3/0-6	1.89	1.58	1.86	1/4
PBTS-3-3/0	3	3/0-6	2.65	1.58	1.86	1/4
PBTS-4-3/0	4	3/0-6	3.42	1.58	1.86	1/4
PBTS-5-3/0	5	3/0-6	4.18	1.58	1.86	1/4
PBTS-6-3/0	6	3/0-6	4.95	1.58	1.86	1/4

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Per NEC Article 310-316, allowable ampacities are as follows: #4-95 Amps, 1/0-170 Amps, 3/0-225 Amps, 250-290 Amps, 350-350 Amps, 600-475 Amps, 750-535 Amps

Consult factory for additional port configurations

Replacement caps & plugs available. Consult Factory

Tested to UL 486A/B, UL File E6207

D


TYPE PBTS

Features

- Broad wire range: 750kcmil-14
- UL Listed and CSA Certified for 600 volts, 90° C
- Dual rated
- Cold temperature rated to -45° C
- High dielectric strength plastisol
- Black cover
- Removable plugs
- Prefilled with De-ox®

Benefits

- Flexibility in the field
- Ensures reliability
- For copper or aluminum conductor
- Application variability
- Chemical resistant
- UV Rated
- Entry port closure
- Prevents oxides from forming



D

Catalog Number	No. Of Ports	Wire Range	Dimensions			Hex Size
			L	W	H	
PBTS-2-250	2	250kcmil-6	2.17	1.91	2.17	5/16
PBTS-3-250	3	250kcmil-6	3.07	1.91	2.17	5/16
PBTS-4-250	4	250kcmil-6	3.96	1.91	2.17	5/16
PBTS-5-250	5	250kcmil-6	4.85	1.91	2.17	5/16
PBTS-6-250	6	250kcmil-6	5.75	1.91	2.17	5/16
PBTS-2-350	2	350kcmil-6	2.51	2.03	2.62	5/16
PBTS-3-350	3	350kcmil-6	3.56	2.03	2.62	5/16
PBTS-4-350	4	350kcmil-6	4.61	2.03	2.62	5/16
PBTS-5-350	5	350kcmil-6	5.66	2.03	2.62	5/16
PBTS-6-350	6	350kcmil-6	6.71	2.03	2.62	5/16
PBTS-2-500	2	600kcmil-4	2.97	2.28	3.04	3/8
PBTS-3-500	3	600kcmil-4	4.12	2.28	3.04	3/8
PBTS-4-500	4	600kcmil-4	5.28	2.28	3.04	3/8
PBTS-5-500	5	600kcmil-4	6.44	2.28	3.04	3/8
PBTS-6-500	6	600kcmil-4	7.59	2.28	3.04	3/8
PBTS-2-750	2	750kcmil-250kcmil	3.47	2.75	3.31	1/2
PBTS-3-750	3	750kcmil-250kcmil	4.89	2.75	3.31	1/2
PBTS-4-750	4	750kcmil-250kcmil	6.32	2.75	3.31	1/2
PBTS-5-750	5	750kcmil-250kcmil	7.74	2.75	3.31	1/2
PBTS-6-750	6	750kcmil-250kcmil	9.16	2.75	3.31	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Per NEC Article 310-316, allowable ampacities are as follows: #4-95 Amps, 1/0-170 Amps, 3/0-225 Amps, 250-290 Amps, 350-350 Amps, 600-475 Amps, 750-535 Amps

Consult factory for additional port configurations

Replacement caps & plugs available. Consult Factory

Tested to UL 486A/B, UL File E6207


TYPE PBTM

Features

- Mountable
- Broad wire range: 750kcmil-6
- UL Listed and CSA Certified for 600 volts, 90° C
- Dual rated
- Cold temperature rated to -45° C
- High dielectric strength plastisol
- Black cover
- Removable plugs
- Prefilled with De-ox®

Benefits

- Isolated mounting in trough, wire way or panels
- Flexibility in the field
- Ensures reliability
- For copper or aluminum conductor
- Application variability
- Chemical resistant
- UV Rated
- Entry port closure
- Prevents oxides from forming



Catalog Number	No. Of Ports	Wire Range	Dimensions			Hex Size	Mounting Holes
			L	W	H		
PBTD-2-3/0-M	2	3/0-6	3.42	1.68	1.86	3/16	1/4
PBTD-3-3/0-M	3	3/0-6	4.18	1.68	1.86	3/16	1/4
PBTD-4-3/0-M	4	3/0-6	4.95	1.68	1.86	3/16	1/4
PBTD-5-3/0-M	5	3/0-6	5.71	1.68	1.86	3/16	1/4
PBTD-6-3/0-M	6	3/0-6	6.48	1.68	1.86	3/16	1/4
PBTD-2-250-M	2	250kcmil-6	3.96	2.13	2.17	5/16	1/4
PBTD-3-250-M	3	250kcmil-6	4.85	2.13	2.17	5/16	1/4
PBTD-4-250-M	4	250kcmil-6	5.75	2.13	2.17	5/16	1/4
PBTD-5-250-M	5	250kcmil-6	6.64	2.13	2.17	5/16	1/4
PBTD-6-250-M	6	250kcmil-6	7.53	2.13	2.17	5/16	1/4
PBTD-2-350-M	2	350kcmil-6	4.61	2.25	2.62	5/16	5/16
PBTD-3-350-M	3	350kcmil-6	5.67	2.25	2.62	5/16	5/16
PBTD-4-350-M	4	350kcmil-6	6.71	2.25	2.62	5/16	5/16
PBTD-5-350-M	5	350kcmil-6	7.76	2.25	2.62	5/16	5/16
PBTD-6-350-M	6	350kcmil-6	8.81	2.25	2.62	5/16	5/16
PBTD-2-500-M	2	600kcmil-4	5.28	2.63	3.04	3/8	5/16
PBTD-3-500-M	3	600kcmil-4	6.44	2.63	3.04	3/8	5/16
PBTD-4-500-M	4	600kcmil-4	7.59	2.63	3.04	3/8	5/16
PBTD-5-500-M	5	600kcmil-4	8.75	2.63	3.04	3/8	5/16
PBTD-6-500-M	6	600kcmil-4	9.90	2.63	3.04	3/8	5/16
PBTD-2-750-M	2	750kcmil-250kcmil	6.32	3.25	3.31	1/2	3/8
PBTD-3-750-M	3	750kcmil-250kcmil	7.74	3.25	3.31	1/2	3/8
PBTD-4-750-M	4	750kcmil-250kcmil	9.16	3.25	3.31	1/2	3/8
PBTD-5-750-M	5	750kcmil-250kcmil	10.58	3.25	3.31	1/2	3/8
PBTD-6-750-M	6	750kcmil-250kcmil	12.00	3.25	3.31	1/2	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Per NEC Article 310-316, allowable ampacities are as follows: #4-95 Amps, 1/0-170 Amps, 3/0-225 Amps, 250-290 Amps, 350-350 Amps, 600-475 Amps, 750-535 Amps

Consult factory for additional port configurations

Replacement caps & plugs available. Consult Factory.

Tested to UL 486A/B, UL File E6207

TYPE PBTF

Features

- Broad wire range: 750kcmil-14
- UL 486A/B Listed for 600 volts, 90° C
- Dual rated
- Cold temperature rated to -45° C
- High dielectric strength plastisol
- Black cover
- Removable plugs
- Prefilled with De-ox®
- NIMBUS Flexible caps are Reflex Blue
- Patented screw design

Benefits

- Flexibility in the field
- Ensures reliability
- For copper or aluminum conductor
- Application variability
- Chemical resistant
- UV Rated
- Entry port closure
- Prevents oxides from forming
- Easy identification in the field
- Eliminates the need for ferrules therefore making it reusable, allows for use of flexible or building conductor



D

Item ID	No. of Ports*	Conductor Range	Alternate Conductor Size	Ampere Rating	Dimensions			Hex Size
					Length	Width	Height	
PBTS-2-4-F+	2	8-14 H,I,K,M,DLO	4-14 AWG	95	1.24	1.22	1.42	1/8
PBTS-3-4-F	3	8-14 H,I,K,M,DLO	4-14 AWG	95	1.70	1.22	1.42	1/8
PBTS-4-4-F	4	8-14 H,I,K,M,DLO	4-14 AWG	95	2.16	1.22	1.42	1/8
PBTS-6-4-F	6	8-14 H,I,K,M,DLO	4-14 AWG	95	3.07	1.22	1.42	1/8
PBTS-2-1/0-F	2	1-14 H,I,K DLO 2-14 M	1/0-14 AWG	170	1.67	1.53	1.63	3/16
PBTS-3-1/0-F	3	1-14 H,I,K DLO 2-14 M	1/0-14 AWG	170	2.29	1.53	1.63	3/16
PBTS-4-1/0-F	4	1-14 H,I,K DLO 2-14 M	1/0-14 AWG	170	2.92	1.53	1.63	3/16
PBTS-6-1/0-F	6	1-14 H,I,K DLO 2-14 M	1/0-14 AWG	170	4.17	1.53	1.63	3/16
PBTS-2-3/0-F	2	2/0-6 H,I,K,DLO 1-6 M	3/0-6 AWG	225	1.89	1.58	1.86	1/4
PBTS-3-3/0-F	3	2/0-6 H,I,K,DLO 1-6 M	3/0-6 AWG	225	2.65	1.58	1.86	1/4
PBTS-4-3/0-F	4	2/0-6 H,I,K,DLO 1-6 M	3/0-6 AWG	225	3.42	1.58	1.86	1/4
PBTS-6-3/0-F	6	2/0-6 H,I,K,DLO 1-6 M	3/0-6 AWG	225	4.95	1.58	1.86	1/4
PBTS-2-250-F	2	4/0-6 H,I,K 2/0-6 M 3/0-6 DLO	250kcmil-6 AWG	290	2.17	1.91	2.17	1/4
PBTS-3-250-F	3	4/0-6 H,I,K 2/0-6 M 3/0-6 DLO	250kcmil-6 AWG	290	3.07	1.91	2.17	1/4
PBTS-4-250-F	4	4/0-6 H,I,K 2/0-6 M 3/0-6 DLO	250kcmil-6 AWG	290	3.96	1.91	2.17	1/4
PBTS-6-250-F	6	4/0-6 H,I,K 2/0-6 M 3/0-6 DLO	250kcmil-6 AWG	290	5.75	1.91	2.17	1/4
PBTS-2-350-F	2	250-6 H,I,K 4/0-6 M 262.2-6 DLO	350kcmil-6 AWG	350	2.51	2.03	2.62	5/16
PBTS-3-350-F	3	250-6 H,I,K 4/0-6 M 262.2-6 DLO	350kcmil-6 AWG	350	3.56	2.03	2.62	5/16
PBTS-4-350-F	4	250-6 H,I,K 4/0-6 M 262.2-6 DLO	350kcmil-6 AWG	350	4.61	2.03	2.62	5/16
PBTS-6-350-F	6	250-6 H,I,K 4/0-6 M 262.2-6 DLO	350kcmil-6 AWG	350	6.71	2.03	2.62	5/16
PBTS-2-500-F	2	350-4 H,I,K 4/0-4 M 373.7-4 DLO	600kcmil-4 AWG	475	2.78	2.38	3.03	3/8
PBTS-3-500-F	3	350-4 H,I,K 4/0-4 M 373.7-4 DLO	600kcmil-4 AWG	475	4.06	2.38	3.03	3/8
PBTS-4-500-F	4	350-4 H,I,K 4/0-4 M 373.7-4 DLO	600kcmil-4 AWG	475	5.34	2.38	3.03	3/8
PBTS-6-500-F	6	350-4 H,I,K 4/0-4 M 373.7-4 DLO	600kcmil-4 AWG	475	7.91	2.38	3.03	3/8
PBTS-2-750-F	2	500-3/0 H,I,K 4/0-3/0 M 535.3-3/0 DLO	750kcmil-4/0 AWG	535	3.34	2.69	3.06	1/2
PBTS-3-750-F	3	500-3/0 H,I,K 4/0-3/0 M 535.3-3/0 DLO	750kcmil-4/0 AWG	535	4.90	2.69	3.06	1/2
PBTS-4-750-F	4	500-3/0 H,I,K 4/0-3/0 M 535.3-3/0 DLO	750kcmil-4/0 AWG	535	6.46	2.69	3.06	1/2
PBTS-6-750-F	6	500-3/0 H,I,K 4/0-3/0 M 535.3-3/0 DLO	750kcmil-4/0 AWG	535	9.58	2.69	3.06	1/2

* Consult factory for additional port configurations All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Per NEC Article 310-316, allowable ampacities are as follows: #4-95 Amps, 1/0-170 Amps, 3/0-225 Amps, 250-290 Amps, 350-350 Amps, 600-475 Amps, 750-535 Amps
Replacement caps & plugs available. Consult Factory. Tested to UL 486A/B, UL File E6207 +Standard hex screw

TYPE PBTf

Features

- Broad wire range: 750kcmil-14
- UL 486A/B Listed for 600 volts, 90° C
- Dual rated
- Cold temperature rated to -45° C
- High dielectric strength plastisol
- Black cover
- Removable plugs
- Prefilled with De-ox®
- NIMBUS Flexible caps are Reflex Blue
- Patented screw design

Benefits

- Flexibility in the field
- Ensures reliability
- For copper or aluminum conductor
- Application variability
- Chemical resistant
- UV Rated
- Entry port closure
- Prevents oxides from forming
- Easy identification in the field
- Eliminates the need for ferrules therefore making it reusable, allows for use of flexible or building conductor



D

Item ID	No. of Ports*	Conductor Range	Alternate Conductor Size	Ampere Rating	Dimensions			Hex Size
					Length	Width	Height	
PBTD-2-4-F+	2	8-14 H,I,K,M,DLO	4-14 AWG	95	1.24	1.25	1.42	1/8
PBTD-3-4-F	3	8-14 H,I,K,M,DLO	4-14 AWG	95	1.70	1.25	1.42	1/8
PBTD-4-4-F	4	8-14 H,I,K,M,DLO	4-14 AWG	95	2.16	1.25	1.42	1/8
PBTD-6-4-F	6	8-14 H,I,K,M,DLO	4-14 AWG	95	3.07	1.24	1.42	1/8
PBTD-2-1/0-F	2	1-14 H,I,K DLO 2-14 M	1/0-14 AWG	170	1.67	1.63	1.63	3/16
PBTD-3-1/0-F	3	1-14 H,I,K DLO 2-14 M	1/0-14 AWG	170	2.29	1.63	1.63	3/16
PBTD-4-1/0-F	4	1-14 H,I,K DLO 2-14 M	1/0-14 AWG	170	2.92	1.63	1.63	3/16
PBTD-6-1/0-F	6	1-14 H,I,K DLO 2-14 M	1/0-14 AWG	170	4.17	1.63	1.63	3/16
PBTD-2-3/0-F	2	2/0-6 H,I,K,DLO 1-6 M	3/0-6 AWG	225	1.89	1.68	1.86	1/4
PBTD-3-3/0-F	3	2/0-6 H,I,K,DLO 1-6 M	3/0-6 AWG	225	2.65	1.68	1.86	1/4
PBTD-4-3/0-F	4	2/0-6 H,I,K,DLO 1-6 M	3/0-6 AWG	225	3.42	1.68	1.86	1/4
PBTD-6-3/0-F	6	2/0-6 H,I,K,DLO 1-6 M	3/0-6 AWG	225	4.95	1.68	1.86	1/4
PBTD-2-250-F	2	4/0-6 H,I,K 2/0-6 M 3/0-6 DLO	250kcmil-6 AWG	290	2.17	2.13	2.17	1/4
PBTD-3-250-F	3	4/0-6 H,I,K 2/0-6 M 3/0-6 DLO	250kcmil-6 AWG	290	3.07	2.13	2.17	1/4
PBTD-4-250-F	4	4/0-6 H,I,K 2/0-6 M 3/0-6 DLO	250kcmil-6 AWG	290	3.96	2.13	2.17	1/4
PBTD-6-250-F	6	4/0-6 H,I,K 2/0-6 M 3/0-6 DLO	250kcmil-6 AWG	290	5.75	2.13	2.17	1/4
PBTD-2-350-F	2	250-6 H,I,K 4/0-6 M 262.2-6 DLO	350kcmil-6 AWG	350	2.51	2.25	2.62	5/16
PBTD-3-350-F	3	250-6 H,I,K 4/0-6 M 262.2-6 DLO	350kcmil-6 AWG	350	3.56	2.25	2.62	5/16
PBTD-4-350-F	4	250-6 H,I,K 4/0-6 M 262.2-6 DLO	350kcmil-6 AWG	350	4.61	2.25	2.62	5/16
PBTD-6-350-F	6	250-6 H,I,K 4/0-6 M 262.2-6 DLO	350kcmil-6 AWG	350	6.71	2.25	2.62	5/16
PBTD-2-500-F	2	350-4 H,I,K 4/0-4 M 373.7-4 DLO	600kcmil-4 AWG	475	2.47	2.63	2.63	3/8
PBTD-3-500-F	3	350-4 H,I,K 4/0-4 M 373.7-4 DLO	600kcmil-4 AWG	475	3.75	2.63	2.63	3/8
PBTD-4-500-F	4	350-4 H,I,K 4/0-4 M 373.7-4 DLO	600kcmil-4 AWG	475	5.03	2.63	2.63	3/8
PBTD-6-500-F	6	350-4 H,I,K 4/0-4 M 373.7-4 DLO	600kcmil-4 AWG	475	7.59	2.63	2.63	3/8
PBTD-2-750-F	2	500-3/0 H,I,K 4/0-3/0 M 535.3-3/0 DLO	750kcmil-4/0 AWG	535	3.34	3.25	3.21	1/2
PBTD-3-750-F	3	500-3/0 H,I,K 4/0-3/0 M 535.3-3/0 DLO	750kcmil-4/0 AWG	535	4.90	3.25	3.21	1/2
PBTD-4-750-F	4	500-3/0 H,I,K 4/0-3/0 M 535.3-3/0 DLO	750kcmil-4/0 AWG	535	6.46	3.25	3.21	1/2
PBTD-6-750-F	6	500-3/0 H,I,K 4/0-3/0 M 535.3-3/0 DLO	750kcmil-4/0 AWG	535	9.58	3.25	3.21	1/2

* Consult factory for additional port configurations All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 Per NEC Article 310-316, allowable ampacities are as follows: #4-95 Amps, 1/0-170 Amps, 3/0-225 Amps, 250-290 Amps, 350-350 Amps, 600-475 Amps, 750-535 Amps
 Replacement caps & plugs available. Consult Factory. Tested to UL 486A/B, UL File E6207 +Standard hex screw

TYPE PBTf

Features

- Broad wire range: 750kcmil-14
- UL 486A/B Listed for 600 volts, 90° C
- Dual rated
- Cold temperature rated to -45° C
- High dielectric strength plastisol
- Black cover
- Removable plugs
- Prefilled with De-ox®
- NIMBUS Flexible caps are Reflex Blue
- Patented screw design

Benefits

- Flexibility in the field
- Ensures reliability
- For copper or aluminum conductor
- Application variability
- Chemical resistant
- UV Rated
- Entry port closure
- Prevents oxides from forming
- Easy identification in the field
- Eliminates the need for ferrules therefore making it reusable, allows for use of flexible or building conductor



D

Item ID	No. of Ports*	Conductor Range	Alternate Conductor Size	Ampere Rating	Dimensions			Hex Size		
					Length	Width	Height			
PBTD-2-3/0-M-F	2	2/0-6 H,I,K,DLO	1-6 M	3/0-6 AWG	225	3.42	1.68	1.86	1/4	
PBTD-3-3/0-M-F	3	2/0-6 H,I,K,DLO	1-6 M	3/0-6 AWG	225	4.18	1.68	1.86	1/4	
PBTD-4-3/0-M-F	4	2/0-6 H,I,K,DLO	1-6 M	3/0-6 AWG	225	4.95	1.68	1.86	1/4	
PBTD-6-3/0-M-F	6	2/0-6 H,I,K,DLO	1-6 M	3/0-6 AWG	225	6.48	1.68	1.86	1/4	
PBTD-2-250-M-F	2	4/0-6 H,I,K	2/0-6 M	3/0-6 DLO	250kcmil-6 AWG	290	3.96	2.13	2.17	5/16
PBTD-3-250-M-F	3	4/0-6 H,I,K	2/0-6 M	3/0-6 DLO	250kcmil-6 AWG	290	4.85	2.13	2.17	5/16
PBTD-4-250-M-F	4	4/0-6 H,I,K	2/0-6 M	3/0-6 DLO	250kcmil-6 AWG	290	5.73	2.13	2.17	5/16
PBTD-6-250-M-F	6	4/0-6 H,I,K	2/0-6 M	3/0-6 DLO	250kcmil-6 AWG	290	7.53	2.13	2.17	5/16
PBTD-2-350-M-F	2	250-6 H,I,K	4/0-6 M	262.2-6 DLO	350kcmil-6 AWG	350	4.61	2.25	2.62	5/16
PBTD-3-350-M-F	3	250-6 H,I,K	4/0-6 M	262.2-6 DLO	350kcmil-6 AWG	350	5.67	2.25	2.62	5/16
PBTD-4-350-M-F	4	250-6 H,I,K	4/0-6 M	262.2-6 DLO	350kcmil-6 AWG	350	6.71	2.25	2.62	5/16
PBTD-6-350-M-F	6	250-6 H,I,K	4/0-6 M	262.2-6 DLO	350kcmil-6 AWG	350	8.81	2.25	2.62	5/16
PBTD-2-500-M-F	2	350-4 H,I,K	4/0-4 M	373.7-4 DLO	600kcmil-4 AWG	475	5.34	3.03	3.20	3/8
PBTD-3-500-M-F	3	350-4 H,I,K	4/0-4 M	373.7-4 DLO	600kcmil-4 AWG	475	6.62	3.03	3.20	3/8
PBTD-4-500-M-F	4	350-4 H,I,K	4/0-4 M	373.7-4 DLO	600kcmil-4 AWG	475	7.41	3.03	3.20	3/8
PBTD-6-500-M-F	6	350-4 H,I,K	4/0-4 M	373.7-4 DLO	600kcmil-4 AWG	475	10.47	3.03	3.20	3/8
PBTD-2-750-M-F	2	500-3/0 H,I,K	4/0-3/0 M	535.3-3/0 DLO	750kcmil-4/0 AWG	535	6.46	3.25	3.58	1/2
PBTD-3-750-M-F	3	500-3/0 H,I,K	4/0-3/0 M	535.3-3/0 DLO	750kcmil-4/0 AWG	535	8.02	3.25	3.58	1/2
PBTD-4-750-M-F	4	500-3/0 H,I,K	4/0-3/0 M	535.3-3/0 DLO	750kcmil-4/0 AWG	535	9.58	3.25	3.58	1/2
PBTD-6-750-M-F	6	500-3/0 H,I,K	4/0-3/0 M	535.3-3/0 DLO	750kcmil-4/0 AWG	535	12.70	3.25	3.58	1/2

* Consult factory for additional port configurations

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Per NEC Article 310-316, allowable ampacities are as follows: #4-95 Amps, 1/0-170 Amps, 3/0-225 Amps, 250-290 Amps, 350-350 Amps, 600-475 Amps, 750-535 Amps

Replacement caps & plugs available. Consult Factory.

Tested to UL 486A/B, UL File E6207

TYPE PCT

Features

- Transparent flexible insulating cover
- Captive pressure screws
- Self-closing openings
- Access from both sides of connector
- Broad wire range: 800kcmil-14
- UL Listed for 600 volts, 90° C
- Dual Rated

Benefits

- No taping and allows visual inspection of connection
- No wasted time finding screws
- No lost or loose caps and plugs
- Provides greater versatility
- Reduces inventory
- Ensures reliability
- For copper or aluminum conductor




Fig. 1 (Patented)




Fig. 2

Catalog Number	Figure No.	No. Of Ports	Wire Range	Ampere Rating	Dimensions			Hex Size
					L	W	H	
PCT-2-4	1	2	4-14	95	1.46	1.57	1.43	slot
PCT-4-4	1	4	4-14	95	2.46	1.57	1.43	slot
PCT-6-4	1	6	4-14	95	3.46	1.57	1.43	slot
PCT-8-4	1	8	4-14	95	4.46	1.57	1.43	slot
PCT-2-2/0	2	2	2/0-14	195	2.61	2.30	1.97	3/16
PCT-4-2/0	2	4	2/0-14	195	4.30	2.30	1.97	3/16
PCT-6-2/0	2	6	2/0-14	195	5.98	2.30	1.97	3/16
PCT-8-2/0	2	8	2/0-14	195	7.67	2.30	1.97	3/16
PCT-2-4/0	2	2	4/0-6	260	2.33	2.49	2.25	5/16
PCT-4-4/0	2	4	4/0-6	260	4.19	2.49	2.25	5/16
PCT-6-4/0	2	6	4/0-6	260	6.05	2.49	2.25	5/16
PCT-8-4/0	2	8	4/0-6	260	7.91	2.49	2.25	5/16
PCT-2-350	2	2	350 kcmil-6	350	2.75	2.69	2.65	5/16
PCT-4-350	2	4	350 kcmil-6	350	5.06	2.69	2.65	5/16
PCT-6-350	2	6	350 kcmil-6	350	7.37	2.69	2.65	5/16
PCT-8-350	2	8	350 kcmil-6	350	9.68	2.69	2.65	5/16
PCT-2-600	2	2	600 kcmil-4	475	3.17	3.20	3.27	3/8
PCT-4-600	2	4	600 kcmil-4	475	5.73	3.20	3.27	3/8
PCT-6-600	2	6	600 kcmil-4	475	8.29	3.20	3.27	3/8
PCT-8-600	2	8	600 kcmil-4	475	10.86	3.20	3.27	3/8
PCT-2-800	2	2	800kcmil-250kcmil	555	3.91	3.34	3.30	1/2
PCT-4-800	2	4	800kcmil-250kcmil	555	7.03	3.34	3.30	1/2
PCT-6-800	2	6	800kcmil-250kcmil	555	10.15	3.34	3.30	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Not suitable for direct burial.

Tested to UL 486A/B, UL File E6207


TYPE SPAR

Features

- Transparent flexible insulating cover
- Range adjustable trim-to-fit tip
- Unique shape and compact design
- Connector, cover and cable tie packaged together
- UL Listed and CSA Certified for 600 volts
- Dual Rated

Benefits

- No taping and allows visual inspection of splice
- Ensures proper fit of cover to cable
- Provides ease of installation, versatility and serviceability of connections made in tight spaces
- Provides ease of ordering
- Ensures reliability
- Use with copper or aluminum conductor



D

Catalog Number	Wire Range	Dimensions			Screw Size & Shape
		L	W	H	
SPAR-4	4-14	3.30	1.55	.76	slotted
SPAR-2	2-14	3.83	1.75	.95	slotted
SPAR-1/0	1/0-14	4.80	1.94	1.14	3/16" socket head
SPAR-250	250kcmil-6	5.67	2.41	1.29	5/16" socket head
SPAR-350	350kcmil-10	6.17	3.29	1.79	5/16" socket head
SPAR-500	500kcmil-4	7.94	3.66	2.28	3/8" socket head

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Not suitable for direct burial.
DE-OX Oxide Inhibitor is recommended for all aluminum terminations.
Tested to UL 486A/B, UL File E6207

KUP-L-TAP® Insulation Piercing Connectors Save Time And Money

Tin plated, hardened copper contact teeth easily penetrate most types of conductor insulation.


Bolt tightens with just a wrench. Available in stainless steel for corrosive environments.

KUP-L-TAP® is dual-rated for copper and aluminum conductors.

End tabs knock out easily by hand.

A horizontal line grid provides a visual guide for proper alignment of connector body.

KUP-L-TAP® body is molded of tough, resilient glass-filled nylon. Silicone compound acts as a blocking agent to protect connection from oxidation



TYPE IPC



Features

- Body is molded from tough, resilient glass-filled nylon
 - Compact design
 - Tin plated copper contact teeth
 - Insulation piercing
 - Perforated end tabs
 - Pre-filled with silicone lubricant
 - Versatile
 - Increased safety
- Horizontal line grid
 - Temperature rating 90° C

Benefits

- Provides high degree of breakage resistance and long dependable use
- Saves space
- Easily penetrates most types of insulation
- No need to strip the conductor which saves installation time
- Break out easily by hand
- Prevents oxidation and moisture from entering the contact area
- Can be used as a splice or tap connector
- Contains no external energized parts. Can be installed "hot" on energized conductors providing tap conductor is not under load.
- Provides a visual guide for proper installation of conductors




Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Wire Range		Volts	Current Rating		Dimensions			Torque Ft. Lbs.	Bolt Head Size
		Main	Tap		CU	AL	L	W	H		
IPC-1/0-2	3	1/0-8	2-8	300 (480 Grounded Y System)	130	100	1-7/32	1-15/32	2-5/16	16	1/2
IPC-4/0-6	2	4/0-4	6-14	600	75	60	1-27/64	1	1-7/8	13	1/2
IPC-4/0-2/0	3	4/0-2	2/0-6	600	195	150	1-21/32	1-7/8	2-7/8	25	1/2
IPC-250-4/0	2	250kcmil-1	4/0-6	600	260	205	1-7/8	2-11/32	3-11/32	30	5/8
IPC-350-4/0	3	350kcmil-4/0	4/0-10	300 (480 Grounded Y System)	260	205	1-43/64	2-7/16	3-1/8	25	5/8
IPC-350-350	4	350kcmil-4/0	350kcmil-4/0	300 (480 Grounded Y System)	350	280	2-43/64	2-23/32	3-1/4	25	5/8
IPC-500-12	1	500kcmil-250kcmil	10-12	300 (480 Grounded Y System)	40	35	1-43/64	2-7/16	3-1/4	25	5/8
IPC-500-250	1	500kcmil-250kcmil	250kcmil-4	600	290	230	2-27/64	2-29/32	3-3/4	55	5/8-11/16
IPC-500-500	1	500kcmil-300kcmil	500kcmil-250kcmil	600	430	350	3-3/16	3-5/8	5	75	7/8-7/8
IPC-750-500	1	750kcmil-500kcmil	500kcmil-350kcmil	600	430	350	3-3/16	3-5/8	5	75	7/8-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

Power Distribution Blocks



PDH



234 - 235

PDE



236

PDL




237

PDS



238 - 239

PDM



240 - 241

LDAU/LDBU



242

PDBU



243 - 245

LDA/LDB

Snap Bloc®



246

PDA/PDC



247

PDB



248 - 253

TYPE PDH

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- UL 1059 Recognized 90° C 600 Volts and CSA Certified
- Electro-tin plated
- High Short Circuit Rating 100K RMS SYM Amps
- For use with building code or flexible conductor

Benefits

- Suitable for use with either copper or aluminum conductors
- Ensures reliability
- Provides low contact resistance
- Added protection




Fig. 1




Fig. 2




Fig. 3

F

Catalog Number	Fig. No.	Amps	High SCCR Conditions										SCCR RMS SYM Amps	Volts Max	Dimensions (in.)						Cover ID
			Rated Conductor Range		Suitable Conductors Per Pole		Overcurrent Protection Fuse Required Class/Max Amp Rating†								A	B	C	D	E	F w/cover	
			Line	Load	Line	Load	J	T	RK1	RK5	G	CC									
PDH-11-2-1*	1	115	(1) 2-14	(1) 2-14	(1) 2-6	(1) 2-6	200	200	200	100	60	30	200,000	600	0.83	2.29	1.53	-	1.93	1.60	C-2-1
PDH-11-2-2*	1	115	(1) 2-14	(1) 2-14	(1) 2-6	(1) 2-6	200	200	200	100	60	30	200,000	600	1.46	2.29	1.53	-	1.93	1.60	C-2-2
PDH-11-2-3*	1	115	(1) 2-14	(1) 2-14	(1) 2-6	(1) 2-6	200	200	200	100	60	30	200,000	600	2.10	2.29	1.53	1.27	1.93	1.60	C-2-3
PDH-11-2-4*	1	115	(1) 2-14	(1) 2-14	(1) 2-6	(1) 2-6	200	200	200	100	60	30	200,000	600	2.75	2.29	1.53	1.92	1.93	1.60	C-2-4
PDH-14-2-1*	1	115	(1) 2-14	(4) 10-18	(1) 2-6	(4) 10-14	200	200	200	100	60	30	200,000	600	0.83	2.29	1.53	-	1.93	1.60	C-2-1
PDH-14-2-2*	1	115	(1) 2-14	(4) 10-18	(1) 2-6	(4) 10-14	200	200	200	100	60	30	200,000	600	1.46	2.29	1.53	-	1.93	1.60	C-2-2
PDH-14-2-3*	1	115	(1) 2-14	(4) 10-18	(1) 2-6	(4) 10-14	200	200	200	100	60	30	200,000	600	2.10	2.29	1.53	1.27	1.93	1.60	C-2-3
PDH-14-2-4*	1	115	(1) 2-14	(4) 10-18	(1) 2-6	(4) 10-14	200	200	200	100	60	30	200,000	600	2.75	2.29	1.53	1.92	1.93	1.60	C-2-4
PDH-11-2/0-1	2	175	(1) 2/0-14	(1) 2/0-14	(1) 2/0-6	(1) 2/0-6	200	200	200	100	60	30	100,000	600	1.00	3.00	2.42	-	2.25	2.57	-
PDH-11-2/0-2	2	175	(1) 2/0-14	(1) 2/0-14	(1) 2/0-6	(1) 2/0-6	200	200	200	100	60	30	100,000	600	1.82	3.00	2.42	0.81	2.25	2.57	-
PDH-11-2/0-3	2	175	(1) 2/0-14	(1) 2/0-14	(1) 2/0-6	(1) 2/0-6	200	200	200	100	60	30	100,000	600	2.55	3.00	2.42	1.63	2.25	2.57	-
PDH-11-2/0-A‡	2	175	(1) 2/0-14	(1) 2/0-14	(1) 2/0-6	(1) 2/0-6	200	200	200	100	60	30	100,000	600	0.89	3.00	2.42	-	2.25	-	NA
PDH-14-2/0-1	2	175	(1) 2/0-14	(4) 4-14	(1) 2/0-6	(4) 4-14	200	200	200	100	60	30	100,000	600	1.00	3.00	2.42	-	2.25	2.57	-
PDH-14-2/0-2	2	175	(1) 2/0-14	(4) 4-14	(1) 2/0-6	(4) 4-14	200	200	200	100	60	30	100,000	600	1.82	3.00	2.42	0.81	2.25	2.57	-
PDH-14-2/0-3	2	175	(1) 2/0-14	(4) 4-14	(1) 2/0-6	(4) 4-14	200	200	200	100	60	30	100,000	600	2.55	3.00	2.42	1.63	2.25	2.57	-
PDH-14-2/0-A‡	2	175	(1) 2/0-14	(4) 4-14	(1) 2/0-6	(4) 4-14	200	200	200	100	60	30	100,000	600	0.89	3.00	2.42	-	2.25	-	NA
PDH-12-350-1	3	310	(1) 350-6	(2) 2/0-14	(1) 350-3/0	(1) 2/0-1	600	600	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-12-350-2	3	310	(1) 350-6	(2) 2/0-14	(1) 350-3/0	(1) 2/0-1	600	600	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-12-350-3	3	310	(1) 350-6	(2) 2/0-14	(1) 350-3/0	(1) 2/0-1	600	600	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-14-400-1	3	335	(1) 400-6	(4) 2-14	(1) 400-3/0	(4) 2-8	400	400	400	100	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-14-400-2	3	335	(1) 400-6	(4) 2-14	(1) 400-3/0	(4) 2-8	400	400	400	100	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-14-400-3	3	335	(1) 400-6	(4) 2-14	(1) 400-3/0	(4) 2-8	400	400	400	100	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-26-2/0-1	3	350	(2) 2/0-14	(6) 4-14	(1) 2/0-2	(6) 4-8	400	400	400	100	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-26-2/0-2	3	350	(2) 2/0-14	(6) 4-14	(1) 2/0-2	(6) 4-8	400	400	400	100	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-26-2/0-3	3	350	(2) 2/0-14	(6) 4-14	(1) 2/0-2	(6) 4-8	400	400	400	100	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-14A-500-1	3	380	(1) 500-4	(3) 2-14 (1) 350-6	(1) 500-3/0	(4) 350-6	600	600	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-14A-500-2	3	380	(1) 500-4	(3) 2-14 (1) 350-6	(1) 500-3/0	(4) 350-6	600	600	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-14A-500-3	3	380	(1) 500-4	(3) 2-14 (1) 350-6	(1) 500-3/0	(4) 350-6	600	600	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-11-600-1	3	420	(1) 600-2	(1) 600-2	(1) 600-2	(1) 600-2	400	400	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-11-600-2	3	420	(1) 600-2	(1) 600-2	(1) 600-2	(1) 600-2	400	400	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-11-600-3	3	420	(1) 600-2	(1) 600-2	(1) 600-2	(1) 600-2	400	400	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Cover not standard, available as an option. ‡ Adder Block, cover not available.

† For further details on conductors, fuse ratings, and additional SCCR ratings please refer to product data sheets.

TYPE PDH

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- UL 1059 Recognized 90° C 600 Volts and CSA Certified
- Electro-tin plated
- High Short Circuit Rating 100K RMS SYM Amps
- For use with building code or flexible conductor

Benefits

- Suitable for use with either copper or aluminum conductors
- Ensures reliability
- Provides low contact resistance
- Added protection




Fig. 3




Fig. 4

Catalog Number	Fig. No.	Amps	Rated Conductor Range		High SCCR Conditions								SCCR RMS SYM Amps	Volts Max	Dimensions (in.)						Cover ID
					Suitable Conductors Per Pole		Overcurrent Protection Fuse Required Class/Max Amp Rating†								A	B	C	D	E	F w/cover	
					Line	Load	J	T	RK1	RK5	G	CC									
PDH-18-600-1	3	420	(1) 600-2	(8) 2-14	(1) 600-3/0	(8) 2-8	400	400	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-18-600-2	3	420	(1) 600-2	(8) 2-14	(1) 600-3/0	(8) 2-8	400	400	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-18-600-3	3	420	(1) 600-2	(8) 2-14	(1) 600-3/0	(8) 2-8	400	400	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-112-600-1	3	420	(1) 600-2	(12) 4-14	(1) 600-3/0	(12) 4-8	600	600	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-112-600-2	3	420	(1) 600-2	(12) 4-14	(1) 600-3/0	(12) 4-8	600	600	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-112-600-3	3	420	(1) 600-2	(12) 4-14	(1) 600-3/0	(12) 4-8	600	600	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-19A-600-1	3	420	(1) 600-2	(6) 2-14 (3) 1/0-14	(1) 600-3/0	(9) 1/0-8	600	600	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-19A-600-2	3	420	(1) 600-2	(6) 2-14 (3) 1/0-14	(1) 600-3/0	(9) 1/0-8	600	600	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-19A-600-3	3	420	(1) 600-2	(6) 2-14 (3) 1/0-14	(1) 600-3/0	(9) 1/0-8	600	600	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-22-250-1	3	510	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	600	600	400	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-22-250-2	3	510	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	600	600	400	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-22-250-3	3	510	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	(2) 250-1/0	600	600	400	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-28-250-1	3	510	(2) 250-1/0	(8) 2-14	(2) 250-1/0	(8) 2-14	600	600	600	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-28-250-2	3	510	(2) 250-1/0	(8) 2-14	(2) 250-1/0	(8) 2-14	600	600	600	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-28-250-3	3	510	(2) 250-1/0	(8) 2-14	(2) 250-1/0	(8) 2-14	600	600	600	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-212-250-1	3	510	(2) 250-1/0	(12) 4-14	(2) 250-1/0	(12) 4-14	600	600	600	200	60	30	100,000	600	1.96	4.00	3.49	-	3.38	3.49	-
PDH-212-250-2	3	510	(2) 250-1/0	(12) 4-14	(2) 250-1/0	(12) 4-14	600	600	600	200	60	30	100,000	600	3.66	4.00	3.49	1.70	3.38	3.49	-
PDH-212-250-3	3	510	(2) 250-1/0	(12) 4-14	(2) 250-1/0	(12) 4-14	600	600	600	200	60	30	100,000	600	5.36	4.00	3.49	3.40	3.38	3.49	-
PDH-22-350-1*	4	620	(2) 350-4	(2) 350-4	(2) 350-4	(2) 350-4	450	450	400	200	60	30	100,000	600	3.17	5.50	3.12	-	4.75	3.18	C-6-1
PDH-22-350-2*	4	620	(2) 350-4	(2) 350-4	(2) 350-4	(2) 350-4	450	450	400	200	60	30	100,000	600	5.85	5.50	3.12	2.69	4.75	3.18	C-6-2
PDH-22-350-3*	4	620	(2) 350-4	(2) 350-4	(2) 350-4	(2) 350-4	450	450	400	200	60	30	100,000	600	8.54	5.50	3.12	5.38	4.75	3.18	C-6-3
PDH-22-500-1*	4	760	(2) 500-4	(2) 500-4	(2) 500-4	(2) 500-4	600	600	400	200	60	30	100,000	600	3.17	5.50	3.12	-	4.75	3.18	C-6-1
PDH-22-500-2*	4	760	(2) 500-4	(2) 500-4	(2) 500-4	(2) 500-4	600	600	400	200	60	30	100,000	600	5.85	5.50	3.12	2.69	4.75	3.18	C-6-2
PDH-22-500-3*	4	760	(2) 500-4	(2) 500-4	(2) 500-4	(2) 500-4	600	600	400	200	60	30	100,000	600	8.54	5.50	3.12	5.38	4.75	3.18	C-6-3
PDH-28-500-1*	4	760	(2) 500-6	(8) 2/0-14	(2) 500-250	(8) 2/0-14	600	600	400	200	60	30	100,000	600	3.17	5.50	3.12	-	4.75	3.18	C-6-1
PDH-28-500-2*	4	760	(2) 500-6	(8) 2/0-14	(2) 500-250	(8) 2/0-14	600	600	400	200	60	30	100,000	600	5.85	5.50	3.12	2.69	4.75	3.18	C-6-2
PDH-28-500-3*	4	760	(2) 500-6	(8) 2/0-14	(2) 500-250	(8) 2/0-14	600	600	400	200	60	30	100,000	600	8.54	5.50	3.12	5.38	4.75	3.18	C-6-3
PDH-212-500-1*	4	760	(2) 500-6	(12) 4-14	(2) 500-250	(12) 4-8	400	400	400	200	60	30	100,000	600	3.17	5.50	3.12	-	4.75	3.18	C-6-1
PDH-212-500-2*	4	760	(2) 500-6	(12) 4-14	(2) 500-250	(12) 4-8	400	400	400	200	60	30	100,000	600	5.85	5.50	3.12	2.69	4.75	3.18	C-6-2
PDH-212-500-3*	4	760	(2) 500-6	(12) 4-14	(2) 500-250	(12) 4-8	400	400	400	200	60	30	100,000	600	8.54	5.50	3.12	5.38	4.75	3.18	C-6-3

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Cover not standard, available as an option.

† For further details on conductors, fuse ratings, and additional SCCR ratings please refer to product data sheets.



TYPE PDE

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- UL Listed 75° C and CSA Certified, 600 volts
- Electro-tin plated
- High Short Circuit Rating 100K RMS SYM Amps
- Enclosed block provides IP-20 touch protection
- For use with building code or flexible conductor

Benefits

- Suitable for use with either copper or aluminum conductors
- Ensures reliability
- Provides low contact resistance
- Added protection



Catalog Number	Amps (CU Wire)	Rated Conductor Range		High SCCR Conditions								SCCR RMS SYM Amps	Volts Max	Dimensions (in.)				
				Suitable Conductors Per Pole		Overcurrent Protection Fuse Required Class/Max Amp Rating								A	B	C	D	E
				Line	Load	J	T	RK1	RK5	G	CC							
PDE-11-3/0	200	(1) 3/0-14	(1) 3/0-14	(1) 3/0-8	(1) 3/0-8	225	225	200	60	60	30	100,000	600	1.20	3.61	2.71	.56	3.00
PDE-11-3/0-CU	200	(1) 3/0-14	(1) 3/0-14	(1) 3/0-8	(1) 3/0-8	225	225	200	60	60	30	100,000	600	1.20	3.61	2.71	.56	3.00
PDE-14-3/0	200	(1) 3/0-14	(4) 2-14	(1) 3/0-8	(4) 2-14	225	225	200	60	60	30	100,000	600	1.20	3.61	2.71	.56	3.00
PDE-14-3/0-CU	200	(1) 3/0-14	(4) 2-14	(1) 3/0-8	(4) 2-14	225	225	200	60	60	30	100,000	600	1.20	3.61	2.71	.56	3.00
PDE-18-400†	335	(1) 400-6 (1) 2/0-14	(8) 2-16	(1) 400-3/0	(8) 2-8	400	400	400	200	60	30	100,000	600	2.27	4.39	3.14	1.11	3.75
PDE-18-400-CU†	335	(1) 400-6 (1) 2/0-14	(8) 2-16	(1) 400-3/0	(8) 2-8	400	400	400	200	60	30	100,000	600	2.27	4.39	3.14	1.11	3.75
PDE-22-250†	510	(2) 250-6	(2) 250-6	(2) 250-1/0	(2) 250-1/0	400	400	400	200	60	30	100,000	600	2.27	4.39	3.14	1.11	3.75
PDE-22-250-CU†	510	(2) 250-6	(2) 250-6	(2) 250-1/0	(2) 250-1/0	400	400	400	200	60	30	100,000	600	2.27	4.39	3.14	1.11	3.75

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

All PDE blocks are single pole and snap together for 2 and 3 pole configurations

† For further details on conductors, fuse ratings, and additional SCCR ratings please refer to product data sheets.

‡ UL Recognized.




TYPE PDL

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- UL Listed 75° C and CSA Certified, 600 volts
- Electro-tin plated
- High Short Circuit Rating 100K RMS SYM Amps

Benefits

- Suitable for use with either copper or aluminum conductors
- Ensures reliability
- Provides low contact resistance
- Added protection



Catalog Number	Amps (CU Wire)	Rated Conductor Range		High SCCR Conditions								SCCR RMS SYM Amps	Volts Max	Dimensions (in.)				
				Suitable Conductors Per Pole		Overcurrent Protection Fuse Required Class/Max Amp Rating								A	B	C	D	E
				Line	Load	Line	Load	J	T	RK1	RK5							
PDL-11-2/0-3	175	(1) 2/0-14	(1) 2/0-14	(1) 2/0-6	(1) 2/0-6	200	200	200	100	60	30	100,000	600	4.25	3.00	3.05	1.63	2.25
PDL-14-2/0-3	175	(1) 2/0-14	(4) 4-14	(1) 2/0-6	(4) 4-14	200	200	200	100	60	30	100,000	600	4.25	3.00	3.05	1.63	2.25
PDL-16-2/0-3	175	(1) 2/0-14	(6) 4-14	(1) 2/0-6	(6) 4-14	200	200	200	100	60	30	100,000	600	4.25	3.00	3.05	1.63	2.25
PDL-16-400-3	335	(1) 400-6	(6) 2-14	(1) 400-3/0	(6) 2-8	400	400	400	100	60	30	100,000	600	6.00	5.50	3.96	3.25	4.75
PDL-112-600-3	335	(1) 600-2	(12) 4-14	(1) 600-3/0	(12) 4-8	600	600	400	200	60	30	100,000	600	6.00	5.50	3.96	3.25	4.75
PDL-19A-600-3	335	(1) 600-2	(3) 1/0-14 (6) 2-14	(1) 600-3/0	(9) 1/0-8	600	600	400	200	60	30	100,000	600	6.00	5.50	3.96	3.25	4.75

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

PDL Distribution Blocks are also UL listed with high SCCR ratings with certain Circuit Breaker Combinations - consult factory.

† For further details on conductors, fuse ratings, and additional SCCR ratings please refer to product data sheets.





TYPE PDS

Features

- Connector, copper, tin plated
- Stud, brass, tin plated
- UL Recognized 75° C and CSA Certified
- Insulator base adders available
- Din rail or panel mountable
- Rated for 600 volts

Benefits

- Rated for copper conductor
- Intended for wires terminated with crimp lugs
- Ensures reliability
- Easily snap together to create variable pole power blocks



F

Catalog Number	Rated Amps	Conductor Range		Stud Ctr to Ctr	Line In	Line Out	Dimensions						Cover ID
		Line	Load				A	B	C	D	E	F w/cover	
PDS-11-KE-1†	230	(1) 3/8-16 X 1-3/16	(1) 1/4-20 x 1-3/16	-	Stud	Stud	1.94	4.00	2.61	-	3.38	3.38	C-4-1
PDS-11-KE-2†	230	(1) 3/8-16 X 1-3/16	(1) 1/4-20 x 1-3/16	-	Stud	Stud	3.47	4.00	2.61	1.53	3.38	3.38	C-4-2
PDS-11-KE-3†	230	(1) 3/8-16 X 1-3/16	(1) 1/4-20 x 1-3/16	-	Stud	Stud	5.00	4.00	2.61	3.06	3.38	3.38	C-4-3
PDS-11-PP-1	230	(1) 3/8-16 x 1-7/16	(1) 3/8-16 x 1-7/16	-	Stud	Stud	2.29	4.75	2.90	-	4.13	4.13	C-5-1
PDS-11-PP-2	230	(1) 3/8-16 x 1-7/16	(1) 3/8-16 x 1-7/16	-	Stud	Stud	4.17	4.75	2.90	1.88	4.13	4.13	C-5-2
PDS-11-PP-3	230	(1) 3/8-16 x 1-7/16	(1) 3/8-16 x 1-7/16	-	Stud	Stud	6.05	4.75	2.90	3.76	4.13	4.13	C-5-3
PDS-12-PC-1	260	(1) 3/8-16 x 1-7/16	(2) 1/4-20 x 9/16	.750	Stud	Stud	2.29	4.75	2.90	-	4.13	4.13	C-5-1
PDS-12-PC-2	260	(1) 3/8-16 x 1-7/16	(2) 1/4-20 x 9/16	.750	Stud	Stud	4.17	4.75	2.90	1.88	4.13	4.13	C-5-2
PDS-12-PC-3	260	(1) 3/8-16 x 1-7/16	(2) 1/4-20 x 9/16	.750	Stud	Stud	6.05	4.75	2.90	3.76	4.13	4.13	C-5-3
PDS-12-PG-1	360	(1) 3/8-16 x 1-7/16	(2) 1/4-20 X 1-7/16	1.125	Stud	Stud	3.17	5.50	3.12	-	4.75	4.75	C-6-1
PDS-12-PG-2	360	(1) 3/8-16 x 1-7/16	(2) 1/4-20 X 1-7/16	1.125	Stud	Stud	5.85	5.50	3.12	2.69	4.75	4.75	C-6-2
PDS-12-PG-3	360	(1) 3/8-16 x 1-7/16	(2) 1/4-20 X 1-7/16	1.125	Stud	Stud	8.54	5.50	3.12	5.38	4.75	4.75	C-6-3
PDS-12-PP-1	360	(1) 3/8-16 x 1-7/16	(2) 3/8-16 x 1-7/16	1.125	Stud	Stud	3.17	5.50	3.12	-	4.75	4.75	C-6-1
PDS-12-PP-2	360	(1) 3/8-16 x 1-7/16	(2) 3/8-16 x 1-7/16	1.125	Stud	Stud	5.85	5.50	3.12	2.69	4.75	4.75	C-6-2
PDS-12-PP-3	360	(1) 3/8-16 x 1-7/16	(2) 3/8-16 x 1-7/16	1.125	Stud	Stud	8.54	5.50	3.12	5.38	4.75	4.75	C-6-3
PDS-11-RR-1	410	(1) 1/2-13 x 1-7/16	(1) 1/2-13 x 1-7/16	-	Stud	Stud	3.17	5.50	3.12	-	4.75	4.75	C-6-1
PDS-11-RR-2	410	(1) 1/2-13 x 1-7/16	(1) 1/2-13 x 1-7/16	-	Stud	Stud	5.85	5.50	3.12	2.69	4.75	4.75	C-6-2
PDS-11-RR-3	410	(1) 1/2-13 x 1-7/16	(1) 1/2-13 x 1-7/16	-	Stud	Stud	8.54	5.50	3.12	5.38	4.75	4.75	C-6-3
PDS-11-HH-1	840	(1) 3/8-16 x 1	(1) 3/8-16 x 1	-	Stud	Stud	2.29	4.75	2.90	-	4.13	4.13	C-5-1
PDS-11-HH-2	840	(1) 3/8-16 x 1	(1) 3/8-16 x 1	-	Stud	Stud	4.17	4.75	2.90	1.88	4.13	4.13	C-5-2
PDS-11-HH-3	840	(1) 3/8-16 x 1	(1) 3/8-16 x 1	-	Stud	Stud	6.05	4.75	2.90	3.76	4.13	4.13	C-5-3

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG) For further details on conductor classes please refer to product data sheets

UL1059 terminal block standard file No. E84782 CSA certified CSA c22.2 No. 158, File number MC 249467 (wire classes B & C only)

† Connector aluminum, tin plated

TYPE PDS

Features

- Connector, copper, tin plated
- Stud, brass, tin plated
- UL Recognized 75° C and CSA Certified
- Insulator base adders available
- Din rail or panel mountable
- Rated for 600 volts

Benefits

- Rated for copper conductor
- Intended for wires terminated with crimp lugs
- Ensures reliability
- Easily snap together to create variable pole power blocks





Fig. 1




Fig. 2

Catalog Number	Fig. No.	Amps	Rated Conductor Range		Stud Ctr to Ctr	Line In	Line Out	Dimensions						Cover ID
			Line	Load				A	B	C	D	E	F w/cover	
PDS-11-UU-A*	1	200	(1) M6 x 15	(1) M6 x 15	-	Metric	Metric	1.00	3.00	2.42	-	2.25	-	NA
PDS-11-UU-1	1	200	(1) M6 x 15	(1) M6 x 15	-	Metric	Metric	1.00	3.00	2.42	-	2.25	2.57	-
PDS-11-UU-2	1	200	(1) M6 x 15	(1) M6 x 15	-	Metric	Metric	1.82	3.00	2.42	0.81	2.25	2.57	-
PDS-11-UU-3	1	200	(1) M6 x 15	(1) M6 x 15	-	Metric	Metric	2.55	3.00	2.42	1.62	2.25	2.57	-
PDS-11-CC-A*	1	200	(1) 1/4-20 x 9/16	(1) 1/4-20 x 9/16	-	Stud	Stud	1.00	3.00	2.42	-	2.25	-	NA
PDS-11-CC-1	1	200	(1) 1/4-20 x 9/16	(1) 1/4-20 x 9/16	-	Stud	Stud	1.00	3.00	2.42	-	2.25	2.57	-
PDS-11-CC-2	1	200	(1) 1/4-20 x 9/16	(1) 1/4-20 x 9/16	-	Stud	Stud	1.82	3.00	2.42	0.81	2.25	2.57	-
PDS-11-CC-3	1	200	(1) 1/4-20 x 9/16	(1) 1/4-20 x 9/16	-	Stud	Stud	2.55	3.00	2.42	1.62	2.25	2.57	-
PDS-11-SS-1	2	310	(1) M10 x 30	(1) M10 x 30	-	Metric	Metric	1.96	4.00	3.33	-	3.38	3.49	-
PDS-11-SS-2	2	310	(1) M10 x 30	(1) M10 x 30	-	Metric	Metric	3.66	4.00	3.33	1.70	3.38	3.49	-
PDS-11-SS-3	2	310	(1) M10 x 30	(1) M10 x 30	-	Metric	Metric	5.36	4.00	3.33	3.40	3.38	3.49	-
PDS-11-KK-1	2	310	(1) 3/8-16 x 1-3/16	(1) 3/8-16 x 1-3/16	-	Stud	Stud	1.96	4.00	3.33	-	3.38	3.49	-
PDS-11-KK-2	2	310	(1) 3/8-16 x 1-3/16	(1) 3/8-16 x 1-3/16	-	Stud	Stud	3.66	4.00	3.33	1.70	3.38	3.49	-
PDS-11-KK-3	2	310	(1) 3/8-16 x 1-3/16	(1) 3/8-16 x 1-3/16	-	Stud	Stud	5.36	4.00	3.33	3.40	3.38	3.49	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

For further details on conductor classes please refer to product data sheets

UL1059 terminal block standard file No. E84782 CSA certified CSA c22.2 No. 158, File number MC 249467 (wire classes B & C only)

* Cover not available for adder blocks

- Indicates that snap on cover is standard



TYPE PDM

Features

- Connector, high conductive aluminium, tin plated
- Brass, tin plated stud
- UL Recognized 75° C and CSA Certified
- Insulator base adders available
- Panel Mountable
- Rated for 600 volts

Benefits

- Rated for copper and aluminum conductor
- Intended for wires terminated with crimp lugs
- Ensures Reliability
- Easily snap together to create variable pole power blocks





Fig. 1




Fig. 2

F

Catalog Number	Fig. No.	Amps	Rated Conductor Range		Stud Ctr to Ctr	Line In	Line Out	MAX AIC	Dimensions						Cover ID
			Line	Load					A	B	C	D	E	F w/cover	
PDM-11-2/0F-1	1	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1-3/8	-	Lug	Stud	-	1.94	4.00	2.61	-	3.38	3.38	C-4-1
PDM-11-2/0F-2	1	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1-3/8	-	Lug	Stud	-	3.47	4.00	2.61	1.53	3.38	3.38	C-4-2
PDM-11-2/0F-3	1	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1-3/8	-	Lug	Stud	-	5.00	4.00	2.61	3.06	3.38	3.38	C-4-3
PDM-11-350J-1	1	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/8	-	Lug	Stud	65KA	1.94	4.00	2.61	-	3.38	3.38	C-4-1
PDM-11-350J-2	1	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/8	-	Lug	Stud	65KA	3.47	4.00	2.61	1.53	3.38	3.38	C-4-2
PDM-11-350J-3	1	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/8	-	Lug	Stud	65KA	5.00	4.00	2.61	3.06	3.38	3.38	C-4-3
PDM-12-500D-1	1	380	(1) 500 kcmil-#4 Awg	(2) 1/4-20 x 1-1/16	.750	Lug	Stud	-	2.29	4.75	2.90	-	4.13	4.13	C-5-1
PDM-12-500D-2	1	380	(1) 500 kcmil-#4 Awg	(2) 1/4-20 x 1-1/16	.750	Lug	Stud	-	4.17	4.75	2.90	1.88	4.13	4.13	C-5-2
PDM-12-500D-3	1	380	(1) 500 kcmil-#4 Awg	(2) 1/4-20 x 1-1/16	.750	Lug	Stud	-	6.05	4.75	2.90	3.76	4.13	4.13	C-5-3
PDM-11-500N-1	1	380	(1) 500 kcmil-#4 Awg	(1) 3/8-16 x 1-5/16	-	Lug	Stud	-	2.29	4.75	2.90	-	4.13	4.13	C-5-1
PDM-11-500N-2	1	380	(1) 500 kcmil-#4 Awg	(1) 3/8-16 x 1-5/16	-	Lug	Stud	-	4.17	4.75	2.90	1.88	4.13	4.13	C-5-2
PDM-11-500N-3	1	380	(1) 500 kcmil-#4 Awg	(1) 3/8-16 x 1-5/16	-	Lug	Stud	-	6.05	4.75	2.90	3.76	4.13	4.13	C-5-3
PDM-21-500Q-1	1	760	(2) 500 kcmil-#4 Awg	(1) 1/2-13 x 1-5/16	-	Lug	Stud	-	3.17	5.50	3.12	-	4.75	4.75	C-6-1
PDM-21-500Q-2	1	760	(2) 500 kcmil-#4 Awg	(1) 1/2-13 x 1-5/16	-	Lug	Stud	-	5.85	5.50	3.12	2.69	4.75	4.75	C-6-2
PDM-21-500Q-3	1	760	(2) 500 kcmil-#4 Awg	(1) 1/2-13 x 1-5/16	-	Lug	Stud	-	8.54	5.50	3.12	5.38	4.75	4.75	C-6-3
PDM-22-500N-1	1	760	(2) 500 kcmil-#4 Awg	(2) 3/8-16 x 1-5/16	1.160	Lug	Stud	-	3.17	5.50	3.12	-	4.75	4.75	C-6-1
PDM-22-500N-2	1	760	(2) 500 kcmil-#4 Awg	(2) 3/8-16 x 1-5/16	1.160	Lug	Stud	-	5.85	5.50	3.12	2.69	4.75	4.75	C-6-2
PDM-22-500N-3	1	760	(2) 500 kcmil-#4 Awg	(2) 3/8-16 x 1-5/16	1.160	Lug	Stud	-	8.54	5.50	3.12	5.38	4.75	4.75	C-6-3
PDM-11-2A-1	2	115	(1) #2-#14 Awg	(1) 10-32 x .60	-	Lug	Stud	-	0.83	2.29	1.53	-	2.07	2.07	C-2-1
PDM-11-2A-2	2	115	(1) #2-#14 Awg	(1) 10-32 x .60	-	Lug	Stud	-	1.46	2.29	1.53	-	2.07	2.07	C-2-2
PDM-11-2A-3	2	115	(1) #2-#14 Awg	(1) 10-32 x .60	-	Lug	Stud	-	2.10	2.29	1.53	1.27	2.07	2.07	C-2-3
PDM-11-2A-4	2	115	(1) #2-#14 Awg	(1) 10-32 x .60	-	Lug	Stud	-	2.75	2.29	1.53	1.93	2.07	2.07	C-2-4
PDM-11-2/0T-A**	2	175	(1) 2/0-#14 Awg	(1) M6 x 13	-	Lug	Metric	-	1.00	3.00	2.42	-	2.25	-	NA
PDM-11-2/0T-1‡	2	175	(1) 2/0-#14 Awg	(1) M6 x 13	-	Lug	Metric	-	1.00	3.00	2.42	-	2.25	2.57	-
PDM-11-2/0T-2‡	2	175	(1) 2/0-#14 Awg	(1) M6 x 13	-	Lug	Metric	-	1.82	3.00	2.42	0.81	2.25	2.57	-
PDM-11-2/0T-3‡	2	175	(1) 2/0-#14 Awg	(1) M6 x 13	-	Lug	Metric	-	2.55	3.00	2.42	1.63	2.25	2.57	-
PDM-11-2/0B-A*	2	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1/2	-	Lug	Stud	100KA	1.00	3.00	2.42	-	2.25	-	NA
PDM-11-2/0B-1	2	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1/2	-	Lug	Stud	100KA	1.00	3.00	2.42	-	2.25	2.57	-
PDM-11-2/0B-2	2	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1/2	-	Lug	Stud	100KA	1.82	3.00	2.42	0.81	2.25	2.57	-
PDM-11-2/0B-3	2	175	(1) 2/0-#14 Awg	(1) 1/4-20 x 1/2	-	Lug	Stud	100KA	2.55	3.00	2.42	1.63	2.25	2.57	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG) For further details on conductor classes please refer to product data sheets
 UL1059 terminal block standard file No. E84782 CSA certified CSA c22.2 No. 158, File number MC 249467 (wire classes B & C only)

* Cover not available for adder blocks

- Indicates that snap on cover is standard ‡ Steel Stud



TYPE PDM

Features

- Connector, high conductive aluminium, tin plated
- Brass, tin plated stud
- UL Recognized 75° C and CSA Certified
- Insulator base adders available
- Panel Mountable
- Rated for 600 volts

Benefits

- Rated for copper and aluminum conductor
- Intended for wires terminated with crimp lugs
- Ensures Reliability
- Easily snap together to create variable pole power blocks



Catalog Number	Amps	Rated Conductor Range		Stud Ctr to Ctr	Line In	Line Out	MAX AIC	Dimensions						Cover ID
		Line	Load					A	B	C	D	E	F w/cover	
PDM-11-350S-1	310	(1) 350 kcmil-#6 Awg	(1) M10 x 30	-	Lug	Metric	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-11-350S-2	310	(1) 350 kcmil-#6 Awg	(1) M10 x 30	-	Lug	Metric	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-11-350S-3	310	(1) 350 kcmil-#6 Awg	(1) M10 x 30	-	Lug	Metric	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-11-350M-1	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/4	-	Lug	Stud	65KA	1.96	4.00	3.33	-	3.38	3.49	-
PDM-11-350M-2	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/4	-	Lug	Stud	65KA	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-11-350M-3	310	(1) 350 kcmil-#6 Awg	(1) 3/8-16 x 1-1/4	-	Lug	Stud	65KA	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-18-S2-1	510	(1) M10 x 30	(8) #2-#14 Awg	-	Metric	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-18-S2-2	510	(1) M10 x 30	(8) #2-#14 Awg	-	Metric	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-18-S2-3	510	(1) M10 x 30	(8) #2-#14 Awg	-	Metric	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-112-S4-1	510	(1) M10 x 30	(12) #4-#14 Awg	-	Metric	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-112-S4-2	510	(1) M10 x 30	(12) #4-#14 Awg	-	Metric	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-112-S4-3	510	(1) M10 x 30	(12) #4-#14 Awg	-	Metric	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-14-S2/0-1	510	(1) M10 x 30	(4) 2/0-#14 Awg	-	Metric	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-14-S2/0-2	510	(1) M10 x 30	(4) 2/0-#14 Awg	-	Metric	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-14-S2/0-3	510	(1) M10 x 30	(4) 2/0-#14 Awg	-	Metric	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-18-K2-1	510	(1) 3/8-16 x 1-3/16	(8) #2-#14 Awg	-	Stud	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-18-K2-2	510	(1) 3/8-16 x 1-3/16	(8) #2-#14 Awg	-	Stud	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-18-K2-3	510	(1) 3/8-16 x 1-3/16	(8) #2-#14 Awg	-	Stud	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-112-K4-1	510	(1) 3/8-16 x 1-3/16	(12) #4-#14 Awg	-	Stud	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-112-K4-2	510	(1) 3/8-16 x 1-3/16	(12) #4-#14 Awg	-	Stud	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-112-K4-3	510	(1) 3/8-16 x 1-3/16	(12) #4-#14 Awg	-	Stud	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-
PDM-14-K2/0-1	510	(1) 3/8-16 x 1-3/16	(4) 2/0-#14 Awg	-	Stud	Lug	-	1.96	4.00	3.33	-	3.38	3.49	-
PDM-14-K2/0-2	510	(1) 3/8-16 x 1-3/16	(4) 2/0-#14 Awg	-	Stud	Lug	-	3.66	4.00	3.33	1.70	3.38	3.49	-
PDM-14-K2/0-3	510	(1) 3/8-16 x 1-3/16	(4) 2/0-#14 Awg	-	Stud	Lug	-	5.36	4.00	3.33	3.40	3.38	3.49	-

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

For further details on conductor classes please refer to product data sheets

UL1059 terminal block standard file No. E84782 CSA certified CSA c22.2 No. 158, File number MC 249467 (wire classes B & C only)

- Indicates that snap on cover is standard



TYPE

LDAU

LDBU

Features

- Modular design
- Easy to assemble
- UL listed 90° C 600 Volts
- Electro-tin plated 6061-T6 aluminum alloy
- Multiple conductor capability

Benefits

- Simplifies stocking. Combines any number of blocks with multiple conductor ranges into the specific configuration required for the job.
- Unique locking feature allows individual blocks to be combined quickly without special tools
- Ensures reliability
- Suitable for use with both copper and aluminum conductors in any combination
- Individual blocks supplied in a variety of configurations with one or two main cable ports and four, six, or twelve taps. All are range taking.



Fig. 1



Fig. 2




F

Catalog Number	Figure Number	Connector		Primary			Secondary			Ampere
		Primary	Secondary	Wire Range	Openings Per Pole	Hex Size	Wire Range	Openings Per Pole	Hex Size	Rating Per Pole
LDBU-112-350	1			350kcmil-6	1	3/8	4-14	12	Slot	310
LDAU-112-350	2			350kcmil-6	1	3/8	4-14	12	Slot	310
LDBU-112A-350	1			350kcmil-6	1	3/8	4-14	12	Slot	310
LDAU-112A-350	2			350kcmil-6	1	3/8	4-14	12	Slot	310
LDBU-16-350	1			350kcmil-6	1	3/8	2/0-14	6	3/16	310
LDAU-16-350	2			350kcmil-6	1	3/8	2/0-14	6	3/16	310
LDBU-16-500	1			500kcmil-4	1	3/8	2/0-14	6	3/16	380
LDAU-16-500	2			500kcmil-4	1	3/8	2/0-14	6	3/16	380
LDBU-26-350	1			350kcmil-6	2	3/8	2/0-14	6	3/16	620
LDAU-26-350	2			350kcmil-6	2	3/8	2/0-14	6	3/16	620
LDBU-212-4/0	1			4/0-6	2	1/4	4-14	12	Slot	460
LDAU-212-4/0	2			4/0-6	2	1/4	4-14	12	Slot	460
LDBU-212-500	1			500kcmil-4	2	3/8	4-14	12	Slot	760
LDAU-212-500	2			500kcmil-4	2	3/8	4-14	12	Slot	760
LDBU-26-500	1			500kcmil-4	2	3/8	2/0-14	6	3/16	760
LDAU-26-500	2			500kcmil-4	2	3/8	2/0-14	6	3/16	760
LDBU-24-500	1			500kcmil-4	2	3/8	4/0-6	4	5/16	760
LDAU-24-500	2			500kcmil-4	2	3/8	4/0-6	4	5/16	760
LDBU-11-500	1			500kcmil-4	1	3/8	500kcmil-4	1	3/8	380
LDAU-11-500	2			500kcmil-4	1	3/8	500kcmil-4	1	3/8	380
LDBU-22-350	1			350kcmil-6	2	3/8	350kcmil-6	2	3/8	620
LDAU-22-350	2			350kcmil-6	2	3/8	350kcmil-6	2	3/8	620
LDBU-22-500	1			500kcmil-4	2	3/8	500kcmil-4	2	3/8	760
LDAU-22-500	2			500kcmil-4	2	3/8	500kcmil-4	2	3/8	760

Side Panel can be ordered separately Cat. No. LDS-1

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 1953, UL File E112158



Dimensions

A	B	C	D=Dia.	E	F	G	H	J = Cover	K	L	M	N
3	5-1/2	3-7/16	.28 Slot	1-1/2	5/16	4-7/8	1/4	1/2	4.75	2.69	.38	1.50

TYPE PDBU

Features

- Lay-In primary cable ports
- Valox insulating base
- UL 1953 Listed for 600 volts
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy


Benefits

- Designed for feed through of two primary conductors and up to six taps with no need to break the main feeder cable
- Provides a high degree of impact resistance with superior insulating qualities
- Ensures reliability
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors



Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole			Primary	Secondary
	PDBU-26-750-1			750kcmil-250kcmil	2	250kcmil-6			6	950

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 1953, UL File E112158



Block Size	No. of Poles	Dimensions							
		A	B	C	D	E	F	G	H
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16

* Valox® is a registered trade name of the General Electric Company.



TYPE PDBU

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Valox* insulating base
- UL 1953 Listed 90° C 600 volts
- Electro-tin plated

Benefits

- Reliable use for copper conductor only
- Provides a high degree of impact resistance with superior insulating qualities
- Ensures reliability
- Provides low contact resistance



Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Block Size	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary


All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Valox® is a registered trade name of the General Electric Company.

A versatile tap hole, wire range 8-14 AWG included on the connector.

Tested to UL 1953, UL File E112158

F



Block Size	No. of Poles	Dimensions									
		A	B	C	D	E	F	G	H	J	K
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16	9/32	9/16

TYPE PDBU

Features

- Multiple taps
- Valox* insulating base
- UL 1953 Listed 90° C 600 Volts
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy
- Short Circuit Rating 10K RMS SYM Amps

Benefits

- Three different connector configurations provide a wide range of tapping capabilities for up to four primary conductors
- Provides a high degree of impact resistance with superior insulating qualities
- Ensures reliability
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors
- Added protection



Fig. 1











Fig. 2



Fig. 3




Fig. 4

Catalog Number	Figure Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number of Poles	Block Size	Hex Size	
		Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
PDBU-428-500-1	1			500kcmil-4	4	4-14	28	1520	1	W	3/8	Slot
PDBU-49-500-1	2			500kcmil-4	4	350kcmil-6 4/0-6	6 3	1520	1	W	3/8	3/8 5/16
PDBU-55-500-1	4			500kcmil-3/0	5	500kcmil-3/0	5	1600	1	W	3/8	3/8
PDBU-412-500-1	3			500kcmil-4	4	4/0-6	12	1520	1	W	3/8	5/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Valox® is a registered trade name of the General Electric Company.

° A versatile tap hole, wire range 8-14 AWG included on the connector.

Tested to UL 1953, UL File E112158



Block Size	No. of Poles	Dimensions									
		A	B	C	D	E	F	G	H	J	K
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16	9/32	9/16

TYPE

LDA

LDB

Features

- Modular design
- Easy to assemble
- UL Recognized 90° C 600 Volts and is CSA Certified
- Electro-tin plated 6061-T6 aluminum alloy
- Clear cover
- Multiple conductor capability

Benefits

- Simplifies stocking. Combines any number of blocks with multiple conductor ranges into the specific configuration required for the job.
- Unique locking feature allows individual blocks to be combined quickly without special tools
- Ensures reliability
- Suitable for use with both copper and aluminum conductors in any combination
- Permits visual inspection
- Individual blocks supplied in a variety of configurations with one or two main cable ports and four, six, or twelve taps. All are range taking.



Fig. 1






Fig. 2

F

Catalog Number	Figure Number	Connector		Primary			Secondary			Ampere
		Primary	Secondary	Wire Range	Openings Per Pole	Hex Size	Wire Range	Openings Per Pole	Hex Size	Rating Per Pole
LDB-112-350	1			350kcmil-6	1	3/8	4-14	12	Slot	310
LDA-112-350	2			350kcmil-6	1	3/8	4-14	12	Slot	310
LDB-112A-350	1			350kcmil-6	1	3/8	4-14	12	Slot	310
LDA-112A-350	2			350kcmil-6	1	3/8	4-14	12	Slot	310
LDB-16-350	1			350kcmil-6	1	3/8	2/0-14	6	3/16	310
LDA-16-350	2			350kcmil-6	1	3/8	2/0-14	6	3/16	310
LDB-16-500	1			500kcmil-4	1	3/8	2/0-14	6	3/16	380
LDA-16-500	2			500kcmil-4	1	3/8	2/0-14	6	3/16	380
LDB-26-350	1			350kcmil-6	2	3/8	2/0-14	6	3/16	620
LDA-26-350	2			350kcmil-6	2	3/8	2/0-14	6	3/16	620
LDB-212-4/0	1			4/0-6	2	1/4	4-14	12	Slot	460
LDA-212-4/0	2			4/0-6	2	1/4	4-14	12	Slot	460
LDB-212-500	1			500kcmil-4	2	3/8	4-14	12	Slot	760
LDA-212-500	2			500kcmil-4	2	3/8	4-14	12	Slot	760
LDB-26-500	1			500kcmil-4	2	3/8	2/0-14	6	3/16	760
LDA-26-500	2			500kcmil-4	2	3/8	2/0-14	6	3/16	760
LDB-24-500	1			500kcmil-4	2	3/8	4/0-6	4	5/16	760
LDA-24-500	2			500kcmil-4	2	3/8	4/0-6	4	5/16	760
LDB-11-500	1			500kcmil-4	1	3/8	500kcmil-4	1	3/8	380
LDA-11-500	2			500kcmil-4	1	3/8	500kcmil-4	1	3/8	380
LDB-22-350	1			350kcmil-6	2	3/8	350kcmil-6	2	3/8	620
LDA-22-350	2			350kcmil-6	2	3/8	350kcmil-6	2	3/8	620
LDB-22-500	1			500kcmil-4	2	3/8	500kcmil-4	2	3/8	760
LDA-22-500	2			500kcmil-4	2	3/8	500kcmil-4	2	3/8	760

Side Panel can be ordered separately Cat. No. LDS-1

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 1059, UL File E84782



Dimensions

A	B	C	D=Dia.	E	F	G	H	J = Cover	K	L	M	N
3	5-1/2	3-7/16	.28 Slot	1-1/2	5/16	4-7/8	1/4	1/2	4.75	2.69	.38	1.50

TYPE PDA PDC

Features

- Modular design
- Easy to assemble
- UL Recognized 90° C 600 Volts and is CSA Certified
- Electro-tin plated
- Lexan® insulating base
- Manufactured from high strength 6061-T6 aluminum alloy

Benefits

- Simplifies stocking. Combines any number of blocks with multiple conductor ranges into the specific configuration required for the job.
- Unique locking feature allows individual blocks to be combined quickly without special tools
- Ensures reliability
- Provides low contact resistance
- Provides a high degree of impact resistance with superior insulating qualities
- Suitable for use with either copper or aluminum conductors



Fig. 1



Fig. 2



Fig. 3



Fig. 4


Catalog Number	Figure Number	Connector		Primary		Secondary		Rating Per Pole	Ampere of Poles	No. Hex Size	
		Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole			Primary	Secondary
PDC-14-2/0-1	1			2/0-14	1	4-14	4	175	1	3/16	Slot
PDA-14-2/0-1	2			2/0-14	1	4-14	4	175	Adder	3/16	Slot
PDC-11-2/0-1	3			2/0-14	1	2/0-14	1	175	1	3/16	3/16
PDA-11-2/0-1	4			2/0-14	1	2/0-14	1	175	Adder	3/16	3/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Covers available 1-10 Poles. Specify length.

*Lexan is a registered trademark of SABIC INNOVATIVE PLASTICS HOLDINGS BV.

Tested to UL 1059, UL File E84782



Block Size	No. of Poles	Dimensions						
		A	B	C	D	E	F	G
S	1	1.05	1.94	2.88	2.25	.31	.53	.80
S	2	1.85	1.94	2.88	2.25	.31	.53	.80

"A" Dimension increases by .80 per additional pole.

TYPE PDB

Features

- Range taking
- Valox* insulating base
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy
- UL Recognized rated 90° C and is CSA Certified, rated for 600 volts

Benefits

- Provides great flexibility in using the connector as an in line splice or to reduce conductor size
- Provides a high degree of impact resistance with superior insulating qualities
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors
- Ensures reliability



F

Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Block Size	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
PDB-16-2/0-1			2/0-12	1	4-14	6	175	1	M	3/16	Slot
PDB-16-2/0-2			2/0-12	1	4-14	6	175	2	M	3/16	Slot
PDB-16-2/0-3			2/0-12	1	4-14	6	175	3	M	3/16	Slot
PDB-26-2/0-1			2/0-12	2	2-14	6	350	1	M	3/16	Slot
PDB-26-2/0-2			2/0-12	2	2-14	6	350	2	M	3/16	Slot
PDB-26-2/0-3			2/0-12	2	2-14	6	350	3	M	3/16	Slot
PDB-112-350-1			350kcmil-6	1	4-14	12	310	1	L	3/8	Slot
PDB-112-350-2			350kcmil-6	1	4-14	12	310	2	L	3/8	Slot
PDB-112-350-3			350kcmil-6	1	4-14	12	310	3	L	3/8	Slot
PDB-112A-350-1			350kcmil-6	1	4-14	12	310	1	M	3/8	Slot
PDB-112A-350-2			350kcmil-6	1	4-14	12	310	2	M	3/8	Slot
PDB-112A-350-3			350kcmil-6	1	4-14	12	310	3	M	3/8	Slot
PDB-14-500-1			500kcmil-4	1	2/0-14	4	380	1	M	3/8	3/16
PDB-14-500-2			500kcmil-4	1	2/0-14	4	380	2	M	3/8	3/16
PDB-14-500-3			500kcmil-4	1	2/0-14	4	380	3	M	3/8	3/16
PDB-16-350-1			350kcmil-6	1	2/0-14	6	310	1	L	3/8	3/16
PDB-16-350-2			350kcmil-6	1	2/0-14	6	310	2	L	3/8	3/16
PDB-16-350-3			350kcmil-6	1	2/0-14	6	310	3	L	3/8	3/16
PDB-162-500-1			500kcmil-4	1	2-14	6	380	1	M	3/8	Slot
PDB-162-500-2			500kcmil-4	1	2-14	6	380	2	M	3/8	Slot
PDB-162-500-3			500kcmil-4	1	2-14	6	380	3	M	3/8	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Valox* is a registered trade name of the General Electric Company.

Tested to UL 1059, UL File E84782




Fig. 1




Fig. 2




Fig. 3

Dimensions

Block Size	Number Of Poles	Figure Number	A	B	C	D	E	F	G	H	J	K
M	1	1	1-27/32	4	2-5/8	31/32	-	5/16	3-3/8	3/8	13/64	13/32
M	2	2	3-13/32	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
M	3	3	5	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
L	1	1	3	5-1/2	3-1/2	1-1/2	-	3/8	4-3/4	7/16	9/32	1/2
L	2	2	5-11/16	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2
L	3	3	8-3/8	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2

TYPE PDB

Features

- Range taking
- Valox* insulating base
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy
- UL Recognized rated 90° C and is CSA Certified, rated for 600 volts

Benefits

- Provides great flexibility in using the connector as an in line splice or to reduce conductor size
- Provides a high degree of impact resistance with superior insulating qualities
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors
- Ensures reliability



Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Block Size	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
PDB-212-4/0-1			4/0-6	2	4-14	12	460	1	M	3/8	Slot
PDB-212-4/0-2			4/0-6	2	4-14	12	460	2	M	3/8	Slot
PDB-212-4/0-3			4/0-6	2	4-14	12	460	3	M	3/8	Slot
PDB-26-350-1			350kcmil-6	2	2/0-14	6	620	1	L	3/8	3/16
PDB-26-350-2			350kcmil-6	2	2/0-14	6	620	2	L	3/8	3/16
PDB-26-350-3			350kcmil-6	2	2/0-14	6	620	3	L	3/8	3/16
PDB-16-500-1			500kcmil-4	1	2/0-14	6	380	1	L	3/8	3/16
PDB-16-500-2			500kcmil-4	1	2/0-14	6	380	2	L	3/8	3/16
PDB-16-500-3			500kcmil-4	1	2/0-14	6	380	3	L	3/8	3/16
PDB-212-500-1			500kcmil-4	2	4-14	12	760	1	L	3/8	Slot
PDB-212-500-2			500kcmil-4	2	4-14	12	760	2	L	3/8	Slot
PDB-212-500-3			500kcmil-4	2	4-14	12	760	3	L	3/8	Slot
PDB-24-500-1			500kcmil-4	2	4/0-6	4	760	1	L	3/8	5/16
PDB-24-500-2			500kcmil-4	2	4/0-6	4	760	2	L	3/8	5/16
PDB-24-500-3			500kcmil-4	2	4/0-6	4	760	3	L	3/8	5/16
PDB-26-500-1			500kcmil-4	2	2/0-14	6	760	1	L	3/8	3/16
PDB-26-500-2			500kcmil-4	2	2/0-14	6	760	2	L	3/8	3/16
PDB-26-500-3			500kcmil-4	2	2/0-14	6	760	3	L	3/8	3/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 * Valox® is a registered trade name of the General Electric Company.

Tested to UL 1059, UL File E84782




Fig. 1




Fig. 2




Fig. 3

Dimensions

Block Size	Number Of Poles	Figure Number	A	B	C	D	E	F	G	H	J	K
M	1	1	1-27/32	4	2-5/8	31/32	-	5/16	3-3/8	3/8	13/64	13/32
M	2	2	3-13/32	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
M	3	3	5	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
L	1	1	3	5-1/2	3-1/2	1-1/2	-	3/8	4-3/4	7/16	9/32	1/2
L	2	2	5-11/16	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2
L	3	3	8-3/8	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2

TYPE PDB

Features

- Multiple taps
- Range taking
- Valox* insulating base
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy
- UL Recognized rated 90° C and is CSA Certified, rated for 600 volts

Benefits

- Depending on product selected, up to twelve taps can be taken from one or two mains
- Provides tapping flexibility over a broad wire range
- Provides a high degree of impact resistance with superior insulating qualities
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors
- Ensures reliability






F

Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Block Size	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
PDB-11-2/0-1			2/0-14	1	2/0-14	1	175	1	M	3/16	3/16
PDB-11-2/0-2			2/0-14	1	2/0-14	1	175	2	M		
PDB-11-2/0-3			2/0-14	1	2/0-14	1	175	3	M		
PDB-11-350-1			350kcmil-6	1	350kcmil-6	1	310	1	M	3/8	3/8
PDB-11-350-2			350kcmil-6	1	350kcmil-6	1	310	2	M		
PDB-11-350-3			350kcmil-6	1	350kcmil-6	1	310	3	M		
PDB-11-500-1			500kcmil-4	1	500kcmil-4	1	380	1	L	3/8	3/8
PDB-11-500-2			500kcmil-4	1	500kcmil-4	1	380	2	L		
PDB-11-500-3			500kcmil-4	1	500kcmil-4	1	380	3	L		
PDB-22-2/0-1			2/0-14	2	2/0-14	2	350	1	M	3/16	3/16
PDB-22-2/0-2			2/0-14	2	2/0-14	2	350	2	M		
PDB-22-2/0-3			2/0-14	2	2/0-14	2	350	3	M		
PDB-22-350-1			350kcmil-6	2	350kcmil-6	2	620	1	L	3/8	3/8
PDB-22-350-2			350kcmil-6	2	350kcmil-6	2	620	2	L		
PDB-22-350-3			350kcmil-6	2	350kcmil-6	2	620	3	L		
PDB-22-500-1			500kcmil-4	2	500kcmil-4	2	760	1	L	3/8	3/8
PDB-22-500-2			500kcmil-4	2	500kcmil-4	2	760	2	L		
PDB-22-500-3			500kcmil-4	2	500kcmil-4	2	760	3	L		

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Valox® is a registered trade name of the General Electric Company.

Tested to UL 1059, UL File E84782



Dimensions

Block Size	Number Of Poles	Figure Number	A	B	C	D	E	F	G	H	J	K
M	1	1	1-27/32	4	2-5/8	31/32	-	5/16	3-3/8	3/8	13/64	13/32
M	2	2	3-13/32	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
M	3	3	5	4	2-5/8	31/32	1-17/32	5/16	3-3/8	3/8	13/64	13/32
L	1	1	3	5-1/2	3-1/2	1-1/2	-	3/8	4-3/4	7/16	9/32	1/2
L	2	2	5-11/16	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2
L	3	3	8-3/8	5-1/2	3-1/2	1-1/2	2-11/16	3/8	4-3/4	7/16	9/32	1/2

TYPE PDB

Features

- Lay-In primary cable ports
- Valox insulating base
- Clear cover
- UL 1059 Recognized and CSA Certified for 600 volts
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy


Benefits

- Designed for feed through of two primary conductors and up to six taps with no need to break the main feeder cable
- Provides a high degree of impact resistance with superior insulating qualities
- Permits visual inspection
- Ensures reliability
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors



Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole			Primary	Secondary
	PDB-26-750-1			750kcmil-250kcmil	2	250kcmil-6			6	950

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 1059, UL File E84782



Block Size	No. of Poles	Dimensions							
		A	B	C	D	E	F	G	H
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16

* Valox® is a registered trade name of the General Electric Company.



TYPE PDB

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Valox* insulating base
- UL 1059 Recognized 90° C 600 volts
- Electro-tin plated
- Clear cover

Benefits


- Reliable use for copper conductor only
- Provides a high degree of impact resistance with superior insulating qualities
- Ensures reliability
- Provides low contact resistance
- Provides visual inspection



Catalog Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number Of Poles	Block Size	Hex Size	
	Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
										Primary	Secondary
PDB-55-600-1			600kcmil-250kcmil	5	600kcmil-250kcmil	5	1900	1	W	3/8	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 Valox® is a registered trade name of the General Electric Company.
 A versatile tap hole, wire range 8-14 AWG included on the connector.
 Tested to UL 1059, UL File E84782

F



Block Size	No. of Poles	Dimensions									
		A	B	C	D	E	F	G	H	J	K
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16	9/32	9/16

TYPE PDB

Features

- Multiple taps
- Valox* insulating base
- Clear cover
- UL 1059 Recognized 90° C 600 Volts and is CSA Certified
- Electro-tin plated
- Manufactured from high strength 6061-T6 aluminum alloy

Benefits

- Three different connector configurations provide a wide range of tapping capabilities for up to four primary conductors
- Provides a high degree of impact resistance with superior insulating qualities
- Permits visual inspection
- Ensures reliability
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors



Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Connector		Primary		Secondary		Ampere Rating Per Pole	Number of Poles	Block Size	Hex Size	
		Primary	Secondary	Wire Range	Openings Per Pole	Wire Range	Openings Per Pole				Primary	Secondary
PDB-428-500-1	1			500kcmil-4	4	4-14	28	1520	1	W	3/8	Slot
PDB-49-500-1	2			500kcmil-4	4	350kcmil-6 4/0-6	6 3	1520	1	W	3/8	3/8 5/16
‡ PDB-55-500-1	4			500kcmil-3/0	5	500kcmil-3/0	5	1600	1	W	3/8	3/8
PDB-412-500-1	3			500kcmil-4	4	4/0-6	12	1520	1	W	3/8	5/16


All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Valox® is a registered trade name of the General Electric Company.

































° A versatile tap hole, wire range 8-14 AWG included on the connector.

‡ Not CSA Certified


Tested to UL 1059, UL File E84782



Block Size	No. of Poles	Dimensions									
		A	B	C	D	E	F	G	H	J	K
W	1	6-7/32	4	4-3/8	1-19/32	3	3/8	3-1/4	7/16	9/32	9/16

GGA  256	GGC  257	ULT  258	 Bronze Ground Clamps Type BGDB  ClearGround® Intersystem Ground Tap Type GBT			
ELT  259	CGRC  260	BGRC  261				
SRC  262	GRC  263	RLT  264				
DCGC  265	BGC  266	BGC  267				
BGDB  268	BGCS  269	SPS  270 - 271				
SPD  272 - 273	TTGC  274	GUB  275				
GS/GSR  277	D167  278	CAN, N-174  279	AGC  280	SGC  280	SGB  281	
GBL  282	CGBL  283	GBT  284	GRM  285	GRF  285	NB  286	

- **Pure wrought copper extrusions prevent corrosion due to dissimilar metals, have the same conductivity as copper conductors, and are pre-filled with inhibiting compound**



1 ULT

Compression Line Tap/C-Crimp

Applications: Tap Connector, Lap Splice Connector
 Conductor Range: #6 solid – 4/0



2 GGC

Compression Ground Tap Connector

Applications: Tap Connector, Lap Splice Connector
 Conductor Range: #6 solid – 500kcmil
 Copper Ground Rods: 1/2", 5/8", 3/4"



3 GGA

Compression Ground Grid Cross Connector

Compression elements can be rotated or adjusted prior to installation
 Applications: Cross Connector, Ground Rod Connector
 Conductor Range: #6 solid – 500kcmil
 Copper Ground Rods: 1/2", 5/8", 3/4"




TYPE GGA

Features

- Manufactured from high strength copper alloy
- Clearly marked with wire size and die index
- Range taking
- Connector can be adjusted prior to installation
- Non-hazardous installation
- Prefilled with inhibiting compound
- Temperature Rating 90° C

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion. Suitable for direct burial.
- Provides easy identification and tooling recommendation
- Reduces inventory. Six sizes cover a wire range from 500kcmil to #6, and 1/2" to 3/4" ground rods.
- Permits adjustments to be made for misaligned cross grids
- Can be installed in all types of weather with no need for protective equipment or clothing. Does not produce heat or dangerous particles.
- Prevents oxides from forming
- Ensures reliability



Catalog Number	Wire Range				Dimensions						Die Index Number	
	Cable to Cable		Cable to Ground Rod		A	B	C	D	E	F	Side A	Side B
	Side A	Side B	Side A	Side B								
GGA-1	2str-6sol	2str-6sol	-	-	.75	.75	1.09	1.09	.313	2.50	0	0
GGA-2	250kcmil-1str	2str-6sol	1/2 - 5/8 Rod	2str-6sol	.75	.75	1.66	1.09	.313	2.50	997	0
GGA-3	250kcmil-2str	250kcmil-2str	1/2 - 5/8 Rod	250kcmil-2str	.75	.75	1.66	1.66	.500	2.50	997	997
GGA-4	500kcmil-250kcmil	2str-6sol	1/2 - 5/8 Rod	2str-6sol	.75	.75	2.09	1.09	.313	2.50	998	0
GGA-5	500kcmil-250kcmil	250kcmil-2str	5/8 - 3/4 Rod	250kcmil-2str	.75	.75	2.09	1.66	.500	2.50	998	997
GGA-6	500kcmil-250kcmil	500kcmil-250kcmil	5/8 - 3/4 Rod	500kcmil-250kcmil	.75	.75	2.28	2.28	.750	2.50	999/1011	999/1011

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 467, UL File E34440

The GGA Series compression ground grid cross connector can be used to connect a copper ground grid system together or to connect a copper ground grid system to a copper clad ground rod. The GGA Series of compression connectors allow adjustment of each side of the connector prior to installation. The GGA Series of compression connectors are pre-filled with inhibiting compound and are suitable for direct burial.

Notes:

1. ILSCO ILC-12 or ILC-15 Series Tools and ILD Series Dies may be used. Note: Adapter required when using ILC-15 Series Tool. Burndy tools and dies may also be used.
2. When used with ground rods, it is recommended to rough up the end of ground rod where GGA is to be placed. This provides good rotational resistance. Perform a "pre-crimp" on ground rod prior to installing GGA connector. Use an indent type of die such as Burndy's U2CABT (Die Index #348) or UPRECRIMP-12, -58, -34.*
3. Each side of the GGA Series may be rotated around the rod to any desired position before crimping.

* "UPRECRIMP" and "U2CABT" are registered trademarks TM of Burndy/FCI

ILSCO Grounding Grid Connectors

RoHS
Compliant

UL
LISTED
667P

SF
LR-5465


TYPE GGC

Features

- Manufactured from high strength copper alloy
- Clearly marked with wire size and die index
- Range taking
- Versatile
- Non-hazardous installation
- Prefilled with inhibiting compound
- Temperature Rating 90° C

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion. Suitable for direct burial.
- Provides easy identification and tooling recommendation
- Reduces inventory. Eight sizes cover a wire range from 500kcmil to #6, and 1/2" to 3/4" ground rods.
- Can be used as a tap connector or as a lap splice connector
- Can be installed in all types of weather with no need for protective equipment or clothing. Does not produce heat or dangerous particles.
- Prevents oxides from forming
- Ensures reliability



Catalog Number	Wire Range		Main Ground Rod	Dimensions			Die Index Index
	Main	Tap		A	B	C	
GGC-1	2str-6sol	2str-6sol	-	1.4	.75	.33	0
GGC-2	250kcmil-1/0str 1/2 - 5/8 Rod	2str-4sol	1/2 - 5/8	2.1	.75	.33	997
GGC-3	250kcmil-1/0str 1/2 - 5/8 Rod	2/0str-1/0str	1/2 - 5/8	2.1	.75	.44	997
GGC-4	250kcmil-1/0str 1/2 - 5/8 Rod	250kcmil-3/0str	1/2 - 5/8	2.1	.75	.61	997
GGC-5	500kcmil-250kcmil 5/8 - 3/4 Rod	2str-4sol	5/8 - 3/4	2.6	.75	.33	998
GGC-6	500kcmil-250kcmil 5/8 - 3/4 Rod	2/0str-1/0str	5/8 - 3/4	2.6	.75	.44	998
GGC-7	500kcmil-250kcmil 5/8 - 3/4 Rod	250kcmil-3/0str	5/8 - 3/4	2.6	.75	.61	998
GGC-8	500kcmil-250kcmil 5/8 - 3/4 Rod	500kcmil-350kcmil	5/8 - 3/4	2.9	.75	.84	999/1011

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 467, UL File E34440

NOTE: Hydraulic tools required on all sizes except GGC-1
Dieless tools can not be used

The GGC Series compression ground tap connector can be used as a tap connector to connect copper ground wire to a copper clad ground rod or as a lap splice connector splicing copper conductors together. The GGC Series of compression connectors are pre-filled with inhibiting compound and are suitable for direct burial.

Notes:

1. ILSCO ILC-12 or ILC-15 Series Tools and ILD Series Dies may be used. Note: Adapter required when using ILC-15 Series Tool. Burndy tools and dies may also be used.
2. When used with ground rods, it is recommended to rough up the end of ground rod where GGC is to be placed. This provides good rotational resistance. Perform a "pre-crimp" on ground rod prior to installing GGC connector. Use an indent type of die such as Burndy's U2CABT (Die Index #348) or UPRECRIMP-12, -58, -34.*
3. When using #6 AWG solid wire in the tap side, fold conductor double prior to crimping.
4. When using GGC-4, if 3/0 conductor is used in the tap side, use a minimum of 2/0 conductor in the run side.

* "UPRECRIMP" and "U2CABT" are registered trademarks TM of Burndy/FCI



4730 Madison Road, Cincinnati, Ohio 45227-1426 Phone 513 533-6200 Fax 513 871-4084 Web site www.ilsco.com
Canada 1050 Lakeshore Road East, Mississauga, Ontario, Canada L5E1E4 Phone 905 274-2341 Fax 905 274-8763

G


TYPE ULT

Features

- Manufactured from high strength copper alloy
- Clearly marked with wire size and die index
- Range taking
- Suitable for use in circuits rate 35KV or less (Refer to UL486A - UL486B); proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion
- Provides easy identification and tooling recommendation
- Reduces inventory
- Application versatility



Catalog Number	Copper Wire Range		Die Index	Dimensions		
	Main	Tap		L	W	H
ULT-4-Z	4str-6sol	6str-6sol	BG or 5/8	3/4	15/32	49/64
ULT-5-Z	4str-6sol	4str-4sol	BG or 5/8	3/4	15/32	27/32
ULT-6-Z	2str-2sol	4str-8sol	C	7/8	5/8	1
ULT-7-Z	2str-2sol	2str-2sol	C	7/8	39/64	1-1/16
ULT-12-Z	4/0str-3/0str	4/0str-3/0str	F or D3	1-1/8	1	1-5/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

TYPE ELT

Features

- Manufactured from copper alloy
- Clearly marked with wire size and die index
- Range taking
- UL Listed and CSA Certified for grounding and bonding
- May be used in ground grid applications

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion. Suitable for direct burial in earth or concrete
- Provides easy identification and tooling recommendation
- Reduces inventory
- Ensures reliability
- Flexibility in application



Catalog Number	Copper Wire Range		Width	Die Index
	Main	Tap		
ELT-1	2str-6sol	2str-6sol	.75	C (U Type)
ELT-4	2/0str-1str	2str-6str	.75	0 (U Type)
ELT-2	2/0str-1str	2/0str-1str	.75	0 (U Type)
ELT-5	250kcmil-3/0str	2/0str-6sol	.75	997 (U Type)
ELT-3	250kcmil-3/0str	250kcmil-3/0str	.900	997 (U Type)
ELT-6	500kcmil-300kcmil	250kcmil-3/0str	.875	1011 (U Type)

Tooling Information

Catalog Number	ILSCO			Burndy		
	ILC-12H-N ILC-12-N Die No. No. of Crimps	ILCB-12-N Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	Y-35 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps
ELT-1	ILD-C (1)	ILD-C (1)	- -	C (U Type) (1)	C (U Type) (1)	C (U Type) (1)
ELT-4	ILD-O (1)	ILD-O (1)	- -	O (U Type) (1)	O (U Type) (1)	O (U Type) (1)
ELT-2	ILD-O (1)	ILD-O (1)	- -	O (U Type) (1)	O (U Type) (1)	O (U Type) (1)
ELT-5	ILD-U997 (1)	ILD-U997 (1)	- -	997 (U Type) (1)	997 (U Type) (1)	997 (U Type) (1)
ELT-3	ILD-U997 (1)	ILD-U997 (1)	- -	997 (U Type) (1)	997 (U Type) (1)	997 (U Type) (1)
ELT-6	- -	- -	ILD-P1011 (2)	- -	1011 (U Type) (2)	1011 (U Type) (1)

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 467, UL File E34440


TYPE CGRC

Features

- Manufactured from cast bronze
- Supplied with stainless steel hardware
- Suitable for grounding and bonding in applications such as swimming pools and spas
- Copper conductor only

Benefits

- Ensures maximum strength and durability
- Suitable for direct burial in earth or concrete



Catalog Number	Ground Rod Size	Rebar Size	Ground Rod Wire Range	Rebar Wire Range	Dimensions		
					L	W	H
CGRC-38 +	3/8	#3	4-10	4-10	1/2	11/16	1
CGRC-48	1/2	#4	2-10	2-10	9/16	27/32	1-3/16
CGRC-58	5/8	#5	2-10	4-10	9/16	15/16	1-9/32
CGRC-68	3/4	#6	2-10	4-10	9/16	1-1/16	1-9/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Plain copper finish.

+ Not UL Listed or CSA Certified

Tested to UL 467, UL File E34440

ILSCO Cast Bronze Ground Rod Clamps

RoHS
Compliant

UL
LISTED
667P

SA
LR-29601


TYPE BGRC

Features

- Manufactured from cast bronze
- Supplied with stainless steel hardware
- Copper conductor only

Benefits

- Ensures maximum strength and durability
- Suitable for direct burial in earth or concrete



Catalog Number	Ground Rod Size	Rebar Size	Ground Rod Wire Range	Rebar Wire Range	Dimensions		
					L	W	H
BGRC-48	1/2	-	2-10	-	7/8	3/4	1-1/4
BGRC-58	5/8	#5	1/0-8	1/0-8	1-1/32	29/32	1-13/32
BGRC-68	3/4	-	1/0-8	-	1	1	1-5/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 467, UL File E34440

G



ILSCO Cast Bronze Ground Rod Clamp

RoHS
Compliant

UL
LISTED
8M24

TYPE
SRC

Features

- Manufactured from bronze alloy
- Stainless steel bolt
- UL Listed for both copper clad and galvanized ground rods
- Range taking

Benefits

- Provides maximum strength and superior conductivity
- For direct burial
- Ensures reliability
- Reduces inventory requirement



Catalog Number	Ground Rod Size	Ground Rod Wire Range	Dimensions		
			L	W	H
SRC-1/0	3/8, 1/2, 5/8 3/4	10 sol - 1/0 str 8 sol - 1/0 str	13/16	1	1-1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E198108

G



ILSCO Ground Rod Clamps




TYPE GRC

Features

- Manufactured from seamless bronze tubing
- Supplied with silicon bronze screw
- Suitable for grounding and bonding in applications such as swimming pools and spas
- Copper conductor only

Benefits

- Provides maximum strength and superior conductivity
- Ground rod clamp is suitable for direct burial in earth or concrete



Catalog Number	Ground Rod Size	Ground Wire Range	Rebar Size	Rebar Wire Range	Dimensions	
					L	W
GRC-38	3/8	4-10	#3	4-10	5/8	5/8
GRC-58+	5/8	2-8	-	-	15/16	7/8
GRC-68	3/4, 5/8	2-8 for 3/4 rod, 1/0-8 for 5/8 rod	#5	1/0-8	1	1
GRC-75*	3/4	3/0-8	-	-	3/4	1-5/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 Plain copper finish.
 + RUS Listed.
 * Not UL Listed
 Tested to UL 467, UL File E34440




TYPE RLT

Features

- Prefilled with oxide inhibitor and bagged
- Clearly marked with wire size and die index
- UL Listed and CSA Certified for direct burial in earth or concrete
- Range taking
- Manufactured from high strength copper alloy

Benefits

- Prevents oxides from forming
- Provides easy identification and tooling recommendation
- Ensures reliability
- Reduces inventory. Eight sizes cover a wire range of 500kcmil -#2
- Provides maximum conductivity and eliminates the possibility of corrosion



Catalog Number	Ground Rod Size	Wire Range	Die Index	Dimensions	
				H	L
RLT-2	1/2	2 (.292 Dia.) - 2/0 (.419 Dia.)	998/1011	1.94	.88
RLT-3	5/8	2 (.292 Dia.) - 2/0 (.419 Dia.)	998/1011	1.97	.88
RLT-4	3/4	2 (.292 Dia.) - 2/0 (.419 Dia.)	998/1011	2.19	.88
RLT-5	1/2	4/0 (.528 Dia.) - 250kcmil (.575 Dia.)	998/1011	1.94	.88
RLT-6	5/8	4/0 (.528 Dia.) - 250kcmil (.575 Dia.)	998/1011	2.14	.88
RLT-7	3/4	4/0 (.528 Dia.) - 250kcmil (.575 Dia.)	998/1011	2.19	.88
RLT-8	5/8	300kcmil (.630 Dia.) - 500kcmil (.813 Dia.)	998/1011	2.14	.88
RLT-9	3/4	300kcmil (.630 Dia.) - 500kcmil (.813 Dia.)	998/1011	2.44	.88

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587

ILSCO Die Cast Ground Clamp

RoHS
Compliant

UL
LISTED
8M24


TYPE DCGC

Features

- Manufactured from die cast zinc alloy
- Assembled with zinc plated steel hardware
- Copper conductor only

Benefits

- Provides maximum durability while providing economy
- Provides corrosion resistance



Catalog Number	Conduit Size	Ground Wire Range	L	W	H
DCGC-1	1/2, 3/4, 1	2-8	2-13/64	1-3/8	1-1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587

G



ILSCO Cast Brass Ground Clamp




TYPE BGC

Features

- Manufactured from cast brass
- Type BGC-DB supplied with stainless steel or silicon bronze hardware
- Copper conductor only

Benefits

- Provides maximum conductivity and strength
- BGC-1DB and BGC-2DB are suitable for direct burial in earth or concrete. Can be used to ground swimming pools and spas.



Catalog Number	Pipe Size	Ground Wire Range	Dimensions		
			L	W	H
BGC-1	1/2, 3/4, 1	2-10	2-9/32	1-7/16	1-1/2
BGC-2	1-1/4, 1-1/2, 2	2-10	3-9/16	2-1/4	2
BGC-1DB*	1/2, 3/4, 1	2-10	2-9/32	1-7/16	1-1/2
BGC-2DB*	1-1/4, 1-1/2, 2	2-10	3-8/16	2-1/4	2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Suitable for direct burial in earth or concrete.

UL File E158587

ILSCO Cast Bronze Ground Clamps




TYPE BGC

Features

- Manufactured from cast bronze
- Versatile
- Copper conductor only

Benefits

- Provides maximum conductivity and strength
- Type BGC supplied with conduit hub for 1/2"-1" rigid conduit; type BGC-A can be used for bare or armoured cable



Catalog Number	Figure Number	Pipe Size	Conduit Hub Size	Wire Range	Dimensions		
					H	W	L
BGC1-50	1	1/2-1	1/2	4str-8sol	1-1/2	1-1/32	2-1/4
BGC1-75	1	1/2-1	3/4	4str-8sol	1-1/2	1-1/32	2-1/4
BGC1-10	1	1/2-1	1	4str-8sol	1-1/2	1-1/32	2-1/4
BGC2-50	1	1-1/4-2	1/2	4str-8sol	2	1-3/4	3-19/32
BGC2-75	1	1-1/4-2	3/4	4str-8sol	2	1-3/4	3-19/32
BGC2-10	1	1-1/4-2	1	4str-8sol	2	1-3/4	3-19/32
BGC-1A*	2	1/2-1	-	4str-8sol	1-1/2	1-3/8	2-1/4
BGC-2A	2	1-1/4-2	-	4str-8sol	2	2-3/32	3-19/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 * CSA Certified
 UL File E158587



ILSCO Cast Bronze Ground Clamps




TYPE BGDB

Features

- Manufactured from bronze alloy
- UL Listed for direct burial in earth or concrete
- Lay-In feature

Benefits

- Ensures maximum strength and superior conductivity
- Ensures reliability
- Reduces installation time



Catalog Number	Figure Number	Pipe Size	Rebar Size	Ground Rod Size	Ground Wire Range	Screw Material	Dimensions	
							L	W
BGC-2T-DB*	1	1/2-1	3/8-1	1/2-1	2str-10sol	silicon bronze	2-3/4	2-1/4
BGC-2P-DB*	2	1/2-1	3/8-1	1/2-1	2str-10sol	silicon bronze	2-3/4	2-1/4
BGC-2PS-DB+	3	1/2-1	3/8-1	1/4-1	2str-10sol 2 #8sol	stainless steel	2-1/4	2-1/4
BGC-4/0P-DB=##	4	1/2-1	3/8-1	1/2-1	4/0-8str	stainless steel	3	2-1/4
BGC-4/0S-DB=##	5	1/2-1	3/8-1	1/2-1	4/0-8str	stainless steel	2-3/4	2-1/4

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* UL File E207816

+ UL File E198108

= UL File E178441

Not RoHS compliant

G



ILSCO Ground Clamp with Strap

RoHS
Compliant

UL
LISTED
8M24



TYPE BGCS

Features

- UL Listed and CSA Certified
 - Conduit hub for 1/2" thru 1" rigid conduit
 - Zinc plated screws
 - ETP copper strap
- For copper conductor only

Benefits

- Ensures reliability
- Range taking
- Corrosion resistance
- Protects conduit system from vibrations and provides maximum conductivity



Fig. 1

Fig. 2

Fig. 3

Fig. 4

Catalog Number	Figure Number	Water Pipe Range	Conduit Hub Size	Ground Wire Range
CH-1	1	-	1	3/0 AWG - 10sol
CH-34	1	-	3/4	2/0 AWG - 10sol
J2124	2	2-1/2-4	-	4str - 10sol
J6	2	4-1/2-6	-	4str - 10sol
BGC-1-50S	3	1/2-1	1/2	8sol - 4str
BGC-1-75S	3	1/2-1	3/4	8sol - 4str
BGC-1-10S	3	1/2-1	1	8sol - 4str
BGC-1-50SH	4	1/2-1	1/2	2/0 - 10
BGC-1-75SH	4	1/2-1	3/4	2/0 - 10
BGC-1-10SH	4	1/2-1	1	2/0 - 10

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E207816

G




TYPE SPS

Features

- Range taking
- Re-usable
- UL 486A/B and UL 467 Listed
- For grounding of steel structures, fence posts and tapping cables from bus bar
- For copper to copper connections

Benefits

- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Ensures reliability
- Flexibility in the field



Catalog Number	Conductor Range AWG MM ²				Maximum Diameter Range	Stud Size	Dimensions				
	Stranded		Solid				A	B	C	D	E
	Max.	Min.	Max.	Min.							
SPSS-0	8	12 (4mm ²)	8 (10mm ²)	12 (4mm ²)	.146-.080	1/4-20 x 1/2	11/16	1/2	23/64	15/32	1/2
SPSS-1	7 (10mm ²)	10 (6mm ²)	6 (10mm ²)	10 (6mm ²)	.170-.102	1/4-20 x 1/2	13/16	1/2	23/64	15/32	21/32
SPSS-2	5 (16mm ²)	10 (6mm ²)	4 (16mm ²)	10 (6mm ²)	.217-.102	5/16-18 x 5/8	15/16	5/8	25/64	17/32	23/32
SPSS-3	3 (25mm ²)	10 (6mm ²)	2 (35mm ²)	10 (6mm ²)	.271-.102	3/8-16 x 5/8	1/2	5/8	29/64	5/8	25/32
SPSS-4	1 (35mm ²)	8 (6mm ²)	2 (35mm ²)	8 (10mm ²)	.332-.128	3/8-16 x 5/8	1-1/16	5/8	29/64	11/16	7/8
SPSS-5	1/0 (50mm ²)	2 (35mm ²)	2 (35mm ²)	-	.385-.258	1/2-13 x 3/4	1-1/4	3/4	37/64	3/4	15/16
SPSS-6	2/0 (70mm ²)	2 (35mm ²)	2 (35mm ²)	-	.443-.258	1/2-13 x 3/4	1-13/32	3/4	37/64	7/8	1-1/16
SPSS-8	4/0 (95mm ²)	1 (35mm ²)	-	-	.570-.289	5/8-11 x 1	1-9/16	1	51/64	1	1-5/16
SPSS-9	350 (150mm ²)	1/0 (70mm ²)	-	-	.715-.373	5/8-11 x 1	2	1-1/4	51/64	1-5/16	1-11/16
SPSS-10	500 (240mm ²)	3/0 (95mm ²)	-	-	.840-.464	3/4-10 x 1-1/4	2-1/4	1-3/4	63/64	1-1/2	1-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587


TYPE SPS

Features

- Range taking
- Re-usable
- UL 486A/B and UL 467 Listed
- For grounding of steel structures, fence posts and tapping cables from bus bar
- For copper to copper connections

Benefits

- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Ensures reliability
- Flexibility in the field



Catalog Number	Conductor Range AWG MM ²				Maximum Diameter Range	Stud Size	Dimensions				
	Stranded		Solid				A	B	C	D	E
	Max.	Min.	Max.	Min.							
SPSL-0	8	12 (4mm ²)	8 (10mm ²)	12 (4mm ²)	.146-.080	1/4-20 x 1	11/16	1	55/64	15/32	1/2
SPSL-1	7 (10mm ²)	10 (6mm ²)	6 (10mm ²)	10 (6mm ²)	.170-.102	1/4-20 x 1	13/16	1	55/64	15/32	21/32
SPSL-2	5 (16mm ²)	10 (6mm ²)	4 (16mm ²)	10 (6mm ²)	.217-.102	5/16-18 x 1	15/16	1	53/64	17/32	23/32
SPSL-3	3 (25mm ²)	10 (6mm ²)	2 (35mm ²)	10 (6mm ²)	.271-.102	3/8-16 x 1-1/8	1/2	1-1/8	61/64	5/8	25/32
SPSL-4	1 (35mm ²)	8 (6mm ²)	2 (35mm ²)	8 (10mm ²)	.332-.128	3/8-16 x 1-1/8	1-1/16	1-1/8	61/64	11/16	7/8
SPSL-5	1/0 (50mm ²)	2 (35mm ²)	2 (35mm ²)	-	.385-.258	1/2-13 x 1-1/4	1-1/4	1-1/4	1-5/64	3/4	15/16
SPSL-6	2/0 (70mm ²)	2 (35mm ²)	2 (35mm ²)	-	.443-.258	1/2-13 x 1-1/4	1-13/32	1-1/4	1-5/64	7/8	1-1/16
SPSL-8	4/0 (95mm ²)	1 (35mm ²)	-	-	.570-.289	5/8-11 x 1-1/2	1-9/16	1-1/2	1-19/64	1	1-5/16
SPSL-10	500 (240mm ²)	3/0 (95mm ²)	-	-	.840-.464	3/4-10 x 1-3/4	2-1/4	1-1/2	1-31/64	1-1/2	1-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587




TYPE SPD

Features

- Range taking
- Re-usable
- UL 486A/B and UL 467 Listed
- For grounding of steel structures, fence posts and tapping cables from bus bar
- For copper to copper connections

Benefits

- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Ensures reliability
- Flexibility in the field



Catalog Number	Conductor Range AWG MM ²				Maximum Diameter Range	Stud Size	Dimensions				
	Stranded		Solid				AA	B	C	D	E
	Max.	Min.	Max.	Min.							
SPDS-0	8	12 (4mm ²)	8 (10mm ²)	12 (4mm ²)	.146-.080	1/4-20 x 1/2	13/16	1/2	23/64	15/32	1/2
SPDS-1	7 (10mm ²)	10 (6mm ²)	6 (10mm ²)	10 (6mm ²)	.170-.102	1/4-20 x 1/2	31/32	1/2	23/64	15/32	21/32
SPDS-2	5 (16mm ²)	10 (6mm ²)	4 (16mm ²)	10 (6mm ²)	.217-.102	5/16-18 x 5/8	1-1/8	5/8	25/64	17/32	23/32
SPDS-3	3 (25mm ²)	10 (6mm ²)	2 (35mm ²)	10 (6mm ²)	.271-.102	3/8-16 x 5/8	1-1/4	5/8	29/64	5/8	25/32
SPDS-4	1 (35mm ²)	8 (6mm ²)	2 (35mm ²)	8 (10mm ²)	.332-.128	3/8-16 x 5/8	1-3/8	5/8	29/64	11/16	7/8
SPDS-5	1/0 (50mm ²)	2 (35mm ²)	2 (35mm ²)	-	.385-.258	1/2-13 x 3/4	1-19/32	3/4	37/64	3/4	15/16
SPDS-6	2/0 (70mm ²)	2 (35mm ²)	2 (35mm ²)	-	.443-.258	1/2-13 x 3/4	1-13/16	3/4	37/64	7/8	1-1/16
SPDS-8	4/0 (95mm ²)	1 (35mm ²)	-	-	.570-.289	5/8-11 x 1	2-1/16	1	51/64	1	1-5/16
SPDS-9	350 (150mm ²)	1/0 (70mm ²)	-	-	.715-.373	5/8-11 x 1	2-3/4	1-1/4	51/64	1-5/16	1-11/16
SPDS-10	500 (240mm ²)	3/0 (95mm ²)	-	-	.840-.464	3/4-10 x 1-1/4	3-1/8	1-3/4	63/64	1-1/2	1-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587


TYPE SPD

Features

- Range taking
- Re-usable
- UL 486A/B and UL 467 Listed
- For grounding of steel structures, fence posts and tapping cables from bus bar
- For copper to copper connections

Benefits

- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Ensures reliability
- Flexibility in the field



Catalog Number	Conductor Range AWG MM ²				Maximum Diameter Range	Stud Size	Dimensions				
	Stranded		Solid				AA	B	C	D	E
	Max.	Min.	Max.	Min.							
SPDL-0	8	12 (4mm ²)	8 (10mm ²)	12 (4mm ²)	.146-.080	1/4-20 x 1	13/16	1	55/64	15/32	1/2
SPDL-1	7 (10mm ²)	10 (6mm ²)	6 (10mm ²)	10 (6mm ²)	.170-.102	1/4-20 x 1	31/32	1	55/64	15/32	21/32
SPDL-2	5 (16mm ²)	10 (6mm ²)	4 (16mm ²)	10 (6mm ²)	.217-.102	5/16-18 x 1	1-1/8	1	53/64	17/32	23/32
SPDL-3	3 (25mm ²)	10 (6mm ²)	2 (35mm ²)	10 (6mm ²)	.271-.102	3/8-16 x 1-1/8	1-1/4	1-1/8	61/64	5/8	25/32
SPDL-4	1 (35mm ²)	8 (6mm ²)	2 (35mm ²)	8 (10mm ²)	.332-.128	3/8-16 x 1-1/8	1-3/8	1-1/8	61/64	11/16	7/8
SPDL-5	1/0 (50mm ²)	2 (35mm ²)	2 (35mm ²)	-	.385-.258	1/2-13 x 1-1/4	1-19/32	1-1/4	1-5/64	3/4	15/16
SPDL-6	2/0 (70mm ²)	2 (35mm ²)	2 (35mm ²)	-	.443-.258	1/2-13 x 1-1/4	1-13/16	1-1/4	1-5/64	7/8	1-1/16
SPDL-8	4/0 (95mm ²)	1 (35mm ²)	-	-	.570-.289	5/8-11 x 1-1/2	2-1/16	1-1/2	1-19/64	1	1-5/16
SPDL-9	350 (150mm ²)	1/0 (70mm ²)	-	-	.715-.373	5/8-11 x 1-1/2	2-3/4	1-1/2	1-19/64	1-5/16	1-11/16
SPDL-10	500 (240mm ²)	3/0 (95mm ²)	-	-	.840-.464	3/4-10 x 1-3/4	3-1/8	1-1/2	1-31/64	1-1/2	1-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587

G


TYPE TTGC

Features

- Manufactured from bronze
- Eye bolt on TTGC2 rotates to accommodate cable in vertical or horizontal direction
- Range taking
- Stud fits all standard EEI-NEMA distribution transformers

Benefits

- Provides maximum strength and superior conductivity
- Flexibility
- Permits inventories to be kept to a minimum
- Reliability



Catalog Number	Conductor Range		Stud Thread Size UNC - 2A	Dimensions		
	Max.	Min.		A	B	C
TTGC2	2/0	8 sol	1/2-13	1-51/64	1-9/64	1-21/32
TTGC3	1 str	10 sol	1/2-13	1-3/8	1-3/64	1-9/16
TTGC4+	1 str	10 sol	1/2-13	1-1/4	7/8	1-3/8
TTGC2TN+	2/0	8 sol	1/2-13	1-51/64	1-9/64	1-21/32
TTGC3TN*	1 str	10 sol	1/2-13	1-3/8	1-3/64	1-9/16
TTGC4TN*	1 str	10 sol	1/2-13	1-1/4	7/8	1-3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

+ RUS Listed

* Tin Plated

ILSCO Bronze, U-Bolt Ground Clamp




TYPE GUB

Features

- Components are cast or forged from copper alloy
- Specially designed spacer
- Range taking
- Re-usable
- UL 467 Listed for direct burial and CSA Certified

Benefits

- Provides maximum conductivity
- Affords more positive contact area
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Ensures reliability



Catalog Number	Conductor		Nominal Rod		IPS Pipe Size		Dimensions		
	Max.	Min.	Max.	Min.	Max.	Min.	A	B	C
GUB-1	4	8	3/4	5/8	3/8	-	2-13/16	1-9/16	2-1/4
GUB-2	2/0	4	3/4	5/8	3/8	-	2-13/16	1-9/16	2-1/4
GUB-3	250kcmil	2/0	3/4	5/8	3/8	-	2-13/16	1-9/16	2-1/4
GUB-4	4	8	1	7/8	3/4	1/2	2-3/4	1-9/16	2-5/8
GUB-5	2/0	4	1	7/8	3/4	1/2	2-3/4	1-9/16	2-5/8
GUB-6	250kcmil	2/0	1	7/8	3/4	1/2	2-3/4	1-9/16	2-5/8
GUB-7	4	8	1-1/4	1-1/8	1	-	3-5/16	1-9/16	2-3/4
GUB-8	2/0	4	1-1/4	1-1/8	1	-	3-5/16	1-9/16	2-3/4
GUB-9	4	8	1-1/2	1-3/8	1-1/4	-	3-7/16	1-9/16	2-15/16
GUB-10	2/0	4	1-1/2	1-3/8	1-1/4	-	3-7/16	1-9/16	2-15/16
GUB-11	250kcmil	2/0	1-1/2	1-3/8	1-1/4	-	3-7/16	1-9/16	2-15/16
GUB-12	4	8	1-7/8	1-5/8	1-1/2	-	3-15/16	1-9/16	3-3/16
GUB-13	2/0	4	1-7/8	1-5/8	1-1/2	-	3-15/16	1-9/16	3-3/16
GUB-14	250kcmil	2/0	1-7/8	1-5/8	1-1/2	-	3-15/16	1-9/16	3-3/16
GUB-15	4	8	2-3/8	2	2	-	4-7/16	1-9/16	3-11/16
GUB-16	2/0	4	2-3/8	2	2	-	4-7/16	1-9/16	3-11/16
GUB-17	250kcmil	2/0	2-3/8	2	2	-	4-7/16	1-9/16	3-11/16
GUB-18	2/0	4	2-7/8	2-1/2	2-1/2	-	4-15/16	1-9/16	4-3/16
GUB-19	250kcmil	2/0	2-7/8	2-1/2	2-1/2	-	4-15/16	1-9/16	4-3/16
GUB-20	2/0	4	3-1/2	3	3	-	5-9/16	1-9/16	4-13/16
GUB-21	250kcmil	2/0	3-1/2	3	3	-	5-9/16	1-9/16	4-13/16
GUB-22	2/0	4	4	3-1/2	3-1/2	-	6-1/16	1-9/16	5-1/2
GUB-23	2/0	4	4-1/2	4	4	-	6-5/16	1-9/16	5-11/16
GUB-24	250kcmil	2/0	4-1/2	4	4	-	6-5/16	1-9/16	5-11/16



All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587



4730 Madison Road, Cincinnati, Ohio 45227-1426 Phone 513 533-6200 Fax 513 871-4084 Web site www.ilsco.com
Canada 1050 Lakeshore Road East, Mississauga, Ontario, Canada L5E1E4 Phone 905 274-2341 Fax 905 274-8763

ILSCO Bronze Waterpipe Ground Clamp




TYPE GPL3

Features

- Range taking
- Cable clamp rotates
- Silicon bronze hardware
- UL 467 Listed

Benefits

- Inventory reduction
- Allows ground conductor to be attached parallel to pipe or at 90°
- Corrosion resistant
- Suitable for direct burial in earth or concrete



Catalog Number	Ground Wire Range	IPS Pipe Size	Dimensions		Fits Pipe O.D. Range
			W	H	
GPL3902BU	4 - 4/0	1/2 - 1	3.250	3.500	.840 - 1.32
GPL3903BU	4 - 4/0	1-1/4 - 2	4.250	4.000	1.66 - 2.38
GPL3904BU	4 - 4/0	2-1/2 - 3-1/2	5.000	6.500	2.88 - 4.00
GPL3905BU	4 - 4/0	4 - 5	7.500	7.500	4.50 - 5.56
GPL3906BU	4 - 4/0	6	8.625	8.500	6.62
GPL3907BU	4 - 4/0	8	10.625	10.000	8.62
GPL3908BU	4 - 4/0	10	12.750	12.000	10.75
GPL3909BU	4 - 4/0	12	14.750	14.000	12.75

G

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E34440



TYPE GS GSR

Features

- Manufactured from annealed copper sheet
- Two styles available
- Type GSR supplied in 10' coils with 1/4" holes

Benefits

- Provides maximum conductivity and greater flexibility
- Heavy-Duty or lightweight in four different lengths
- Can be cut to desired length which reduces inventory



Fig. 1



Fig. 2

Catalog Number	Figure Number	Pipe Size	Dimensions		Type
			L	W	
GS-1	1	3/8-1	5-17/32	3/4	Heavy .050 thick
GS-2	1	3/8-2	9-5/16	3/4	Heavy .050 thick
GS-3	1	3/8-3	12-3/4	3/4	Heavy .050 thick
GS-4	1	3/8-4	15-3/4	3/4	Heavy .050 thick
GS-10	1	3/8-1	5-17/32	3/4	Light .025 thick
GS-20	1	3/8-2	9-5/16	3/4	Light .025 thick
GS-30	1	3/8-3	12-3/4	3/4	Light .025 thick
GS-40	1	3/8-4	15-3/4	3/4	Light .025 thick
GSR-Plain*	2	-	10 ft.	3/4	Light .030 thick

* 1/4" Holes


TYPE D167

Features

- Manufactured from high strength copper tubing
- Range taking
- UL Recognized for 600 volts

Benefits

- Provides maximum conductivity
- A wide range of conductor sizes can be used in the same connector
- Ensures reliability for copper conductor



Catalog Number	Number Of Taps	Wire Range		Dimensions					Mounting Hole Positions	
		Main	Tap	L	Height With Maximum Wire	W	Bolt Size	Two Mounting Holes	From End Of Bar To First Mounting Hole	Distance Between Holes
D167-4	4	4-14	6-14	2-3/4	3/4	11/32	#10	13/64	.581 (2nd hole)	1.98
D167-6	6	4-14	6-14	3-1/2	3/4	11/32	#10	13/64	.978 (3rd hole)	1.98
D167-8	8	4-14	6-14	4-7/16	3/4	11/32	#10	13/64	1.375 (4th hole)	1.98
D167-10	10	4-14	6-14	5-1/8	3/4	11/32	#10	13/64	1.772 (5th hole)	1.98
D167-12	12	4-14	6-14	5-15/16	3/4	11/32	#10	13/64	2.169 (6th hole)	1.98
D167-14	14	4-14	6-14	6-23/32	3/4	11/32	#10	13/64	2.566 (7th hole)	1.98

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

TYPE CAN

Features

- Manufactured from high strength copper tubing
- Compact design
- Range taking
- Circuit bars inserted at a 20 angle
- Copper conductor only

Benefits

- Provides maximum conductivity
- Up to 42 circuit taps can be made in just 5 1/2" of space
- A wide range of conductor sizes can be used in the same connector
- Provides easy wire insertion




Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Number Of Taps	Wire Range		Dimensions			
			Main	Tap	L	Height With Maximum Wire	W	Two Tapped Mounting Holes
CAN-300	1	24	250kcmil-6	6-14	2-5/16	1-5/16	5-1/8	10-32
CAN-301	1	30	250kcmil-6	6-14	3	1-5/16	4-13/32	10-32
CAN-302	1	36	250kcmil-6	6-14	3	1-5/16	5-1/8	10-32
CAN-303	1	42	250kcmil-6	6-14	3	1-7/16	5-1/2	10-32
R-16	2	Mounting block of general purpose (phenolic black) suitable for mounting any of CAN Neutrals. 2-1/2" wide x 2-1/2" long x 1" thick.						
E-223	3	10-32 x 1/2" round head steel machine screws for fastening neutrals to mounting blocks. (Use lock washer to provide rigid assembly.)						
E-153	3	1/4-28 wire pressure screw 7/16" long. Screw is steel, zinc plated and chromate dipped.						
N-174	4	Supplied in 5' 9" lengths. Approximately 174 outlets. Wire range 14-6.						

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

ILSCO Dual Rated Ground Clamp

RoHS
Compliant

UL
LISTED
667P

TYPE AGC SGC

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Clear plated
- Versatile
- Range taking
- SGC Lay-In feature

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Effectively grounds aluminum or copper conductors to copper water pipe, galvanized pipe or steel conduit
- Three sizes cover a range from 1/2" to 4" pipe with a ground wire range of 250kcmil - #14 which reduces inventory
- Provides ease of installation for long ground wire runs




Fig. 1



Fig. 2



Fig. 3

Catalog Number	Figure Number	Pipe Size	Rebar Size	Ground Wire Range	Screw Type	Dimensions		Hex Size
						L	W	
AGC-1	1	1/2-3/4-1	4, 5, 6	1/0-14	Slot	2-1/4	11/16	Slot
AGC-2	2	1 1/4-1 1/2-2	-	250kcmil-6	Hex Socket	3-3/4	13/16	5/16
AGC-4	2	2 1/2-3-3 1/2-4	-	250kcmil-6	Hex Socket	6-5/16	1	5/16
SGC-1/0*	3	1/2-3/4-1"	-	1/0-14	Slot	2-1/4	11/16	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.

* Typical application would be grounding computer floor room system.

UL File E34440

G

ILSCO Dual Rated Lay-In Ground Lug

RoHS
Compliant

UL
LISTED
667P

SA
LR-29601



TYPE SGB

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Lay-in feature
- Stainless steel hardware
- Serrations in conductor wire way
- Unique clamp design
- 1/4" max frame thickness
- Meets ASTM B117-09

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- For corrosion resistance, greater torque and ease of installation
- Cuts oxidation
- No holes to be drilled for mounting
- Mount to solar panel frames
- Resistance to outdoor salt spray



Catalog Number	Ground Wire Range	Dimensions		
		L	W	H
SGB-4	4-14	1.375	.500	.940

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL 467 for grounding and bonding.

UL File E34440

DE-OX Inhibitor is recommended for all aluminum terminations.

TYPE GBL

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Lay-in feature

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation




Fig. 1



Fig. 2

Catalog Number	Figure Number	Ground Wire Range	Bolt Size	Dimensions							Hex Size
				C	D	E	F	G	H	T	
*GBL-4	1	4-14	10	7/32	5/8	31/64	1-3/32	13/64	25/64	51/64	Slot
+GBL-4SS	1	4-14	10	7/32	5/8	31/64	1-3/32	13/64	25/64	51/64	Slot
GBL-1/0	1	1/0-14	1/4	9/32	51/64	27/32	1-5/8	7/16	5/8	1-5/32	Slot
GBL-250	2	250kcmil-6	1/4	9/32	31/64	1	2-3/16	29/64	7/8	1-23/32	7/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL File E34440

* UL 467 and UL 486A/B Listed

+ UL 467 Listed

+ Supplied with stainless steel hardware. Meets ASTM B117-09 and is resistant to outdoor salt spray.

DE-OX Inhibitor is recommended for all aluminum terminations.

TYPE CGBL

Features

- Lay-in feature
- Manufactured from high strength copper
- Stainless steel hardware

Benefits

- Provides ease of installation of continuous loop grounding conductor
- Suitable for direct burial and for use with copper conductors
- Resists oxidation and corrosion in earth or concrete




Fig. 1



Fig. 2

Catalog Number	Figure Number	Ground Wire Range	Bolt Size	Dimensions							Screw Type
				C	D	E	F	G	H	T	
GBL-4DB	1	4-14	10	.218	.680	.470	1.150	.190	.375	.825	Slot
GBL-4DB-14	1	4-14	1/4	.265	.680	.470	1.150	.210	.472	.825	Slot
GBL-4DBT*	1	4-14	10	.218	.680	.470	1.150	.190	.375	.825	Slot
GBL-4DBT-14*	1	4-14	1/4	.265	.680	.470	1.150	.210	.472	.825	Slot
GBL-4DBTH*	2	4-14	10	.218	.680	.470	1.150	.190	.375	.825	Hex
GBL-4DBTH-14*	2	4-14	1/4	.265	.680	.470	1.150	.210	.472	.825	Hex

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 467, UL File E34440

* T indicates tin plating

Mounting hardware kits available, consult ILSCO

TYPE GBT

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Approved for UL 467 (Grounding & Bonding)
- Lay in style
- No mounting required
- 4 Taps (#2-14) stranded or solid
- Stainless steel screws
- Serrations in conductor wire way
- Patented

Benefits

- For use with copper and aluminum conductors
- Meets NEC 250.94 installation requirements.
- Eliminates the need to cut or splice into existing conductor
- Allows fast simple installation on ground conductor below meter
- For bonding multiple communication systems (Phone, TV, Cable, etc.)
- For corrosion resistance
- Cuts oxidation



Fig. 1



Fig. 2




Fig. 3

Catalog Number	Figure Number	Wire Range Main	Wire Range Tap	Length	Width	Height	Hex Size	
							Main	Tap
GBT-1/0	1	1/0-8	2-14str-sol	2.250	1.125	1.160	S	S
GBT-250	1	250kcmil-8str - 1/0-8sol	2-14str-sol	2.250	1.375	1.587	7/32	S
GBT-1/0-M	2	1/0-8	2-14str-sol	2.250	1.750	1.160	S	S
GBT-1/0-M-W/C	3	1/0-8	2-14str-sol	2.730	3.930	2.110	S	S

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL File E34440

TYPE GRM GRF

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Type GRM - Elongated steel stud
- Type GRF - Threaded female design

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of grounding a single conductor to steel structures or to tap a single conductor from bus bar
- Provides ease of installation for a variety of standard stud sizes




Fig. 1




Fig. 2

Catalog Number	Figure Number	Wire Range Single Cable				Dia. Thread	Dimensions			Hex Size
		Max.	Min.	Steel Strand	A		B	L		
GRM-2A	1	2str	12sol/str	5/16	1/4"-20	-	11/16	1-1/4	Slot	
GRM-2B	1	2str	12sol/str	5/16	5/16"-18	-	3/8	1-1/4	Slot	
GRM-2C	1	2str	12sol/str	5/16	3/8"-16	-	9/16	1-1/4	Slot	
GRM-0	1	1/0str	2str	3/8	1/2"-13	-	1	1-9/16	Slot	
GRM-250A	1	250kcmil	1/0	9/16	1/2"-13	-	1	2-1/8	5/16	
GRM-250B	1	250kcmil	1/0	9/16	5/8"-11	-	1	2-1/8	5/16	
GRM-350	1	350kcmil	4/0	-	5/8"-11	-	1	2-1/2	3/8	
GRM-500	1	500kcmil	350kcmil	-	3/4"-10	-	1-3/8	2-15/16	3/8	
GRM-750	1	750kcmil	500kcmil	-	3/4"-10	-	1-3/8	3-3/8	1/2	
GRF-2A	2	2str	12sol/str	5/16	1/4"-20	5/16	-	1-1/4	Slot	
GRF-2B	2	2str	12sol/str	5/16	5/16"-18	3/8	-	1-1/4	Slot	
GRF-2C	2	2str	12sol/str	5/16	3/8"-16	7/16	-	1-1/4	Slot	
GRF-0	2	1/0str	2str	3/8	1/2"-13	1/2	-	1-9/16	Slot	
GRF-250A	2	250kcmil	1/0	9/16	1/2"-13	1/2	-	2-1/8	5/16	
GRF-250B	2	250kcmil	1/0	9/16	5/8"-11	3/4	-	2-1/8	5/16	
GRF-350	2	350kcmil	4/0	-	5/8"-11	3/4	-	2-1/2	3/8	
GRF-500	2	500kcmil	350kcmil	-	3/4"-10	7/8	-	2-15/16	3/8	
GRF-750	2	750kcmil	500kcmil	-	3/4"-10	7/8	-	3-3/8	1/2	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

DE-OX Inhibitor is recommended for all aluminum terminations.



TYPE NB

Features

- Preassembled, stacked neutral bars
- Available with phenolic base
- Electro-tin plated
- Fabricated from high strength 6061-T6 aluminum alloy

Benefits

- Compact, space saving design offers multiple range taking flexibility and is suitable for grounding applications
- Provides insulation from mounting surface
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors




Fig. 1



Fig. 2




Fig. 3

Catalog Number	Figure Number	Number Of Circuit Taps	Wire Range		Dimensions			Two Tapped Mounting Holes	Hex Size	
			Circuit Taps	Line Loads	Approx. Height with Max. Wire	L	W		Main	Tap
NB-350-12	1	12	14-4	350kcmil-6	1-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-12-W/R16*	2	12	14-4	350kcmil-6	2-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-24	1	24	14-4	350kcmil-6	1-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-24-W/R16*	2	24	14-4	350kcmil-6	2-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-30	1	30	14-4	350kcmil-6	1-17/32	4-3/32	2-17/32	10-32	3/8	Slot
NB-350-30-W/R16*	2	30	14-4	350kcmil-6	2-17/32	4-3/32	2-17/32	10-32	3/8	Slot
NB-350-36	1	36	14-4	350kcmil-6	1-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-36-W/R16*	2	36	14-4	350kcmil-6	2-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-42	1	42	14-4	350kcmil-6	1-17/32	5-11/32	2-17/32	10-32	3/8	Slot
NB-350-42-W/R16*	2	42	14-4	350kcmil-6	2-17/32	5-11/32	2-17/32	10-32	3/8	Slot


All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Part includes phenolic mounting block R-16

Tested to UL 486A/B, UL File E6207

Catalog Number	Figure Number	Number of Outlets	Wire Range	Length
NB-120	3	120	30 outlets 1/0-14 90 outlets 6-14	36.25"

UL File E6207



ILSCO FLEX BRAID CONNECTORS

ILSCO manufactures high quality flexible braid electrical connectors for power and grounding applications. Flex braid connectors are ideal for grounding electrical cabinet doors and in situations where vibration exists. This includes generators, turbines, motors, substations and transformers.

ILSCO flex braid connectors are UL Listed and CSA Certified for grounding per UL 467, file E34440.

Flex braids are also commonly used on bus systems and for equipment misalignment solutions.

ILSCO flex braids consist of high quality tin-plated copper braid with seamless copper tube ferrules stamped on the ends. The ferrules have rounded smooth edges to prevent chaffing of braid strands.

ILSCO provides four standard ferrule designs as shown above, but we will be glad to quote custom designs per your specifications.



TYPE T

Features

- Manufactured from pure copper braid
- Electro-tin plated
- Seamless pure copper ferrules
- Inside ferrule ends are rounded
- Ferrule ends swedged to braid
- Extra flexible braid

Benefits

- Provides superior ground path
- Corrosion resistant
- Low resistance
- Prevent chafing of strands
- Permanent low-resistance connection
- Easily connects and bonds moving parts



Catalog Number*	Number of Mounting Holes	Mounting Hole Diameter	Amps	Circular Mils. of Braids	Number of stacked braids	Dimensions		
						L**	T	W
T252/11N12	1	0.562	200	77,184	1	12.000	0.250	1.000
T252/21N12	1	0.562	340	154,386	2	12.000	0.250	1.000
T252/31N12	1	0.562	470	231,552	3	12.000	0.380	1.000
T252/41N12	1	0.562	600	308,734	4	12.000	0.380	1.000
T282/11N12	1	0.562	340	153,600	1	12.000	0.250	1.630
T282/21N12	1	0.562	530	307,000	2	12.000	0.250	1.630
T282/31N12	1	0.562	700	460,800	3	12.000	0.310	1.630
T282/41N12	1	0.562	800	614,400	4	12.000	0.380	1.630

* Add suffix "T" for tin-plated

** The two digits following the letter "N" define overall length in inches (12 equals 12:- shown).
For length other than 12 inches, insert the desired length.

ILSCO Flex Braid Connectors





TYPE T

Features

- Manufactured from pure copper braid
- Electro-tin plated
- Seamless pure copper ferrules
- Inside ferrule ends are rounded
- Ferrule ends swedged to braid
- Extra flexible braid

Benefits

- Provides superior ground path
- Corrosion resistant
- Low resistance
- Prevent chafing of strands
- Permanent low-resistance connection
- Easily connects and bonds moving parts



Catalog Number*	Number of Mounting Holes	Mounting Hole Diameter	Amps	Circular Mils. of Braids	Number of stacked braids	Dimensions		
						L**	T	W
T252/12N12	2	0.562	200	77,184	1	12.000	0.250	1.000
T252/22N12	2	0.562	340	154,386	2	12.000	0.250	1.000
T252/32N12	2	0.562	470	231,552	3	12.000	0.380	1.000
T252/42N12	2	0.562	600	308,734	4	12.000	0.380	1.250
T282/12N12	2	0.562	340	153,600	1	12.000	0.250	1.630
T282/22N12	2	0.562	530	307,000	2	12.000	0.250	1.630
T282/32N12	2	0.562	700	460,800	3	12.000	0.310	1.630
T282/42N12	2	0.562	800	614,400	4	12.000	0.380	1.630
T287/12N12	2	0.562	370	230,000	1	12.000	0.250	1.500
T287/22N12	2	0.562	700	460,000	2	12.000	0.380	1.500
T287/32N12	2	0.562	820	690,000	3	12.000	0.500	1.500
T287/42N12	2	0.562	1000	920,000	4	12.000	0.750	1.630
T294/12N12	2	0.562	415	300,000	1	12.000	0.250	1.500
T294/22N12	2	0.562	700	600,000	2	12.000	0.500	1.500
T294/32N12	2	0.562	960	900,000	3	12.000	0.750	1.630
T294/42N12	2	0.562	1200	1,200,000	4	12.000	1.000	1.630

* Add suffix "T" for tin-plated

** The two digits following the letter "N" define overall length in inches (12 equals 12:- shown).
For length other than 12 inches, insert the desired length.





TYPE T

Features

- Manufactured from pure copper braid
- Electro-tin plated
- Seamless pure copper ferrules
- Inside ferrule ends are rounded
- Ferrule ends swedged to braid
- Extra flexible braid

Benefits

- Provides superior ground path
- Corrosion resistant
- Low resistance
- Prevent chafing of strands
- Permanent low-resistance connection
- Easily connects and bonds moving parts



Catalog Number*	Number of Mounting Holes	Mounting Hole Diameter	Amps	Circular Mils. of Braids	Number of stacked braids	Dimensions		
						L**	T	W
T278/14N12-3	4	0.562	360	211,200	1	12.000	0.250	3.000
T278/24N12-3	4	0.562	625	422,400	2	12.000	0.310	3.000
T278/34N12-3	4	0.562	800	633,600	3	12.000	0.380	3.000
T278/44N12-3	4	0.562	940	844,900	4	12.000	0.500	3.000

* Add suffix "T" for tin-plated

** The two digits following the letter "N" define overall length in inches (12 equals 12:- shown).
For length other than 12 inches, insert the desired length.

ILSCO Flex Braid Connectors

RoHS
Compliant

UL
LISTED
667P






TYPE T

Features

- Manufactured from pure copper braid
- Electro-tin plated
- Seamless pure copper ferrules
- Inside ferrule ends are rounded
- Ferrule ends swedged to braid
- Extra flexible braid

Benefits

- Provides superior ground path
- Corrosion resistant
- Low resistance
- Prevent chafing of strands
- Permanent low-resistance connection
- Easily connects and bonds moving parts


























Catalog Number*	Number of Mounting Holes	Mounting Hole Diameter	Amps	Circular Mils. of Braids	Number of stacked braids	Dimensions		
						L**	T	W
T278/14N12-4	4	0.562	625	422	1	12.000	0.250	4.000
T278/24N12-4	4	0.562	940	844,000	2	12.000	0.310	4.000
T278/34N12-4	4	0.562	1200	1,266,000	3	12.000	0.380	4.000
T278/44N12-4	4	0.562	1600	1,688,000	4	12.000	0.500	4.000

* Add suffix "T" for tin-plated

** The two digits following the letter "N" define overall length in inches (12 equals 12:- shown).
For length other than 12 inches, insert the desired length.

G1



<p>DBK</p>  <p>293</p>	<p>ASK</p>  <p>293</p>	<p>USPA-SS</p>  <p>294</p>	<p>SS, SSK, SSKC</p>  <p>295</p>	<p>PED-SS</p>  <p>296</p>
<p>GGA</p>  <p>297</p>	<p>GGC</p>  <p>298</p>	<p>ELT</p>  <p>299</p>	<p>SLU-DB, XT-DB</p>  <p>300</p>	<p>CGRC</p>  <p>301</p>
<p>BGRC</p>  <p>301</p>	<p>SRC</p>  <p>302</p>			
<p>GRC</p>  <p>303</p>	<p>RLT</p>  <p>304</p>			
<p>BGC</p>  <p>305</p>	<p>BGDB</p>  <p>306</p>			
<p>SPS</p>  <p>307 - 308</p>	<p>SPD</p>  <p>309 - 310</p>			
<p>TTGC</p>  <p>311</p>	<p>GUB</p>  <p>312</p>			
<p>GPL3</p>  <p>313</p>	<p>CGBL</p>  <p>314</p>			

TYPE DBK ASK

Features

- DBK-1 connectors manufactured from electrolytic copper
- All other connectors manufactured from high strength aluminum alloy
- Heavy wall heat shrink tubing with sealant
- Connector and heat shrink packaged together
- Rated for 600 volts, 90° C

Benefits

- Provides maximum conductivity for UF cable
- Provides high conductivity and can be used with either aluminum or copper conductors
- Provides watertight splice. Kits with heat shrink are designed to withstand abrasions due to direct burial in rocky soil.
- Provides ease of ordering
- Ensures reliability



Fig. 1



Fig. 2



Fig. 3

Catalog Number	Figure Number	UF Cable Range		Wire Range	Testing Certification
		Minimum	Maximum		
DBK-1	1	14/2 with Ground	8/3 with Ground	-	
DBK-2	2	-	-	2-8	
DBK-250	2	-	-	250kcmil-1	

Tested UL 486D, UL File E125087

ABOVE GRADE SPLICE KITS

ASK-2*	3	-	-	2-8	
ASK-250*	3	-	-	250kcmil-1	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*Not UL Listed for direct burial.

Tested to UL 486A/B, UL File E6207

TYPE USPA-SS

Features

- Encapsulated in EPDM rubber with a nominal thickness of 125 Mil and a dielectric strength of 240 Volts per Mil
- Pre-marked end inserts
- O-Ring design screw cap inserts
- Connector is produced from high strength 6061-T6 aluminum alloy
- Connector rated for 600 volts, 90° C
- Range taking
- UL Listed and CSA Certified for direct burial in earth or concrete

Benefits

- Completely watertight in line splice. Ready for installation. (not a mold for use with mixed compounds) No taping required. No temperature or humidity restrictions.
- Simply cut end inserts to appropriate marked wire size and insert conductor into connector
- Ensures connector integrity while allowing ease of access to set screws, ensuring excellent sealing
- Suitable for use with either copper or aluminum conductors
- Ensures reliability
- Reduces inventory




Fig. 1




Fig. 2



Fig. 3

Catalog Number	Figure Number	Wire Range		Length	Hex Size	Recommended Torque-Inch Lbs.
		Barrel A	Barrel B			
USPA-350SS-DB +	1	350kcmil-10str	350kcmil-10str	8- 5/8	5/16	350
USPA-500SS-DB	2	500kcmil-10	500kcmil-10	9-13/16	5/16	450
USPA-750SS-DB	3	750kcmil-2	750kcmil-2	9-13/16	5/16	500

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

+ RUS Listed

Tested to UL 486D, UL File E125087

TYPE
SS
SSK
SSKC

Features

- Watertight EPDM rubber splice cover
- Tapered ends
- Ready for installation
- Type SS is cover only supplied with lubricant
- Type SSK kit is supplied with both connector and lubricant
- Connector rated for 600 volts, 90° C

Benefits

- No taping required. Suitable for direct burial
- Fits a wide range of conductor sizes
- Not a mold, can be used in any type of weather. (moisture and humidity are not a factor)
- Can be used with standard aluminum or copper compression from 500kcmil - 6. Lubricant permits easy insertion of conductors into sleeve.
- Supplied with dual-rated mechanical splice connector with a wire range of 350kcmil - 6
- Ensures reliability



Fig. 1



Fig. 2

Catalog Number	Figure Number	Wire Range		L
		Bolted Connector	Compression Sleeves	
SSK-350-Z	1	350kcmil-6	-	5-1/2
SS-350-Z	2	350kcmil-6	500kcmil-6	5-1/2



Catalog Number	Connector Catalog Number	Wire Size	Wire Range When Installed With IDT-12 Tool
SSKC-6-Z	AS-6	6	6
SSKC-4-Z	AS-4	4	4-6
SSKC-2-Z	AS-2	2	2-6
SSKC-1/0-Z	AS-1/0	1/0	1/0-1
SSKC-2/0-Z	AS-2/0	2/0	2/0-1
SSKC-3/0-Z	AS-3/0	3/0	3/0-1
SSKC-4/0-Z	AS-4/0	4/0	4/0-1
SSKC-250-Z	AS-250	250kcmil	250kcmil-1/0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE PED-SS

Features

- Available in a variety of conductor configurations and three wire ranges
- Manufactured from high strength aluminum alloy
- Clear plated
- Dual rated
- EPDM cover has dielectric strength of 240 volts per mil and nominal thickness of 125 mils
- UL Listed and CSA Certified for direct burial in earth or concrete
- Rated for 600 volts

Benefits

- Provides multiple conductor installation for a broad wire range
- Provides maximum conductivity
- Low contact resistance
- Use with both copper and aluminum conductors
- Completely watertight, no taping required. Suitable for direct burial in earth or concrete



Fig. 1



Fig. 2




Fig. 3

Catalog Number	Figure Number	Wire Range	Number of Ports	Dimensions		
				W	H	L
PED3-350SS-DB	1	350kcmil-10str	3	4.40	2.70	3.67
PED4-350SS-DB	1	350kcmil-10str	4	4.40	2.70	4.82
PED5-350SS-DB	1	350kcmil-10str	5	4.40	2.70	6.04
PED6-350SS-DB	1	350kcmil-10str	6	4.40	2.70	7.14
PED8-350SS-DB	1	350kcmil-10str	8	4.40	2.70	9.45
PED-3-500-SS-Z *	2	500kcmil-10	3	5.06	2.82	4.57
PED-4-500-SS-Z *	2	500kcmil-10	4	5.06	2.82	6.04
PED-5-500-SS-Z *	2	500kcmil-10	5	5.06	2.82	7.50
PED-6-500-SS-Z *	2	500kcmil-10	6	5.06	2.82	8.98
PED-8-500-SS-Z *	2	500kcmil-10	8	5.06	2.82	11.92
PED-4-750-SS-Z *	3	750kcmil-2	4	6.50	3.53	6.97
PED-6-750-SS-Z *	3	750kcmil-2	6	6.50	3.53	10.35
PED-8-750-SS-Z *	3	750kcmil-2	8	6.50	3.53	13.73

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Extra screw closure caps and extra conductor plugs available.

* Not UL Listed or CSA Certified.

Tested to UL 486D, UL File E125087


TYPE GGA

Features

- Manufactured from high strength copper alloy
- Clearly marked with wire size and die index
- Range taking
- Connector can be adjusted prior to installation
- Non-hazardous installation
- Prefilled with inhibiting compound
- Temperature Rating 90° C

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion. Suitable for direct burial.
- Provides easy identification and tooling recommendation
- Reduces inventory. Six sizes cover a wire range from 500kcmil to #6, and 1/2" to 3/4" ground rods.
- Permits adjustments to be made for misaligned cross grids
- Can be installed in all types of weather with no need for protective equipment or clothing. Does not produce heat or dangerous particles.
- Prevents oxides from forming
- Ensures reliability



Catalog Number	Wire Range				Dimensions						Die Index Number	
	Cable to Cable		Cable to Ground Rod		A	B	C	D	E	F	Side A	Side B
	Side A	Side B	Side A	Side B								
GGA-1	2str-6sol	2str-6sol	-	-	.75	.75	1.09	1.09	.313	2.50	0	0
GGA-2	250kcmil-1str	2str-6sol	1/2 - 5/8 Rod	2str-6sol	.75	.75	1.66	1.09	.313	2.50	997	0
GGA-3	250kcmil-2str	250kcmil-2str	1/2 - 5/8 Rod	250kcmil-2str	.75	.75	1.66	1.66	.500	2.50	997	997
GGA-4	500kcmil-250kcmil	2str-6sol	1/2 - 5/8 Rod	2str-6sol	.75	.75	2.09	1.09	.313	2.50	998	0
GGA-5	500kcmil-250kcmil	250kcmil-2str	5/8 - 3/4 Rod	250kcmil-2str	.75	.75	2.09	1.66	.500	2.50	998	997
GGA-6	500kcmil-250kcmil	500kcmil-250kcmil	5/8 - 3/4 Rod	500kcmil-250kcmil	.75	.75	2.28	2.28	.750	2.50	999/1011	999/1011

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 467, UL File E34440

The GGA Series compression ground grid cross connector can be used to connect a copper ground grid system together or to connect a copper ground grid system to a copper clad ground rod. The GGA Series of compression connectors allow adjustment of each side of the connector prior to installation. The GGA Series of compression connectors are pre-filled with inhibiting compound and are suitable for direct burial.

Notes:

1. ILSCO ILC-12 or ILC-15 Series Tools and ILD Series Dies may be used. Note: Adapter required when using ILC-15 Series Tool. Burndy tools and dies may also be used.
2. When used with ground rods, it is recommended to rough up the end of ground rod where GGA is to be placed. This provides good rotational resistance. Perform a "pre-crimp" on ground rod prior to installing GGA connector. Use an indent type of die such as Burndy's U2CABT (Die Index #348) or UPRECRIMP-12, -58, -34.*
3. Each side of the GGA Series may be rotated around the rod to any desired position before crimping.

* "UPRECRIMP" and "U2CABT" are registered trademarks TM of Burndy/FCI

ILSCO Grounding Grid Connectors

RoHS
Compliant

UL
LISTED
667P

SF
LR-5465


TYPE GGC

Features

- Manufactured from high strength copper alloy
- Clearly marked with wire size and die index
- Range taking
- Versatile
- Non-hazardous installation
- Prefilled with inhibiting compound
- Temperature Rating 90° C

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion. Suitable for direct burial.
- Provides easy identification and tooling recommendation
- Reduces inventory. Eight sizes cover a wire range from 500kcmil to #6, and 1/2" to 3/4" ground rods.
- Can be used as a tap connector or as a lap splice connector
- Can be installed in all types of weather with no need for protective equipment or clothing. Does not produce heat or dangerous particles.
- Prevents oxides from forming
- Ensures reliability



Catalog Number	Wire Range		Main Ground Rod	Dimensions			Die Index Index
	Main	Tap		A	B	C	
GGC-1	2str-6sol	2str-6sol	-	1.4	.75	.33	0
GGC-2	250kcmil-1/0str 1/2 - 5/8 Rod	2str-4sol	1/2 - 5/8	2.1	.75	.33	997
GGC-3	250kcmil-1/0str 1/2 - 5/8 Rod	2/0str-1/0str	1/2 - 5/8	2.1	.75	.44	997
GGC-4	250kcmil-1/0str 1/2 - 5/8 Rod	250kcmil-3/0str	1/2 - 5/8	2.1	.75	.61	997
GGC-5	500kcmil-250kcmil 5/8 - 3/4 Rod	2str-4sol	5/8 - 3/4	2.6	.75	.33	998
GGC-6	500kcmil-250kcmil 5/8 - 3/4 Rod	2/0str-1/0str	5/8 - 3/4	2.6	.75	.44	998
GGC-7	500kcmil-250kcmil 5/8 - 3/4 Rod	250kcmil-3/0str	5/8 - 3/4	2.6	.75	.61	998
GGC-8	500kcmil-250kcmil 5/8 - 3/4 Rod	500kcmil-350kcmil	5/8 - 3/4	2.9	.75	.84	999/1011

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 467, UL File E34440

**NOTE: Hydraulic tools required on all sizes except GGC-1
Dieless tools can not be used**

The GGC Series compression ground tap connector can be used as a tap connector to connect copper ground wire to a copper clad ground rod or as a lap splice connector splicing copper conductors together. The GGC Series of compression connectors are pre-filled with inhibiting compound and are suitable for direct burial.

Notes:

1. ILSCO ILC-12 or ILC-15 Series Tools and ILD Series Dies may be used. Note: Adapter required when using ILC-15 Series Tool. Burndy tools and dies may also be used.
2. When used with ground rods, it is recommended to rough up the end of ground rod where GGC is to be placed. This provides good rotational resistance. Perform a "pre-crimp" on ground rod prior to installing GGC connector. Use an indent type of die such as Burndy's U2CABT (Die Index #348) or UPRECRIMP-12, -58, -34.*
3. When using #6 AWG solid wire in the tap side, fold conductor double prior to crimping.
4. When using GGC-4, if 3/0 conductor is used in the tap side, use a minimum of 2/0 conductor in the run side.

* "UPRECRIMP" and "U2CABT" are registered trademarks TM of Burndy/FCI

TYPE ELT

Features

- Manufactured from copper alloy
- Clearly marked with wire size and die index
- Range taking
- UL Listed and CSA Certified for grounding and bonding
- May be used in ground grid applications

Benefits

- Provides maximum conductivity and eliminates the possibility of corrosion. Suitable for direct burial in earth or concrete
- Provides easy identification and tooling recommendation
- Reduces inventory
- Ensures reliability
- Flexibility in application



Catalog Number	Copper Wire Range		Width	Die Index
	Main	Tap		
ELT-1	2str-6sol	2str-6sol	.75	C (U Type)
ELT-4	2/0str-1str	2str-6str	.75	0 (U Type)
ELT-2	2/0str-1str	2/0str-1str	.75	0 (U Type)
ELT-5	250kcmil-3/0str	2/0str-6sol	.75	997 (U Type)
ELT-3	250kcmil-3/0str	250kcmil-3/0str	.900	997 (U Type)
ELT-6	500kcmil-300kcmil	250kcmil-3/0str	.875	1011 (U Type)

Tooling Information

Catalog Number	ILSCO			Burndy		
	ILC-12H-N ILC-12-N Die No. No. of Crimps	ILCB-12-N Die No. No. of Crimps	ILC-15H Die No. No. of Crimps	Y-35 Die Index No. of Crimps	Y-45 Die Index No. of Crimps	Y-46 Die Index No. of Crimps
ELT-1	ILD-C (1)	ILD-C (1)	- -	C (U Type) (1)	C (U Type) (1)	C (U Type) (1)
ELT-4	ILD-O (1)	ILD-O (1)	- -	O (U Type) (1)	O (U Type) (1)	O (U Type) (1)
ELT-2	ILD-O (1)	ILD-O (1)	- -	O (U Type) (1)	O (U Type) (1)	O (U Type) (1)
ELT-5	ILD-U997 (1)	ILD-U997 (1)	- -	997 (U Type) (1)	997 (U Type) (1)	997 (U Type) (1)
ELT-3	ILD-U997 (1)	ILD-U997 (1)	- -	997 (U Type) (1)	997 (U Type) (1)	997 (U Type) (1)
ELT-6	- -	- -	ILD-P1011 (2)	- -	1011 (U Type) (2)	1011 (U Type) (1)

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

See stuffer sheet for complete information on tooling.

Tested to UL 467, UL File E34440


TYPE SLU

Features

- Manufactured from electrolytic copper tubing and strip stock
- Compact design
- Range taking
- Re-usable
- UL Listed
- V-bottom collar

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Suitable for direct burial in earth or concrete
- Wires are wedged between arched pressure bar and collar establishing positive contact and firm permanent grip



Catalog Number	Wire Range Copper	Bolt Size	Dimensions							Hex Size
			C	D	E	F	G	H	T	
SLU-35DB	6-14 & List Comb. (A)	#10	13/64	7/16	15/32	1-3/16	7/32	3/8	3/4	Slot
SLU-70DB	2-8 & List Comb. (B)	1/4	17/64	1/2	21/32	1-17/32	1/4	1/2	1	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

(A) UL Listed wire combinations: (2) 14; (2) 12; (2) 10; (2) 8 and (4) 16

(B) UL Listed wire combinations: (2) 6 and (2) 8

Tested to UL 467, UL File E34440


TYPE XT

Features

- Manufactured from electrolytic copper tubing and strip stock
- Compact design
- Range taking
- Re-usable
- UL Listed

Benefits

- Provides maximum conductivity and strength
- Saves space and reduces installation time.
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Suitable for direct burial in earth or concrete



Catalog Number	Wire Range	Bolt Size	Dimensions							Hex Size
			C	D	E	F	G	H	T	
XT-6DB	6-14	#10	13/64	3/8	17/32	1	7/32	3/8	3/4	Slot
XT-4DB	4-14 & List Comb. (A)	1/4	17/64	1/2	5/8	1-1/8	1/4	1/2	5/8	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

(A) UL Listed wire combinations: (2) 14; (2) 12; (2) 10; (2) 8 and (4) 16

Tested to UL 467, UL File E34440

TYPE BGRC CGRC

Features

- Manufactured from cast bronze
- Supplied with stainless steel or silicone bronze hardware

Benefits

- Insures maximum strength and durability
- Suitable for direct burial in earth or concrete





Fig. 1



Fig. 2

Catalog Number	Figure Number	Ground Rod Size	Ground Rod Wire Range	Rebar Size	Rebar Wire Range	Dimensions		
						L	W	H
BGRC-48	1	1/2	2-10	-	-	7/8	3/4	1-1/4
BGRC-58	1	5/8	1/0-8	#5	1/0-8	1-1/32	29/32	1-13/32
BGRC-68	1	3/4	1/0-8	-	-	1	1	1-5/8
CGRC-38+	2	3/8	4-10	#3	4-10	1/2	11/16	1
CGRC-48	2	1/2	2-10	#4	2-10	9/16	27/32	1-3/16
CGRC-58	2	5/8	2-10	#5	4-10	9/16	15/16	1-9/32
CGRC-68	2	3/4	2-10	#6	4-10	9/16	1-1/16	1-9/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Plain copper finish.

+ Not UL Listed or CSA Certified

Tested to UL 467, UL File E34440



TYPE
SRC

Features

- Manufactured from bronze alloy
- Stainless steel bolt
- UL Listed for both copper clad and galvanized ground rods
- Range taking

Benefits

- Provides maximum strength and superior conductivity
- For direct burial
- Ensures reliability
- Reduces inventory requirement



Catalog Number	Ground Rod Size	Ground Rod Wire Range	Dimensions		
			L	W	H
SRC-1/0	3/8, 1/2, 5/8 3/4	10 sol - 1/0 str 8 sol - 1/0 str	13/16	1	1-1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E198108


TYPE GRC

Features

- Manufactured from seamless bronze tubing
- Supplied with silicon bronze screw
- Suitable for grounding and bonding in applications such as swimming pools and spas
- Copper conductor only

Benefits

- Provides maximum strength and superior conductivity
- Ground rod clamp is suitable for direct burial in earth or concrete



Catalog Number	Ground Rod Size	Ground Wire Range	Rebar Size	Rebar Wire Range	Dimensions	
					L	W
GRC-38	3/8	4-10	#3	4-10	5/8	5/8
GRC-58+	5/8	2-8	-	-	15/16	7/8
GRC-68	3/4, 5/8	2-8 for 3/4 rod, 1/0-8 for 5/8 rod	#5	1/0-8	1	1
GRC-75*	3/4	3/0-8	-	-	3/4	1-5/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Plain copper finish.

+ RUS Listed.

* Not UL Listed

Tested to UL 467, UL File E34440


TYPE RLT

Features

- Prefilled with oxide inhibitor and bagged
- Clearly marked with wire size and die index
- UL Listed and CSA Certified for direct burial in earth or concrete
- Range taking
- Manufactured from high strength copper alloy

Benefits

- Prevents oxides from forming
- Provides easy identification and tooling recommendation
- Ensures reliability
- Reduces inventory. Eight sizes cover a wire range of 500kcmil -#2
- Provides maximum conductivity and eliminates the possibility of corrosion



Catalog Number	Ground Rod Size	Wire Range	Die Index	Dimensions	
				H	L
RLT-2	1/2	2 (.292 Dia.) - 2/0 (.419 Dia.)	998/1011	1.94	.88
RLT-3	5/8	2 (.292 Dia.) - 2/0 (.419 Dia.)	998/1011	1.97	.88
RLT-4	3/4	2 (.292 Dia.) - 2/0 (.419 Dia.)	998/1011	2.19	.88
RLT-5	1/2	4/0 (.528 Dia.) - 250kcmil (.575 Dia.)	998/1011	1.94	.88
RLT-6	5/8	4/0 (.528 Dia.) - 250kcmil (.575 Dia.)	998/1011	2.14	.88
RLT-7	3/4	4/0 (.528 Dia.) - 250kcmil (.575 Dia.)	998/1011	2.19	.88
RLT-8	5/8	300kcmil (.630 Dia.) - 500kcmil (.813 Dia.)	998/1011	2.14	.88
RLT-9	3/4	300kcmil (.630 Dia.) - 500kcmil (.813 Dia.)	998/1011	2.44	.88

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587


TYPE BGC

Features

- Manufactured from cast brass
- Type BGC-DB supplied with stainless steel or silicon bronze hardware
- Copper conductor only

Benefits

- Provides maximum conductivity and strength
- BGC-1DB and BGC-2DB are suitable for direct burial in earth or concrete. Can be used to ground swimming pools and spas.



Catalog Number	Pipe Size	Ground Wire Range	Dimensions		
			L	W	H
BGC-1	1/2, 3/4, 1	2-10	2-9/32	1-7/16	1-1/2
BGC-2	1-1/4, 1-1/2, 2	2-10	3-9/16	2-1/4	2
BGC-1DB*	1/2, 3/4, 1	2-10	2-9/32	1-7/16	1-1/2
BGC-2DB*	1-1/4, 1-1/2, 2	2-10	3-8/16	2-1/4	2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Suitable for direct burial in earth or concrete. UL467

UL File E158587


TYPE BGDB

Features

- Manufactured from bronze alloy
- UL Listed for direct burial in earth or concrete
- Lay-In feature

Benefits

- Ensures maximum strength and superior conductivity
- Ensures reliability
- Reduces installation time



Catalog Number	Figure Number	Pipe Size	Rebar Size	Ground Rod Size	Ground Wire Range	Screw Material	Dimensions	
							L	W
BGC-2T-DB*	1	1/2-1	3/8-1	1/2-1	2str-10sol	silicon bronze	2-3/4	2-1/4
BGC-2P-DB*	2	1/2-1	3/8-1	1/2-1	2str-10sol	silicon bronze	2-3/4	2-1/4
BGC-2PS-DB+	3	1/2-1	3/8-1	1/4-1	2str-10sol 2 #8sol	stainless steel	2-1/4	2-1/4
BGC-4/0P-DB=##	4	1/2-1	3/8-1	1/2-1	4/0-8str	stainless steel	3	2-1/4
BGC-4/0S-DB=##	5	1/2-1	3/8-1	1/2-1	4/0-8str	stainless steel	2-3/4	2-1/4

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* UL File E207816

+ UL File E198108

= UL File E178441

Not RoHS compliant


TYPE SPS

Features

- Range taking
- Re-usable
- UL 486A/B and UL 467 Listed
- For grounding of steel structures, fence posts and tapping cables from bus bar
- For copper to copper connections

Benefits

- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Ensures reliability
- Flexibility in the field



Catalog Number	Conductor Range AWG MM ²				Maximum Diameter Range	Stud Size	Dimensions				
	Stranded		Solid				A	B	C	D	E
	Max.	Min.	Max.	Min.							
SPSS-0	8	12 (4mm ²)	8 (10mm ²)	12 (4mm ²)	.146-.080	1/4-20 x 1/2	11/16	1/2	55/64	15/32	1/2
SPSS-1	7 (10mm ²)	10 (6mm ²)	6 (10mm ²)	10 (6mm ²)	.170-.102	1/4-20 x 1/2	13/16	1/2	55/64	15/32	21/32
SPSS-2	5 (16mm ²)	10 (6mm ²)	4 (16mm ²)	10 (6mm ²)	.217-.102	5/16-18 x 5/8	15/16	5/8	53/64	17/32	23/32
SPSS-3	3 (25mm ²)	10 (6mm ²)	2 (35mm ²)	10 (6mm ²)	.271-.102	3/8-16 x 5/8	1/2	5/8	61/64	5/8	25/32
SPSS-4	1 (35mm ²)	8 (6mm ²)	2 (35mm ²)	8 (10mm ²)	.332-.128	3/8-16 x 5/8	1-1/16	5/8	61/64	11/16	7/8
SPSS-5	1/0 (50mm ²)	2 (35mm ²)	2 (35mm ²)	-	.385-.258	1/2-13 x 3/4	1-1/4	3/4	1-5/64	3/4	15/16
SPSS-6	2/0 (70mm ²)	2 (35mm ²)	2 (35mm ²)	-	.443-.258	1/2-13 x 3/4	1-13/32	3/4	1-5/64	7/8	1-1/16
SPSS-8	4/0 (95mm ²)	1 (35mm ²)	-	-	.570-.289	5/8-11 x 1	1-9/16	1	1-19/64	1	1-5/16
SPSS-9	350 (150mm ²)	1/0 (70mm ²)	-	-	.715-.373	5/8-11 x 1	2	1-1/4	1-19/64	1-5/16	1-11/16
SPSS-10	500 (240mm ²)	3/0 (95mm ²)	-	-	.840-.464	3/4-10 x 1-1/4	2-1/4	1-3/4	1-31/64	1-1/2	1-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587




TYPE SPS

Features

- Range taking
- Re-usable
- UL 486A/B and UL 467 Listed
- For grounding of steel structures, fence posts and tapping cables from bus bar
- For copper to copper connections

Benefits

- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Ensures reliability
- Flexibility in the field



Catalog Number	Conductor Range AWG MM ²				Maximum Diameter Range	Stud Size	Dimensions				
	Stranded		Solid				A	B	C	D	E
	Max.	Min.	Max.	Min.							
SPSL-0	8	12 (4mm ²)	8 (10mm ²)	12 (4mm ²)	.146-.080	1/4-20 x 1	11/16	1	55/64	15/32	1/2
SPSL-1	7 (10mm ²)	10 (6mm ²)	6 (10mm ²)	10 (6mm ²)	.170-.102	1/4-20 x 1	13/16	1	55/64	15/32	21/32
SPSL-2	5 (16mm ²)	10 (6mm ²)	4 (16mm ²)	10 (6mm ²)	.217-.102	5/16-18 x 1	15/16	1	53/64	17/32	23/32
SPSL-3	3 (25mm ²)	10 (6mm ²)	2 (35mm ²)	10 (6mm ²)	.271-.102	3/8-16 x 1-1/8	1/2	1-1/8	61/64	5/8	25/32
SPSL-4	1 (35mm ²)	8 (6mm ²)	2 (35mm ²)	8 (10mm ²)	.332-.128	3/8-16 x 1-1/8	1-1/16	1-1/8	61/64	11/16	7/8
SPSL-5	1/0 (50mm ²)	2 (35mm ²)	2 (35mm ²)	-	.385-.258	1/2-13 x 1-1/4	1-1/4	1-1/4	1-5/64	3/4	15/16
SPSL-6	2/0 (70mm ²)	2 (35mm ²)	2 (35mm ²)	-	.443-.258	1/2-13 x 1-1/4	1-13/32	1-1/4	1-5/64	7/8	1-1/16
SPSL-8	4/0 (95mm ²)	1 (35mm ²)	-	-	.570-.289	5/8-11 x 1-1/2	1-9/16	1-1/2	1-19/64	1	1-5/16
SPSL-10	500 (240mm ²)	3/0 (95mm ²)	-	-	.840-.464	3/4-10 x 1-3/4	2-1/4	1-1/2	1-31/64	1-1/2	1-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587


TYPE SPD

Features

- Range taking
- Re-usable
- UL 486A/B and UL 467 Listed
- For grounding of steel structures, fence posts and tapping cables from bus bar
- For copper to copper connections

Benefits

- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Ensures reliability
- Flexibility in the field



Catalog Number	Conductor Range AWG MM ²				Maximum Diameter Range	Stud Size	Dimensions				
	Stranded		Solid				AA	B	C	D	E
	Max.	Min.	Max.	Min.							
SPDS-0	8	12 (4mm ²)	8 (10mm ²)	12 (4mm ²)	.146-.080	1/4-20 x 1/2	13/16	1/2	55/64	15/32	1/2
SPDS-1	7 (10mm ²)	10 (6mm ²)	6 (10mm ²)	10 (6mm ²)	.170-.102	1/4-20 x 1/2	31/32	1/2	55/64	15/32	21/32
SPDS-2	5 (16mm ²)	10 (6mm ²)	4 (16mm ²)	10 (6mm ²)	.217-.102	5/16-18 x 5/8	1-1/8	5/8	53/64	17/32	23/32
SPDS-3	3 (25mm ²)	10 (6mm ²)	2 (35mm ²)	10 (6mm ²)	.271-.102	3/8-16 x 5/8	1-1/4	5/8	61/64	5/8	25/32
SPDS-4	1 (35mm ²)	8 (6mm ²)	2 (35mm ²)	8 (10mm ²)	.332-.128	3/8-16 x 5/8	1-3/8	5/8	61/64	11/16	7/8
SPDS-5	1/0 (50mm ²)	2 (35mm ²)	2 (35mm ²)	-	.385-.258	1/2-13 x 3/4	1-19/32	3/4	1-5/64	3/4	15/16
SPDS-6	2/0 (70mm ²)	2 (35mm ²)	2 (35mm ²)	-	.443-.258	1/2-13 x 3/4	1-13/16	3/4	1-5/64	7/8	1-1/16
SPDS-8	4/0 (95mm ²)	1 (35mm ²)	-	-	.570-.289	5/8-11 x 1	2-1/16	1	1-19/64	1	1-5/16
SPDS-9	350 (150mm ²)	1/0 (70mm ²)	-	-	.715-.373	5/8-11 x 1	2-3/4	1-1/4	1-19/64	1-5/16	1-11/16
SPDS-10	500 (240mm ²)	3/0 (95mm ²)	-	-	.840-.464	3/4-10 x 1-1/4	3-1/8	1-3/4	1-31/64	1-1/2	1-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587




TYPE SPD

Features

- Range taking
- Re-usable
- UL 486A/B and UL 467 Listed
- For grounding of steel structures, fence posts and tapping cables from bus bar
- For copper to copper connections

Benefits

- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Ensures reliability
- Flexibility in the field



Catalog Number	Conductor Range AWG MM ²				Maximum Diameter Range	Stud Size	Dimensions				
	Stranded		Solid				AA	B	C	D	E
	Max.	Min.	Max.	Min.							
SPDL-0	8	12 (4mm ²)	8 (10mm ²)	12 (4mm ²)	.146-.080	1/4-20 x 1	13/16	1	55/64	15/32	1/2
SPDL-1	7 (10mm ²)	10 (6mm ²)	6 (10mm ²)	10 (6mm ²)	.170-.102	1/4-20 x 1	31/32	1	55/64	15/32	21/32
SPDL-2	5 (16mm ²)	10 (6mm ²)	4 (16mm ²)	10 (6mm ²)	.217-.102	5/16-18 x 1	1-1/8	1	53/64	17/32	23/32
SPDL-3	3 (25mm ²)	10 (6mm ²)	2 (35mm ²)	10 (6mm ²)	.271-.102	3/8-16 x 1-1/8	1-1/4	1-1/8	61/64	5/8	25/32
SPDL-4	1 (35mm ²)	8 (6mm ²)	2 (35mm ²)	8 (10mm ²)	.332-.128	3/8-16 x 1-1/8	1-3/8	1-1/8	61/64	11/16	7/8
SPDL-5	1/0 (50mm ²)	2 (35mm ²)	2 (35mm ²)	-	.385-.258	1/2-13 x 1-1/4	1-19/32	1-1/4	1-5/64	3/4	15/16
SPDL-6	2/0 (70mm ²)	2 (35mm ²)	2 (35mm ²)	-	.443-.258	1/2-13 x 1-1/4	1-13/16	1-1/4	1-5/64	7/8	1-1/16
SPDL-8	4/0 (95mm ²)	1 (35mm ²)	-	-	.570-.289	5/8-11 x 1-1/2	2-1/16	1-1/2	1-19/64	1	1-5/16
SPDL-9	350 (150mm ²)	1/0 (70mm ²)	-	-	.715-.373	5/8-11 x 1-1/2	2-3/4	1-1/2	1-19/64	1-5/16	1-11/16
SPDL-10	500 (240mm ²)	3/0 (95mm ²)	-	-	.840-.464	3/4-10 x 1-3/4	3-1/8	1-1/2	1-31/64	1-1/2	1-7/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587


TYPE TTGC

Features

- Manufactured from bronze
- Eye bolt on TTGC2 rotates to accommodate cable in vertical or horizontal direction
- Range taking
- Stud fits all standard EEI-NEMA distribution transformers

Benefits

- Provides maximum strength and superior conductivity
- Flexibility
- Permits inventories to be kept to a minimum
- Reliability



Catalog Number	Conductor Range		Stud Thread Size UNC - 2A	Dimensions		
	Max.	Min.		A	B	C
TTGC2	2/0	8 sol	1/2-13	1-51/64	1-9/64	1-21/32
TTGC3	1 str	10 sol	1/2-13	1-3/8	1-3/64	1-9/16
TTGC4+	1 str	10 sol	1/2-13	1-1/4	7/8	1-3/8
TTGC2TN+	2/0	8 sol	1/2-13	1-51/64	1-9/64	1-21/32
TTGC3TN*	1 str	10 sol	1/2-13	1-3/8	1-3/64	1-9/16
TTGC4TN*	1 str	10 sol	1/2-13	1-1/4	7/8	1-3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

+ RUS Listed

* Tin Plated




TYPE GUB

Features

- Components are cast or forged from copper alloy
- Specially designed spacer
- Range taking
- Re-usable
- UL 467 Listed for direct burial and CSA Certified

Benefits

- Provides maximum conductivity
- Affords more positive contact area
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Ensures reliability



Catalog Number	Conductor		Nominal Rod		IPS Pipe Size		Dimensions		
	Max.	Min.	Max.	Min.	Max.	Min.	A	B	C
GUB-1	4	8	3/4	5/8	3/8	-	2-13/16	1-9/16	2-1/4
GUB-2	2/0	4	3/4	5/8	3/8	-	2-13/16	1-9/16	2-1/4
GUB-3	250kcmil	2/0	3/4	5/8	3/8	-	2-13/16	1-9/16	2-1/4
GUB-4	4	8	1	7/8	3/4	1/2	2-3/4	1-9/16	2-5/8
GUB-5	2/0	4	1	7/8	3/4	1/2	2-3/4	1-9/16	2-5/8
GUB-6	250kcmil	2/0	1	7/8	3/4	1/2	2-3/4	1-9/16	2-5/8
GUB-7	4	8	1-1/4	1-1/8	1	-	3-5/16	1-9/16	2-3/4
GUB-8	2/0	4	1-1/4	1-1/8	1	-	3-5/16	1-9/16	2-3/4
GUB-9	4	8	1-1/2	1-3/8	1-1/4	-	3-7/16	1-9/16	2-15/16
GUB-10	2/0	4	1-1/2	1-3/8	1-1/4	-	3-7/16	1-9/16	2-15/16
GUB-11	250kcmil	2/0	1-1/2	1-3/8	1-1/4	-	3-7/16	1-9/16	2-15/16
GUB-12	4	8	1-7/8	1-5/8	1-1/2	-	3-15/16	1-9/16	3-3/16
GUB-13	2/0	4	1-7/8	1-5/8	1-1/2	-	3-15/16	1-9/16	3-3/16
GUB-14	250kcmil	2/0	1-7/8	1-5/8	1-1/2	-	3-15/16	1-9/16	3-3/16
GUB-15	4	8	2-3/8	2	2	-	4-7/16	1-9/16	3-11/16
GUB-16	2/0	4	2-3/8	2	2	-	4-7/16	1-9/16	3-11/16
GUB-17	250kcmil	2/0	2-3/8	2	2	-	4-7/16	1-9/16	3-11/16
GUB-18	2/0	4	2-7/8	2-1/2	2-1/2	-	4-15/16	1-9/16	4-3/16
GUB-19	250kcmil	2/0	2-7/8	2-1/2	2-1/2	-	4-15/16	1-9/16	4-3/16
GUB-20	2/0	4	3-1/2	3	3	-	5-9/16	1-9/16	4-13/16
GUB-21	250kcmil	2/0	3-1/2	3	3	-	5-9/16	1-9/16	4-13/16
GUB-22	2/0	4	4	3-1/2	3-1/2	-	6-1/16	1-9/16	5-1/2
GUB-23	2/0	4	4-1/2	4	4	-	6-5/16	1-9/16	5-11/16
GUB-24	250kcmil	2/0	4-1/2	4	4	-	6-5/16	1-9/16	5-11/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E158587

ILSCO Bronze Waterpipe Ground Clamp




TYPE GPL3

Features

- Range taking
- Cable clamp rotates
- Silicon bronze hardware
- UL 467 Listed

Benefits

- Inventory reduction
- Allows ground conductor to be attached parallel to pipe or at 90°
- Corrosion resistant
- Suitable for direct burial in earth or concrete



Catalog Number	Ground Wire Range	IPS Pipe Size	Dimensions		Fits Pipe O.D. Range
			W	H	
GPL3902BU	4 - 4/0	1/2 - 1	3.250	3.500	.840 - 1.32
GPL3903BU	4 - 4/0	1-1/4 - 2	4.250	4.000	1.66 - 2.38
GPL3904BU	4 - 4/0	2-1/2 - 3-1/2	5.000	6.500	2.88 - 4.00
GPL3905BU	4 - 4/0	4 - 5	7.500	7.500	4.50 - 5.56
GPL3906BU	4 - 4/0	6	8.625	8.500	6.62
GPL3907BU	4 - 4/0	8	10.625	10.000	8.62
GPL3908BU	4 - 4/0	10	12.750	12.000	10.75
GPL3909BU	4 - 4/0	12	14.750	14.000	12.75

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL File E34440



TYPE CGBL

Features

- Lay-in feature
- Manufactured from high strength copper
- Stainless steel hardware

Benefits

- Provides ease of installation of continuous loop grounding conductor
- Suitable for direct burial and for use with copper conductors
- Resists oxidation and corrosion in earth or concrete




Fig. 1



Fig. 2

Catalog Number	Figure Number	Ground Wire Range	Bolt Size	Dimensions							Screw Type
				C	D	E	F	G	H	T	
GBL-4DB	1	4-14	10	.218	.680	.470	1.150	.190	.375	.825	Slot
GBL-4DB-14	1	4-14	1/4	.265	.680	.470	1.150	.210	.472	.825	Slot
GBL-4DBT*	1	4-14	10	.218	.680	.470	1.150	.190	.375	.825	Slot
GBL-4DBT-14*	1	4-14	1/4	.265	.680	.470	1.150	.210	.472	.825	Slot
GBL-4DBTH*	2	4-14	10	.218	.680	.470	1.150	.190	.375	.825	Hex
GBL-4DBTH-14*	2	4-14	1/4	.265	.680	.470	1.150	.210	.472	.825	Hex

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 467, UL File E34440

* T indicates tin plating

Mounting hardware kits available, consult ILSCO

SILICONE TAPE



316

HEAVY WALL



317

HEAVY WALL END CAPS



318

MEDIUM WALL




319

THIN WALL



320

THIN WALL BULK REELS



321

HEAT GUN



322

TYPE MIS

Features

- Self fusing
- 700 PSI tensile strength
- Insulates 8,000 volts per layer
- Withstands 500° F
- Flexible at -85° F
- Mil-Spec-I - 46852

Wrap 'N Seal Silicone Tape is a self-fusing silicone tape suitable for many applications, including wrapping electrical connections and wire harnesses. The silicone tape only bonds to itself with no adhesive mess. It conforms to any shape and withstands UV rays, acids and fuels. Once wrapped, it bonds immediately, forming a permanent air and watertight seal. It becomes permanently fused in 24 hours.



Catalog Number	Color	W	L
99200	White	1"	20'
99201	Red	1"	20'
99202	Black	1"	20'
99205	Green	1"	20'
99206	Blue	1"	20'
99207	Yellow	1"	20'
99208	Clear	1"	20'
99209	Glow in the Dark	1"	20'
99211	Gray	1"	20'
99212	Orange/Red	1"	20'

TYPE

Heavy Wall

Features

- 3:1 shrink ratio
- UL Listed 486D and CSA Certified for 600 volts
- Inner adhesive liner
- Flame retardant

Benefits

- Provides a wide range of coverage when used on connectors and cable
- Ensures reliability for insulating terminations and splices
- Melts to form intimate contact with part to seal out elements and produce a watertight seal suitable for above ground, direct burial and underwater applications
- Meets Mil Spec 23053/15 rigid requirements for flame retardancy



Catalog Number	Wire Range	Exp. Id.	Rec. Id.	Recovered Wall Thickness	L
21106-B3*	6-14	0.400	0.150	0.060	6"
21112-B3*	6-14	0.400	0.150	0.060	12"
21206-B3	1-8	0.750	0.220	0.090	6"
21209-B3	1-8	0.750	0.220	0.090	9"
21212-B3	1-8	0.750	0.220	0.090	12"
21230	1-8	0.750	0.220	0.090	30"
21406-B2	4/0-2	1.100	0.375	0.120	6"
21409-B2	4/0-2	1.100	0.375	0.120	9"
21412-B2	4/0-2	1.100	0.375	0.120	12"
21448	4/0-2	1.100	0.375	0.120	48"
21609-B2	400kcmil-4/0	1.500	0.500	0.140	9"
21612-B2	400kcmil-4/0	1.500	0.500	0.140	12"
21648	400kcmil-4/0	1.500	0.500	0.140	48"
21709-B	1000kcmil-500kcmil	2.000	0.750	0.155	9"
21712-B	1000kcmil-500kcmil	2.000	0.750	0.155	12"
21748	1000kcmil-500kcmil	2.000	0.750	0.155	48"

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*UL Listed wire range 12 - 6.

UL File E158587

TYPE
**Heavy
Wall**

Features

- 3:1 shrink ratio
- Inner adhesive liner
- Rated for 600 volts

Benefits

- Provides a wide range of coverage when used on connectors and cable
- Melts to form intimate contact with part to seal out elements and produce a watertight seal suitable for above ground, direct burial and underwater applications
- Ensures reliability



Catalog Number	Wire Range	Exp. Id.	Rec. Id.	Recovered Wall Thickness	L
23081-B2	4/0-8	.75	0.22	.08	3.5"
23125-B2	500kcmil-4/0	1.30	0.43	.08	4.5"
23210-B2	1000kcmil-400kcmil	2.05	0.75	.08	4.5"

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE
Medium Wall

Features

- Clear tubing
- 2.5:1 shrink ratio
- Inner adhesive liner
- Rated for 600 volts

Benefits

- Provides convenient see through capability which gives assurance that termination was made properly after shrink process has been performed
- Provides a wide range of coverage when used on connectors and cable
- Melts to form intimate contact with part to seal out elements and produce a watertight seal suitable for above ground, direct burial and underwater applications
- Ensures reliability



Catalog Number	Wire Range	Exp. Id.	Rec. Id.	Recovered Wall Thickness	L
22106-B3	14-18	0.290	0.080	0.047	6"
22112-B3	14-18	0.290	0.080	0.047	12"
22206-B3	8-12	0.375	0.135	0.050	6"
22212-B3	8-12	0.375	0.135	0.050	12"
22306-B3	2-8	0.500	0.195	0.055	6"
22312-B3	2-8	0.500	0.195	0.055	12"
22406-B2	4/0-1	1.000	0.400	0.075	6"
22412-B2	4/0-1	1.000	0.400	0.075	12"

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE

Thin Wall

Features

- 2:1 shrink ratio
- UL Recognized and CSA Certified
- Rated for 600 volts
- Convenient disk dispenser

Benefits

- Provides a wide range of coverage when used on connectors and cable
- Assures product reliability for insulating and protecting terminations and splices
- Ensures reliability
- Protects tubing from damage and keeps it clean



Catalog Number	Wire Range	Exp. Id.	Rec. Id.	Recovered Wall Thickness	L
24001-B10	26-34	0.046	0.023	0.016	6"
24002-B10	24-30	0.063	0.031	0.017	6"
24003-B10	22-28	0.093	0.046	0.020	6"
24004-B10	20-26	0.125	0.062	0.020	6"
24005-B10	18-22	0.187	0.093	0.020	6"
24006-B10	14-16	0.250	0.125	0.025	6"
24007-B5	10-12	0.312	0.156	0.025	6"
24008-B5	6-8	0.375	0.187	0.025	6"
24009-B5	4-6	0.500	0.250	0.025	6"
24010-B5	2/0-2	0.750	0.375	0.030	6"
24011-B5	4/0-1	1.000	0.500	0.035	6"
24999-B12+	-	-	-	-	-
25001	26-34	0.046	0.023	0.016	96" Disk
25002	24-30	0.063	0.031	0.017	96" Disk
25003	22-28	0.093	0.046	0.020	96" Disk
25004	20-26	0.125	0.062	0.020	96" Disk
25005	18-22	0.187	0.093	0.020	96" Disk
25006	14-16	0.250	0.125	0.025	96" Disk
25007	10-12	0.3112	0.156	0.025	96" Disk
25008	6-8	0.375	0.187	0.025	96" Disk
25009	4-6	0.500	0.250	0.025	96" Disk
25010	2/0-2	0.750	0.375	0.030	96" Disk
25011	4/0-1	1.000	0.500	0.035	96" Disk

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 + 24999-B12 contains 3 ea. 24005, 24006, 24008, 24009
 UL File E158587

TYPE


Thin Wall

Features

- 2:1 shrink ratio
- UL Recognized and CSA Certified
- Rated for 600 volts

Benefits

- Provides a wide range of coverage when used on connectors and cable
- Assures product reliability for insulating and protecting terminations and splices
- Ensures reliability



Catalog Number	Wire Range	Exp. Id.	Rec. Id.	Recovered Wall Thickness	Cut Length
26001	26-34	0.046	0.023	0.016	1000'
26002	24-30	0.063	0.031	0.017	1000'
26003	22-28	0.093	0.046	0.020	500'
26004	20-26	0.125	0.062	0.020	500'
26005	18-22	0.187	0.093	0.020	200'
26006	14-16	0.250	0.125	0.025	200'
26007	10-12	0.312	0.156	0.025	500'
26008	6-8	0.375	0.187	0.025	200'
26009	4-6	0.500	0.250	0.025	200'
26010	2/0-2	0.750	0.375	0.030	200'
26011	4/0-1	1.000	0.500	0.035	200'

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE
Electric Heat Gun

Features

- Two temperature settings 750F and 1100F
- Three way switch OFF/HI/LO
- Built-in fold down stand
- 1200 Watt 120 V AC
- Heat deflector
- Impact resistant
- Six foot cord

Benefits

- Provides versatility in applying recommended heat, deliverable in seconds
- Aids in producing proper air flow from heat gun
- Provides hands free operation
- Provides high output of air and heat
- Allows for concentration of heat for rapid heat shrink process
- Provides extra durability in harsh environments
- Provides operator convenience



Catalog Number	Description
27001	Heat Gun, 11 Disks Thin Wall Heat Shrink
94502	Electric Heat Gun 120v
94504	Replacement Adaptor for 94502

IDTB-6-LIO  324		ILCB-12-LIO  325		ILC-10-N  326	
MT-25  327	94285  328	ND-58  329	ND-60  330	ILC-12-N  331	ILC-12H-N  332
IDT-6  333	IDT-6H  334	ILC-15H  335	5ACR  336	FP-1  337	HH-10N  338
COMPRESSION INDEX 339 - 345		COMPRESSION DIES AND ADAPTORS  346 - 348		TOOL ACCESSORIES  349	
		94130  350		94145  351	
		WS-1  351		CTR  351	
				TS  352	
				TW  352	
				WR  352	
				94502  353	

TYPE IDTB-6-LIO

Features

- 18 Volt battery
- Lithium-Ion technology
- 70% more crimp cycles than Ni-Cad
- Battery powered
- Dieless crimping operation
- Ram automatically retracts when crimp cycle is complete
- Automatic retraction stop which retracts the ram just enough to get ready for the next cycle
- Flip top head
- Head rotates 360 degrees
- Pistol grip design
- Molded-in rubber grip
- Quick charge 120 volt charger
- Two 18 volt batteries included
- LED work light
- Diagnostics built in

Benefits

- Powerful, quick crimp, saves time
- Faster, longer life, quicker charge, lighter
- More crimps between charges
- Portable, can be used in any location
- Versatility, works on large range of wire sizes
- Confirms crimp is complete
- Saves time and energy
- Easy connector loading and unloading
- Adapts to variable cable directions
- Easy to handle and operate
- Provides non-slip comfortable grip
- Less down time
- Convenient, no waiting
- Lights up dark enclosures/cabinets
- Can retrieve tool statistics (ie: # of crimps)

Specifications

Force developed: 6.2 Tons
 Weight: 10.8 lbs.
 Overall Length: 15-1/2"
 Connector Range: 750kcmil-#6



For Use with

Aluminum Connectors	Copper Connectors
ACL, ACN Series thru 750kcmil	CLN4, CLN9, CLND,
2ACL, 2ACN Series thru 750kcmil	CLNF, CLNN, CLNS,
AS Series thru 750kcmil	CLNU, CLW4, CLW9,
IACL Series thru 500kcmil	CLWD, CLWF, CLWN,
2IACL Series thru 500kcmil	CLWS, CSN4, CSN9,
	CSND, CSNF, CSNN,
	CSNS, CSW4, CSW9,
	CSWD, CSWF, CSWN,
	CSWS 750kcmil thru 6

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Includes:

- 2 Batteries
- 1 Battery Charger
- Durable Plastic Carrying Case
- Instruction Manual

ILSCO Battery Powered Crimping Tool



TYPE ILCB-12-LIO

Features

- 18 Volt battery
- Lithium-Ion technology
- 70% more crimp cycles than Ni-Cad
- Battery powered
- Accepts IlSCO standard "U" dies
- Ram automatically retracts when crimp cycle is complete
- Automatic retraction stop which retracts the ram just enough to get ready for the next cycle
- Head rotates 360 degrees
- Pistol grip design
- Molded-in rubber grip
- Quick charge 120 volt charger
- Two 18 volt batteries included
- LED work light
- Diagnostics built in

Benefits

- Powerful, quick crimp, saves time
- Faster, longer life, quicker charge, lighter
- More crimps between charges
- Portable, can be used in any location
- Precision crimps
- Confirms crimp is complete
- Saves time and energy
- Adapts to variable cable directions
- Easy to handle and operate
- Provides non-slip comfortable grip
- Less down time
- Rotate batteries, keep working on job
- Lights up dark enclosures/cabinets
- Can retrieve tool statistics (ie: # of crimps)

Specifications

Force developed:	12 Tons
Weight:	14.9 lbs.
Overall length:	16-3/4"
Jaw Opening:	1.65"
Connector Range:	1000kcmil-#6



For Use with*

Aluminum Connectors	Copper Connectors
CPM Series	CLN4, CLN9, CLND,
ACM Series	CLNF, CLNN, CLNS,
ACO Series	CLNU, CLW4, CLW9,
ACO-90 Series	CLWD, CLWF, CLWN,
ACL, ACN Series thru 750kcmil	CLWS, CSN4, CSN9,
2ACL, 2ACN Series thru 750kcmil	CSND, CSNF, CSNN,
AS Series thru 750kcmil	CSNS, CSW4, CSW9,
AH 1-4	CSWD, CSWF, CSWN,
HT Series	CSWS 1000kcmil thru 8
IACL Series thru 750kcmil	
2IACL Series thru 750kcmil	

*See page 350 for required compression dies
All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Includes:

- 2 Batteries
- 1 Battery Charger
- Durable Plastic Carrying Case
- Instruction Manual



TYPE
ILC-10-N

Features

- Rotatable die
- Additional die affixed to frame
- Crimp cavities are color coded to industry standards
- Ratchet control mechanism
- Heat treated frame and dies
- Long, molded handles

Benefits

- Crimps #2, #4, #6 and #8 copper compression connectors
- Crimps 1/0 and #1 copper compression connectors
- Reduces the possibility of improper die selection
- Assures a complete crimp
- Dependable, long lasting tool
- Ergonomic design to reduce hand stress

Specifications

Weight: 1-3/8 lbs.
 Overall Length: 11"
 Width: 3.75"
 Jaw Opening: .5"
 Conductor Range: 1/0-8 CU



For Use with

Copper Connectors

CLN4, CLN9, CLND,

CLNF, CLNN, CLNS,

CLNU, CLW4, CLW9,

CLWD, CLWF, CLWN,

CLWS, CSN4, CSN9,

CSND, CSNF, CSNN,

CSNS, CSW4, CSW9,

CSWD, CSWF, CSWN,

CSWS 1/0 thru 8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE MT-25

Features

- Dieless single indent compressor
- Steel adjusting knob
- UL Listed terminals and splices
- Broad wire range
- Mounting hole for bench mounting applications

Benefits

- Reduces installed cost by having no separate dies to purchase, change or lose
- Provides fast and easy setting. Simply align the line on the die nest with the wire size gauge for proper crimping results.
- Ensures reliability. ILSCO's standard line of connectors are UL Listed when crimped with the MT-25 tool
- Convenience

Specifications

Length: 22.65"
 Weight: 6 lbs.
 Depth: 4.86"
 Width: 1.12"
 Conductor Range: 250kcmil-8 CU
 4/0-8 AL



For Use with

Aluminum Connectors	Copper Connectors
ACL, ACN 4/0-8	CLN4, CLN9, CLND,
2ACL, 2ACN 4/0-8	CLNF, CLNN, CLNS,
AS 4/0-8	CLNU, CLW4, CLW9,
	CLWD, CLWF, CLWN,
	CLWS, CSN4, CSN9,
	CSND, CSNF, CSNN,
	CSNS, CSW4, CSW9,
	CSWD, CSWF, CSWN,
	CSWS 250kcmil thru 8
	CCL, CRAM

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE 94285

Features


- ① • Controlled cycle ratchet mechanism
- ② • Built in rotatable dies
- ③ • Comfort grip handles
- UL Listed terminals and splices

Benefits

- Acts as a quality control device, once a crimp is started, the tool will not open until it is completed. (Tool has emergency release mechanism.)
- No separate dies to purchase or lose
- Helps ease fatigue with continuous use
- Ensures reliability. ILSCO's standard line of connectors are UL Listed when crimped with the 94285 tool

Specifications

Length: 25-1/4"
 Weight: 6.1 lbs.
 Conductor Range: 250kcmil-8 CU
 3/0-8 AL



For Use with

Aluminum Connectors	Copper Connectors
ACL, ACN 3/0-8	CLN4, CLN9, CLND,
2ACL, 2ACN 3/0-8	CLNF, CLNN, CLNS,
AS 3/0-8	CLNU, CLW4, CLW9,
	CLWD, CLWF, CLWN,
	CLWS, CSN4, CSN9,
	CSND, CSNF, CSNN,
	CSNS, CSW4, CSW9,
	CSWD, CSWF, CSWN,
	CSWS 250kcmil thru 8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)


TYPE ND-58

- Features**
- ① • High strength, butting, forged steel jaw
 - ② • Two permanent die grooves
 - ③ • Large diameter hardened steel bolts
 - ④ • Spring loaded positive lock die retainer buttons
 - ⑤ • Orange alignment grooves
 - ⑥ • PTFE[®] impregnated steel backed bronze bushings
 - ⑦ • Over center cam action
 - ⑧ • Adjustment screws
 - ⑨ • Handle butt stops and heat shrink tubing
 - ⑩ • High quality clear hickory handles
 - ⑪ • Bent handles and anti-slip handle grips

- Benefits**
- Assures proper crimps
 - No additional dies required for "0" and "D₃" size tap connectors. The "D₃" groove accommodates the complete line of type "W-" die inserts.
 - Provides increased strength and greater bearing area
 - Allows fast, easy, one-hand die insertion. No lost dies.
 - Allows easy visual field check for proper tool adjustment
 - Over 90,000 crimps provided with Teflon impregnated steel backed bronze bushings
 - Assures full crimp force
 - Easy tool adjustment with allen wrench screws
 - Operator protection provided with butt stops and heat shrink tubing
 - Long life expectancy provided with select clear hickory handles and light weight high strength aluminum alloy castings
 - Easier tool operation is provided with bent handles and anti-slip grips

Specifications

Crimp Force: 9,000 lbs.
 Length: 25-3/8"
 Weight: 9 lbs.



For Use with

Aluminum Connectors	Copper Connectors
PICS Series	GGA-1
P840 Series	GGC-1
UCL 1/0-4	ULT 4-7
UCS 1/0-4	
HT Series	
AH 1-4	


TYPE ND-60

- Features**
- ① • High strength, butting, forged steel jaw
 - ② • Two permanent die grooves
 - ③ • Large diameter hardened steel bolts
 - ④ • Spring loaded positive lock die retainer buttons
 - ⑤ • Orange alignment grooves
 - ⑥ • PTFE[®] impregnated steel backed bronze bushings
 - ⑦ • Over center cam action
 - ⑧ • Adjustment screws
 - ⑨ • Handle butt stops and heat shrink tubing
 - ⑩ • High quality clear hickory handles
 - ⑪ • Bent handles and anti-slip handle grips

- Benefits**
- Assures proper crimps
 - No additional dies required for "BG" and "D₃" size tap connectors. The "D₃" groove accommodates the complete line of type "W." die inserts.
 - Provides increased strength and greater bearing area
 - Allows fast, easy, one-hand die insertion. No lost dies.
 - Allows easy visual field check for proper tool adjustment
 - Over 90,000 crimps provided with Teflon impregnated steel backed bronze bushings
 - Assures full crimp force
 - Easy tool adjustment with allen wrench screws
 - Operator protection provided with butt stops and heat shrink tubing
 - Long life expectancy provided with select clear hickory handles and light weight high strength aluminum alloy castings
 - Easier tool operation is provided with bent handles and anti-slip grips

Specifications

Crimp Force: 9,000 lbs.
Length: 25-3/8"
Weight: 9 lbs.



For Use with

Aluminum Connectors	Copper Connectors
PICS Series	GGA-1
P840 Series	GGC-1
UCL 1/0-4	ULT 4-7
UCS 1/0-4	
HT Series	
AH 1-4	

TYPE ILC-12-N

Features

- Head tested to 50,000 crimp cycles
- Accepts industry standard "U" dies
- Light head - 13.2 lbs.
- Two speed pump
- Ram automatically retracts when crimp cycle is complete
- Head rotates 360 degrees

Benefits

- Durable and dependable
- Flexibility and economy
- Easy to hold, less tiring for numerous crimps
- Reduces cycle time
- Confirms crimp was completed
- Convenience when working in tight areas

Specifications

Force developed: 12 Tons
 Operating pressure: 10,000 PSI
 Weight: 13.2 lbs.
 Overall length: 21-1/2"
 Jaw Opening: 1.65"
 Conductor Range: 1000kcmil-#8



For Use with*	
Aluminum Connectors	Copper Connectors
CPM Series	CLN4, CLN9, CLND,
ACM Series	CLNF, CLNN, CLNS,
ACO Series	CLNU, CLW4, CLW9,
ACO-90 Series	CLWD, CLWF, CLWN,
ACL, ACN 750kcmil-8	CLWS, CSN4, CSN9,
2ACL, 2ACN 750kcmil-1/0	CSND, CSNF, CSNN,
AS 750kcmil-8	CSNS, CSW4, CSW9,
AH 1-4	CSWD, CSWF, CSWN,
HT Series	CSWS 1000kcmil thru 8
IACL Series thru 750kcmil	
2IACL Series thru 750kcmil	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 *See page 350 for required compression dies

Includes:

Steel Carrying Case
 Instruction Manual

TYPE ILC-12H-N

Features

- Head tested to 50,000 crimp cycles
- Accepts industry standard "U" dies
- Hot stick attachment point
- Light head - 9.7 lbs
- Equipped with 3/8" male screw coupler
- Ram automatically retracts when crimp cycle is complete

Benefits

- Durable and dependable
- Flexibility and economy
- Offers the option of performing line maintenance when properly protected
- Easy to hold, less tiring for numerous crimps
- For use with standard industry hoses
- Confirms crimp was completed

Specifications

Force developed: 12 Tons
 Operating pressure: 10,000 PSI
 Weight: 9.7 lbs.
 Overall Length: 11-7/8"
 Jaw Opening: 1.65"
 Conductor Range: 1000kcmil-#8



For Use with*

Aluminum Connectors	Copper Connectors
CPM Series	CLN4, CLN9, CLND,
ACM Series	CLNF, CLNN, CLNS,
ACO Series	CLNU, CLW4, CLW9,
ACO-90 Series	CLWD, CLWF, CLWN,
ACL 750kcmil-8	CLWS, CSN4, CSN9,
2ACL 750kcmil-1/0	CSND, CSNF, CSNN,
AS 750kcmil-8	CSNS, CSW4, CSW9,
AH 1-7	CSWD, CSWF, CSWN,
HT Series	CSWS 1000kcmil thru 8
IACL Series	
2IACL Series	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 *See page 350 for required compression dies

Additional Requirements:

- Hose
- Pump

Includes:

Steel Carrying Case
 Instruction Manual

TYPE IDT-6

Features

- Dieless operation
- Automatic two speed pump
- Ram automatically retracts when crimp cycle is complete
- Head rotates 360 degrees
- Flip top head
- Lightweight - 9.0 lbs.

Benefits

- No dies to lose or replace, one tool does it all
- Rapid advance, reduces cycle time
- Confirms crimp was completed
- Convenience when working in tight areas
- Easy connector loading and unloading
- Easy to hold, less tiring for numerous crimps

Specifications

Force developed: 6.2 Tons
 Weight: 9.0 lbs.
 Overall Length: 21-1/16"
 Connector Range: 750kcmil-#6



For Use with	
Aluminum Connectors	Copper Connectors
ACL, ACN Series thru 750kcmil	CLN4, CLN9, CLND,
2ACL, 2ACN Series thru 750kcmil	CLNF, CLNN, CLNS,
AS Series thru 750kcmil	CLNU, CLW4, CLW9,
IACL Series thru 500kcmil	CLWD, CLWF, CLWN,
2IACL Series thru 500kcmil	CLWS, CSN4, CSN9,
	CSND, CSNF, CSNN,
	CSNS, CSW4, CSW9,
	CSWD, CSWF, CSWN,
	CSWS 1000kcmil thru 6

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 *See page 350 for required compression dies

Includes:

Steel Carrying Case
 Instruction Manual

TYPE IDT-6H

Features

- Dieless operation
- Flip top head
- Lightweight - 6.2 lbs
- Equipped with 3/8" male screw coupler

Benefits

- No dies to lose or replace, one tool does it all
- Easy connector loading and unloading
- Easy to hold, less tiring for numerous crimps
- For use with standard industry hoses

Specifications

Force developed: 6.2 Tons
 Operating pressure: 10,000 PSI
 Overall Length: 10-1/2"
 Weight: 6.2 lbs.
 Conductor Range: 750kcmil-#6



For Use with

Aluminum Connectors	Copper Connectors
ACL, ACN Series thru 750kcmil	CLN4, CLN9, CLND,
2ACL, 2ACN Series thru 750kcmil	CLNF, CLNN, CLNS,
AS Series thru 750kcmil	CLNU, CLW4, CLW9,
IACL Series thru 500kcmil	CLWD, CLWF, CLWN,
2IACL Series thru 500kcmil	CLWS, CSN4, CSN9,
	CSND, CSNF, CSNN,
	CSNS, CSW4, CSW9,
	CSWD, CSWF, CSWN,
	CSWS 750kcmil thru 6

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Additional Requirements:

- Hose
- Pump

Includes:

Steel Carrying Case
 Instruction Manual

TYPE ILC-15H

Features

- Lightweight - only 14.1 lbs
- Accepts P or U dies with adaptor
- Hot stick attachment point
- Equipped with 3/8" male screw coupler
- Zinc plated head

Benefits

- Easy to hold, less tiring for numerous crimps
- Versatility and efficiency. Use your current dies with this tool
- Offers the option of performing line maintenance when properly protected
- For use with standard industry hoses
- Excellent corrosion resistance for long tool life

Specifications

Force developed: 15 Tons
 Operating pressure: 10,000 PSI
 Weight (with case): 14.1 lbs.
 Overall length: 15"
 Maximum width: 3"
 Conductor Range: 1000kcmil-#8



For Use with*	
Aluminum Connectors	Copper Connectors
CPM Series	CLN4, CLN9, CLND,
ACM Series	CLNF, CLNN, CLNS,
ACO Series	CLNU, CLW4, CLW9,
ACO-90 Series	CLWD, CLWF, CLWN,
ACL, ACN 1000kcmil-8	CLWS, CSN4, CSN9,
2ACL, 2ACN 1000kcmil-1/0	CSND, CSNF, CSNN,
AS 1000kcmil-8	CSNS, CSW4, CSW9,
HT Series	CSWD, CSWF, CSWN,
AH Series	CSWS 1000kcmil thru 8
IACL Series	
2IACL Series	
ALNN	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 *See page 350 for required compression dies

Note: If using "P" dies, an ILD-PADP must be used.
 If using "U" dies, an ILD-UADP must be used.

Additional Requirements:

- Hose
- Pump
- Adaptor required with all dies

TYPE 5ACR

Features

- 1/2 HP, 115VSC 50/60 Hz Motor
- Lightweight, compact design with carrying handle
- 10,000 PSI high-pressure pump with high-pressure relief valve
- Two-stage pump for rapid advance
- Pressure matched quick coupler

Benefits

- Convenient 115 V-AC electric powered motor and run on as low as 60 VAC
- Easy to lift, carry and transport tool around job site with lightweight body and handle
- High quality crimps are achieved with built in, factory set pressure release valve
- Two-stage pumping system of the unique, intermittent duty pump is designed for years of dependable service
- Saves time with quick disconnect hydraulic fitting

Technical Data:

Motor: 1/2 HP single phase, 115VAC 9 amps
 Electric Control: Remote control with 10' cord
 Oil Delivery per minute: 250 cu in @ 200 PSI,
 19 cu in @ 10,000 PSI
 Oil Reservoir: 1 gallon (3.7 liters)
 Overall Length: 10.52"
 Overall Width: 8.10"
 Overall Height: 15.95"
 Pump Weight (with oil): 29 lbs

For Use with

ILC-12H	ILC-12H-N
IDT-12H	IDT-6H
ILC-14H	ILC-15H
ILC-15	



TYPE FP-1

Features


- ① • Lightweight rugged design, portable
- ② • Built in handle
- ③ • Spring loaded arm
- ④ • Long arm
- ⑤ • Diamond plate steel foot pad
- ⑥ • Sturdy leg stabilizers
- ⑦ • Quick-disconnect hydraulic fitting, uses only Pioneer fittings
- ⑧ • Built-in factory set pressure relief valve

Benefits

- Easy to lift and carry
- Easy to transport and move tool around job site with built in handle
- Easy operation provided with spring assisted return arm
- Maximum mechanical advantage provided with long arm extending beyond pump body
- Quality, heavy duty foot pad provided with diamond plate steel. (slip resistant)
- Solid tool base provided with sturdy broad leg stabilizers
- Time saving quick disconnect hydraulic fitting
- High quality crimps provided with factory set pressure release valve with audible click to signal completion of crimp

Specifications

Reservoir volume:	1-1/8 qts.
Length:	24-3/4"
Width:	5"
Weight:	19 lbs.
Closed Height:	6-1/2"
Height (with arm open):	17"
Output Pressure:	10,000 PSI



For Use on

Hydraulic Tools

ILC-12H	ILC-12H-N
IDT-12H	IDT-6H
ILC-14H	ILC-15H
ILC-15	



**TYPE
HH-10N****Features**

- Pre-filled with oil
- Strain reliefs
- Insulated hose
- Rated 10,000 PSI
- Pioneer fittings
- 10 ft. Hose length

Benefits

- Convenience
- Safety
- Safety
- Powers most remote heads
- Standard for most hydraulic tools
- Convenience

**For use with IlSCO and other hydraulic tools,
IlSCO 5ACR pump and FP-1 foot pump.**

Catalog Number	Coupler Type	For Use With
HH-10N	Male - Female	IDT-6H, ILC-12H-N, ILC-15H



Tooling Information

Compression Terminals ASxx and ALxx	ILSCO TOOLS			BURNDY TOOLS		
	Die Code	ILC-15H, ILC-15 15 Ton ILC-30H 30 Ton	IDT-12-N 15 Ton Dieless	Die Code	Y46, Y46C	Y644M, PAT644 15 Ton Dieless
1000	(P) 302	3*	1*	P44ART	3*	1*

RANGE TAKING

Lug Size	Standard Wire Size	Expanded Wire Size	No. Crimps for ILSCO IDT-12-N and Burndy Y644M
1000	1000kcmil	1000kcmil-750kcmil	1*

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* See note d) below

- The ASxx and ALxx connectors are marked with the die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly space or connector.
- Dieless tools are not color coded or do not contain the die index.
- Strip length = Barrel Length + 1/16 inch.
- For long barrel connectors, add 1 additional crimp.

ILSCO TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire Hydraulic Tools

Lug Size	Class B/C Wire Size	Color Code	Die Index	Manual Hand Tools						IDT-6, IDT-6H 6.2 Ton Dieless, IDTB-6, IDTB-6-LIO 6.2 Ton Dieless Battery	ILC-12-N, ILC-12H-N, ILC-12, ILC-12H, ILC-14, ILC-14H 12 Ton, ILCB-12-N, ILCB-12, ILCB-12-LIO 12 Ton Battery	IDT-12-N 15 Ton Dieless	IDT-12, IDT-12H, IDTB-12 11 Ton Dieless	ILC-15H 15 Ton, ILC-30H 30 Ton	ILC-750
				94285			MT-25	ILC-10-N							
				Left Die	Right Die	Crimps	Crimps	Index	Crimps						
8	8 AWG	Red	21	M	K	2	1	Red	1					1	1
6	6 AWG	Blue	24	K	K	2	1	Blue	2	1	1			1	1
5	5 AWG	Blue	24	K	K	2	1	Blue	2	1	1			1	1
4	4 AWG	Gray	29	K	K	2	1	Gray	2	1	1	1	1	1	1
3	3 AWG	White	29	K	K	2	1	Gray	2	1	1	1	1	1	1
2	2 AWG	Brown	33	H	H	2	2	Brown	2	1	1	1	1	1	1
1	1 AWG	Green	37	H	H	2	2	Green	2	1	1	1	1	1	1
1/0	1/0 AWG	Pink	42	E	A	2	2	Pink	4	1	1	1	1	1	1
2/0	2/0 AWG	Black	45	E	A	3	2			1	1	1	1	1	1
3/0	3/0 AWG	Orange	50	A	C	3	2			2	1	1	1	1	1
4/0	4/0 AWG	Purple	54	A	B	3	2			2	1	1	1	1	1
250	250kcmil	Yellow	62	A	A	3	2			2	1	1	1	1	1
300	300kcmil	White	66							2	2	1	1	2	2
350	350kcmil	Red	71							2	2	1	1	2	2
400	400kcmil	Blue	76							2	2	1	1	2	2
500	500kcmil	Brown	87							2	2	1	1	2	2
600	600kcmil	Green	94							2	2	1	1	2	2
700	700kcmil	Pink	99							3	2	1	1	2	2
750	750kcmil	Black	106							3	2	1	1	2	2
1000	1000kcmil	White	125								2	1	1	2	2

RANGE TAKING

Lug Size	Standard Wire Size	Expanded Wire Size	No. Crimps for ILSCO IDT-12, IDT-12-N and Burndy Y644M, PAT644	No. Crimps for ILSCO IDTB-6, IDTB-6-LIO, IDT-6 and IDT-6H
4	4 AWG	4 - 6 AWG		1
3	3 AWG	3 - 6 AWG	1	1
2	2 AWG	2 - 6 AWG	1	1
1	1 AWG	1 - 6 AWG	1	1
1/0	1/0 AWG	1/0 - 6 AWG	1	1
2/0	2/0 AWG	2/0 - 4 AWG	1	1
3/0	3/0 AWG	3/0 - 2 AWG	1	2
4/0	4/0 AWG	4/0 - 1 AWG	1	2
250	250kcmil	250kcmil - 1/0 AWG	1	2
300	300kcmil	300kcmil - 2/0 AWG	1	2
350	350kcmil	350kcmil - 3/0 AWG	1	2
400	400kcmil	400kcmil - 4/0 AWG	1	2
500	500kcmil	500kcmil - 250kcmil	1	2
600	600kcmil	600kcmil - 250kcmil	1	2
700	700kcmil	700kcmil - 350kcmil	1	3
750	750kcmil	750kcmil - 500kcmil	1	3
1000	1000kcmil	1000kcmil - 750kcmil	1	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL Listed and CSA Certified when installed with tools and dies shown above

- a) Connectors are marked with color, die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- b) The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- c) Strip Length = Barrel Length + 1/16 Inch
- d) For long barrel connectors double the amount of crimps indicated on chart except for 1000kcmil add only one additional crimp.

ILSCO TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire

Hydraulic Tools

Lug Size	Class B/C Wire Size	Color Code	Die Index	Manual Hand Tools						IDT-6, IDT-6H 6.2 Ton Dieless, IDTB-6 IDTB-6-LIO 6.2 Ton Dieless Battery	ILC-12-N, ILC-12H-N, ILC-12, ILC-12H, ILC-14, ILC-14H 12 Ton, ILCB-12-N, ILCB-12, ILCB-12-LIO 12 Ton Battery	IDT-12-N 15 Ton Dieless	IDT-12, IDTB-12 11 Ton Dieless	ILC-15H 15 Ton, ILC-30H 30 Ton
				94285			MT-25	ILC-10-N						
				Left Die	Right Die	Crimps	Crimps	Index	Crimps					
8	8 AWG	Red	21	M	K	2	1	Red	1		1			1
6	6 AWG	Blue	24	K	K	2	1	Blue	2	1	1		1	1
5	5 AWG	Blue	24	K	K	2	1	Blue	2	1	1		1	1
4	4 AWG	Gray	29	K	K	2	1	Gray	2	1	1	1	1	1
3	3 AWG	White	29	K	K	2	1	Gray	2	1	1	1	1	1
2	2 AWG	Brown	33	H	H	2	2	Brown	2	1	1	1	1	1
1	1 AWG	Green	37	H	H	2	2	Green	2	1	1	1	1	1
1/0	1/0 AWG	Pink	42	E	A	2	2	Pink	4	1	1	1	1	1
2/0	2/0 AWG	Black	45	E	A	3	2			1	1	1	1	1
3/0	3/0 AWG	Orange	50	A	C	3	2			2	1	1	1	1
4/0	4/0 AWG	Purple	54	A	B	3	2	Purple		2	1	1	1	1
250	250kcmil	Yellow	62	A	A	3	2			2	1	1	1	1
300	300kcmil	White	66							2	2	1	1	2
350	350kcmil	Red	71							2	2	1	1	2
400	400kcmil	Blue	76							2	2	1	1	2
500	500kcmil	Brown	87							2	2	1	1	2
600	600kcmil	Green	94							2	2	1	1	2
700	700kcmil	Pink	99							3	2	1	1	2
750	750kcmil	Black	106							3	2	1	1	2
1000	1000kcmil	White	125								2	1	1	2

RANGE TAKING

Lug Size	Standard Wire Size	Expanded Wire Size	No. Crimps for ILSCO IDT-12, IDT-12-N and Burndy Y644M, PAT644	No. Crimps for ILSCO IDTB-6, IDTB-6-LIO, IDT-6 and IDT-6H
4	4 AWG	4 - 6 AWG		1
3	3 AWG	3 - 6 AWG	1	1
2	2 AWG	2 - 6 AWG	1	1
1	1 AWG	1 - 6 AWG	1	1
1/0	1/0 AWG	1/0 - 6 AWG	1	1
2/0	2/0 AWG	2/0 - 4 AWG	1	1
3/0	3/0 AWG	3/0 - 2 AWG	1	2
4/0	4/0 AWG	4/0 - 1 AWG	1	2
250	250kcmil	250kcmil - 1/0 AWG	1	2
300	300kcmil	300kcmil - 2/0 AWG	1	2
350	350kcmil	350kcmil - 3/0 AWG	1	2
400	400kcmil	400kcmil - 4/0 AWG	1	2
500	500kcmil	500kcmil - 250kcmil	1	2
600	600kcmil	600kcmil - 250kcmil	1	2
700	700kcmil	700kcmil - 350kcmil	1	3
750	750kcmil	750kcmil - 500kcmil	1	3
1000	1000kcmil	1000kcmil - 750kcmil	1	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
UL Listed and CSA Certified when installed with tools and dies shown above

- a) Number of crimps shown on chart must be on each end of the CT splicer connectors.
- b) The CT connectors are marked with color, the die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- c) The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- d) For long barrel (CTL) connectors add one additional crimp to each side of barrel.

ILSCO TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire

Hydraulic Tools

Lug Size	Fine Strand Wire Size	Approved Wire Classes	Color Code	Die Index	Manual Hand Tools					Hydraulic Tools					
					94285			ILC-10-N		6.2 Ton Dieless Battery	ILC-12-N, ILC-12H-N, ILC-12, ILC-12H, ILC-14, ILC-14H 12 Ton, ILCB-12-N, ILCB-12, ILCB-12-LIO 12 Ton Battery	IDT-12-N 15 Ton Dieless	IDT-12, IDT-12H, 11 Ton Dieless	ILC-15H 15 Ton, ILC-30H 30 Ton	ILC-750
					Left Die	Right Die	Crimps	Index	Crimps						
8	8	G,H,I,K,M,DLO	Red	21				Red	1		1			1	1
5	6	G,H,I,K,M,DLO	Blue	24				Blue	2		1			1	1
3	4	G,H,I,K,M,DLO	White	29	K	K	2	Gray	2	1	1	1	1	1	1
1	2	G,H,I,K,M,DLO	Green	37	H	H	2	Green	2	1	1	1	1	1	1
1/0	1	G,H,I,K,M,DLO	Pink	42	H	H	2	Pink	4	1	1	1	1	1	1
2/0	1/0	G,H,I,K,M,DLO	Black	45	E	A	3			1	1	1	1	1	1
3/0	2/0	G,H,I,K,M,DLO	Orange	50	E	A	3			1	1	1	1	1	1
4/0	3/0	G,H,I,K,M,DLO	Purple	54	A	B	3			1	1	1	1	1	1
250	4/0	G,H,I,K,M,DLO	Yellow	62	A	B	3			1	1	1	1	1	1
300	250	G,H	White	66						1	2	1	1	2	2
350	250	I,K,M	Red	71						1	2	1	1	2	2
350	262	DLO	Red	71						1	2	1	1	2	2
400	300	G,H,I,K,M	Blue	76						2	2	1	1	2	2
400	313	DLO	Blue	76						2	2	1	1	2	2
500	350	G,H,I,K,M	Brown	87						2	2	1	1	2	2
500	373	DLO	Brown	87						2	2	1	1	2	2
600	400	G,H,I,K,M	Green	94						2	2	1	1	2	2
600	444	DLO	Green	94						2	2	1	1	2	2
700	500	G,H,I,K,M	Pink	99						3	2	1	1	2	2
700	535	DLO	Pink	99						3	2	1	1	2	2
750	600	G,H,I,M	Black	106						3	2	1	1	2	2
750	646	DLO	Black	106						3	2	1	1	2	2
1000	750	G,H,I	White	125							3	1	1	3	
1000	777	DLO	White	125							3	1	1	3	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL Listed and CSA Certified when installed with tools and dies shown above

- Connectors are marked with color, die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- Strip Length = Barrel Length + 1/16 Inch
- For long barrel connectors double the amount of crimps indicated on chart except for 1000kcmil add only one additional crimp.

ILSCO TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire

Hydraulic Tools

Lug Size	Fine Strand Wire Size	Approved Wire Classes	Color Code	Die Index	Manual Hand Tools					IDT-6, IDT-6H 6.2 Ton Dieless, IDTB-6 ICB-6-LIO 6.2 Ton Dieless Battery	ILC-12-N, ILC-12H-N, ILC-12, ILC-12H, ILC-14, ILC-14H 12 Ton, ILCB-12-N, ILCB-12, ILCB-12-LIO 12 Ton Battery	IDT-12-N 15 Ton Dieless	IDT-12H, IDTB-12 11 Ton Dieless	ILC-15H 15 Ton, ILC-30H 30 Ton						
					94285			ILC-10-N							Crimps	Crimps	Crimps	Crimps	Crimps	Crimps
					Left Die	Right Die	Crimps	Index	Crimps											
8	8	G,H,I,K,M,DLO	Red	21	M	K	2	Red	1		1			1						
5	6	G,H,I,K,M,DLO	Blue	24	K	K	2	Blue	2		1			1						
3	4	G,H,I,K,M,DLO	White	29	K	K	2	Gray	2	1	1			1						
1	2	G,H,I,K,M,DLO	Green	37	H	H	2	Green	2	1	1	1	1	1						
1/0	1	G,H,I,K,M,DLO	Pink	42	H	H	2	Pink	4	1	1	1	1	1						
2/0	1/0	G,H,I,K,M,DLO	Black	45	E	A	3			1	1	1	1	1						
3/0	2/0	G,H,I,K,M,DLO	Orange	50	E	A	3			2	1	1	1	1						
4/0	3/0	G,H,I,K,M,DLO	Purple	54	A	B	3			2	1	1	1	1						
250	4/0	G,H,I,K,M,DLO	Yellow	62	A	B	3			2	1	1	1	1						
300	250	G,H	White	66						2	2	1	1	2						
350	250	I,K,M	Red	71						2	2	1	1	2						
350	262	DLO	Red	71						2	2	1	1	2						
400	300	G,H,I,K,M	Blue	76						2	2	1	1	2						
400	313	DLO	Blue	76						2	2	1	1	2						
500	350	G,H,I,K,M	Brown	87						2	2	1	1	2						
500	373	DLO	Brown	87						2	2	1	1	2						
600	400	G,H,I,K,M	Green	94						2	2	1	1	2						
600	444	DLO	Green	94						2	2	1	1	2						
700	500	G,H,I,K,M	Pink	99						3	3	1	1	3						
700	535	DLO	Pink	99						3	3	1	1	3						
750	600	G,H,I,M	Black	106						3	3	1	1	3						
750	646	DLO	Black	106						3	3	1	1	3						
1000	750	G,H,I	White	125							3	1	1	3						
1000	777	DLO	White	125							3	1	1	3						

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL Listed and CSA Certified when installed with tools and dies shown above

- a) Number of crimps shown on chart must be on each end of the CT splicer connectors.
- b) The CT connectors are marked with color, the die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- c) The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- d) For long barrel (CTL) connectors add one additional crimp to each side of barrel.

COMPETITOR'S TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire

Lug Size	Class B/C Wire Size	Anderson		Burdny							T&B				Greenlee					
		VC6-FT, VC6-FTR, VC6-FT-BP, VC7-FT, VC7-FTR Dieless		PAT81KFT, Y81KFT, Y81KFTMBH Dieless		‡ Y644M, PAT644 Dieless		Y35, Y35BH, Y39, Y750, Y750BH, PAT750		Y46, Y46C Requires Die Adaptor		TBM25S		13100A, TBM14M, TBM14BSCR		K111		HK06FT, RK06FT, EK06FT Dieless		1990 Dieless
		Crimps	Index	Crimps	Crimps	Crimps	Die Part	Crimps	Die Part	Crimps	Index	Crimps	Die Part	Crimps	Index	Crimps	Crimps	Crimps		
8	8 AWG	1	Red	1	1		U8CRT	1	U8CRT	1	Red	1	15520	1	Red	1				
6	6 AWG	1	Blue	1	1		U5CRT	1	U5CRT	1	Blue	1	15522	1	Blue	2	1			
5	5 AWG	1	Blue	1	1		U5CRT	1	U5CRT	1	Blue	1	15522	1	Blue	2	1			
4	4 AWG	1	Gray	2	1	1	U4CRT	1	U4CRT	1	Gray	2	15527-CK	1	Gray	2	1	1		
3	3 AWG	1	White	2	1	1	U3CRT	1	U3CRT	1					Gray	2	1	1		
2	2 AWG	1	Brown	2	1	1	U2CRT	1	U2CRT	1	Brown	2	15528	1	Brown	2	1	1		
1	1 AWG	1			1	1	U1CRT-1	1	U1CRT-1	1			15513-CK	1	Green	2	1	1		
1/0	1/0 AWG	1			1	1	U25RT	1	U25RT	1			15508	1	Pink	4	1	1		
2/0	2/0 AWG	1			1	1	U26RT	1	U26RT	1			15526	1			1	1		
3/0	3/0 AWG	1			1	1	U27RT	1	U27RT	1			15530	1			2	1		
4/0	4/0 AWG	1			1	1	U28RT	1	U28RT	1			15511	1			2	1		
250	250kcmil	2			2	1	U29RT	1	U29RT	1			15510-CK	1			2	1		
300	300kcmil	2			2	1	U30RT	2	U30RT	2			15534	2			2	1		
350	350kcmil	3*			2	1	U31RT	2	U31RT	2			15514-CK	2			2	1		
400	400kcmil	3*			2	1	U32RT	2	U32RT	2			15512	2			2	1		
500	500kcmil	3*			2	1	U34RT	2	U34RT	2			15506	2			2	1		
600	600kcmil	4*			2	1	U36RT	2	U36RT	2			15536-CK	2			2	1		
700	700kcmil	4*			3	1	U38RT	2	U38RT	2			15505	2			3	1		
750	750kcmil	4*			3	1	U39RT	2	U39RT	2			15515-CK	2			3	1		
1000	1000kcmil				3	1			P44RT	3			15504	2				1		

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Dieless* - Crimps will overlap

UL Listed and CSA Certified when installed with tools and dies shown above

- a) Connectors are marked with color, die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- b) The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- c) Consult manufacturers data for catalog numbers of dies for each tool.
- d) Strip Length = Barrel Length + 1/16 Inch
- e) For long barrel connectors double the amount of crimps indicated on chart except for 1000kcmil add only one additional crimp.

‡ Allows expanded wire range to be used.

COMPETITOR'S TOOLS - Tooling Information

WARNING! Do Not Use with Aluminum Wire

Lug Size	Fine Strand Wire Size	Approved Wire Classes	Anderson		Burdny						T&B				Greenlee					
			VC6-FT, VC6-FTR, VC6-FT-BP, VC7-FT, VC7-FTR Dieless		PAT81KFT, Y81KFT, Y81KFTMBH Dieless		‡ Y644M, PAT644 Dieless	Y35, Y35BH, Y39, Y750, Y750BH, PAT750		Y46, Y46C Requires Die Adaptor		TBM25S		13100A, TBM14M, TBM14BSCR		K111		HK06FT, RK06FT, EK06FT Dieless		1990 Dieless
			Crimps	Index	Crimps	Crimps	Crimps	Die Part	Crimps	Die Part	Crimps	Index	Crimps	Die Part	Crimps	Index	Crimps	Crimps	Crimps	
8	8	G,H,I,K,M,DLO	1	Red	1	1		U8CRT	1	U8CRT	1	Red	1	15520	1	Red	1			
5	6	G,H,I,K,M,DLO	1	Blue	2	1		U5CRT	1	U5CRT	1	Blue	2	15522	1	Blue	2			
3	4	G,H,I,K,M,DLO	1	Gray	2	1	1	U4CRT	1	U4CRT	1	Gray	2	15528	1	Gray	2	1	1	
1	2	G,H,I,K,M,DLO	1	Brown	2	1	1	U2CRT	1	U2CRT	1	Brown	3	15513-CK	1	Green	2	1	1	
1/0	1	G,H,I,K,M,DLO	1			1	1	U1CRT-1	1	U1CRT-1	1			15508	1	Pink	4	1	1	
2/0	1/0	G,H,I,K,M,DLO	1			1	1	U25RT	1	U25RT	1			15526	1			1	1	
3/0	2/0	G,H,I,K,M,DLO	2			2	1	U26RT	1	U26RT	1			15530	1			1	1	
4/0	3/0	G,H,I,K,M,DLO	2			2	1	U27RT	1	U27RT	1			15511	1			1	1	
250	4/0	G,H,I,K,M,DLO	2			2	1	U28RT	1	U28RT	1			15510-CK	2			1	1	
300	250	G,H	2			2	1	U29RT	2	U29RT	2			15534	2			1	1	
350	250	I,K,M	3*			2	1	U30RT	2	U30RT	2				2			1	1	
350	262	DLO	3*			2	1		2		2				2			1	1	
400	300	G,H,I,K,M	3*			2	1	U31RT	2	U31RT	2			15514-CK	2			2	1	
400	313	DLO	3*			2	1		2		2				2			2	1	
500	350	G,H,I,K,M	3*			2	1	U32RT	2	U32RT	2			15512	2			2	1	
500	373	DLO	3*			2	1		2		2			15517	2			2	1	
600	400	G,H,I,K,M	4*			2	1	U34RT	2	U34RT	2			15536-CK	2			2	1	
600	444	DLO	4*			2	1		2		2				2			2	1	
700	500	G,H,I,K,M	4*			3	1	U38XRT	2	U38XRT	2			15505	2			3	1	
700	535	DLO	4*			3	1		2		2				2			3	1	
750	600	G,H,I,M	4*			3	1	U39RT	2	U39RT	2			15515-CK	2			3	1	
750	646	DLO	4*			3	1		2		2				2			3	1	
1000	750	G,H,I				3	1			U44XRT	3			15504	3				1	
1000	777	DLO				3	1				3				3				1	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Dieless* - Crimps will overlap

UL Listed and CSA Certified when installed with tools and dies shown above

- a) Connectors are marked with color, die numbers and required number of crimps for ILSCO hydraulic tools. When using other listed tools, consult chart for crimps required. Crimps should be evenly spaced on connector.
- b) The ILSCO 94285, MT-25 and all dieless tools are not color coded or do not contain the die index.
- c) Strip Length = Barrel Length + 1/16 Inch
- d) For long barrel connectors double the amount of crimps indicated on chart except for 1000kcmil add only one additional crimp.

‡ Allows expanded wire range to be used.



Compressor Dies For ILC-12-N, ILC-12H-N, ILCB-12-N, ILC-15H, ILC-12, ILC-12H, ILC-14, ILC-14H, ILCB-12, ILCB-12-LIO, ILC-15, ILC-750

Catalog Number	Wire Size		
	Aluminum Terminals and Splices	ACM and ACO Pin Connectors	CPM Pin Connectors
ILD-1			
ILD-2	8		
ILD-3	6		
ILD-4	4		
ILD-5			
ILD-6			
ILD-7	2, 1		
ILD-8	1/0	6, 4, 2, 1	
ILD-9	6, 4, 2, 1		
ILD-10	2/0, 3/0		
ILD-11			
ILD-12	4/0	1/0, 2/0, 3/0, 4/0	1/0, 2/0, 3/0, 4/0
ILD-13	250kcmil		
ILD-14	300kcmil, 350kcmil	250kcmil, 300kcmil, 350kcmil	250kcmil, 300kcmil, 350kcmil
ILD-15			
ILD-16	400kcmil		
ILD-16A	*500kcmil	400kcmil, 500kcmil	400kcmil, 500kcmil
ILD-17	*600kcmil, *700kcmil		
ILD-18	*700kcmil	600kcmil, 750kcmil	600 kcmil, 750kcmil
ILD-20	1000kcmil		
ILD-P302	‡1000kcmil		

* Cannot be used on Sleeves with ILC-12-N, ILC-12H-N, ILC-12 and ILC-12H tools

‡ For use on ALNN-1000-12-134



Compressor Dies For ILC-12, ILC-12-N, ILC-12H, ILC-12H-N, ILCB-12, ILCB-12-N, ILCB-12-LIO, ILC-14, ILC-14H, ILC-15, ILC-15H, ILC-750

Catalog Number	Class B/C Copper Wire Only	Fine Strand Copper Wire Only
	Series CS, CL, CT, CTL	Series CS, CL, CT, CTL
ILD-21	8 AWG	8 FLEX CLASS G,H,I,K,M,DLO
ILD-24	6 AWG, 5 AWG	6 FLEX CLASS G,H,I,K,M,DLO
ILD-29	4-3 AWG	4 FLEX CLASS G,H,I,K,M,DLO
ILD-33	2 AWG	-
ILD-37	1 AWG	2 FLEX CLASS G,H,I,K,M,DLO
ILD-42	1/0 AWG	1 FLEX CLASS G,H,I,K,M,DLO
ILD-45	2/0 AWG	1/0 FLEX CLASS G,H,I,K,M,DLO
ILD-50	3/0 AWG	2/0 FLEX CLASS G,H,I,K,M,DLO
ILD-54	4/0 AWG	3/0 FLEX CLASS G,H,I,K,M,DLO
ILD-62	250kcmil	4/0 FLEX CLASS G,H,I,K,M,DLO
ILD-66	300kcmil	250 G,H
ILD-71	350kcmil	250 I,K,M, 262 DLO
ILD-76	400kcmil	300 G,H,I,K,M, 313 DLO
ILD-87	500kcmil	350 G,H,I,K,M, 373 DLO
ILD-94	600kcmil	400 G,H,I,K,M, 444 DLO
ILD-99	700kcmil	500 G,H,I,K,M, 535 DLO
ILD-106	750kcmil	600 G,H,I,M, 646 DLO
ILD-125	1000kcmil	750 G,H,I, 777 DLO

TYPE W DIES FOR
ND-60
ND-58



Catalog Number	For Use With	
	Aluminum Compression Connectors	Copper Compression Connectors
ND-0	HT-1, HT-2, AH-1	GGC-1, GGA-1, GGA-2, GGA-4
ND-BG	PICS-61 thru PICS-78	ULT-4, ULT-5
ND-C		ULT-6, ULT-7
ND-K-840	UCS-2/0, UCS-3/0, UCS-4/0, UCS-250, PICS-834 thru PICS-869	

FOR TYPE
ILC-15
ILC-15H
ILC-750



Figure 1



Figure 2

Catalog Number	Figure Number	For Use With	
		Aluminum Compression Connectors	Copper Compression Connectors
ILD-K-840*+	1	UCS-2/0, UCS-3/0, UCS-4/0, UCS-250, PICS-834 thru PICS-869	
ILD-C*+	1		ULT-6, ULT-7, ELT-1
ILD-D ₃ *+	1	HT-2, HT-3, HT-4, HT-5, HT-7, AH-2, AH-3, AH-4	ULT-12
ILD-0*	1	HT-1, HT-6, HT-8, AH-1	GGA-1, GGA-1, GGA-2, GGA-4, ELT-2, ELT-4
ILD-N*+	1	AH-5, AH-6, AH-7	
ILD-KR+	2	AH-8, AH-9, AH-10, AH-11, AH-12	AH-10, AH-11, AH-12
ILD-U997*+	1		GGA-2, GGA-3, GGA-5, GGC-2, GGC-3, GGC-4, ELT-3, ELT-5
ILD-U998+	1		GGA-4, GGA-5, GGC-5, GGC-6, GGC-7, RLT
ILD-P998	2	Can only be used with ILC-15 or ILC-15H	GGA-4, GGA-5, GGC-5, GGC-6, GGC-7, RLT
ILD-P999	2	Can only be used with ILC-15 or ILC-15H	GGA-6, GGC-8
ILD-U1011+	1		GGA-6, GGC-8, ELT-6, RLT
ILD-P1011°	2		GGA-6, GGC-8, RLT
ILD-UBG	1	PICS-61 thru PICS-78	ULT-4, ULT-5
ILD-P302	1	ALNN	

* May also be used with ILC-12-N, ILC-12H-N, ILCB-12-N, ILC-12, ILC-12H, ILCB-12
+ Must be used with ILDPADP when using ILC-15, must be used with ILDPADP when using ILC-15H
o Must be used with ILDPADP when using ILC-15H

Die Adaptors

FOR TYPE
ILC-15
ILC-15H



Figure 1



Figure 2



Figure 3

Catalog Number	Figure Number	Description
ILD-ADP	1	Permits ILDPADP to ILDPADP to be inserted in ILC-15 tool
ILD-UADP	2	Permits ILDPADP to ILDPADP to be inserted in ILC-15H tool
ILD-PADP	3	Permits "P" style dies to be inserted in ILC-15H tool



Fig. 1



Fig. 2



Fig. 3

Catalog Number	Figure Number	Description
ILD-DIE-CASE	1	Crimping die carrying case (dies not included), accommodates 15 dies
IDT-6-TON-TEST-KIT	2	10 Test slugs and gauge
IDT-12-TON-TEST-KIT	2	30 Test slugs and gauge
CUTTER-DIES	3	Guy wire cutting dies

TYPE

94130**Controlled-Cycle
Crimper****Features**

- Dieless tool
- Ratchet mechanism
- Compound action
- Cushion grip handles
- Crimps insulated wire terminals
- Wire Range: 10-22 AWG, Weight .8 lb

Benefits

- No need to purchase and maintain dies
- Assures proper crimp force every time
- Delivers maximum crimp force with minimum effort
- Provides user comfort
- Provides flexibility in use



TYPE

94145**Multi Purpose
Crimp Tool****Features**

- Heavy duty carbon steel construction
- Comfort grip handles
- Spring loaded action
- Safety lock mechanism
- Color coded crimp nest
- Crimp nest
- Wire cutter
- Machine screw cutters
- Wire stripper/wire gauge

Benefits

- Provides durable rugged reliability
- Provides user comfort
- Enables multiple crimps
- Provides for compact storage
- For insulated terminals
- For uninsulated terminals
- Easily cuts solid and stranded wire
- Cuts and rethreads 4-40, 6-32, 8-32, 10-24, and 10-32 machine screws
- 26-8 AWG




TYPE

WS-1**Wire Stripper****Features**

- Cushion grip handles
- Crimp die
- Wire strip gauge
- Plier nose
- Wire loop holes
- Wire cutter
- "Open" spring
- Metric markings
- Precision stripping
- Wire crimp range: 14-18 AWG

Benefits

- Eases pressure on hands when working for long periods or with larger conductor
- Built in crimp die allows you to crimp insulated terminals from 18AWG to 14AWG
- Convenient stamped wire strip gauge makes it easy to strip conductors to specific length consistently
- Flat plier nose allows you to conveniently punch and twist knock outs
- Built in looping holes allow you to conveniently bend eye loop into end of conductor
- Built in cutter is precision ground to cut small conductor copper intended to be stripped (Strips #10 - 18 AWG)
- Conveniently holds tool in open position to facilitate wire insertion
- Metric markings provide for use of tool on products that have been sized metrically
- Precision ground wire stripping holes provide a clean cutting and stripping action of insulation



All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE
CTR-2/0

- Features**
- 7-1/2" overall length
 - Sharp precision ground blades
 - Heat treated blades
 - Narrow head design
 - Cuts up to 2/0 copper or aluminum cable

- Benefits**
- Better leverage for easier cutting
 - Clean, distortion-free cuts
 - Long, dependable and durable operation
 - Provides easy access to confined areas
 - Wide cutting range for a pouch tool



TYPE
CTR-350

- Features**
- Sharp precision ground blades
 - Moly steel blades
 - Durable 16" metal handles
 - Cuts copper and aluminum cable up to 350kcmil

- Benefits**
- Provides clean distortion-free cuts
 - Offers extra strength to prevent blade breakage, blades stay sharper longer
 - Provides easy handling
 - Provides wide cutting range



TYPE
CTR-500

- Features**
- Sharp precision ground blades
 - Moly steel blades
 - Durable 20-3/4" fiberglass handles
 - Cuts copper and aluminum cable up to 500kcmil

- Benefits**
- Provides clean, distortion-free cuts
 - Offers extra strength to prevent blade breakage, blades stay sharper longer
 - Provides easy handling
 - Provides wide cutting range



TYPE
CTR-750

- Features**
- Cuts copper and aluminum cable up to 750kcmil
 - Lightweight
 - Ratchet mechanism
 - 16" length
 - Open/close lever
 - Alloy steel precision ground replaceable blades

- Benefits**
- Provides large cutting capacity
 - Weight of only 3 lbs. prevents operator fatigue
 - Allows large cables to be cut with minimum effort
 - Compact size provides ease of use in cramped spaces
 - Lever that controls cutting blade direction makes the tool easy to use
 - Provides years of service by being able to replace blades when necessary



All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE MECHANICAL TOOLS



Catalog Number	Figure Number	Description	Hex Size	Length
DR-516	5	Driver for Torque Wrench	5/16	-
DR-38	5	Driver for Torque Wrench	3/8	-
DR-12	5	Driver for Torque Wrench	1/2	-
HW-13	2	Screwdriver Bit for TS-35, .214 x .040	-	-
HW-14	2	Screwdriver Bit for TS-35, .250 x .042	-	-
TK-1	-	Torque Kit with TS-35, HW-13, HW-14, TW-1, DR-516, DR-38, Case	-	-
TK-2	-	Torque Kit with TS-35, HW-13, HW-14, TW-750R, TW-150R, DR-516, DR-38, Case	-	-
TS-35	1	Torque Screwdriver 0-36 lbs.	-	-
TW-1	3	Torque Wrench 0-600 in. lbs.	-	-
TW-150R	4	Torque Wrench (Ratchet type) 5-150 in. lbs.	-	-
TW-750R	4	Torque Wrench (Ratchet type) 100-750 in. lbs.	-	-
WR-1	7	Double Wrench	3/16, 5/16	4
WR-1A	6	Wrench	3/16	4-1/2
WR-3	6	Wrench	1/4	5-1/4
WR-4	6	Wrench	5/16	3-3/16
WR-5	6	Wrench	3/8	4-1/2
WR-9	6	Wrench	5/16	10
WR-10	6	Wrench	3/8	10
WR-12	6	Wrench	1/2	5-1/2
WC	8	Wire Brush	-	-

TYPE

**Electric
Heat Gun****Features**

- Two temperature settings 750F and 1100F
- Three way switch OFF/HI/LO
- Built-in fold down stand
- 1200 Watt 120 V AC
- Heat deflector
- Impact resistant case
- Six foot cord
- Supplied in plastic carrying case

Benefits

- Provides versatility in applying recommended heat, deliverable in seconds
- Aids in producing proper air flow from heat gun
- Provides hands free operation
- Provides high output of air and heat
- Allows for concentration of heat for rapid heat shrink process
- Provides extra durability in harsh environments
- Provides operator convenience
- Provides ease of storage and accessibility



Catalog Number	Description
27001	Heat Gun, 11 Disks Thin Wall Heat Shrink
94502	Electric Heat Gun 120v
94504	Replacement Adaptor for 94502

<p>C</p>  <p>355</p>	<p>M</p>  <p>356</p> <p>M</p>  <p>357</p>	<p>D167</p>  <p>358</p>
<p>CAN</p>  <p>359</p>	<p>N-174</p>  <p>359</p>	<p>NB</p>  <p>360</p>
<p>DE-OX</p>  <p>361</p>	<p>DUCT SEAL</p>  <p>362</p>	
<p>NBW</p>  <p>363</p>	<p>Cable Ties</p>  <p>364 - 368</p>	



TYPE C

Features

- Manufactured from special bronze alloy except 100 and 200 amp styles. Arched bottoms
- All formed corners are designed with a radius

Benefits

- Spring type material ensures positive contact. Provide firm and secure mounting, and prevents expansion after fuse is inserted.
- Prevents fracturing



Catalog Number	Figure Number	Amp-Volts	Dimensions									
			A	B	C	Bolt Size	D	E	F	G	H	J
C-10	1	30-250	7/8	3/64	19/32	#10	13/64	17/32	9/16	1/32	19/32	1/2
C-11	4	60-250	1-1/8	1/16	51/64	#10	15/64	51/64	13/16	3/64	21/32	5/8
C-12	5	60-250	1-1/8	1/16	13/16	#8	3/16	47/64	13/16	3/64	21/32	5/8
C-13	9	60-600	1-9/32	1/16	1-1/8	1/4	17/64	13/16	1-1/16	3/64	21/32	5/8
C-14	6	60-350	1	-	51/64	*	*	5/8	13/16	3/64	-	5/8
C-15	7	60-250	1-1/32	-	51/64	#10	13/64	5/8	13/16	3/64	-	5/8
C-16	11	100-250	1-43/64	-	29/32	1/4	17/64	1-11/64	1/8	5/64	-	7/8
C-17	10	100-250	1-23/64	-	15/16	1/4	17/64	57/64	1/8	5/64	-	7/8
C-19	2	30-250	7/8	-	39/64	#8	11/64**	17/32	9/16	1/32	-	1/2
C-23	8	60-600	1-5/16	1/16	31/32	#8	3/16	29/32	1-1/16	3/64	21/32	23/32
C-24	12	200-250/600	1-15/16	-	1-1/4	5/16	11/32	1-1/8	3/16	3/32	-	1-1/4
C-28	3	50-250	61/64	-	1/2	#8	3/16	23/32	7/64	3/64	-	1/2

** Stud hole center 9/32 from one side and 7/32 from other side.

* Slotted 13/64 x 13/32.

ILSCO Wire Reinforced Fuse Clips

RoHS
Compliant

K

TYPE
M

Features

- Manufactured from copper alloy
- Supplied with permanently installed steel spring
- Spring is heat treated and plated

Benefits

- Ensures high conductivity
- Ensures tighter grip and positive contact with either knife or ferrule type fuses.
- Prevents hydrogen embrittlement




Fig. 1



Fig. 2

Catalog Number	Figure Number	Amp-Volts	Dimensions									
			A	B	C	Bolt Size	D	E	F	G	H	J
M-161	1	30-250	27/32	1/16	19/32	#10	13/64	17/32	9/16	1/32	17/32	1/2
M-162	1	30-600	1-1/32	1/16	3/4	1/4	1/4	21/32	13/16	1/32	17/32	1/2
M-163	1	60-250	1-13/64	1/16	51/64	#10	7/32	51/64	13/16	3/64	21/32	21/32
M-164	1	60-600	1-3/8	1/16	31/32	#8	3/16	29/32	1-1/16	3/64	21/32	5/8
M-165	2	100-250/600	1-23/64	-	29/32	1/4	17/64-Slot	-	1/8	5/64	-	7/8
M-233	2	200-250/600	1-15/16	-	1-1/4	5/16	11/32-Slot	-	3/16	3/32	-	1-1/4
M-628	2	400-600	2-7/16	-	1-1/2	-	5/16-18 (2)	-	1/4	1/8	-	1-3/4

TYPE M

Features

- Manufactured from copper alloy
- Supplied with permanently installed steel spring
- Spring is heat treated and plated
- Supplied with a slot or a hole for a steel rejection device.
- Electro-tin plated

Benefits

- Ensures high conductivity
- Ensures tighter grip and positive contact with either knife or ferrule type fuses.
- Prevents hydrogen embrittlement
- Prevents the insertion of any other type fuse except class R
- Provides low contact resistance




Fig. 1



Fig. 2

Catalog Number	Figure Number	Amp-Volts	Dimensions			
			A	B	C	D
M-2432	1	30-250	7/8	19/32	21/32	19/32
M-2433	1	60-250	1.200	23/32	59/64	51/64
M-2434	1	30-600	1-1/32	19/32	59/64	3/4
M-2435	1	60-600	1.390	23/32	1-5/64	31/32
M-2398	2	100-250/600	1-23/64	7/8	1/8	29/32
M-2399	2	200-250/600	1-15/16	1-1/4	3/16	1-15/64

UL File E58652

K


TYPE D167

Features

- Manufactured from high strength copper tubing
- Range taking
- UL Recognized for 600 volts

Benefits

- Provides maximum conductivity
- A wide range of conductor sizes can be used in the same connector
- Ensures reliability for copper conductor



Catalog Number	Number Of Taps	Wire Range		Dimensions					Mounting Hole Positions	
		Main	Tap	L	Height With Maximum Wire	W	Bolt Size	Two Mounting Holes	From End Of Bar To First Mounting Hole	Distance Between Holes
D167-4	4	4-14	6-14	2-3/4	3/4	11/32	#10	13/64	.581 (2nd hole)	1.98
D167-6	6	4-14	6-14	3-1/2	3/4	11/32	#10	13/64	.978 (3rd hole)	1.98
D167-8	8	4-14	6-14	4-7/16	3/4	11/32	#10	13/64	1.375 (4th hole)	1.98
D167-10	10	4-14	6-14	5-1/8	3/4	11/32	#10	13/64	1.772 (5th hole)	1.98
D167-12	12	4-14	6-14	5-15/16	3/4	11/32	#10	13/64	2.169 (6th hole)	1.98
D167-14	14	4-14	6-14	6-23/32	3/4	11/32	#10	13/64	2.566 (7th hole)	1.98

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 Tested to UL 486A/B, UL File E6207

TYPE CAN

Features

- Manufactured from high strength copper tubing
- Compact design
- Range taking
- Circuit bars inserted at a 20 angle
- Copper conductor only

Benefits

- Provides maximum conductivity
- Up to 42 circuit taps can be made in just 5 1/2" of space
- A wide range of conductor sizes can be used in the same connector
- Provides easy wire insertion




Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Number Of Taps	Wire Range		Dimensions			
			Main	Tap	L	Height With Maximum Wire	W	Two Tapped Mounting Holes
CAN-300	1	24	250kcmil-6	6-14	2-5/16	1-5/16	5-1/8	10-32
CAN-301	1	30	250kcmil-6	6-14	3	1-5/16	4-13/32	10-32
CAN-302	1	36	250kcmil-6	6-14	3	1-5/16	5-1/8	10-32
CAN-303	1	42	250kcmil-6	6-14	3	1-7/16	5-1/2	10-32
R-16	2	Mounting block of general purpose (phenolic black) suitable for mounting any of CAN Neutrals. 2-1/2" wide x 2-1/2" long x 1" thick.						
E-223	3	10-32 x 1/2" round head steel machine screws for fastening neutrals to mounting blocks. (Use lock washer to provide rigid assembly.)						
E-153	3	1/4-28 wire pressure screw 7/16" long. Screw is steel, zinc plated and chromate dipped.						
N-174	4	Supplied in 5' 9" lengths. Approximately 174 outlets. Wire range 14-6.						

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207

TYPE NB

Features

- Preassembled, stacked neutral bars
- Available with phenolic base
- Electro-tin plated
- Fabricated from high strength 6061-T6 aluminum alloy

Benefits

- Compact, space saving design offers multiple range taking flexibility and is suitable for grounding applications
- Provides insulation from mounting surface
- Provides low contact resistance
- Suitable for use with either copper or aluminum conductors





Fig. 1



Fig. 2




Fig. 3

Catalog Number	Figure Number	Number Of Circuit Taps	Wire Range		Dimensions			Two Tapped Mounting Holes	Hex Size	
			Circuit Taps	Line Loads	Approx. Height with Max. Wire	L	W		Main	Tap
NB-350-12	1	12	14-4	350kcmil-6	1-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-12-W/R16*	2	12	14-4	350kcmil-6	2-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-24	1	24	14-4	350kcmil-6	1-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-24-W/R16*	2	24	14-4	350kcmil-6	2-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-30	1	30	14-4	350kcmil-6	1-17/32	4-3/32	2-17/32	10-32	3/8	Slot
NB-350-30-W/R16*	2	30	14-4	350kcmil-6	2-17/32	4-3/32	2-17/32	10-32	3/8	Slot
NB-350-36	1	36	14-4	350kcmil-6	1-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-36-W/R16*	2	36	14-4	350kcmil-6	2-17/32	4-23/32	2-17/32	10-32	3/8	Slot
NB-350-42	1	42	14-4	350kcmil-6	1-17/32	5-11/32	2-17/32	10-32	3/8	Slot
NB-350-42-W/R16*	2	42	14-4	350kcmil-6	2-17/32	5-11/32	2-17/32	10-32	3/8	Slot

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Part includes phenolic mounting block R-16

Tested to UL 486A/B, UL File E6207

Catalog Number	Figure Number	Number of Outlets	Wire Range	Length
NB-120	3	120	30 outlets 1/0-14 90 outlets 6-14	36.25"

UL File E6207

TYPE DE-OX®

ILSCO Oxide inhibitor is available in three different formulas: PLAIN, ZINC, COPPER. Oxide Inhibitor is applied to the connector prior to inserting the wire conductor, providing an air-tight seal around the conductor, preventing oxides from forming. All three formulas are available in a variety of package sizes.

- PLAIN - ILSCO DE-OX series is suitable for aluminum or copper terminations.
- ZINC - ILSCO DE-OX-Z series contains flecks of zinc mixed into the plain formula, providing improved pull-out strength and reduced operating temperatures for aluminum or copper terminations.
- COPPER - ILSCO DE-OX-C series contains flecks of copper mixed into the plain formula, providing improved pull-out strength and reduced operating temperatures for copper terminations.



PLAIN Catalog Number	Container Size & Type	Packaging
DE-OX -5CC	5cc Packet	Display Carton of 150
DE-OX-5CC-B4	5cc Packet	4 Per Bag, 25 Bags Per Carton
DE-OX-1OZ	1 oz. Tube	Display Carton of 50
DE-OX-4OZ	4 oz. Bottle	Display Carton of 12
DE-OX-8OZ	8 oz. Bottle	Display Carton of 12
DE-OX-1GAL	1 Gallon Can	1 Can
DE-OX-5GAL	5 Gallon Bucket	1 Bucket
UDE-OX-V-4OZ*+	4 oz. Bottle	Display Carton of 12
UDE-OX-V-8OZ*+	8 oz. Bottle	Display Carton of 12
ZINC Catalog Number	Container Size & Type	Packaging
DE-OX-Z-5CC	5cc Packet	Display Carton of 150
DE-OX-Z-1OZ	1 oz. Tube	Display Carton of 50
DE-OX-Z-4OZ	4 oz. Bottle	Display Carton of 12
DE-OX-Z-8OZ	8 oz. Bottle	Display Carton of 12
DE-OX-Z-1GAL	1 Gallon Can	1 Can
DE-OX-Z-5GAL	5 Gallon Bucket	1 Bucket
COPPER Catalog Number	Container Size & Type	Packaging
DE-OX-C-5CC	5cc Packet	Display Carton of 150
DE-OX-C-1OZ	1 oz. Tube	Display Carton of 50
DE-OX-C-4OZ	4 oz. Bottle	Display Carton of 12
DE-OX-C-8OZ	8 oz. Bottle	Display Carton of 12
DE-OX-C-1GAL	1 Gallon Can	1 Can
DE-OX-C-5GAL	5 Gallon Bucket	1 Bucket

* V denotes synthetic base, chalk color, doesn't stain blankets, etc.

+ Not UL Listed
UL File E312012

K

TYPE DS

Features

- Available in 1 LB and 5 LB packages
- Remains pliable
- Non-corrosive
- Can be painted immediately

Benefits

- Provides convenience of selecting the right size for the job
- Will not dry out, crack and fall out of installation
- Will not irritate skin, or corrode metals, or have harmful effects on plastics
- No need to wait for product to dry



Catalog Number

DS-1

DS-5

Packaging

10 1 lb. bags

5 5 lb. bags


TYPE NBW

Features

- Individually packaged
- Aluminum nut and bolt
- Belleville washer

Benefits

- All components for mounting one connector are kept together to avoid mismatched hardware
- Provides consistent and even thermal expansion and contraction to prevent loosening of mounting hardware due to heat cycling
- Maintains tension on connection through thermal expansion and contraction



Catalog Number	Bolt Size	Bolt Length	Included In Kit
NBW-38-125	3/8-16	1-1/4	Aluminum Nut, Stainless Steel Belleville Washer, Aluminum Flat Washer, Stainless Steel Flat Washer, Aluminum Bolt
NBW-50-150	1/2-13	1-1/2	Aluminum Nut, Stainless Steel Belleville Washer, Aluminum Flat Washer, Stainless Steel Flat Washer, Aluminum Bolt
NBW-50-200	1/2-13	2	Aluminum Nut, Stainless Steel Belleville Washer, Aluminum Flat Washer, Stainless Steel Flat Washer, Aluminum Bolt
NBW-50-250	1/2-13	2-1/2	Aluminum Nut, Stainless Steel Belleville Washer, Aluminum Flat Washer, Stainless Steel Flat Washer, Aluminum Bolt
NBW-58-250	5/8-11	2-1/2	Aluminum Nut, Stainless Steel Belleville Washer, Aluminum Flat Washer, Stainless Steel Flat Washer, Aluminum Bolt
NBW-58-300	5/8-11	3	Aluminum Nut, Stainless Steel Belleville Washer, Aluminum Flat Washer, Stainless Steel Flat Washer, Aluminum Bolt

TYPE TIES

Features

- Quick & Easy
- Strong & Flexible
- Nylon 6/6

Benefits

- Can accommodate .75" to 15" bundle diameter
- Tensile strengths from 18 lbs to 250 lbs
- Resists weather & chemicals


Heavy Duty Cable Ties

Catalog Number	Length	Width	Color	Tensile Strength	Bundle Diameter	Bag Qty
93180	25.0	0.35	NATURAL	175 LBS.	7.0	100
93280	25.0	0.35	UV BLACK	175 LBS.	7.0	100
93195	36.5	0.35	NATURAL	175 LBS.	10.7	50
93295	36.5	0.35	UV BLACK	175 LBS.	10.7	50
93199	48.0	0.35	NATURAL	175 LBS.	15.0	50
93299	48.0	0.35	UV BLACK	175 LBS.	15.0	50

Super Heavy Duty Cable Ties

Catalog Number	Length	Width	Color	Tensile Strength	Bundle Diameter	Bag Qty
93190	22.0	0.50	NATURAL	250 LBS.	6.0	100
93290	22.0	0.50	UV BLACK	250 LBS.	6.0	100
93196	34.0	0.50	NATURAL	250 LBS.	10.1	50
93296	34.0	0.50	UV BLACK	250 LBS.	10.1	50

TYPE TIES

Features

- Quick & Easy
- Strong & Flexible
- Nylon 6/6

Benefits

- Can accommodate .75" to 15" bundle diameter
- Tensile strengths from 18 lbs to 250 lbs
- Resists weather & chemicals



Standard Cable Ties

Catalog Number	Length	Width	Color	Tensile Strength	Bundle Diameter	Bag Qty
93110	4.0	0.10	NATURAL	18 LBS.	.75	100
93110M	4.0	0.10	NATURAL	18 LBS.	.75	1000
93210	4.0	0.10	UV BLACK	18 LBS.	.75	100
93210M	4.0	0.10	UV BLACK	18 LBS.	.75	1000
93120	5.7	0.14	NATURAL	40 LBS.	1.25	100
93120M	5.7	0.14	NATURAL	40 LBS.	1.25	1000
93220	5.7	0.14	UV BLACK	40 LBS.	1.25	100
93220M	5.7	0.14	UV BLACK	40 LBS.	1.25	1000
93130	8	0.19	NATURAL	50 LBS.	2.0	100
93130M	8	0.19	NATURAL	50 LBS.	2.0	1000
93230	8	0.19	UV BLACK	50 LBS.	2.0	100
93230M	8	0.19	UV BLACK	50 LBS.	2.0	1000
93150	11.8	0.19	NATURAL	50 LBS.	3.0	100
93150M	11.8	0.19	NATURAL	50 LBS.	3.0	1000
93250	11.8	0.19	UV BLACK	50 LBS.	3.0	100
93250M	11.8	0.19	UV BLACK	50 LBS.	3.0	1000
93160	14.6	0.19	NATURAL	50 LBS.	4.0	100
93160M	14.6	0.19	NATURAL	50 LBS.	4.0	1000
93260	14.6	0.19	UV BLACK	50 LBS.	4.0	100
93260M	14.6	0.19	UV BLACK	50 LBS.	4.0	1000
93170	14.5	0.30	NATURAL	120 LBS.	4.0	100
93170D	14.5	0.30	NATURAL	120 LBS.	4.0	500
93270	14.5	0.30	UV BLACK	120 LBS.	4.0	100
93270D	14.5	0.30	UV BLACK	120 LBS.	4.0	500
93185	28	0.30	NATURAL	120 LBS.	8.0	100
93185D	28	0.30	NATURAL	120 LBS.	8.0	500
93285	28	0.30	UV BLACK	120 LBS.	8.0	100
93285D	28	0.30	UV BLACK	120 LBS.	8.0	500

TYPE TIES

Features

- Quick & Easy
- Strong & Flexible
- Nylon 6/6

Benefits

- Can accommodate .75" to 15" bundle diameter
- Tensile strengths from 18 lbs to 250 lbs
- Resists weather & chemicals


Mounting Head Cable Ties

Catalog Number	Length	Width	Bolt Size	Color	Tensile Strength	Bundle Diameter	Bag Qty
93310	4.5	.10	#4	NATURAL	18 LBS.	.62	100
93410	4.5	.10	#4	UV BLACK	18 LBS.	.62	100
93320	5.9	.14	#8	NATURAL	40 LBS.	1.25	100
93420	5.9	.14	#10	UV BLACK	40 LBS.	1.25	100
93340	8	.19	#10	NATURAL	50 LBS.	2	100
93440	8	.19	#10	UV BLACK	50 LBS.	2	100
93350	12.6	.19	#10	NATURAL	50 LBS.	3	100
93450	12.6	.19	#10	UV BLACK	50 LBS.	3	100
93380	15	.19	#10	NATURAL	50 LBS.	4	100
93480	15	.19	#10	UV BLACK	50 LBS.	4	100
93390	15	.30	#10	NATURAL	120 LBS.	4	100
93490	15	.30	#10	UV BLACK	120 LBS.	4	100

Push Mount Cable Ties

Catalog Number	Length	Width	Color	Tensile Strength	Bundle Diameter	Bag Qty
93345	7.9	.19	NATURAL	50 LBS.	2	100
93445	7.9	.19	UV BLACK	50 LBS.	2	100

Releasable Cable Ties

Catalog Number	Length	Width	Color	Tensile Strength	Bundle Diameter	Bag Qty
93620	5.9	.30	NATURAL	50 LBS.	1.2	100
93720	5.9	.30	UV BLACK	50 LBS.	1.2	100
93640	7.8	.30	NATURAL	50 LBS.	2	100
93740	7.8	.30	UV BLACK	50 LBS.	2	100
93650	10.5	.30	NATURAL	50 LBS.	3	100
93750	10.5	.30	UV BLACK	50 LBS.	3	100

TYPE TIES

Features

- Quick & Easy
- Strong & Flexible
- Nylon 6/6

Benefits

- Can accommodate .75" to 15" bundle diameter
- Tensile strengths from 18 lbs to 250 lbs
- Resists weather & chemicals



Colored Cable Ties



Catalog Number	Length	Width	Color	Tensile Strength	Bundle Diameter	Bag Qty
93110-R	4.0	0.10	RED	18 LBS.	.75	100
93230-R	8	0.19	RED	50 LBS.	2.0	100
93110-GR	4.0	0.10	GREEN	18 LBS.	.75	100
93230-GR	8	0.19	GREEN	50 LBS.	2.0	100
93110-Y	4.0	0.10	YELLOW	18 LBS.	.75	100
93230-Y	8	0.19	YELLOW	50 LBS.	2.0	100
93110-BL	4.0	0.10	BLUE	18 LBS.	.75	100
93230-BL	8	0.19	BLUE	50 LBS.	2.0	100
93110-OR	4.0	0.10	ORANGE	18 LBS.	.75	100
93230-OR	8	0.19	ORANGE	50 LBS.	2.0	100

Stainless Steel Cable Ties

Catalog Number	Length	Width	Color	Tensile Strength	Bundle Diameter	Bag Qty
93804	8	.18	SS Steel (302/304)	100	2	100
93808	14	.18	SS Steel (302/304)	100	4	100
93812	20	.18	SS Steel (302/304)	100	6	100
93805	8	.30	SS Steel (302/304)	250	2	100
93809	14	.30	SS Steel (302/304)	250	4	100
93813	26	.30	SS Steel (302/304)	250	8	100

TYPE TIES

Features

- Quick & Easy
- Strong & Flexible
- Nylon 6/6
- Adhesive backed mounting bases

Benefits

- Can accommodate .75" to 15" bundle diameter
- Tensile strengths from 18 lbs to 250 lbs
- Resists weather & chemicals
- Easy Installation


Mounting Bases


Catalog Number	Length	Width	Height	Color	Bolt Size	Slot Size	Bag Qty
93511	.75	.75	.205	NATURAL	#6	.05	100
93513	.75	.75	.205	UV BLACK	#6	.05	100
93510	1.0	1.0	.215	NATURAL	#8	.07	100
93512	1.0	1.0	.215	UV BLACK	#8	.07	100
93514	2.0	2.0	.300	NATURAL	#6 & #8	.30	100
93515	2.0	2.0	.300	UV BLACK	#6 & #8	.30	100

Cable Tie Installation Tool

Catalog Number	Color	Description
94400	RED	Installation and cutoff tool for standard cable ties 18-50 lbs

Cable Tie Kit

Catalog Number	Qty	Kit Includes
93403	1	94400 Cable Tie Installation Tool
	50	93230 8 UV Black 50 LB Cable Ties
	100	93120 5.7 Natural 40 LB Cable Ties
	10	93510 1 X 1 Natural Mounting Bases



All Inclusive Merchandiser


Merchandiser-3ft:

- 1 Gondola
- 1 Header
- 5 Laser Engraved Wire Shelves
- 15 4" Blue Bins
- 5 6 1/2" Blue Bins
- 10 8" Blue Bins
- 25 Basket Clips for Labels
- 25 Basket Clip labels *

Optional (part numbers noted):

Wheel-Kit-3ft (for 3ft merchandiser)

* Basket Clip Labels are printed on demand.
Part #'s required to print labels.



Blue-Bin-4
Blue-Bin-6
Blue-Bin-8



Wheel-Kit-3ft



CONTACT ILSCO OF CANADA

1050 Lakeshore Road East, Mississauga, Ontario, Canada L5E1E4

Phone 905 274-2341 Fax 905 274-8763

Technical..... 371 - 377

Decimal Conversion Chart..... 378

Wire Size Charts 379

Wire Amperage Rating Chart..... 380 - 381

Torque Index 382

Torque Information 383

RoHS Compliance 384

Cross Reference Guide 385

A brief summary of comparative properties of metals suitable for current carrying applications and required features of the connector are listed below in Table 1.

Order	Metal	% Volume Conductivity	Relative Abundance earth's surface %
1.	Silver	108.3	
2.	Copper	100.0	0.088%
3.	Gold	73.4	
4.	Aluminum	64.9	8.0%
5.	Magnesium	38.0	1.8%

The commercial use of copper and aluminum for electrical application are obvious, in terms of economic justifications. The accelerated use of aluminum becomes even more obvious when realized that it requires twice the amount of copper by weight, to carry a specified amount of current. At the unit price per pound of prime metal it is readily seen why aluminum is increasing in electrical application.

As the next logical step, an examination of available alloys and forms of aluminum should be made to determine the optimum choice for the manufacture of electrical connectors. Please refer to Table 2

Alloy	Form	Typical Yield Strength	Minimum Yield Strength	Elongation	% Conductivity
6061-T6	Extrusion	40-45,000	35,000	12	40
6063-T6	Extrusion	31,000	25,000	12	53
Al. Mag.	Sand Cast	22,000	22,000	12	25
356-T6	Sand Cast	24,000	24,000	3½	39
AXS 679 (380A)	Die Cast	21,000	21,000	3	25

During the initial analysis of these materials, reference was made to the experience over many years of the effect of stress on tensioned overhead conductors. It is well documented that in order to assure mechanical stability of these conductors, over long periods of time, it is necessary to design the line so that the maximum stress will not exceed 50% of the conductors rated breaking strength. In the case of aluminum conductors the alloy most commonly used is EC-H19 having a yield strength of 22,000 psi and a tensile strength of 24,000 psi. From the foregoing it is obvious that a maximum stress level of 12,000 psi representing 50% of ultimate tensile strength or approximately 55% of yield strength, will result in the conductor remaining mechanically stable throughout its life.

With this initial premise being established it was necessary to confirm whether or not a determinable stress limit could be effectively applied to the design of connectors. The method of testing used to confirm this premise is noted in detail in table 8.


Additional factors of design were recognized as necessary to achieve a stable and reliable connector. Requirements of aluminum connectors for use with aluminum or copper conductors.

- a. Adequate strength of the connector to prevent creep loss in the connection from exceeding the creep loss of the conductor.
- b. Strong enough clamping force (torque) to keep the connector operating temperature at a level below the operating temperature of the maximum size conductor.
- c. High enough conductivity to provide adequate efficiency (minimum of 40%).

To illustrate the significance of these requirements, Table 3 headed *Terminal life Cycle*, presents an examination of terminal temperature in relation to clamping force. The horizontal dotted line indicates the temperature of the conductor at maximum rise. The tightening characteristic curve shows a lowering of terminal temperature rise with an increased clamping force. Terminal temperature, measured in degrees centigrade, is used in our illustration as a measure of connector resistance. As the tightening characteristic curve approaches the dotted conductor temperature line at the same current value, the connector and conductor resistance approximate each other.

The curves labeled Relaxation Characteristic, merely indicate the anticipated progression a connector would follow to failure, once clamping force has been reduced to a level where terminal resistance can no longer be maintained at a low level. Point A on each curve represents that point where resistance is sufficiently high to cause and elevated operating temperature of the connector which will then progress to ultimate connector failure.

Proceeding with the assumption that stress limitation is a most critical factor in connector design it was then necessary to select and test the alloy materials which evidence the most favorable conductivity/yield strength/economic factors. The initial selection of aluminum alloy 6061-T6 has long since been determined to be the best available material from which to fabricate connectors for use with both aluminum and copper conductors.



Before proceeding further a definition of terms used, to assure understanding of the basis for the conclusions reached later in the paper, are listed.

Physical Property of Aluminum

N

Tensile Strength


The maximum tensile load which a material is capable of withstanding under gradually and uniformly applied loading, divided by the original cross-sectional area in the minimum plane perpendicular to the direction of loading. Commonly the term is taken to mean the same as "ultimate tensile strength" or the less accurate "breaking strength."

Yield Strength

The stress at which material exhibits a specified permanent set. The value of set used for aluminum and its alloys is 0.002 inch per inch or 0.2%. For the aluminum alloys the yield strength in tension and compression are approximately the same.

Elongation

The increase in distance between two gage marks that results from stressing the specimen in tension to fracture. Please see table 5.



To record elongation, tensile loading is continually applied until specimen fractures, at which time two pieces are mated and distance between gage marks accurately measured. The resultant dimension divided by the original increment provides the value expressed in %, of the materials ability to stretch under load, or its elongation.

Elastic Limit

The stress value below which no permanent set or permanent deformation takes place; the highest stress which will permit return to original shape upon removal of force causing the stress.

Elasticity

The ability of a material to return to its original shape and size upon removal of a load below the elastic limit.


Creep

A precise unit of measure disclosing the increase in dimension of a unit specimen having a specified area =A, an applied force =W with resultant constant stress= $\frac{W}{A}$. The initial increment of measurement L, is

effected by three factors resulting in amount of increase or creep, stress, time and temperature.

To determine and express the creep rate for a given specimen in terms of inches of creep, per inches of original gage length, per hour, the factors of stress and temperature must be maintained constant. A change in either or both, will result in a change in the creep rate. Please refer to Tables 6 and 7.


Table 6
Creep Measurement



WIRE AREA = A

- 1.) CONSTANT STRESS (PSI) $\frac{W}{A}$
- 2.) TOTAL CREEP = $\Delta \ell$
 CREEP RATE = $\frac{\Delta \ell}{L \times \text{HRS}}$ Inches / Inch / Hour
 (At Temperature T)
- 3.) TEMPERATURE CONSTANT FOR EACH MEASUREMENT
 VARIED TO REDUCE CREEP VS TEMP. CURVES

Table 7
Creep Rate vs. Temp.



Cold Flow

As compared to Creep, cold flow has no units of measure. The best description of cold flow relating to application within the electrical industry, is an excessively high rate of creep i.e. normal creep rate static load condition would be expressed in a fraction of an inch per inch of length. Cold flow, conversely if possible to measure it in definable terms, would be expressed in terms of inches of movement per inch of length. Cold flow then can be expressed as movement of appreciable magnitude occurring at a stress level in a very short length of time at an ambient temperature. Neither time or temperature are critical in assessing the effecting force of cold flow.

It is significant to realize that it is an absolute necessity to have cold flow of the conductor within a bolted connector to develop the desired low resistance contact, required for electrical/mechanical stability of the connection. So is it necessary to have cold flow of both the conductor and connector in the making of a compression connection. In these two instances a mechanical union of the two components is made by means of an externally applied force to assure both electrical and mechanical reliability. In the case of a soldered or welded connection this component union is made metallurgically.

Creep Loss

The unit of measurement, expressed in % of the initially applied mechanical force to a connection, divided by the resultant measured force after the unit has been subjected to controlled loadings of temperature and time. This value is relatively easy to determine for bolted connectors by accurately measuring applied torque before and after applying control factors of time and temperature. The resultant loss of torque is the creep loss experienced within the connection assembly.

It is difficult and inaccurate to project anticipated creep loss within a compression assembly since there is no way of effecting a measurement of the initially applied force and the resultant force remaining on the connection after the mechanical or hydraulic compression tool is removed from the connector.


The maximum desired creep loss in a connector/conductor assembly stated, is that portion of the total creep component represented by the creep component of the conductor alone.

This brings us to the threshold of the discussion of design parameters used by IlSCO in the manufacturer of aluminum connectors.

N

Table 8
Tolerable Creep Limits for Aluminum Connector

Material
Aluminum 6061T6



To best understand the importance of the function of creep components in a connection assembly, recall the definition of cold flow wherein it is stated that it is necessary to the formulation of an electrically/mechanically stable connection to have cold flow of the conductor. Since cold flow is by definition a high rate of creep and since creep occurs only where constant stress is applied; the connection will undergo creep movement as a result of load cycling. It is mandatory that the connector be so designed that all creep within the assembly occur in the conductor.

The determination of tolerable creep limits for aluminum connector design were established through the test described below and pictured in Table 8

This test established the maximum stress which can be imposed on an aluminum connector made from Alloy 6061-T6 as being 23,000 psi which is approximately 1/2 typical yield strength. The value of creep loss for the first three connectors were identical; 13.3% whereas the fourth exhibited a 25% creep loss. The explanation is simply that the loads applied to the section modulus of each of the first three test connectors resulted in a stress level below the elastic limit of the material and thereby causing no creep movement in the connector. The conductor on the other hand must be physically moved, and this conductor movement resulted in a redistribution of strand displacement and resultant redistribution of load. The 13.3% creep loss therefore can be stated as being that movement occurring within the conductor.

The Fourth sample, however, evidenced in higher creep loss, resulting from creep in the conductor and the connector since the connector was stressed beyond its elastic limit and contributed to the total creep of the assembly.

The confirmation by actual test of this limitation of stress to 1/2 the materials yield strength has been utilized in the design of all connectors manufactured by IlSCO.

Preparation of wire

When an aluminum cable is installed, certain procedures should be followed to insure a good connection.

1. The insulation should be stripped with a whittling motion to prevent the cable from being nicked.
2. The cable should then be cleaned with a wire brush. This removes the oxides from the surface of the conductor.
3. In many cases, an oxide inhibitor is applied to the conductor immediately prior to installation. However, this is not absolutely necessary.
4. For mechanical connectors, the set screw should be tightened. After a few seconds, the set screw should be retightened to insure a good connection. For compression connectors, the lug should be crimped around the conductor using the proper tool.

MILLIMETER/DECIMAL/FRACTION CONVERSION CHART

Milli-meter	Decimal	Fraction (inches)	Milli-meter	Decimal	Fraction (inches)	Milli-meter	Decimal	Fraction (inches)	Milli-meter	Decimal	Fraction (inches)	Milli-meter	Decimal	Fraction (inches)
0.1	.0039		5.159	.2031	13/64	10.2	.4016		15.3	.6024		20.3	.7992	
0.2	.0079		5.2	.2047		10.3	.4055		15.4	.6063		20.4	.8031	
0.3	.0118		5.3	.2087		10.319	.4063	13/32	15.478	.6094	39/64	20.5	.8071	
0.397	.0156	1/64	5.4	.2126		10.4	.4094		15.5	.6102		20.6	.8110	
0.4	.0157		5.5	.2165		10.5	.4134		15.6	.6142		20.638	.8125	13/16
0.5	.0197		5.556	.2188	7/32	10.6	.4173		15.7	.6181		20.7	.8150	
0.6	.0236		5.6	.2205		10.7	.4213		15.8	.6220		20.8	.8189	
0.7	.0276		5.7	.2244		10.716	.4219	27/64	15.875	.6250	5/8	20.9	.8228	
0.794	.0313	1/32	5.8	.2283		10.8	.4252		15.9	.6260		21.0	.8268	
0.8	.0315		5.9	.2323		10.9	.4291		16.0	.6299		21.034	.8281	53/64
0.9	.0354		5.953	.2344	15/64	11.0	.4331		16.1	.6339		21.1	.8307	
1.0	.0394		6.0	.2362		11.1	.4370		16.2	.6378		21.2	.8346	
1.1	.0433		6.1	.2402		11.113	.4375	7/16	16.272	.6406	41/64	21.3	.8386	
1.191	.0469	3/64	6.2	.2441		11.2	.4409		16.3	.6417		21.4	.8425	
1.2	.0472		6.3	.2480		11.3	.4449		16.4	.6457		21.431	.8438	27/32
1.3	.0512		6.350	.2500	1/4	11.4	.4488		16.5	.6496		21.5	.8465	
1.4	.0551		6.4	.2520		11.5	.4528		16.6	.6535		21.6	.8504	
1.5	.0591		6.5	.2559		11.509	.4531	29/64	16.669	.6563	21/32	21.7	.8543	
1.588	.0625	1/16	6.6	.2598		11.6	.4567		16.7	.6575		21.8	.8583	
1.6	.0630		6.7	.2638		11.7	.4606		16.8	.6614		21.828	.8594	55/64
1.7	.0669		6.747	.2656	17/64	11.8	.4646		16.9	.6654		21.9	.8622	
1.8	.0709		6.8	.2677		11.9	.4685		17.0	.6693		22.0	.8661	
1.9	.0748		6.9	.2717		11.906	.4688	15/32	17.066	.6719	43/64	22.1	.8701	
1.984	.0781	5/64	7.0	.2756		12.0	.4724		17.1	.6732		22.2	.8740	
2.0	.0787		7.1	.2795		12.1	.4764		17.2	.6772		22.225	.8750	7/8
2.1	.0827		7.144	.2813	9/32	12.2	.4803		17.3	.6811		22.3	.8780	
2.2	.0866		7.2	.2835		12.3	.4843		17.4	.6850		22.4	.8819	
2.3	.0906		7.3	.2874		12.303	.4844	31/64	17.463	.6875	11/16	22.5	.8858	
2.381	.0938	3/32	7.4	.2913		12.4	.4882		17.5	.6890		22.6	.8898	
2.4	.0945		7.5	.2953		12.5	.4921		17.6	.6929		22.622	.8906	57/64
2.5	.0984		7.541	.2969	19/64	12.6	.4961		17.7	.6968		22.7	.8937	
2.6	.1024		7.6	.2992		12.7	.5000	1/2	17.8	.7008		22.8	.8976	
2.7	.1063		7.7	.3031		12.8	.5039		17.859	.7031	45/64	22.9	.9016	
2.778	.1094	7/64	7.8	.3071		12.9	.5079		17.9	.7047		23.0	.9055	
2.8	.1102		7.9	.3110		13.0	.5118		18.0	.7087		23.019	.9063	29/32
2.9	.1142		7.938	.3125	5/16	13.097	.5156	33/64	18.1	.7126		23.1	.9094	
3.0	.1181		8.0	.3150		13.1	.5157		18.2	.7165		23.2	.9134	
3.1	.1220		8.1	.3189		13.2	.5197		18.256	.7188	23/32	23.3	.9173	
3.175	.1250	1/8	8.2	.3228		13.3	.5236		18.3	.7205		23.4	.9213	
3.2	.1260		8.3	.3268		13.4	.5276		18.4	.7244		23.416	.9219	59/64
3.3	.1299		8.334	.3281	21/64	13.494	.5313	17/32	18.5	.7283		23.5	.9252	
3.4	.1339		8.4	.3307		13.5	.5315		18.6	.7323		23.6	.9291	
3.5	.1378		8.5	.3346		13.6	.5354		18.653	.7344	47/64	23.7	.9331	
3.572	.1406	9/64	8.6	.3386		13.7	.5394		18.7	.7362		23.8	.9370	
3.6	.1417		8.7	.3425		13.8	.5433		18.8	.7402		23.813	.9375	15/16
3.7	.1457		8.731	.3438	11/32	13.891	.5469	35/64	18.9	.7441		23.9	.9409	
3.8	.1496		8.8	.3465		13.9	.5472		19.0	.7480		24.0	.9449	
3.9	.1535		8.9	.3504		14.0	.5512		19.050	.7500	3/4	24.1	.9488	
3.969	.1563	5/32	9.0	.3543		14.1	.5551		19.1	.7520		24.2	.9528	
4.0	.1575		9.1	.3583		14.2	.5591		19.2	.7559		24.209	.9531	61/64
4.1	.1614		9.128	.3594	23/64	14.288	.5625	9/16	19.3	.7598		24.3	.9567	
4.2	.1654		9.2	.3622		14.3	.5630		19.4	.7638		24.4	.9606	
4.3	.1693		9.3	.3661		14.4	.5669		19.447	.7656	49/64	24.5	.9646	
4.366	.1719	11/64	9.4	.3701		14.5	.5709		19.5	.7677		24.6	.9685	
4.4	.1732		9.5	.3740		14.6	.5748		19.6	.7717		24.606	.9688	31/32
4.5	.1772		9.525	.3750	3/8	14.684	.5781	37/64	19.7	.7756		24.7	.9724	
4.6	.1811		9.6	.3780		14.7	.5787		19.8	.7795		24.8	.9764	
4.7	.1850		9.7	.3819		14.8	.5827		19.844	.7813	25/32	24.9	.9803	
4.763	.1875	3/16	9.8	.3858		14.9	.5866		19.9	.7835		25.0	.9843	
4.8	.1890		9.9	.3898		15.0	.5906		20.0	.7874		25.003	.9844	63/64
4.9	.1929		9.922	.3906	25/64	15.081	.5938	19/32	20.1	.7913		25.1	.9882	
5.0	.1969		10.0	.3937		15.1	.5945		20.2	.7953		25.2	.9921	
5.1	.2008		10.1	.3976		15.2	.5984		20.241	.7969	51/64	25.3	.9961	
												25.400	1.0000	1

AWG VS. METRIC WIRE SIZES

Circ. Mils	Equivalent Circ. Mils	Awg. Size	Metric Wire Size mm ²	Stranding/ Wire Diameter Per Strand		Approximate Overall Diameter		Circ. Mils	Equivalent Circ. Mils	Awg. Size	Metric Wire Size mm ²	Stranding/ Wire Diameter Per Strand		Approximate Overall Diameter	
				in	mm	in	mm					in	mm		
-	937	-	0.50	1/.032	1/.813	.032	0.81	83690	-	1	-	19/.0664	19/1.69	.332	8.43
1020	-	20	-	7/.0121	7/.030	.036	0.91	-	98680	-	50	19/.073	19/1.85	.365	9.27
-	1480	-	0.75	1/.039	1/.991	.039	0.99	105600	-	1/0	-	19/.0745	19/1.89	.373	9.46
1620	-	18	-	1/.0403	1/1.02	.040	1.02	133100	-	2/0	-	19/.0837	19/2.13	.419	10.6
1620	-	18	-	7/.0152	7/.386	.046	1.16	-	138100	-	70	19/.086	19/2.18	.430	10.9
-	1974	-	1.0	1/.045	1/1.14	.045	1.14	167800	-	3/0	-	19/.094	19/2.39	.470	11.9
-	1974	-	1.0	7/.017	7/.432	.051	1.30	167800	-	3/0	-	37/.0673	37/1.71	.471	12.0
2580	-	16	-	1/.0508	1/1.29	.051	1.29	-	187500	-	95	19/.101	19/2.57	.505	12.8
2580	-	16	-	7/.0192	7/.488	.058	1.46	-	187500	-	95	37/.072	37/1.83	.504	12.8
-	2960	-	1.5	1/.055	1/1.40	.055	1.40	211600	-	4/0	-	19/.1055	19/2.68	.528	13.4
-	2960	-	1.5	7/.021	7/.533	.063	1.60	-	237.8 kcmil	-	120	37/.081	37/2.06	.567	14.4
4110	-	14	-	1/.0641	1/1.63	.064	1.63	250 kcmil	-	-	-	37/.0822	37/2.09	.575	14.6
4110	-	14	-	7/.0242	7/.615	.073	1.84	300 kcmil	-	-	150	37/.090	37/2.29	.630	16.0
-	4934	-	2.5	1/.071	1/1.80	.071	1.80	350 kcmil	-	-	-	37/.0973	37/2.47	.681	17.3
-	4934	-	2.5	7/.027	7/.686	.081	2.06	-	365.1 kcmil	-	185	37/.100	37/2.54	.700	17.8
6530	-	12	-	1/.0808	1/2.05	.081	2.05	400 kcmil	-	-	-	37/.104	37/2.64	.728	18.5
6530	-	12	-	7/.0305	7/.775	.092	2.32	-	473.6 kcmil	-	240	37/.114	37/2.90	.798	20.3
-	7894	-	4	1/.089	1/2.26	.089	2.26	-	473.6 kcmil	-	240	61/.089	61/2.26	.801	20.3
-	7894	-	4	7/.034	7/.864	.102	2.59	500 kcmil	-	-	-	37/.1162	37/2.95	.813	20.7
-	-	-	-	-	-	-	-	500 kcmil	-	-	-	61/.0905	61/2.30	.814	20.7
10380	-	10	-	1/.1019	1/2.59	.102	2.59	-	592.1 kcmil	-	300	61/.099	61/2.51	.891	22.6
10380	-	10	-	7/.0385	7/.978	.116	2.93	-	61/.0992	-	300	61/.0992	61/2.52	.893	22.7
-	11840	-	6	1/.109	1/2.77	.109	2.77	600 kcmil	-	-	-	61/.1071	61/2.72	.964	24.5
-	11840	-	6	7/.042	7/1.07	.126	3.21	700 kcmil	-	-	-	61/.1109	61/2.82	.998	25.4
13090	-	9	-	1/.1144	1/2.91	.114	2.91	750 kcmil	-	-	-	91/.0908	91/2.31	.999	25.4
13090	-	9	-	7/.0432	7/1.10	.130	3.30	750 kcmil	-	-	-	61/.114	61/2.90	1.026	26.1
16510	-	8	-	1/.1285	1/3.26	.128	3.26	-	789.4 kcmil	-	400	61/.1145	61/2.91	1.031	26.2
16510	-	8	-	7/.0486	7/1.23	.146	3.70	800 kcmil	-	-	-	91/.0938	91/2.38	1.032	26.2
-	19740	-	10	1/.141	1/3.58	.141	3.58	800 kcmil	-	-	-	61/.1280	61/3.25	1.152	29.3
-	19740	-	10	7/.054	7/1.37	.162	4.12	1000 kcmil	986.8 kcmil	-	500	91/.1048	91/2.66	1.153	29.3
20820	-	7	-	1/.1443	1/3.67	.144	3.67	1000 kcmil	-	-	-	91/.117	91/2.97	1.287	32.7
20820	-	7	-	7/.0545	7/1.38	.164	4.15	-	1233.7 kcmil	-	625	91/.117	91/2.97	1.287	32.7
26240	-	6	-	1/.162	1/4.11	.162	4.11	1250 kcmil	-	-	-	91/.1172	91/2.98	1.289	32.7
26240	-	6	-	7/.0612	7/1.55	.184	4.66	1250 kcmil	-	-	-	127/.0992	127/2.52	1.290	32.8
-	31580	-	16	7/.068	7/1.73	.204	5.18	1500 kcmil	-	-	-	91/.1284	91/3.26	1.412	35.9
33090	-	5	-	7/.0688	7/1.75	.206	5.24	1500 kcmil	-	-	-	127/.1087	127/2.76	1.413	35.9
41740	-	4	-	7/.0772	7/1.96	.232	5.88	-	1578.8 kcmil	-	800	91/.132	91/3.35	1.452	36.9
-	49340	-	25	7/.085	7/2.16	.255	6.48	-	1973.5 kcmil	-	1000	91/.147	91/3.73	1.617	41.1
-	49340	-	25	19/.052	19/1.32	.260	6.60	2000 kcmil	-	-	-	127/.1255	127/3.19	1.632	41.5
52620	-	3	-	7/.0867	7/2.20	.260	6.61	2000 kcmil	-	-	-	169/.1088	169/2.76	1.632	41.5
66360	-	2	-	7/.0974	7/2.47	.292	7.42	-	-	-	-	-	-	-	-
-	69070	-	35	7/.100	7/2.54	.300	7.62	-	-	-	-	-	-	-	-
-	69070	-	35	19/.061	19/1.55	.305	7.75	-	-	-	-	-	-	-	-

DIESEL LOCOMOTIVE AND CAR WIRING CABLE

Conductor Stranding	Approx. Size Awg	Circular Mil Area	Conductor Diameter Inches
19/0117	16	2601	.060
19/27	14	3831	.096
19/25	12	6088	.116
27/24	10	10910	.146
37/24	8	14950	.166
61/24	6	24640	.226
91/24	5	36760	.256
105/24	4	42420	.286
125/24	3	50500	.300
150/24	2	60600	.366
225/24	1	90900	.424
275/24	1/0	111100	.454
325/24	2/0	131300	.494
450/24	3/0	181800	.604
550/24	4/0	222200	.634
650/24	262.6	262600	.712
775/24	313.1	313100	.792
925/24	373.7	373700	.852
1100/24	444.4	444400	.922
1325/24	535.3	535300	1.022
1600/24	646.4	646400	1.122
1925/24	777.7	777700	1.182
2300/24	929.2	929200	1.292
2750/24	1111.0	1111000	1.43

ILSCO Amperage Rating

310.15

ARTICLE 310 — CONDUCTORS FOR GENERAL WIRING

Table 310.15(B)(16) (formerly Table 310.16) Allowable Ampacities of Insulated Conductors Rated Up to and Including 2000 Volts, 60°C Through 90°C (140°F Through 194°F), Not More Than Three Current-Carrying Conductors in Raceway, Cable, or Earth (Directly Buried), Based on Ambient Temperature of 30°C (86°F)

Size AWG or kcmil	Temperature Rating of Conductor [See Table 310.104(A).]						Size AWG or kcmil
	60°C (140°F)	75°C (167°F)	90°C (194°F)	60°C (140°F)	75°C (167°F)	90°C (194°F)	
	Types TW, UF	Types RHW, THHW, THW, THWN, XHHW, USE, ZW	Types TBS, SA, SIS, FEP, FEPB, ML, RHH, RHW-2, THHN, THHW, THW-2, THWN-2, USE-2, XHH, XHHW, XHHW-2, ZW-2	Types TW, UF	Types RHW, THHW, THW, THWN, XHHW, USE	Types TBS, SA, SIS, THHN, THHW, THW-2, THWN-2, RHH, RHW-2, USE-2, XHH, XHHW, XHHW-2, ZW-2	
COPPER			ALUMINUM OR COPPER-CLAD ALUMINUM				
18**	—	—	14	—	—	—	—
16**	—	—	18	—	—	—	—
14**	15	20	25	—	—	—	—
12**	20	25	30	15	20	25	12**
10**	30	35	40	25	30	35	10**
8	40	50	55	35	40	45	8
6	55	65	75	40	50	55	6
4	70	85	95	55	65	75	4
3	85	100	115	65	75	85	3
2	95	115	130	75	90	100	2
1	110	130	145	85	100	115	1
1/0	125	150	170	100	120	135	1/0
2/0	145	175	195	115	135	150	2/0
3/0	165	200	225	130	155	175	3/0
4/0	195	230	260	150	180	205	4/0
250	215	255	290	170	205	230	250
300	240	285	320	195	230	260	300
350	260	310	350	210	250	280	350
400	280	335	380	225	270	305	400
500	320	380	430	260	310	350	500
600	350	420	475	285	340	385	600
700	385	460	520	315	375	425	700
750	400	475	535	320	385	435	750
800	410	490	555	330	395	445	800
900	435	520	585	355	425	480	900
1000	455	545	615	375	445	500	1000
1250	495	590	665	405	485	545	1250
1500	525	625	705	435	520	585	1500
1750	545	650	735	455	545	615	1750
2000	555	665	750	470	560	630	2000

*Refer to 310.15(B)(2) for the ampacity correction factors where the ambient temperature is other than 30°C (86°F).

**Refer to 240.4(D) for conductor overcurrent protection limitations.

Copyright 2012 National Fire Protection Association (NFPA). Licensed, by agreement, for individual use and single download on May 4, 2012 to Cheryl Hennessy of ILSCO. No other reproduction or transmission in any form permitted without written permission of NFPA. For inquires or to report unauthorized use, contact licensing@nfp.org.

Table 310.15(B)(3)(a) Adjustment Factors for More Than Three Current-Carrying Conductors in a Raceway or Cable

Number of Conductors ¹	Percent of Values in Table 310.15(B)(16) through Table 310.15(B)(19) as Adjusted for Ambient Temperature if Necessary
4-6	80
7-9	70
10-20	50
21-30	45
31-40	40
41 and above	35

¹Number of conductors is the total number of conductors in the raceway or cable adjusted in accordance with 310.15(B)(5) and (6).

TIGHTENING TORQUE VALUES FOR ILSCO MECHANICAL SCREW CONNECTORS

AWG. OR CIRCULAR MILL SIZE	TIGHTENING TORQUE IN INCH POUNDS	
	SCREW DRIVER	EXTERNAL DRIVE WRENCH
14	35	75
12	35	75
10	35	75
8	40	75
6	45	110
4	45	110
2	50	150
1	50	150
1/0	50	180
2/0	50	180
3/0		250
4/0		250
250		325
350		325
500		375
600		375
700		375
750		375
800		500
1000		500

TIGHTENING TORQUE VALUES FOR ILSCO SOCKETHEAD SCREW CONNECTORS

INTERNAL SOCKET SIZE ACROSS FLATS INCHES	TIGHTENING TORQUE IN INCH POUNDS
	1/8
5/32	100
3/16	120
7/32	150
1/4	200
5/16	275
3/8	375
1/2	500
9/16	600

Please reference the instruction sheet included with your connector for specific torque values.

ILSCO Torque Information


Table I shows the recommended tightening torques for silicon bronze, stainless steel, galvanized steel and aluminum alloy hardware. The shaded portion represents torques presently recommended by NEMA-CC1-1984 specification.

**TABLE I
TIGHTENING TORQUES**



Bolt Diameter	Nominal Torque Values			
	Silicon Bronze, Galvanized or Stainless Steel		Aluminum Alloy (Lubricated)	
	Ft.-Lbs.	Inch-Lbs.	Ft.-Lbs.	Inch-Lbs
5/16-18	15	180	—	—
3/8-16	20	240	14	168
1/2-13	40	480	25	300
5/8-11	55	660	40	480
3/4-10	80	960	70	840

For optimum efficiency, it is necessary that the correct bolt, nut and washer combination be used with the correct combination of conductor materials. Table II shows acceptable methods of joining different combinations of bus bar. Where different combinations of metals are being joined, a follow-up device such as a conical pressure washer is usually recommended if one, or both, bus materials are soft drawn aluminum. If both bars are hard drawn, large flat washers will suffice regardless of the bolt materials.

Other considerations which should be taken into account when selecting hardware are corrosion and vibration. For example, if severe corrosion is anticipated, non-corrosive materials such as stainless steel or silicon bronze, should be selected in preference to galvanized steel. If vibration is anticipated, the use of locking washers should be considered.



**TABLE II
METHODS OF JOINING BUS BARS**

If "A" Bar is and If "B" Bar is	Copper	Aluminum	Steel	Aluminum	Steel
	Copper	Copper	Copper	Aluminum	Aluminum
Hard Drawn Bus such as aluminum alloy. 	(1) Silicon Bronze (2) Stainless Steel	(1) Silicon Bronze (2) Aluminum (3) Stainless Steel	(1) Silicon Bronze (2) Stainless Steel	(1) Aluminum (2) Stainless Steel (3) Silicon Bronze, Plated	(1) Aluminum (2) Stainless Steel
Soft Drawn Bus such as EC-H13 Aluminum. 	(1) Silicon Bronze (2) Stainless Steel	(1) Silicon Bronze (2) Aluminum (3) Stainless Steel (4) Conical Pressure Washer Plated or Stainless Steel	(1) Silicon Bronze (2) Stainless Steel	(1) Aluminum (2) Stainless Steel (3) Silicon Bronze Plated (4) Conical Pressure Washer Plated or Stainless Steel	(1) Aluminum (2) Stainless Steel (3) Conical Pressure Washer Plated or Stainless Steel

(1) Denotes preferred hardware usage

Note: Contact sealant recommended between aluminum to aluminum and aluminum to copper connections, unless other protective measures are taken.

Bar Connections

The tang of a compression or a mechanical connector is a bus bar, which connects to another bus bar. If you remember the rule about wire brushing and using joint compound with bare (unplated) aluminum, you cannot go wrong. Plated parts should be cleaned with a solvent if they are dirty, but never abrade or otherwise disturb the plating! Fig. 3 shows a typical bar connection and the type of hardware used.




Figure 3. Contact surfaces must be clean. Use a joint compound with bare aluminum. Conical pressure washer is usually recommended if one, or both, bus materials are soft drawn aluminum.

N

Restriction of Hazardous Substances (RoHS)
European Directive 2002/95/EC

As of July 1st 2006 ILSCO Corporation is capable of supplying all items offered for sale compliant with the standards listed in the RoHS directive.

All cataloged items are RoHS Compliant unless noted otherwise.

ILSCO Corporation makes no independent representations or a warranty, expressed or implied, and assumes no liability in connection with the use of this information.

***Access to Cross Reference can be
found under Reference Tab
at www.ILSCO.com***

Two Ways to Search

1. Type in all or part of the competitive or IlSCO part number into the **SEARCH** box in the header, then click **GO**.
2. Click "Search Options" in the header. From there, you are given five ways to search.

By Keyword: Type in a keyword and click **GO**. For example, typing "splice" will return a list of products that can be used to splice conductor. You can click on any of the products listed and you will be taken to the catalog page.

By IlSCO Catalog #: Type in all or part of the IlSCO part number and click **GO**. You can click on any of the products listed and you will be taken to the catalog page.

By UPC/NAED Part #: Type in the IlSCO UPC number and click **GO**. The IlSCO corporate identifier, 783669, is already given. For example, typing "88774" will return information on "TA-2".

By Competitive Part #: Type in all or part of the competitive part number and click **GO**. You do not need to know the manufacturer. You are given a list of comparable IlSCO products. You can click on any of the products listed and you will be taken to the catalog page.

Choose a category: Select a product category from the list and click **GO**. You will receive a list of the product groups in that category. You can click on any of the products listed and you will be taken to the catalog page.

If your request is not in our database, you will be sent to a screen where you can send an e-mail to IlSCO's technical support department. Your request will be answered promptly.

This cross reference information has been compiled from tables, catalogs and data which are generally available. Since changes are made regularly in the industry, we cannot accept responsibility for any errors, but we will endeavor at all times to keep these tables up-to-date. Refer to our current catalog for exact specifications on ILSCO connectors. All connectors are not exact equals, but enough similarities exist that they can be used for the same application.

ILSCO Alpha Numeric Index

Catalog No.	Page No.	Catalog No.	Page No.
ACN	51-54	FP-1	337
ACL	51-54	GBL	169, 282
2ACL	55-56	GBT	170, 284
ACM	61-63	GGA	46, 256, 297
2ACN	55	GGC	47, 257, 298
ACO	64-65	GPL3	276, 313
ACO-90	66	GRC	206, 236, 303
5ACR	340	GRF	181, 285
AGC	167, 280	GRM	181, 285
AH	75	GS	277
AK	113, 165	GSR	277
AS	69-71	GTA	116, 137
ASK	178, 293	GTC	119, 139
ASL	57	GTT	118, 138
AU	129	GT2	120, 140
BGC	208-209, 266-267, 305	GT4T	121, 141
BGCS	269	GTA/GTT KIT	122
BGDB	210, 368, 306	GUB	275, 312
BGRC	204, 261, 301	H	183
C	355	Hardware	383
CA	136	Heat Shrink	3159-322
Cable Ties	364-368	HH-10N	338
CAN	212, 279, 359	HL	199
CCL	34-39	H2L	201
CCS	45	H3L	202
CGBL	283, 314	HT	76
CGRC	203, 260, 301	HW	352
CL	197-198, 200	2IACL	68
CLND	23-28	IACL	67
CLNF	29-30	IDT-6	333
CLNS	14-16	IDT-6H	334
CLNU	31	IDTB-6-LIO	324
CLWD	17-22	IK	108, 213
CLWN	33	IK3	109, 214
CLWS	11-13	IKB	111, 216
CO	189-190	IKS	112, 217
Compression Dies	85-87, 346-348	ILC-10-N	326
Compression Index	78-84, 339-345	ILC-12-N	331
Cool Seal	89	ILC-12H-N	332
COPP	191	ILC-15H	335
CP	188	ILCB-12-LIO	325
CPM	58-60	ILD	85, 346
CPML	58-60	Ilscos	94-105
CRAM	40-41	Ilscos Kits	93
Crimp 'N Seal	90-92	Ilscos Tools	106
CSWD	5-10	IPC	115, 164, 231-232
CSWN	32	LDA	156, 246
CSWS	2-4	LDAU	152, 242
CT	43	LDB	156, 246
CTL	44	LDBU	152, 242
CTR	351	LO	185
DCGC	207, 265	LO-S	186
DBA	114, 166	LU	196
DBA-S	114, 166	LY	187
DBK	178, 293		
D167	211, 278, 358		
DE-OX	361		
DR	352		
Duct Seal	362		
E	183		
E (Screws)	212, 279, 359		
ELT	49, 259, 299		



ILSCO Alpha Numeric Index

Catalog No.	Page No.	Catalog No.	Page No.
M	356-357	SPD	272-273, 309-310
Merchandising	369	SPS	270-271, 307-308
MGTT	123, 142	SRC	205, 262, 302
MIS	316	SS	179, 295
MT-25	327	SSK	179, 295
MU	196	SSKC	179, 295
N	195	SX	193
NB	176, 286, 360	T	288-291
NBW	363	TA	128
ND	329-330	T3A	130
N-174	212, 279, 359	T4A4	131
P840	74	TC	192
PB	132	Technical Information	371-385
PBT	220	TK	352
PBTD	221-222	TLK	133
PBTF	226-228	Torque Index	218, 382
PBTM	225	TS	352
PBTO	220	TTGC	274, 311
PBTS	223-224	TW	352
PCT	125, 229	Tool Accessories	349
PDA	157, 247	Tools	324-353
PDB	158-163, 248-253	UCS	72
PDBU	153-155, 243-245	ULT	48, 258
PDC	157, 247	USGL	134
PDE	146, 236	USPA-SS	177, 294
PDH	144-145, 234-235	VT	186
PDL	147, 237	WC	352
PDM	150-151, 240-241	WR	352
PDS	148-149, 238-239	WS	106, 350
PEC	172	XT	187
PED-Z	171	XT-DB	187, 300
PED-CP	173	21000	317
PED-SS	296	22000	319
PED-X	172	23000	318
PET	174	24000	320
PG	180	25000	320
PICS	73	26000	321
PSA-Z	172	27000	322, 353
PTA	124, 143	30000	92
PTT	175	31000	90-92
R-16	212, 279, 359	44000	94-104
RLT	77, 264, 304	45000	99, 102, 104-105
SAU	182	94130	106, 350
SAS	182	94145	106, 350
2SC	194	94285	328
SGB	168, 281	94502	322, 353
SGC	167, 280	94504	322, 353
SK	110, 215	99200	316
SLS	182		
SLU	182		
SLU-DB	182, 300		
SLUH	184		
Solder Lugs	42		
SPA	135		
SPAR	117, 230		



Notes

