



Mineral Lubricants



Quality Lubricant Products for the HVAC/R Industry

NL Naphthenic Mineral Oils (pale oils) are the traditional choice for lubrication in air conditioning and refrigeration compressors. They are used primarily in systems designed for CFCs (R-12, R-502) and HCFCs (R-22, retrofit blends).

NL Mineral Oils are made from the highest quality base stocks and provide outstanding performance and protection in compressors. Available in 150 SUS, 300 SUS and 500 SUS viscosities, these products can be used in most reciprocating, scroll, screw and many centrifugal compressors on the market today.

NL Mineral Oils perform well over a wide temperature range. They have very good chemical stability and provide very good protection and lubrication at higher compressor temperatures. In addition, they have low wax content and have chemical characteristics that promote a low pour point and good oil return to the compressor at low evaporator temperatures. Naphthenic Mineral Oils do a very good job of preventing system deposits compared to paraffinic (white) mineral oils.

Available Sizes	Part Numbers
1 Gallon	1501G 3001G 5001G
5 Gallon	1505G 3005G 5005G
55 Gallon	15055G 30055G 50055G

TYPICAL PROPERTIES

PROPERTY	Test Method	150	300	500
Viscosity, SUS @ 100°F	ASTM D445	155	325	510
Flash Point, °F	ASTM D92	350	400	405
Pour Point, °F	ASTM D97	-50	-30	-15
Floc Point, °F	ASTM D86	-72	-56	-51
Color Gardner	ASTM D1500	<0.5	<0.5	<0.5
Typical water content, ppm	ASTM D1533	<25	<25	<25
Specific Gravity	ASTM D1250	.904	0.910	0.916



National Refrigerants, Inc.

11401 Roosevelt Boulevard
Philadelphia, PA 19154
Tel: 800.262.0012
fax: 215.698.7466
web: www.refrigerants.com
e-mail: info@refrigerants.com



Lubricants Cross Reference Guide

MINERAL OIL	Part #	Viscosity	Equivalent Part #	OEM Part #
NL 150	1501G	150 SUS/32 ISO	Calumet C3, Suniso 3GS	York D, F – Trane 32, 43
NL 300	3001G	300 SUS/68 ISO	Calumet C4, Suniso 4GS	York C – Trane 15, 31, 45
NL 500	5001G	500 SUS/100 ISO	Calumet C5, Suniso 5GS	York E
NL WF 32	WF32	150 SUS/32 ISO	Texaco WF 32	
NL WF 68	1TD	300 SUS/68 ISO	Texaco WF 68	York A

ALKYLBENZENE	Part #	Viscosity	Equivalent Part #	OEM Part #
NL AKB 150	150AKB1G	150 SUS/32 ISO	Zerol 150, Soltex 150	
NL AKB 200R	200AKB1G	200 SUS/46 ISO	Zerol 200TD	
NL AKB 300	300AKB1G	300 SUS/68 ISO	Zerol 300, Soltex 300	

POLYOLESTER	Part #	Viscosity	Equivalent Part #	OEM Part #
NL PE 32	PE321G	150 SUS/32 ISO	Ultra 32-3MAF, Castrol SW32	York K, O – Trane 78
NL PE 68	PE681G	300 SUS/68 ISO	Emkarate 68H, Castrol SW68	York H – Trane 37, 48

Solest® Product Name	Part #	Viscosity	Equivalent OEM Part #
Solest LT 32	SolestLT321G	32 ISO/150 SUS	York K
Solest 46	Solest461G	46 ISO/200 SUS	York J
Solest 68	Solest681G	68 ISO/300 SUS	York H - Trane 37 - Frick 13
Solest 100	Solest1001G	100 ISO/500 SUS	York S
Solest 120	Solest1201G	120 ISO/600 SUS	York L
Solest 150	Solest1501G	150 ISO/700 SUS	
Solest 170	Solest1701G	170 ISO/800 SUS	
Solest 220	Solest2201G	220 ISO/1000 SUS	Castrol SW220
CP 4214-320	CP4214-3201G	320 ISO/1500 SUS	York G
Solest 370	Solest3701G	370 ISO/1700 SUS	
AKB 500 E	AKB500E1G	100 ISO/500 SUS	BVA 100E, Zerol 500



National Refrigerants, Inc.

11401 Roosevelt Boulevard
Philadelphia, PA 19154
Tel: 800.262.0012
fax: 215.698.7466
web: www.refrigerants.com
e-mail: info@refrigerants.com