

LS • PW



LS 06 RUP



PW 6 RUP

VOLUME CONTROL

LS 06 RUP GIRA STANDARD 55

The **volume controls (LS)** with masking frame, 1-Frame, plate and rotary Switch, color white, for flush mounting, generally including a 24 Volt priority override relay, are available in 6 to 100 Watt and come with a 12-step continuously rotating attenuation switch with a zero position without remaining volume.

The description »NO« means suitable for low impedance applications. The volume control in the »Fail to safe« version bridges the mandatory signalling relay of the volume control, if the voltage of the mandatory signal declines from 24 to 0 Volt.

In this case the volume control is supplied with full power.

Type	Power	Dimensions
LS 06 RUP Gira Standard 55	6	81x81x56
LS 12 RUP Gira Standard 55	12	81x81x56
LS 12 UP NO Gira Standard 55	12	81x81x56
LS 50 RUP Gira Standard 55	50	81x81x74
LS 100 RUP Gira Standard 55	100	81x81x74

PROGRAM VARIETY

PW 6 RUP GIRA STANDARD 55

The **program selector (PW)** allows the selection of 6 different program sources. The program selector is generally equipped with a 24 Volt priority override relay and GIRA Standard 55 frame. Colour: white.

Type	Program	Dimensions
PW 6 RUP Gira Standard 55	6	81x81x56