









H-RBPT-1 Residential Bathroom Plumbing Trainer

- 3'- 6" X 8'- 0" platform dimensions: Aluminum frame, waterproof treated ³/₄" plywood floor
- 6" rear wall 4' X 8' Wood stud frame, Aluminum plate front, clear lexan back
- Gravity flush WC floor mounted
- Grab bar above WC
- Power outlet next to grab bar
- Lavatory with faucet wall hung
- · Floor mounted service/mop sink (acting as shower pan)
- Tub / Shower valve w/ shower head
- Clothes washer box w/ waste and water on back side of wall
- Waste line rodding exercise under floor
- Water cold and hot connections on right side of floor platform (for water hook up)
- · Rodding waste line left side w/female adapter w/plug
- Rodding waste line right side pipe penetrate 4" past platform (for waste hook up)
- · 4 heavy duty wheels all 4 rotating two locking

Fixtures

- WC Gerber HE-21-802 Avalanche 1.28 Round Front 12" Rough-In Toilet
- Lavatory American Standard Penlyn Wall-Hung Lavatory 0373050 w/ concealed arms support
- Lavatory faucet American Standard 4801.862 Amarilis Heritage Faucet with Triune Cross

Handles

- Grab bar 18" grab bar generic brand
- Service/mop sink 24" fiberglass mop sink generic brand
- Tub/Shower valve / Shower head Delta Faucet Classic Monitor 13 Series Tub /Shower /trim Model #: T13420-H2OT with Delta Universal TS Valve Body IPS
- Clothes washer box: Sioux Chief OX Box 696 series clothes washer faucets with water hammer arresters and clothes washer outlet box.

Piping

- Water supply copper pipe
- Waste PVC schedule 40



H-RBPT-2 Residential Bathroom Plumbing Trainer

- 3'- 6" X 8'- 0" platform dimensions: Aluminum frame, waterproof treated 3/4" plywood floor
- 6" rear wall 4' X 8' Wood stud frame, aluminum plate front, clear lexan back
- Pressure assist one piece WC floor mounted
- Grab bar above WC

Hampden

- · Power outlet next to grab bar
- · Lavatory with faucet wall hung
- Floor mounted service sink (acting as shower pan)
- · Tub / Shower valve w/ shower head and tub spout
- Clothes washer box w/ waste and water on back side of wall
- Waste line rodding exercise under floor
- Water cold and hot connections on right side of floor platform (for water hook up)
- Rodding waste line left side w/female adapter w/plug
- Rodding waste line right side pipe penetrate 4" past platform (for waste hook up)
- 4 heavy duty wheels all 4 rotating, two locking

Fixtures

- WC Gerber 21-012 Maurice One Piece Pressure Assist Toilet (Ultra Flush)
- Lavatory American Standard Penlyn Wall-Hung Lavatory 0373050 w/ concealed arms support
- Lavatory faucet Delta Lewiston Two Handle Widespread Lavatory Faucet #35902LF-SS
- Grab bar 18" grab bar generic brand
- Service sink 24" fiberglass mop sink generic brand
- Tub / Shower valve Delta Faucet Classic Monitor 13 Series Tub /Shower / trim Model #: T13420-H2OT with Delta Universal TS Valve Body PEX
- Clothes washer box: Sioux Chief OX Box 696 series clothes washer faucets with water hammer arresters and clothes washer outlet box.

Piping

- Water supply PEX
- Waste ABS schedule 40



ENGINEERING CORPORATION






H-CPLT-3 Commercial Plumbing Trainer

Commercial Plumbing - Module 3:

- 3'- 6" X 8'- 0" platform dimensions: Aluminum frame, waterproof treated ³/₄" plywood floor
- 6" rear wall 4' X 8' Wood stud frame, aluminum plate front, clear lexan back
- · Floor mounted washfountain 36" semi circular
- · Power outlet
- · Service sink w/ Service sink faucet
- · Waste line rodding exercise under floor
- · Water cold and hot connections on right side of floor platform (for water hook up)
- · Rodding waste line left side w/female adapter w/plug
- · Rodding waste line right side pipe penetrate 4" past platform (for waste hook up)
- · 4 heavy duty wheels all 4 rotating, two locking

Fixtures

- Washfountain Bradley Sentry Semi-Circular Shallow Bowl Washfountain SN2023
 - o Floor mounted
 - o Off line vent with supplies from below
 - o Foot control hold open air valve
 - o Standard pedestal height
 - o Tempered line supply
 - o No soap dispenser
 - o With Back splash



- o Faucet: 8341.076 exposed voke wall mount with vacuum breaker and stops in shank
- o Trap Standard: 7798.020 cast iron P trap standard to wall and strainer for 2"
- Drum trap -

Piping

- Water supply copper tube
- Waste PVC schedule 40



H-CRPT-4 Commercial Restroom Plumbing Trainer

Commercial Restroom Plumbing - Module 4:

- 3'- 8" X 8'- 0" platform dimensions Aluminum frame and floor
- 16" center wall centered at 4' 4' high with aluminum diamond plate face facing clear lexan panel face of wall
- · Wall hung flushometer WC back to back on center wall
- · Power outlet next to WC
- Urinal 0.25 gal flush electronic (battery) flushometer back to back on center wall
- Water cold and hot connections on right side of floor platform (for water hook up)
- 4 heavy duty wheels all 4 rotating, two locking

Fixtures

- WC Kohler Kingston K-4325 1.28gpf Wall Hung Water Closet: JR Smith Fig. 0210Y No-Hub w/2" vent Vertical WC Carrier
- Kohler Exposed Wave Flushometer Valve 1.28gpf K-10673
- Urinal Sloan WEUS-1002.1201-0.25 Solis Optima Plus Systems Solar Powered High Efficiency Urinal Flushometer and Urinal

Piping

- Water supply copper tube
- · Waste cast iron no hub









H-FFFT-5 Fixtures/Fittings/Faucets Trainer

Consists of:

- 3' X 8' X 3' 6" aluminum rolling stand (verify dimensions to fit faucet placement)
- Full length trough on all four sides
- Each faucet with hot and cold supply
- 20 faucets 8 on each long side 2 on each short side
- 2" drain for hook up
- $2ea \frac{3}{4}$ " water connection for hook up
- 4 heavy duty wheels all 4 rotating, two locking

Lavatory faucets -


- Single handle
 - o Hansgrohe Allegro 0418000
 - o Grohe Eurosmart Lavatory Center Set Less Drain - 32 710
 - o Delta Classic single Handle Lavatory Faucet 505 Double handle
 - o Greber Brianne 43-231 Series
 - o Chicago Faucets Deck Mounted Manual Faucet 797-CP
 - o Delta Classic Two Handle Lavatory Faucet 2500
 - Electronic 2 ea Kohler Electronic Faucet K-13461
 - Metering 2 ea Delta Two Handle Metering Lavatory Faucet
 #2507-HDF

Kitchen faucets –

- Single handle Pullout spout
 - o Gerber Single Handle Pull Out Kitchen Faucet Allerton 40-485 Series
 - o Gerber Single Handle Kitchen Faucet 40-100 Series with spray
 - o Gerber Hardwater Single Handle Kitchen Faucet 40-501 Series / Less pop up hole and drain assembly
 - o Gerber Brianne single Handle Pull Down Kitchen Faucet 40-480
 - o Grohe Dual Spray Pull Down Lady Lux Cafe 33 758
 - o Hans Grohe Allegro E Pull out Kitchen Faucet 06461000
 - o Delta Palo Pull out Kitchen Faucet 467-DST
 - Double handle
 - o Chicago Faucet Manual Faucet Deck mounted 8" Widespread 1100-CP

Specialty faucets – 2ea

- Pre-rinse spray valve
 - o T&S Brass B-0105 Pre rinse spray valve assembly
 - o T&S Brass B-0113 Pre Rinse Spray with Flexible Stainless Steel Hose /with valve









H-PFRT-6 Pipe Freeze and Repair Trainer

Consists of the following parts:

- · Identical to model in pictures below
- · Small sink
- 1 " copper pipe as shown in picture
- Two separate risers each with ball valves underneath cabinet
- 1' between 1" brass unions on front horizontal line
- Hose bib draining into sink
- Hose bib connection for hook up
- 1-1/2" quick connection for drainage hook up
- For use with Ridgid SF-2500 Pipe Freezer
- 4 heavy duty wheels all 4 rotating, two locking



H-RWHT-7 Residential Water Heaters Trainer

- 2'- 6" X 8'- 0" aluminum platform dimensions (verify dimensions to carry WH)
- 6" rear wall 5' X 8' aluminum or steel studs aluminum front and clear lexan back
- · Electrical wiring for use
- Steel IPS gas piping for use with connection on right side
- Water cold and hot connections on right side of floor platform (for water hook up)
- · Heavy duty wheels all rotating, two locking

Heaters

- Residential gas water heater sealed combustion chamber – power vent – propane – 40 gal
 - o Bradford White ICON NG Residential Atmospheric Vent Energy Saver Water Heater W/ ICON 40gal
 - o Bradford White Power Vent Water Heater Model # M-1TW-40S6SX
- Residential electric water heater 40 gal
 - o Rheem RHE PRO40-2 Electric Water Heater (40gal.)





Hampden[®] ENGINEERING CORPORATION





H-CWHT-8 Commercial Water Heaters Trainer

- 2'- 6" X 8'- 0" platform dimensions (verify dimensions to carry WH)
- 6" rear wall 5' X 8' aluminum or steel studs aluminum front and clear lexan back
- Electrical wiring for use
- Steel IPS gas piping
- Water cold and hot connections on right side of floor platform (for water hook up)
- · Heavy duty wheels all rotating

Heaters

- Commercial gas with electronic ignition Bradford White Model # D-38T-155-3N
- Commercial gas with milivolt ignition Bradford White Model # DM-38T-155-3n
- Tankless water heater
 - o Noritz NR71 (N-0631S) Series Residential Tankless Water Heater

H-WHCT-9 Water Heater Controls Trainer

Consists of the following:

Hampden

- Bradford White Icon Control System Cutaway Display, Pipe for use
- Noritz Tankless Water Heater System Cutaway Display
- Module platform to fit Controls Aluminum frame and front clear lexan back
- Width of platform to fit WH
- Height of displays at waist high for easy access (depending on equipment from BW)











H-PUMT-10 Pumps Trainer

- Platform aluminum frame and floor
- Rear wall 4' high aluminum studs with aluminum fromt and clear lexan back
- · Lay out other pumps for display on wall
- Make Module to fit Pump display
- Width of platform to fit WH
- Height of displays at waist high for easy access (depending on equipment from BW)
- Ejector pump
 - o Tramco 400SE Automatic Sewage Pump (100gpm)
- Sump pump
 - o Hydromatic Model: B-A1/BV-A1, Sump/Effluent Pump (32gpm)
- Laundry pump
 - o Diamond Pumps Model LTP
- · Re-circulating pump
 - o Grundfos Alpha hot water re-circulating pump



H-BFPD-1 Backflow Prevention Demonstrator

The Hampden **MODELH-BFPD-1** Back Flow Prevention Demonstrator provides the instructor with the ability to demonstrate multiple methods of back flow prevention of liquids.

Eight circuits are laid out on this double sided mobile demonstrator. The bench is constructed from furniture grade steel, finished in instrument tan texture enamel. Four casters are mounted to the bench, two with locks, two without. The panel is mounted to the top of the bench and is constructed from 11 gauge furniture grade steel, finished in gloss white enamel. Four circuits are laid out on each side of the panel with the components labeled with KEM black silkscreen enamel.

The components mounted to the panel are:

- Double Check Valve BFP 1
- Double Check Valve Assembly BFP 2
- Standard Duty BFP 1
- Heavy Duty BFP 1
- Reduced Pressure BFP 2
- Pressure Vacuum Breaker 4
- Ball Valves
- Gate Valves
- Lot of ³/₄" Copper Tubing
- Lot of 3/4" Fittings

The components mounted on the bench are:

- · Water Storage Tank
- Water Pump
- Return Drain











H-PPST-1 Piping/Pipefitters System Trainer



The Hampden **Model H-PPST-1** Piping/ Pipefitters System Trainer provides the student with a hands on trainer for piping. The student will learn the necessary methods of connecting and running metal/iron piping, plastic piping, copper tubing, and hydraulic hose. Each material has its own particular methods used in plumbing.

The Hampden **Model H-PPST-1** Piping/ Pipefitters System Trainer consists of a frame that students use to mount and run pipes, valves, and other components. Once the piping is complete, the system will be tested by allowing water to be pumped through it. The student will learn how to make the necessary connections, depending on the type of material that the pipe is made from.

Unit includes the following parts: Mobile Frame, Pump, Tank, Piping, Valves, Tool Box, Flow Meter, and Protection. H-PVST-1 Pump and Valve System Trainer



The Hampden **Model H-PVST-1** Pump and Valve System Trainer is a custom designed unit built to meet the plant specific training needs of the industrial facility. The trainer includes the basic facilities necessary to pump water (or other fluids) in a loop, together with the plant specific pump(s), valves and control configurations. Furthermore, all major components are flange fitted which allows easy removal from the unit. This will enable the trainee to learn the proper service procedures.

The unit is permanently mounted on a steel panel and base and the front of the panel is silkscreened with a schematic of the pumping system. This unit is 60° H x 70^oW x 30^oD and comes with an instruction manual.



For the latest from Hampden, visit our home page at http://www.hampden.com or e-mail us at sales@hampden.com



99 Shaker Road P.O. Box 563, East Longmeadow, MA 01028-0563 • TEL. (413) 525-3981 • (888) HEC-CORP • FAX (413) 525-4741