	Royco 756	
/ersion: 1.0	Revision Date: 12/05/2014	Print Date: 05/05/20
SECTION 1. PRODUCT AND C	OMPANY IDENTIFICATION	
Product name	: Royco 756	
Product Use Description:	Lubricant	
Company:	<u>Manufacturer</u> Anderol Specialty Lubricants, a division 215 Merry Lane East Hanover, NJ 07936 United States of America	of Chemtura Corporation
	Telephone: +1 203-573-4596, Toll Free	: +1 888-263-3765
Emergency telephone number:	CHEMTREC: (24 hours) 800-424-9300 : : 703-527-3887)
	For additional emergency telephone nur Data Sheet.	nbers see section 16 of the Safe
Prepared by	Product Safety Department (US) +1 866-430-2775	
	MSDSRequest@chemtura.com	
	EAR AND BEARING OIL, EP (ISO 680) chemical and restrictions on use	
Recommended use	: Lubricant	
Restrictions on use	: For industrial use only.	

SECTION 2. HAZARDS IDENTIFICATION

Form	liquid
Colour	red
Odour	aromatic

GHS Classification

Aspiration hazard	: Category 1
Acute aquatic toxicity	: Category 3
Chronic aquatic toxicity	: Category 3

GHS Label element

: Danger

NDEKOL	SAFETY DATA SHEET					
ecialty Lubricants						
Royco 756						
ersion: 1.0	Revision Date: 12/05/2014	Print Date: 05/05/2015				
Hazard pictograms						
Hazard statements	: H304 May be fatal if swallowed a H412 Harmful to aquatic life with					
Other hazards	: None					
Precautionary statements	 Prevention: P273 Avoid release to the enviror Response: P301 + P310 IF SWALLOWED: In CENTER or doctor/ physician. P331 Do NOT induce vomiting. Storage: P405 Store locked up. Disposal: P501 Dispose of contents/ contai disposal plant. 	mmediately call a POISON				
Carcinogenicity:						
IARC	No component of this product presen equal to 0.1% is identified as probabl human carcinogen by IARC.					
	Group 3: Not classifiable as to its car	cinogenicity to humans				
		2-46-7				
	hydrotreated light	2-47-8				
OSHA	2,6-di-tert-butyl-p-cresol 128- No component of this product presen equal to 0.1% is identified as a carcir carcinogen by OSHA. No component of this product presen equal to 0.1% is identified as a carcir	it at levels greater than or nogen or potential it at levels greater than or				
NTP	carcinogen by OSHA. No component of this product presen equal to 0.1% is identified as a know by NTP. No component of this product presen equal to 0.1% is identified as a know by NTP.	t at levels greater than or n or anticipated carcinogen t at levels greater than or				

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS



Royco 756

Version: 1.0

Revision Date: 12/05/2014

Print Date: 05/05/2015

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 50 - < 70 %
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 20 - < 30 %
Distillates (petroleum), hydrotreated light	64742-47-8	>= 5 - < 10 %
NJTS# 136411-5778P Polyolefins		>= 1 - < 5 %
Phenol, isobutylenated, phosphate (3:1)	68937-40-6	>= 0.1 - < 1 %
2,6-di-tert-butyl-p-cresol	128-37-0	>= 0.1 - < 1 %

SECTION 4. FIRST AID MEASURES

If inhaled	f inhaled Move to fresh air. f not breathing, give artificial respiration f breathing is difficult, give oxygen. n case of bluish discolouration (lips, ea give oxygen as quickly as possible. Call a physician or poison control centro	r lobes, fingernails),
In case of skin contact	n case of skin contact Wash off with soap and water. Remove contaminated clothing and sho Wash contaminated clothing before re- Get medical attention if irritation develo	use.
In case of eye contact	n case of eye contact Flush with plenty of water. f eye irritation persists, consult a specia	alist.
If swallowed	f swallowed, DO NOT induce vomiting. Call a physician or poison control centro	
Most important symptoms and effects, both acute and delayed	Aspiration may cause pulmonary oeder	na and pneumonitis.
Notes to physician	For specialist advice physicians should nformation Service.	contact the Poisons

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO2) Dry powder Foam Alcohol-resistant foam Water mist	
Unsuitable extinguishing media	: Water	
SAP 6.0 SDS 2012-2 NA GHS	3 / 10	SDS Number: 40000001788



Royco 756

Version: 1.0	Revision Date: 12/05/2014	Print Date: 05/05/2015		
Specific hazards during firefighting	: Burning produces noxious and to	ixic fumes.		
Specific extinguishing methods	: Use extinguishing measures that circumstances and the surroundi Use a water spray to cool fully clo	ng environment.		
Special protective equipment for firefighters	: In the event of fire, wear self-con Use personal protective equipme	0 11		

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation.
Environmental precautions	:	Do not contaminate water. Do not flush into surface water or sanitary sewer system. Discharge into the environment must be avoided.
Methods and materials for containment and cleaning up	:	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Keep container closed when not in use.
Conditions for safe storage	: Keep container tightly closed in a dry and well-ventilated place.
Materials to avoid	: Strong acids and strong bases, Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	NIOSH REL
AP 6.0 SDS 2012-2 NA GHS	6.0 SDS 2012-2 NA GHS 4 / 10 SDS Number: 40000000178			mber: 400000001788



Royco 756

Version: 1.0 Revision Date: 12/05/2014 Print Date: 05/05/2015 ST (Mist) 10 mg/m3 NIOSH REL TWA (Mist) 5 mg/m3 OSHA P0 Distillates (petroleum), 64742-46-7 TWA 500 ppm OSHA Z-1 hydrotreated middle 2,000 mg/m3 TWA (Mist) 5 mg/m3 OSHA Z-1 TWA 400 ppm OSHA P0 1,600 mg/m3TWA (Mist) 5 mg/m3 NIOSH REL ST (Mist) 10 mg/m3 NIOSH REL TWA (Mist) 5 mg/m3 OSHA P0 Distillates (petroleum), 64742-47-8 TWA 500 ppm OSHA Z-1 2,000 mg/m3 hydrotreated light TWA 200 mg/m3 ACGIH TWA 400 ppm OSHA P0 1,600 mg/m3 NJTS# 136411-5778P TWA (Mist) 5 mg/m3 OSHA Z-1 Polyolefins TWA (Mist) 5 mg/m3 NIOSH REL ST (Mist) 10 mg/m3 NIOSH REL TWA (Mist) 5 mg/m3 OSHA P0 2,6-di-tert-butyl-p-cresol 128-37-0 OSHA P0 TWA 10 mg/m3 TWA 2 mg/m3 ACGIH (Inhalable fraction and vapor) ACGIH TWA 2 mg/m3 (Inhalable fraction and vapor) TWA 10 mg/m3 NIOSH REL

Engineering measures	 Ensure that eyewash stations and safety s the workstation location. Effective exhaust ventilation system 	showers are close to
Personal protective equipmen	t	
Respiratory protection	 not required under normal use When workers are facing concentrations a limit they must use appropriate certified re 	-
Hand protection		
Remarks	: Neoprene gloves	
Eye protection	: Safety glasses with side-shields or Tightly fitting safety goggles	
Skin and body protection	: impervious clothing	
Hygiene measures	: Avoid contact with skin, eyes and clothing Handle in accordance with good industrial practice.	
SAP 6.0 SDS 2012-2 NA GHS	5 / 10	SDS Number: 40000001788



Royco 756

Version: 1.0

Revision Date: 12/05/2014

Print Date: 05/05/2015

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	red
Odor	:	aromatic
рН	:	Not applicable
pour point	:	< -60 °C
Boiling point/boiling range	:	No data available
Flash point	:	> 93.3 °C Method: ASTM D 93
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative density	:	ca. 0.86
<u>Solubility(ies)</u>		
Water solubility	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	13.9 mm2/s (40 °C)

SECTION 10. STABILITY AND REACTIVITY

reactions	Stable under normal conditions.	
Conditions to avoid	: Heat, flames and sparks. Contamination	
Incompatible materials	: Strong acids and strong bases	
SAP 6.0 SDS 2012-2 NA GHS	6 / 10	SDS Number: 40000001788



Version: 1.0

Royco 756

Revision Date: 12/05/2014

Print Date: 05/05/2015

Oxidizing agents

Hazardous decomposition : Carbon oxides products

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity 2,6-di-tert-butyl-p-cresol (Component)	: LD50: > 2,930 mg/kg Species: Rat Method: OECD Test Guideline 401
Acute dermal toxicity 2,6-di-tert-butyl-p-cresol (Component)	: LD50: > 2,000 mg/kg Species: Rat Method: OECD Test Guideline 402
Skin irritation NJTS# 136411-5778P Polyolefins (Component) 2,6-di-tert-butyl-p-cresol (Component)	 Result: No skin irritation Species: Rabbit Result: No skin irritation
Eye irritation NJTS# 136411-5778P Polyolefins (Component) 2,6-di-tert-butyl-p-cresol (Component)	 Result: No eye irritation Species: Rabbit Result: No eye irritation
Sensitisation 2,6-di-tert-butyl-p-cresol (Component)	: Species: Guinea pig Classification: Did not cause sensitisation on laboratory animals.
CMR effects NJTS# 136411-5778P Polyolefins (Component)	: Carcinogenicity: Animal testing did not show any carcinogenic effects. Mutagenicity: Animal testing did not show any mutagenic effects. Teratogenicity: No effects on or via lactation, Did not show teratogenic effects in animal experiments. Reproductive toxicity: No toxicity to reproduction
2,6-di-tert-butyl-p-cresol (Component)	: Mutagenicity: Animal testing did not show any mutagenic effects. Teratogenicity: No effects on or via lactation Reproductive toxicity: No toxicity to reproduction
Further information (Product)	: No data is available on the product itself.



Royco 756

Version: 1.0

Revision Date: 12/05/2014

Print Date: 05/05/2015

Ecotoxicity effects	
Toxicity to fish (Product)	: Remarks: No data available
Toxicity to daphnia and other	aquatic invertebrates
NJTS# 136411-5778P Polyolefins (Component)	: EC50: 190 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)
Phenol, isobutylenated, phosphate (3:1) (Component)	: EC50: 0.202 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)
Phenol, isobutylenated, phosphate (3:1) (Component)	: NOEC: 0.093 mg/l Exposure time: 90 d aquatic invertebrates (Chronic toxicity)
Bioaccumulation (Product)	: Remarks: No data available
Mobility (Product)	: Remarks: No data available
Biodegradability (Product)	: Result: No data available
Further information on eco	logy
Ecotoxicology Assessment	:
Results of PBT assessment (This mixture contains no sub- Additional ecological information (Product)	Product) stance considered to be persistent, bioaccumulating and toxic (F : The product itself has not been tested.



Royco 756

Version: 1.0

Revision Date: 12/05/2014

Print Date: 05/05/2015

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: Dispose of waste material in compliance with all federal, state, and local regulations.
Contaminated packaging	: Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

ADR

Not dangerous goods

RID Not dangerous goods

MERCOSUR Not dangerous goods

DOT Not dangerous goods

ΙΑΤΑ

Not dangerous goods

IMDG

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
xylene	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.



Royco 756 Version: 1.0 Revision Date: 12/05/2014 Print Date: 05/05/2015 SARA 311/312 Hazards : Acute Health Hazard **SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. **SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313. **US State Regulations California Prop 65** WARNING! This product contains a chemical known to the State of California to cause cancer. formaldehyde 50-00-0 The components of this product are reported in the following inventories: **US.TSCA On TSCA Inventory** DSL All components of this product are on the Canadian DSL. On the inventory, or in compliance with the inventory AICS NZIOC Not in compliance with the inventory ENCS On the inventory, or in compliance with the inventory KECI On the inventory, or in compliance with the inventory PICCS On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory IECSC

SECTION 16. OTHER INFORMATION

Further information

Other Emergency Phone Number

Latin America:	Brazil	+55 113 711 9144
	All other countries	+44 (0) 1235 239 670
<u>Mexico:</u>		+52 555 004 8763

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.