

Replacement guide - Austauschliste - udskiftningsliste - liste de remplacement

Smedegaard	Connection/ mm length	Grundfos New UPS	Grundfos UPS/C/UMC	Conn. length	Wilo	Connection mm length	Wilo Top S	Connection mm length
EV 2- 40-2C	1"/180*							
EV 2- 65-2C	1"/180*		UPS 25-25/40	1"/180	RS 25/ 50r	1"/180		
EV 2- 65-2C	1"/180*		UPS 25- 40	1"/180	RS 25/ 60r	1"/180		
EV 2- 70-2C	1"/180*		UPS 25- 60	1"/180	RS 25/ 70r	1"/180		
EV 2- 72-2C	1"/180		UPS 25- 80	1"/180			Top RS 25/ 7	1"/180
EV 3- 72-2C	1¼"/180		UPS 32- 55	1¼"/180	RS 30/ 80r	1¼"/180	Top RS 30/ 7	1¼"/180
EV 3-100-2C	1¼"/180		UPS 32- 80	1¼"/180	RS 30/100r	1¼"/180	Top RS 30/10	1¼"/180
(EV 3- 72-2C)	1¼"/180	UPS 32-60F	UPC 32- 60	32/220				
(EV 3-100-2C)	1¼"/180	UPS 32-120F	UPC 32-120	32/220				
EV 4- 67-2C	40/220				S 40/ 80r	40/220	Top S 40/ 4	40/220
EV 4- 95-2C	40/250	UPS 32-120F	UPC 32-120	32/220				
EV 4- 60-2C	40/250		UPS 40- 50	40/250				
EV 4- 75-2C	40/250	UPS 40-60/2	UPC 40- 60	40/250	S 40/ 90r	40/250	Top S 40/ 7	40/250
EV 4- 95-2C	40/250	UPS 40-120	UPC 40-120	40/250	S 50/ 80r	50/240	Top S 40/10	40/250
EV 5- 88-2C	50/280	UPS 50-60/2	UPC 50- 60	50/280	S 50/100r	50/280	Top S 50/ 7	50/280
EV 5- 95-2C	50/280	UPS 50-120	UPC 50-120	50/280	S 50/125r	50/280	Top S 50/10	50/280
EV 5- 95-2C	50/280				S 50/140r	50/340	Top S 65/13	65/340
EV 5- 88-2C	50/280	UPS 65-60	UPC 65- 60	65/340	S 65/ 80r	65/280	Top S 65/ 7	65/340
EV 6- 95-2C	65/340	UPS 65-120	UPS 65-120	65/340	S 65/125r	65/340	Top S 65/10 (-13)	65/340
EV 6-110-2C	65/340				S 65/140r	65/340	Top S 65/13	65/340
EV 8- 95-2C	80/360	UPS 80-120	UPC 80-120	80/360	S 80/125r	80/360	Top S 80/ 7 (-10)	80/360
EV 8-100-2C	80/360	UPS 80-120	UPC 80-120	80/360	S 80/125r	80/360	Top S 80/10	80/360
EV 4-100-4C	40/250	UPS 40-30	UMC 40-30	40/250	P 40/100r	40/250		
EV 4-125-4C	40/250	UPS 40-60/4	UMC 40-60	40/250	P 40/160r	40/320		
EV 5-125-4C	50/280	UPS 50-30	UMC 50-30	50/280				
EV 5-125-4C	50/280	UPS 50-60/4	UMC 50-60	50/280	P 50/125r	50/280		
EV 6-125-4C	65/340	UPS 65-30	UMC 65-30	65/340	P 65/125r	65/340		
EV 6-125-4C	65/340	UPS 65-60	UMC 65-60	65/340	P 65/125r	65/340		
EV 8-125-4C	80/360	UPS 80-30	UMC 80-30	80/360	P 80/125r	80/360		
EV 8-125-4C	80/360	UPS 80-60	UMC 80-60	80/360	P 80/125r	80/360		
(EV 8- 95-2C)	80/360	UPS 100-30	UMC100-30	100/450				
(EV 8- 95-2C)	80/360	UPS 100-60	UMC100-60	100/450				
EV 5-160-4C	50/340				P 50/160r	50/340		
EV 6-160-4C	65/370				P 65/160r	65/340		
EV 8-160-4C	80/390				P 80/160r	80/360		
EV 8-200-4C	80/440				P 80/250r	80/500		
EV 10-160-4C	100/470				P 100/160r	100/395		
EV 10-210-4C	100/485				P 100/200r	100/550		

* EV 2-40/65/70-2C circulators exists with the following connections and port to port dimensions: 1" x 130mm, 1" x 180mm, 1¼" x 130mm, 1¼" x 180mm, 25mm flanged 120mm.

Flanges on EV 40/50/65mm pumps are double drilled PN6/10 for maximum interchangeability. 80mm pump casings can be supplied in PN6 or PN10 (PN10 is standard).

01.01.2001 - We reserve the right to change specifications - Änderungen vorbehalten - Ret til ændringer forbeholdes.