

SERIES 1000

LAWN TRACTORS

- LTX 1040
- LTX 1042
- LTX 1045
- LTX 1046
- LTX 1046VT
- LTX 1050
- LTX 1050VT
- SLTX 1050
- SLTX 1054

FEATURES

42", 46" TWIN-BLADE DECKS AND 50", 54" TRIPLE-BLADE DECKS

WEIGHT 468 LBS. TO 567 LBS.

HEAVY-DUTY 9-GAUGE STEEL FRAME RAILS

ACCURATE, EASY-TO-READ GAS GAUGE

PADDED FOOT RESTS

FENDER FLARES WITH GLOVE BOX

SMARTJET™ DECK WASH

FULL LINE OF ATTACHMENTS AND ACCESSORIES AVAILABLE

3- AND 5-YEAR LIMITED WARRANTY*

HOME OWNER PREMIUM OUTDOOR EQUIPMENT



YOU CAN'T GET ANY BETTER.™



PROOF THAT CUB CADET TRACTORS ARE BUILT BETTER.

The Series 1000 Lawn Tractor is the most innovative and maneuverable lawn tractor in its category. It features a best-in-class 12" turning radius, professional-grade engines, and welded steel frames that are the thickest in the industry — giving you the dependability you deserve. Combine that with a premium cutting system that leaves no grass uncut, and you've got a lawn tractor that can't be beat, not to mention it keeps the investment you call home looking beautiful.

STRONGER ENGINES

Powerful Cub Cadet professional-grade engines by Kohler® and Briggs & Stratton® provide exceptional cutting performance, even in tall, thick grass.



TOUGHER BUILT TRACTORS

They're built to last with fully welded steel frames that are the thickest in the industry, not to mention cast-iron front axles. And each is backed by a 5-year warranty.



CLEANER CUT


The cutting system features a deep deck that provides optimal grass lift and mulching capability. The overlapping blades ensure that no grass is left uncut, and a wide discharge chute spreads grass clippings evenly — providing a manicured lawn without clumping or uncut grass.



TIGHTER TURNING RADIUS THAN ANY COMPETITOR

The most maneuverable lawn tractor in its class gets the job done faster with a 12" turning radius. It easily mows around obstacles, reducing the need for trimming and backing up.

■ CUB CADET®
■ COMPETITORS



SMOOTHER RIDE

A comfortable, ergonomic design features high-back seats, extensive leg room, available arm rests, rubber-cushioned foot pads and soft-touch controls — delivering an easy and enjoyable mowing experience.

*See specifications for warranty information.

SERIES 1000 LAWN TRACTORS

ENGINE	LTX 1040	LTX 1042	LTX 1045
Engine type	19 HP* Cub Cadet professional-grade Kohler® Courage® single-cylinder	19 HP* Cub Cadet professional-grade Kohler® Courage® single-cylinder	20 HP* Cub Cadet professional-grade Kohler® Courage® single-cylinder
Cylinders/material	1/cast-iron sleeve		
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter		
DRIVE SYSTEM			
Drive system	Automatic CVT w/cruise control	Automatic w/heavy-duty hydrostatic pump	Automatic w/heavy-duty hydrostatic pump
Engine to transmission	Twin CVT drive belt	Heavy-duty Kevlar® belt	Heavy-duty Kevlar® belt
Cruise control	Standard		
Transmission housing	Die-cast aluminum		
STEERING			
Steering	Manual sector & pinion		
Front axle	Heavy-duty cast-iron w/dual grease fittings — 5-year limited warranty		
Spindles	3/4" w/grease fittings		
Ball joints	2 automotive-style		
Rear axle diameter	3/4" diameter with dual steel drive hubs		
Turning radius	12"		
CHASSIS			
Chassis type	Robotically welded frame assembly		
Frame	Heavy-duty 9-gauge steel frame rails — 5-year limited warranty		
Hood & grill	Corrosion- and dent-resistant high-impact ABS		
Fender & bumper	Steel fender w/grab handles	Steel fender w/grab handles and glove box	Steel fender w/grab handles and glove box
ELECTRICAL SYSTEM			
Alternator	15 amp. regulated		
Battery	12V/heavy-duty 190 cold crank amp.		
Charging system	Flywheel alternator		
Headlights	Standard		
System monitor package	Digital hour meter, change oil service minder, battery voltage monitor, park brake and PTO start sequence LEDs		
Safety systems	Neutral start, operator presence, reverse safety switch, brake pedal lock, RevTEK™ reverse mowing technology		
OPERATION			
PTO clutch	Manual lever control		
Deck lift	Manual/12-position		
Brakes	Automotive-style disc		
Seat	Mid-back seat, 12 positions with 6" seat travel	High-back seat, 12 positions with 6" seat travel	High-back seat, 12 positions with 6" seat travel
ADDITIONAL SPECIFICATIONS			
Front tires	15" x 6"		
Rear tires	20" x 8"		
Forward speed	0 – 5.2 mph		
Reverse speed	0 – 2.3 mph		
Fuel tank	3.5 gal. easy fill, rustproof		
Engine oil	1.6 qt.		
Transmission oil	19 oz.	1.9 qt.	1.9 qt.
Wheelbase	47.5"		
Overall length	69"		
Estimated weight w/deck	468 lbs.	498 lbs.	510 lbs.
MOWING DECK			
Cutting width/blades	42" heavy-duty twin blades	42" heavy-duty twin blades	46" heavy-duty twin blades
Deck cutting height	1.5" – 4"		
Mower deck construction	12-gauge steel		
Mower drive system	Heavy-duty Kevlar® belt		
Anti-scalping	4 wheels		
Mulch kit	Optional		
Deck spindles	Die-cast aluminum spindle housings w/ball bearings and grease fittings for long life		
Deck pulleys	All steel w/heavy-duty bearings		
Deck attach/removal	QuickAttach™ in seconds, no tools required		
Deck wash	Patented SmartJet™ high-pressure deck washing system		
WARRANTY†			
3-year/120-hr and 5-year/500-hr limited warranty			



†Cub Cadet will provide a limited warranty for a period of 5 years or 500 hours, whichever occurs first, for the frame and pivoting cast-iron front axle on all new Cub Cadet Series 1000 tractors. For complete details on 3-year and 5-year limited warranties, see your Cub Cadet Independent Dealer or operator's manual. 3 years or 120 hours, whichever comes first. Warranty does not cover normal wear on parts, batteries, and frame and front axle. Frame and front axle are covered for 5 years or 500 hours, whichever comes first. See operator's manual for details on Cub Cadet's Manufacturer's Limited Warranty for Series 1000 Lawn Tractors.



ENGINE	LTX 1046	LTX 1046VT	LTX 1050	LTX 1050VT
Engine type	22 HP* Cub Cadet professional-grade Kohler® Courage® V-Twin OHV	23 HP* Cub Cadet professional-grade Briggs & Stratton® V-Twin OHV	22 HP* Cub Cadet professional-grade Kohler® Courage® V-Twin OHV	24 HP* Cub Cadet professional-grade Briggs & Stratton® V-Twin OHV
Cylinders/material	2/cast-iron sleeve			
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter			
DRIVE SYSTEM				
Drive system	Automatic w/heavy-duty hydrostatic pump			
Engine to transmission	Heavy-duty Kevlar® belt			
Cruise control	Standard			
Transmission housing	Die-cast aluminum			
STEERING				
Steering	Manual sector & pinion			
Front axle	Heavy-duty cast-iron w/dual grease fittings – 5-year limited warranty			
Spindles	3/4" w/grease fittings			
Ball joints	2 automotive-style			
Rear axle diameter	3/4" diameter with dual steel drive hubs			
Turning radius	12"			
CHASSIS				
Chassis type	Robotically welded frame assembly			
Frame	Heavy-duty 9-gauge steel frame rails – 5-year limited warranty			
Hood & grill	Corrosion- and dent-resistant high-impact ABS			
Fender & bumper	Steel fender w/grab handles and glove box			
ELECTRICAL SYSTEM				
Alternator	15 amp. regulated			
Battery	12V/H.D. 235 cold crank amp.	12V/H.D. 235 cold crank amp.	12V/H.D. 190 cold crank amp.	12V/H.D. 190 cold crank amp.
Charging system	Flywheel alternator			
Headlights	Standard			
System monitor package	Digital hour meter, change oil service minder, battery voltage monitor, park brake and PTO start sequence LEDs			
Safety systems	Neutral start, operator presence, reverse safety switch, brake pedal lock, RevTEK™ reverse mowing technology			
OPERATION				
PTO clutch	Electronic fingertip engagement for smooth operation of deck or attachments			
Deck lift	Manual/12-position			
Brakes	Automotive-style disc			
Seat	High-back seat, 12 positions with 6" seat travel			
ADDITIONAL SPECIFICATIONS				
Front tires	15" x 6"			
Rear tires	20" x 8"	20" x 8"	20" x 10"	20" x 10"
Forward speed	0 – 5.2 mph			
Reverse speed	0 – 2.3 mph			
Fuel tank	3.5 gal. easy fill, rustproof			
Engine oil	1.9 qt.			
Transmission oil	2.0 qt.			
Wheelbase	47.5"			
Overall length	69"			
Estimated weight w/deck	513 lbs.	513 lbs.	548 lbs.	548 lbs.
MOWING DECK				
Cutting width/blades	46" heavy-duty twin blades	46" heavy-duty twin blades	50" heavy-duty triple blades	50" heavy-duty triple blades
Deck cutting height	1.5" – 4"			
Mower deck construction	12-gauge steel			
Mower drive system	Heavy-duty Kevlar® belt			
Anti-scalping	4 wheels			
Mulch kit	Optional			
Deck spindles	Die-cast aluminum spindle housings w/ball bearings and grease fittings for long life			
Deck pulleys	All steel w/heavy-duty bearings			
Deck attach/removal	QuickAttach™ in seconds, no tools required			
Deck wash	Patented SmartJet™ high-pressure deck washing system			
WARRANTY†				
3-year/120-hr and 5-year/500-hr limited warranty				

*as rated by engine manufacturer †See your local Cub Cadet Independent Dealer for warranty details.



SERIES 1000 LAWN TRACTORS



ENGINE	SLTX 1050	SLTX 1054
Engine type	25 HP* Cub Cadet professional-grade Kohler® Courage® V-Twin OHV	26 HP* Cub Cadet professional-grade Kohler® Courage® V-Twin OHV
Cylinders/material	2/cast-iron sleeve	
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter	
DRIVE SYSTEM		
Drive system	Automatic w/heavy-duty hydrostatic pump	
Engine to transmission	Heavy-duty Kevlar® belt	
Cruise control	Standard	
Transmission housing	Die-cast aluminum	
STEERING		
Steering	Manual sector & pinion	
Front axle	Heavy-duty cast-iron w/dual grease fittings — 5-year limited warranty	
Spindles	3/4" w/grease fittings	
Ball joints	2 automotive-style	
Rear axle diameter	3/4" diameter with dual steel wheel drive hubs	
Turning radius	12"	
CHASSIS		
Chassis type	Robotically welded frame assembly	
Frame	Heavy-duty 9-gauge steel frame rails — 5-year limited warranty	
Hood & grill	Corrosion- and dent-resistant high-impact ABS	
Fender & bumper	Steel fender w/twin rear fender flares w/grab handles and glove box and tubular steel bumper	
ELECTRICAL SYSTEM		
Alternator	15 amp. regulated	
Battery	12V/H.D. 235 cold crank amp.	
Charging system	Flywheel alternator	
Headlights	Standard	
System monitor package	Digital hour meter, change oil service minder, battery voltage monitor, park brake and PTO start sequence LEDs	
Safety systems	Neutral start, operator presence, reverse safety switch, brake pedal lock, RevTEK™ reverse mowing technology	
OPERATION		
PTO clutch	Electronic fingertip engagement for smooth operation of deck or attachments	
Deck lift	Manual/6-position/spring-assisted	
Brakes	Automotive-style disc	
Seat	Deluxe high-back seat, 12-position fingertip adjustment mechanism with 6" of travel. (Arm rests standard on SLTX 1054)	
ADDITIONAL SPECIFICATIONS		
Front tires	16" x 6.5"	
Rear tires	22" x 9.5"	
Forward speed	0 – 5.2 mph	
Reverse speed	0 – 2.3 mph	
Fuel tank	3.5 gal. easy fill, rustproof	
Engine oil	1.9 qt.	
Transmission oil	2.0 qt.	
Wheelbase	47.5"	
Overall length	69"	
Estimated weight w/deck	548 lbs.	567 lbs.
MOWING DECK		
Cutting width/blades	50" heavy-duty triple blades	54" heavy-duty triple blades
Deck cutting height	1.5" – 4"	
Mower deck construction	12-gauge steel	
Mower drive system	Heavy-duty Kevlar® belt	
Anti-scalping	4 wheels, 1 roller (front)	
Mulch kit	Optional	
Deck spindles	Die-cast aluminum spindle housings w/ball bearings and grease fittings for long life	
Deck pulleys	All steel w/heavy-duty bearings	
Deck attach/removal	QuickAttach™ in seconds, no tools required	
Deck wash	Patented SmartJet™ high-pressure deck washing system	
WARRANTY*		
	3-year/120-hr and 5-year/500-hr limited warranty	

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

*as rated by engine manufacturer †See your local Cub Cadet Independent Dealer for warranty details.