



**SuperDoctor 5**

**User's Guide**

**Version 1.5a**

---

The information in this USER'S MANUAL has been carefully reviewed and is believed to be accurate. The vendor assumes no responsibility for any inaccuracies that may be contained in this document, makes no commitment to update or to keep current the information in this manual, or to notify any person organization of the updates. Please Note: For the most up-to-date version of this manual, please see our web site at [www.supermicro.com](http://www.supermicro.com).

Super Micro Computer, Inc. ("Supermicro") reserves the right to make changes to the product described in this manual at any time and without notice. This product, including software, if any, and documentation may not, in whole or in part, be copied, photocopied, reproduced, translated or reduced to any medium or machine without prior written consent.

IN NO EVENT WILL SUPERMICRO BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, SPECULATIVE OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OR INABILITY TO USE THIS PRODUCT OR DOCUMENTATION, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. IN PARTICULAR, SUPERMICRO SHALL NOT HAVE LIABILITY FOR ANY HARDWARE, SOFTWARE, OR DATA STORED OR USED WITH THE PRODUCT, INCLUDING THE COSTS OF REPAIRING, REPLACING, INTEGRATING, INSTALLING OR RECOVERING SUCH HARDWARE, SOFTWARE, OR DATA.

Any disputes arising between manufacturer and customer shall be governed by the laws of Santa Clara County in the State of California, USA. The State of California, County of Santa Clara shall be the exclusive venue for the resolution of any such disputes. Super Micro's total liability for all claims will not exceed the price paid for the hardware product.

FCC Statement: This equipment has been tested and found to comply with the limits for a Class A digital device pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the manufacturer's instruction manual, may cause harmful interference with radio communications. Operation of this equipment in a residential area is likely to cause harmful interference, in which case you will be required to correct the interference at your own expense.

California Best Management Practices Regulations for Perchlorate Materials: This Perchlorate warning applies only to products containing CR (Manganese Dioxide) Lithium coin cells. Perchlorate Material-special handling may apply. See <http://www.dtsc.ca.gov/hazardouswaste/perchlorate/> for further details.

Manual Revision 1.5a

Release Date: January 5, 2017

Unless you request and receive written permission from Super Micro Computer, Inc., you may not copy any part of this document.

---

Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.

Copyright © 2017 by Super Micro Computer, Inc.

All rights reserved.

Printed in the United States of America

---

## Revision History

Date	Rev	Description
Jul-18-2013	1.0	1. Initial document.
Aug-23-2013	1.1	1. Fixed typos. 2. Added more system information types. 3. Added power control functions. 4. Added BIOS flashing functions. 5. Added system tray support on system desktop.
Nov-15-2013	1.2	1. Added user-defined threshold functions. 2. Added the support for completing SD5 installation without restarting the Windows operating system. 3. Changed default install folder. 4. Changed variables in the silent mode installation file.
Feb-7-2014	1.2a	1. Changed some figures.
Mar-7-2014	1.2b	1. Added "Appendix C Updating Configuration". 2. Changed SD5 system requirements. 3. Changed default user name and password. 4. Changed some figures.
Apr-14-2014	1.2c	1. Changed document layout and Supermicro logo.
Sep-1-2014	1.2d	1. Changed SSM full name to Supermicro Server Manager. 2. Changed mail title in E-mail Alert. 3. Added RHEL 7 into SD5 system requirements. 4. Added more system information types.
Nov-7-2014	1.2e	1. Added online installation of smartmontools. 2. Added the feature of flashing BIOS without jumpers. 3. Changed the list of supported of SMART health.
Apr-7-2015	1.3	1. Added the support for monitoring the memory health of SD5 on Windows platforms. 2. Integrated the FRU information to "Power Supply Type" under the "SystemInfo" of SD5 Web. 3. Added a serial number after a hard disk name for clearer identification of disks.
May-15-2015	1.3a	1. Fixed error figures. 2. Added a chapter for configuring Linux syslog.
Jun-12-2015	1.3b	1. Added user interfaces for OS event log in "Alert Configuration". 2. Added the support for LSI MegaRAID 3108. 3. Deleted "Linux Syslog Configuration" chapter.

---

Jul-31-2015	1.4	<ol style="list-style-type: none"> <li>1. Added the support for BIOS flashing on X9 MBs or later Linux platforms.</li> <li>2. Improved the user interfaces to change user account and password.</li> <li>3. Changed built-in JRE version in SD5 from JRE 6 update 43 to JRE 8 update 51.</li> <li>4. Added LSI MegaRAID driver limitation for the monitoring of RAID health.</li> </ol>
Oct-30-2015	1.4a	<ol style="list-style-type: none"> <li>1. Added limitations for ChangeJVM utility.</li> <li>2. Changed some figures.</li> </ol>
Mar-30-2016	1.4b	<ol style="list-style-type: none"> <li>1. Removed 32-bit Oses from supported OS list.</li> <li>2. Changed built-in JRE version in SD5 from JRE 6 update 51 to JRE 8 update 77.</li> <li>3. Changed figures of installer and uninstaller.</li> </ol>
May-25-2016	1.4c	<ol style="list-style-type: none"> <li>1. Changed some figures due to the built-in JRE upgraded to JRE 8 update 92.</li> </ol>
Aug-29-2016	1.4d	<ol style="list-style-type: none"> <li>1. Added the support for SD5 Tray configuration in SD5 installer.</li> <li>2. Changed the tree structure on the RAID tab, and the attributes of BBU and RAID disks on the health information page.</li> </ol>
Oct-28-2016	1.5	<ol style="list-style-type: none"> <li>1. Added Windows Server 2016 64-bit into supported OS list.</li> <li>2. Changed the download URL of Smartmontools.</li> <li>3. Changed some figures due to the built-in JRE upgraded to JRE 8 update 102.</li> </ol>
Jan-5-2017	1.5a	<ol style="list-style-type: none"> <li>1. Changed some figures due to the built-in JRE upgraded to JRE 8 update 112.</li> </ol>

---

## Contents

Part 1	Background .....	10
1	SuperDoctor 5 Overview .....	11
1.1	Key Features.....	11
1.2	Minimum System Requirements .....	13
1.3	Default TCP/UDP Ports .....	13
2	Setting Up SD5 .....	14
2.1	Installing SD5.....	14
2.1.1	Windows Installation .....	14
2.1.2	Linux Installation.....	21
2.1.3	Silent Mode Installation.....	26
2.1.4	Tips for Deploying a Large Number of SD5s .....	30
2.2	Verifying the Installation.....	31
2.3	Manually Controlling SD5 Service .....	31
2.4	Uninstalling SD5 .....	32
2.4.1	Uninstalling in Windows .....	32
2.4.2	Uninstalling in Linux.....	34
2.4.3	Silent Mode Uninstall.....	35
Part 2	SuperDoctor 5 .....	36
3	SuperDoctor 5 Configurations .....	37
3.1	Working Concept .....	37
3.2	Connection Modes.....	38
3.3	Configuration Overview .....	43
3.3.1	Agent Object Definition .....	44
3.3.2	Acceptor Object Definition .....	45
3.3.3	Keystore Object Definition.....	46
3.3.4	Plug-in Object Definition.....	47
3.3.5	Action Object Definition .....	48
3.4	Built-in Plug-ins and Actions .....	49
3.4.1	admin plug-in (admin_plugin).....	49
3.4.2	echo plug-in (echo_plugin) .....	56
3.4.3	executable plug-in (executable_plugin).....	57

---

3.4.4	healthinfo plug-in (healthinfo_plugin).....	58
3.4.5	power plug-in (power_plugin) .....	64
3.4.6	systeminfo plug-in (systeminfo_plugin) .....	66
3.4.7	smart plug-in (smart_plugin) .....	70
3.4.8	bios log plug-in (bios_log_plugin) .....	72
3.4.9	memory plug-in (memory_health_plugin) .....	73
3.4.10	storage plug-in (storage_health_plugin) .....	75
3.4.11	LSI RAID plug-in (lsiraid_plugin) .....	76
3.4.12	notification plug-in (notification_plugin).....	78
4	SD5 Web.....	81
4.1	SD5 Web Login .....	81
4.2	Health Information .....	82
4.3	System Information .....	87
4.4	Reports.....	88
4.5	SD5 Web Configuration .....	89
4.5.1	Alert Configuration .....	89
4.5.2	Monitored Items .....	91
4.5.3	Account Setting.....	93
4.5.4	Flashing BIOS.....	94
4.6	RAID .....	98
4.7	Power Control .....	102
5	SNMP Extension .....	104
5.1	Setting Up the SNMP Service on Windows.....	104
5.1.1	Preparation .....	104
5.1.2	Configuring the SNMP Service .....	105
5.1.3	Verifying the SNMP Service .....	106
5.2	Setting Up the SNMP Service on Linux .....	106
5.2.1	Preparation .....	106
5.2.2	Configuring the SNMP Service .....	106
5.2.3	Verifying the SNMP Service .....	107
5.3	Supermicro MIB .....	108

---

6	SuperDoctor 5 Command Line Program .....	110
6.1	SDC Commands.....	110
6.1.1	–h: Display sdc command arguments .....	110
6.1.2	–d: Dump SNMP Messages .....	111
6.1.3	–e: Display All Monitored Items and their Status .....	111
6.1.4	–f: Write SNMP Messages to a Specified File .....	112
6.1.5	–i: Display All Monitored Items and their Status Repeatedly.....	113
6.1.6	–ia: Import Alert Configuration.....	114
6.1.7	–r: Reset the Chassis Intrusion.....	115
6.1.8	–rd: Detect the Monitored Items Again.....	115
6.1.9	–v: Display sdc version information.....	116
6.1.10	–reboot: Reboot the System.....	116
6.1.11	–shutdown: Shutdown the System.....	117
6.1.12	–abort: About the Shutdown or Reboot Command .....	117
6.1.13	–dt: Delay Seconds to Run Power Command .....	117
6.1.14	–flash: Flash BIOS.....	118
6.1.15	–flashlog: Show Flash History .....	118
6.1.16	–et: Export Threshold Configuration .....	119
6.1.17	–it: Import Threshold Configuration.....	120
6.1.18	–rt: Reset Threshold to Default Settings.....	122
6.1.19	–is: Install Smartmontools .....	122
7	SD5 Tray .....	124
7.1	Verifying SD5 Tray on Windows.....	124
7.2	Manually Controlling SD5 Tray .....	125
Part 3	Advanced Topics .....	126
8	SSM Utilities .....	127
8.1	Using ChangeJVM to Change a Java VM .....	127
8.2	Using Change_cert_pwd to Change the Certificate Password .....	129
9	SSM Certification.....	130
Part 4	Appendices.....	132
A	Log Settings .....	133



---

B	Third-Party Software.....	134
C	Updating Configurations.....	135
	Contacting Supermicro .....	136

---

# Part 1 Background

# 1 SuperDoctor 5 Overview

SuperDoctor 5 (SD5) is an agent system that runs on monitored hosts designed by Supermicro to provide local system health and information. SD5 supports a Web-based interface program and a command line interface program for server management.

## 1.1 Key Features

- Supports monitoring, control, and management functions.
  - Hardware Monitoring: fan speed, temperature, voltage, chassis intrusion, redundant power failure, power consumption, disk health, raid health, and memory health.
  - 20 Types of system information: BIOS, Baseboard, Chassis, Computer System, Disk Drives, Memory, Network, Printer, Processor, System Slot, IPMI, Power Supply, Account, Operating System, Process, Service, Share, Time Zone, OEM Strings, and System Cfg Options.
- Provides SNMP extensions for network management system.
- Easy to use Web-based and command line interfaces.
- Notifications sent via email and SNMP traps.
- Easy to customize:
  - Pluggable hardware and software monitoring plug-ins.
  - Compatible with Nagios plug-ins.
- Supports Windows and Linux platforms.




Figure 1-1: SD5 Web-based Console



#### Notes:

1. Monitoring memory health by SuperDoctor 5 is not available on Supermicro desktop motherboards. In addition, not all Supermicro servers support the function of monitoring memory health. Please refer to the Supermicro web site for an up-to-date list of supported products.
  2. Monitoring SMART health supports non-RAID internal hard disks and does not support USB hard disks and flash disks. **To use this function, install the smartctl utility program first.**
  3. Monitoring RAID health is available on LSI MegaRAID 2108, 2208 and 3108 controllers. LSI MegaRAID 2008, LSI Fusion-MPT based and Intel Rapid Storage Technology controllers are not supported.
  4. The system information is platform dependent. Types include Desktop Monitor, Floppy, Keyboard, Port Connector, Parallel Port, Pointing Device, Serial Port, Computer Summary, Startup Command, and Video Controller, which are supported on Windows platforms only.
  5. BIOS flashing function supports Supermicro motherboards newer than H8, X8, and X9 series on Windows platforms and motherboards newer than X9 series on Linux platforms. Please refer to the Supermicro web site for an up-to-date list of supported products.
  6. The system tray function is supported on Windows platforms only.
-

---

## 1.2 Minimum System Requirements

- Hardware
  - Supermicro servers
  - 200 MB free disk space
  - 64 MB available RAM
  - An Ethernet network interface card
- Operating System
  - Red Hat Enterprise Linux Server 5.x (64-bit), 6.x (64-bit), 7.x (64-bit)
  - SUSE Linux Enterprise 11.x (64-bit), 12.x (64-bit)
  - Windows Server 2008 R2 64-bit
  - Windows Server 2012 R2 64-bit
  - Windows Server 2016 64-bit



Note that SuperDoctor 5 might be run on the operating systems not in the support list but not fully validated by Supermicro.

- 
- Browser
    - Internet Explorer 8.x
    - Firefox 3.x
  - Screen resolution
    - 1024 x 768 or higher resolution

## 1.3 Default TCP/UDP Ports

- Binds TCP port 8181 for HTTP
- Binds TCP port 8444 for HTTPS
- Binds TCP ports 5333, 5666, and 5999 for NRPE (See [3.2 Connection Modes](#) for more information)
- Binds for internal communications TCP port 7777 and a free TCP port between 31000-32999
- SNMP GET sent on UDP 161
- SNMP Trap sent on UDP 162

---

## 2 Setting Up SD5

---

### 2.1 Installing SD5

SD5 provides installers for both Windows and Linux platforms. A user can run the installers in either of two modes: GUI interactive mode and text-console mode. The text-console mode can be run with either interaction or silence. If a user wants to deploy SD5 to a large number of hosts, installing with the text-console mode in silence is particularly useful.

#### 2.1.1 Windows Installation

1. Execute the SD5 installer. **Note that you must have Administrator privileges to install and run SD5.**
2. Click the **Next** button to continue.




Figure 2-1

3. Select the “I accept the terms of the License Agreement” option and click the **Next** button to continue.




Figure 2-2

4. Click the **Choose** button to select a directory to install SuperDoctor 5 and click the **Next** button to continue.




Figure 2-3

---

5. Select “Built-in (JRE 1.8.0\_112)” built-in Java VM and click the **Next** button.

---



**Note:** If you select "Choose a Java VM", the architecture of the selected Java VM must be compatible with the installer. For example, to use an x86 version of SuperDoctor 5, you need to select an x86 version of Java VM. Also note that only JVM version newer than 1.8.0 is supported.

---




Figure 2-4

6. In this step, users can decide whether to install SuperDoctor 5 SNMP extension or not. SuperDoctor 5 contains an SNMP extension module that should be plugged in into the Microsoft Windows SNMP service. Users can therefore query the readings of monitored items via SNMP. To install the SNMP extension, the Microsoft Windows SNMP service must be installed first.

If the Microsoft Windows SNMP service is not installed, you can either:

- exit the installation program to manually install the Microsoft Windows SNMP service,
- or
- install SuperDoctor 5 without the SNMP extension.






Figure 2-5

If the Microsoft Windows SNMP service is installed and started, you can either

- install SuperDoctor 5 and the SNMP extension,
- or
- install SuperDoctor 5 without the SNMP extension.




Figure 2-6

7. Select **Yes** to use the default key stores and click the **Next** button to continue. For more information on how the keystores are used, see [9 SSM Certification](#) in this manual.




Figure 2-7

8. Three communication modes are supported in SuperDoctor 5. See [3.2 Connection Modes](#) for more information. By default, Mode B (SSL) and Mode C (Keypair) are enabled when SuperDoctor 5 is installed. You can configure the port numbers. Click the **Next** button to continue.




Figure 2-8

- SuperDoctor 5 provides the Web console “SD5 Web” (see [4 SD5 Web](#) in this manual for more information). Select **Yes** to enable the SD5 Web. You can also configure the default HTTP port number and the default HTTPS port number to access the SD5 Web. When completed, click the **Next** button to continue. As for SD5 Tray, select **Yes** to enable the the SD5 Tray as well (see [7 SD5 Tray](#) in this manual for details).




Figure 2-9

- Click the **Install** button to install the SuperDoctor 5 software on your computer.




Figure 2-10

11. The installation is complete. Note that you do not need to reboot your computer to use SD5. Click the **Done** button to exit.





Figure 2-11

---

## 2.1.2 Linux Installation


1. Execute the SuperDoctor 5 installer. **Note that you must have root privileges to install and run SD5.**
2. Press the **Enter** key (on your keyboard) to continue.



```
root@localhost:~  
=====SD5 (created with InstallAnywhere)=====  
-----  
Preparing CONSOLE Mode Installation...  
  
-----  
Introduction  
-----  
  
InstallAnywhere will guide you through the installation of SuperDoctor 5.  
  
It is strongly recommended that you quit all programs before continuing with  
this installation.  
  
Respond to each prompt to proceed to the next step in the installation. If  
you want to change something on a previous step, type 'back'.  
  
You may cancel this installation at any time by typing 'quit'.  
  
PRESS <ENTER> TO CONTINUE:
```

Figure 2-12


3. Accept the license agreement and press the Enter key to continue.



```
root@localhost:~  
6. COMPLETE AGREEMENT. This Licence constitutes the entire agreement between  
the parties with respect to the use of the Software and Materials, and  
supersedes all prior or contemporaneous understandings or agreements, written  
or oral, regarding such subject matter. No amendment to or modification of  
this Licence will be binding unless in writing and signed by a duly authorized  
representative of Super Micro Computer Inc.  
  
Super Micro Computer Inc.  
980 Rock Avenue  
San Jose, CA 95131  
USA  
  
(408) 503-8000 Voice  
(408) 503-8008 Fax  
  
PRESS <ENTER> TO CONTINUE:  
  
E-mail: support@supermicro.com  
Internet: http://www.supermicro.com  
  
SD5(SuperDoctor 5) Copyright (c) 1993-2016 by Super Micro Computer Inc. and its  
licensors. All Rights Reserved.  
  
DO YOU ACCEPT THE TERMS OF THIS LICENSE AGREEMENT? (Y/N):
```

Figure 2-13

- 
4. Enter a directory to install SuperDoctor 5 and press the Enter key to continue. We recommend installing SuperDoctor 5 to the default folder (/opt/Supermicro/SuperDoctor5).




```
root@localhost:~
=====
Choose an install folder
=====
Where would you like to install?

Default Install Folder: /opt/Supermicro/SuperDoctor5

ENTER AN ABSOLUTE PATH, OR PRESS <ENTER> TO ACCEPT THE DEFAULT
:
```

Figure 2-14

5. Use the built-in Java VM and press the Enter key to continue.



```
root@localhost:~
=====
Choose a Java VM
=====
Please choose a Java VM for use by the installed application. Select
"Built-in" option to use built-in Java VM or select "Choose a Java VM" option
to use another Java VM version.

->1- Built-in (JRE 1.8.0_112)
   2- Choose a Java VM

ENTER THE NUMBER FOR YOUR CHOICE, OR PRESS <ENTER> TO ACCEPT THE DEFAULT::
```


Figure 2-15



**Note:** If you select "Choose a Java VM" option, the architecture of the selected Java VM must be compatible with the installer. For example, to use an x86 version of SuperDoctor 5, you need to select an x86 version of Java VM. Also note that only JVM version newer than 1.8.0 is supported.

---

6. Use the default key stores and press the Enter key to continue. For more information on how the keystores are used, see [9 SSM Certification](#) in this manual.



```
root@localhost:~
=====
Setup a key store
=====
Do you want to use the default key stores provided by the installer? A key
store contains public keys or private keys that are used to create a secure
communication channel between the SuperDoctor 5 and its callers (i.e., the SSM
Server, SSM Web, and SSM CLI).

->1- Yes
   2- No

ENTER THE NUMBER FOR YOUR CHOICE, OR PRESS <ENTER> TO ACCEPT THE DEFAULT::
```

Figure 2-16

- 
7. Three communication modes are supported in SuperDoctor 5. See [3.2 Connection Modes](#) in this manual for more information. By default, Mode B (SSL) and Mode C (Keypair) are enabled when SD5 is installed. You can configure the port numbers. Press the **Enter** key to continue.




Figure 2-17

8. SuperDoctor 5 provides the Web console “SD5 Web” (see [4 SD5 Web](#) in this manual for more information). Select **1** (Yes) to enable the SD5 Web. You can also configure the default HTTP port number and the default HTTPS port number to access the SD5 Web. When completed, press the **Enter** key to continue.





Figure 2-18

9. This step shows the pre-installation summary. Press the **Enter** key to continue.



```
root@localhost:~
=====
Pre-Installation summary
=====

Please review the following before continuing:

Install Folder:
  /opt/Supermicro/SuperDoctor5

KEEP CONFIG


DISPLAY_NAME

Disk Space Information (for Installation Target):
  Required: 368,389,254 Bytes
  Available: 26,567,258,112 Bytes

PRESS <ENTER> TO CONTINUE:
```

Figure 2-19

10. Press the **Enter** key to install the SuperDoctor 5 software on your computer.



```
root@localhost:~
=====
Ready To Install
=====


InstallAnywhere is now ready to install SuperDoctor 5 onto your system at the
following location:

  /opt/Supermicro/SuperDoctor5

PRESS <ENTER> TO INSTALL:
```

Figure 2-20

11. The installation is complete. Press the **Enter** key to exit the installer. **Note that you do not need to reboot your computer to use SD5.**



```
root@localhost:~
=====
Installation Complete
=====

Congratulations. SuperDoctor 5 has been successfully installed to:

/opt/Supermicro/SuperDoctor5

SuperDoctor 5 Web URL and default login account
URL http://localhost:8181
ID/PW ADMIN/ADMIN

Copyright (c) 1993-2016 Super Micro Computer Inc.


PRESS <ENTER> TO EXIT THE INSTALLER:
```

Figure 2-21



---

12. SuperDoctor 5 contains an SNMP extension module that can be plugged in to the default Linux SNMP service. The last step shows how to manually configure the default Linux SNMP service to enable the SuperDoctor 5 SNMP extension. To install the SNMP extension, the default Linux SNMP service must be installed first. The figure below shows the steps to manually plug the SuperDoctor 5 SNMP extension in to the default Linux SNMP service.



```
root@localhost:~
=====
SuperDoctor 5 SNMP extension configuration steps
=====

Do the following settings to enable the SNMP function provided by the
SuperDoctor 5 SNMP extension.

1. Add the following line into the file /etc/snmp/snmpd.conf
pass .1.3.6.1.4.1.10876 /opt/Supermicro/SuperDoctor5/libs/native/snmpagent
2. Restart the SNMP service.
service snmpd restart
3. For Red Hat Enterprise Linux 5.x, use the following command to allow the
SNMP extension to access hardware resources.
setsebool -P snmpd_disable_trans=1
4. For Red Hat Enterprise Linux 6.x, open /etc/selinux/config file and replace
"SELINUX=enforcing" with "SELINUX=disabled"

PRESS <ENTER> TO CONTINUE:
```

Figure 2-22

---

### 2.1.3 Silent Mode Installation

Silent mode installation provides a way to install SuperDoctor 5 without interaction from users. This is particularly useful when users want to deploy SuperDoctor 5 to a large number of hosts. To use silent mode installation, a property file that contains the necessary SuperDoctor 5 installation settings must be provided.

1. Prepare a property file for silent mode installation. All configuration options required by the SuperDoctor 5 installer are included in the property file. The example below shows how SuperDoctor 5 is installed on a Linux platform.

```
# This file was built by the Replay feature of InstallAnywhere.  
# It contains variables that were set by Panels or Consoles.
```

```
#Choose Install Folder  
# e.g., C:\\Program Files\\Supermicro\\SuperDoctor5  
#           /opt/Supermicro/SuperDoctor5  
#-----  
USER_INSTALL_DIR=/opt/Supermicro/SuperDoctor5  
  
#Choose Install Feature  
#-----  
CHOSEN_INSTALL_FEATURE_LIST=SuperDoctor5  
  
#Choose a Java VM  
#-----  
USE_DEFAULT_JVM=Yes  
# INSTALLED_JVM_PATH=/usr/java/jdk1.8.0_77/jre/bin/java  
#-----  
#Setup a keystore  
#-----  
USE_DEFAULT_KEYSTORE=Yes  
  
#AGENT_PRIVATE_KEYSTORE_PATH=/opt/agent.auth  
#AGENT_PUBLIC_KEYSTORE_PATH=/opt/agent.trust  
#USE_AGENT_DEFAULT_KEYSTORE_PASSWORD=Yes  
#AGENT_KEYSTORE_PASSWORD=your-keystore-password  
  
#Setup SNMP on Agent side  
#-----  
# Install SNMP extension  
USE_AGENT_SNMP_EXTENSION=No  
  
#Setup Agent connection ports  
#-----  
AGENT_ALLOW_IP=127.0.0.1  
AGENT_NO_SSL_PORT=5333  
AGENT_SSL_PORT=5666  
AGENT_KEYPAIR_PORT=5999  
  
#Setup Agent Web  
#-----  
USE_AGENT_WEB=Yes  
AGENT_WEB_HTTP_PORT=8181  
AGENT_WEB_HTTPS_PORT=8444  
  
### End of file
```

2. Modify the property to meet your needs. Possible attributes and values of the property file are listed below.

Attribute	Description	Option
USER_INSTALL_DIR	Install folder  <b>Note: It's necessary for you to choose the same install folder each time when you install each of these features on a host.</b>	
CHOSEN_INSTALL_FEATURE_LIST	Install features  <b>Note: Keep features in one line and be separated by a comma.</b>	SuperDoctor5
USE_DEFAULT_JVM	Uses default Java VM	Yes   No
INSTALLED_JVM_PATH	JVM path if <b>USE_DEFAULT_JVM=No</b>	
USE_AGENT_SNMP_EXTENSION	Installs SNMP extension	No   Yes
USE_DEFAULT_KEYSTORE	Uses default key store	Yes   No
AGENT_PRIVATE_KEYSTORE_PATH	Agent private key store path if <b>USE_DEFAULT_KEYSTORE=No</b>	
AGENT_PUBLIC_KEYSTORE_PATH	Agent public key store path if <b>USE_DEFAULT_KEYSTORE=No</b>	
USE_AGENT_DEFAULT_KEYSTORE_PASSWORD	Uses default password for agent key store.  <b>Note: It's required to set the USE_DEFAULT_KEYSTORE=No when you use customized password.</b>	Yes   No
AGENT_KEYSTORE_PASSWORD	The password for agent key store if <b>USE_DEFAULT_KEYSTORE=No</b> and <b>USE_AGENT_DEFAULT_KEYSTORE_PASSWORD=No</b>	Your-password
AGENT_ALLOW_IP	Allows connections to Internet addresses  <b>Note: Internet addresses should be in one line and separated by a comma.</b>	
AGENT_NO_SSL_PORT	Binds TCP ports for connection with plain text	5333
AGENT_SSL_PORT	Binds TCP ports for Anonymous SSL connection	5666

AGENT_KEYPAIR_PORT	Binds TCP ports for SSL connection with a public key infrastructure	5999
USE_AGENT_WEB	Enables SD5 Web	Yes   No
AGENT_WEB_HTTP_PORT	SD5 Web listen port	8181
AGENT_WEB_HTTPS_PORT	SD5 Web secure listen port	8444

3. Begin the silent mode installation.

For Windows platforms:

**SuperDoctor5Installer.exe -i silent -f [property\_file\_name]**

For Linux platforms:

**./SuperDoctor5Installer.bin -i silent -f [property\_file\_name]**

Note that there is no error message shown on the console in silent mode. Once the installation is completed, an **SD5\_InstallLog.log** file is generated in the [install folder] folder. This file contains installation log data that can be used for debugging purposes.

You can open the following log files to check whether SuperDoctor 5 is installed successfully. Note that these steps are optional and meant for troubleshooting only.

4. Check SD5\_InstallResult.log file to make sure SuperDoctor 5 is properly installed. Note that no error messages are shown on the console in silent mode. Once the installation is complete, the SD5\_InstallResult.log file is generated in the [install folder] folder. The following SD5\_InstallResult.log file shows that SuperDoctor 5 is properly installed.

```
Installation Result: Success
```

If a previous version of SuperDoctor 5 is detected during the installation process, the log file is shown like this:

```
Installation Time: Tue May 15 09:58:53 CST 2012
Detect previous: 'YES'
Installation Result: Success
```

With the installation log data, you can start troubleshooting.

Step 5: Check SD5\_InstallLog.log. The SD5\_InstallLog.log file is generated in the [install folder] folder. This file contains installation log data that can be used for debugging installation process. The following SD5\_InstallResult.log file shows an example that guides you to check SD5\_InstallLog.log file.

---

Installation Result: Failed  
Root Cause: Installation Process Failed

Please open SD5\_InstallLog.log to check "WARNING" or "ERROR" keywords and see if there are problems.

After opening the SD5\_InstallLog.log, you are able to see warnings or errors in the log file.

```
....  
Summary  
-----
```

```
Installation: Successful
```

```
1885 Successes  
5 Warnings  
0 NonFatalErrors  
0 FatalErrors
```

Note that all warnings and errors are logged in the file for reference.

---

## 2.1.4 Tips for Deploying a Large Number of SD5s

Suppose that you are going to deploy SuperDoctor 5 to a cluster containing 100 Supermicro servers. You can run the SuperDoctor 5 installer in silent mode to automate the installation process. Please follow these steps:

1. Prepare the SuperDoctor 5 installation program.
2. Prepare a silent mode installation file that will be used by the SuperDoctor 5 installer. Please refer to [2.1.3 Silent Mode Installation](#) to prepare the silent mode installation file.
3. Put the SuperDoctor 5 installation program and the silent mode installation file in a shared folder that can be accessed by the 100 Supermicro servers via the network (e.g., use NFS). Alternatively, you can establish an environment so that the 100 Supermicro servers can download the files using the `wget` program (e.g., put the files in a folder managed by a web server).
4. Write a Linux shell script to install SuperDoctor 5. The example below shows how SuperDoctor 5 is installed in the `/opt` folder on a Linux box:

```
cd /opt
echo "Delete the old SuperDoctor 5 Installer if there is one"
rm ./SuperDoctor5Installer*.bin

echo "Try to uninstall SuperDoctor 5"
/opt/Supermicro/SuperDoctor5/Uninstall/Uninstall -i silent

echo "Delete /opt/Supermicro/SuperDoctor5 folder"
rm -rf /opt/Supermicro/SuperDoctor5

echo "Download the new SuperDoctor 5 Installer"
wget http://your-server.com:8080/SuperDoctor5Installer_5.0.0.bin

echo "Download the silent mode configuration file "
wget http://your-server.com:8080/installer_agent.properties

echo "Install SuperDoctor 5"
chmod +x SuperDoctor5Installer*.bin
./SuperDoctor5Installer_5.0.0.bin -i silent -f installer_agent.properties

echo "Check SuperDoctor 5 service status"
service sd5 status
```


5. Deploy the script to each of the servers and then run it to install SuperDoctor 5.

---

## 2.2 Verifying the Installation

You can use the following commands to check whether SuperDoctor 5 is installed successfully and the service is running. Note that these steps are optional and meant for troubleshooting only.

After restarting your Windows system, open a DOS prompt and enter the following commands to make sure the SD5 service has been installed and started.



```
Administrator: Command Prompt
C:\Users\Administrator>sc query sd5
SERVICE_NAME: sd5
        TYPE               : 10  WIN32_OWN_PROCESS
        STATE                : 4   RUNNING
                        (STOPPABLE, NOT_PAUSABLE, ACCEPTS_SHUTDOWN)
        WIN32_EXIT_CODE      : 0    (0x0)
        SERVICE_EXIT_CODE  : 0    (0x0)
        CHECKPOINT          : 0x0
        WAIT_HINT           : 0x0

C:\Users\Administrator>
```

Figure 2-23

For Linux users, use the following commands to check the SD5 service:

```
# service sd5 status
```

RHEL 7.x and SLES 12.x users have additional commands to check SD5 services:

```
# systemctl status sd5
```

## 2.3 Manually Controlling SD5 Service

If SuperDoctor 5 service is not automatically started, you can start and stop the service manually.

For Windows platforms: In the **[install folder]** folder, execute **startSD5Service.bat** and **stopSD5Service.bat** to start and stop the SuperDoctor 5 service, respectively.

For Linux platforms: In the **[install folder]** folder, execute **startSD5Service.sh** and **stopSD5Service.sh** to start and stop the SD5 service, respectively.

---

## 2.4 Uninstalling SD5

In this section, we will show you how to uninstall SD5 on different platforms.

### 2.4.1 Uninstalling in Windows

1. Execute the Uninstall.exe in the [install folder]\Uninstall folder. **Note that you must have Administrator privileges to uninstall SD5.**
2. Click the **Uninstall** button to continue.




Figure 2-24

3. Please wait while the program uninstalls.




Figure 2-25



- 
4. When the uninstall is complete, click the **Done** button to exit the uninstaller.




Figure 2-26




**Note:** SuperDoctor 5 and Super Doctor III share the same drivers on Windows platforms. Uninstalling Super Doctor III will remove the shared drivers and damage SuperDoctor 5. Please do not install both applications on the same host.

---

---

## 2.4.2 Uninstalling in Linux


1. Execute the Uninstaller program located in the [install folder]\Uninstall\ folder. **Note that you must have root privileges to uninstall SD5.**



```
root@localhost/opt/Supermicro/SuperDoctor5/Uninstall
[root@localhost ~]# cd /opt/Supermicro/SuperDoctor5/Uninstall
[root@localhost Uninstall]# ./Uninstall
```

Figure 2-27

2. Press the **Enter** key (on your keyboard) to continue.



```
root@localhost/opt/Supermicro/SuperDoctor5/Uninstall
=====
SD5                                     (created with InstallAnywhere)
=====
Preparing CONSOLE Mode Uninstallation...

-----
Uninstall SuperDoctor 5
-----

About to uninstall...


SuperDoctor 5

This will remove features installed by InstallAnywhere. It will not remove
files and folders created after the installation.

PRESS <ENTER> TO CONTINUE:
```

Figure 2-28

3. Please wait while the program uninstalls.




```
root@localhost/opt/Supermicro/SuperDoctor5/Uninstall
=====
Uninstalling...
-----

...*
*
*****
*****
*****
*****
...*
*
*****
*****
*****
```

Figure 2-29

---

4. The uninstall is complete.

A terminal window titled "root@localhost:/opt/Supermicro/SuperDoctor5/Uninstall" with standard window controls. The terminal output shows "Uninstall Complete" followed by a dashed line separator and the message "Some items could not be removed." The prompt is "[root@localhost Uninstall]#".

```
root@localhost:/opt/Supermicro/SuperDoctor5/Uninstall
-----
Uninstall Complete
-----
Some items could not be removed.
[root@localhost Uninstall]#
```

Figure 2-30

### 2.4.3 Silent Mode Uninstall

Use the following argument to execute the Uninstaller program located in the [install folder]\Uninstall\ folder. **Note that you must have root privileges to uninstall SD5.**

```
Uninstall -i silent -f [property_file_name]
```

---

# Part 2 SuperDoctor 5

---

## 3 SuperDoctor 5 Configurations

SuperDoctor 5 needs to be installed on a host to provide in-band management functions. You can customize SuperDoctor 5 by modifying its configuration file, which is the `agent.cfg` file located in the `[install folder]` folder. Note that you need to manually restart SuperDoctor 5 after editing configurations. To restart the service of SuperDoctor 5, refer to [2.3 Manually Controlling SD5 Service](#). In most situations, you use SuperDoctor 5 once it is installed without modifying its configurations. This chapter introduces the working concepts of SuperDoctor 5 and the configuration objects it uses.

### 3.1 Working Concept

When SuperDoctor 5 is started, it listens to the TCP/IP ports and waits for requests sent by the SSM Server, SSM Web, and SSM CLI. SuperDoctor 5 supports five configuration objects, which control how SuperDoctor 5 functions.




Figure 3-1: The relationships among SuperDoctor 5 configuration objects

- 
- **Agent:** An agent object represents the SuperDoctor 5 application, which contains attributes such as **agent\_name**, **description**, and **version**. Only one agent object can be defined in the configuration file. By connecting the agent object to acceptor objects, you can define the port number and the connection type (SSL or Non-SSL) that SuperDoctor 5 should support.
  - **Acceptor:** An acceptor object contains an Internet address, a TCP port number, a connection type (SSL or Non-SSL), and key stores. An acceptor is enabled only when it is connected to an agent object. An agent object can have more than one acceptor object to provide multiple connection channels.
  - **Keystore:** When SSL is enabled in an acceptor object, you need to provide keystores to the acceptor to create an SSL connection. A keystore object is used to indicate the location of a keystore on the disk.
  - **Plug-in:** Similar to the SSM Server, SuperDoctor 5 applies a plug-in architecture and relies on plug-ins to provide management functions. The primary function of a plug-in object is to tell SuperDoctor 5 which plug-in main program should be invoked when a request is dispatched to the plug-in.
  - **Action:** A SuperDoctor 5 plug-in can provide multiple functions that can be called by clients (i.e. the SSM Server, SSM Web, and SSM CLI). An action object is used to export one function of a plug-in to the clients. A plug-in without defining any action object is useless because it cannot be invoked by the clients.

## 3.2 Connection Modes

SuperDoctor 5 supports three connection modes: plain text with allowed IP, anonymous SSL connection with allowed IP, and SSL connection with a public key infrastructure.

### Mode A: Plain text with allowed IP

Mode A provides the best transmission efficiency because data is transmitted as plain text without encryption between the client and SuperDoctor 5. To prevent unauthorized access to SuperDoctor 5, a connection can be established only if the request comes from an Internet address listed on the `allow_ip` attribute of the agent object.

---

### Configuration example:

#### 1. Defining a non-SSL acceptor object

The definition of a built-in non-SSL acceptor object is shown below. The **ssl\_enabled** attribute is set to **false** and the default port number for the non-SSL connection is 5333.

```
define acceptor {
    acceptor_name    non_SSL
    description      default non ssl port
    port            5333
    ssl_enabled     false
}
```

#### 2. Configuring the agent object

The definition of an agent object configured to use the above non-SSL acceptor is shown below. First, the **acceptor** attribute is set to **non\_SSL** (the value of the `acceptor_name` of the non-SSL acceptor) to tell SuperDoctor 5 to enable this acceptor. Second, IP addresses or domain names (in this example, 192.168.12.175.) are added that are allowed to access SuperDoctor 5 with the **allow\_ip** attribute.

```
define agent{
    agent_name      Agent
    description     Default Agent
    allow_ip       192.168.12.175
    plugin_path     ./plugins
    acceptor      non_SSL
    version         1.0.0
}
```

### Mode B: Anonymous SSL connection with allowed IP

Mode B is a trade-off between transmission efficiency and security. In this mode, an anonymous SSL connection is established so that data is encrypted between the client and SuperDoctor 5. However, since an anonymous SSL is used, preventing unauthorized access to SuperDoctor 5 is still required. Thus, the `allow_ip` attribute of an agent object is also used in mode B.

---

## Configuration example:

### 1. Defining an anonymous SSL acceptor

The definition of a built-in anonymous SSL acceptor object is shown below. The **ssl\_enabled** attribute is set to **true** and the default port number is **5666**. For establishing anonymous SSL connections, the **agent\_keystore** attribute needs to be set to a **keystore** object, which is used to encrypt data.

```
define acceptor {
    acceptor_name      default_acceptor
    description        default ssl port
    port               5666
    ssl_enabled        true
    agent_keystore     default_agent_keystore
}
```

### 2. Defining a keystore object

The definition of a built-in keystore object is shown below. The keystore contains a SuperDoctor 5 private key for encryption. The default keystore is located in the **[install folder]\certificates\agent.auth** file. See [9 SSM Certification](#) for more information on how to generate new keystores.

```
define keystore{
    keystore_name      default_agent_keystore
    description        keystore
    keystore_file      ./certificates/agent.auth
    keystore_password  <your-keystore-password>
}
```



---

### 3. Configuring the agent object

The definition of an agent object configured to use the above anonymous SSL acceptor is shown below. First, the **acceptor** attribute is set to **default\_acceptor** (the value of the **acceptor\_name** of the anonymous SSL acceptor) to tell SuperDoctor 5 to enable this acceptor. Second, IP addresses or domain names (in this example, 192.168.12.175.) are added to the **allow\_ip** attribute to access SuperDoctor 5.

```
define agent{
    agent_name      Agent
    description     Default Agent
    allow_ip       192.168.12.175
    plugin_path     ./plugins
    acceptor      default_acceptor
    version         1.0.0
}
```

#### Mode C: SSL encryption with a public key infrastructure

Mode C ensures secure communications and simplifies the authentication configuration with a public key infrastructure (PKI). See [9 SSM Certification](#) for more information about how the SSM Server and SuperDoctor 5 create a secure communication channel with the PKI. Since the PKI is used, the **allow\_ip** attribute of an agent object is no longer required for authentication.

#### Configuration examples:

##### 1. Defining an SSL acceptor supporting PKI

The definition of a built-in SSL acceptor object supporting PKI is shown in the example below. The **ssl\_enabled** attribute is set to true and the default port number is 5999. To establish SSL connections with PKI, the **agent\_keystore** and **trust\_keystore** attributes need to be set to a keystore object.

```
define acceptor{
    acceptor_name    keypair_acceptor
    description     default ssl port
    port           5999
    ssl_enabled    true
    agent_keystore default_agent_keystore
    trust_keystore default_trust_keystore
}
```

---

## 2. Defining two keystore objects

The definitions of two built-in keystore objects for supporting PKI are shown in the examples below. The `default_agent_keystore` contains an SD5 private key for encryption and the `default_trust_keystore` contains a client's public key for decryption.

```
define keystore{
    keystore_name      default_agent_keystore
    description        keystore
    keystore_file     ./certificates/agent.auth
    keystore_password <your-keystore-password>
}
```

```
define keystore{
    keystore_name      default_trust_keystore
    description        truststore
    keystore_file     ./certificates/agent.trust
    keystore_password <your-keystore-password>
}
```

## 3. Configuring the agent object

The definition of an agent object configured to use the above SSL acceptor is shown in the example below. All you need to do is to set the `acceptor` attribute to `keypair_acceptor` (the value of the `acceptor_name` of the SSL acceptor with PKI) so that SuperDoctor 5 can enable this acceptor. The `allow_ip` attribute is not used in this connection mode.

```
define agent{
    agent_name          Agent
    description         Default Agent
    allow_ip
    plugin_path         ./plugins
    acceptor           keypair_acceptor
    version             1.0.0
}
```



**Note:** By default, only modes B and C are enabled. To enable mode A, please modify the agent object configuration and append **no\_SSL** to the acceptor attribute.

```
define agent{
...
acceptor                default_acceptor, keypair_acceptor, no_SSL
}
```

---

## 3.3 Configuration Overview

Two kinds of configuration files are used by an SD5:

- **agent.cfg:** This is the main configuration file of an SD5. Three objects are defined in this file: **Agent**, **Acceptor**, and **Keystore**.
- **plugin.cfg:** This file is used to define SuperDoctor 5 plug-ins and their exported actions. The plug-ins located in the same plug-in path specified in the `plugin_path` attribute of an agent object should define one `plugin.cfg` file so that SuperDoctor 5 can discover how many plug-ins and actions are supported. A subfolder of a **plug-in path** can define its own `plugin.cfg` file. This file can also be packaged in the same jar file containing the Java bytecode that implements a plug-in.



**Note:** Multiple plug-ins can be defined in one jar file and SuperDoctor 5 will determine how many plug-ins are available according to the content of the `plugin.cfg` file.

---

The five object definitions are explained in the following sections.

---

### 3.3.1 Agent Object Definition

An agent object represents one SuperDoctor 5 program. It includes the information of the agent name, plug-in path and supporting connection modes.

```
define agent{
    agent_name      Agent
    description     Default Agent
    allow_ip        192.168.10.55, ssm.supermicro.com, 127.0.0.1
    plugin_path     ./plugins
    acceptor        default_acceptor, keypair_acceptor
    version         1.0.0
}
```

**agent\_name\***

The name of the agent object.

**description**

The description of the agent object.

**allow\_ip\***

The IP addresses or host names allowed to connect to the Agent are defined here. Multiple values should be separated by a comma. This attribute works if a non-SSL or anonymous SSL connection is used.

**plugin\_path\***

The root folder where the plug-ins are located.

**acceptor\***

The acceptors that are supported by the Agent. Multiple values should be separated by a comma.

**Version**

The version of the Agent.

(\*indicates a required attribute)

---

### 3.3.2 Acceptor Object Definition

An acceptor object is used to define the acceptable ways for it to connect to its clients. By defining various Acceptor objects, SuperDoctor 5 can support different kinds of connection methods at the same time.

```
define acceptor{
    acceptor_name      keypair_acceptor
    description        default_ssl_port
    address             *
    port                5999
    ssl_enabled        true
    agent_keystore     default_agent_keystore
    trust_keystore     default_trust_keystore
}
```

**acceptor\_name\***

The name of the acceptor object.

**description**

The description of the acceptor object.

**address**

The IP address where the acceptor should receive connections from. If a host has more than one network interface card, SuperDoctor 5 can be configured with this attribute to accept connections from particular IP addresses bound to the network interface cards. The acceptor will forward connection requests from all network interface cards if this attribute is not declared or if its value is an asterisk.

**port\***

The port number the acceptor should listen to.

**ssl\_enabled\***

Enables or disables SSL when a connection is established.

**agent\_keystore**

The private key used by the acceptor. This attribute is required if connection modes B and C are used.

**trust\_keystore**

The public key of SuperDoctor 5 clients. This attribute is required if the third connection mode is used.

(The asterisk mark “\*” indicates a required attribute.)

---

### 3.3.3 Keystore Object Definition

A keystore object is used to describe the name and the path (i.e., location) of a keystore as well as the password to access it. This object is applicable if the SSL connection is supported by SuperDoctor 5. See [3.2 Connection Modes](#) in this manual for more information.

```
define keystore{
    keystore_name      default_agent_keystore
    description        A keystore for storing agent's public/private key
    keystore_file      ./certificates/agent.auth
    keystore_password  <your-keystore-password>
}
```

keystore\_name\*

The name of the keystore object.

description\*

The description of the keystore object.

keystore\_file\*

The full file name (including path) of the keystore.

keystore\_password\*

The password used to open the keystore.

(The asterisk mark "\*" indicates a required attribute.)

---

### 3.3.4 Plug-in Object Definition

The primary goal of a plug-in object is to indicate a Java class that implements monitoring, control, or management functions. Usually, a plug-in is only activated by SuperDoctor 5 when a request is sent to the plug-in. By setting the active attribute of a plug-in object to 1, SuperDoctor 5 will proactively invoke the preload function of the plug-in every time SuperDoctor 5 starts. A plug-in can be disabled by setting the enable attribute to 0.

```
define plugin {
    plugin_name    healthinfo_plugin
    class_name     com.supermicro.ssm.agent.plugin.healthinfo.HealthInfoPlugin
    description    HealthInfo Plugin
    version        1.0.0
    active         1
    enabled        1
}
```

plug-in\_name\*

A unique name of the plug-in object.

class\_name\*

The Java implementation class of the plug-in object.

description\*

The description of the plug-in object.

version\*

The version of the plug-in object.

active

1: The plug-in will be loaded when SuperDoctor 5 is started.

0: The plug-in will not be loaded when SuperDoctor 5 is started. (Default value.)

enabled

1: Enable the plug-in. (Default value.)

0: Disable the plug-in.

(The asterisk mark "\*" indicates a required attribute.)

---

### 3.3.5 Action Object Definition

An action object defines the exported function and arguments provided by a plug-in.

```
define action {
    action_name      healthinfoitemnumber
    plugin_name      healthinfo_plugin
    description      Return the number of health monitored items
    args             -mn $ARG1$
    max_instance     0
}
```

#### action\_name\*

The name of the action object. The action name is the name to be invoked by SuperDoctor 5 clients. For example, when using `jcheck_nrpe` to connect to SuperDoctor 5, this attribute is provided with the `-c` argument of `jcheck_nrpe`.

#### plugin\_name\*

The name of the plug-in object implemented by this action. Every action belongs to one and only one plug-in.

#### description\*

The description of the action object.

#### args

The arguments required by the action. For example, when using `jcheck_nrpe` to connect to SuperDoctor 5, this attribute is provided with the `-a` argument of `jcheck_nrpe`.

#### max\_instance

The maximum number of concurrent clients allowed to invoke the action. This attribute is used to prevent SuperDoctor 5 from being overloaded due to burst requests for an action. This attribute could be omitted if concurrent access constraint to an action is not necessary.

(The asterisk mark “\*” indicates a required attribute.)



---

## 3.4 Built-in Plug-ins and Actions

The built-in plug-ins of SuperDoctor 5 are packaged in the

**[install folder]\plugins\builtin\SSMAgentPlugin-build.xx.jar** file. Note that you need to manually restart SuperDoctor 5 after editing configurations. For details on restarting the service of SuperDoctor 5, refer to [2.3 Manually Controlling SD5 Service](#). In most situations, you do not need to understand or change the built-in plug-ins. However, if you want to write your own automation scripts to invoke the functions exported by the plug-ins, you can find the necessary information in this section. Users who want to develop new SuperDoctor 5 plug-ins can also learn how to define a plugin.cfg file for their own plug-ins.

### 3.4.1 admin plug-in (admin\_plugin)

This plug-in is used to manage all SuperDoctor 5 plug-ins and the life cycle of SuperDoctor 5. Actions provided by the admin plug-in include `plugin_ver`, `all_plugin_ver`, `restart`, `update`, `generate_config`, and `check_now`. The definition of the plug-in is shown below.

```
define plugin {
    plugin_name    admin_plugin
    class_name     com.supermicro.ssm.agent.plugin.admin.AdminPlugin
    description    Admin Plugin
    version        1.0.0
}
```

---

### 3.4.1.1 *plugin\_ver* Action

This action is used to query the version of a specific plug-in.

```
define action {
    action_name      plugin_ver
    plugin_name      admin_plugin
    description      Get the version of the plug-in
    args             -v -n $ARG1$
}
```

Options:

ARG1: The name of the plug-in.

Usage:

```
jcheck_nrpe -H <host address> -dk -c plugin_ver -a <ARG1>
```

Example:

Use `jcheck_nrpe` to query the version of `admin_plugin` on host `10.134.12.18`.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c plugin_ver -a
admin_plugin
admin_plugin version = 1.0.0
```

Figure 3-2

---

### 3.4.1.2 *all\_plugin\_ver* Action

This action is used to query the versions of all plug-ins.

```
define action {  
    action_name      all_plugin_ver  
    plugin_name      admin_plugin  
    description      Get versions of all plug-ins  
    args             -v  
}
```

Options:

None.

Usage:

`jcheck_nrpe -H <host address> -dk -c all_plugin_ver`

Example:

Use `jcheck_nrpe` to inquire the versions of all plug-ins on host 10.134.12.18.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c all_plugin_ver  
Agent version = 2.1-build.9066-20140117191958  
Plugin version ...  
processor_plugin = 1.0.0  
healthinfo_plugin = 1.0.0  
compound_health_plugin = 1.0.0  
receive_passive_check_plugin = 1.0.0  
lsiraid_plugin = 1.0.0  
agent_web = 1.0.0  
echo_plugin = 1.0.0  
memory_health_plugin = 1.0.0  
fake_healthinfo_plugin = 1.0.0  
ipmi_plugin = 1.0.0  
notification_plugin = 1.0.0  
send_passive_check_plugin = 1.0.0  
bios_log_plugin = 1.0.0  
smart_plugin = 1.0.0  
admin_plugin = 1.0.0  
systeminfo_plugin = 1.0.0  
executable_plugin = 1.0.0  
power_plugin = 1.0.0  
storage_health_plugin = 1.0.0  
flashBIOS_plugin = 1.0.0
```

Figure 3-3

---

### 3.4.1.3 restart Action

This action is used to restart SuperDoctor 5.

```
define action {  
    action_name      restart  
    plugin_name      admin_plugin  
    description      Restart Agent  
    args             -s  
}
```

Options:

None.

Usage:

jcheck\_nrpe -H <host address> -dk -c restart

Example:

Use jcheck\_nrpe to restart SuperDoctor 5 on host 10.134.12.18.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c restart  
Agent restart message has been sent.
```

Figure 3-4

---

### 3.4.1.4 update Action

This action is used to update SuperDoctor 5. The definition of this action is shown below.

```
define action {  
    action_name      update  
    plugin_name      admin_plugin  
    description      Update Agent  
    args             -u $ARG1$  
}
```

Options:

ARG1: The update site containing the latest version of SuperDoctor 5.

Note:

If the version of the installed SuperDoctor 5 is earlier than the latest version available on the update site, the action will be performed.

Usage:

`jcheck_nrpe -H <host address> -dk -c update -a <ARG1>`

Example:

Use `jcheck_nrpe` to update SuperDoctor 5 on host 10.134.12.18.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c update -a http  
://ssm3.supermicro.com.tw:8080/cruisecontrol/artifacts/Downloads/ -t 240  
Agent restart message has been sent.
```

Figure 3-5

If the program does not need to be updated, a message “Nothing to update” appears (see the figure below).

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c update -a http  
://ssm3.supermicro.com.tw:8080/cruisecontrol/artifacts/Downloads/ -t 240  
Nothing to update.
```

Figure 3-6

---

### 3.4.1.5 *generate\_config* Action

This action is used to generate service object definitions for a particular plug-in. The definition of this action is shown below.

```
define action {  
    action_name      generate_config  
    plugin_name      admin_plugin  
    description      Generate configurations  
    args             -H $ARG1$ --args $ARG2$ -check_ipmi $ARG3$  
}
```

#### Options:

ARG1: The IP address of the agent-managed host.

ARG2: The name of the configuration object(s). Valid values include ALL, ping\_host, and each of the plug-in names. Multiple values are separated by a comma.

ARG3: true: Generate IPMI related object definitions as well.

false: Do not generate IPMI related object definitions.

#### Usage:

```
jcheck_nrpe -H <host address> -dk -c generate_config -a <ARG1>!  
<ARG2>!  
<ARG3> -plus
```

#### Example:

Use jcheck\_nrpe to generate object definitions on host 10.134.12.18.

```

[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c generate_conf
g -a 10.134.12.18\!ALL\!true -plus
[[{"agent_version":"1.0.0_build.457-20140124163824","agent_os_version":"Red Hat Ente
rprise Linux Server release 6.0","use":"agent_managed host, linux_host","wol_mac_add
ress":"00-30-48-fd-e4-08"}, [{"use":"processor_health","check_command":"jcheck_proc
essor_health!1!pid0","service_description":"Processor health"}, [{"notification_peri
od":"24x7","check_interval":60,"use":"health_compare","host_name":null,"check_peri
od":"24x7","retry_interval":1,"contacts":"admin","notifications_enabled":1,"notificati
on_options":"w,u,c,r,f","service_description":"FAN 1","check_command":"jcheck_health
!!a!0!0!784","notification_interval":120,"contact_groups":"admins"}, {"notification_p
eriod":"24x7","check_interval":60,"use":"health_compare","host_name":null,"check_per
iod":"24x7","retry_interval":1,"contacts":"admin","notifications_enabled":1,"notific
ation_options":"w,u,c,r,f","service_description":"FAN 2","check_command":"jcheck_hea
lth!!a!1!0!784","notification_interval":120,"contact_groups":"admins"}, {"notificati
on_period":"24x7","check_interval":60,"use":"health_compare","host_name":null,"check
_period":"24x7","retry_interval":1,"contacts":"admin","notifications_enabled":1,"noti
fication_options":"w,u,c,r,f","service_description":"FAN 3","check_command":"jcheck_
health!!a!2!0!784","notification_interval":120,"contact_groups":"admins"}, {"notifica
tion_period":"24x7","check_interval":60,"use":"health_compare","host_name":null,"che
ck_period":"24x7","retry_interval":1,"contacts":"admin","notifications_enabled":1,"n
otification_options":"w,u,c,r,f","service_description":"FAN 4","check_command":"jche
ck_health!!a!3!0!784","notification_interval":120,"contact_groups":"admins"}, {"notif
ication_period":"24x7","check_interval":60,"use":"health_compare","host_name":null,"
check_period":"24x7","retry_interval":1,"contacts":"admin","notifications_enabled":1
,"notification_options":"w,u,c,r,f","service_description":"FAN 5","check_command":"j
check_health!!a!4!0!784","notification_interval":120,"contact_groups":"admins"}, {"no
tification_period":"24x7","check_interval":60,"use":"health_compare","host_name":nul
l,"check_period":"24x7","retry_interval":1,"contacts":"admin","notifications_enabled
":1,"notification_options":"w,u,c,r,f","service_description":"CPU1 Vcore","check_com
mand":"jcheck_health!!a!8!1352!824","notification_interval":120,"contact_groups":"ad
mins"}, {"notification_period":"24x7","check_interval":60,"use":"health_compare","hos
t_name":null,"check_period":"24x7","retry_interval":1,"contacts":"admin","notificati
ons_enabled":1,"notification_options":"w,u,c,r,f","service_description":"CPU1 DIMM",
"check_command":"jcheck_health!!a!10!1656!1336","notification_interval":120,"contact
_groups":"admins"}, {"notification_period":"24x7","check_interval":60,"use":"health_c
ompare","host_name":null,"check_period":"24x7","retry_interval":1,"contacts":"admin"
,"notifications_enabled":1,"notification_options":"w,u,c,r,f","service_description":

```

Figure 3-7

---

## 3.4.2 echo plug-in (echo\_plugin)

This plug-in is used for testing purposes. The definition of this plug-in is shown below.

```
define plugin {
    plugin_name    echo_plugin
    class_name     com.supermicro.ssm.agent.plugin.echo.EchoPlugin
    description    Echo Plugin
    version        1.0.0
}
```

### 3.4.2.1 echo Action

This action is used to return the same message received by SuperDoctor 5 back to the client.

```
define action {
    action_name    echo
    plugin_name    echo_plugin
    description    Echo
    args           --text $ARG1$
}
```

Options:

ARG1: The input message.

Usage:

```
jcheck_nrpe -H <host address> -dk -c echo -a <ARG1>
```

Example:

Use jcheck\_nrpe to echo a message.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c echo -a "Test
echo"
Test echo
```

Figure 3-8



---

### 3.4.3 executable plug-in (executable\_plugin)

This plug-in is designed to execute external programs or scripts. By using this plug-in, users can extend the functions of SuperDoctor 5 without writing new SuperDoctor 5 Java plug-ins. The definition of this plug-in is shown below.

```
define plugin {
    plugin_name    executable_plugin
    class_name     com.supermicro.ssm.agent.plugin.executable.ExecutablePlugin
    description    Executable Plugin
    version        1.0.0
}
```

#### 3.4.3.1 executable Action

This action is used to execute an external program.

```
define action {
    action_name    executable
    plugin_name    executable_plugin
    description    Execute an external command
    args           --executable $ARG1$ --args $ARG2$ --timeout $ARG3$
}
```

Options:

ARG1: The file name of the external program.

ARG2: The arguments for the external program. Multiple values should be separated by a space, such as "arg1 arg2 arg3".

ARG3: The time in seconds the plug-in should wait for the external program to complete its execution. The default value is 60.

Usage:

```
jcheck_nrpe -H <host address> -dk -c executable -a <ARG1>!<ARG2>!<ARG3>
```

---

Example:

Use jcheck\_nrpe to execute an echo program on host 10.134.12.18.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c executable -a
echo\!"Test echo"
Test echo
```

Figure 3-9

### 3.4.4 healthinfo plug-in (healthinfo\_plugin)

This plug-in is used to check the health of all monitored items. Six actions are included: health\_item\_num, health\_reading, health\_compare, health\_def, health\_all, and reset\_switch. They are used to get the number of monitored items, query readings of monitored items, check health status with user-defined thresholds, retrieve definitions of monitored items, check health status using default thresholds, and reset chassis intrusion, respectively. The definition of this plug-in is shown below.

```
define plugin {
    plugin_name      healthinfo_plugin
    class_name
    com.supermicro.ssm.agent.plugin.healthinfo2.HealthInfoPlugin2
    description      HealthInfo Plugin
    version          1.0.0
    active           1
}
```

#### 3.4.4.1 health\_item\_num Action

This action is used to get the number of monitored items.

```
define action {
    action_name      health_item_num
    plugin_name      healthinfo_plugin
    description      Get the number of health monitored items
    args             -mn $ARG1$
}
```

---

Options:

ARG1: Types of monitored items. The valid values are:

- a: all monitored items
- f: fan
- v: voltage
- s: switch
- c: circuit

Usage:

`jcheck_nrpe -H <host> -dk -c health_item_num -a <ARG1>`

Example:

Use `jcheck_nrpe` to get the count of all monitored items on host 192.168.12.18.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c health_item_num -a a
63
```

Figure 3-10

---

### 3.4.4.2 *health\_reading* Action

This action is used to get the reading of a specific monitored item.

```
define action {  
    action_name      health_reading  
    plugin_name      healthinfo_plugin  
    description      Get reading of a health monitored item  
    args             $ARG1$ -t $ARG2$ -n $ARG3$  
}
```

Options:

ARG1: -csv: Display the result in CSV format

ARG2: Types of monitored items. The valid values are:

a: all monitored items

f: fan

v: voltage

s: switch

c: circuit

ARG3: The index of a monitored item (begins with 0)

Usage:

```
jcheck_nrpe -H <host> -dk -c health_reading -a <ARG1>!<ARG2>!<ARG3>
```

Example:

Use `jcheck_nrpe` to get the reading of the first fan on host 10.134.12.18.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c health_reading  
-a \!f\!0  
[0]FAN 1 is 9216RPM
```

Figure 3-11

---

### 3.4.4.3 *health\_compare Action*

Check the health status of a specific monitored item with user-defined thresholds.

```
define action {
    action_name    health_compare
    plugin_name    healthinfo_plugin
    description    Get and compare reading of a health monitored item with high/low limits
    args           $ARG1$ -t $ARG2$ -n $ARG3$ -high $ARG4$ -low $ARG5$
}
```

Options:

ARG1: -csv: Display the results in CSV format

ARG2: Types of monitored items. The valid values are:

a: all monitored items

f: fan

v: voltage

s: switch

c: circuit

ARG3: The index of a monitored item (begins with 0).

ARG4: The high limit.

ARG5: The low limit.

Usage:

```
jcheck_nrpe -H <host address> -dk -c health_compare -a <ARG1>!<ARG2>!<ARG3>!<ARG4>!<ARG5>
```

Example:

Use `jcheck_nrpe` to check the health status of the first voltage on host 10.134.12.18 with a user-defined high limit of 1350 mV and low limit of 900 mV.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c health_compare
-a \!v\!0\!1350\!900
[0] CPU1 Vcore is normal(1350mV>=1024mV>=900mV)
```

Figure 3-12

### 3.4.4.4 health\_def Action

This action is used to retrieve the definitions of all monitored items. The generated definitions are used by SSM Web to generate the default monitoring services of an agent-managed host.

```
define action {
    action_name    health_def
    plugin_name    healthinfo_plugin
    description    Get the definitions of all health monitored items
    args           -d $ARG1$ -f $ARG2$
}
```

Options:

ARG1: The IP address of an agent-managed host.

ARG2: 1: Filter inactive items;

0: Do not filter inactive items.

Usage:

```
jcheck_nrpe -H <host address> -dk -c health_def -a <ARG1>|<ARG2>
```

Example:

Use jcheck\_nrpe to get the definitions of all monitored items on host 10.134.12.18.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c health_def -a
10.134.12.18 -plus
[{"notification_period":"24x7","check_interval":60,"use":"health_compare","host_name
":"10.134.12.18","check_period":"24x7","retry_interval":1,"contacts":"admin","notifi
cations_enabled":1,"notification_options":"w,u,c,r,f","service_description":"FAN 1",
"check_command":"jcheck_health!!a!0!0!784","notification_interval":120,"contact_grou
ps":"admins"}, {"notification_period":"24x7","check_interval":60,"use":"health_compar
e","host_name":"10.134.12.18","check_period":"24x7","retry_interval":1,"contacts":"a
dmin","notifications_enabled":1,"notification_options":"w,u,c,r,f","service_descript
ion":"FAN 2","check_command":"jcheck_health!!a!1!0!784","notification_interval":120,
"contact_groups":"admins"}, {"notification_period":"24x7","check_interval":60,"use":
"health_compare","host_name":"10.134.12.18","check_period":"24x7","retry_interval":1,
"contacts":"admin","notifications_enabled":1,"notification_options":"w,u,c,r,f","ser
vice_description":"FAN 3","check_command":"jcheck_health!!a!2!0!784","notification_i
nterval":120,"contact_groups":"admins"}, {"notification_period":"24x7","check_interva
l":60,"use":"health_compare","host_name":"10.134.12.18","check_period":"24x7","retry
_interval":1,"contacts":"admin","notifications_enabled":1,"notification_options":"w,
u,c,r,f","service_description":"FAN 4","check_command":"jcheck_health!!a!3!0!784","n
otification_interval":120,"contact_groups":"admins"}, {"notification_period":"24x7","
check_interval":60,"use":"health_compare","host_name":"10.134.12.18","check_period":
"24x7","retry_interval":1,"contacts":"admin","notifications_enabled":1,"notification
_options":"w,u,c,r,f","service_description":"FAN 5","check_command":"jcheck_health!!
a!4!0!784","notification_interval":120,"contact_groups":"admins"}, {"notification_per
iod":"24x7","check_interval":60,"use":"health_compare","host_name":"10.134.12.18","c
heck_period":"24x7","retry_interval":1,"contacts":"admin","notifications_enabled":1,
"notification_options":"w,u,c,r,f","service_description":"CPU1 Vcore","check_command
":"jcheck_health!!a!8!1352!824","notification_interval":120,"contact_groups":"admins
"}, {"notification_period":"24x7","check_interval":60,"use":"health_compare","host_na
me":"10.134.12.18","check_period":"24x7","retry_interval":1,"contacts":"admin","noti
fications_enabled":1,"notification_options":"w,u,c,r,f","service_description":"CPU1
DIMM","check_command":"jcheck_health!!a!10!1656!1336","notification_interval":120,"c
ontact_groups":"admins"}, {"notification_period":"24x7","check_interval":60,"use":"he
alth_compare","host_name":"10.134.12.18","check_period":"24x7","retry_interval":1,"c
ontacts":"admin","notifications_enabled":1,"notification_options":"w,u,c,r,f","servi
ce_description":"+1.5 V","check_command":"jcheck_health!!a!12!1656!1336","notificati
on_interval":120,"contact_groups":"admins"}, {"notification_period":"24x7","check_int
erval":60,"use":"health_compare","host_name":"10.134.12.18","check_period":"24x7","r
```

Figure 3-13

---

### 3.4.4.5 *health\_all* Action

Check the health status of all monitored items with default thresholds.

```
define action {
    action_name    health_all
    plugin_name    healthinfo_plugin
    description    Get readings of all monitored items and compare with default high/low limits
    args           -a -x $ARG1$ -f $ARG2$
}
```

Options:

ARG1: The index of monitored items to be excluded. Multiple values are separated by a comma.

ARG2: 1: Filter inactive items;

0: Do not filter inactive items.

Usage:

jcheck\_nrpe -H <host address> -dk -c health\_all -a <ARG1>!<ARG2>

Example:

Use jcheck\_nrpe to check the health status of all monitored items on host 192.168.12.18 with default thresholds.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c health_all
Checked: 22, OK: 22. |
FAN_1=9216RPM;0;0;784;13000 FAN_2=10404RPM;0;0;784;13000 FAN_3=9216RPM;0;0;784;13000
FAN_4=9216RPM;0;0;784;13000 FAN_5=9216RPM;0;0;784;13000 CPU1_Vcore=0.928V;0;0;0.824
;1.352 CPU1_DIMM=1.512V;0;0;1.336;1.656 +1.5_V=1.52V;0;0;1.336;1.656 +5_V=5.088V;0;0
;4.48;5.536 +5VSB=5.088V;0;0;4.48;5.536 +12_V=12.19V;0;0;10.706;13.25 +1.1_V=1.12V;0
;0;0.976;1.216 +3.3VCC=3.312V;0;0;2.928;3.648 +3.3VSB=3.264V;0;0;2.928;3.648 VBAT=3.
192V;0;0;2.928;3.648 System_Temp=30C;0;0;0;75 P1-DIMM1A=37C;0;0;0;75 P1-DIMM2A=34C;0
;0;0;75 Chassis_Intru=OSWITCH;0;0;-1;2 PS_Status=OSWITCH;0;0;-1;2 PS2_Fan1=8512RPM;0
;0;720;13000 PS2_Temperature1=41C;0;0;0;10000 PS2_Temperature2=36C;0;0;0;10000 PS2_A
CInputCurrent=0.156A;0;0;-10000;10000 PS2_DC12VOutputCurrent=4.5A;0;0;-10000;10000 P
S2_ACInputPower=33W;0;0;-10000;10000 PS2_DC12VOutputPower=56W;0;0;-10000;10000 PS2_A
CInputVoltage=225.5V;0;0;-10000;10000 PS2_DC12VOutputVoltage=12.187V;0;0;-10000;1000
0 PS2_Status=OSWITCH;0;0;-1;2 PS1_Fan1=8352RPM;0;0;720;13000 PS1_Temperature1
```

Figure 3-14

---

### 3.4.4.6 *reset\_switch* Action

Clear a chassis intrusion flag. The definition of this action is shown below.

```
define action {
    action_name      reset_switch
    plugin_name      healthinfo_plugin
    description      Clear the trigger created by switch
    args             -reset
}
```

Options:

None.

Usage:

```
jcheck_nrpe -H <host address> -dk -c reset_switch
```

Example:

Use `jcheck_nrpe` to reset the chassis intrusion flag on host 10.134.12.18.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c reset_switch
Switch [Chassis Intrusion] reset successful.
```

Figure 3-15

### 3.4.5 *power plug-in (power\_plugin)*

This plug-in is used to support power control functions such as power off, reboot, and shutdown. The definition of this plug-in is shown below.

```
define plugin {
    plugin_name power_plugin
    class_name   com.supermicro.ssm.agent.plugin.powercontrol.PowerControlPlugin
    description  Power Plugin
    version      1.0.0
}
```



---

### 3.4.5.1 *powercontrol* Action

This action implements power off, reboot, and shutdown functions.

```
define action {
    action_name      powercontrol
    plugin_name      power_plugin
    description      Power control the local machine
    args             -t $ARG1$ -d $ARG2$
    version          1.0.0
}
```

#### Options:

ARG1: Types of power control functions. The valid values are:

0: Abort. This argument is not recommended for use.

1: Power off. This argument is not recommended for use.

2: Reboot.

3: Shutdown.

ARG2: The number of seconds to wait before the power control command takes effect.

#### Usage:

```
jcheck_nrpe -H <host address> -dk -c powercontrol -a <ARG1>!<ARG2>
```

#### Example:

Use `jcheck_nrpe` to reboot host 10.134.12.34 after 10 seconds.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.34 -dk -c powercontrol -a 2\!10
The reboot command is fired.
```

Figure 3-16

---

## 3.4.6 systeminfo plug-in (systeminfo\_plugin)

This plug-in is used to query local system information. Two actions are included: systeminfo for getting all system information items and systeminfo\_item for getting one specific system information item. The definition of this plug-in is shown below.

```
define plugin {
  plugin_name      systeminfo_plugin
  class_name       com.supermicro.ssm.agent.plugin.systeminfo.SystemInfoPlugin
  description      SystemInfo Plugin
  version          1.0.0
}
```

### 3.4.6.1 systeminfo Action

This action is used to query software and hardware information such as the OS version, CPU model, physical memory, printer, services, and so on.

```
define action {
  action_name      systeminfo
  plugin_name      systeminfo_plugin
  description      Get system information of local machine
  max_instance    1
}
```

Options:  
None.

Usage:  
jcheck\_nrpe -H <host address> -dk -c systeminfo

Example:  
Use jcheck\_nrpe to get system information on host 10.134.12.18.

```

[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c systeminfo -t
120 -plus
{"19":[],"35":[{"OEM Record":[],"FRU File ID":"","Base Compatibility Record":[],"
DC Load":[],"Firmware Version":"1.0","Product Serial Number":"P7031CA39IT7147","E
xtended Compatibility Record":[],"Product Version":"1.0","Product Name":"PWS-703P-
1R","Power Supply Information":{"Overall capacity (watts):700<br>Peak VA:795<br>In
rush:25<br>Inrush interval (ms):17<br>Low end Input voltage range 1 (mV):100000<br>H
igh end Input voltage range 1 (mV):140000<br>Low end Input voltage range 2 (mV):1800
00<br>High end Input voltage range 2 (mV):240000<br>Low end Input frequency range:50
<br>High end Input frequency range:60<br>A\\C dropout tolerance (ms):15<br>Hot Swa
p Support<br>Autoswitch<br>Power factor correction<br>No Predictive fail support<br>
Hold up time (second):0<br>Peak capacity (watts):700<br>Combined Wattage Voltage 1:1
2V<br>Combined Wattage Voltage 2:12V<br>Total Combined Wattage Voltage:0<br>Predicti
ve fail pin indicates pass\\fail.The signal asserted (1) indicates failure.\\"},"M
anufacturer Name":"SUPERMICRO","Asset Tag":"","DC Output":{"Standby<br>Output numb
er:1<br>Nominal voltage:5000 (mV) <br>Maximum negative voltage deviation:4800 (mV) <br>M
aximum positive voltage deviation:5250 (mV) <br>Ripple and Noise pk-pk 10Hz to 30MHz:5
0 (mV) <br>Minimum current draw:0 (mA) <br>Maximum current draw:4000 (mA)\\"},"Output numb
er:2<br>Nominal voltage:12000 (mV) <br>Maximum negative voltage deviation:11520 (mV) <br
>Maximum positive voltage deviation:12600 (mV) <br>Ripple and Noise pk-pk 10Hz to 30MH
z:120 (mV) <br>Minimum current draw:0 (mA) <br>Maximum current draw:58000 (mA)\\"},"Manag
ement Access Record":[],"Product Part\\Model Number":"PWS-703P-1R"}, {"OEM Record":
[],"FRU File ID":"","Base Compatibility Record":[],"DC Load":[],"Firmware Vers
ion":"1.0","Product Serial Number":"P7031CA39IT7145","Extended Compatibility Record"
:[],"Product Version":"1.0","Product Name":"PWS-703P-1R","Power Supply Information
":{"Overall capacity (watts):700<br>Peak VA:795<br>Inrush:25<br>Inrush interval (m
s):17<br>Low end Input voltage range 1 (mV):100000<br>High end Input voltage range 1
 (mV):140000<br>Low end Input voltage range 2 (mV):180000<br>High end Input voltage
 range 2 (mV):240000<br>Low end Input frequency range:50<br>High end Input frequency
 range:60<br>A\\C dropout tolerance (ms):15<br>Hot Swap Support<br>Autoswitch<br>Po
wer factor correction<br>No Predictive fail support<br>Hold up time (second):0<br>Pe
ak capacity (watts):700<br>Combined Wattage Voltage 1:12V<br>Combined Wattage Voltag
e 2:12V<br>Total Combined Wattage Voltage:0<br>Predictive fail pin indicates pass\\
\\fail.The signal asserted (1) indicates failure.\\"},"Manufacturer Name":"SUPERMICRO
","Asset Tag":"","DC Output":{"Standby<br>Output number:1<br>Nominal voltage:5000 (
mV) <br>Maximum negative voltage deviation:4800 (mV) <br>Maximum positive voltage devia
tion:5250 (mV) <br>Ripple and Noise pk-pk 10Hz to 30MHz:50 (mV) <br>Minimum current draw

```

Figure 3-17

### 3.4.6.2 systeminfo\_item Action

This action is used to query one specific system information item.

```

define action {
    action_name      systeminfo_item
    plugin_name      systeminfo_plugin
    description      Get specific system information of a local machine
    args             -i $ARG1$
    max_instance     1
}

```

---

Options:

ARG1: Types of system information items include:

Options:

ARG1:

0: account  
1: baseboard  
2: bios  
3: cd rom  
4: chassis  
5: computer system  
6: disk  
7: floppy  
8: keyboard  
9: logical disk  
10: logical memory  
11: memory  
12: desktop monitor  
13: network  
14: os  
15: processor  
16: process  
17: port connector  
18: pointing device  
19: parallel port  
20: printer  
21: service  
23: share  
24: serial port  
25: system slot  
26: computer summary  
27: time zone  
28: video controller  
30: ipmi  
34: startup command  
35: fru  
36: oem strings  
37: system cfg options  
38: power supply

Usage:

jcheck\_nrpe -H <host address> -dk -c systeminfo\_item -a <ARG1>

Example:

Use jcheck\_nrpe to get user accounts on host 10.134.12.18.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c systeminfo_ite
m -a 0 -plus
[{"Name":"root","Caption":"","Description":"root","Domain":"","Disabled":"false","Fu
ll Name":""}, {"Name":"bin","Caption":"","Description":"bin","Domain":"","Disabled":
true,"Full Name":""}, {"Name":"daemon","Caption":"","Description":"daemon","Domain":
"", "Disabled":"true","Full Name":""}, {"Name":"adm","Caption":"","Description":"adm",
"Domain":"","Disabled":"true","Full Name":""}, {"Name":"lp","Caption":"","Description
":"lp","Domain":"","Disabled":"true","Full Name":""}, {"Name":"sync","Caption":"","De
scription":"sync","Domain":"","Disabled":"true","Full Name":""}, {"Name":"shutdown",
"Caption":"","Description":"shutdown","Domain":"","Disabled":"true","Full Name":""}, {"
Name":"halt","Caption":"","Description":"halt","Domain":"","Disabled":"true","Full
Name":""}, {"Name":"mail","Caption":"","Description":"mail","Domain":"","Disabled":"t
rue","Full Name":""}, {"Name":"uucp","Caption":"","Description":"uucp","Domain":"","D
isabled":"true","Full Name":""}, {"Name":"operator","Caption":"","Description":"opera
tor","Domain":"","Disabled":"true","Full Name":""}, {"Name":"games","Caption":"","Des
cription":"games","Domain":"","Disabled":"true","Full Name":""}, {"Name":"gopher","Ca
ption":"","Description":"gopher","Domain":"","Disabled":"true","Full Name":""}, {"Nam
e":"ftp","Caption":"","Description":"FTP User","Domain":"","Disabled":"true","Full N
ame":""}, {"Name":"nobody","Caption":"","Description":"Nobody","Domain":"","Disabled
":"true","Full Name":""}, {"Name":"dbus","Caption":"","Description":"System message bu
s","Domain":"","Disabled":"true","Full Name":""}, {"Name":"usbmuxd","Caption":"","Des
cription":"usbmuxd user","Domain":"","Disabled":"true","Full Name":""}, {"Name":"avah
i-autoipd","Caption":"","Description":"Avahi IPv4LL Stack","Domain":"","Disabled":"t
rue","Full Name":""}, {"Name":"vcsa","Caption":"","Description":"virtual console memo
ry owner","Domain":"","Disabled":"true","Full Name":""}, {"Name":"rpc","Caption":"","
Description":"Rpcbind Daemon","Domain":"","Disabled":"true","Full Name":""}, {"Name":
"rtkit","Caption":"","Description":"RealtimeKit","Domain":"","Disabled":"true","Full
Name":""}, {"Name":"abrt","Caption":"","Description":"","Domain":"","Disabled":"true
","Full Name":""}, {"Name":"nscd","Caption":"","Description":"NSCD Daemon","Domain":
"", "Disabled":"true","Full Name":""}, {"Name":"haldaemon","Caption":"","Description":
"HAL daemon","Domain":"","Disabled":"true","Full Name":""}, {"Name":"apache","Caption
":"","Description":"Apache","Domain":"","Disabled":"true","Full Name":""}, {"Name":"ns
lcd","Caption":"","Description":"LDAP Client User","Domain":"","Disabled":"true","Fu
ll Name":""}, {"Name":"saslauth","Caption":"","Description":"\Saslauthd user","", "Dom
ain":"","Disabled":"true","Full Name":""}, {"Name":"postfix","Caption":"","Descriptio
n":"","Domain":"","Disabled":"true","Full Name":""}, {"Name":"avahi","Caption":"","De
scription":"Avahi mDNS/DNS-SD Stack","Domain":"","Disabled":"true","Full Name":""},
```

Figure 3-18

---

### 3.4.7 smart plug-in (smart\_plugin)

This plug-in is used to monitor the total number and health information of hard drives. Two actions are included: smart\_check\_cache, and storage\_health\_cache.

```
define plugin {
    plugin_name      smart_plugin
    class_name       com.supermicro.ssm.agent.plugin.smarthd.SMARTHDPlugin
    description      SMART HD Plugin
    active           1
    version          1.0.0
}
```

To use this plug-in, the hard drives to be monitored must support SMART.

#### 3.4.7.1 smart\_check\_cache Action

This action is used to actively collect hard drive health information and save the information to a cache file every 3600 seconds (1 hour).

```
define action {
    action_name      smart_check_cache
    plugin_name      smart_plugin
    description      S.M.A.R.T. HDD Check(s) Cache
    version          1.0.0
    check_interval   3600
}
```

Options:

None.

Usage:

The action is designed to automatically run periodically for maintaining a hard drive cache to increase the performance of the hard drive monitoring function.

---

### 3.4.7.2 *storage\_health\_cache* Action

This action queries hard drive health information from the hard drive cache maintained by the `smart_check_cache` action. Regardless of the total number of installed hard drives on the monitored host, running this action usually takes a few seconds.

```
define action {
    action_name      storage_health_cache
    plugin_name      smart_plugin
    description      Storage Action
    args             -q $ARG1$ -s $ARG2$ -cache 1
}
```

Options:

ARG1: Expected numbers of hard drives (-1: Disable the check).

ARG2: Check the hard drive status with SMART (0: Disable the check).

Usage:

`jcheck_nrpe -H <host address> -dk -c storage_health_cache -a <ARG1>!<ARG2>`

Example:

Use `jcheck_nrpe` to get the health information of hard drives from the hard drive cache on host 192.168.12.104.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.14.104 -dk -c storage_health_cache -a \!1\!1 -dk
Intel Corporation Patsburg 6 Port SATA AHCI Controller
-- 1 physical disk(s)
-- /dev/sda (VNP210B2GHRK3B) is SMART check OK
```

Figure 3-19

---

### 3.4.8 bios log plug-in (bios\_log\_plugin)

This plug-in is used to get BIOS event logs. The bios\_log\_num action retrieves BIOS event logs every 5 minutes. The definition of this plug-in is shown below.

```
define plugin {
    plugin_name      bios_log_plugin
    class_name       com.supermicro.ssm.agent.plugin.bioslog.BiosLogPlugin
    description      BIOS Log Check Plugin
    active           1
    version          1.0.0
}
```



**Note:** This plug-in applies to hosts running Linux operating systems only.

---

#### 3.4.8.1 bios\_log\_num Action

This action is used to read BIOS event logs every 300 seconds (5 minutes).

```
define action {
    action_name      bios_log_num
    plugin_name      bios_log_plugin
    description      BIOS Log Check(s)
    args             -t $ARG1$ -d $ARG2$
    version          1.0.0
    check_interval   300
}
```

Options:

None.

Usage:

The action is designed to run automatically and periodically for retrieving BIOS event logs.



---

## 3.4.9 memory plug-in (memory\_health\_plugin)

This plug-in is used to monitor memory health information by counting CECC and UECC error events. It can also monitor the total number of DIMMs installed on the host under monitoring. One action is included: memory\_health for getting memory health information. The definition of this plug-in is shown below.

```
define plugin {
    plugin_name      memory_health_plugin
    class_name
    com.supermicro.ssm.agent.plugin.memory.PhysicalMemPlugin
    description      Memory Check Plugin
    version          1.0.0
}
```



**Note:** This plug-in applies to hosts running Linux operating systems only.

---

### 3.4.9.1 memory\_health Action

This action is used to monitor memory health information.

```
define action {
    action_name      memory_health
    plugin_name      memory_health_plugin
    description      CECC/UECC Checks for Physical Memory
    args             -nm $ARG1$ -c $ARG2$
    version          1.0.0
}
```

Options:

ARG1: Expected number of DIMMs (-1: Disable the check).

ARG2: The threshold for CECC and UECC.

---

The argument format is as follows:

[type][duration][fail count],....

- [type]:
  - m: Correctable single bit ECC errors.
  - M: Uncorrectable ECC errors.
- [duration]:
  - d: day
  - h: hour
  - m: minute
  - s: second

[fail count]: The acceptable number of failures. To trigger a critical status, the failure counts must be greater than this value.

To specify a threshold for memory that indicates four single bit ECC errors per 1GB RAM within one day (24 hours) are allowed (i.e., m1d4) and 0 uncorrectable ECC errors are allowed within 1 hour (i.e., M1h0):

m1d4,M1h0

Usage:

jcheck\_nrpe -H <host address> -dk -c memory\_health -a <ARG1>!  
<ARG2>

Example:

Use jcheck\_nrpe to get the health information of DIMMs on host 10.134.12.18.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.12.18 -dk -c memory_health  
-a 2\!m1d1,M1d0 -dk  
Memory is OK; 2 DIMM(s), 8.0 GB RAM; CECC OK, threshold: 1 time(s) in 1 day; UECC OK  
, threshold: 0 time(s) in 1 day.
```

Figure 3-20

---

### 3.4.10 storage plug-in (storage\_health\_plugin)

The plug-in is used to monitor the total number of hard disks, the SMART status of hard disks and the health status of RAID controllers. One action is included: storage\_health\_allinone.

```
define plugin {
    plugin_name      storage_health_plugin
    class_name       com.supermicro.ssm.agent.plugin.storage.StoragePlugin
    description      Storage Health Allinone Plugin
    active           1
    version          1.0.0
    enabled          1
}
```

To use this plug-in, the hard drives to be monitored must support SMART. Currently, the RAID health check is available on LSI MegaRAID 2108, 2208 and 3108 controllers.

#### 3.4.10.1 storage\_health\_allinone Action

This action is used to query storage health information including SMART status of hard disks and health status of RAID controllers. The SMART health information is from the hard drive cache maintained by the smart\_check\_cache action. The RAID health information is from the RAID controller cache maintained by the raid\_health action. Regardless of the total number of installed hard drives and RAID controllers on the monitored host, running this action usually takes a few seconds.

```
define action {
    action_name      storage_health_allinone
    plugin_name      storage_health_plugin
    description      Storage Allinone Action
    args            -q $ARG1$ -s $ARG2$ -r $ARG3$
}
```

Options:

ARG1: Expected numbers of hard drives (-1: Disable the check).

ARG2: Check the hard drive status with SMART (0: Disable the check).

ARG3: Check RAID health (0: Disable the check).

---

Usage:

`jcheck_nrpe -H <host address> -dk -c storage_health_allinone -a <ARG1>!<ARG2>!<ARG3>`

Example:

Use `jcheck_nrpe` to get the storage health information on host 10.134.14.104.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.14.104 -dk -c storage_health_allinone -a 4\!1\!1 -dk
Physical disk number is incorrect on the system, expect: 4, actual: 3

Intel Corporation Patsburg 6 Port SATA AHCI Controller
-- 1 physical disk(s)
-- /dev/sda (VNP210B2GHRK3B) is SMART check OK

Supermicro SMC2108 Controller
-- 2 physical disk(s)
-- The status of RAID is normal.
```

Figure 3-21

### 3.4.11 LSI RAID plug-in (`lsiraid_plugin`)

This plug-in is used to monitor the health of RAID controllers. Two actions are included: `raid_health` and `lsiraid_check_cache`.

```
define plugin {
    plugin_name      lsiraid_plugin
    class_name       com.supermicro.ssm.agent.plugin.raid.LSIRaidPlugin
    description      LSI RAID Plugin
    active           1
    version          1.0.0
    enabled          1
}
```

---

### 3.4.11.1 *raid\_health* Action

This action is used to query RAID health information using cache data maintained by `lsiraid_check_cache` action. Regardless of the total number of installed RAID controllers and hard drives combined to RAID on the monitored host, running this action usually takes a few seconds.

```
define action {
    action_name      raid_health
    plugin_name      lsiraid_plugin
    description      Raid Action
    args             -cache 1
    varson           1.0.0
}
```

Options:

None.

Usage:

```
jcheck_nrpe -H <host address> -dk -c raid_health -a cache 1
```

Example:

Use `jcheck_nrpe` to get the health information of RAID controllers on host 10.134.14.104.

```
[root@localhost jcheck_nrpe]# ./jcheck_nrpe.sh -H 10.134.14.104 -dk -c raid_health -a cache 1 -dk
Supermicro SMC2108 Controller
-- 2 physical disk(s)
-- The status of RAID is normal.
```

Figure 3-22

---

### 3.4.11.2 *lsiraid\_check\_cache* Action

This action is used to actively collect the health information of RAID controllers and save the information to a cache file every 180 seconds (or 3 minutes).

```
define action {
    action_name      lsiraid_check_cache
    plugin_name      lsiraid_plugin
    description      LSI RAID Check(s) Cache
    version          1.0.0
    check_interval   180
    enabled          1
}
```

Options:  
None.

Usage:

The action is designed to automatically run periodically for maintaining a RAID cache to increase the performance of the RAID monitoring function.

### 3.4.12 notification plug-in (*notification\_plugin*)

This notification plug-in is used to monitor its configuration file, **polling.properties**, located in the **[install folder]\config** folder. The notification behavior of SuperDoctor 5 depends on the **polling.properties** file of polling setting, and notification methods. Once the file is changed, the notification behavior will be changed. See [4.5.1 Alert Configuration](#) for more information. The definition of this plug-in is shown below.

```
define plugin {
    plugin_name      notification_plugin
    class_name
    com.supermicro.ssm.agent.plugin.notification.NotificationPlugin
    description      Notification plugin
    active           1
    version          1.0.0
    enabled          1
}
```

---

### 3.4.12.1 *change\_alerts action*

This action is used to notify the changes of polling.properties. SuperDoctor 5 then will send notifications by the definition the polling.properties.

```
define action {
    action_name      change_alerts
    plugin_name      notification_plugin
    args             -send
    description      Alert Configuration Changes
}
```

Options:

None.

Usage:

jcheck\_nrpe -H <host address> -dk -c change\_alerts

### 3.4.12.2 *start\_filewatcher action*

This action is used to start a file watcher to monitor polling.properties every second.

```
define action {
    action_name      start_filewatcher
    plugin_name      notification_plugin
    args             -start
    description      Start File Watcher
    check_interval   1
}
```

Options:

None.

Usage:

jcheck\_nrpe -H <host address> -dk -c start\_filewatcher

---

### 3.4.12.3 *stop\_filewatcher* action

This action is used to stop the file watcher to monitor **polling.properties**.

```
define action {  
    action_name      stop_filewatcher  
    plugin_name      notification_plugin  
    args             -stop  
    description      Stop File Watcher  
}
```

Options:

None.

Usage:

jcheck\_nrpe -H <host address> -dk -c stop\_filewatcher



---

## 4 SD5 Web

---

SuperDoctor 5 includes a built-in plug-in called SD5 Web, which provides a Web-based console for SuperDoctor 5. The SD5 Web allows users to view health information and system information as well as to set configuration data via Web browsers.

### 4.1 SD5 Web Login

Type the following URL in your browser to connect to the SD5 Web:

**http://[SuperDoctor 5 address]:8181/SuperDoctor5**

The login page is shown below. The default user name and password are **ADMIN** and **ADMIN**.



The screenshot shows a web browser window displaying the SD5 Web login page. In the top right corner, there is a language selection dropdown menu labeled 'Select Language : English'. The main content area contains a login form with two text input fields. The first field is labeled 'User Name:' and the second is labeled 'Password:'. A 'Login' button is located at the bottom right of the form.

Figure 4-1

## 4.2 Health Information

SD5 Web graphically displays the status of the monitored devices, including fan speed, voltage, temperature, chassis intrusion, power failure, hard disk drives, and memory. An item in green indicates a healthy state while a red one denotes a critical state. Notifications can be sent when a monitored item reaches critical status. You can configure the notification behavior on the Configuration page. See [4.5 SD5 Web Configuration](#) for more information.




Figure 4-2




Figure 4-3



**Note:** The default argument for CECC and UECC is 1 time in one day per 1GB and 0 times in one day, respectively.

The SMART health monitoring function supports non-RAID internal hard drives, and does not support USB hard drives or flash drives. **To use this function, first install the smartctl utility program.** For Windows users, when you install smartmontools including smartctl online, click **Install Smartmontools** (see the figure below).




Figure 4-4

A GPL (GNU General Public License) 2.0 license agreement dialog box shows up. Read the agreement carefully before installing smartmontools. If you accept the terms of the agreement, click **I Agree** to continue installation.




Figure 4-5

To manually install the smartmontools package, follow these steps:

1. Download the smartmontools package from <ftp://ftp.supermicro.com/GPL/smartmontools/windows/smartctl.zip>.
2. Extract the zip file and copy all(\*.\*) files into the [install folder]/libs/native.
3. In text console, execute the "sdc -rd" command to detect the hardware configuration again.

The health information page also shows power supply information if supported power supplies are connected to the motherboard via I<sup>2</sup>C. Depending on their design, power supplies might have Field Replaceable Unit (FRU) Data and/or PMBus functions. Supported power supplies with PMBus functions are able to provide real time input current and power consumption information. The following figure shows the health information of a set of redundant power supplies with PMBus displaying the input current and the input wattage. **Note that power supply information may not be available on particular models of motherboards even if power supplies are connected to the motherboards.**




Figure 4-6

The following figure shows the health information of a battery backup power (BBP<sup>®</sup>). Different colors are used to indicate the battery state. Green color means the battery is healthy, and red color means the battery is dead. If the current reading of the battery is negative, the color turns yellow to warn that the battery is discharged. In addition, the energy reading tells the percentage of the charge status of the battery.




Figure 4-7

The health information of the LSI MegaRAID RAID controller is also supported on the page. The health of a RAID controller is a combined status that depends on the states of its components such as battery backup unit (BBU), virtual drives, and hard disks. If all components belonging to the adapter are OK, the status of the adapter shows OK. Otherwise, it could be Warning or Critical depending on the states of the components. Valid states for BBU, virtual drives and hard disks are:

- BBU This shows the current status of a BBU. Valid values are OK (Optimal), Critical (BBU status is missing or degraded) and Unknown (incomplete command output).
- Virtual drive This shows the current status of a virtual drive. Valid values are OK (Optimal), Warning (Partially Degraded or Degraded) and Critical (Offline).
- Hard disk This shows some attributes of a hard disk such as port status and firmware state. Valid values are OK (port status is active, and the firmware state is equal to online or hotspare or unconfigured good or jbod), Warning (port status is active, and the firmware state is equal to rebuild or copyback ) and Critical (port status is inactive or unknown or the firmware state is offline or missing or failed or unconfigured bad).




Figure 4-8



**Note:** Only LSI MegaRAID 2108, 2208 and 3108 RAID controllers are supported currently on both Windows and Linux platforms. Other LSI MegaRAID RAID controllers (i.e. LSI MegaRAID 2008 and 2308 RAID controllers) are not fully tested and Non-LSI MegaRAID

---

---


RAID controllers (i.e. LSI Fusion-MPT based and Intel Rapid Storage Technology) are not supported in this version.

---

---

## 4.3 System Information

The system information provided by the SD5 Web is similar to that provided by the SSM Web.



The screenshot displays the 'System Info' tab of the SD5 Web interface. On the left, a tree view shows categories like Hardware and Software. The 'BIOS' item under Hardware is selected. The main content area shows a table of BIOS information:

BIOS	
Manufacturer:	American Megatrends Inc.
Version:	3.0a
Release Date:	12/5/13
SMBIOS Major Version:	2
SMBIOS Minor Version:	7
SMBIOS Present:	TRUE

Figure 4-9



### Notes:

1. The system information contents are platform dependent. Particular information available on a Windows host may not be presented on a Linux host, and vice versa. Also, Linux does not support all types of system information objects in the same way that Windows supports them. Types including Desktop Monitor, Floppy, Keyboard, Port Connector, Parallel Port, Pointing Device, Serial Port, Computer Summary, Startup Command, and Video Controller are supported on Windows platforms only.
2. The Current Clock Speed (MHz) in the Processor category is read from the DMI table. It may not reflect the real time data when you check the current clock speed under operating systems.

---

## 4.4 Reports

SuperDoctor 5 provides three CSV (Comma Separated Values) format reports. These reports can be downloaded and viewed with CSV supported tools like Microsoft Excel.

- System Information Report: This report contains information shown in the System Info function. See [4.3 System Information](#) for more information.
- Health Information Log Report: This report includes the historical data of monitored item readings. Readings of selected (i.e. enabled) monitored items will be written to a file only if the **Polling Interval** value is set and the Log option is enabled in the **Alert Configuration** function. See [4.5.1 Alert Configuration](#) and [4.5.2 Monitored Item](#) for more information.
- Event Log Report: This report contains events that represent problems and recoveries with monitored items. When the status of a monitored item is changed, an event log is written to the Event Log Report. Note that to write events to the log file, the **Polling Interval** on the Configuration page must be set.




Figure 4-10



---

## 4.5 SD5 Web Configuration

This page includes four submenus: **Alert Configuration**, **Monitored Item**, **Password Setting** and **Flash BIOS**.

### 4.5.1 Alert Configuration

On this page you can configure the SD5 Web notification methods. Five methods are supported: **Log**, **Email**, **SNMP Trap**, **System Tray** and **OS Event Log**. The meanings of each argument are illustrated below:

- **Enabled Pooling:** SuperDoctor 5 periodically checks the health status of monitored items if pooling is enabled. No alert is sent if pooling is disabled.
- **Polling Interval:** Determines how frequently in seconds the SD5 Web should check the health status of monitored items. The minimum value is 3 seconds.
- **Log:** Keeps alerts in a log file named “log.txt[yyyy-mm-dd-sequence]” located in the **[install folder]** folder. The file is split into two files once its size becomes greater than 10 MB. The total number of log files to be kept can be configured by setting the “backup files to keep around” argument.
- **E-mail Alert:** Sends alerts via e-mail. To use this function, you need to set recipients, an e-mail server address and a port number as well as a sender’s e-mail address. Check SSL or TLS if the e-mail server uses secure connections. If the e-mail server requires authentication, you will need to set up an account and password to log in to the e-mail server. Multiple recipients must be separated by a comma.
- **SNMP Trap:** Sends alerts with SNMP traps. Multiple recipients are separated by a comma.
- **System Tray Popup Alert:** Sends alerts to local desktop. Note that the function is only available on Windows platform. For more information on using the **SD5 Tray** program to receive alerts, please refer to [7 SD5 Tray](#).
- **OS Event Log:** Writes alerts to Windows Logs for Windows platforms and system logs for Linux platforms.

Figure 4-11



**Note:** On Linux platforms, you may need to add the host name and the IP address to the `/etc/hosts` file if SNMP traps cannot be sent.

The E-mail message format is defined by the following attributes:

- Mail title:
  - Item 1: the type of an alert ("Problem ", "Recovery ")
  - Item 2: the name of the monitored item
  - Item 3: the status of the monitored item ("OK", "Warning", "Critical" , or "Unknown")
  - Item 4: the time of an alert in date time format
  - Item 5: the host name and host address which sent out an alert
- Mail body:
  - Item 6: the output message about the status of the monitored item

For example, the subject line of an e-mail alert shows "Problem: RAID Adapter 0(Supermicro SMC2108) - Virtual Drive 0 is WARNING at 2012/3/12 13:50:13 from softlab1(192.168.12.30)" and the mail body of an e-mail alert shows "RAID Adapter 0(Supermicro SMC2108) - Virtual Drive 0(RAID5, 500GB) is Degraded".



**Notes:**

1. A problem alert will be sent while the status of the monitored item is non-OK (i.e., WARNING, UNKNOWN or CRITICAL) from the initial or is from an OK state to a non-OK state or is from a non-OK state to another non-OK state.
2. A recovery alert will be sent while the status of the monitored item is from a non-OK state to an OK state.

The SNMP Trap description is defined by the following attributes:

- Item 1: the type of an alert ("Problem", "Recovery")
- Item 2: the name of the monitored item
- Item 3: the status of the monitored item ("OK", "Warning", "Critical", or "Unknown")
- Item 4: the time of an alert in date time format
- Item 5: the output message about the status of the monitored item

For example, the description of an SNMP trap shows "Problem: RAID Adapter 0(Supermicro SMC2108) - Virtual Drive 0 is WARNING at 2012/3/12 13:50:13. Virtual Drive 0(RAID5, 500GB) is Degraded".

## 4.5.2 Monitored Items

On this page, you can decide if an item should be monitored or not. You can also change both the high and low limits of an item. All possible monitored items are listed. When SuperDoctor 5 is first started, it detects unplugged monitored items and disables them automatically. Thus, the first time you see this page, some items may be already disabled.

Monitored Item						Save	Set to factory default limits	Reselect
<input type="checkbox"/>	Monitored Item	High Limit	Low Limit	Reading	Status			
<b>- Fan</b>								
<input type="checkbox"/>	FAN1		600 RPM	NA	NA			
<input type="checkbox"/>	FAN2		600 RPM	NA	NA			
<input type="checkbox"/>	FAN3		600 RPM	NA	NA			
<input checked="" type="checkbox"/>	FAN4		600 RPM	1700.0 RPM	OK			
<input type="checkbox"/>	FANA		600 RPM	NA	NA			
<b>- Voltage</b>								
<input checked="" type="checkbox"/>	Vcpu	2.088 V	1.26 V	1.693 V	OK			
<input checked="" type="checkbox"/>	VDIMM	1.719 V	1.124 V	1.453 V	OK			
<input checked="" type="checkbox"/>	12V	13.224 V	10.521 V	11.847 V	OK			
<input checked="" type="checkbox"/>	5VCC	5.527 V	4.38 V	4.969 V	OK			
<input checked="" type="checkbox"/>	3.3VCC	3.659 V	2.894 V	3.344 V	OK			
<input checked="" type="checkbox"/>	VBAT	3.6 V	2.49 V	3 V	OK			
<input checked="" type="checkbox"/>	AVCC	3.599 V	2.489 V	3.329 V	OK			
<input checked="" type="checkbox"/>	VSB	3.599 V	2.489 V	3.299 V	OK			
<b>- Temperature</b>								
<input type="checkbox"/>	CPU Temp	100°C / 212°F		NA	NA			
<input checked="" type="checkbox"/>	System Temp	85°C / 185°F		26.0 °C / 78.8 °F	OK			
<input checked="" type="checkbox"/>	Peripheral Temp	85°C / 185°F		44.0 °C / 111.2 °F	OK			
<input type="checkbox"/>	PCH Temp	95°C / 203°F		NA	NA			
<input checked="" type="checkbox"/>	VRM Temp	92°C / 197°F		28.0 °C / 82.4 °F	OK			
<input checked="" type="checkbox"/>	DIMMA1 Temp	85°C / 185°F		26.0 °C / 78.8 °F	OK			
<input checked="" type="checkbox"/>	DIMMA2 Temp	85°C / 185°F		26.0 °C / 78.8 °F	OK			
<input checked="" type="checkbox"/>	DIMMB1 Temp	85°C / 185°F		26.0 °C / 78.8 °F	OK			
<input checked="" type="checkbox"/>	DIMMB2 Temp	85°C / 185°F		26.0 °C / 78.8 °F	OK			
<b>- Status</b>								
<input checked="" type="checkbox"/>	Chassis Intru				OK			
<b>- Hard Disk</b>								
<input checked="" type="checkbox"/>	Nvidia (50026B72410F3D49)				OK			
<b>- Memory</b>								
<input checked="" type="checkbox"/>	Memory				OK			
<b>- Power Supply</b>								
<input checked="" type="checkbox"/>	Power Supply 1				OK			

Figure 4-12

You can change the high and low limits of an item, or you can deselect an item if you no longer wish to monitor it. Click the **Save** button to apply changes immediately. A row with high/low limits in invalid format will be highlighted (see the figure below). To view the detailed error message, move the mouse over the warning icon.

Monitored Item					
Save Set to factory default limits Redetect					
<input type="checkbox"/>	Monitored Item	High Limit	Low Limit	Reading	Status
<b>- Fan</b>					
<input type="checkbox"/>	Fan1		675 RPM	NA	NA
<input checked="" type="checkbox"/>	Fan2		675 RPM	1755.0 RPM	OK
<input type="checkbox"/>	Fan3		675 RPM	NA	NA
<input checked="" type="checkbox"/>	Fan4		0 RPM	7020.0 RPM	OK
<input type="checkbox"/>	Fan5		675 RPM	NA	NA
<input type="checkbox"/>	Fan6		675 RPM	NA	NA
<input type="checkbox"/>	Fan7		675 RPM	NA	NA
<input type="checkbox"/>	Fan8		675 RPM	NA	NA
<b>- Voltage</b>					
<input checked="" type="checkbox"/>	CPU1 Vcore	1.384 V	0.824 V	0.92 V	OK
<input type="checkbox"/>	CPU2 Vcore	1.384 V	0.824 V	NA	NA
<input checked="" type="checkbox"/>	CPU1 VTT	1.352 V	+1.5 V	1.16 V	OK
<input type="checkbox"/>	CPU2 VTT	1.352 V			NA
<input checked="" type="checkbox"/>	DIMM1	1.656 V	1.336 V	1.528 V	OK
<input type="checkbox"/>	DIMM2	1.656 V	1.336 V	NA	NA

Figure 4-13

To restore the default threshold values, click the **Set to factory default limits** button.

Sometimes your hardware configuration may change, such as when a new power supply is used or new fans are plugged in. In such cases, you can click the **Redetect** button to detect the monitored items again (see the figure below).

Monitored Item					
Save Set to factory default limits Redetect					
<input type="checkbox"/>	Monitored Item	High Limit	Low Limit	Reading	Status
<b>- Fan</b>					
<input checked="" type="checkbox"/>	Fan1		675 RPM	4320.0 RPM	OK
<input checked="" type="checkbox"/>	Fan2		675 RPM	2430.0 RPM	OK
<input checked="" type="checkbox"/>	Fan3		675 RPM	NA	Critical
<input type="checkbox"/>	Fan4		675 RPM	NA	NA
<input type="checkbox"/>	Fan5		675 RPM	NA	NA
<input type="checkbox"/>				NA	NA
<input type="checkbox"/>				NA	NA
<input type="checkbox"/>				NA	NA
<b>- Voltage</b>					
<input type="checkbox"/>				0.896 V	NA
<input type="checkbox"/>				NA	NA
<input checked="" type="checkbox"/>	CPU1 VTT	1.352 V	0.824 V	1.176 V	OK
<input type="checkbox"/>	CPU2 VTT	1.352 V	0.824 V	NA	NA
<input checked="" type="checkbox"/>	DIMM1	1.656 V	1.336 V	1.528 V	OK
<input type="checkbox"/>	DIMM2	1.656 V	1.336 V	NA	NA
<input checked="" type="checkbox"/>	+1.5V	1.656 V	1.336 V	1.464 V	OK

**Redetect Monitored Items**

Please wait while monitored items are being detected.

Loading...

OK

Figure 4-14

SuperDoctor 5 will be restarted after the detection process is complete and you have to log in SuperDoctor 5 again. Click the **OK** button to go to the SD5 login web page.

Monitored Item					
<input type="button" value="Save"/> <input type="button" value="Set to factory default limits"/> <input type="button" value="Redetect"/>					
<input type="checkbox"/>	Monitored Item	High Limit	Low Limit	Reading	Status
<b>- Fan</b>					
<input checked="" type="checkbox"/>	Fan1		675 RPM	4320.0 RPM	OK
<input checked="" type="checkbox"/>	Fan2		675 RPM	2430.0 RPM	OK
<input checked="" type="checkbox"/>	Fan3		675 RPM	NA	Critical
<input type="checkbox"/>	Fan4		675 RPM	NA	NA
<input type="checkbox"/>	Fan5		675 RPM	NA	NA
<input type="checkbox"/>				NA	NA
<input type="checkbox"/>				NA	NA
<input type="checkbox"/>				NA	NA
<b>- Voltage</b>					
<input type="checkbox"/>				0.896 V	NA
<input type="checkbox"/>				NA	NA
<input checked="" type="checkbox"/>	CPU1 VTT	1.352 V	0.824 V	1.176 V	OK
<input type="checkbox"/>	CPU2 VTT	1.352 V	0.824 V	NA	NA
<input checked="" type="checkbox"/>	DIMM1	1.656 V	1.336 V	1.528 V	OK

**Redetect Monitored Items**

Monitored items have been detected. Please click the OK button to log in.

Figure 4-15

### 4.5.3 Account Setting

You can change the account and the password for the built-in account on this page. Note that the function of creating new accounts is not supported.

**Account Setting**

User\*

Current Password\*

New Password\*

Confirm New Password\*

Figure 4-16

## 4.5.4 Flashing BIOS

On this page you can upload BIOS binary files and flash the BIOS to a system that has SuperDoctor 5 installed. Note that this function supports Supermicro motherboards newer than H8, X8, and X9 series on Windows platforms and motherboards newer than X9 series on Linux platforms.

The following table lists the BIOS flashing supported by SD5:

Platform \ MB Series	H8	X8	X9	X10
Windows	✓	✓	✓	✓
Linux	✗	✗	✓	✓



**Note:** A jumper-less solution is provided for X10 Grantley platforms. For details, see later in this section. Also, it's recommended that you check the original settings of the boot order in the BIOS Setup. Flashing the BIOS can cause the system reboot from a boot device which is not previously set.

A screenshot of the 'Flash BIOS' web interface. The interface is divided into several sections: 'Current BIOS information' with fields for Manufacturer (American Megatrends Inc.), Version (1.1), Release Date (2/5/15), SMBIOS Major Version (2), SMBIOS Minor Version (8), SMBIOS Present (TRUE), ROM Size (KB) (8192), and UEFI Supported (TRUE); 'BIOS flash history' showing two successful flash events; 'Upload BIOS' with a 'Browse...' button for the BIOS binary file; 'Available BIOS' listing three files: BIOS\_20150505-002608.BAK, BIOS\_20150505-203456.BAK, and x10dr15.414; and a 'Flash' button. A red 'WARNING!' message is displayed, stating: '(1) If you flash the wrong BIOS, the computer will not start boot at the next startup. Please choose the correct BIOS to flash. (2) Motherboard ME type will require the user to manually disable ME or enable update ME or enable ME FW Image RE-flash via BIOS setup menu.'

Figure 4-17

The Flash BIOS page includes four fields:

- 
- Current BIOS information: A table displays the current BIOS information, such as version, release date and ROM size.
  - BIOS flash history: The BIOS flashing activities via Super Doctor 5 is logged in the list. The flashing is logged whether it is successful or not. If you have never used SD5 to flash the BIOS before, the history field is empty.
  - Upload BIOS: A user can choose and upload the desired ROM BIOS binary file. If you have never uploaded BIOS binary files in SD5 before, the **Available BIOS** field is empty.
  - Available BIOS block: A list contains BIOS binary files backed up or uploaded in SD5. Note that to prevent the BIOS from being corrupted, you are required to disable ME (Intel Management Engine) before updating the BIOS. Find **disable ME** or **enable update ME** or **enable ME FW Image RE-flash** in the BIOS setup menu.

Select a BIOS to start flashing. A warning message shows up to remind you of not removing the AC power or turning off the computer until the BIOS is completely flashed (see the figure below).




Figure 4-18

Later another warning message shows up to remind you of rebooting the system for the changes to take effect (see the figure below).




Figure 4-19

The original BIOS will be backed up in the **[install folder]\BIOS\rom** folder if the BIOS is flashed successfully.

---

## Jumper-less Solution for X10 Grantley Platforms

Before X10 Grantley, users manually set onboard jumper (JPME2) to enable the ME manufacturing mode. This was required upon all software-strap settings being updated in the Flash Descriptor Table (FDT) inside the ME region. When flashing BIOS on multiple systems with different FDTs, such a way of flashing BIOS was not doable. Supermicro then introduced a jumper-less solution on X10 Grantley platforms to flash BLOS.


When the FDT is different, a system installed with SuperDoctor 5 needs to reboot to enter the ME manufacturing mode to update BIOS. The number of systems rebooting depends on if the Flash Descriptor Table (FDT) is identical between the current system BIOS and the updating image file.



**Note:** In order to continue updating BIOS after reboot, make sure the OS in use is the same as the one on which the multi-boot function is set.

---

- When the FDT is the same, SuperDoctor 5 will start flashing BIOS and remind you to reboot the system for the changes to take effect (see the figure below).




```
Execution Result
>>>> Flash new BIOS >>>>>
Supermicro Update Manager (for UEFI BIOS) 1.5.0 (2015/06/26) (x86_64)
Copyright©2015 Super Micro Computer, Inc. All rights reserved
Reading BIOS flash ..... (100%)
Checking BIOS ID ...
Checking ME Firmware ...
Comparing FDT for ROM file and flash.... (98%)
FDT is same, Update BIOS and ME(exclude FDT) regions....
Reading BIOS flash ..... (100%)
Checking BIOS ID ...
Checking BIOS ID ...
Writing BIOS flash ..... (100%)
Verifying BIOS flash ..... (100%)
Checking ME Firmware ...
Putting ME data to BIOS ..... (98%)
Writing ME region in BIOS flash ...
- FDT won't be updated when ME is not in Manufacturing mode!!
  BIOS upgrade continues...
- Updated Recovery Loader to OPRx
- Updated FPT, MFSB, FTFR and MFS
- ME Entire Image done
WARNING:Must power cycle the system for the changes to take effect!

Note: The BIOS has been flashed successfully at 2015/07/23 02:56:48. Please reboot the c
No error.
```

Figure 4-20



- When the FDT is different, SuperDoctor 5 will continue updating BIOS after the first reboot (see the figure below).



```
Execution Result
with file name sum_jumperless_update_YYYYMMDDhhmmss.log
The timestamp is the time when SUM starts updating BIOS
If the below message is shown in the log:
"Must power cycle the system for the changes to take effect!"
,the BIOS update procedure is SUCCESS
SECOND REBOOT: required IMMEDIATELY after update SUCCESS at FIRST REBOOT.
this will load BIOS back to normal mode

*****
After reboot, System will automatically flash BIOS. Please wait...
>>>> Flash new BIOS >>>>>
Supermicro Update Manager (for UEFI BIOS) 1.5.0 (2015/06/26) (x86_64)
Copyright©2015 Super Micro Computer, Inc. All rights reserved
Reading BIOS flash ..... (100%)
Checking BIOS ID ...
Programming BIOS and ME (including FDT)
Checking BIOS ID ...
Writing BIOS flash ..... (100%)
Verifying BIOS flash ..... (100%)
Checking ME Firmware ...
Putting ME data to BIOS ..... (98%)
Writing ME region in BIOS flash ...
- Update success for /FDT!!
- Updated Recovery Loader to OPRx
- Updated FPT, MFSB, FTPR and MFS
- ME Entire Image done
WARNING:Must power cycle the system for the changes to take effect!
Note: The BIOS has been flashed successfully at 2015/07/23 05:13:04. Please reboot th
Close
```

Figure 4-21

## 4.6 RAID

The RAID tab will be shown while SuperDoctor 5 detects whether the LSI MegaRAID RAID controller is available in the system. The layout of RAID is divided into two parts:

- Tree Area: A tree structure serves as a menu for users to get more information, such as RAID controllers, virtual drives, and hard disks.
- Content Area: shows the detailed information of the selected node in the Tree Area.




Figure 4-22

There are two main (virtual) nodes in one adapter: the **Virtual Drive(s)** node, and the **Drives** node. These two virtual tree nodes are used for classification:

**Virtual Drives** This node comprises all virtual drives. Virtual drives are the volumes that are configured as RAID 0, 1, 5 and 10.

**Drives** This node comprises all hard disks of the adapter.

The RAID controller named **LSI 2208 MegaRAID** contains two virtual drives (RAID 1 and RAID 10), and six hard disks (Slot 0, 1, 2, 4, 5 and 8).




Figure 4-23



**Note:** The RAID tree will not automatically refresh periodically. It requires the user to refresh it manually by clicking the Refresh icon in the upper right corner of the Tree Area.

Click on **LSI 2208 MegaRAID** tree node. The detailed properties are shown on the right panel.




Figure 4-24

Click the **Virtual Drive 0, RAID 1, 464.729 GB** tree node on the left panel. The detailed properties of a virtual drive are shown on the right panel.

Virtual Drive 0, RAID1, 464.729 GB	
<b>Properties</b>	
Virtual Drive ID	0
Target ID	
Name	
RAID Level	RAID1
Size	464.729 GB
State	Optimal
Mirror Data	
Strip Size	64 KB
Number Of Drives	2
Span Depth	1
Default Cache Policy	WriteBack
Current Cache Policy	Read Ahead, Always WriteBack, Cached IO
Default Access Policy	
Current Access Policy	Read Write
Disk Cache Policy	Disk's Default
Encryption Type	None
Default Power Savings Policy	
Current Power Savings Policy	
Can spin up in 1 minute	
LD has drives that support T10 power conditions	
LD's IO profile supports MAX power savings with cached write	
Bad Blocks Exist	
Is VD Cached	

Figure 4-25

Click on the **Slot 4, 465.761 GB** tree node on the left panel, and you can view the detailed properties of a hard disk.

Slot 4, 465.761 GB	
<b>Properties</b>	
Slot Number	4
Raw Size	465.761 GB
Firmware state	Online
Device Firmware Level	KC44
Inquiry Data	W2A3Z7W1 ST500DM002-1BD142 KC44
Device Speed	6.0Gb/s
Link Speed	6.0Gb/s
Media Type	HDD
Drive's write cache	N/A
Drive's NCQ setting	Enabled
Port-0's Linkspeed	6.0Gb/s
Port-1's Linkspeed	
Foreign State	
Media Error Count	0
Other Error Count	0
Predictive Failure Count	0
Last Predictive Failure Event Sequence Number	0

Figure 4-26



**Note:** Only LSI MegaRAID 2108, 2208 and 3108 RAID controllers are currently supported on both Windows and Linux platforms. Other LSI MegaRAID RAID controllers (i.e. LSI MegaRAID 2008 and 2308 RAID controllers) are not fully tested and Non-LSI MegaRAID RAID controllers (i.e. LSI Fusion-MPT based and Intel Rapid Storage Technology) are not supported in this version.

---

## 4.7 Power Control

The Power Control allows users remotely turn off the system via **Graceful Power Control** or **Power Control**.




Figure 4-27

- **Graceful Power Control:** SD5 Web allows a user to reboot or shut down the system within 60 seconds. On the system console, a message shows up to remind the user of saving the working files. Before the system is rebooted or shut down, it's allowed to cancel the action either locally or remotely.
- **Power Control:** SD5 Web allows a user to reboot or shut down the system right away. The system will reboot or shut down without any warning messages. Note that the action cannot be cancelled.

To execute a Graceful Power Control, select Reboot, and then click the Submit button. A dialog box shows up for confirmation.




Figure 4-28

Click **OK**. A countdown dialog box shows up, and the rebooting will begin 60 seconds later.




Figure 4-29

To execute a Power Control, select Reboot radio and click the Submit button. A dialog box shows up.




Figure 4-30

Click **OK** to start rebooting.

---

## 5 SNMP Extension

---

SuperDoctor 5 provides a program called SuperDoctor 5 SNMP Extension, which allows users to get health information via Simple Network Management Protocol (SNMP). To use this function, you have to install the operating system's built-in SNMP service in advance. In Windows, the Microsoft Windows implementation of SNMP has to be installed. In Linux, the Net-SNMP package is most commonly used. SuperDoctor 5 SNMP Extension can then be integrated into the operating system's built-in SNMP service to provide Supermicro proprietary management information bases (MIBs).

### 5.1 Setting Up the SNMP Service on Windows

#### 5.1.1 Preparation

Please follow these steps to install the SNMP service:

For Windows 2000/Windows XP/Windows 2003:

1. Open the **Control Panel**.
2. Open **Add/Remove Programs**.
3. Open **Add/Remove Windows Components**.
4. Open **Management and Monitoring Tools in the Components List**.
5. Check **Simple Network Management Protocol**.
6. Click **Next** to begin the installation.

For Windows 2008:

1. Open the **Control Panel**.
2. Click **Programs**.
3. Click **Turn Windows features on or off**.
4. Click **Add Features**.
5. Check **SNMP Services** from the list.
6. Click **Install** to begin the installation.



## 5.1.2 Configuring the SNMP Service

1. Open the **Control Panel**.
2. Click **Administrative Tools**.
3. Click **Services**.
4. Select the **SNMP Service**.




Figure 5-1

5. Double-click the **SNMP Service**, and the **SNMP Service Properties (Local Computer)** dialog box appears.





Figure 5-2

6. Click the **Security** tab
7. In the Accepted community names setting, click the **Add...** button to add a **public** community with READ ONLY rights.
8. Select **Accept SNMP packets from any host**.
9. Click the **OK** button to complete the settings.

## 5.1.3 Verifying the SNMP Service

You can use `sc query snmp` to check the SNMP service in console mode.



```
Administrator: Command Prompt
C:\Users\Administrator>sc query snmp
SERVICE_NAME: snmp
        TYPE               : 10  WIN32_OWN_PROCESS
        STATE                : 4   RUNNING
                        (STOPPABLE, NOT_PAUSABLE, IGNORES_SHUTDOWN)
        WIN32_EXIT_CODE       : 0   (0x0)
        SERVICE_EXIT_CODE   : 0   (0x0)
        CHECKPOINT           : 0x0
        WAIT_HINT            : 0x0
C:\Users\Administrator>
```

Figure 5-3

## 5.2 Setting Up the SNMP Service on Linux

### 5.2.1 Preparation

Please contact your system administrator to install the **NET-SNMP** service on your Linux boxes before using the SuperDoctor 5 SNMP extension.

### 5.2.2 Configuring the SNMP Service

1. Use a text editor to open the `/etc/snmp/snmpd.conf` file.
2. Add the following line into the **Pass through control** section of the file:

```
pass .1.3.6.1.4.1.10876 [install folder]/libs/native/snmpagent
```

3. If you are using Red Hat Enterprise Linux (RHEL) 5.x platforms, use the following command to allow SNMP extensions to access hardware resources:

```
setsebool -P snmpd_disable_trans=1
```

---

For RHEL 6.x users, edit the `/etc/selinux/config` file and replace "**SELINUX=enforcing**" with "**SELINUX=disabled**". Save the `/etc/selinux/config` file and reboot the system.

4. Use the following command to restart the SNMP service:

```
service snmpd restart
```

5. Use an SNMP client to walk through the Supermicro MIB tree (i.e., the **.1.3.6.1.4.1.10876** OID tree). If it fails to get any data from `.1.3.6.1.4.1.10876`, compare the sample `snmpd.conf` file below to your `snmpd.conf` file and check if something is configured wrong.

```
com2sec notConfigUser default public
group notConfigGroup v1 notConfigUser
group notConfigGroup v2c notConfigUser

view allview included .1
access notConfigGroup "" any noauth exact allview none none

syslocation Unknown (edit /etc/snmp/snmpd.conf)
syscontact Root <root@localhost> (configure /etc/snmp/snmp.local.conf)

pass .1.3.6.1.4.1.10876 /opt/Supermicro/SuperDoctor5/libs/native/snmpagent
```

### 5.2.3 Verifying the SNMP Service

For Linux users, use this command to check SNMP service:

```
service snmpd status
```

## 5.3 Supermicro MIB


The Supermicro MIB subtree begins from .1.3.6.1.4.1.10876. Please find a file named **SSM\_MIB.zip** on your SuperDoctor 5 CD to get detailed SNMP MIB/OID information.

The MIB zip file includes 5 files:

- **SUPERMICRO-SMI.my**: The file contains Supermicro MIB information used by SuperDoctor® and SSM.
- **SUPERMICRO-HEALTH-MIB.my**: The file contains HEALTH MIB module used by SuperDoctor® and SSM.
- **SUPERMICRO-SSM-MIB.my**: The file contains SSM MIB module used by SuperDoctor 5.
- **xtree.txt**: The file represents HEALTH and SSM module structure in tree structure format.
- **xiden.txt**: The file represents HEALTH and SSM module structure in identifier format.

A screenshot generated by the **snmpwalk** program of the NET-SNMP libraries on Linux platforms is shown below.

```
snmpwalk -v 1 localhost -c public .1.3.6.1.4.1.10876
```




```
root@softlab3:~# snmpwalk -v 1 localhost -c public .1.3.6.1.4.1.10876
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.1 = STRING: "FAN 1"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.2 = STRING: "FAN 2"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.3 = STRING: "FAN 3"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.4 = STRING: "FAN 4"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.5 = STRING: "FAN 5"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.6 = STRING: "FAN 6"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.7 = STRING: "FAN 7"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.8 = STRING: "FAN 8"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.9 = STRING: "CPU1 Vcore"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.10 = STRING: "CPU2 Vcore"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.11 = STRING: "CPU1 DIMM"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.12 = STRING: "CPU2 DIMM"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.13 = STRING: "+1.5 v"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.14 = STRING: "+5 V"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.15 = STRING: "+5VSB"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.16 = STRING: "+12 V"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.17 = STRING: "+1.1 v"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.18 = STRING: "+3.3VCC"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.19 = STRING: "+3.3VSB"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.20 = STRING: "VBAT"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.21 = STRING: "CPU1 Temp"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.22 = STRING: "CPU2 Temp"
SNMPv2-SMI::enterprises.10876.2.1.1.1.1.2.23 = STRING: "System Temp"
```

Figure 5-4

---

The figure below shows how the **snmpwalk** program of the NET-SNMP libraries using Supermicro MIBs is run on Linux platform.

```
snmpwalk -v 1 localhost -c public .1.3.6.1.4.1.10876
```

A terminal window titled 'root@softlab3:~' showing the execution of the 'snmpwalk' command. The command is '[root@softlab3 ~]# snmpwalk -v 1 localhost -c public .1.3.6.1.4.1.10876'. The output lists 23 Supermicro MIB objects, each with its OID and a string value. The values include 'FAN 1' through 'FAN 8', 'CPU1 Vcore', 'CPU2 Vcore', 'CPU1 DIMM', 'CPU2 DIMM', '+1.5 V', '+5 V', '+5VSB', '+12 V', '+1.1 V', '+3.3VCC', '+3.3VSB', 'VBAT', 'CPU1 Temp', 'CPU2 Temp', and 'System Temp'.

```
root@softlab3:~  
[root@softlab3 ~]# snmpwalk -v 1 localhost -c public .1.3.6.1.4.1.10876  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.1 = STRING: FAN 1  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.2 = STRING: FAN 2  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.3 = STRING: FAN 3  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.4 = STRING: FAN 4  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.5 = STRING: FAN 5  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.6 = STRING: FAN 6  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.7 = STRING: FAN 7  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.8 = STRING: FAN 8  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.9 = STRING: CPU1 Vcore  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.10 = STRING: CPU2 Vcore  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.11 = STRING: CPU1 DIMM  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.12 = STRING: CPU2 DIMM  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.13 = STRING: +1.5 V  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.14 = STRING: +5 V  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.15 = STRING: +5VSB  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.16 = STRING: +12 V  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.17 = STRING: +1.1 V  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.18 = STRING: +3.3VCC  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.19 = STRING: +3.3VSB  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.20 = STRING: VBAT  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.21 = STRING: CPU1 Temp  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.22 = STRING: CPU2 Temp  
SUPERMICRO-HEALTH-MIB::smHealthMonitorName.23 = STRING: System Temp
```

Figure 5-5

---

# 6 SuperDoctor 5 Command Line Program

---


SuperDoctor 5 provides a command line interface program **sd**, which displays health information in text mode.

## 6.1 SDC Commands

The **sd** program is located in the **[install folder]** folder. This file is named **sd.bat** for Windows platforms and **sd.sh** for Linux platforms.

### 6.1.1 -h: Display **sd** command arguments

In text console, execute **sd -h** and you will see the **sd** supported arguments.



```
Administrator: C:\Windows\system32\CMD.exe
c:\Program Files\Supermicro\SuperDoctor5>sd -h
*****
Product                - X8DT3
SuperDoctor 5 version  - 5.1.0_build.567-20141103143034
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
usage: sd
-abort,--abort          abort the shutdown or reboot command
-d,--dump              dump the internal format of Supermicro SNMP
MIBs
-dt,--delaytime <arg> delay <arg> seconds to shutdown or reset
the system
-e,--execute           run sd only once
-et,--exportThreshold export threshold configuration
-f,--file <arg>       output the internal format of Supermicro
SNMP MIBs to a file
-flash,--flash <arg> flash BIOS <arg> ROM
-flashlog,--biosflashlog show all bios flash log
-h,--help             show this page
-i,--interval <arg>  run sd every <arg> seconds
-ia,--importAlert <arg> import alert configuration <arg>
-is,--installSmartmontools Install Smartmontools
-it,--importThreshold <arg> import threshold configuration <arg>
-r,--reset            reset the chassis intrusion
-rd,--redetect        detect the monitored items again
-reboot,--reboot      reboot the system
-rt,--resetThreshold reset threshold to default settings
-shutdown,--shutdown shutdown the system
-v,--version          show the version information

c:\Program Files\Supermicro\SuperDoctor5>_
```


Figure 6-1

## 6.1.2 -d: Dump SNMP Messages

The `-d` option displays the internal formats of the Supermicro MIBs. This argument is for debugging purposes and should not be used by end users.

## 6.1.3 -e: Display All Monitored Items and their Status

In text console, execute `sdc -e` and you will see the status of monitored items



```
Administrator: C:\Windows\system32\cmd.exe
C:\Program Files\Supermicro\SuperDoctor5>sdc.bat -e
*****
Product
SuperDoctor 5 version - X8DT3
SuperDoctor 5 version - 5.2.0-build.509-20150520110720
Copyright(c) 1993-2015 Super Micro Computer, Inc. All Rights Reserved.
*****
Monitored Item      High Limit  Low Limit  Reading  Status
-----
Fan7 Fan Speed      709 RPM    709 RPM    0.0 RPM  CRITICAL
Fan8 Fan Speed      709 RPM    709 RPM    5720.0 RPM
+5U Voltage          5.504 U    4.512 U    5.088 U
+12U Voltage         13.107 U   10.803 U   12.339 U
CPU1 DIMM Voltage    1.648 U    1.2 U      1.584 U
+1.5U Voltage        1.648 U    1.352 U    1.512 U
+3.3U Voltage        3.648 U    2.952 U    3.312 U
+3.3Ush Voltage      3.648 U    2.952 U    3.216 U
UBAT Voltage         3.648 U    2.952 U    3.216 U
CPU1 Temp            75 C       27.0 C
System Temp          75 C       27.0 C
Chassis Intrusion    Good
PS Failure           Good
CPU 1 DIMM 1A Temp   65 C       -31.0 C
CPU 1 DIMM 2A Temp   65 C       -31.0 C
CPU 1 DIMM 3A Temp   65 C       33.0 C
CPU 2 DIMM 1A Temp   65 C       -31.0 C
CPU 2 DIMM 2A Temp   65 C       -31.0 C
CPU 2 DIMM 3A Temp   65 C       33.0 C
\\.\PHYSICALDRIVE0
<MSE423RP1UH4UH>
Good
P1-1A <CECC>         2          0
P1-2A <CECC>         2          0
P1-3A <CECC>         2          0
P1-1A <UECC>         0          0
P1-2A <UECC>         0          0
P1-3A <UECC>         0          0
-----
Wed May 27 15:47:31 2015
C:\Program Files\Supermicro\SuperDoctor5>_
```

Figure 6-2



### Notes:

1. The Status column (see the figure above) is empty, indicating that the monitored item is healthy.
2. Only the health of internal hard drive is shown. No health status of USB hard drives and flash drives is indicated.
3. RAID health is available on LSI MegaRAID 2108, 2208 and 3108 controllers.

```

*****
Monitored Item          High Limit  Low Limit  Reading    Status
-----
CPU1 Temp               80 C       37.0 C
System Temp            85 C       30.0 C
Peripheral Temp        85 C       35.0 C
PCH Temp               95 C       49.0 C
H0G Temp               95 C       50.0 C
FAN1                   450 RPM    1875.0 RPM
FAN2                   450 RPM    1725.0 RPM
VTT                    1.392 U    0.864 U    1.04 U
CPU1 Ucore             1.52 U    0.512 U    0.832 U
UDIMM AB               1.696 U    1.152 U    1.488 U
UDIMM CD               1.696 U    1.152 U    1.504 U
3.3V                   3.792 U    2.784 U    3.312 U
+3.3USB                3.792 U    2.784 U    3.36 U
5V                     5.696 U    4.288 U    4.992 U
+5USB                  5.696 U    4.288 U    4.992 U
12V                   13.568 U   10.494 U   11.978 U
UBAT                   3.456 U    2.544 U    3.216 U
Chassis Intru                    Good
P1_DIMMA1 <CECC>                2          0
P1_DIMMA2 <CECC>                2          0
P1_DIMMA1 <UECC>                0          0
P1_DIMMA2 <UECC>                0          0
LSI 2208 MegaRAID #0                    Good
UD 0 <RAID1>                    Good
UD 1 <RAID10>                   Good
Slot 0                          Good
Slot 1                          Good
Slot 2                          Good
Slot 4                          Good
Slot 5                          Good
Slot 8                          Good
PWS-1K41P-1R REV1.1<PMBus>
PS2 Fan1                       5312.0 RPM
PS2 Fan2                       8320.0 RPM
PS2 Temperature1                24.0 C
PS2 ACInputCurrent              1.109 A
PS2 DC12VOutputCurrent          8.5 A
PS2 ACInputPower                120.0 W
PS2 DC12VOutputPower            102.0 W
PS2 ACInputVoltage              111.5 V
PS2 DC12VOutputVoltage          12.128 V
PS2 Status                      Good
*****
Wed Jul 20 22:57:27 2016

```

Figure 6-3

### 6.1.4 -f: Write SNMP Messages to a Specified File

The -f option is similar to the -d option except that the former writes the internal formats of the Supermicro MIBs to a file. This argument is for internal use and should not be used by end users.

```

Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdc -f mib.txt
The format of snmp message had been created in mib.txt
C:\Program Files\Supermicro\SuperDoctor5>_


```

Figure 6-4



## 6.1.5 -i: Display All Monitored Items and their Status Repeatedly

The difference between the `-i` and `-e` commands is the frequency of displaying the monitored results. The `sdc -e` command only shows the status of monitored items once, and the `-i` command repeatedly shows their status.



```
Administrator: C:\Windows\system32\cmd.exe
C:\Program Files\Supermicro\SuperDoctor5>sdc.bat -i 10
*****
Product                - X8DT3
SuperDoctor 5 version - 5.2.0-build.509-20150520110720
Copyright(c) 1993-2015 Super Micro Computer, Inc. All Rights Reserved.
*****
Monitored Item          High Limit  Low Limit  Reading    Status
-----
Fan7 Fan Speed          709 RPM    709 RPM    0.0 RPM    CRITICAL
Fan8 Fan Speed          709 RPM    709 RPM    5744.0 RPM
+5V Voltage             5.504 U    4.512 U    5.088 U
+12V Voltage            13.187 U   10.803 U   12.339 U
CPU1 DIMM Voltage       1.648 U    1.2 U      1.584 U
+1.5V Voltage           1.648 U    1.352 U    1.512 U
+3.3V Voltage           3.648 U    2.952 U    3.312 U
+3.3Vsb Voltage         3.648 U    2.952 U    3.216 U
UBAT Voltage            3.648 U    2.952 U    3.216 U
CPU1 Temp               LOW
System Temp            75 C       27.0 C
Chassis Intrusion      Good
PS Failure              Good
CPU 1 DIMM 1A Temp     65 C       -31.0 C
CPU 1 DIMM 2A Temp     65 C       -31.0 C
CPU 1 DIMM 3A Temp     65 C       33.0 C
CPU 2 DIMM 1A Temp     65 C       -31.0 C
CPU 2 DIMM 2A Temp     65 C       -31.0 C
CPU 2 DIMM 3A Temp     65 C       33.0 C
\\.\PHYSICALDRIVE0    Good
  <MSE423RP1UH4UH>
P1-1A <CECC>           2          0
P1-2A <CECC>           2          0
P1-3A <CECC>           2          0
P1-1A <UECC>           0          0
P1-2A <UECC>           0          0
P1-3A <UECC>           0          0
-----
Wed May 27 15:48:46 2015
```

Figure 6-5



**Note:** Press the **Ctrl+C** keys to exit the `sdc` program.

---


## 6.1.6 -ia: Import Alert Configuration

The **-ia** argument is provided to import alert configuration data for SuperDoctor 5 without a web console. To execute the command **sd -ia**, a property file that contains the necessary alert settings is required.

Modify **alertcfg.properties.template** located in the **[install folder]\config** folder to suit your needs. Possible attributes and values of the property file are shown below. Note that the attributes and options are case insensitive.

Attribute	Description	Option
polling	Enables Pooling	true   false
pollinginterval	The interval in seconds between checks for the health status of monitored items if Polling=true Note: Minimal value is 3.	
log	Enables logging if polling=true	true   false
maxbackupindex	Backup files to keep around if log=true	
mail	Enables email alerts if polling=true	true   false
to	Recipients if mail=true Note: Multiple values are separated by a comma.	
from	Sender's email if mail=true	
smtp	SMTP server if mail=true	
port	Port if mail=true	
encryption	Connection security if mail=true	None   SSL   TLS
authentic	SMTP authentication if mail=true	true   false
username	Username (SMTP authentication) if mail=true	
password	Password (SMTP authentication) if mail=true	
trap	Enable trap alerts if polling=true	true   false
trapreceiver	Trap receivers if trap=true Note: Format: IP:port; Multiple values are separated by a comma.	
tray	Enable system tray if polling=true	true   false
syslog	Enable OS event log if polling=true	true   false

In text console, execute **sd** **-ia** [property\_file\_name] and you will see the import status of the alert configuration file.




```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sd -ia alertcfg.properties.template
*****
Product           - X8DT3
SuperDoctor 5 version - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
Alert configuration is imported successfully !
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-6

### 6.1.7 -r: Reset the Chassis Intrusion

In text console, execute the command **sd -r** to reset the chassis intrusion flag. The result is shown below:




```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sd -r
*****
Product           - X8DT3
SuperDoctor 5 version - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
Switch [Chassis Intrusion] reset successful.
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-7

### 6.1.8 -rd: Detect the Monitored Items Again

Sometimes your hardware configurations may change, such as a new power supply being used or new fans being plugged in. In these cases, you can execute the command **sd -rd** to detect the monitored items again. The **sd** program will start re-detecting and wait for SuperDoctor 5 to restart.



```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sd -rd
*****
Product           - X8DT3
SuperDoctor 5 version - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
Monitored items have been detected.
C:\Program Files\Supermicro\SuperDoctor5>
```


Figure 6-8

---

## 6.1.9 -v: Display sdc version information

The **-v** argument shows the sdc version information. In the prompt, enter the command **sdc -v**.

In text console, execute the command **sdc -v** to show the version of the **sdc**. The result is shown below:




```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdc -v
*****
Product                - X8DT3
SuperDoctor 5 version  - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
5.1.0_build.505-20140306134728
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-9

## 6.1.10 -reboot: Reboot the System

In a text console, execute the command **sdc -reboot** to immediately reboot the system. The result is shown below:




```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdc -reboot
*****
Product                - X8DT3
SuperDoctor 5 version  - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
Command has been fired.
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-10

### 6.1.11 –shutdown: Shutdown the System

In a text console, execute the command **sdcc -shutdown** to immediately shut down the system. The result is shown below:




```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdcc -shutdown
*****
Product           - X8DT3
SuperDoctor 5 version - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
Command has been fired.
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-11

### 6.1.12 –abort: About the Shutdown or Reboot Command

In a text console, execute the command **sdcc -abort** to immediately cancel the shutdown or reboot command. The result is shown below:




```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdcc -abort
*****
Product           - X8DT3
SuperDoctor 5 version - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
Command has been fired.
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-12

### 6.1.13 –dt: Delay Seconds to Run Power Command

In a text console, execute the command **sdcc -reboot -dt 60** to reboot the system 60 seconds later. The result is shown below:




```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdcc -reboot -dt 60
*****
Product           - X8DT3
SuperDoctor 5 version - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
Command has been fired.
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-13

---

## 6.1.14 –flash: Flash BIOS

In a text console, execute the command **sdc –flash** to flash the BIOS. This function supports Supermicro motherboards newer than H8, X8, and X9 series on Windows platforms and motherboards newer than X9 series on Linux platforms. To execute the **command sdc –flash**, a BIOS binary file must be provided. The result is shown below:



```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdc -flash "C:\Users\Administrator\Down
loads\X8DT32.317"
*****
Product           - X8DT3
SuperDoctor 5 version - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
No error.
Please restart your system to apply BIOS changes.
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-14




### Notes:

1. To avoid BIOS from being corrupted, you are required to disable ME (Intel Management Engine) before updating the BIOS. Find **disable ME** or **enable update ME** or **enable ME FW Image RE-flash** in the BIOS setup menu.
2. The command cannot be cancelled. Once you enter the command, the system starts flashing BIOS.
3. The BIOS binary file will be copied into **the [install folder]\BIOS\rom** folder so that you are able to see the file via the SD5 Web interface.
4. It's recommended that you check the original settings of the boot order in the BIOS Setup. Flashing the BIOS can cause the system reboot from a boot device which is not previously set.

---

## 6.1.15 –flashlog: Show Flash History

The BIOS flashing completed via SD5 will be logged whether the flashing is successful or not. To view the flashing history, execute the command **sdc –flashlog**.




```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdc -flashlog
*****
Product                - X8DT3
SuperDoctor 5 version  - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
2014/03/06 14:23:40 Flash BIOS X8DT32.317 in 111 seconds successfully and backup
the original BIOS to BIOS_20140306-142148.BAK
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-15

## 6.1.16 -et: Export Threshold Configuration

In text console, execute the command **sdc -et** to export the thresholds (high/low limits) of all monitored items.



```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdc -et
*****
Product                - X8DT3
SuperDoctor 5 version  - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
The thresholdConfig.csv has been created in C:\Program Files\Supermicro\SuperDoc
tor5\thresholdConfig.csv
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-16

Open **thresholdConfig.csv** located in the **[install folder]** folder, you can see the details of monitored items, such as name, high limit, and low limit.

	A	B	C	D	E	F	G
1	Key	Type	IsMonitored	Name	HighLimit	LowLimit	Reading
2	1	103	TRUE	CPU1 Temp			LOW
3	2	103	FALSE	CPU2 Temp			NA
4	3	3	TRUE	System Temp		75	33
5	4	2	TRUE	CPU1 Vcore	1.352	0.672	0.952
6	5	2	FALSE	CPU2 Vcore	1.352	0.672	0
7	6	2	TRUE	CPU1 DIMM	1.648	1.2	1.584
8	7	2	FALSE	CPU2 DIMM	1.648	1.2	0
9	8	2	TRUE	+1.5V	1.656	1.336	1.512
10	9	2	TRUE	+3.3V	3.648	2.928	2.976
11	10	2	TRUE	+3.3VSB	3.648	2.928	3.216
12	11	2	TRUE	+5V	5.536	4.48	4.768
13	12	2	TRUE	+12V	13.25	10.706	11.872
14	13	2	TRUE	VBAT	3.648	2.928	3.216
15	14	1	FALSE	Fan1		675	0
16	15	1	FALSE	Fan2		675	0
17	16	1	FALSE	Fan3		675	0
18	17	1	TRUE	Fan4		675	2430
19	18	1	FALSE	Fan5		675	0
20	19	1	FALSE	Fan6		675	0
21	20	1	FALSE	Fan7		675	0
22	21	1	TRUE	Fan8		675	2430
23	96	3	TRUE	P1-DIMM1A Temp	80		40
24	97	3	FALSE	P1-DIMM1B Temp	80		0
25	98	3	TRUE	P1-DIMM2A Temp	80		43
26	99	3	FALSE	P1-DIMM2B Temp	80		0
27	100	3	TRUE	P1-DIMM3A Temp	80		43
28	101	3	FALSE	P1-DIMM3B Temp	80		0

Figure 6-17

### 6.1.17 **-it: Import Threshold Configuration**

The **-it** argument is provided to import threshold configuration data (high/low limits) for SuperDoctor 5 without a web console. To execute the command **sdcli -it**, it is required to have a CSV (Comma-separated values) file containing the threshold. Note that to have the CSV file, execute **-et** to export threshold configuration in advance.


Modify **thresholdConfig.csv** located in the **[install folder]** folder to suit your needs. Note that you can only decide if an item should be monitored (column: **IsMonitored**) and to change the threshold (column: **HighLimit** and **LowLimit**) of an item.



	A	B	C	D	E	F	G
1	Key	Type	IsMonitored	Name	HighLimit	LowLimit	Reading
2	1	103	TRUE	CPU1 Temp			LOW
3	2	103	FALSE	CPU2 Temp			NA
4	3	3	TRUE	System Temp	75		33
5	4	2	TRUE	CPU1 Vcore	1.352	0.672	0.952
6	5	2	FALSE	CPU2 Vcore	1.352	0.672	0
7	6	2	FALSE	CPU1 DIMM	1.648	1.2	1.584
8	7	2	FALSE	CPU2 DIMM	1.648	1.2	0
9	8	2	TRUE	+1.5V	1.656	1.336	1.512
10	9	2	TRUE	+3.3V	3.648	2.928	2.976
11	10	2	TRUE	+3.3VSB	3.648	2.928	3.216
12	11	2	TRUE	+5V	5.536	4.48	4.768
13	12	2	TRUE	+12V	14.25	10.706	11.872
14	13	2	TRUE	VBAT	3.648	2.928	3.216
15	14	1	FALSE	Fan1		675	0
16	15	1	FALSE	Fan2		675	0
17	16	1	FALSE	Fan3		675	0
18	17	1	TRUE	Fan4		800	2430
19	18	1	FALSE	Fan5		675	0
20	19	1	FALSE	Fan6		675	0
21	20	1	FALSE	Fan7		675	0
22	21	1	TRUE	Fan8		675	2430
23	96	3	TRUE	P1-DIMM1A Temp	80		40
24	97	3	FALSE	P1-DIMM1B Temp	80		0

Figure 6-18

In text console, execute **sdcs -it [csv\_file\_name]** and you will see the import status of the threshold configuration file:




```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdcs -it thresholdConfig.csv
*****
Product           - X8DT3
SuperDoctor 5 version - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
Threshold configuration is imported successfully !
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-19

### 6.1.18 -rt: Reset Threshold to Default Settings

In text console, execute the command **sdcs -rt** to reset the thresholds (high/low limits) to the manufacturer's default settings.



```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5>sdcs -rt
*****
Product           - X8DT3
SuperDoctor 5 version - 5.1.0_build.505-20140306134728
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****
Threshold configuration is reset to default.
C:\Program Files\Supermicro\SuperDoctor5>
```

Figure 6-20

### 6.1.19 -is: Install Smartmontools

In text console, execute the command **sdcs -is** to install smartmontools on Windows platforms online. Note that smartmontools including the smartctl utility is required for SD5 to monitor SMART health of hard drives. Read the GPL (GNU General Public License) 2.0 license agreement carefully before installing smartmontools. If you accept the terms or the agreement, input **Y** to continue installation.

```
Administrator: C:\Windows\system32\CMD.exe - sdc -is
C:\Users\Administrator>sdsc -is
*****
Product           - X8DT3
SuperDoctor 5 version - 5.1.0_build.571-20141105181103
Copyright(c) 1993-2014 Super Micro Computer, Inc. All Rights Reserved.
*****

IMPORTANT - READ CAREFULLY BEFORE INSTALLING SMARTMONTTOOLS
=====
                GNU GENERAL PUBLIC LICENSE
                Version 2, June 1991

    Copyright (C) 1989, 1991 Free Software Foundation, Inc.
    59 Temple Place - Suite 330, Boston, MA 02111-1307, USA
    Everyone is permitted to copy and distribute verbatim copies
    of this license document, but changing it is not allowed.

                Preamble

    The licenses for most software are designed to take away your
PRESS <ENTER> TO CONTINUE:
-
```

Figure 6-21

---

# 7 SD5 Tray

---

SuperDoctor 5 provides a program called **SD5 Tray** allowing the Windows user to get alert messages on the desktop. To use this function, you have to configure SD5 notification methods in advance, see [4.5.1 Alert Configuration](#) for more information. Note that this function is only available on Windows platforms.

## 7.1 Verifying SD5 Tray on Windows

When you install SuperDoctor 5 with SD5 Tray a SD5 tray icon will appear in your system tray (note that SD5 Tray is disabled in SD5 installer by default). To enable SD5 Tray manually after installation, you can execute the **enable\_tray.bat** script in the **[install\_folder]\tray** folder. When you install SuperDoctor 5, SD5 will insert an SD5 tray icon into your system tray. To see the SD5 tray icon (see the figure below), use the same account you install SD5 to log on the Windows system.



Figure 7-1

When the SD5 Tray receives alert messages, the tray icon will change.



Figure 7-2

Click the SD5 tray icon. The detailed alert messages are displayed in the dialog box.




Figure 7-3

The buttons in the dialog box:

- **Acknowledge:** Acknowledges an alert. Every alert will be kept until it is acknowledged. If acknowledged, it will no longer display in the dialog box.
- **Dismiss:** Minimizes the dialog box.
- **Previous:** Reads the previous alert.
- **Next:** Reads the next alert.

## 7.2 Manually Controlling SD5 Tray

Besides the SD5 tray icon, you are able to see a minimized window showing on the task bar.




Figure 7-4

You can close the SD5 Tray by right-clicking the SD5 window and then selecting **Close**.




Figure 7-5

To start the SD5 Tray on the desktop, click the Windows **Start** button, select **All Programs**, click the **Startup** folder, and click **Start SuperDoctor 5 Tray**.




Figure 7-6

## Part 3 Advanced Topics

---

## 8 SSM Utilities

---

Two Supermicro Server Manager (SSM) utility applications, **changejvm** and **change\_cert\_pwd**, are provided to change Java VM and to assign the password used in the agent key store used by SD5. This chapter shows you how to use the utilities.

### 8.1 Using ChangeJVM to Change a Java VM

When users install SuperDoctor 5, they can choose the kind of Java VM to be used. The utility **changejvm** located in the **[install folder]\tools** folder can be used to change a Java VM.

Usage:

```
changejvm [-p <arg>] [-h | --help ] [-j <arg>]
```


Options:

- p            The root folder of SD5. The argument is optional and the default value is **[install folder]**.
- \*-j           The kind of Java VM to be used, e.g., /usr/java/jdk1.8.0\_51/jre/bin/java
- h, --help   Shows the help menu.

(\*indicates a required attribute)

The following figure shows how the command

**changejvm.bat -j "C:\Program Files\Java\jre1.8.0\_45\bin\java.exe" -p "C:\Program Files\Supermicro\SuperDoctor5"** is used to change to another version of Java VM (JRE 1.8.0\_45).




```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5\tools>changejvm.bat -j "C:\Program Files\Java\jre1.8.0_45\bin\java.exe" -p "C:\Program Files\Supermicro\SuperDoctor5"
The JUM paths have been changed successfully.
C:\Program Files\Supermicro\SuperDoctor5\tools>
```

Figure 8-1

---

The following figure shows how the command **changejvm.bat -j "C:\Program Files\Supermicro\SuperDoctor5\jre\bin\java.exe" -p "C:\Program Files\Supermicro\SuperDoctor5"** is used to change to the built-in Java VM of SD5. The built-in Java VM (JRE 1.8.0\_77) is located in the **[install folder]\jre\bin** folder.



```
Administrator: Command Prompt
C:\Program Files\Supermicro\SuperDoctor5\tools>changejvm.bat -j "C:\Program Files\Supermicro\SuperDoctor5\jre\bin\java.exe" -p "C:\Program Files\Supermicro\SuperDoctor5"
The JVM paths have been changed successfully.
C:\Program Files\Supermicro\SuperDoctor5\tools>_
```

Figure 8-2



**Notes:**

1. You need to stop the SuperDoctor 5 service before changing Java VM if SuperDoctor 5 is still running.
2. You need to manually restart the SuperDoctor 5 service after changing Java VM.
3. The architecture of Java VM you selected must suit the installation program. For example, to use an x86 version of SD5, you need to install an x86 version of Java VM first.
4. It's recommended that you use the latest version of JRE 8 in SD5. Currently, only Oracle JRE 8 update 77 has been tested on both Windows and Linux platforms. Other Oracle JREs (i.e. JRE 6 and JRE 7) and Non-Oracle Java VMs (i.e. OpenJDK) are not supported in this version.



---

## 8.2 Using Change\_cert\_pwd to Change the Certificate Password

When you create a customized certification with the SSMCertificate program, you can reassign the certificate password to be used in SD5. The utility **change\_cert\_pwd** located in the **[install folder]\tools** folder can be used to change the certificate password defined in the agent.cfg.

Usage:

```
change_cert_pwd [-p <arg>] [-h | --help ] [-s <arg>]
```

Options:


\*-p           The password to be encoded in agent.cfg.

-s            The root folder of SD5, e.g., /opt/Supermicro/SuperDoctor5. The argument is optional and the default value is SD5\_HOME.

-h, --help   Shows the help menu.

(\*indicates a required attribute)

The following figure shows how the command **change\_cert\_pwd.bat -p 123456 -s ..\** is used to change the password in agent.cfg used by SD5.



```
Administrator: Command Prompt
C:\>change_cert_pwd.bat -p 123456 -s ..\
The password in agent.cfg has been changed successfully.
C:\>_
```

Figure 8-3

Note that you need to restart SD5 service for the new certificate password to take effect.

## 9 SSM Certification

When server-side applications (i.e. SSM Server, SSM Web, and SSM CLI) communicate with SuperDoctor 5, the communication channel can be configured to use Secure Sockets Layer (SSL). SSM supports secure communications with SSL and a public key infrastructure (PKI). A built-in key pair shared by the SSM Server, SSM Web, and SSM CLI and a key pair for SuperDoctor 5 are included in the SSM installation program. By default, SSM uses the built-in key pairs to establish an SSL channel for communications.




Figure 9-1

As shown above, the SSM Server and SuperDoctor 5 use two key stores to preserve their key pairs and the trusted client's public keys, respectively. (Note that the SSM Server, SSM Web, and SSM CLI use the same Server Trust Store and Server Key Store to establish secure communication channels with SuperDoctor 5.) For the SSM Server, the Server Key Store contains an SSM Server private key. For SuperDoctor 5, the Agent Key Store contains a SuperDoctor 5 private key. The Agent Trust Store contains SSM Server public keys. To ensure secure communications, the SSM Server uses the SuperDoctor 5's public key to encipher messages and sends the enciphered messages to SuperDoctor 5. The enciphered messages can only be deciphered with the SuperDoctor 5's private key, which is safely kept by SuperDoctor 5. When SuperDoctor 5 sends messages back to the SSM Server, it uses the SSM Server's public key to encipher the messages that are then deciphered by the SSM Server with its own private key. Even if the messages are sniffed by hackers, they cannot understand the enciphered messages.

---

Note that you do not need to manually replace the built-in key pairs if you install SuperDoctor 5 only. For more information on replacing the default key pairs by using the **SSM Certificate** program, please refer to *12 SSM Certification* in *SSM User's Guide*.

---

## Part 4 Appendices

---

# A Log Settings

SuperDoctor 5 uses a log file to record runtime information and errors. By default, SD5 backs up 10 copies of 1 log file when it reaches a maximum size of 8 MB. The backup files are sequentially numbered. For instance, backup files are named sd5.log.1, sd5.log.2, sd5.log.3, and so on. You can change the maximum log file size and maximum number of backup copies.

Configure log properties of SuperDoctor 5:

1. Stop the SuperDoctor 5 Service. Please refer to [2.3 Manually Controlling SD5 Service](#) for more information.
2. Find **log4j.properties** located in **[install folder]\config** and open it with a text editor.
3. Find the content that contains this line:  
**log4j.appender.LOGFILE.MaxFileSize=8000KB**  
Modify the word 8000KB to an appropriate value. Allowable units are KB, MB and GB. This line may be commented out if no file size constraint is to be applied.
4. Find the content that contains this line: **log4j.appender.LOGFILE.MaxBackupIndex=10**  
Modify the keyword 10 to an appropriate value.
5. Save the file and restart the SuperDoctor 5 service.

---

## B Third-Party Software

The open source libraries used by SD5 are listed below:

Library	License
Antlr	BSD
Apache commons	Apache License
cglib	Apache License
com4j	MIT
Ehcache	Apache License
JACOB	LGPL
JavaMail (mail.jar)	CDDL
jcommon	LGPL
jetty	Apache License, Eclipse Public License
JFreeChart	LGPL
Java Native Access	LGPL
Joda Time	Apache License
jQuery	MIT
json-simple	Apache License
JLine	BSD
gson	Apache License
google-guice	Apache License
Log4J	Apache License
Quartz	Apache License
Smiparser	Apache License
SLF4J	MIT
SNMP4J	Apache License
Spring framework	Apache License
Wicket	Apache License
xstream	BSD
xml-apis	Apache License
xerces XML parser	Apache License

# C Updating Configurations

For non-IPMI SKU motherboards, SuperDoctor 5 automatically detects the monitored sensors based on the configuration files. When the message “The health information of the XXXXX motherboard is not available” on the Health Info page, it is necessary to update SuperDoctor 5 and the configuration files since the older version of SuperDoctor 5 may fail to detect the sensors. The steps below guides you to update the configuration files manually.




Figure C-1

To update the configuration files, follow these steps:

1. Download the latest file **TMHealth2-resource-XXX.jar** from the Supermicro FTP site:  
[ftp://ftp.supermicro.com/utility/SuperDoctor\\_5/](ftp://ftp.supermicro.com/utility/SuperDoctor_5/).
2. Copy and paste this file to replace the existing file **[install folder]/plugin/builtin/TMHealth2-resource-XXX.jar**.
3. Execute the command `sdcc -rd` to redetect the monitored items with the new configuration file.

---

# Contacting Supermicro

## Headquarters

Address: Super Micro Computer, Inc.  
980 Rock Ave.  
San Jose, CA 95131 U.S.A.  
Tel: +1 (408) 503-8000  
Fax: +1 (408) 503-8008  
Email: [marketing@supermicro.com](mailto:marketing@supermicro.com) (General Information)  
[support@supermicro.com](mailto:support@supermicro.com) (Technical Support)  
Web Site: [www.supermicro.com](http://www.supermicro.com)

## Europe

Address: Super Micro Computer B.V.  
Het Sterrenbeeld 28, 5215 ML  
's-Hertogenbosch, The Netherlands  
Tel: +31 (0) 73-6400390  
Fax: +31 (0) 73-6416525  
Email: [sales@supermicro.nl](mailto:sales@supermicro.nl) (General Information)  
[support@supermicro.nl](mailto:support@supermicro.nl) (Technical Support)  
[rma@supermicro.nl](mailto:rma@supermicro.nl) (Customer Support)  
Web Site: [www.supermicro.nl](http://www.supermicro.nl)

## Asia-Pacific

Address: Super Micro Computer, Inc.  
3F, No. 150, Jian 1st Rd.  
Zhonghe Dist., New Taipei City 235  
Taiwan (R.O.C)  
Tel: +886-(2) 8226-3990  
Fax: +886-(2) 8226-3992  
Email: [support@supermicro.com.tw](mailto:support@supermicro.com.tw)  
Web Site: [www.supermicro.com.tw](http://www.supermicro.com.tw)





This page is intentionally left blank