



KONICA MINOLTA

CHROMA METER CR-400/410

25



CR-410

CR-400

The Standard in Measuring Color & Light

Giving Shape to Ideas

Introducing the successor to the Konica Minolta CR-300/310, our best-selling colorimeter globally accepted as the standard in a wide range of industries.

CR-400

Measurement area Ø8mm

CR-410

Measurement area Ø50mm



The measuring head can perform measurement alone.

The measuring head is detachable from the data processor. Now, you can take measurements directly with the head alone. What's more, you can connect the measuring head directly to a PC. Simply install our optional software, and your PC can function as the data processor.

Easy-to-understand the name on the buttons, ensure smooth measurement and setting operations.

Achieves exceptional accuracy

Inter-instrument agreement : CR-400: ΔE^*ab within 0.6
CR-410: ΔE^*ab within 0.8

Repeatability : within ΔE^*ab 0.07

User calibration function ensures higher accuracy.

(Settings can be configured with the data processor or via a PC with optional software installed.)

Color difference tolerance can be set to perform PASS/WARN/FAIL

(Settings can be configured with the data processor or via a PC with optional software installed.)

Offers a wider range of color systems than the CR-300/310 Series.

The measuring head alone can store up to 1,000 measurements. When the data processor is connected, up to 2,000 measurements can be stored. (The measuring head can store up to 100 color-difference target colors with or without the data processor connected.)

Capable of displaying color-difference graphs that provide a visual representation of the color difference.

(When connected to data processor)

A simple, cellular-phone-type text entry system is provided for entering the names of color-difference target colors and calibration channels.

(When connected to data processor)

Features a large, easy-to-see LCD with a built-in backlight.

The LCD offers six user-selectable languages for the display mode, including English and Japanese.

(When connected to data processor)

Can be powered with rechargeable batteries for reduced operating costs.

User-defined evaluation formulas freely set up.

The CR-400 Series features a User Index function that allows you to configure the evaluation formula and color-calculation formula as desired. This feature is intended to meet the needs of color-control applications in which industry-specific or customized evaluation formulas are used instead of the versatile color system and standard evaluation formula such as $L^*a^*b^*$.

(Settings can be configured via a PC with optional software installed.)

Abundant accessories applicable to various materials.

A varied selection of accessories is available to accommodate various types of targets including powder, paste and opaque liquids.

Compact data processor incorporates a high-speed printer.

The compact, lightweight data processor is battery-operated* and features a built-in high-speed printer. Its size and weight are approximately one-half those of the conventional DP-300 Series. In addition, the CR-400 Series is designed with a detachable shoulder strap for easier portability. *An AC adapter is included as a standard accessory.

Full data compatibility with the CR-300/310 series

To ensure data compatibility, the CR-400 Series utilizes the same illumination-viewing optical system as the conventional CR-300/310 Series. As a result, those upgrading from the preceding model can make full use of their existing data.

The CR-400/410 Series really shows its abilities in these applications.

When measuring powders or pastes



When color control is performed with a customized evaluation formula, instead of the versatile color system



When a compact colorimeter is needed in the field



When measurements need to be printed on-site for labeling of samples



With the varied accessories, you can measure targets with diverse profiles.



Granular-Materials Attachment **CR-A50**



Glass Light-Projection Tube
CR-A33f (For CR-400)
CR-A33e (For CR-410)




User-defined evaluation formulas can be entered as desired. Now, you can control color with customized evaluation formulas.

User index function


-Example-

Evaluation of tomato ripeness= $a^*/b^*+0.3a^*/L^*$




Note: The evaluation formula and grade indicated above are hypothetical examples used only to demonstrate the user index function.

The measuring head can be used independently of the data processor. This is advantageous when portability is required or limited space is available.



The compact data processor features a built-in printer for superior mobility.

System Diagram



Optional Accessories



Granular-Materials Attachment
CR-A50

With the Granular-Materials Attachment CR-A50, the color of powders, pastes, grains, and other granular substances can be easily and accurately measured.



Glass Light-Projection Tube
CR-A33f (For CR-400) and **CR-A33e** (For CR-410)

Glass Light-Projection Tube CR-A33f and CR-A33e have a glass plate at the tip and can be used for measuring wet surfaces or for ensuring that materials such as textiles are flat during measurements.




Pivoting Base **CR-A12** (For CR-400)

Attaching the Pivoting Base CR-A12 to the Measuring head of the CR-400 ensures greater stability and accuracy in measurements. Light-Projection Tube CR-A33c is also included.

SpectraMagic™ NX

Supports Windows® Vista/7/8.1/10

SpectraMagic™ NX enables you to perform comprehensive color inspection and analysis of incoming raw materials, in process production, and outbound color critical goods and materials in virtually any industry. With SpectraMagic™ NX you can insert digital images with measured data. Measure samples in any of 8 universally accepted color spaces. Select from 16 illuminants, and up to 40 indices to determine specific color and appearance properties, such as brightness, haze, yellowness, opacity and strength. You can even configure up to 8 customized color equations. Reports range from simple Pass/Fail to trend charts, histograms, color plots, and spectral graphs. SpectraMagic™ NX comes with predefined templates, or you can create your own templates. For illustrations and explanations to understanding color and color measurement technology, there is a link to Konica Minolta's well known and respected "Precise Color Communication".



Specifications

Color space	L*a*b*, L*C*h, Lab99, LCh99, XYZ, Hunter Lab, Yxy, L*u'v', L*u'v*, Munsell, and their color differences (excluding Munsell)
Index	WI (CIE 1982, ASTM E313-73, Hunter, Berger, Taube, Stensby, Ganz, Tint(Ganz), YI (ASTM D1925-70, ASTM E313-73, ASTM E313-96, DIN6167), WB (B ASTM E313-73), Standard Depth (ISO 105.A06), RxRvRz, Gray scale (ISO 105.A05)
Color difference equation	ΔE^*_{ab} (CIE 1976), ΔE^*_{94} (CIE 1994), ΔE_{00} (CIE 2000), ΔE_99 (DIN99), ΔE (Hunter), CMC (I:c), FMC-2, NBS 100, NBS 200
Observer	2 Standard Observer
Illuminant	C, D ₅₀
Graph display	L*a*b* absolute value, $\Delta L^*a^*b^*$ (color difference distribution), Hunter Lab absolute value, Hunter ΔL^* (color difference distribution), Trend chart and histogram of each color space and color difference equation, Pseudo Color display

System requirements

OS: Windows® Vista Business 32-bit, 64-bit
Windows® 7 Professional 32-bit, 64-bit
Windows® 8.1 Pro 32-bit, 64-bit
Windows® 10 Pro 32-bit, 64-bit

The hardware of the computer system to be used must meet or exceed the greater of the recommended system requirements for the compatible OS being used or the following specifications.


CPU: Pentium® III 600 MHz equivalent or faster

Memory: 128 MB or more (256 MB or more recommended)

Hard disk: 450 MB or more of free space for installation

Display resolution: 1,024 x 768 dots or more/ 16-bit colors or more

Other: DVD-ROM drive (required for installation); one free USB port for protection key; one free port (serial port or additional USB port) for connection to instrument when connecting via cable (or USB port for USB Bluetooth® adapter when using a USB Bluetooth® adapter for performing communication with CM-700d or CM-600d via Bluetooth®); Internet Explorer Version. 5.01 or later.



System requirements

OS: Windows® 7 Professional 32-bit, 64-bit
Windows® 8.1 Pro 32-bit, 64-bit
Windows® 10 Pro 32-bit, 64-bit

The hardware of the computer system to be used must meet or exceed the greater of the recommended system requirements for the compatible OS being used or the following specifications.

CPU: Pentium® 166MHz or higher

Memory: 32MB or higher

Hard disk: 100MB or more free space

Display resolution: VGA (640x 480) or higher

• Windows® is a trademark or registered trademark of Microsoft Corporation in the USA and other countries.

• Pentium® is a trademark of Intel Corporation in the USA and other countries.

• Bluetooth® is a registered trademark of Bluetooth SIG, Inc. and is used under license agreement.

Specifications

Name	Chroma Meter Measuring Head	
Model	CR-400 Head	CR-410Head
Illumination/viewing system	Diffuse illumination/0 viewing angle (Specular component included/Conforms to JIS Z 8722 condition c standard.)	Wide-area illumination/0 viewing angle (Specular component included)
Detector	Silicon photo cell (6)	
Display range	Y: 0.01 to 160.00% (reflectance)	
Light source	Pulsed xenon lamp	
Measurement time	1 seconds.	
Minimum measurement interval	3 seconds.	
Battery performance	Approx. 800 measurements (when using batteries under company testing Konica Minolta's conditions)	
Measurement/illumination area	ø8/ø11	ø50/ø53
Repeatability	Within ΔE*ab0.07 standard deviation (when the white calibration plate is measured 30 times at intervals of 10 seconds)	
Inter-instrument agreement	ΔE*ab: within 0.6	ΔE*ab: within 0.8
Observer	2 degrees Closely matches CIE 1931 Standard Observers: ($\bar{x}_2\lambda$, $\bar{y}_2\lambda$, $\bar{z}_2\lambda$)	
Illuminant *1	C, D ₆₅	
Display *1	Chroma values, color difference values, PASS/WARN/FAIL display	
Tolerance judgment *1	Color difference tolerance (box tolerance and elliptical tolerance)	
Colorimetric data/indexes	XYZ, Y xy, L*a*b*, Hunter Lab, L*C*h, Munsell (only illuminant C), CMC(l:c), CIE1994, Lab99, LCh99, CIE2000, CIE Wi-Tw (only illuminant D ₆₅), WI ASTM E313 (only illuminant C), YI ASTM D1925 (only illuminant C), YI ASTM E313 (only illuminant C), User index (up to six can be registered from computer)	
Languages	Operating keys : English LCD : English (default) (LCD : German, French, Italian, Spanish, Japanese) *1	
Data memory	1,000 (measuring head and data processor save different data)	
Color difference target colors	100	
Calibration channels *1	20 channels (ch00 : white calibration, ch01 to ch19 : user calibration)	
Display	Dot-matrix LCD with back light (15 chars x 9 lines + 1 line for icon display)	
Interface	RS-232C compliant (for data processor/PC) * Baud rate : 4800, 9600, 19200 (bps), set at 9600 bps when shipped from factory	
Power	4 AAA size alkaline or Ni-MH batteries, AC Adapter AC120V ~ 50-60Hz (for N.America and Japan) AC230V ~ 50-60Hz (for worldwide except N.America)	
Size (W x H x D)	102 x 217 x 63 mm	102 x 244 x 63 mm
Weight	Approx. 550g	Approx. 570g
	(including 4 AAA size batteries and not including RS-232C cable)	
Operation temperature/humidity range	0 to 40 °C, relative humidity 85% or less (at 35 °C) with no condensation * Operating temperature/humidity range of products for North America : 5 to 40 °C, relative humidity 80% or less (at 31 °C) with no condensation	
Storage temperature/humidity range	-20 to 40 °C, relative humidity 85% or less (at 35 °C) with no condensation	
Other	LCD back light ON/OFF function (when ON, back light stays ON for 30 seconds after last key or measurement operation)	


*1 indicates when connected to the Data Processor or when not set using the Data Processor or the optional software, that some of the function are not available when the measuring head is not connected.

Name	Data Processor
Model	DP-400
Display range	Y: 0.01 to 160.00% (reflectance)
Measurement time *2	1 Seconds.
Minimum measurement interval *2	3 Seconds.
Battery performance	Approx. 800 measurements (when using batteries under company testing Konica Minolta's conditions)
Illuminant	C, D ₆₅
Display	Chroma values, color difference values, color difference graphs, PASS/WARN/FAIL display
Tolerance judgment *2	Color difference tolerance (box tolerance and elliptical tolerance) Only for the display function
Colorimetric data/indexes	XYZ, Y xy, L*a*b*, Hunter Lab, L*C*h, Munsell (only illuminant C), CMC(l:c), CIE1994, Lab99, LCh99, CIE2000, CIE Wi-Tw (only illuminant D ₆₅), WI ASTM E313 (only illuminant C), YI ASTM D1925 (only illuminant C), YI ASTM E313 (only illuminant C), User index (up to six registered in the Measuring Head can be used)
Languages	Operating keys : English, LCD : English (default), German, French, Italian, Spanish, Japanese
Data memory	Max. 2,000 pieces of data (divisible into 100 pages) Deletion and Undoing selected stored data (one piece of data or all data) are possible
Color difference target colors *2	Only for the operating function (100 pieces of data when the measuring head is connected; input of measurement values or numeric) (independent of page function)
Calibration channels *2	Only for the operating function (20 channels when the measuring head is connected) (ch00: white calibration; ch01 to ch19: user calibration)
Page function	100 pages
Display	Dot-matrix LCD with back light (16 chars x 9 lines + 1 line for icon display) Contrast adjustment
Printer	384 dot line thermal printer (can also print graphs) Automatically prints out all measurement results (can be set not to print)
Statistical function	Maximum, minimum, average, and standard deviation
Automatic measurement *2	Date and time display: year, month, day, hour, minute Timer: 3seconds. to 99 minutes. (Some measurement modes require more than 3 seconds.)
Interface	RS-232C compliant Baud rate (bps) : 19,200 fixed (when connected to PC) When measuring head is connected baud rate is automatically set to that of the measurement head
Power	4 AA size alkaline or Ni-MH batteries, AC Adapter AC120V ~ 50-60Hz (for N.America and Japan) AC230V ~ 50-60Hz (for worldwide except N.America)
Size (W x H x D)	100 x 73 x 255 mm
Weight	Approx. 600g (not including batteries and paper)
Operation temperature/humidity range	0 to 40 °C, relative humidity 85% or less (at 35 °C) with no condensation * Operating temperature/humidity range of products for North America : 5 to 40 °C, relative humidity 80% or less (at 31 °C) with no condensation
Storage temperature/humidity range	-20 to 40 °C, relative humidity 85% or less (at 35 °C) with no condensation
Other	User calibration function (multi-calibration/manual calibration) *2, Measurements for automatic average function, Print ON/OFF function, CR-400 measurement data import function *2, All color space print ON/OFF function, Data protection ON/OFF function, Back light ON/OFF function, Buzzer ON/OFF function, Display color limit function, Remote mode (stored data output), Character input function (alphanumeric)


*2 indicates that part of or all functions are not available when the measurement head is not connected.

Dimensions (Units: mm)


Measuring Head CR-400



Measuring Head CR-410



Data Processor DP-400



Standard/Optional accessories

Color Data Software CM-S100w	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
SpectraMagic™ NX	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
CR-400 Utility Software	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
CR-S4w	<input checked="" type="radio"/>		
White Calibration Plate			
CR-A43	<input checked="" type="radio"/>		
White Calibration Plate			
CR-A44		<input checked="" type="radio"/>	
Protective Cap			
CR-A72	<input checked="" type="radio"/>		
Protective Cap			
CR-A104		<input checked="" type="radio"/>	
RS-232C Cable	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>
CR-A101 (Head-DP)	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>
RS-232C Cable	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
CR-A102 (for PC)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
AC Adapter	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>
Wrist Strap	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>
CR-A73	<input checked="" type="radio"/>	<input type="radio"/>	
Shoulder Strap			
SS-01			
Hard Case	<input type="radio"/>	<input type="radio"/>	
CR-A103	<input type="radio"/>	<input type="radio"/>	
Roll Paper (one roll)			
Roll Paper			
DP-A22 (five rolls)			
4 AA Size Batteries			<input checked="" type="radio"/>
4 AAA Size Batteries	<input checked="" type="radio"/>	<input type="radio"/>	
Glass Light-Projection Tube	<input type="radio"/>		
CR-A33a/f	<input type="radio"/>		
Light-Projection Tube	<input type="radio"/>		
CR-A33c/d			
Glass Light-Projection Tube		<input type="radio"/>	
CR-A33e			
Granular-Materials Attachment	<input type="radio"/>	<input type="radio"/>	
CR-A50			
Pivoting Base	<input type="radio"/>		
CR-A12	<input type="radio"/>		
Color Tiles	<input type="radio"/>		

● Standard accessory
○ Optional accessory

The specifications and appearance shown herein are subject to change without notice.



SAFETY PRECAUTIONS

For correct use and for your safety, be sure to read the instruction manual before using the instrument.

- Always connect the instrument to the specified power supply voltage. Improper connection may cause a fire or electric shock.
- Be sure to use the specified batteries. Using improper batteries may cause a fire or electric shock.

KONICA MINOLTA, INC.

Konica Minolta Sensing Americas, Inc.

Konica Minolta Sensing Europe B.V.

Osaka, Japan

New Jersey, U.S.A.

European Headquarter /BENELUX

German Office

French Office

UK Office

Italian Office

Swiss Office

Nordic Office

Polish Office

Turkish Office

SE Sales Division

Beijing Office

Guangzhou Office

Chongqing Office

Qingdao Office

Wuhan Office

Phone : 888-473-2656 (in USA), 201-236-4300 (outside USA)

Phone : +31 (0) 30 248-1193

Phone : +49 (0) 89 4357 156 0

Phone : +33 (0) 1 80 11 10 70

Phone : +44 (0) 1925 467300

Phone : +39 02849488.00

Phone : +41 (0) 43 322-9800

Phone : +46 (0) 31 7099464

Phone : +48 (0) 71 73452-11

Phone : +90 (0) 216-528 56 56

Phone : +86-(0)21-5489 0202

Phone : +86-(0)10-8522 1551

Phone : +86-(0)20-3826 4220

Phone : +86-(0)23-6773 4988

Phone : +86-(0)532-8079 1871

Phone : +86-(0)27-8544 9942

Phone : +65 6563-5533

Phone : +82 (0) 2-523-9726

Fax : 201-785-2482

Fax : +31 (0) 30 24 81 211

Fax : +49 (0) 89 4357 156 99

Fax : +33 (0) 1 80 11 10 82

Fax : +44 (0) 1925 711143

Fax : +39 02849488.30

Fax : +41 (0) 43 322-9809

Fax : +48 (0) 71 734 52 10

Fax : +90 (0) 212-253 49 69

Fax : +86-(0)21-5489 0005

Fax : +86-(0)10-8522 1241

Fax : +86-(0)20-3826 4223

Fax : +86-(0)23-6773 4799

Fax : +86-(0)532-8079 1873

Fax : +86-(0)27-8544 9991

Fax : +65 6560-9721

Fax : +82(0)31-995-6511

Konica Minolta Sensing Singapore Pte Ltd.

Konica Minolta Sensing Korea Co., Ltd.

Addresses and telephone/fax numbers are subject to change without notice. For the latest contact information, please refer to the KONICA MINOLTA Worldwide Offices web page:

©2002-2017 KONICA MINOLTA, INC.