

# EtherFast® 10/100 + 56K Modem PC Card

*Dual-Speed Networking and a 56K v.90 Modem in an Integrated PC Card – No Dongles or Couplers to Lose or Break*



No Dongle!



EtherFast 10/100 + 56K Modem PC Card (PCMLM56)

The EtherFast 10/100 + 56K Modem PC Card will give your notebook computer a simultaneous connection to any 10/100 Local Area Network and the Internet. It's two cards in one – the unique integrated coupler is equipped with an auto-sensing 10/100 RJ-45 port and a standard RJ-11 telephone port built right in. Just one integrated unit takes up only one PCMCIA slot – plus there's no cables or dongles to lose!

Hotswapping technology lets you insert or remove the EtherFast 10/100 + 56K Modem PC Card while your computer is on, and a convenient auto sleep mode turns the card off when it isn't being used to help preserve your notebook PC's battery life. Ready to run with all major operating systems and fully compliant with all major standards, the EtherFast 10/100 + 56K Modem PC Card is guaranteed to help you stay connected for years to come!

## Benefits

- Simultaneously Connect to the Internet and a 10BaseT/100BaseTX Network
- Fully Integrated PC Card – No Dongle or Cable Coupler to Lose or Break
- Surf the Web, Send Email and Share Files On Your Notebook PC at Up to 100Mbps
- Unique Design Only Takes Up One PCMCIA Card Slot
- Free Software Driver Upgrades
- Free Technical Support

## Features

- Simultaneously Connect to the Internet and a 10Base/100BaseTX Network Through One 16-Bit PCMCIA PC Card
- Unique Design Takes Up Only One Card Slot
- Fully Integrated PC Card – No Cable Coupler to Break or Lose
- Runs with Windows 98, 95, NT 4.0 and Linux
- Type II PCMCIA 56Kbps Data Modem with 10/100 LAN and 14.4Kbps Send/Receive Fax
- Compatible with V.90 and K56Flex Standards
- Versatile Modem Runs with Regular Telephone Lines
- Backward Compatible with Older V.x Standards, Slower Dialups, ISPs, and Modems
- Fully Hotswappable
- Free Technical Support and Software Upgrades
- 5-Year Limited Warranty

## Specifications

<b>Standards</b>	IEEE 802.3, IEEE 802.3u, V.90, K56Flex, V.34bis, V.34, V.32bis, V.32, V.22bis, V.23, V.22/Bell 212A, V.21/Bell 103
<b>Topology</b>	Star
<b>Protocol</b>	CSMA/CD
<b>Ports</b>	<b>1</b> 10BaseT/100BaseTX Dual-Speed Auto-Sensing RJ-45 Port <b>1</b> Standard RJ-11 Port
<b>Speed</b>	<b>LAN</b> 10Mbps and 100Mbps <b>Modem</b> 56Kbps Downstream 33.6Kbps Upstream 14.4Kbps Tx/Rx Fax
<b>Card Type</b>	16-Bit PCMCIA Type II
<b>LEDs</b>	<b>LAN</b> Link, Activity, 10/100 (Lit if 100Mbps) <b>Modem</b> Carrier Detect, Transmit, Receive

## Package Contents

### EtherFast 10/100 + 56K Modem PC Card

- One EtherFast 10/100 + 56K Modem PC Card
- One RJ-45 Network Cable
- One RJ-11 Telephone Cable
- Driver Diskette
- User Guide and Registration Card  
**(Model No.: PCMLM56)**

## Environmental

<b>Dimensions</b>	4.4" x 2.3" x 0.65"
<b>Unit Weight</b>	2.0 oz.
<b>Power</b>	5v/260mA, 60mA Sleep
<b>Certifications</b>	FCC Class A CE Mark, Commercial UL and CSA Listed
<b>Operating Temp.</b>	32°F to 120°F (0°C to 49°C)
<b>Storage Temp.</b>	-40°F to 158°F (-40°C to 70°C)
<b>Operating Hum.</b>	10% to 85% Non-Condensing
<b>Storage Hum.</b>	5% to 90% Non-Condensing

<b>Sales</b>	<b>(800) 546-5797</b>
<b>Support</b>	<b>(949) 261-1288</b>
<b>Fax</b>	<b>(949) 261-8868</b>
<b>BBS</b>	<b>(949) 261-2888</b>
<b>Email</b>	<b>sales@linksys.com</b>
<b>Web</b>	<b>www.linksys.com</b>

