## Super 800/1100L - Linkage Sprayer



with BP125/20 pump and optional flush tank



Pictured: 800L with BP125/20 pump

MODEL SPECIFICATIONS				
Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body with raised pump mount. BP75/20: 71L/min. capacity 2000kPa pressure. BP125/20: 121L/min. capacity 2000kPa pressure.				
3 outlet manual control valve with pressure regulator.				
Low profile, 800 and 1100L Polytuff impact resistant polyethylene construction, external sightline with floating ball and non-spill offset screw-down lid with single breather. 15L freshwater tank with screw-down lid and on/off tap. 4L toolbox with polythylene lid. 50mm Camlock bottom fill (1100L only).				
Galvanised steel, with adjustable cat II hitch. Vertical boom channel positions boom at optimum spray height.				
Bypass agitation.				
1100L: Venturi suction probe with detachable hose.				
0-25 Bar dual stage glycerine filled gauge.				
Lid strainer, suction line strainer with stop valve fitted at the side of the tank to enable ease of filter maintenance.				
Quality driveshaft with quick release pins & safety cover.				
L (MM)	W (MM)	H (MM)	KG (DRY)	
1350	1395	1315	145	
1350	1395	1610	160	
	Silvan self-prinitrile diaphra aluminium boo BP75/20: 71L/BP125/20: 121  3 outlet manu Low profile, 8 polyethylene of floating ball a single breather and on/off tap 50mm Camloc Galvanised steboom channel Bypass agitat 1100L: Venturi 0-25 Bar dual Lid strainer, sthe side of the Quality drives L (MM) 1350	Silvan self-priming oil-backed nitrile diaphragms and corros aluminium body with raised p BP75/20: 71L/min. capacity 2 BP125/20: 121L/min. capacity 3 outlet manual control valve  Low profile, 800 and 1100L Po polyethylene construction, ex floating ball and non-spill off single breather. 15L freshwat and on/off tap. 4L toolbox wit 50mm Camlock bottom fill (11 Galvanised steel, with adjusta boom channel positions boom Bypass agitation.  1100L: Venturi suction probe volume and construction probe volume and constru	Silvan self-priming oil-backed diaphragm typ nitrile diaphragms and corrosion resistant, caluminium body with raised pump mount. BP75/20: 71L/min. capacity 2000kPa pressur BP125/20: 121L/min. capacity 2000kPa pressur BP125/20: 121L/min. capacity 2000kPa pressur of the profile, 800 and 1100L Polytuff impact response polyethylene construction, external sightline floating ball and non-spill offset screw-down single breather. 15L freshwater tank with scrand on/off tap. 4L toolbox with polythylene life somm Camlock bottom fill (1100L only).  Galvanised steel, with adjustable cat II hitch boom channel positions boom at optimum spill bypass agitation.  1100L: Venturi suction probe with detachable o-25 Bar dual stage glycerine filled gauge. Lid strainer, suction line strainer with stop vertical side of the tank to enable ease of filter mouality driveshaft with quick release pins & strainer with stop vertical side of the tank to enable ease of filter mouality driveshaft with quick release pins & strainer with stop vertical side of the tank to enable asset of filter mouality driveshaft with quick release pins & strainer with stop vertical side of the tank to enable asset of filter mouality driveshaft with quick release pins & strainer with stop vertical side of the tank to enable asset of filter mouality driveshaft with quick release pins & strainer with stop vertical side of the tank to enable asset of filter mouality driveshaft with quick release pins & strainer with stop vertical side of the tank to enable asset of filter mouality driveshaft with quick release pins & strainer with stop vertical side of the strainer with stop vertical strainer with stop vertical side side of the strainer with stop vertical side side side side side side side sid	

MODEL DESCRIPTION	CODE			
800L LINKAGE: BP75/20 pump, no boom	K08N-75			
800L LINKAGE: BP125/20 pump, no boom	K08N-125			
1100L LINKAGE: BP75/20 pump, no boom	K11NH-75			
1100L LINKAGE: BP125/20 pump, no boom	K11NH-125			
FACTORY OPTIONS*	CODE			
6m Field boom	032-044-6			
8m Field boom	032-044-8			
10m Field boom	032-044-10			
6m Devil boom with hydraulic fold	032-19D			
8m Devil boom with hydraulic fold	032-25D			
10m Devil boom with hydraulic fold	032-32DM			
10m HD Devil boom with hydraulic fold	032-32D			
12m HD Devil boom with hydraulic fold**	032-40D			
14m HD Devil boom with hydraulic fold**	032-48D			
15m HD Devil boom with hydraulic fold**	032-50D			
Hydraulic lift, galvanised single hydraulic system - 6, 8 & 10m devil booms	032-19DL			
Hydraulic lift, galvanised single hydraulic system - 10, 12, 14 & 15m HD Devil booms	032-40DL			
Hydraulic lift with airbag suspension - 10, 12, 14 & 15m HD Devil booms	032-40DLAB			
8 Jet vine boom (Used with BP60/20 pump only)	032-G			
10 Jet vine boom (Used with BP60/20 pump only)	032-H			
Olive boom (Use with BP125/20 pump only)	032-R			
Undervine and mid row boom	032-HERB			
Boomless nozzle mounting kit (brass nozzle not included)	K99-10			
70L flush tank kit to flush the filter, spraylines and nozzles	K99-47			
16L foam marker (double side)	K99-39			
57L Paddock marker foam marker	K99-43			
Economy hosereel, 20m hose (10mm ID) & Triam spraygun	180E02012CT			
Reel tuff 12V remote reel with Turbo 400 spray gun	K99-51			
Electric on/off control 3 section	K99-34			
Electric control 3 section with in cab pressure adjustment	K99-29			
Bravo 180S automatic rate controller	J99-151			
Silmix chemical hopper	K99-21			
Note: Not all options will fit all models. Extra charges may apply to fitment.				

\*\* If fitting 12, 14 & 15m HD Devil boom to a 800L TPL add \$800 for heavier frame