

ALL KEY FOBS MUST BE PRESENT AND REPROGRAMMED WHEN PROGRAMMING NEW FOBS

Programming Instructions:

- 1) Turn the ignition switch to ON. (II)
- 2) Press the LOCK or UNLOCK button on one of the remotes. (An programmed remote can be used for this step.)
- 3) Turn ignition switch to LOCK. (0)
- 4) Repeat steps 1,2 and 3 two more times using the same keyless remote used in step 2.
- 5) Turn the ignition switch so it is ON. (II)
- 6) Press the LOCK or UNLOCK button. Make sure the power door locks cycle to confirm you are in programming mode.
- 7) Press the lock or UNLOCK button on EACH remote you want to program, if you have more than 1. Make sure door locks cycle after you push each remote button to confirm system has accepted the remote.
- 8) Turn the ignition switch to LOCK (0) to exit programming mode.
- 9) Test remote(s) to ensure they work properly.

FCC WARNING

Statement 15.19(a)(3): This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Changes or modifications not expressly approved by Dorman Products Inc. could void the user's authority to operate the equipment.

FCC Part 15.21: THE GRANTEE IS NOT RESPONSIBLE FOR ANY CHANGES OR MODIFICATIONS NOT EXPRESSLY APPROVED BY THE PARTY RESPONSIBLE FOR COMPLIANCE. SUCH MODIFICATIONS COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.

IC WARNING

FVIN 63999357IC

The term IC before the Certification/Registration number only signifies that the Industry Canada technical specifications were met. Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.